

**47 C.F.R. Part 1, Subpart I, Section 1.1310
47 C.F.R. Part 2, Subpart J, Section 2.1091
Maximum Permissible Exposure Calculations**

**For Kinestral Technologies Inc
FCC ID: 2AJXY-DR250**

802.15.4 Transceiver

EUT Device Category = General Population/Uncontrolled Exposure

EUT consists of one ISM band radio transmitting operating over a range of:
2405 MHz to 2475 MHz

MPE Summary:

According subpart 1.1307 (b)(1) and 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

Limits for General Population/Uncontrolled Exposure

| Limits for General Population/Uncontrolled Exposure | | | | | | |
|--|-------|-------------------------|-------|-------------------------|------------------------|-------------------------------------|
| Frequency (MHz) | Range | Electric Strength (V/m) | Field | Magnetic Strength (A/m) | Field | Power Density (mW/cm ²) |
| 0.3-1.34 | 614 | | 1.63 | | *(100) | 30 |
| 1.34-30 | | 824/f | | 2.19/f | *(180/f ²) | 30 |
| 30-300 | 27.5 | | 0.073 | | 0.2 | 30 |
| 300-1500 | / | | / | | f/1500 | 30 |
| 1500-100,000 | / | | / | | 1.0 | 30 |

f = frequency in MHz;

* = Plane-wave equivalent power density

Calculated Formulary:

Predication of MPE limit at a given distance

$$S = \frac{PG}{4\pi R^2}$$

S = power density (in appropriate units, e.g. mW/cm²)

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

PG = EIRP

MPE and Limit are calculated as follows:

| f (MHz) | EIRP (mW) | Power Density (mW/cm ²) | Limit (mW/cm ²) | Δ |
|---------|-----------|-------------------------------------|-----------------------------|-------|
| 2405 | 15.71 | 0.003 | 1.000 | 0.997 |
| 2440 | 33.58 | 0.007 | 1.000 | 0.993 |
| 2475 | 35.66 | 0.007 | 1.000 | 0.993 |

Result: The device meets FCC MPE limit at 20 cm for General Population/Uncontrolled Exposure as specified in 47 CRF §1.1310 and §2.1091.