

TEST REPORT

REPORT NUMBER: B19W50601-MPE-Rev1

ON

Type of Equipment: LTE /HSPA/GSM/GNSS MODULE
Type of Designation: SIM7600G-H/SIM7600G-H miniPCIE
Manufacturer: Simcom Wireless Solutions Limited
FCC ID: 2AJYU-8PYA003

ACCORDING TO

FCC CFR 47 Part 2.1091 《Radiofrequency radiation exposure evaluation: mobile devices》

FCC CFR 47 Part1.1310 《Radiofrequency radiation exposure limits》

Chongqing Academy of Information and Communication Technology

Month date, year

Dec, 12, 2019

Signature



Zhang Yan

Director

Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of Chongqing Academy of Information and Communications Technology.

CONTENTS

1.	TEST LABORATORY	3
1.1.	TESTING LOCATION	3
1.2.	TESTING ENVIRONMENT	3
1.3.	PROJECT DATA	3
1.4.	SIGNATURE	3
2.	CLIENT INFORMATION	4
2.1.	APPLICANT INFORMATION	4
2.2.	MANUFACTURER INFORMATION	4
3.	EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE)	5
3.1.	ABOUT EUT	5
3.2.	INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST	5
3.3.	INTERNAL IDENTIFICATION OF AE USED DURING THE TEST	5
4.	REFERENCE DOCUMENTS	6
4.1.	APPLICABLE STANDARDS	6
4.2.	TEST LIMITS	6
5.	TEST RESULTS	7
5.1.	RF POWER OUTPUT	7
5.2.	CALCULATION INFORMATION	7
5.3.	RESULTS	8
5.4.	RESULT OF GSM 850	8
5.5.	RESULT OF GSM1900	9
5.6.	RESULT OF GPRS 850 4TS	9
5.7.	RESULT OF GRPS 1900 4TS	10
5.8.	RESULT OF WCDMA BAND2	10
5.9.	RESULT OF WCDMA BAND4	10
5.10.	RESULT OF WCDMA BAND5	11

Chongqing Academy of Information and Communications Technology
Report No.:B19W50601-MPE-Rev1

5.11. RESULT OF LTE BAND2..... 11

5.12. RESULT OF LTE BAND4..... 12

5.13. RESULT OF LTE BAND5..... 12

5.14. RESULT OF LTE BAND7..... 12

5.15. RESULT OF LTE BAND12..... 13

5.16. RESULT OF LTE BAND13..... 13

5.17. RESULT OF LTE BAND25..... 13

5.18. RESULT OF LTE BAND26..... 14

5.19. RESULT OF LTE BAND41..... 14

5.20. RESULT OF LTE BAND66..... 15

ANNEX A: EUT PHOTOGRAPH 16

Chongqing Academy of Information and Communications Technology

Report No.:B19W50601-MPE-Rev1

1. Test Laboratory

1.1. Testing Location

Company Name:	Chongqing Academy of Information and Communications Technology
Address:	No. 8, Yuma Road, Chayuan New City, Nan'an District, Chongqing, P. R. China
Postal Code:	401336
Telephone:	0086-23-88069965
Fax:	0086-23-88608777

1.2. Testing Environment

Normal Temperature:	21.3℃
Relative Humidity:	75%

1.3. Project Data

Testing Start Date:	2019-12-11
Testing End Date:	2019-12-11


1.4. Signature



2019-12-11

Fu Bohao
(Prepared this test report)

Date



2019-12-11

Wang Lili
(Reviewed this test report)

Date



2019-12-11

Zhang Yan
Director of the laboratory
(Approved this test report)

Date

2. Client Information

2.1. Applicant Information

Company Name:	Simcom Wireless Solutions Limited
Address /Post:	No.633 Jinzhong Road,Shanghai
Telephone:	021-32523020
Fax:	--
Email:	--
Contact Person:	Yang.liang

2.2. Manufacturer Information

Company Name:	SIMCom Wireless Solutions Limited
Address /Post:	No.633 Jinzhong Road,Shanghai
Telephone:	021-32523020
Fax:	--
Email:	--
Contact Person:	Yang.liang

3. Equipment Under Test (EUT) and Ancillary Equipment (AE)**3.1. About EUT**

Description:	LTE /HSPA/GSM/GNSS MODULE
Model name:	SIM7600G-H/SIM7600G-H miniPCIE
GSM Frequency Band	GSM850/1900
UMTS Frequency Band	Band2/4/5
LTE Frequency Band	Band2/4/5/7/12/13/19/25/26/66/41
GPRS Multislot Class	12
EGPRS Multislot Class	12
Note: Photographs of EUT are shown in ANNEX A of this test report.	

3.2. Internal Identification of EUT used during the test

EUT ID*	SN or IMEI	HW Version	SW Version	Date of receipt
S3	868822040006874	V1.02	SIM7600M22_V2.0	2019-11-11

*EUT ID: is used to identify the test sample in the lab internally.

3.3. Internal Identification of AE used during the test

EUT ID*	SN	Description
NA	NA	NA

*AE ID: is used to identify the test sample in the lab internally.

4. Reference Documents

4.1. Applicable Standards

The MPE report was carried out on a sample equipment to demonstrate limited compliance with FCC CFR 47 Part 2.1091.

FCC CFR 47 Part 2.1091: Radiofrequency radiation exposure evaluation: mobile devices

4.2. Test Limits

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

MPE for the upper tier (people in controlled environments)

Frequency Range [MHz]	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f ²)*	6
30-300	61.4	0.163	1.0	6
300-1500	--	--	f/300	6
1500-100000	--	--	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	--	--	f/1500	30
1500-100000	--	--	1.0	30

Note: f=frequency in MHz; *Plane-wave equivalent power density

For the DUT, the limits for the general public when an RF safety program is unavailable.

5. Test Results

5.1. RF Power Output

Frequency Band	Highest Averaged Power Output(dBm)	Highest Frame-Averaged Output Power (dBm)	Antenna Gain(dBi)
GSM850	35	25.97	-1
GSM1900	30	20.97	6
GPRS850 4TS	35	31.99	-1
GPRS1900 4TS	30	26.99	6
WCDMA Band2	22	22	11
WCDMA Band4	22	22	11
WCDMA Band5	23	23	8
LTE Band2	22	22	11
LTE Band4	22	22	11
LTE Band5	23	23	8
LTE Band7	23	23	11
LTE Band12	23.5	23.5	7
LTE Band13	24	24	6
LTE Band25	23	23	10
LTE Band26	24	24	8
LTE Band41	24	24	9
LTE Band66	23.5	23.5	9

Notes:

1) Division Factors

To average the power, the division factor is as follows:

1TX-slot = 1 transmit time slot out of 8 time slots=> conducted power divided by (8/1) => -9.03dB

2TX-slots = 2 transmit time slots out of 8 time slots=> conducted power divided by (8/2) => -6.02dB

3TX-slots = 3 transmit time slots out of 8 time slots=> conducted power divided by (8/3) => -4.26dB

4TX-slots = 4 transmit time slots out of 8 time slots=> conducted power divided by (8/4) => -3.01dB

2) According to the conducted power as above, the measurements are performed with 1Txslots for 850MHz and 1900MHz.

5.2. Calculation Information

For conservative evaluation consideration, only maximum power of each frequency band based on the tighter limits respectively are used to calculate the boundary power density.

Based on the FCC KDB 447498 D01 and 47 CFR §2.1091, the DUT is evaluated as a mobile device.

$$S = \frac{PG}{4\pi d^2}$$

Where

P = Power in Watts

G = Numeric antenna gain

d = Distance in meters

S = Power density in milliwatts / square centimeter

5.3. Results

Frequency range	Limit(mW/m ²)	Results(mW/m ²)	Verdict
GSM850	0.55	0.062	Pass
GSM1900	1.0	0.099	Pass
GPRS 850 4TS	0.55	0.250	Pass
GPRS 1900 4TS	1.0	0.396	Pass
WCDMA Band2	1.0	0.397	Pass
WCDMA Band4	1.0	0.397	Pass
WCDMA Band5	0.55	0.250	Pass
LTE Band2	1.0	0.397	Pass
LTE Band4	1.0	0.397	Pass
LTE Band5	0.55	0.250	Pass
LTE Band7	1.0	0.500	Pass
LTE Band12	0.47	0.223	Pass
LTE Band13	0.50	0.199	Pass
LTE Band25	1.0	0.397	Pass
LTE Band26	0.54	0.315	Pass
LTE Band41	1.0	0.397	Pass
LTE Band66	1.0	0.353	Pass

5.4. Result of GSM 850

Test Results: MPE Limit Calculation: the EUT'S operating frequencies @ 824.2~848.8MHz; The maximum conducted is 25.97 dBm. The maximum gain is -1.0dBi. Therefore, maximum limit for general public RF exposure: $824.2/1500=0.55\text{mW/cm}^2$.

$$S = \frac{PG}{4\pi d^2}$$

P= input power of the antenna (395.4mW)

G = antenna gain (0.794 numeric)

r = distance to the center of radiation of antenna (in meter)=20 cm

Address: No. 8,Yuma Road, Chayuan New City, Nan'an District, Chongqing, P. R. China,401336
FAX:0086-23-88608777

Tel: 0086-23-88069965

$$S=(395.4*0.794)/(4\pi*20^2)=0.062\text{mW/cm}^2$$

Therefore, at 20 cm the spectral power density is less than the 0.55 mW/cm² limit for uncontrolled exposure.

5.5. Result of GSM1900

Test Results: MPE Limit Calculation: the EUT'S operating frequencies @ 1850.2~1909.8 MHz; The maximum conducted is 20.97dBm. The maximum gain is 6.0 dBi. Therefore, maximum limit for general public RF exposure:1.0 mW/cm².

$$S = \frac{PG}{4\pi d^2}$$

P= input power of the antenna (125.03mW)

G = antenna gain (3.981numeric)

r = distance to the center of radiation of antenna (in meter)=20 cm

$$S=(125.03*3.981)/(4\pi*20^2)=0.099\text{ mW/cm}^2$$

Therefore, at 20 cm the spectral power density is less than the 1.0 mW/cm² limit for uncontrolled exposure.

5.6. Result of GPRS 850 4TS

Test Results: MPE Limit Calculation: the EUT'S operating frequencies @ 824.2~848.8MHz; The maximum conducted is 31.99 dBm. The maximum gain is -1.0dBi. Therefore, maximum limit for general public RF exposure: 824.2/1500=0.55mW/cm².

$$S = \frac{PG}{4\pi d^2}$$

P= input power of the antenna (1581.2mW)

G = antenna gain (0.794 numeric)

r = distance to the center of radiation of antenna (in meter)=20 cm

$$S=(1581.2*0.794)/(4\pi*20^2)=0.250\text{ mW/cm}^2$$

Therefore, at 20 cm the spectral power density is less than the 0.55 mW/cm² limit for uncontrolled exposure.

5.7. Result of GRPS 1900 4TS

Test Results: MPE Limit Calculation: the EUT'S operating frequencies @ 1850.2~1909.8 MHz; The maximum conducted is 26.99dBm. The maximum gain is 6.0 dBi. Therefore, maximum limit for general public RF exposure:1.0 mW/cm².

$$S = \frac{PG}{4\pi d^2}$$

P= input power of the antenna (500.03 mW)

G = antenna gain (3.981numeric)

r = distance to the center of radiation of antenna (in meter)=20 cm

$$S=(500.03*3.981)/(4\pi*20^2)=0.396 \text{ mW/cm}^2$$

Therefore, at 20 cm the spectral power density is less than the 1.0 mW/cm² limit for uncontrolled exposure.

5.8. Result of WCDMA Band2

Test Results: MPE Limit Calculation: the EUT'S operating frequencies @ 1852.4~1907.6 MHz; The maximum conducted is 22.0 dBm. The maximum gain is 11.0dBi. Therefore, maximum limit for general public RF exposure:1.0 mW/cm².

$$S = \frac{PG}{4\pi d^2}$$

P= input power of the antenna (158.49 mW)

G = antenna gain (12.589numeric)

r = distance to the center of radiation of antenna (in meter)=20 cm

$$S=(158.46*12.589)/(4\pi*20^2)=0.397 \text{ mW/cm}^2$$

Therefore, at 20 cm the spectral power density is less than the 1.0 mW/cm² limit for uncontrolled exposure.

5.9. Result of WCDMA Band4

Test Results: MPE Limit Calculation: the EUT'S operating frequencies @ 1712.4~1752.6 MHz; The maximum conducted is 22.0 dBm. The maximum gain is 11.0dBi. Therefore, maximum limit for general public RF exposure:1.0 mW/cm².

$$S = \frac{PG}{4\pi d^2}$$

P= input power of the antenna (158.49 mW)

G = antenna gain (12.589numeric)

r = distance to the center of radiation of antenna (in meter)=20 cm

$$S=(158.46*12.589)/(4\pi*20^2)=0.397\text{mW/cm}^2$$

Therefore, at 20 cm the spectral power density is less than the 1.0 mW/cm² limit for uncontrolled exposure.

5.10. Result of WCDMA Band5

Test Results: MPE Limit Calculation: the EUT'S operating frequencies @ 826.4~846.6MHz; The maximum conducted is 23.0 dBm. The maximum gain is 8.0dBi. Therefore, maximum limit for general public RF exposure:826.4/1500=0.55 mW/cm².

$$S = \frac{PG}{4\pi d^2}$$

P= input power of the antenna (199.53 mW)

G = antenna gain (6.310numeric)

r = distance to the center of radiation of antenna (in meter)=20 cm

$$S=(199.53*6.310)/(4\pi*20^2)=0.250\text{mW/cm}^2$$

Therefore, at 20 cm the spectral power density is less than the 0.55 mW/cm² limit for uncontrolled exposure.

5.11. Result of LTE Band2

Test Results: MPE Limit Calculation: the EUT'S operating frequencies @1850.0~1909.9 MHz; The maximum conducted is 22.0dBm. The maximum gain is 11.0dBi. Therefore, maximum limit for general public RF exposure: 1.0 mW/cm².

$$S = \frac{PG}{4\pi d^2}$$

P= input power of the antenna (158.49 mW)

G = antenna gain (12.589numeric)

r = distance to the center of radiation of antenna (in meter)=20 cm

$$S=(158.46*12.589)/(4\pi*20^2)=0.397\text{mW/cm}^2$$

Therefore, at 20 cm the spectral power density is less than the 1.0mW/cm² limit for uncontrolled exposure.

5.12. Result of LTE Band4

Test Results: MPE Limit Calculation: the EUT'S operating frequencies @ 1710.0~1754.9 MHz; The maximum conducted is 22.0dBm. The maximum gain is 11.0 dBi. Therefore, maximum limit for general public RF exposure: 1.0 mW/cm².

$$S = \frac{PG}{4\pi d^2}$$

P= input power of the antenna (158.49 mW)

G = antenna gain (12.589numeric)

r = distance to the center of radiation of antenna (in meter)=20 cm

$$S=(158.46*12.589)/(4\pi*20^2)=0.397\text{mW/cm}^2$$

Therefore, at 20 cm the spectral power density is less than the 1.0mW/cm² limit for uncontrolled exposure.

5.13. Result of LTE Band5

Test Results: MPE Limit Calculation: the EUT'S operating frequencies @ 824.0~848.9 MHz; The maximum conducted is 23.0dBm. The maximum gain is 8.0 dBi. Therefore, maximum limit for general public RF exposure: 824.0/1500=0.55 mW/cm².

$$S = \frac{PG}{4\pi d^2}$$

P= input power of the antenna (199.53 mW)

G = antenna gain (6.310numeric)

r = distance to the center of radiation of antenna (in meter)=20 cm

$$S=(199.53*6.310)/(4\pi*20^2)=0.250\text{mW/cm}^2$$

Therefore, at 20 cm the spectral power density is less than the 0.55mW/cm² limit for uncontrolled exposure.

5.14. Result of LTE Band7

Test Results: MPE Limit Calculation: the EUT'S operating frequencies @ 2500.0~2569.9 MHz; The maximum conducted is 23.0dBm. The maximum gain is 11.0 dBi. Therefore, maximum limit for general public RF exposure: 1.0 mW/cm².

$$S = \frac{PG}{4\pi d^2}$$

P= input power of the antenna (199.53mW)

G = antenna gain (12.589numeric)

r = distance to the center of radiation of antenna (in meter)=20 cm

$$S=(199.53*12.589)/(4\pi*20^2)=0.500\text{mW/cm}^2$$

Therefore, at 20 cm the spectral power density is less than the 1.0mW/cm^2 limit for uncontrolled exposure.

5.15. Result of LTE Band12

Test Results: MPE Limit Calculation: the EUT'S operating frequencies @ 699.0~715.9 MHz; The maximum conducted is 23.5dBm. The maximum gain is 7.0 dBi. Therefore, maximum limit for general public RF exposure: $699.0/1500=0.47\text{ mW/cm}^2$.

$$S = \frac{PG}{4\pi d^2}$$

P= input power of the antenna (223.87mW)

G = antenna gain (5.012numeric)

r = distance to the center of radiation of antenna (in meter)=20 cm

$$S=(223.87*5.012)/(4\pi*20^2)=0.223\text{mW/cm}^2$$

Therefore, at 20 cm the spectral power density is less than the 0.47mW/cm^2 limit for uncontrolled exposure.

5.16. Result of LTE Band13

Test Results: MPE Limit Calculation: the EUT'S operating frequencies @ 746.0~755.9 MHz; The maximum conducted is 24.0dBm. The maximum gain is 6.0 dBi. Therefore, maximum limit for general public RF exposure: $746.0/1500=0.50\text{ mW/cm}^2$.

$$S = \frac{PG}{4\pi d^2}$$

P= input power of the antenna (251.19mW)

G = antenna gain (3.981numeric)

r = distance to the center of radiation of antenna (in meter)=20 cm

$$S=(251.19*3.981)/(4\pi*20^2)=0.199\text{mW/cm}^2$$

Therefore, at 20 cm the spectral power density is less than the 0.50mW/cm^2 limit for uncontrolled exposure.

5.17. Result of LTE Band25

Test Results: MPE Limit Calculation: the EUT'S operating frequencies @ 1850.0~1914.9 MHz; The

maximum conducted is 23.0dBm. The maximum gain is 10.0 dBi. Therefore, maximum limit for general public RF exposure: 1.0 mW/cm².

$$S = \frac{PG}{4\pi d^2}$$

P= input power of the antenna (199.53mW)

G = antenna gain (10.0numeric)

r = distance to the center of radiation of antenna (in meter)=20 cm

$$S=(199.53*10.0)/(4\pi*20^2)=0.397\text{mW/cm}^2$$

Therefore, at 20 cm the spectral power density is less than the 1.0mW/cm² limit for uncontrolled exposure.

5.18. Result of LTE Band26

Test Results: MPE Limit Calculation: the EUT'S operating frequencies @ 814.0~848.9 MHz; The maximum conducted is 24.0dBm. The maximum gain is 8.0 dBi. Therefore, maximum limit for general public RF exposure: 814.0/1500=0.54 mW/cm².

$$S = \frac{PG}{4\pi d^2}$$

P= input power of the antenna (251.19mW)

G = antenna gain (6.310numeric)

r = distance to the center of radiation of antenna (in meter)=20 cm

$$S=(251.19*6.310)/(4\pi*20^2)=0.315\text{mW/cm}^2$$

Therefore, at 20 cm the spectral power density is less than the 0.54mW/cm² limit for uncontrolled exposure.

5.19. Result of LTE Band41

Test Results: MPE Limit Calculation: the EUT'S operating frequencies @ 2496.0~2689.9 MHz; The maximum conducted is 24.0dBm. The maximum gain is 9.0 dBi. Therefore, maximum limit for general public RF exposure: 1.0 mW/cm².

$$S = \frac{PG}{4\pi d^2}$$

P= input power of the antenna (251.19mW)

G = antenna gain (7.943numeric)

r = distance to the center of radiation of antenna (in meter)=20 cm

$$S=(251.19*7.943)/(4\pi*20^2)=0.397\text{mW/cm}^2$$

Therefore, at 20 cm the spectral power density is less than the 1.0mW/cm² limit for uncontrolled exposure.

5.20. Result of LTE Band66

Test Results: MPE Limit Calculation: the EUT'S operating frequencies @ 1710.0~1779.9 MHz; The maximum conducted is 23.5dBm. The maximum gain is 9.0 dBi. Therefore, maximum limit for general public RF exposure: 1.0 mW/cm².

$$S = \frac{PG}{4\pi d^2}$$

P= input power of the antenna (223.87mW)

G = antenna gain (7.943numeric)

r = distance to the center of radiation of antenna (in meter)=20 cm

$$S=(223.87*7.943)/(4\pi*20^2)=0.353\text{mW/cm}^2$$

Therefore, at 20 cm the spectral power density is less than the 1.0 mW/cm² limit for uncontrolled exposure.

ANNEX A: EUT photograph

See the document” SIM7600G-H/SIM7600G-H miniPCIE -External Photos”.

*****END OF REPORT*****