



FCC Radio Test Report

FCC ID: 2AJZ4-KK-FT

This report concerns (check one): ⊠Original Grant □Class II Change

Project No. Equipment Model Name Applicant Address	: : : : :	1610C053 Temperature & humidity sensor KK-FT Hangzhou Konke Information Technology Co., Ltd. 28F Huafeng international mansion,No.200 Xinye Road Jianggan District, Hangzhou, Zhejiang Province, China
Date of Receipt Date of Test Issued Date Tested by	:	Oct. 09, 2016 Oct. 09, 2016 ~ Nov. 15, 2016 Nov. 16, 2016 BTL Inc.
Testing Engineer		: Shawn Xivo (Shawn Xiao)
Technical Manag	er	: David Mao (David Mao)
Authorized Signa	itor	y :

BTL INC.

No.3, Jinshagang 1st Road, Shixia, Dalang Town, Dongguan, Guangdong, China.

(Steven Lu)

TEL: +86-769-8318-3000 FAX: +86-769-8319-6000

Report No.: BTL-FCCP-1-1610C053 Page 1 of 65





Declaration

BTL represents to the client that testing is done in accordance with standard procedures as applicable and that test instruments used has been calibrated with standards traceable to international standard(s) and/or national standard(s).

BTL's reports apply only to the specific samples tested under conditions. It is manufacture's responsibility to ensure that additional production units of this model are manufactured with the identical electrical and mechanical components. **BTL** shall have no liability for any declarations, inferences or generalizations drawn by the client or others from **BTL** issued reports.

BTL's report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

This report is the confidential property of the client. As a mutual protection to the clients, the public and **BTL-self**, extracts from the test report shall not be reproduced except in full with **BTL**'s authorized written approval.

BTL's laboratory quality assurance procedures are in compliance with the **ISO Guide 17025** requirements, and accredited by the conformity assessment authorities listed in this test report.

Limitation

For the use of the authority's logo is limited unless the Test Standard(s)/Scope(s)/Item(s) mentioned in this test report is (are) included in the conformity assessment authorities acceptance respective.

Report No.: BTL-FCCP-1-1610C053 Page 2 of 65





Table of Contents	Page
1 . CERTIFICATION	6
2 . SUMMARY OF TEST RESULTS	7
	-
2.1 TEST FACILITY	8
2.2 MEASUREMENT UNCERTAINTY	8
3. GENERAL INFORMATION	9
3.1 GENERAL DESCRIPTION OF EUT	9
3.2 DESCRIPTION OF TEST MODES	10
3.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING	10
3.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TES	TED 11
3.5 DESCRIPTION OF SUPPORT UNITS	11
4 . EMC EMISSION TEST	12
4.1 CONDUCTED EMISSION MEASUREMENT	12
4.1.1 POWER LINE CONDUCTED EMISSION LIMITS	12
4.1.2 TEST PROCEDURE 4.1.3 DEVIATION FROM TEST STANDARD	12 12
4.1.4 TEST SETUP	13
4.1.5 EUT OPERATING CONDITIONS	13
4.1.6 EUT TEST CONDITIONS	13
4.1.7 TEST RESULTS	13
4.2 RADIATED EMISSION MEASUREMENT 4.2.1 RADIATED EMISSION LIMITS	14 14
4.2.1 RADIATED EMISSION CIMITS 4.2.2 TEST PROCEDURE	14 15
4.2.3 DEVIATION FROM TEST STANDARD	15
4.2.4 TEST SETUP	16
4.2.5 EUT TEST CONDITIONS	17
4.2.6 TEST RESULTS (9KHZ TO 30MHZ) 4.2.7 TEST RESULTS (30MHZ TO 1000 MHZ)	17 17
4.2.8 TEST RESULTS (ABOVE 1000 MHZ)	17
5 . BANDWIDTH TEST	18
5.1 APPLIED PROCEDURES / LIMIT	18
5.1.1 TEST PROCEDURE	18
5.1.2 DEVIATION FROM STANDARD	18
5.1.3 TEST SETUP 5.1.4 EUT OPERATION CONDITIONS	18 18
5.1.5 EUT TEST CONDITIONS	18
5.1.6 TEST RESULTS	18
6 . MAXIMUM OUTPUT POWER TEST	19

Report No.: BTL-FCCP-1-1610C053





Table of Contents	Page
6.1 APPLIED PROCEDURES / LIMIT 6.1.1 TEST PROCEDURE 6.1.2 DEVIATION FROM STANDARD 6.1.3 TEST SETUP 6.1.4 EUT OPERATION CONDITIONS 6.1.5 EUT TEST CONDITIONS 6.1.6 TEST RESULTS	19 19 19 19 19 19
7 . ANTENNA CONDUCTED SPURIOUS EMISSION	20
7.1 APPLIED PROCEDURES / LIMIT 7.1.1 TEST PROCEDURE 7.1.2 DEVIATION FROM STANDARD 7.1.3 TEST SETUP 7.1.4 EUT OPERATION CONDITIONS 7.1.5 EUT OPERATION CONDITIONS 7.1.6 TEST RESULTS	20 20 20 20 20 20 20 20
8 . POWER SPECTRAL DENSITY TEST	21
8.1 APPLIED PROCEDURES / LIMIT 8.1.1 TEST PROCEDURE 8.1.2 DEVIATION FROM STANDARD 8.1.3 TEST SETUP 8.1.4 EUT OPERATION CONDITIONS 8.1.5 EUT TEST CONDITIONS 8.1.6 TEST RESULTS	21 21 21 21 21 21 21
9 . MEASUREMENT INSTRUMENTS LIST	22
10 . EUT TEST PHOTO	23
ATTACHMENT A - CONDUCTED EMISSION	27
ATTACHMENT B - RADIATED EMISSION (9KHZ TO 30MHZ)	28
ATTACHMENT C - RADIATED EMISSION BETWEEN (30MHZ TO 1000MHZ	Z) 33
ATTACHMENT D - RADIATED EMISSION (ABOVE 1000MHZ)	40
ATTACHMENT E - BANDWIDTH	53
ATTACHMENT F - MAXIMUM OUTPUT POWER TEST	56
ATTACHMENT G - ANTENNA CONDUCTED SPURIOUS EMISSION	59
ATTACHMENT H - POWER SPECTRAL DENSITY TEST	63

Report No.: BTL-FCCP-1-1610C053





REPORT ISSUED HISTORY

Issued No.	Description	Issued Date
BTL-FCCP-1-1610C053	Original Issue.	Nov. 16, 2016

Report No.: BTL-FCCP-1-1610C053 Page 5 of 65





1. CERTIFICATION

Equipment : Temperature & humidity sensor

Brand Name: KONKE Model Name: KK-FT

Applicant : Hangzhou Konke Information Technology Co., Ltd.

Manufacturer: AmbitMicrosystems (shanghai) LTD.

Address : No.1925 NanleRoad Songjiang EPZ Shanghai, China

Factory

: AmbitMicrosystems (shanghai) LTD.: No.1925 NanleRoad Songjiang EPZ Shanghai, China Address

Date of Test : Oct. 09, 2016 ~ Nov. 15, 2016

Test Sample: Engineering Sample

Standard(s) : FCC Part15, Subpart C (15.247) / ANSI C63.10-2013

The above equipment has been tested and found compliance with the requirement of the relative standards by BTL Inc.

The test data, data evaluation, and equipment configuration contained in our test report (Ref No. BTL-FCCP-1-1610C053) were obtained utilizing the test procedures, test instruments, test sites that has been accredited by the Authority of TAF according to the ISO-17025 quality assessment standard and technical standard(s).

Report No.: BTL-FCCP-1-1610C053 Page 6 of 65





2. SUMMARY OF TEST RESULTS

Test procedures according to the technical standard(s):

Applied Standard(s): FCC Part15 (15.247), Subpart C				
Standard(s) Section	Test Item	Judgment	Remark	
15.207	Conducted Emission	N/A	NOTE (1)	
15.247(d)	Antenna conducted Spurious Emission	PASS		
15.247(a)(2)	6dB Bandwidth	PASS		
15.247(b)(3)	Peak Output Power	PASS		
15.247(e)	Power Spectral Density	PASS		
15.203	Antenna Requirement	PASS		
15.209/15.205	Transmitter Radiated Emissions	PASS		

NOTE:

(1)" N/A" denotes test is not applicable to this device.

Report No.: BTL-FCCP-1-1610C053 Page 7 of 65





2.1 TEST FACILITY

The test facilities used to collect the test data in this report is at the location of No.3, Jinshagang 1st Road, Shixia, Dalang Town, Dongguan, Guangdong, China.

BTL's test firm number for FCC: 319330

2.2 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. The measurement instrumentation uncertainty considerations contained in CISPR 16-4-2.

The reported uncertainty of measurement $\mathbf{y} \pm \mathbf{U}$, where expanded uncertainty \mathbf{U} is based on a standard uncertainty multiplied by a coverage factor of $\mathbf{k=2}$, providing a level of confidence of approximately 95 %.

A. Radiated Measurement:

Test Site	Method	Measurement Frequency Range	Ant. H / V	U, (dB)
		9KHz~30MHz	V	3.79
	CISPR	9KHz~30MHz	Ι	3.57
		30MHz ~ 200MHz	V	3.82
		30MHz ~ 200MHz	Ι	3.78
DG-CB03		200MHz ~ 1,000MHz	V	4.10
DG-CB03 CIS		200MHz ~ 1,000MHz	Н	4.06
		1GHz~18GHz	V	3.12
		1GHz~18GHz	Н	3.68
		18GHz~40GHz	V	4.15
		18GHz~40GHz	Н	4.14

Note: Unless specifically mentioned, the uncertainty of measurement has not been taken into account to declare the compliance or non-compliance to the specification.

Report No.: BTL-FCCP-1-1610C053 Page 8 of 65





3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

Equipment	Temperature & humidity sensor	
Brand Name	KONKE	
Model Name	KK-FT	
Model Difference	N/A	
Product Description	Operation Frequency	2405~2480 MHz
	Modulation Technology	DSSS, OQPSK
1 Toddet Description	Bit Rate of Transmitter	250Kbps
	Output Power (Max.)	1.63 dBm
Power Source	Supplied from battery (Model: CR2450).	
Power Rating	DC 3V	

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.

2. Channel List:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
01	2405	09	2445
02	2410	10	2450
03	2415	11	2455
04	2420	12	2460
05	2425	13	2465
06	2430	14	2470
07	2435	15	2475
08	2440	16	2480

3. Table for Filed Antenna:

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	Magic wireless	MW2412	Chip	N/A	3

Report No.: BTL-FCCP-1-1610C053 Page 9 of 65





3.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	TX Mode NOTE (1)

For Conducted Test			
Final Test Mode Description			
N/A	" N/A" denotes test is not applicable to this device.		

For Radiated Test	
Final Test Mode	Description
Mode 1	TX Mode NOTE (1)

Note:

(1) The measurements are performed at the high, middle, low available channels.

3.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of IEEE 802.15.4.


Test Software Version	N/A		
Frequency (MHz)	2405	2445	2480
IEEE 802.15.4	N/A	N/A	N/A

Report No.: BTL-FCCP-1-1610C053 Page 10 of 65





3.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED



3.5 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	FCC ID	Series No.
-	Notebook	Lenovo	H2510	DOC	SS07999198

Item	Shielded Type	Ferrite Core	Length	Note
1	NO	NO	0.2m	Fixture Cable

Report No.: BTL-FCCP-1-1610C053 Page 11 of 65





4. EMC EMISSION TEST

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 POWER LINE CONDUCTED EMISSION LIMITS (Frequency Range 150KHz-30MHz)

Fraguency of Emission (MHz)	Conducted Limit (dBµV)		
Frequency of Emission (MHz)	Quasi-peak	Average	
0.15 -0.5	66 to 56*	56 to 46*	
0.50 -5.0	56	46	
5.0 -30.0	60	50	

Note:

- (1) The limit of " * " decreases with the logarithm of the frequency
- (2) The test result calculated as following: Measurement Value = Reading Level + Correct Factor Correct Factor = Antenna Factor + Cable Loss - Amplifier Gain(if use) Margin Level = Measurement Value - Limit Value

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

4.1.2 TEST PROCEDURE

- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipment powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e For the actual test configuration, please refer to the related Item –EUT Test Photos.

4.1.3 DEVIATION FROM TEST STANDARD


No deviation

Report No.: BTL-FCCP-1-1610C053





4.1.4 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

4.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical function (as a customer would normally use it), EUT was programmed to be in continuously transmitting/receiving data or hopping on mode.

4.1.6 EUT TEST CONDITIONS

Temperature: N/A Relative Humidity: N/A Test Voltage: N/A

4.1.7 TEST RESULTS

Please refer to the Attachment A.

Remark:

- (1) All readings are QP Mode value unless otherwise stated AVG in column of <code>『Note』</code>. If the QP Mode Measured value compliance with the QP Limits and lower than AVG Limits, the EUT shall be deemed to meet both QP & AVG Limits and then only QP Mode was measured, but AVG Mode didn't perform. In this case, a " * " marked in AVG Mode column of Interference Voltage Measured.
- (2) Measuring frequency range from 150KHz to 30MHz.
- (3) "N/A" denotes test is not applicable to this device.

Report No.: BTL-FCCP-1-1610C053





4.2 RADIATED EMISSION MEASUREMENT

4.2.1 RADIATED EMISSION LIMITS

In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

LIMITS OF RADIATED EMISSION MEASUREMENT (9KHz-1000MHz)

Frequency	Field Strength	Measurement Distance
(MHz)	(microvolts/meter)	(meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
960~1000	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

Frequency (MHz)	Band edge at 3	3m (dBµV/m)	Harmonic at 1.5m (dBµV/m)		
	Peak	Average	Peak	Average	
Above 1000	74	54	80 (Note 5)	60(Note 5)	

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).
- (4) The test result calculated as following: Measurement Value = Reading Level + Correct Factor Correct Factor = Antenna Factor + Cable Loss - Amplifier Gain(if use) Margin Level = Measurement Value - Limit Value

(5)
$$FS_{\text{limit}} = FS_{\text{max}} - 20\log\left(\frac{d_{\text{limit}}}{d_{\text{measure}}}\right)$$

20log d limit/d measure=20log 3/1.5=6dB.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency 10th carrier harmonic	
RBW / VBW	RBW 1MHz VBW 3MHz peak detector for Pk value
(Emission in restricted band)	RMS detector for AV value

Report No.: BTL-FCCP-1-1610C053 Page 14 of 65





Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9KHz~90KHz for PK/AVG detector
Start ~ Stop Frequency	90KHz~110KHz for QP detector
Start ~ Stop Frequency	110KHz~490KHz for PK/AVG detector
Start ~ Stop Frequency	490KHz~30MHz for QP detector
Start ~ Stop Frequency	30MHz~1000MHz for QP detector

4.2.2 TEST PROCEDURE

- a. The measuring distance of 3 m shall be used for measurements. The EUT was placed on the top of a rotating table 0.8 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(below 1GHz)
- b. The measuring distance of 3 m shall be used for measurements. The EUT was placed on the top of a rotating table 1.5 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(above 1GHz)
- c. The height of the equipment or of the substitution antenna shall be 0.8 m or 1.5 m, the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights find the maximum reading (used Bore sight function).
- e. The receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1GHz.
- f. The initial step in collecting radiated emission data is a receiver peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- g. All readings are Peak unless otherwise stated QP in column of Note. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform. (below 1GHz)
- h. All readings are Peak Mode value unless otherwise stated AVG in column of Note. If the Peak Mode Measured value compliance with the Peak Limits and lower than AVG Limits, the EUT shall be deemed to meet both Peak & AVG Limits and then only Peak Mode was measured, but AVG Mode didn't perform. (above 1GHz)
- i. For the actual test configuration, please refer to the related Item –EUT Test Photos.

4.2.3 DEVIATION FROM TEST STANDARD

No deviation


Report No.: BTL-FCCP-1-1610C053 Page 15 of 65






4.2.4 TEST SETUP

(A) Radiated Emission Test Set-Up Frequency Below 1 GHz



(B) Radiated Emission Test Set-Up Frequency Above 1 GHz




Report No.: BTL-FCCP-1-1610C053 Page 16 of 65





(C) For Radiated Emissions Below 30MHz



4.2.5 EUT TEST CONDITIONS

Temperature: 25°C Relative Humidity: 55% Test Voltage: DC 3V

4.2.6TEST RESULTS (9KHZ TO 30MHZ)

Please refer to the Attachment B.

Remark:

- (1) The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.
- (2) Distance extrapolation factor = 40 log (specific distance / test distance) (dB).
- (3) Limit line = specific limits (dBuV) + distance extrapolation factor.

4.2.7TEST RESULTS (30MHZ TO 1000 MHZ)

Please refer to the Attachment C.

Remark:

- (1) Measuring frequency range from 30MHz to 1000MHz.
- (2) If the peak scan value lower limit more than 20dB, then this signal data does not show in table.

4.2.8TEST RESULTS (ABOVE 1000 MHZ)

Please refer to the Attachment D.

Remark:

- (1) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission
- (2) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (3) EUT Orthogonal Axis:
 - "X" denotes Laid on Table, "Y" denotes Vertical Stand, "Z" denotes Side Stand
- (4) During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna
- (5) No limit: This is fundamental signal, the judgment is not applicable. For fundamental signal judgment was referred to Peak output test.

Report No.: BTL-FCCP-1-1610C053





5. BANDWIDTH TEST

5.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(a)(2)	Bandwidth	>= 500KHz (6dB bandwidth)	2405~2480 MHz	PASS

5.1.1 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b. Spectrum Setting: RBW= 100KHz, VBW=300KHz, Sweep time = 2.5 ms.

5.1.2 DEVIATION FROM STANDARD

No deviation.

5.1.3 TEST SETUP

EUT	SPECTRUM
	ANALYZER

5.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.5 unless otherwise a special operating condition is specified in the follows during the testing.

5.1.5 EUT TEST CONDITIONS

Temperature: 25°C Relative Humidity: 55% Test Voltage: DC 3V

5.1.6 TEST RESULTS

Please refer to the Attachment E.

Report No.: BTL-FCCP-1-1610C053 Page 18 of 65





6. MAXIMUM OUTPUT POWER TEST

6.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(b)(3)	Maximum Output Power	1 watt or 30dBm	2405~2480 MHz	PASS

6.1.1 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b. The maximum peak conducted output power was performed in accordance with method 9.1.1 of FCC KDB 558074 D01 DTS Meas Guidance v03r05.
- c. Spectrum Setting: RBW= 3MHz, VBW=10MHz, Sweep time = 2.5 ms.

6.1.2 DEVIATION FROM STANDARD

No deviation.

6.1.3 TEST SETUP

EUT	SPECTRUM
	ANALYZER

6.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.5 unless otherwise a special operating condition is specified in the follows during the testing.

6.1.5 EUT TEST CONDITIONS

Temperature: 25°C Relative Humidity: 55% Test Voltage: DC 3V

6.1.6 TEST RESULTS

Please refer to the Attachment F.

Report No.: BTL-FCCP-1-1610C053 Page 19 of 65





7. ANTENNA CONDUCTED SPURIOUS EMISSION

7.1 APPLIED PROCEDURES / LIMIT

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.

7.1.1 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b. Spectrum Setting: RBW= 100KHz, VBW=300KHz, Sweep time = 10 ms.
- c. Offset=antenna gain + cable loss

7.1.2 DEVIATION FROM STANDARD

No deviation.

7.1.3 TEST SETUP



7.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.5 unless otherwise a special operating condition is specified in the follows during the testing.

7.1.5 EUT OPERATION CONDITIONS

Temperature: 25°C Relative Humidity: 55% Test Voltage: DC 3V

7.1.6 TEST RESULTS

Please refer to the Attachment G.

Report No.: BTL-FCCP-1-1610C053 Page 20 of 65





8. POWER SPECTRAL DENSITY TEST

8.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C							
Section	Test Item	Limit	Frequency Range (MHz)	Result			
15.247(e)	Power Spectral Density	8 dBm (in any 3KHz)	2405~2480 MHz	PASS			

8.1.1 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b. Spectrum Setting: RBW=3KHz, VBW=10 KHz, Sweep time = auto.

8.1.2 DEVIATION FROM STANDARD

No deviation.

8.1.3 TEST SETUP

EUT	SPECTRUM
	ANALYZER

8.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.5 unless otherwise a special operating condition is specified in the follows during the testing.

8.1.5 EUT TEST CONDITIONS

Temperature: 25°C Relative Humidity: 55% Test Voltage: DC 3V

8.1.6 TEST RESULTS

Please refer to the Attachment H.

Report No.: BTL-FCCP-1-1610C053 Page 21 of 65





9. MEASUREMENT INSTRUMENTS LIST

	Radiated Emission Measurement									
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until					
1	Antenna	Schwarbeck	VULB9160	9160-3232	Mar. 27, 2017					
2	Amplifier	HP	8447D	2944A09673	Oct. 20, 2017					
3	Receiver	AGILENT	N9038A	MY52130039	Sep. 04, 2017					
4	Test Cable	emci	LMR-400(30MHz- 1GHz)	C-01	Jun. 26, 2017					
5	Controller	CT	SC100	N/A	N/A					
6	Measurement Software	Farad	EZ-EMC Ver.NB-03A1-01	N/A	N/A					
7	Antenna	ETS	3115	00075789	Mar. 27, 2017					
8	Amplifier	Agilent	8449B	3008A02274	Nov. 01, 2017					
9	Test Cable	emci	EMC104-SM-SM- 10000(1GHz-26.5 GHz)	C-68	Jun. 26, 2017					
10	Broad-Band Horn Antenna	Schwarzheck BBHA 9170 9170319		9170319	Mar. 27, 2017					
11	Microwave Preamplifier With Adaptor	EMC INSTRUMENT	EMC2654045	980039 & HA01	Mar. 27, 2017					
12	EMI Test Receiver	R&S	ESCI	100895	Mar. 27, 2017					
13	Active Loop Antenna	R&S	HFH2-Z2	830749/020	Sep. 07, 2017					

١	6dB Bandwidth Measurement							
Ī	Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until		
	1	Spectrum Analyzer	R&S	FSP40	100185	Sep. 04, 2017		

	Peak Output Power Measurement							
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until			
1	Spectrum Analyzer	R&S	FSP40	100185	Sep. 04, 2017			

	Antenna Conducted Spurious Emission Measurement								
Item	m Kind of Equipment Manufacturer		Type No.	Serial No.	Calibrated until				
1	Spectrum Analyzer R&S		FSP40	100185	Sep. 04, 2017				

Power Spectral Density Measurement						
Ite	m Kind	of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
•	Spec	ctrum Analyzer	R&S	FSP40	100185	Sep. 04, 2017

Remark: "N/A" denotes no model name, serial no. or calibration specified.

All calibration period of equipment list is one year.

Report No.: BTL-FCCP-1-1610C053 Page 22 of 65





10. EUT TEST PHOTO








Report No.: BTL-FCCP-1-1610C053 Page 23 of 65





30MHz to 1000MHz Radiated Measurement Photos






Report No.: BTL-FCCP-1-1610C053 Page 24 of 65





Above 1GHz Radiated Measurement Photos





Report No.: BTL-FCCP-1-1610C053 Page 25 of 65





Above 1GHz Radiated Measurement Photos





Report No.: BTL-FCCP-1-1610C053 Page 26 of 65





ATTACHMENT A - CONDUCTED EMISSION

Test Mode:	N/A
Note:	" N/A" denotes test is not applicable to this device.

Report No.: BTL-FCCP-1-1610C053 Page 27 of 65






ATTACHMENT B - RADIATED EMISSION (9KHZ TO 30MHZ)

Report No.: BTL-FCCP-1-1610C053 Page 28 of 65








No. Mk.	Freq.			Measure- ment		Margin		
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	0.012	32.41	23.99	56.40	125.88	-69.48	AVG	
2	0.023	23.48	23.15	46.63	120.37	-73.74	AVG	
3 *	0.043	26.21	20.63	46.84	114.86	-68.02	AVG	

Report No.: BTL-FCCP-1-1610C053 Page 29 of 65








No. Mk.	Freq.	Reading Level		Measure- ment	Limit	Margin		
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	0.221	21.76	18.68	40.44	100.73	-60.29	AVG	
2 *	2.249	20.35	17.59	37.94	69.54	-31.60	QP	
3	8.062	18.76	16.17	34.93	69.54	-34.61	QP	

Report No.: BTL-FCCP-1-1610C053 Page 30 of 65








No. Mk.	Freq.	_		Measure- ment		Margin			
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment	
1 *	0.012	28.35	24.02	52.37	126.24	-73.87	AVG		
2	0.025	21.46	22.88	44.34	119.58	-75.24	AVG		
3	0.072	13.27	19.56	32.83	110.41	-77.58	AVG		

Report No.: BTL-FCCP-1-1610C053 Page 31 of 65







No. Mk.	Freq.	_	Correct Factor	Measure- ment	Limit	Margin			
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment	
1	0.238	19.82	18.66	38.48	100.08	-61.60	AVG		
2 *	2.422	20.31	17.37	37.68	69.54	-31.86	QP		
3	10.620	18.95	15.83	34.78	69.54	-34.76	QP		

Report No.: BTL-FCCP-1-1610C053 Page 32 of 65






ATTACHMENT C - RADIATED EMISSION BETWEEN (30MHZ TO 1000MHZ)

Report No.: BTL-FCCP-1-1610C053







Report No.: BTL-FCCP-1-1610C053 Page 34 of 65






Test Mode: TX 2405MHz Horizontal dBuV/m 80.0 70 60 50 40 X 5 X 8 X 30 20 10 0.0 30.000 127.00 224.00 321.00 418.00 515.00 612.00 709.00 806.00 1000.00 MHz

No. Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Margin		
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1 *	42.125	43.79	-12.07	31.72	40.00	-8.28	peak	
2	216.240	49.15	-14.01	35.14	46.00	-10.86	peak	
3	264.255	48.68	-12.54	36.14	46.00	-9.86	peak	
4	311.785	46.83	-10.14	36.69	46.00	-9.31	peak	
5	384.050	43.10	-8.34	34.76	46.00	-11.24	peak	
6	666.805	35.06	-1.34	33.72	46.00	-12.28	peak	

Report No.: BTL-FCCP-1-1610C053 Page 35 of 65







Report No.: BTL-FCCP-1-1610C053 Page 36 of 65





Test Mode: TX 2445MHz Horizontal 80.0 dBuV/m 70 60 50 40 5 X 30 20 10 0.0 30.000 127.00 224.00 321.00 418.00 515.00 612.00 709.00 806.00 1000.00 MHz

No. Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Margin		
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	42.125	44.54	-12.07	32.47	40.00	-7.53	peak	
2	240.005	52.29	-13.38	38.91	46.00	-7.09	peak	
3 *	311.785	49.65	-10.14	39.51	46.00	-6.49	peak	
4	384.050	46.62	-8.34	38.28	46.00	-7.72	peak	
5	666.805	33.15	-1.34	31.81	46.00	-14.19	peak	
6	816.185	36.48	0.61	37.09	46.00	-8.91	peak	

Report No.: BTL-FCCP-1-1610C053 Page 37 of 65





TX 2480MHz Test Mode: **Vertical** 80.0 dBuV/m 70 60 50 40 5 X Š * š 30 20 10 0.0 30.000 127.00 224.00 321.00 418.00 515.00 612.00 709.00 806.00 1000.00 MHz Reading Correct Measure-No. Mk. Limit Margin Freq. Level Factor ment MHz dBuV dΒ dBuV/m dB dBuV/m Detector Comment 42.610 43.67 31.69 40.00 -8.31 1 -11.98 peak -16.64 2 216.240 43.37 -14.01 29.36 46.00 peak 264.255 42.76 -12.54 30.22 46.00 -15.78 3 peak 4 384.050 40.62 -8.34 32.28 46.00 -13.72 peak 5 36.75 666.805 -1.34 35.41 46.00 -10.59 peak 6 812.305 32.24 0.61 32.85 46.00 -13.15 peak





TX 2480MHz Test Mode: Horizontal 80.0 dBuV/m 70 60 50 40 X X ķ 30 20 10 0.030.000 127.00 224.00 321.00 418.00 515.00 612.00 709.00 806.00 1000.00 MHz Reading Correct Measure-Limit Margin No. Mk. Freq. Level Factor ment MHz dBuV dB dBuV/m dBuV/m dB Detector Comment 41.640 43.32 -12.18 31.14 40.00 -8.86 1 peak 2 * 191.990 48.96 -13.28 -7.82 35.68 43.50 peak 3 263.770 50.08 -12.59 37.49 46.00 -8.51 peak 4 311.785 48.09 -10.14 37.95 46.00 -8.05 peak 5 384.050 45.79 -8.34 37.45 46.00 -8.55 peak

Report No.: BTL-FCCP-1-1610C053

816.185

6

36.33

0.61

36.94

46.00

-9.06

peak






ATTACHMENT D - RADIATED EMISSION (ABOVE 1000MHZ)

Report No.: BTL-FCCP-1-1610C053 Page 40 of 65





Test Mode: TX 2405MHz




No.	Mk	. Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Margin		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		2390.000	25.66	33.75	59.41	74.00	-14.59	peak	
2		2390.000	-12.79	33.75	20.96	54.00	-33.04	AVG	
3	*	2404.550	47.64	33.84	81.48	74.00	7.48	peak	No Limit
4		2404.550	9.19	33.84	43.03	54.00	-10.97	AVG	No Limit

Report No.: BTL-FCCP-1-1610C053 Page 41 of 65







No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Margin		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	* 4	811.135	48.32	5.13	53.45	74.00	-20.55	peak	
2	4	811.084	9.87	5.13	15.00	54.00	-39.00	AVG	

Report No.: BTL-FCCP-1-1610C053 Page 42 of 65



2355.000 2365.00

2375.00



2455.00 MHz

Test Mode : TX 2405MHz

Horizontal

100.0 dBuV/m

90

60

70

40

30

No. I	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Margin		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	2	390.000	28.36	33.75	62.11	74.00	-11.89	peak	
2	2	390.000	-10.09	33.75	23.66	54.00	-30.34	AVG	
3 *	2	405.650	56.04	33.85	89.89	74.00	15.89	peak	No Limit
4	2	405.650	17.59	33.85	51.44	54.00	-2.56	AVG	No Limit

2405.00

2415.00

2425.00

2435.00


2395.00

2385.00

Report No.: BTL-FCCP-1-1610C053 Page 43 of 65












Test Mode: TX 2445MHz




No.	Mk.	Freq.	_	Correct Factor	Measure- ment	Limit	Margin		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1 '	* 2	2445.400	49.09	34.07	83.16	74.00	9.16	peak	No Limit
2	2	2445.400	10.64	34.07	44.71	54.00	-9.29	AVG	No Limit

Report No.: BTL-FCCP-1-1610C053 Page 45 of 65








No.	Mk.	Freq.			Measure- ment		Margin		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	* 4	888.930	49.73	5.53	55.26	74.00	-18.74	peak	
2	4	888.990	11.28	5.53	16.81	54.00	-37.19	AVG	

Report No.: BTL-FCCP-1-1610C053 Page 46 of 65








Report No.: BTL-FCCP-1-1610C053 Page 47 of 65












TX 2480MHz Test Mode: Vertical 100.0 dBuV/m 90 80 70 60 50 40 30 20.0 2430.000 2440.00 2450.00 2460.00 2470.00 2480.00 2490.00 2500.00 2510.00 2530.00 MHz

No.	Mk	. Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Margin		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	*	2479.300	50.25	34.25	84.50	74.00	10.50	peak	No Limit
2		2479.300	11.80	34.25	46.05	54.00	-7.95	AVG	No Limit
3		2483.500	26.71	34.27	60.98	74.00	-13.02	peak	
4		2483.500	-11.74	34.27	22.53	54.00	-31.47	AVG	

Report No.: BTL-FCCP-1-1610C053 Page 49 of 65









No.	Mk	c. Freq.			Measure- ment	Limit	Margin			
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment	
1	*	4961.105	46.43	5.90	52.33	74.00	-21.67	peak		
2		4961.840	7.98	5.90	13.88	54.00	-40.12	AVG		

Report No.: BTL-FCCP-1-1610C053 Page 50 of 65










	No. M	k.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Margin		
			MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
	1 *	24	79.550	58.63	34.26	92.89	74.00	18.89	peak	No Limit
	2 X	24	79.550	20.18	34.26	54.44	54.00	0.44	AVG	No Limit
	3	24	83.500	32.41	34.27	66.68	74.00	-7.32	peak	
-	4	24	83.500	-6.04	34.27	28.23	54.00	-25.77	AVG	
-										

Report No.: BTL-FCCP-1-1610C053 Page 51 of 65











ATTACHMENT E - BANDWIDTH	


Report No.: BTL-FCCP-1-1610C053 Page 53 of 65





Frequency (MHz)	6dB Bandwidth (MHz)	99% Occupied BW (MHz)	Min. Limit (kHz)	Test Result
2405	1.58	2.39	500	Complies
2445	1.60	2.45	500	Complies
2480	1.63	2.44	500	Complies






Date: 26.0CT.2016 14:24:53







Date: 26.0CT.2016 14:22:16



Date: 26.0CT.2016 14:23:17





Page 56 of 65

ATTACHMENT F - MAXIMUM OUTPUT POWER TEST				






Test Mode:	TX Mode

Frequency	Conducted	Conducted	Max. Limit	Max. Limit	Toot Dooult
(MHz)	Power (dBm)	Power (Watt)	(dBm)	(Watt)	Test Result
2405	1.32	0.0014	30.00	1.00	Complies
2445	1.63	0.0015	30.00	1.00	Complies
2480	1.60	0.0014	30.00	1.00	Complies

2405MHz




Date: 15.NOV.2016 13:50:12

Report No.: BTL-FCCP-1-1610C053 Page 57 of 65









Date: 15.NOV.2016 13:50:54

TX 2480MHz



Date: 15.NOV.2016 13:51:18






ATTACHMENT G - ANTENNA CONDUCTED SPURIOUS EMISSION

Report No.: BTL-FCCP-1-1610C053 Page 59 of 65








Date: 26.0CT.2016 14:28:24










Date: 26.0CT.2016 14:14:26

2445MHz (10 Harmonic of the frequency)




Date: 26.0CT.2016 14:15:15

Report No.: BTL-FCCP-1-1610C053 Page 61 of 65





2480MHz (10 Harmonic of the frequency)



Date: 26.0CT.2016 14:15:55

Report No.: BTL-FCCP-1-1610C053 Page 62 of 65





ATTACHMENT H - POWER SPECTRAL DENSITY TEST					






Test Mode : TX Mode

Frequency (MHz)	Power Density (dBm)	Max. Limit (dBm)	Result
2405	-15.29	8	Complies
2445	-14.27	8	Complies
2480	-14.27	8	Complies

2405MHz




Date: 26.0CT.2016 14:25:18


Report No.: BTL-FCCP-1-1610C053 Page 64 of 65







Date: 26.0CT.2016 14:21:15



Date: 26.0CT.2016 14:20:45