

FCC RF EXPOSURE REPORT

FCC ID: 2AJZR-T602C00

Project No. : 1611128
Equipment : Mobile Jacket
Model : iSAPPOS Scanner Jacket
Applicant : iSAPPOS Systems Company Limited
Address : Room 04, 6/F., Block A, Tonic Industrial Centre,
26 Kai Cheung Road, Kowloon Bay, Hong Kong

According: : FCC Guidelines for Human Exposure IEEE
C95.1

BTL Inc.

B1, No. 37, Lane 365, YangGuang St., NeiHu District 114, Taipei, Taiwan
TEL : (0769) 8318-3000 FAX : (0769) 8319-6000

Table for Filed Antenna

Ant.	Manufacturer	Model Name	Antenna Type	Connector	Gain(dBi)
1	ACX	AT5020-B2R8H AA	Chip	N/A	0

GENERAL CONCLUSION:

Maximum measured transmitter power:

Output Power (dBm)	Output Power (mW)	Limit (mW)
-0.12	0.97	10

According to FCC KDB447498 V06, Appendix A, SAR Test Exclusion Thresholds for 100 MHz – 6 GHz and \leq 50 mm

The maximum measured output peak power of this EUT is 0.97mW, less than 10mW at 5mm distance.

Conclusion: No SAR evaluation required since transmitter power is below FCC threshold