

# FCC RF EXPOSURE REPORT

**FCC ID: 2AJZR-T605A00**

**Project No.** : 1706185  
**Equipment** : Premium Docking Station  
**Model** : iSAPPOS 9A+, iSAPPOS 12A+  
**Applicant** : iSAPPOS Systems Company Limited  
**Address** : Room 04, 6/F., Block A, Tonic Industrial Centre,  
NO.26 Kai Cheung Road, Kowloon Bay, Hong Kong

**According:** : FCC Guidelines for Human Exposure IEEE  
C95.1 & KDB447498 D01

**B T L I N C .**

B1, No. 37, Lane 365, YangGuang St., NeiHu District 114, Taipei, Taiwan  
TEL: +886-2-2657-3299 FAX: +886-2-2657-3331

Table for Filed Antenna

Ant.	Manufacturer	Model Name	Antenna Type	Connector	Gain(dBi)
1	Flytech	T605	PCB	N/A	1.07

## GENERAL CONCLUSION:

Maximum measured transmitter power:

Output Power (dBm)	Output Power (mW)	Limit (mW)
0.92	1.236	10

According to FCC KDB447498 D01 V06, Appendix A, SAR Test Exclusion Thresholds for 100 MHz – 6 GHz and  $\leq$  50 mm

The maximum measured output peak power of this EUT is 1.236mW, less than 10mW at 5mm distance.

**Conclusion: No SAR evaluation required since transmitter power is below FCC threshold**