

FCC RF EXPOSURE REPORT

FCC ID: 2AJZR-T605C00

Project No. : 1607236
Equipment : Premium Docking Station
Model : iSAPPOS 9C
Applicant : iSAPPOS Systems Company Limited
Address : Rm 08, 5/F., Block B, Hoplite Industrial Centre,
No. 3-5 Wang Tai Road, Kowloon Bay, Hong
Kong SAR

According: : FCC Guidelines for Human Exposure IEEE
C95.1

BTL Inc.

B1, No. 37, Lane 365, YangGuang St., NeiHu District 114, Taipei, Taiwan
TEL : (0769) 8318-3000 FAX : (0769) 8319-6000

Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain(dBi)
1	 BRITO TECHNOLOGY 昀陽科技有限公司	WLAN Embedded Antenna	Dipole	I-PEX	2.46

GENERAL CONCLUSION:

Maximum measured transmitter power:

Output Power (dBm)	Output Power (mW)	Limit (mW)
0.31	1.07	10

According to FCC KDB447498 V06, Appendix A, SAR Test Exclusion Thresholds for 100 MHz – 6 GHz and \leq 50 mm

The maximum measured output peak power of this EUT is 1.07 mW, less than 10mW at 5mm distance.

Conclusion: No SAR evaluation required since transmitter power is below FCC threshold