

FCC RF EXPOSURE REPORT

FCC ID: 2AJZR-T606B00

Project No. : 1607235

Equipment: Premium Docking Station

Model : iSAPPOS 12B
Applicant : iSAPPOS Systems Company Limited

: Rm 08, 5/F., Block B, Hoplite Industrial Centre, Address

No. 3-5 Wang Tai Road, Kowloon Bay, Hong

Kong SAR

According: : FCC Guidelines for Human Exposure IEEE

C95.1

BTL Inc.

B1, No. 37, Lane 365, YangGuang St., NeiHu District 114, Taipei, Taiwan

TEL: (0769) 8318-3000 FAX: (0769) 8319-6000



Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain(dBi)
1	Brito BRITO TECHNOLOGY 的陽科技有限公司	WLAN Embedded Antenna	Dipole	I-PEX	2.46

GENERAL CONCULUSION:

Maximum measured transmitter power:

OutputPower	Output Power	Limit (mW)	
(dBm)	(mW)		
0.17	1.04	10	

According to FCC KDB447498 V06, Appendix A, SAR Test Exclusion Thresholds for 100 MHz - 6 GHz and $\leq 50 \text{ mm}$

The maximum measured output peak power of this EUT is 1.04 mW, less than 10mW at 5mm distance.

Conclusion: No SAR evaluation required since transmitter power is below FCC threshold