











SAR Exemption Evaluation Report

Product Name: Rylo

Model No. : A0101

FCC ID : 2AK270101A

Applicant: Magenta Labs Inc

Address : 164 Townsend St. Unit 1 San Francisco California

United States 94107

Date of Receipt: July. 25th, 2017

Test Date July. 26th, 2017~Aug. 22nd, 2017

Issued Date : Sept. 19th, 2017

Report No. : 1772163R-RF-US-P20V02

Report Version: V1.0

The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standard through the calibration of the equipment and evaluated measurement uncertainty herein.

This report must not be used to claim product endorsement by CNAS, TAF any agency of the government.

The test report shall not be reproduced without the written approval of DEKRA Testing & Certification (Suzhou)

Co., Ltd.



Test Report Certification

Issued Date: Sept. 19th, 2017

Report No.: 1772163R-RF-US-P20V02



Product Name : Rylo

Applicant : Magenta Labs Inc

Address : 164 Townsend St. Unit 1 San Francisco California United

States 94107

Manufacturer : Magenta Labs Inc

Address : 164 Townsend St. Unit 1 San Francisco California United

States 94107

Model No. : A0101

FCC ID : 2AK270101A

EUT Voltage : DC 3.7V

Applicable Standard : KDB 447498 D01v06

Test Result : Complied

Performed Location : DEKRA Testing & Certification (Suzhou) Co., Ltd.

No.99 Hongye Rd., Suzhou Industrial Park, Suzhou,

215006, Jiangsu, China

TEL: +86-512-6251-5088 / FAX: +86-512-6251-5098

FCC Registration Number: 800392;

Documented By : (Adm. Specialist: Kitty Li)

Reviewed By : Frank he

(Senior Engineer: Frank He)

Approved By : Harry than

(Engineering Manager : Harry Zhao)



1. RF Exposure Evaluation

1.1. Limits

According to KDB 447498 D01 General RF Exposure Guidance v06

4.3.1 Standalone SAR test exclusion considerations

1) The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] \cdot [f(GHz)] \leq 3.0 for 1-g SAR and \leq 7.5 for 10-g extremity SAR,where

f(GHz) is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is \leq 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is \leq 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

- 2) At 100 MHz to 6 GHz and for test separation distances > 50 mm, the SAR test exclusion threshold is determined according to the following, and as illustrated in Appendix B:
- a) [Power allowed at numeric threshold for 50 mm in step 1) + (test separation distance 50 mm)·(f(MHz)/150)] mW, at 100 MHz to 1500 MHz
- b) [Power allowed at numeric threshold for 50 mm in step 1) + (test separation distance 50 mm)·10] mW at > 1500 MHz and \leq 6 GHz
- 3) The 1-g and 10-g SAR test exclusion thresholds for below 100 MHz at test separation distances ≤ 50 mm are determined by:
- a) The power threshold at the corresponding test separation distance at 100 MHz in step 2) is multiplied by [1 + log(100/f(MHz))] for test separation distances > 50 mm and < 200 mm
- b) The power threshold determined by the equation in a) for 50 mm and 100 MHz is multiplied by $\frac{1}{2}$ for test separation distances \leq 50 mm
- c) SAR measurement procedures are not established below 100 MHz. When SAR test exclusion cannot be applied, a KDB inquiry is required to determine SAR evaluation requirements for any test results to be acceptable. Note: when the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.



1.2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

The temperature and related humidity: 18 and 78% RH.

1.3. Test Result of RF Exposure Evaluation


Product	:	Rylo				
Test Item	:	RF Exposure Evaluation				
Test Site	:	AC-6				

Antenna Gain:

Model No.	N/A							
Antenna manufacturer	N/A							
Antenna Delivery		1*TX+1*RX			2*TX+2*RX		3*TX+3*RX	
Antenna technology		SISO						
] MIMO		Basic				
				CDD				
				Sectorized				
				Beam-forming				
Antenna Type		External] Dipole				
				Sectorized				
		Internal		PIFA				
				PCB				
				Ceramic Chip Antenna				
				Stamping Antenna				
				Metal housing Antenna				
Antonno Tochnology	Ant Gain							
Antenna Technology		(dBi)						
⊠siso	-1.59							

Based on The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm and the formula below:

Estimated SAR=
$$\sqrt{f(GHz)} * \frac{\text{(Max Power of channel, mW)}}{\text{Min. Separation Distance, mm}}$$



Conclusion: 2.4GHz SAR was not required.



	Exposure Condition	Pmax	Pmax	Distance		calculation result	Stand-alone Test	SAR Test
Band		(dBm)	(mw)	(mm)	f(GHz)		exclusion threshold	
ВТ	Body	2.78	1.90	5	2.44	0.59	3.00	No

———— The End	