

# INTERTEK TESTING SERVICES

---

## Analysis Report

The equipment under test (EUT) is a transmitter for a RC Car operating at 27.145 MHz which is controlled by a crystal. The EUT is powered by two 1.5V AA batteries. For more detail information pls. refer to the user manual.

Antenna Type: dedicated antenna

Antenna Gain: 0dBi

The nominal conducted output power specified: -44.0dBm (+/- 3dB)

The nominal radiated output power (e.r.p) specified: -46.15dBm (+/- 3dB)

Modulation Type: Pulse modulation

According to the KDB 447498:

The worst-case peak radiated emission for the EUT is 51.0dB<sub>UV</sub>/m at 3m in the frequency 27.145MHz

The EIRP =  $[(FS^*D)^2 / 30] \text{ mW} = -44.23 \text{ dBm}$

The ERP = EIRP – 2.15 = -46.38 dBm  
which is within the production variation.

The maximum conducted output power specified is -41dBm = 0.00008mW

The source-based time-averaging conducted output power

= 0.00008 \* Duty Cycle mW < 0.00008mW (Duty Cycle < 100%)

The SAR Exclusion Threshold Level for 27.145MHz when the minimum test separation distance is < 50mm:

$$= 474 * [1 + \log(100/f(MHz))] / 2$$

$$= 371.2 \text{ mW}$$

Since the source-based time-averaging conducted output power is well below the SAR low threshold level, so the EUT is considered to comply with SAR requirement without testing.

### Transmitter Duty Cycle Calculation

The duration of one cycle = 16.1739ms

Effective period of the cycle =  $1.3333 \text{ ms} \times 4 + 405.8 \mu\text{s} \times 10 = 9.3912 \text{ ms}$

DC =  $9.3912 \text{ ms} / 16.1739 \text{ ms} = 0.5806 \text{ or } 58.06\%$