



FCC PART 15, SUBPART C ISEDC RSS-247, ISSUE 2, FEBRUARY 2017

TEST AND MEASUREMENT REPORT

For

The Detection Group, Inc.

440 N Wolfe Rd. E211, Sunnyvale, CA 94085, USA

**FCC ID: 2AK4V-DT-550
IC: 22517-DT550**

Report Type: Original Report	Product Type: Smart Base Station
Prepared By: <u>Allen Huang</u> Test Technician	
Report Number: <u>R2008146-247</u>	
Report Date: <u>2020-11-06</u>	
Reviewed By: <u>Christian McCaig</u> <u>RF Engineer</u>	
Bay Area Compliance Laboratories Corp. 1274 Anvilwood Avenue, Sunnyvale, CA 94089, USA Tel: +1 (408) 732-9162, Fax: +1 (408) 732-9164	



Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report **must not** be used by the customer to claim product certification, approval, or endorsement by A2LA*, NIST, or any agency of the Federal Government.

* This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk “*” (Rev.2)

TABLE OF CONTENTS

1 General Description.....	5
1.1 Product Description for Equipment Under Test (EUT)	5
1.2 Mechanical Description of EUT	5
1.3 Objective.....	5
1.4 Related Submittal(s)/Grant(s)	5
1.5 Test Methodology	5
1.6 Measurement Uncertainty	6
1.7 Test Facility Registrations	6
1.8 Test Facility Accreditations	7
2 System Test Configuration.....	9
2.1 Justification	9
2.2 EUT Exercise Software.....	9
2.3 Duty Cycle Correction Factor	9
2.4 Equipment Modifications.....	11
2.5 Local Support Equipment	11
2.6 Support Equipment	11
2.7 Interface Ports and Cabling.....	11
3 Summary of Test Results	12
4 FCC §15.203 & ISEDC RSS-Gen §6.8 - Antenna Requirements	13
4.1 Applicable Standards	13
4.2 Antenna Description	13
5 FCC §2.1091, §15.247(i) & ISEDC RSS-102 - RF Exposure.....	14
5.1 Applicable Standards	14
5.2 MPE Prediction.....	15
5.3 MPE Results	15
5.4 RF exposure evaluation exemption for IC	16
6 FCC §15.207 & ISEDC RSS-Gen §8.8 - AC Line Conducted Emissions.....	17
6.1 Applicable Standards	17
6.2 Test Setup	17
6.3 Test Procedure	17
6.4 Corrected Amplitude and Margin Calculation.....	18
6.5 Test Setup Block Diagram.....	18
6.6 Test Equipment List and Details	19
6.7 Test Environmental Conditions	19
6.8 Summary of Test Results.....	19
6.9 Conducted Emissions Test Plots and Data.....	20
7 FCC §15.209, §15.247(d) & ISEDC RSS-247 §5.5, RSS-Gen §8.9, §8.10 - Spurious Radiated Emissions.....	22
7.1 Applicable Standards	22
7.2 Test Setup	24
7.3 Test Procedure	24
7.4 Corrected Amplitude & Margin Calculation.....	24
7.5 Test Equipment List and Details	25
7.6 Test Environmental Conditions	25
7.7 Summary of Test Results.....	25
7.8 Radiated Emissions Test Results	26
8 FCC §15.247(a) (2) & ISEDC RSS-247 §5.2, RSS-Gen §6.7 - Emission Bandwidth.....	29
8.1 Applicable Standards	29
8.2 Measurement Procedure.....	29
8.3 Test Equipment List and Details	29
8.4 Test Environmental Conditions	29
8.5 Test Results	29

9 FCC §15.247(b) (3) & ISEDC RSS-247 §5.4 - Output Power	34
9.1 Applicable Standards	34
9.2 Measurement Procedure.....	34
9.3 Test Equipment List and Details	34
9.4 Test Environmental Conditions	34
9.5 Test Results.....	35
10 FCC §15.247(e) & ISEDC RSS-247 §5.2(2) - Power Spectral Density	37
10.1 Applicable Standards	37
10.2 Measurement Procedure.....	37
10.3 Test Equipment List and Details	37
10.4 Test Environmental Conditions	37
10.5 Test Results.....	38
11 FCC §15.247(d) & ISEDC RSS-247 §5.5 - 100 kHz Bandwidth of Band Edges.....	40
11.1 Applicable Standards	40
11.2 Measurement Procedure.....	40
11.3 Test Equipment List and Details	40
11.4 Test Environmental Conditions	40
11.5 Test Results.....	41
12 FCC §15.247(d) & ISEDC RSS-247 §5.5 - Spurious Emissions at Antenna Terminals	42
12.1 Applicable Standards	42
12.2 Test Procedure	42
12.3 Test Equipment List and Details	42
12.4 Test Environmental Conditions	42
12.5 Test Results.....	42
13 Annex A (Normative) - Test Setup Photographs	45
14 Annex B (Normative) - EUT External Photographs.....	46
15 Annex C (Normative) - EUT Internal Photographs	47
16 Annex D (Normative) - A2LA Electrical Testing Certificate.....	48

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
0	R2008146-247	Original Report	2020-11-06

1 General Description

1.1 Product Description for Equipment Under Test (EUT)

This test and measurement report was prepared on behalf of *The Detection Group, Inc.* and their product model: DT-550, FCC ID: 2AK4V-DT-550; IC: 22517-DT550 or the “EUT” as referred to in this report. It is a Smart Base Station that operates within the 902-928 MHz frequency range. It also includes two pre-certified radio modules: a LTE radio (FCC ID: RI7ME910C1NA, IC: 5131A-ME910C1NA) and 2.4 GHz Wi-Fi/BT/BLE radio (FCC ID: 2AK4V-DT-450, IC: 22517-DT450).

1.2 Mechanical Description of EUT

The EUT measures approximately 15.87 cm (Length), 10.8 cm (Width), and 5.08 cm (Height) and weighs 0.25kg.

The data gathered are from a typical production sample provided by The Detection Group, Inc. with BACL assigned serial number: R2008146.

1.3 Objective

This report was prepared on behalf of *The Detection Group, Inc.* in accordance with Part 2, Subpart J, and Part 15, Subpart C of the Federal Communication Commission’s rules and ISED RSS-247 Issue 2, February 2017.

The objective was to determine compliance with FCC Part 15.247 and ISED RSS-247 for Antenna Requirements, RF Exposure, AC Line Conducted Emissions, Conducted & Radiated Spurious Emissions, Emission Bandwidth, Output Power, Power Spectral Density, and 100kHz Bandwidth of Band edges.

1.4 Related Submittal(s)/Grant(s)

FCC ID: RI7ME910C1NA, IC: 5131A-ME910C1NA (LTE)
FCC ID: 2AK4V-DT-450, IC: 22517-DT450 (2.4GHz Wi-Fi/BT/BLE)

1.5 Test Methodology

All measurements contained in this report were conducted in accordance with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

1.6 Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in the field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.

Parameter	Measurement uncertainty
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±0.57 dB
Power Spectral Density, conducted	±1.48dB
Unwanted Emissions, conducted	±1.57dB
All emissions, radiated	±4.0 dB
AC power line Conducted Emission	±2.0 dB
Temperature	±2 °C
Humidity	±5 %
DC and low frequency voltages	±1.0 %
Time	±2 %
Duty Cycle	±3 %

1.7 Test Facility Registrations

BACL's test facilities that are used to perform Radiated and Conducted Emissions tests are currently recognized by the Federal Communications Commission as Accredited with NIST Designation Number US1129.

BACL's test facilities that are used to perform Radiated and Conducted Emissions tests are currently registered with Industry Canada under Registration Numbers: 3062A-1, 3062A-2, and 3062A-3.

BACL is a Chinese Taipei Bureau of Standards Metrology and Inspection (BSMI) validated Conformity Assessment Body (CAB), under Appendix B, Phase I Procedures of the APEC Mutual Recognition Arrangement (MRA). BACL's BSMI Lab Code Number is: SL2-IN-E-1002R

BACL's test facilities that are used to perform AC Line Conducted Emissions, Telecommunications Line Conducted Emissions, Radiated Emissions from 30 MHz to 1 GHz, and Radiated Emissions from 1 GHz to 6 GHz are currently recognized as Accredited in accordance with the Voluntary Control Council for Interference [VCCI] Article 15 procedures under Registration Number A-0027.

1.8 Test Facility Accreditations

Bay Area Compliance Laboratories Corp. (BACL) is:

A- An independent, 3rd-Party, Commercial Test Laboratory accredited to ISO/IEC 17025:2005 by A2LA (Test Laboratory Accreditation Certificate Number 3297.02), in the fields of: Electromagnetic Compatibility and Telecommunications. Unless noted by an Asterisk (*) in the Compliance Matrix (See Section 3 of this Test Report), BACL's ISO/IEC 17025:2005 Scope of Accreditation includes all of the Test Method Standards and/or the Product Family Standards detailed in this Test Report.

BACL's ISO/IEC 17025:2005 Scope of Accreditation includes a comprehensive suite of EMC Emissions, EMC Immunity, Radio, RF Exposure, Safety and wireline Telecommunications test methods applicable to a wide range of product categories. These product categories include Central Office Telecommunications Equipment [including NEBS - Network Equipment Building Systems], Unlicensed and Licensed Wireless and RF devices, Information Technology Equipment (ITE); Telecommunications Terminal Equipment (TTE); Medical Electrical Equipment; Industrial, Scientific and Medical Test Equipment; Professional Audio and Video Equipment; Industrial and Scientific Instruments and Laboratory Apparatus; Cable Distribution Systems, and Energy Efficient Lighting.

B- A Product Certification Body accredited to ISO/IEC 17065:2012 by A2LA (Product Certification Body Accreditation Certificate Number 3297.03) to certify

- For the USA (Federal Communications Commission):

- 1- All Unlicensed radio frequency devices within FCC Scopes A1, A2, A3, and A4;
- 2- All Licensed radio frequency devices within FCC Scopes B1, B2, B3, and B4;
- 3- All Telephone Terminal Equipment within FCC Scope C.

- For the Canada (Industry Canada):

- 1 All Scope 1-Licence-Exempt Radio Frequency Devices;
- 2 All Scope 2-Licensed Personal Mobile Radio Services;
- 3 All Scope 3-Licensed General Mobile & Fixed Radio Services;
- 4 All Scope 4-Licensed Maritime & Aviation Radio Services;
- 5 All Scope 5-Licensed Fixed Microwave Radio Services
- 6 All Broadcasting Technical Standards (BETS) in the Category I Equipment Standards List.

- For Singapore (Info-Communications Development Authority (IDA)):

- 1 All Line Terminal Equipment: All Technical Specifications for Line Terminal Equipment – Table 1 of IDA MRA Recognition Scheme: 2011, Annex 2
2. All Radio-Communication Equipment: All Technical Specifications for Radio-Communication Equipment – Table 2 of IDA MRA Recognition Scheme: 2011, Annex 2

- For the Hong Kong Special Administrative Region:

- 1 All Radio Equipment, per KHCA 10XX-series Specifications;
- 2 All GMDSS Marine Radio Equipment, per HKCA 12XX-series Specifications;
- 3 All Fixed Network Equipment, per HKCA 20XX-series Specifications.

- For Japan:

- 1 MIC Telecommunication Business Law (Terminal Equipment):
 - All Scope A1 - Terminal Equipment for the Purpose of Calls;
 - All Scope A2 - Other Terminal Equipment
- 2 Radio Law (Radio Equipment):
 - All Scope B1 - Specified Radio Equipment specified in Article 38-2-2, paragraph 1, item 1 of the Radio Law
 - All Scope B2 - Specified Radio Equipment specified in Article 38-2-2, paragraph 1, item 2 of the Radio Law
 - All Scope B3 - Specified Radio Equipment specified in Article 38-2-2, paragraph 1, item 3 of the Radio Law

C- A Product Certification Body accredited to ISO/IEC 17065:2012 by A2LA (Product Certification Body Accreditation Certificate Number 3297.01) to certify Products to USA's Environmental Protection Agency (EPA) ENERGY STAR Product Specifications for:

- 1 Electronics and Office Equipment:
 - for Telephony (ver. 3.0)
 - for Audio/Video (ver. 3.0)

- for Battery Charging Systems (ver. 1.1)
- for Set-top Boxes & Cable Boxes (ver. 4.1)
- for Televisions (ver. 6.1)
- for Computers (ver. 6.0)
- for Displays (ver. 6.0)
- for Imaging Equipment (ver. 2.0)
- for Computer Servers (ver. 2.0)
- 2 Commercial Food Service Equipment
 - for Commercial Dishwashers (ver. 2.0)
 - for Commercial Ice Machines (ver. 2.0)
 - for Commercial Ovens (ver. 2.1)
 - for Commercial Refrigerators and Freezers
- 3 Lighting Products
 - For Decorative Light Strings (ver. 1.5)
 - For Luminaires (including sub-components) and Lamps (ver. 1.2)
 - For Compact Fluorescent Lamps (CFLs) (ver. 4.3)
 - For Integral LED Lamps (ver. 1.4)
- 4 Heating, Ventilation, and AC Products
 - for Residential Ceiling Fans (ver. 3.0)
 - for Residential Ventilating Fans (ver. 3.2)
- 5 Other
 - For Water Coolers (ver. 3.0)

D- A NIST Designated Phase-I and Phase-II Conformity Assessment Body (CAB) for the following economies and regulatory authorities under the terms of the stated MRAs/Treaties:

- Australia: ACMA (Australian Communication and Media Authority) – APEC Tel MRA -Phase I;
- Canada: (Innovation, Science and Economic development Canada - ISEDC) Foreign Certification Body – FCB – APEC Tel MRA -Phase I & Phase II;
- Chinese Taipei (Republic of China – Taiwan):
 - o BSMI (Bureau of Standards, Metrology and Inspection) APEC Tel MRA -Phase I;
 - o NCC (National Communications Commission) APEC Tel MRA -Phase I;
- European Union:
 - o EMC Directive 2014/30/EU US-EU EMC & Telecom MRA CAB (NB)
 - o Radio Equipment (RE) Directive 2014/53/EU US-EU EMC & Telecom MRA CAB (NB)
 - o Low Voltage Directive (LVD) 2014/35/EU
- Hong Kong Special Administrative Region: (Office of the Telecommunications Authority – OFTA) APEC Tel MRA -Phase I & Phase II
- Israel – US-Israel MRA Phase I
- Republic of Korea (Ministry of Communications - Radio Research Laboratory) APEC Tel MRA -Phase I
- Singapore: (Infocomm Media Development Authority - IMDA) APEC Tel MRA -Phase I & Phase II;
- Japan: VCCI - Voluntary Control Council for Interference US-Japan Telecom Treaty VCCI Side Letter-
- USA:
 - o ENERGY STAR Recognized Test Laboratory – US EPA
 - o Telecommunications Certification Body (TCB) – US FCC;
 - o Nationally Recognized Test Laboratory (NRTL) – US OSHA
- Vietnam: APEC Tel MRA -Phase I;

2 System Test Configuration

2.1 Justification

The EUT was configured for testing in accordance to ANSI C63.10.

2.2 EUT Exercise Software

The software “Atmel Studio v7.0.2397” was used to transmit signal for all the modules. The software was provided by *The Detection Group, Inc.* and verified by Allen Huang to comply with the standard requirements being tested against.

2.3 Duty Cycle Correction Factor

According to KDB 558074 D01 DTS Meas Guidance v05r02 section 6.0:


Preferably, all measurements of maximum conducted (average) output power will be performed with the EUT transmitting continuously (i.e., with a duty cycle of greater than or equal to 98%). When continuous operation cannot be realized, then the use of sweep triggering/signal gating techniques can be utilized to ensure that measurements are made only during transmissions at the maximum power control level. Such sweep triggering/signal gating techniques will require knowledge of the minimum transmission duration (T) over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation. Sweep triggering/signal gating techniques can then be used if the measurement/sweep time of the analyzer can be set such that it does not exceed T at any time that data is being acquired (i.e., no transmitter off-time is to be considered).

Radio frequency (MHz)	On Time (ms)	Period (ms)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)
924	26.3921	26.909	98.1	-


Duty Cycle = On Time (ms)/ Period (ms)

Duty Cycle Correction Factor (dB) = $10 \log(1/\text{Duty Cycle})$

Please refer to the following plots.



Date: 28.OCT.2020 16:09:28



Date: 28.OCT.2020 16:10:33

2.4 Equipment Modifications

N/A

2.5 Local Support Equipment

Manufacturer	Description	Model	Serial Number
ASUS	Laptop	FX504-GE-ES72	J6NRCX037440249

2.6 Support Equipment

Manufacturer	Description	Model	Serial Number
Atmel	Debugger/Programmer	Atmel-ICE	1800059972

2.7 Interface Ports and Cabling

Cable Descriptions	Length (m)	From	To
USB to USB-B	1.5	Laptop	Debugger/Programmer
Flex Ribbon	0.15	EUT	Debugger/Programmer

3 Summary of Test Results

Results reported relate only to the product tested.

FCC & ISEDC Rules	Description of Test	Results
FCC §15.203 ISEDC RSS-Gen §6.8	Antenna Requirements	Compliant
FCC §2.1091, §15.247(i) ISEDC RSS-102	RF Exposure	Compliant
FCC §15.207 ISEDC RSS-Gen §8.8	AC Line Conducted Emissions	Compliant
FCC §15.209, §15.247(d) ISEDC RSS-247 §5.5 RSS-Gen §8.9, §8.10	Radiated Spurious Emissions	Compliant
FCC §15.247(a)(2) ISEDC RSS-247 §5.2 RSS-Gen §6.7	6 dB & 99% Emission Bandwidth	Compliant
FCC §15.247(b)(3) ISEDC RSS-247 §5.4	Average Output Power	Compliant
FCC §15.247(e) ISEDC RSS-247 §5.2(2)	Power Spectral Density	Compliant
FCC §15.247(d) ISEDC RSS-247 §5.5	100 kHz Bandwidth of Frequency Band Edge	Compliant
FCC §2.1051, §15.247(d) ISEDC RSS-247 §5.5	Spurious Emissions at Antenna Port	Compliant

4 FCC §15.203 & ISEDC RSS-Gen §6.8 - Antenna Requirements

4.1 Applicable Standards

According to FCC §15.203:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

And according to FCC §15.247 (b) (4), if transmitting antennas of directional gain greater than 6 dBi are used the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

According to ISEDC RSS-Gen §6.8: Transmitter Antenna

The applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotropically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list.

For expediting the testing, measurements may be performed using only the antenna with highest gain of each combination of transmitter and antenna type, with the transmitter output power set at the maximum level. However, the transmitter shall comply with the applicable requirements under all operational conditions and when in combination with any type of antenna from the list provided in the test report (and in the notice to be included in the user manual, provided below).

When measurements at the antenna port are used to determine the RF output power, the effective gain of the device's antenna shall be stated, based on a measurement or on data from the antenna's manufacturer.

The test report shall state the RF power, output power setting and spurious emission measurements with each antenna type that is used with the transmitter being tested.

For license-exempt equipment with detachable antennas, the user manual shall also contain the following notice in a conspicuous location:

This radio transmitter has been approved by Innovation, Science and Economic Development Canada to operate with the antenna types listed below, with the maximum permissible gain indicated. Antenna types not included in this list that have a gain greater than the maximum gain indicated for any type listed are strictly prohibited for use with this device.

Immediately following the above notice, the manufacturer shall provide a list of all antenna types which can be used with the transmitter, indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna type.

4.2 Antenna Description

External/Internal/ Integral	Frequency Range (MHz)	Antenna Type	Maximum Antenna Gain (dBi)
External	902-928 MHz	Whip	1.2

5 FCC §2.1091, §15.247(i) & ISED RSS-102 - RF Exposure

5.1 Applicable Standards

According to FCC §15.247(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for General Population/Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	* (100)	30
1.34-30	824/f	2.19/f	* (180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz

* = Plane-wave equivalent power density

According to ISED RSS-102 Issue 5:

2.5.2 Exemption Limits for Routine Evaluation – RF Exposure Evaluation

RF exposure evaluation is required if the separation distance between the user and/or bystander and the device's radiating element is greater than 20 cm, except when the device operates as follows:

- below 20 MHz⁶ and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 1 W (adjusted for tune-up tolerance);
- at or above 20 MHz and below 48 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $4.49/f^{0.5}$ W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 48 MHz and below 300 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 0.6 W (adjusted for tune-up tolerance);
- at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $1.31 \times 10^{-2} f^{0.6834}$ W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 5 W (adjusted for tune-up tolerance).

In these cases, the information contained in the RF exposure technical brief may be limited to information that demonstrates how the e.i.r.p. was derived.

5.2 MPE Prediction

Predication of MPE limit at a given distance, Equation from OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S = power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

5.3 MPE Results

Maximum average output power at antenna input terminal (dBm): 23.89
Maximum average output power at antenna input terminal (mW): 244.91
Prediction distance (cm): 20
Prediction frequency (MHz): 906
Maximum Antenna Gain, typical (dBi): 1.2
Maximum Antenna Gain (numeric): 1.318
Power density of prediction frequency at 20.0 cm (mW/cm²): 0.0642
FCC MPE limit for uncontrolled exposure at prediction frequency (mW/cm²): 0.604

The device is compliant with the requirement MPE limit for uncontrolled exposure. The maximum power density at the distance of 20 cm is 0.0642 mW/cm². Limit is 0.604 mW/cm².

Radio Co-location

Worst Case Colocation 900MHz radio with LTE and Wi-Fi/BT/BLE radios

Frequency Band	Max Conducted Power (dBm)	Antenna Gain (dBi)	Evaluated Distance (cm)	Worst-Case MPE (mW/cm ²)	MPE Limit (mW/cm ²)	Worst-Case MPE Ratios	Sum of MPE Ratios	Limit
Worst Case								
900 MHz Radio	23.89	1.2	20	0.064	0.604	10.6%		
LTE Radio	24.00	3.5	20	0.112	1.0	11.2%		
Wi-Fi/BT/BLE Radio	22.4	1.4	20	0.048	1.0	4.8%	26.6%	100%

Note: LTE and Wi-Fi/BT/BLE conducted out power from pre-certified reports FCC ID: RI7ME910C1NA and 2AK4V-DT-450.

Note: antenna used for the LTE radio module is model: SR4L034-R by Antenova; antenna information for the Wi-Fi/BT/BLE radio from the original filing FCC ID: 2AK4V-DT-450.

5.4 RF exposure evaluation exemption for IC

Maximum EIRP power = $23.89 \text{ dBm} + 1.2 \text{ dBi} = 25.09 \text{ dBm}$ which is lesser than $1.31 \times 10^{-2} f^{0.6834} = 1.3746 \text{ W} = 31.38 \text{ dBm}$.

Therefore the RF exposure Evaluation is exempt.

6 FCC §15.207 & ISEDC RSS-Gen §8.8 - AC Line Conducted Emissions

6.1 Applicable Standards

As per FCC §15.207 and ISEDC RSS-Gen §8.8 Conducted limits:

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequencies ranges.

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	Quasi-Peak	Average
0.15-0.5	66 to 56 ^{Note 1}	56 to 46 ^{Note 2}
0.5-5	56	46
5-30	60	50

Note 1: Decreases with the logarithm of the frequency.

Note 2: A linear average detector is required

6.2 Test Setup

The measurement was performed at shield room, using the setup per ANSI C63.10-2013 measurement procedure. The specification used was FCC §15.207 and ISEDC RSS-Gen §8.8 limits.

External I/O cables were draped along the edge of the test table and bundle when necessary.

The AC/DC power adapter of the EUT was connected with LISN which provided 120 V / 60 Hz AC power.

6.3 Test Procedure

During the conducted emissions test, the power cord of the EUT host system was connected to the mains outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data were recorded in the peak detection mode, quasi-peak, and average detection mode. Quasi-Peak readings are distinguished with a “QP.” Average readings are distinguished with an “Ave”.

6.4 Corrected Amplitude and Margin Calculation

The Corrected Amplitude (CA) is calculated by adding the Cable Loss (CL), the Attenuator Factor (Atten) to indicated Amplitude (Ai) reading. The basic equation is as follows:


$$CA = Ai + CL + Atten$$

For example, a corrected amplitude of 46.2 dBuV = Indicated Reading (32.5 dBuV) + Cable Loss (3.7 dB) + Attenuator (10 dB)

The “Margin” column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of -7 dB means the emission is 7 dB below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corrected Amplitude} - \text{Limit}$$

6.5 Test Setup Block Diagram



6.6 Test Equipment List and Details

Manufacturer	Description	Model No.	Serial No.	Calibration Date	Calibration Interval
Rohde and Schwarz	EMI Test Receiver	ESU-40	100433	2020-03-25	13 months
Rohde and Schwarz	Impulse Limiter	ESH3-Z2	101964	2020-07-01	1 year
Solar Electronics Company	High Pass Filter	Type 7930-100	7930150204	2020-02-27	1 year
Suirong	30 ft conductive emission cable	LMR 400	-	N/R	N/A
FCC	LISN	FCC-LISN-50-25-2-10-CISPR16	160130	2020-10-13	1 year
Vasona	Test software	V6.0 build 11	10400213	N/R	N/R

Statement of Traceability: **BACL Corp.** attests that all of the calibrations on the equipment items listed above were traceable to NIST or to another internationally recognized National Metrology Institute (NMI), and were compliant with the latest version of A2LA policy P102 “A2LA Policy on Metrological Traceability”.

6.7 Test Environmental Conditions

Temperature:	22 °C
Relative Humidity:	43 %
ATM Pressure:	101.8 kPa

The testing was performed by Allen Huang on 2020-10-28 in the 5 meter chamber 3 test site.

6.8 Summary of Test Results


According to the recorded data in following table, the EUT complied with the FCC 15C and ISEDC RSS-Gen standard's conducted emissions limits, with the margin reading of:

Connection: AC/DC adapter connected to 120 V/60 Hz, AC			
Margin (dB)	Frequency (MHz)	Conductor Mode (Line/Neutral)	Range (MHz)
-25.64	0.15	Line	0.15-30

6.9 Conducted Emissions Test Plots and Data


Worst Case: 906 MHz

120 V, 60 Hz – Line



Frequency (MHz)	Corrected Amplitude (dBuV)	Conductor (Line/Neutral)	Limit (dBuV)	Margin (dB)	Detector (QP/Ave.)
0.15	40.36	Line	66	-25.64	QP
0.202438	31.65	Line	63.51	-31.86	QP
0.16214	37.63	Line	65.35	-27.73	QP
0.187049	32.89	Line	64.17	-31.28	QP
0.267774	25.39	Line	61.19	-35.79	QP
0.215065	29.41	Line	63.01	-33.6	QP

Frequency (MHz)	Corrected Amplitude (dBuV)	Conductor (Line/Neutral)	Limit (dBuV)	Margin (dB)	Detector (QP/Ave.)
0.15	21.25	Line	56	-34.75	Ave.
0.202438	11.44	Line	53.51	-42.07	Ave.
0.16214	16.22	Line	55.35	-39.13	Ave.
0.187049	13.28	Line	54.17	-40.89	Ave.
0.267774	10.96	Line	51.19	-40.22	Ave.
0.215065	11.5	Line	53.01	-41.5	Ave.

120 V, 60 Hz – Neutral

Frequency (MHz)	Corrected Amplitude (dBuV)	Conductor (Line/Neutral)	Limit (dBuV)	Margin (dB)	Detector (QP/Ave.)
0.15	38.59	Neutral	66	-27.41	QP
0.165758	34.57	Neutral	65.17	-30.6	QP
0.269227	24.97	Neutral	61.14	-36.17	QP
0.363677	24.23	Neutral	58.64	-34.42	QP
0.486591	13.01	Neutral	56.23	-43.22	QP
0.584376	13.65	Neutral	56	-42.35	QP

Frequency (MHz)	Corrected Amplitude (dBuV)	Conductor (Line/Neutral)	Limit (dBuV)	Margin (dB)	Detector (QP/Ave.)
0.15	20.67	Neutral	56	-35.33	Ave.
0.165758	16.47	Neutral	55.17	-38.7	Ave.
0.269227	10.11	Neutral	51.14	-41.03	Ave.
0.363677	17.56	Neutral	48.64	-31.08	Ave.
0.486591	4.01	Neutral	46.23	-42.22	Ave.
0.584376	8.7	Neutral	46	-37.3	Ave.

7 FCC §15.209, §15.247(d) & ISEDC RSS-247 §5.5, RSS-Gen §8.9, §8.10 - Spurious Radiated Emissions

7.1 Applicable Standards

As per FCC §15.35(d): Unless otherwise specified, on any frequency or frequencies above 1000 MHz, the radiated emission limits are based on the use of measurement instrumentation employing an average detector function. Unless otherwise specified, measurements above 1000 MHz shall be performed using a minimum resolution bandwidth of 1 MHz.

As Per FCC §15.205(a) and RSS-Gen except as show in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 – 0.110	16.42 – 16.423	960 – 1240	4.5 – 5.15
0.495 – 0.505	16.69475 – 16.69525	1300 – 1427	5.35 – 5.46
2.1735 – 2.1905	25.5 – 25.67	1435 – 1626.5	7.25 – 7.75
4.125 – 4.128	37.5 – 38.25	1645.5 – 1646.5	8.025 – 8.5
4.17725 – 4.17775	73 – 74.6	1660 – 1710	9.0 – 9.2
4.20725 – 4.20775	74.8 – 75.2	1718.8 – 1722.2	9.3 – 9.5
6.215 – 6.218	108 – 121.94	2200 – 2300	10.6 – 12.7
6.26775 – 6.26825	123 – 138	2310 – 2390	13.25 – 13.4
6.31175 – 6.31225	149.9 – 150.05	2483.5 – 2500	14.47 – 14.5
8.291 – 8.294	156.52475 – 156.52525	2690 – 2900	15.35 – 16.2
8.362 – 8.366	156.7 – 156.9	3260 – 3267	17.7 – 21.4
8.37625 – 8.38675	162.0125 – 167.17	3.332 – 3.339	22.01 – 23.12
8.41425 – 8.41475	167.72 – 173.2	3.3458 – 3.358	23.6 – 24.0
12.29 – 12.293	240 – 285	3.600 – 4.400	31.2 – 31.8
12.51975 – 12.52025	322 – 335.4		36.43 – 36.5
12.57675 – 12.57725	399.9 – 410		Above 38.6
13.36 – 13.41	608 – 614		

As per FCC §15.209(a): Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (micro volts/meter)	Measurement Distance (meters)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100**	3
88 - 216	150**	3
216 - 960	200**	3
Above 960	500	3

** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

As per FCC §15.247 (d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

As per ISED RSS-Gen 8.9,

Except when the requirements applicable to a given device state otherwise, emission from licence-exempt transmitters shall comply with the field strength limits shown in the table below. Additional, the level of any transmitter emission shall not exceed the level of the transmitter's fundamental emission.

General Field Strength Limits for Licence-Exemption Transmitters at Frequencies above 30 MHz

Frequency (MHz)	Field Strength ($\mu\text{V/m}$ at 3 meters)
30-88	100
88-216	150
216-960	200
Above 960*	500

* Unless otherwise specified, for all frequencies greater than 1 GHz, the radiated emission limits for licence-exempt radio apparatus stated in applicable RSSs (including RSS-Gen) are based on measurements using a linear average detector function having a minimum resolution bandwidth of 1 MHz. If an average limit is specified for the EUT, then the peak emission shall also be measured with instrumentation properly adjusted for such factors as pulse desensitization to ensure the peak emission is less than 20 dB above the average limit.

Note: Transmitting devices are not permitted in restricted frequency bands unless stated otherwise in the specific RSS.

As per ISED RSS-247 §5.5, in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under Section 5.4(4), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.

7.2 Test Setup

The radiated emissions tests were performed in the 5-meter Chamber, using the setup in accordance with ANSI C63.10-2013. The specification used was the FCC 15 Subpart C and ISEDC RSS-247 limits.

The spacing between the peripherals was 10 centimeters.

External I/O cables were draped along the edge of the test table and bundle when necessary.

7.3 Test Procedure

For the radiated emissions test, the EUT host, and all support equipment power cords was connected to the AC floor outlet.

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

The EUT was set 3 meter away from the testing antenna, which was varied from 1-4 meter, and the EUT was placed on a turntable, which was 0.8 meter and 1.5 meter above the ground plane for below and above 1000 MHz measurements, the table shall be rotated for 360 degrees to find out the highest emission. The receiving antenna should be changed the polarization both of horizontal and vertical.

The spectrum analyzer or receiver is set as:

Below 1000 MHz:

$$\text{RBW} = 100 \text{ kHz} / \text{VBW} = 300 \text{ kHz} / \text{Sweep} = \text{Auto}$$

Above 1000 MHz:

- (1) Peak: $\text{RBW} = 1\text{MHz} / \text{VBW} = 1\text{MHz} / \text{Sweep} = \text{Auto}$
- (2) Average: $\text{RBW} = 1\text{MHz} / \text{VBW} = 10\text{Hz} / \text{Sweep} = \text{Auto}$

7.4 Corrected Amplitude & Margin Calculation

The Corrected Amplitude (CA) is calculated by adding the Antenna Factor (AF), the Cable Loss (CL), the Attenuator Factor (Atten) and subtracting the Amplifier Gain (Ga) to indicated Amplitude (Ai) reading. The basic equation is as follows:

$$\text{CA} = \text{Ai} + \text{AF} + \text{CL} + \text{Atten} - \text{Ga}$$

For example, a corrected amplitude of 40.3 dBuV/m = Indicated Reading (32.5 dBuV) + Antenna Factor (+23.5dB) + Cable Loss (3.7 dB) + Attenuator (10 dB) - Amplifier Gain (29.4 dB)

The “Margin” column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of -7 dB means the emission is 7 dB below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corrected Amplitude} - \text{Limit}$$

7.5 Test Equipment List and Details

Manufacturer	Description	Model No.	Serial No.	Calibration Date	Calibration Interval
Rohde and Schwarz	EMI Test Receiver	ESU-40	100433	2020-03-25	13 months
Rohde & Schwarz	Signal Analyzer	FSV40	1321.3008K39-101203-UW	2020-02-06	1 year
Agilent	Spectrum Analyzer	E4446A	MY48250238	2019-06-26	18 months
Sunol Science Corp	System Controller	SC110V	122303-1	N/R	N/A
Sunol Sciences	Biconilog Antenna	JB3	A020106-2	2019-11-20	2 years
HP	Pre-Amplifier	8447D	2944A07030	2020-08-17	1 year
HP	Pre-Amplifier	8449B	3147A00400	2020-02-27	1 year
ETS Lindgren	Horn Antenna	3117	00218973	2019-02-13	2 years
Insulated Wire Corp.	157 Series 2.92 SM (x2) Armored 33 ft. Cable	KPS-1571AN-3960-KPS	DC 1917	2020-02-28	1 year
-	RF cable	-	-	Each time ¹	N/A
-	Notch Filter	-	-	Each time ¹	N/A
MDP Digital	Microwave LMR 400 UltraFlex Coaxial Cable 35\'	LMR400UF	BACL1904161	2020-05-21	1 year

Note¹: cable and notch filter included in the test set-up will be checked each time before testing.

Statement of Traceability: *BACL Corp.* attests that all of the calibrations on the equipment items listed above were traceable to NIST or to another internationally recognized National Metrology Institute (NMI), and were compliant with the latest version of A2LA policy P102 "A2LA Policy on Metrological Traceability".

7.6 Test Environmental Conditions

Temperature:	19 °C
Relative Humidity:	34 %
ATM Pressure:	102.2 kPa

The testing was performed by Allen Huang on 2020-10-27 at 5 meter chamber 3.

7.7 Summary of Test Results

According to the data hereinafter, the EUT complied with FCC Part 15C and ISED RSS-247 standard's radiated emissions limits, and had the worst margin of:


Mode: Transmitting			
Margin (dB)	Frequency (MHz)	Polarization (Horizontal/Vertical)	Transmitting Channel
-0.51	625.02225	Horizontal	906MHz

Please refer to the following table and plots for specific test result details.

7.8 Radiated Emissions Test Results

1) 30 MHz – 1 GHz Worst Case, Measured at 3 meters

Worst Case: 906 MHz



Frequency (MHz)	Corrected Amplitude (dBµV/m)	Antenna Height (cm)	Antenna Polarity (H/V)	Turntable Azimuth (degrees)	Limit (dBµV/m)	Margin (dB)	Comment
574.99325	49.62	157	H	178	80.54	-30.92	QP ¹
475.02375	46.46	199	H	198	80.54	-34.08	QP ¹
250.00025	40.51	143	H	324	46	-5.49	QP
725.02025	46.4	101	H	27	80.54	-34.14	QP ¹
675.02525	44.97	119	H	62	46	-1.03	QP
625.02225	45.49	126	H	49	46	-0.51	QP

Note¹: Due to frequencies being outside of the restricted bands, the limit was determined to be 30dB below the measured fundamental emission.

2) 1-10 GHz, Measured at 3 Meters


Frequency (MHz)	S.A. Reading (dB μ V)	Turntable Azimuth (degrees)	Test Antenna			Cable Loss (dB)	Pre-Amp. (dB)	Cord. Reading (dB μ V/m)	FCC/ISEDC		Note
			Height (cm)	Polarity (H/V)	Factor (dB/m)				Limit (dB μ V/m)	Margin (dB)	
Low Channel Frequency: 906 MHz											
906	110.4	185	150	H	28.1	1.861	29.82	110.54	-	-	Peak
906	108.83	245	150	V	28.1	1.861	29.82	108.97	-	-	Peak
902	47.12	0	100	H	28.1	1.861	29.82	47.26	80.54	-33.28	Peak ¹
902	47.95	0	100	V	28.1	1.861	29.82	48.09	78.97	-30.88	Peak ¹
1025.3	65.16	70	185	H	27.6	4.061	37.64	59.181	74	-14.819	Peak
1025.3	63.2	20	290	V	27.6	4.061	37.64	57.221	74	-16.779	Peak
1025.3	52.35	70	185	H	27.6	4.061	37.64	46.371	54	-7.629	Ave
1025.3	50.28	20	290	V	27.6	4.061	37.64	44.301	54	-9.699	Ave
1811.7	71.10	245	275	H	30.9	4.535	36.73	69.805	80.54	-10.735	Peak ¹
1811.7	66.44	65	150	V	30.9	4.535	36.73	65.145	78.97	-13.825	Peak ¹
2718	47.17	155	150	H	32.6	5.983	36.24	49.513	74	-24.487	Peak
2718	48.52	270	150	V	32.6	5.983	36.24	50.863	74	-23.137	Peak
2718	45.74	155	150	H	32.6	5.983	36.24	48.083	54	-5.917	Ave
2718	46.68	270	150	V	32.6	5.983	36.24	49.023	54	-4.977	Ave

Frequency (MHz)	S.A. Reading (dB μ V)	Turntable Azimuth (degrees)	Test Antenna			Cable Loss (dB)	Pre-Amp. (dB)	Cord. Reading (dB μ V/m)	FCC/ISEDC		Note
			Height (cm)	Pol (H/V)	Factor (dB/m)				Limit (dB μ V/m)	Margin (dB)	
Middle Channel Frequency: 914 MHz											
914	108.62	185	150	H	28.1	1.861	29.82	108.76	-	-	Peak
914	107.89	245	150	V	28.1	1.861	29.82	108.03	-	-	Peak
1827.4	71.48	240	225	H	30.9	4.535	36.73	70.185	78.76	-8.575	Peak ¹
1827.4	68.09	80	235	V	30.9	4.535	36.73	66.795	78.03	-11.235	Peak ¹
2742	44.42	250	175	H	33.2	6.33	36.28	47.67	74	-26.33	Peak
2742	44.96	40	150	V	33.2	6.33	36.28	48.21	74	-25.79	Peak
2742	40.98	250	175	H	33.2	6.33	36.28	44.23	54	-9.77	Ave
2742	41.32	40	150	V	33.2	6.33	36.28	44.57	54	-9.43	Ave
4608.3	48.04	150	135	H	32.7	5.983	36.24	50.483	74	-23.517	Peak
4608.3	47.97	275	145	V	32.7	5.983	36.24	50.413	74	-23.587	Peak
4608.3	47.14	150	135	H	32.7	5.983	36.24	49.583	54	-4.417	Ave
4608.3	46.40	275	145	V	32.7	5.983	36.24	48.843	54	-5.157	Ave

Frequency (MHz)	S.A. Reading (dB μ V)	Turntable Azimuth (degrees)	Test Antenna			Cable Loss (dB)	Pre-Amp. (dB)	Cord. Reading (dB μ V/m)	FCC/ISEDC		Note
			Height (cm)	Polarity (H/V)	Factor (dB/m)				Limit (dB μ V/m)	Margin (dB)	
High Channel Frequency: 924 MHz											
924	108.97	185	150	H	28.1	1.861	29.82	109.11	-	-	Peak
924	106.53	245	150	V	28.1	1.861	29.82	106.67	-	-	Peak
928	47.85	0	100	H	28.1	1.861	29.82	47.99	79.11	-31.12	Peak ¹
928	48.16	0	100	V	28.1	1.861	29.82	48.3	76.67	-28.37	Peak ¹
1061.3	62.34	285	140	H	27.6	4.061	37.74	56.261	74	-17.739	Peak
1061.3	54.10	345	150	V	27.6	4.061	37.74	48.021	74	-25.979	Peak
1061.3	48.70	285	140	H	27.6	4.061	37.74	42.621	54	-11.379	Ave
1061.3	42.00	345	150	V	27.6	4.061	37.74	35.921	54	-18.079	Ave
1847.7	68.59	250	160	H	30.9	4.535	36.73	67.295	79.11	-11.815	Peak ¹
1847.7	68.35	210	260	V	30.9	4.535	36.73	67.055	76.67	-9.615	Peak ¹
2772	47.57	145	150	H	32.7	5.983	36.24	50.013	74	-23.987	Peak
2772	47.43	275	265	V	32.7	5.983	36.24	49.873	74	-24.127	Peak
2772	46.09	145	150	H	32.7	5.983	36.24	48.533	54	-5.467	Ave
2772	44.84	275	265	V	32.7	5.983	36.24	47.283	54	-6.717	Ave

Note¹: Due to frequencies being outside of the restricted bands, the limit was determined to be 30 dB below the measured fundamental emission.

Plot for worst Case: 906 MHz, measured at 1 m



8 FCC §15.247(a) (2) & ISEDC RSS-247 §5.2, RSS-Gen §6.7 - Emission Bandwidth

8.1 Applicable Standards

According to FCC §15.247(a) (2) and ISEDC RSS-247 §5.2: the minimum 6 dB bandwidth shall be 500 kHz.

8.2 Measurement Procedure

The measurements are based on FCC KDB 558074 D01 DTS Meas Guidance v05r02: Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247 section 8: DTS bandwidth.

8.3 Test Equipment List and Details

Manufacturer	Description	Model No.	Serial No.	Calibration Date	Calibration Interval
Rohde & Schwarz	Signal Analyzer	FSV40	1321.3008K39-101203-UW	2020-02-06	1 year
-	RF cable	-	-	Each time ¹	N/A

Note¹: cable included in the test set-up will be checked each time before testing.

Statement of Traceability: *BACL Corp.* attests that all of the calibrations on the equipment items listed above were traceable to NIST or to another internationally recognized National Metrology Institute (NMI), and were compliant with the latest version of A2LA policy P102 “A2LA Policy on Metrological Traceability”.

8.4 Test Environmental Conditions

Temperature:	21° C
Relative Humidity:	39 %
ATM Pressure:	102.0 KPa


The testing was performed by Allen Huang on 2020-10-26 and 2020-10-29 at RF test site.

8.5 Test Results


Channel	Frequency (MHz)	99% OBW (kHz)	6 dB OBW (kHz)
Low	906	816	667.87
Middle	914	829	670.50
High	924	841	673.12

Please refer to the following plots for detailed test results.


99% OBW, Low Channel: 906 MHz





99% OBW, Middle Channel: 914 MHz




99% OBW, High Channel: 924 MHz



Date: 26.OCT.2020 09:48:00

6 dB OBW, Low Channel: 906 MHz**6 dB OBW, Middle Channel: 914 MHz**

6 dB OBW, High Channel: 924 MHz

Date: 29 OCT 2020 09:23:03

9 FCC §15.247(b) (3) & ISEDC RSS-247 §5.4 - Output Power

9.1 Applicable Standards

According to FCC §15.247(b) (3): For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

According to RSS-247 §5.4: For DTSs employing digital modulation techniques operating in the bands 902-928 MHz and 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1 W. The e.i.r.p. shall not exceed 4 W, except as provided in section 5.4(e).

9.2 Measurement Procedure

The measurements are based on ANSI C63.10-2013, Section 11.9.2.2.2.

9.3 Test Equipment List and Details

Manufacturer	Description	Model No.	Serial No.	Calibration Date	Calibration Interval
Rohde & Schwarz	Signal Analyzer	FSV40	1321.3008K39-101203-UW	2020-02-06	1 year
-	RF cable	-	-	Each time ¹	N/A

Note¹: cable included in the test set-up will be checked each time before testing.

Statement of Traceability: *BACL Corp.* attests that all of the calibrations on the equipment items listed above were traceable to NIST or to another internationally recognized National Metrology Institute (NMI), and were compliant with the latest version of A2LA policy P102 “A2LA Policy on Metrological Traceability”.

9.4 Test Environmental Conditions

Temperature:	21° C
Relative Humidity:	39 %
ATM Pressure:	102.0 KPa


The testing was performed by Allen Huang on 2020-10-26 at 5 meter chamber 3.



9.5 Test Results

Channel	Frequency (MHz)	Average Conducted Output Power (dBm)	Peak Conducted Output Power* (dBm)	FCC/ISEDC Limit (dBm)
Low	906	23.89	26.55	30
Middle	914	23.74	26.12	30
High	924	23.52	25.74	30

*peak power for reference only.

Please refer to the following plots for detailed average power test results.



Middle Channel, 914 MHz**High Channel, 924 MHz**

10 FCC §15.247(e) & ISEDC RSS-247 §5.2(2) - Power Spectral Density

10.1 Applicable Standards

According to ECFR §15.247(e) and RSS-247 §5.2 (2) , for digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

10.2 Measurement Procedure

The measurements are based on FCC KDB 558074 D01 DTS Meas Guidance v05r02: Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247 section 8.4: Maximum power spectral density level in the fundamental emission.

10.3 Test Equipment List and Details

Manufacturer	Description	Model No.	Serial No.	Calibration Date	Calibration Interval
Rohde & Schwarz	Signal Analyzer	FSV40	1321.3008K39-101203-UW	2020-02-06	1 year
-	RF cable	-	-	Each time ¹	N/A

Note¹: cable included in the test set-up will be checked each time before testing.

Statement of Traceability: *BACL Corp.* attests that all of the calibrations on the equipment items listed above were traceable to NIST or to another internationally recognized National Metrology Institute (NMI), and were compliant with the latest version of A2LA policy P102 “A2LA Policy on Metrological Traceability”.

10.4 Test Environmental Conditions


Temperature:	23° C
Relative Humidity:	42 %
ATM Pressure:	102.7 KPa


The testing was performed by Allen Huang on 2020-10-26 at RF test site.

10.5 Test Results


Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)
Low	906	5.99	8
Middle	914	5.64	8
High	924	5.78	8

Low Channel, 906 MHz



Middle Channel, 914 MHz

Date: 26.OCT.2020 09:40:49

High Channel, 924 MHz

Date: 26.OCT.2020 09:53:54

11 FCC §15.247(d) & ISEDC RSS-247 §5.5 - 100 kHz Bandwidth of Band Edges

11.1 Applicable Standards

According to FCC §15.247(d), in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emissions limits specified in §15.209(a) see §15.205(c).

According to ISEDC RSS-247 §5.5. In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under Section 5.4(4), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.

11.2 Measurement Procedure

Span = wide enough to capture the peak level of the emission operating on the channel closest to the band edge, as well as any modulation products which fall outside of the authorized band of operation

RBW = 100 kHz

VBW = 300 kHz

Sweep = coupled

Detector function = peak

Trace = max hold

11.3 Test Equipment List and Details

Manufacturer	Description	Model No.	Serial No.	Calibration Date	Calibration Interval
Rohde & Schwarz	Signal Analyzer	FSV40	1321.3008K39-101203-UW	2020-02-06	1 year
-	RF cable	-	-	Each time ¹	N/A

Note¹: cable included in the test set-up will be checked each time before testing.

Statement of Traceability: *BACL Corp.* attests that all of the calibrations on the equipment items listed above were traceable to NIST or to another internationally recognized National Metrology Institute (NMI), and were compliant with the latest version of A2LA policy P102 “A2LA Policy on Metrological Traceability”.


11.4 Test Environmental Conditions

Temperature:	21° C
Relative Humidity:	39 %
ATM Pressure:	102.0 KPa

The testing was performed by Allen Huang on 2020-10-26 at 5 meter chamber 3.


11.5 Test Results

Low Channel, 906 MHz



Date: 26.OCT.2020 10:13:10

High Channel, 924 MHz



Date: 26.OCT.2020 10:08:02

12 FCC §15.247(d) & ISEDC RSS-247 §5.5 - Spurious Emissions at Antenna Terminals

12.1 Applicable Standards

For FCC §15.247(d) and ISEDC RSS-247 §5.5, in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

12.2 Test Procedure

The RF output of the EUT was connected to a spectrum analyzer through appropriate attenuation. The resolution bandwidth of the spectrum analyzer was set at 100 kHz. Sufficient scans were taken to show any out of band emissions up to 10th harmonic.

12.3 Test Equipment List and Details

Manufacturer	Description	Model No.	Serial No.	Calibration Date	Calibration Interval
Rohde & Schwarz	Signal Analyzer	FSV40	1321.3008K39-101203-UW	2020-02-06	1 year
-	RF cable	-	-	Each time ¹	N/A

Note¹: cable included in the test set-up will be checked each time before testing.

Statement of Traceability: *BACL Corp.* attests that all of the calibrations on the equipment items listed above were traceable to NIST or to another internationally recognized National Metrology Institute (NMI), and were compliant with the latest version of A2LA policy P102 “A2LA Policy on Metrological Traceability”.

12.4 Test Environmental Conditions


Temperature:	21° C
Relative Humidity:	39 %
ATM Pressure:	102.0 KPa

The testing was performed by Allen Huang on 2020-10-26 at 5 meter chamber 3.

12.5 Test Results


Please refer to following plots.

Low Channel, 906 MHz




Date: 26.OCT.2020 10:23:13

Middle Channel, 914 MHz



Date: 26.OCT.2020 10:29:16

High Channel, 924 MHz



Date: 26 OCT 2020 10:32:22

13 Annex A (Normative) - Test Setup Photographs

Please refer to the attachment

14 Annex B (Normative) - EUT External Photographs

Please refer to the attachment

15 Annex C (Normative) - EUT Internal Photographs

Please refer to the attachment

16 Annex D (Normative) - A2LA Electrical Testing Certificate



Accredited Laboratory

A2LA has accredited

BAY AREA COMPLIANCE LABORATORIES CORP.
Sunnyvale, CA

for technical competence in the field of

Electrical Testing

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005 General requirements for the competence of testing and calibration laboratories. This laboratory also meets A2LA R222

- Specific Requirements EPA ENERGY STAR Accreditation Program. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communiqué dated April 2017).



Presented this 2nd day of October 2018.

A blue ink signature of a person's name, likely the Vice President of Accreditation Services.

Vice President, Accreditation Services
For the Accreditation Council
Certificate Number 3297.02
Valid to November 30, 2020
Revised August 31, 2020

For the tests to which this accreditation applies, please refer to the laboratory's Electrical Scope of Accreditation.

Please follow the web link below for a full ISO 17025 scope

<https://www.a2la.org/scopepdf/3297-02.pdf>

--- END OF REPORT ---