


5.5. 6dB bandwidth

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(2):

For digital modulation systems, the minimum 6 dB bandwidth shall be at least 500 kHz.

TEST CONFIGURATION



TEST PROCEDURE

1. Connect the antenna port(s) to the spectrum analyzer input.
2. Configure the spectrum analyzer as shown below (enter all losses between the transmitter output and the spectrum analyzer).
 - Center Frequency = DTS channel center frequency
 - Span=2 x DTS bandwidth
 - RBW = 100 kHz, VBW $\geq 3 \times$ RBW
 - Sweep time= auto couple
 - Detector = Peak
 - Trace mode = max hold
3. Place the radio in continuous transmit mode, allow the trace to stabilize, view the transmitter waveform on the spectrum analyzer.
4. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission, and record the pertinent measurements.

TEST MODE:


Please refer to the clause 3.3

TEST RESULTS

Passed Not Applicable

Type	Channel	6dB Bandwidth(kHz)	Limit (kHz)	Result
BT-BLE	00	694.60	≥ 500	Pass
	19	703.33		
	39	690.30		

Test plot as follows:




5.6. Restricted band

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (d):

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

TEST CONFIGURATION



TEST PROCEDURE

1. The EUT was setup and tested according to ANSI C63.10:2013 for compliance to FCC 47CFR 15.247 requirements.
2. The EUT is placed on a turn table which is 1.5 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
3. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.
4. The antenna is scanned from 1 meter to 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10:2013 on radiated measurement.
5. The receiver set as follow:
RBW=1MHz, VBW=3MHz for Peak value
RBW=1MHz, VBW=3MHz RMS detector for Average value.

TEST MODE:

Please refer to the clause 3.3

TEST RESULTS

Passed Not Applicable

Note:

- 1) Final level= Read level + Antenna Factor+ Cable Loss- Preamp Factor

BT-BLE					CH00				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin Limit (dB)	Polarization	Test value
2310.00	33.67	27.27	6.62	37.65	29.91	74.00	-44.09	Horizontal	Peak
2390.03	33.02	27.53	6.75	37.87	29.43	74.00	-44.57	Horizontal	
2310.00	33.07	27.27	6.62	37.65	29.31	74.00	-44.69	Vertical	
2390.03	32.82	27.53	6.75	37.87	29.23	74.00	-44.77	Vertical	
2310.00	27.83	27.27	6.62	37.65	24.07	54.00	-29.93	Horizontal	Average
2390.03	27.08	27.53	6.75	37.87	23.49	54.00	-30.51	Horizontal	
2310.00	26.92	27.27	6.62	37.65	23.16	54.00	-30.84	Vertical	
2390.03	26.42	27.53	6.75	37.87	22.83	54.00	-31.17	Vertical	

BT-BLE					CH39				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin Limit (dB)	Polarization	Test value
2483.50	45.34	27.85	6.83	37.87	42.15	74.00	-31.85	Horizontal	Peak
2500.00	34.50	27.90	6.84	37.87	31.37	74.00	-42.63	Horizontal	
2483.50	44.34	27.85	6.83	37.87	41.15	74.00	-32.85	Vertical	
2500.00	36.38	27.90	6.84	37.87	33.25	74.00	-40.75	Vertical	
2483.50	41.34	27.85	6.83	37.87	38.15	54.00	-15.85	Horizontal	Average
2500.00	28.62	27.90	6.84	37.87	25.49	54.00	-28.51	Horizontal	
2483.50	40.40	27.85	6.83	37.87	37.21	54.00	-16.79	Vertical	
2500.00	29.40	27.90	6.84	37.87	26.27	54.00	-27.73	Vertical	


5.7. Band edge and Spurious Emission (conducted)

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (d):

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

TEST CONFIGURATION



TEST PROCEDURE

1. Connect the antenna port(s) to the spectrum analyzer input.
2. Establish a reference level by using the following procedure

Center frequency=DTS channel center frequency
 The span = 1.5 times the DTS bandwidth.
 RBW = 100 kHz, VBW $\geq 3 \times$ RBW
 Detector = peak, Sweep time = auto couple, Trace mode = max hold
 Allow trace to fully stabilize
 Use the peak marker function to determine the maximum PSD level

Note that the channel found to contain the maximum PSD level can be used to establish the reference level.
3. Emission level measurement


Set the center frequency and span to encompass frequency range to be measured
 RBW = 100 kHz, VBW $\geq 3 \times$ RBW
 Detector = peak, Sweep time = auto couple, Trace mode = max hold
 Allow trace to fully stabilize
 Use the peak marker function to determine the maximum amplitude level.
4. Place the radio in continuous transmit mode, allow the trace to stabilize, view the transmitter waveform on the spectrum analyzer.
5. Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements specified (at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz). Report the three highest emissions relative to the limit.

TEST MODE:

Please refer to the clause 3.3

TEST RESULTS

Passed Not Applicable



5.8. Spurious Emission (radiated)


LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.209


Frequency	Limit (dBuV/m @3m)	Value
30MHz-88MHz	40.00	Quasi-peak
88MHz-216MHz	43.50	Quasi-peak
216MHz-960MHz	46.00	Quasi-peak
960MHz-1GHz	54.00	Quasi-peak
Above 1GHz	54.00	Average
	74.00	Peak

TEST CONFIGURATION


- 9KHz ~30MHz



- 30MHz ~ 1GHz



- Above 1GHz



TEST PROCEDURE

1. The EUT was setup and tested according to ANSI C63.10:2013 for compliance to FCC 47CFR 15.247 requirements.
2. The EUT is placed on a turn table which is 0.8 meter above ground for below 1GHz, and 1.5m for above 1GHz. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
3. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.
4. The antenna is scanned from 1 meter to 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10:2013 on radiated measurement.
5. Use the following spectrum analyzer settings
 - (1) Span shall be wide enough to fully capture the emission being measured;
 - (2) Below 1GHz, RBW=120KHz, VBW=300KHz, Sweep=auto, Detector function=QP, Trace=max hold;
If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
 - (3) Above 1GHz, RBW=1MHz, VBW=3MHz for Peak value
RBW=1MHz, VBW=3MHz RMS detector for Average value.

TEST MODE:

Please refer to the clause 3.3

TEST RESULTS

Passed Not Applicable


Note:


- 1) Above 1GHz Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
- 2) The emission levels of other frequencies are very lower than the limit and not show in test report.

➤ **9kHz ~ 30MHz**
The EUT was pre-scanned the frequency band (9KHz~30MHz), found the radiated level lower than the limit, so don't show on the report.

➤ **30MHz ~1000MHz**
Have pre-scan all modulation mode, found the BT-BLE mode CH39 which it was worst case, so only the worst case's data on the test report.

➤ 30MHz ~ 1GHz





➤ Above 1GHz

BT-BLE					CH00				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin Limit (dB)	Polarization	Test value
1597.40	41.07	25.01	5.56	36.72	34.92	74.00	-39.08	Vertical	Peak
3033.91	36.53	28.52	7.52	38.22	34.35	74.00	-39.65	Vertical	Peak
4797.27	42.16	31.09	9.54	36.96	45.83	74.00	-28.17	Vertical	Peak
7117.84	32.98	35.90	11.86	34.96	45.78	74.00	-28.22	Vertical	Peak
1597.40	41.86	25.01	5.56	36.72	35.71	74.00	-38.29	Horizontal	Peak
3192.37	36.65	28.58	7.71	38.20	34.74	74.00	-39.26	Horizontal	Peak
4809.50	38.94	31.09	9.55	36.93	42.65	74.00	-31.35	Horizontal	Peak
6886.15	32.56	35.66	11.71	34.90	45.03	74.00	-28.97	Horizontal	Peak

BT-BLE					CH19				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin Limit (dB)	Polarization	Test value
1593.34	43.02	24.99	5.55	36.71	36.85	74.00	-37.15	Vertical	Peak
3200.50	36.85	28.58	7.72	38.20	34.95	74.00	-39.05	Vertical	Peak
4883.52	37.28	31.14	9.59	36.73	41.28	74.00	-32.72	Vertical	Peak
7117.84	32.19	35.90	11.86	34.96	44.99	74.00	-29.01	Vertical	Peak
1541.48	49.44	24.84	5.40	36.64	43.04	74.00	-30.96	Horizontal	Peak
2124.37	43.00	26.59	6.38	37.32	38.65	74.00	-35.35	Horizontal	Peak
4883.52	40.00	31.14	9.59	36.73	44.00	74.00	-30.00	Horizontal	Peak
6235.36	33.19	34.08	11.01	35.29	42.99	74.00	-31.01	Horizontal	Peak

BT-BLE					CH39				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin Limit (dB)	Polarization	Test value
1593.34	42.80	24.99	5.55	36.71	36.63	74.00	-37.37	Vertical	Peak
3192.37	38.13	28.58	7.71	38.20	36.22	74.00	-37.78	Vertical	Peak
4958.68	37.38	31.18	9.64	36.52	41.68	74.00	-32.32	Vertical	Peak
8814.77	31.68	37.66	13.12	34.29	48.17	74.00	-25.83	Vertical	Peak
1597.40	41.27	25.01	5.56	36.72	35.12	74.00	-38.88	Horizontal	Peak
3993.90	35.22	29.48	8.77	38.11	35.36	74.00	-38.64	Horizontal	Peak
4958.68	38.04	31.18	9.64	36.52	42.34	74.00	-31.66	Horizontal	Peak
8022.46	33.00	36.72	12.35	34.53	47.54	74.00	-26.46	Horizontal	Peak

Remark:


- Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
- The peak level is lower than average limit (54dBuV/m), this data is the too weak instrument of signal is unable to test.
- The emission levels of other frequencies are very lower than the limit and not show in test report.


6. Test Setup Photos of the EUT

Conducted Emission (AC Mains)



Radiated Emission





7. External and Internal Photos of the EUT

External Photos

