## Table of product differences

Model	Product picture	Intended use and environment (ambient temperature, altitude, altitude)	Electrical structure (is it the same)							same) (at 1	structure	Software (where software is included, applicable)
			power supply mode	Rated input (volt age, power or curre nt)	Switch power supply, label manufact urer model There are several power supplies	PCB main board key/control panel display (size)	motor	extern al interf ace	The shell openin g	Install ation mode (portab le, fixed, mobile, permane nt install ation)	Enclosure size (length * width * height)	Parameter measurement or setting :(treatment parameter setting or measurement measurement software)  Human-machine interface :(software related to operating interface or other functional aspects)
Telli BP01	BO THE	The blood pressure monitor is intended to measure the systolic pressure, diastolic blood pressure and pulse rate for people over 12years old by using a non-invasive technique at home or in the hospital.	18650 lithium battery	5V/1A	N/A	PCB:000-85E00 00-0000 V00  The three keys (I/O MEM SET) Display Screen size:79*87mm ( display area) LCD size: 81.8*91.9mm	3.7V Motor	Type-C charge couple	5.0mm CUFF connec tor	moveabl e	135*95*52 . 5mm	A key to start  Queriable memory  Configurable time  Set alarm clock  Voice switch can be set  Erasable memory  Available data upload

.

U85E	BB BB W	identical	identic al	ident ical	N/A	identical	iden tical	identi cal	ide ntical	identic al	identical	identical
brief descri	Power supply mode (dry basupply/isolation transform	ttery; Adapter + ;	lithium batt	ery; Buil	t-in power	supply, whether	there is	s lithium	battery o	or other ba	ttery power su	upply; No switching power
ption	identical											
系列内 主测型 号的选 择	principle of selecting the ma	in test model (othe	er cases shou	ıld be neg	otiated with	HTW personnel	):TelliBP(	)1 is the p	rimary tes	t model		

除 后面括号指明的情况 外,预期用途、电源电路板 **必须相同** 通用标准 才可划为同一系列 (预期用途方面:对于监护类产品可监护的参数可以有所删减。可监测参数多的型号,可以 覆盖监测参数少的型号。)

患者应用电路 不同: 专用标准 不可划分为同一系列

患者应用电路 相同,软件-- 参数测量或设置方面 相同,但 仅 人机界面 方面 不同: 专用标准 可划分为同一系列。

对于各型号之间,有多个 比较项目 都存在差异的,不建议 划分到同一系列,而建议 分别测试、分别出测试报告 比较合适。

如果依照以上原则,还无法确定是否可划分为同一系列的话,则请将上表信息发至HTW 咨询。

X \$117,95