



## ANT-W63-IPW1-NP

### WiFi 6 Outdoor Whip Antenna

The Linx ANT-W63-IPW1-NP antenna is an outdoor IP67-rated dipole antenna designed for superior performance in the 2.4 GHz, 5 GHz and 6 GHz bands supporting both WiFi 6 and WiFi 6E.

The ANT-W63-IPW1-NP provides a ground plane independent dipole antenna solution which mounts to metallic and non-metallic surfaces. The antenna housing is UV stabilized (ASA) and connects using an N plug (male pin) connector.

#### FEATURES

- Performance at 5.15 GHz to 5.85 GHz
  - VSWR:  $\leq 2.0$
  - Peak Gain: 8.7 dBi
  - Efficiency: 82%
- Performance at 5.925 GHz to 7.125 GHz
  - VSWR:  $\leq 2.3$
  - Peak Gain: 5.5 dBi
  - Efficiency: 72%
- Ground plane independent dipole antenna
- Compact, low-profile
- Enhanced heat and chemical resistant UV stabilized Luran® S 778T (ASA) antenna housing material
- IP67 rated
- N plug (male pin) connector

#### APPLICATIONS

- WiFi/WLAN coverage
  - WiFi 6E (802.11ax)
  - WiFi 6 (802.11ax)
  - WiFi 5 (802.11ac)
  - WiFi 4 (802.11n)
  - 802.11b/g
- 2.4 GHz ISM applications
  - Bluetooth®
  - ZigBee®
- U-NII bands 1-8
- Internet of Things (IoT) devices
- Smart Home networking
- Sensing and remote monitoring

#### ORDERING INFORMATION

Part Number	Description
ANT-W63-IPW1-NP	WiFi 6 outdoor whip antenna with N plug (male pin) connector

Available from Linx Technologies and select distributors and representatives.

## ELECTRICAL SPECIFICATIONS

Parameter	ISM/WiFi	WiFi/U-NII 1-3	WiFi 6E
Frequency Range	2400 MHz to 2485 MHz	5150 MHz to 5850 MHz	5925 MHz to 7125 MHz
VSWR (max)	4.1	2.0	2.3
Peak Gain (dBi)	3.2	8.7	5.5
Average Gain (dBi)	-2.2	-1.1	-1.8
Efficiency (%)	64	82	72
Impedance		50 Ω	
Wavelength		1/2-wave	
Electrical Type		Dipole	
Polarization		Linear	
Radiation		Omnidirectional	
Max Power		2 W	

Electrical specifications and plots measured with the antenna in a free space orientation.

## MECHANICAL SPECIFICATIONS

Parameter	Value
Connection	N plug (male pin)
Connector Torque Recommended/Maximum	5 Nm/ 15 Nm
Operating Temperature Range	-40 °C to +70 °C
Ingress Protection Rating (IP)	IP67 rated
Antenna Color	White
Weight	76.1 g (2.68 oz)
Dimensions	178.0 mm x Ø25.0 mm (7.00 in x Ø0.98 in)

## PRODUCT DIMENSIONS

Figure 1 provides dimensions of the ANT-W63-IPW1-NP




Figure 1. ANT-W63-IPW1-NP Antenna Dimensions

---

## PACKAGING INFORMATION


The ANT-W63-IPW1-NP antenna is packaged in a clear plastic bag. Distribution channels may offer alternative packaging options.

## IP (INGRESS PROTECTION) RATING

An ingress protection rating (IP rating) refers to the capability of a device to withstand the ingress of dust and/or water under specified conditions. IP rating is typically reserved for marketable product (device) rather than constituent components because design and assembly may affect performance of the device under testing. IP-rated antennas are designed to support the specified level of ingress protection and may be tested in a standalone configuration, however IP testing should be performed on the complete end product to ensure desired performance.

## ANTENNA ORIENTATION

The ANT-W63-IPW1-NP antenna is characterized in two antenna orientations as shown in Figure 2. The antenna in a free space orientation characterizes use of an antenna attached to an enclosure-mounted connector which is connected by cable to a printed circuit board. Although the antenna is a dipole not requiring a ground plane for function, characterization at the center of the ground plane (300 mm x 300 mm) provides insight into antenna performance when attached directly to a connector on a metal enclosure. The two orientations represent the most common end-product use cases.



ANT-W63-IPW1-NP in Free Space

ANT-W63-IPW1-NP at Center of 300 mm x 300 mm Ground Plane

Figure 2. ANT-5GW-IPW1-NP Test Orientations

---

## FREE SPACE, NO GROUND PLANE

The charts on the following pages represent data taken with the antenna oriented in free space as shown in Figure 3.



Figure 3. ANT-5GW-IPW1-NP No Ground Plane (Free Space)

## VSWR

Figure 4 provides the voltage standing wave ratio (VSWR) across the antenna bandwidth. VSWR describes the power reflected from the antenna back to the radio. A lower VSWR value indicates better antenna performance at a given frequency. Reflected power is also shown on the right-side vertical axis as a gauge of the percentage of transmitter power reflected back from the antenna.




Figure 4. ANT-W63-IPW1-NP Antenna VSWR, Free Space

## RETURN LOSS

Return loss (Figure 5), represents the loss in power at the antenna due to reflected signals. Like VSWR, a lower return loss value indicates better antenna performance at a given frequency




Figure 5. ANT-W63-IPW1-NP Antenna Return Loss, Free Space

## PEAK GAIN

The peak gain across the antenna bandwidth is shown in Figure 6. Peak gain represents the maximum antenna input power concentration across 3-dimensional space, and therefore peak performance, at a given frequency, but does not consider any directionality in the gain pattern.




Figure 6. ANT-W63-IPW1-NP Antenna Peak Gain, Free Space

## AVERAGE GAIN

Average gain (Figure 7), is the average of all antenna gain in 3-dimensional space at each frequency, providing an indication of overall performance without expressing antenna directionality.




Figure 7. ANT-W63-IPW1-NP Antenna Average Gain, Free Space

## RADIATION EFFICIENCY

Radiation efficiency (Figure 8), shows the ratio of power delivered to the antenna relative to the power radiated at the antenna, expressed as a percentage, where a higher percentage indicates better performance at a given frequency.





Figure 8. ANT-W63-IPW1-NP Antenna Radiation Efficiency, Free Space


## RADIATION PATTERNS

Radiation patterns provide information about the directionality and 3-dimensional gain performance of the antenna by plotting gain at specific frequencies in three orthogonal planes. Antenna radiation patterns for a free space orientation are shown in Figure 9 using polar plots covering 360 degrees. The antenna graphic at the top of the page provides reference to the plane of the column of plots below it. Note: when viewed with typical PDF viewing software, zooming into radiation patterns is possible to reveal fine detail.

## RADIATION PATTERNS - FREE SPACE



XZ-Plane Gain




YZ-Plane Gain




XZ-Plane Gain


## 2400 MHZ TO 2485 MHZ (2450 MHZ)



XZ-Plane Gain




YZ-Plane Gain



XY-Plane Gain

---

## 5150 MHZ TO 5850 MHZ (5500 MHZ)



## RADIATION PATTERNS - FREE SPACE

### 5925 MHZ TO 7125 MHZ (6500 MHZ)




Figure 9. Radiation Patterns for ANT-W63-IPW1-NP Antenna, in Free Space

## CENTER OF GROUND PLANE

The charts on the following pages represent data taken with the antenna oriented at the center of the ground plane as shown in Figure 10.



Figure 10. ANT-5GW-IPW1-NP, at Center of Ground Plane

## VSWR

Figure 11 provides the voltage standing wave ratio (VSWR) across the antenna bandwidth. VSWR describes the power reflected from the antenna back to the radio. A lower VSWR value indicates better antenna performance at a given frequency. Reflected power is also shown on the right-side vertical axis as a gauge of the percentage of transmitter power reflected back from the antenna.




Figure 11. ANT-W63-IPW1-NP Antenna VSWR, at Center of Ground Plane

## RETURN LOSS

Return loss (Figure 12), represents the loss in power at the antenna due to reflected signals. Like VSWR, a lower return loss value indicates better antenna performance at a given frequency.




Figure 12. ANT-W63-IPW1-NP Antenna Return Loss, at Center of Ground Plane

## PEAK GAIN

The peak gain across the antenna bandwidth is shown in Figure 13. Peak gain represents the maximum antenna input power concentration across 3-dimensional space, and therefore peak performance, at a given frequency, but does not consider any directionality in the gain pattern.




Figure 13. ANT-W63-IPW1-NP Antenna Peak Gain, at Center of Ground Plane

## AVERAGE GAIN

Average gain (Figure 14), is the average of all antenna gain in 3-dimensional space at each frequency, providing an indication of overall performance without expressing antenna directionality.




Figure 14. ANT-W63-IPW1-NP Antenna Average Gain, at Center of Ground Plane

## RADIATION EFFICIENCY

Radiation efficiency (Figure 15), shows the ratio of power delivered to the antenna relative to the power radiated at the antenna, expressed as a percentage, where a higher percentage indicates better performance at a given frequency.





Figure 15. ANT-W63-IPW1-NP Antenna Radiation Efficiency, at Center of Ground Plane

## RADIATION PATTERNS

Radiation patterns provide information about the directionality and 3-dimensional gain performance of the antenna by plotting gain at specific frequencies in three orthogonal planes. Antenna radiation patterns for an orientation at the center of the ground plane are shown in Figure 16 using polar plots covering 360 degrees. The antenna graphic at the top of the page provides reference to the plane of the column of plots below it. Note: when viewed with typical PDF viewing software, zooming into radiation patterns is possible to reveal fine detail.


## RADIATION PATTERNS - CENTER OF GROUND PLANE



XZ-Plane Gain






YZ-Plane Gain




XZ-Plane Gain

## 2400 MHZ TO 2485 MHZ (2450 MHZ)



## 5150 MHZ TO 5850 MHZ (5500 MHZ)



## RADIATION PATTERNS - CENTER OF GROUND PLANE

### 5925 MHZ TO 7125 MHZ (6500 MHZ)




Figure 16. Radiation Patterns for ANT-W63-IPW1-NP Antenna, at Center of Ground Plane

---

## TE TECHNICAL SUPPORT CENTER

USA:	+1 (800) 522-6752
Canada:	+1 (905) 475-6222
Mexico:	+52 (0) 55-1106-0800
Latin/S. America:	+54 (0) 11-4733-2200
Germany:	+49 (0) 6251-133-1999
UK:	+44 (0) 800-267666
France:	+33 (0) 1-3420-8686
Netherlands:	+31 (0) 73-6246-999
China:	+86 (0) 400-820-6015

### te.com

TE Connectivity, TE, TE connectivity (logo), Linx and Linx Technologies are trademarks owned or licensed by the TE Connectivity Ltd. family of companies. All other logos, products and/or company names referred to herein might be trademarks of their respective owners.

The information given herein, including drawings, illustrations and schematics which are intended for illustration purposes only, is believed to be reliable. However, TE Connectivity makes no warranties as to its accuracy or completeness and disclaims any liability in connection with its use. TE Connectivity's obligations shall only be as set forth in TE Connectivity's Standard Terms and Conditions of Sale for this product and in no case will TE Connectivity be liable for any incidental, indirect or consequential damages arising out of the sale, resale, use or misuse of the product. Users of TE Connectivity products should make their own evaluation to determine the suitability of each such product for the specific application.

TE Connectivity warrants to the original end user customer of its products that its products are free from defects in material and workmanship. Subject to conditions and limitations TE Connectivity will, at its option, either repair or replace any part of its products that prove defective because of improper workmanship or materials. This limited warranty is in force for the useful lifetime of the original end product into which the TE Connectivity product is installed. Useful lifetime of the original end product may vary but is not warranted to exceed one (1) year from the original date of the end product purchase.

©2022 TE Connectivity. All Rights Reserved.

10/22 Original

---

DATA AND DEVICES / ANT-W63-IPW1-NP

Linx  
TECHNOLOGIES  
is now part of

TE  
connectivity