

RF TEST REPORT



Report No.: 17070084-FCC-R3 V1

Supersede Report No.: N/A

Applicant	Global Regency Ltd.	
Product Name	Tablet PC	
Model No.	QA863	
Serial No.	N/A	
Test Standard	FCC Part 15.247: 2016, ANSI C63.10: 2013	
Test Date	February 14 to March 09, 2017	
Issue Date	March 16, 2017	
Test Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail	
Equipment complied with the specification		<input checked="" type="checkbox"/>
Equipment did not comply with the specification		<input type="checkbox"/>
Loren Luo	David Huang	
Loren Luo Test Engineer	David Huang Checked By	
This test report may be reproduced in full only Test result presented in this test report is applicable to the tested sample only		

Issued by:

SIEMIC (SHENZHEN-CHINA) LABORATORIES

Zone A, Floor 1, Building 2 Wan Ye Long Technology Park

South Side of Zhoushi Road, Bao'an District, Shenzhen, Guangdong China 518108

Phone: +86 0755 2601 4629801 Email: China@siemic.com.cn

Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

Accreditations for Conformity Assessment

Country/Region	Scope
USA	EMC, RF/Wireless, SAR, Telecom
Canada	EMC, RF/Wireless, SAR, Telecom
Taiwan	EMC, RF, Telecom, SAR, Safety
Hong Kong	RF/Wireless, SAR, Telecom
Australia	EMC, RF, Telecom, SAR, Safety
Korea	EMI, EMS, RF, SAR, Telecom, Safety
Japan	EMI, RF/Wireless, SAR, Telecom
Singapore	EMC, RF, SAR, Telecom
Europe	EMC, RF, SAR, Telecom, Safety

Test Report No.	17070084-FCC-R3 V1
Page	3 of 57

This page has been left blank intentionally.

CONTENTS

1. REPORT REVISION HISTORY	5
2. CUSTOMER INFORMATION	5
3. TEST SITE INFORMATION.....	5
4. EQUIPMENT UNDER TEST (EUT) INFORMATION	6
5. TEST SUMMARY	8
6. MEASUREMENTS, EXAMINATION AND DERIVED RESULTS	9
6.1 ANTENNA REQUIREMENT.....	9
6.2 DTS (6 DB&20 DB) CHANNEL BANDWIDTH.....	10
6.3 MAXIMUM OUTPUT POWER	16
6.4 POWER SPECTRAL DENSITY.....	20
6.5 BAND-EDGE & UNWANTED EMISSIONS INTO RESTRICTED FREQUENCY BANDS	24
6.6 AC POWER LINE CONDUCTED EMISSIONS.....	30
6.7 RADIATED SPURIOUS EMISSIONS & RESTRICTED BAND	36
ANNEX A. TEST INSTRUMENT.....	42
ANNEX B. EUT AND TEST SETUP PHOTOGRAPHS.....	43
ANNEX C. TEST SETUP AND SUPPORTING EQUIPMENT.....	52
ANNEX D. USER MANUAL / BLOCK DIAGRAM / SCHEMATICS / PARTLIST	56
ANNEX E. DECLARATION OF SIMILARITY	57

1. Report Revision History

Report No.	Report Version	Description	Issue Date
17070084-FCC-R3	NONE	Original	March 10, 2017
17070084-FCC-R3 V1	V1	Adjust photos	March 16, 2017

2. Customer information

Applicant Name	Global Regency Ltd.
Applicant Add	20F,Tower A,Wenjin Plaza,Tianbei Rd1,Luohu Dist.,Shenzhen,China
Manufacturer	Global Regency Ltd.
Manufacturer Add	20F,Tower A,Wenjin Plaza,Tianbei Rd1,Luohu Dist.,Shenzhen,China

3. Test site information

Lab performing tests	SIEMIC (Shenzhen-China) LABORATORIES
Lab Address	Zone A, Floor 1, Building 2 Wan Ye Long Technology Park South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108
FCC Test Site No.	718246
IC Test Site No.	4842E-1
Test Software	Radiated Emission Program-To Shenzhen v2.0

4. Equipment under Test (EUT) Information

Description of EUT:	Tablet PC
Main Model:	QA863
Serial Model:	N/A
Date EUT received:	February 13, 2017
Test Date(s):	February 14 to March 09, 2017
Equipment Category :	DTS
Antenna Gain:	Bluetooth/WIFI/BLE:2.67dBi
Antenna Type:	PIFA antenna
Type of Modulation:	802.11b/g/n: DSSS, OFDM Bluetooth: GFSK, π /4DQPSK, 8DPSK BLE: GFSK
RF Operating Frequency (ies):	WIFI: 802.11b/g/n(20M): 2412-2462 MHz WIFI: 802.11n(40M): 2422-2452 MHz Bluetooth& BLE: 2402-2480 MHz
Max. Output Power:	802.11b: 16.01dBm 802.11g: 14.10dBm 802.11n(20M): 12.89dBm 802.11n(40M): 12.04dBm
Number of Channels:	WIFI :802.11b/g/n(20M): 11CH WIFI :802.11n(40M): 7CH Bluetooth: 79CH BLE: 40CH

Test Report No.	17070084-FCC-R3 V1
Page	7 of 57

Port: USB Port, Earphone Port

Adapter:

Model: JML-0500200-LW

Input Power: Input: AC100-240V~50/60Hz,MAX 0.3A

Output: DC 5.0V-2.0A

Battery:

Spec: 3.8V,5300mAh,20.14Wh

Trade Name : Smart Communications

FCC ID: 2AK5R-QA863

5. Test Summary

The product was tested in accordance with the following specifications.

All testing has been performed according to below product classification:

FCC Rules	Description of Test	Result
§15.203	Antenna Requirement	Compliance
§15.247 (a)(2)	DTS (6 dB&20 dB) CHANNEL BANDWIDTH	Compliance
§15.247(b)(3)	Conducted Maximum Output Power	Compliance
§15.247(e)	Power Spectral Density	Compliance
§15.247(d)	Band-Edge & Unwanted Emissions into Restricted Frequency Bands	Compliance
§15.207 (a),	AC Power Line Conducted Emissions	Compliance
§15.205, §15.209, §15.247(d)	Radiated Emissions & Unwanted Emissions into Restricted Frequency Bands	Compliance

Measurement Uncertainty

Emissions		
Test Item	Description	Uncertainty
Band-Edge & Unwanted Emissions into Restricted Frequency Bands and Radiated Emissions & Unwanted Emissions into Restricted Frequency Bands	Confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2 (for EUTs < 0.5m X 0.5m X 0.5m)	+5.6dB/-4.5dB
-	-	-

6. Measurements, Examination And Derived Results

6.1 Antenna Requirement

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT has 1 antenna:


A permanently attached PIFA antenna for Bluetooth/WIFI/BLE, the gain is 2.67dBi for Bluetooth/WIFI/BLE.

The antenna meets up with the ANTENNA REQUIREMENT.

Result: Compliance.

6.2 DTS (6 dB&20 dB) Channel Bandwidth

Temperature	22 °C
Relative Humidity	54%
Atmospheric Pressure	1021mbar
Test date :	February 21, 2017
Tested By :	Loren Luo

Spec	Item	Requirement	Applicable
§ 15.247(a)(2)	a)	6dB BW \geq 500kHz; 20dB BW \geq 500kHz;	<input checked="" type="checkbox"/>
RSS Gen(4.6.1)	b)	99% BW: For FCC reference only; required by IC.	<input checked="" type="checkbox"/>
Test Setup		 Spectrum Analyzer EUT	
Test Procedure		<p>558074 D01 DTS MEAS Guidance v03r03, 8.1 DTS bandwidth</p> <p><u>6dB bandwidth</u></p> <ol style="list-style-type: none"> Set RBW = 100 kHz. Set the video bandwidth (VBW) \geq 3 \times RBW. Detector = Peak. Trace mode = max hold. Sweep = auto couple. Allow the trace to stabilize. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission. <p><u>20dB bandwidth</u></p> <p>C63.10 Occupied Bandwidth (OBW=20dB bandwidth)</p> <ol style="list-style-type: none"> Set RBW = 1%-5% OBW. Set the video bandwidth (VBW) \geq 3 x RBW. Set the span range between 2 times and 5 times of the OBW. Sweep time=Auto, Detector=PK, Trace=Max hold. Once the reference level is established, the equipment is conditioned with typical modulating signals to produce the worst- 	

	case (i.e., the widest) bandwidth. Unless otherwise specified for an unlicensed wireless device, measure the bandwidth at the 20 dB levels with respect to the reference level.
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data Yes N/A


Test Plot Yes (See below) N/A



Measurement result

Test mode	CH	Freq (MHz)	6dB Bandwidth (MHz)	20dB Bandwidth (MHz)	Limit (MHz)
802.11b	Low	2412	7.594	15.71	≥ 0.5
	Mid	2437	8.039	15.23	≥ 0.5
	High	2462	8.067	15.30	≥ 0.5
802.11g	Low	2412	16.39	19.41	≥ 0.5
	Mid	2437	16.42	19.27	≥ 0.5
	High	2462	16.38	19.47	≥ 0.5
802.11n (20M)	Low	2412	17.60	19.79	≥ 0.5
	Mid	2437	17.59	19.88	≥ 0.5
	High	2462	17.56	19.83	≥ 0.5
802.11n (40M)	Low	2422	35.60	39.02	≥ 0.5
	Mid	2437	35.96	38.67	≥ 0.5
	High	2452	35.77	39.57	≥ 0.5

Test Plots



6dB Bandwidth measurement result







802.11n20 6dB Bandwidth - Low CH 2412

802.11n20 6dB Bandwidth - Mid CH 2437



802.11n20 6dB Bandwidth - High CH 2462


802.11n40 6dB Bandwidth - Low CH 2422





802.11n40 6dB Bandwidth - Mid CH 2437

802.11n40 6dB Bandwidth - High CH 2452



20 dB Bandwidth measurement result







802.11n20 20dB Bandwidth - Low CH 2412

802.11n20 20dB Bandwidth - Mid CH 2437



802.11n20 20dB Bandwidth - High CH 2462

802.11n40 20dB Bandwidth - Low CH 2422




802.11n40 20dB Bandwidth - Mid CH 2437

802.11n40 20dB Bandwidth - High CH 2452

6.3 Maximum Output Power

Temperature	22 °C
Relative Humidity	54%
Atmospheric Pressure	1021mbar
Test date :	February 21, 2017
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(b) (3), RSS210 (A8.4)	a)	FHSS in 2400-2483.5MHz with \geq 75 channels: \leq 1 Watt	<input type="checkbox"/>
	b)	FHSS in 5725-5850MHz: \leq 1 Watt	<input type="checkbox"/>
	c)	For all other FHSS in the 2400-2483.5MHz band: \leq 0.125 Watt.	<input type="checkbox"/>
	d)	FHSS in 902-928MHz with \geq 50 channels: \leq 1 Watt	<input type="checkbox"/>
	e)	FHSS in 902-928MHz with \geq 25 & < 50 channels: \leq 0.25 Watt	<input type="checkbox"/>
	f)	DTS in 902-928MHz, 2400-2483.5MHz: \leq 1 Watt	<input checked="" type="checkbox"/>
Test Setup		 Spectrum Analyzer EUT	
Test Procedure		<p>558074 D01 DTS MEAS Guidance v03r03, 9.1.2 Integrated band power method</p> <p>Maximum output power measurement procedure</p> <ul style="list-style-type: none"> - a) Set span to at least 1.5 times the OBW. - b) Set RBW = 1-5% of the OBW, not to exceed 1 MHz. - c) Set VBW \geq 3 x RBW. - d) Number of points in sweep \geq 2 \times span / RBW. (This gives bin-to-bin spacing \leq RBW/2, so that narrowband signals are not lost between frequency bins.) - e) Sweep time = auto. - f) Detector = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode. - g) If transmit duty cycle $<$ 98 %, use a sweep trigger with the level set to enable triggering only on full power pulses. The transmitter shall operate at maximum 	

	<p>power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no off intervals) or at duty cycle $\geq 98\%$, and if each transmission is entirely at the maximum power control level, then the trigger shall be set to “ free run” .</p> <ul style="list-style-type: none"> - h) Trace average at least 100 traces in power averaging (i.e., RMS) mode. - i) Compute power by integrating the spectrum across the OBW of the signal using the instrument’ s band power measurement function, with band limits set equal to the OBW band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at intervals equal to the RBW extending across the entire OBW of the spectrum.
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data Yes N/A


Test Plot Yes (See below) N/A



Output Power measurement result

Type	Test mode	CH	Frequency (MHz)	Conducted Power (dBm)	Limit (dBm)	Result
Output power	802.11b	Low	2412	15.96	30	Pass
		Mid	2437	16.01	30	Pass
		High	2462	15.90	30	Pass
	802.11g	Low	2412	14.07	30	Pass
		Mid	2437	14.06	30	Pass
		High	2462	14.10	30	Pass
	802.11n (20M)	Low	2412	12.89	30	Pass
		Mid	2437	12.26	30	Pass
		High	2462	12.57	30	Pass
	802.11n (40M)	Low	2422	11.30	30	Pass
		Mid	2437	11.48	30	Pass
		High	2452	12.04	30	Pass


Test Plots

The Average Power






802.11n20 - AV Output power - Low CH 2412




802.11n20 - AV Output power - Mid CH 2437



802.11n20 - AV Output power - High CH 2462



802.11n40 - AV Output power - Low CH 2422



802.11n40 - AV Output power - Mid CH 2437

802.11n40 - AV Output power - High CH 2452

6.4 Power Spectral Density

Temperature	22 °C
Relative Humidity	54%
Atmospheric Pressure	1021mbar
Test date :	February 21, 2017
Tested By :	Loren Luo


Test Data Yes N/A
 Test Plot Yes (See below) N/A



Power Spectral Density measurement result

Type	Test mode	CH	Freq (MHz)	PSD	Limit (dBm)	Result
				(dBm)		
PSD	802.11b	Low	2412	-7.581	8	Pass
		Mid	2437	-7.908	8	Pass
		High	2462	-6.850	8	Pass
	802.11g	Low	2412	-14.603	8	Pass
		Mid	2437	-13.222	8	Pass
		High	2462	-13.291	8	Pass
	802.11n (20M)	Low	2412	-15.822	8	Pass
		Mid	2437	-14.993	8	Pass
		High	2462	-15.070	8	Pass
	802.11n (40M)	Low	2422	-19.664	8	Pass
		Mid	2437	-17.883	8	Pass
		High	2452	-18.272	8	Pass

Test Plots


Power Spectral Density measurement result







PSD - Low CH 2412 - 802.11n20

PSD - Mid CH 2437 – 802.11n20



PSD - High CH 2472 - 802.11n20

PSD - Low CH 2422 - 802.11n40




PSD - Mid CH 2437 – 802.11n40

PSD - High CH 2452 - 802.11n40

6.5 Band-Edge & Unwanted Emissions into Restricted Frequency Bands

Temperature	22 °C
Relative Humidity	54%
Atmospheric Pressure	1021mbar
Test date :	February 21, 2017
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(d)	a)	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.	<input checked="" type="checkbox"/>
Test Setup	 <p>The diagram illustrates the test setup. An 'EUT & Support Units' is positioned on a 'Turn Table' at a height of '0.8/1.5m' from the 'Ground Plane'. A '3m' horizontal distance separates the EUT from an 'Ant. Tower'. The 'Ant. Tower' is mounted on a vertical post and is connected to a 'Test Receiver' which is shown with a waveform display. The 'Ant. Tower' is labeled '1-4m Variable'.</p>		
Test Procedure	<p>Radiated Method Only</p> <ul style="list-style-type: none"> - 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator. - 2. Position the EUT without connection to measurement instrument. Put it on the Rotated table and turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range. 		


	<ul style="list-style-type: none"> - 3. First, set both RBW and VBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100kHz bandwidth from band edge, check the emission of EUT, if pass then set Spectrum Analyzer as below: <ul style="list-style-type: none"> a. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasiy Peak detection at frequency below 1GHz. b. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz with Peak detection for Peak measurement at frequency above 1GHz. c. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz with Peak detection for Average Measurement as below at frequency above 1GHz. - 4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency. - 5. Repeat above procedures until all measured frequencies were complete.
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail




Test Data Yes N/A




Test Plot Yes (See below) N/A



Test Plots

Band Edge measurement result



 <p>* RBW 1 MHz * Att 5 dB Ref 102.0 dBμV * VBW 3 MHz SWT 2.5ms</p> <p>M2[1] 45.55 dBμV 2.390000000 GHz</p> <p>1Pk Max 90 dBμV Line Limit 74 80 dBμV 70 dBμV 60 dBμV 50 dBμV 40 dBμV 30 dBμV 20 dBμV 10 dBμV</p> <p>Tdf CF 2.39 GHz Span 80.0 MHz</p>	 <p>* RBW 1 MHz * Att 5 dB Ref 102.0 dBμV * VBW 3 MHz SWT 2.5ms</p> <p>M1[1] 48.89 dBμV 2.483660000 GHz</p> <p>1Pk Max 90 dBμV Line Limit 74 80 dBμV 70 dBμV 60 dBμV 50 dBμV 40 dBμV 30 dBμV 20 dBμV 10 dBμV</p> <p>Tdf CF 2.4835 GHz Span 80.0 MHz</p>
<p>Date: 21.FEB.2017 15:46:40</p> <p>Band Edge, Left Side (Peak) - 802.11g</p> <p>Note: F1 is frequency 2390MHz; F2 is frequency 2400MHz</p>	<p>Date: 21.FEB.2017 15:42:18</p> <p>Band Edge, Right Side (Peak) - 802.11g</p> <p>Note: F1 is frequency 2483.5MHz</p>
 <p>* RBW 1 MHz * Att 5 dB Ref 102.0 dBμV * VBW 10 Hz SWT 16s</p> <p>M2[1] 27.87 dBμV 2.390000000 GHz</p> <p>1Pk Max 90 dBμV Line Limit 54 80 dBμV 70 dBμV 60 dBμV 50 dBμV 40 dBμV 30 dBμV 20 dBμV 10 dBμV</p> <p>Tdf CF 2.39 GHz Span 80.0 MHz</p>	<p>Note: (no need if PK value less than the AV limit)</p>
<p>Date: 21.FEB.2017 15:47:20</p> <p>Band Edge, Left Side (Average) - 802.11g</p> <p>Note: F1 is frequency 2390MHz; F2 is frequency 2400MHz</p>	<p>Band Edge, Right Side (Average) - 802.11g</p> <p>Note: F1 is frequency 2483.5MHz</p>


 <p>* RBW 1 MHz * Att 5 dB Ref 102.0 dBμV * VBW 3 MHz SWT 2.5ms</p> <p>M2[1] 43.59 dBμV 2.389840000 GHz</p> <p>1Pk Max 90 dBμV Line Limit 74 80 dBμV 70 dBμV 60 dBμV 50 dBμV 40 dBμV 30 dBμV 20 dBμV 10 dBμV</p> <p>Tdf CF 2.39 GHz Span 80.0 MHz</p>	 <p>* RBW 1 MHz * Att 5 dB Ref 102.0 dBμV * VBW 3 MHz SWT 2.5ms</p> <p>M1[1] 48.03 dBμV 2.483500000 GHz</p> <p>1Pk Max 90 dBμV Line Limit 74 80 dBμV 70 dBμV 60 dBμV 50 dBμV 40 dBμV 30 dBμV 20 dBμV 10 dBμV</p> <p>Tdf CF 2.4835 GHz Span 80.0 MHz</p>
<p>Date: 21.FEB.2017 15:53:11</p> <p>Band Edge, Left Side (Peak) - 802.11n20</p> <p>Note: F1 is frequency 2390MHz; F2 is frequency 2400MHz</p>	<p>Date: 21.FEB.2017 15:58:09</p> <p>Band Edge, Right Side (Peak) - 802.11n20</p> <p>Note: F1 is frequency 2483.5MHz</p>
 <p>* RBW 1 MHz * Att 5 dB Ref 102.0 dBμV * VBW 10 Hz SWT 16s</p> <p>M2[1] 28.34 dBμV 2.389840000 GHz</p> <p>1Pk Max 90 dBμV Line Limit 54 80 dBμV 70 dBμV 60 dBμV 50 dBμV 40 dBμV 30 dBμV 20 dBμV 10 dBμV</p> <p>Tdf CF 2.39 GHz Span 80.0 MHz</p>	<p>Note: (no need if PK value less than the AV limit)</p>
<p>Date: 21.FEB.2017 15:54:11</p> <p>Band Edge, Left Side (Average) - 802.11n20</p> <p>Note: F1 is frequency 2390MHz; F2 is frequency 2400MHz</p>	<p>Band Edge, Right Side (Average) - 802.11n20</p> <p>Note: F1 is frequency 2483.5MHz</p>

 <p>Plot 1: Left Side (Peak) - 802.11n40</p> <p>CF 2.39 GHz, Span 120.0 MHz</p> <p>1Pk Max: 52.64 dBμV, 2.386170000 GHz</p> <p>1Tdf: 52.36 dBμV, 2.400000000 GHz</p> <p>Limit Check: Line Limit 74, PASS</p> <p>Notes: F1 (2390 MHz), F2 (2400 MHz)</p>	 <p>Plot 2: Right Side (Peak) - 802.11n40</p> <p>CF 2.4835 GHz, Span 120.0 MHz</p> <p>1Pk Max: 47.84 dBμV, 2.485900000 GHz</p> <p>1Tdf: 47.74 dBμV, 2.483500000 GHz</p> <p>Limit Check: Line Limit 74, PASS</p> <p>Notes: F1 (2483.5 MHz)</p>
<p>Date: 21.FEB.2017 16:23:18</p> <p>Band Edge, Left Side (Peak) - 802.11n40</p> <p>Note: F1 is frequency 2390MHz; F2 is frequency 2400MHz</p> <p>Note: (no need if PK value less than the AV limit)</p>	<p>Date: 21.FEB.2017 16:28:01</p> <p>Band Edge, Right Side (Peak) - 802.11n40</p> <p>Note: F1 is frequency 2483.5MHz</p> <p>Note: (no need if PK value less than the AV limit)</p>
<p>Band Edge, Left Side (Average) - 802.11n40</p> <p>Note: F1 is frequency 2390MHz; F2 is frequency 2400MHz</p>	<p>Band Edge, Right Side (Average) - 802.11n40</p> <p>Note: F1 is frequency 2483.5MHz</p>

6.6 AC Power Line Conducted Emissions

Temperature	22 °C
Relative Humidity	54%
Atmospheric Pressure	1021mbar
Test date :	February 21, 2017
Tested By :	Loren Luo

Requirement(s):


Spec	Item	Requirement	Applicable														
47CFR§15. 207, RSS210 (A8.1)	a)	<p>For Low-power radio-frequency devices that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 [mu] H/50 ohms line impedance stabilization network (LISN). The lower limit applies at the boundary between the frequencies ranges.</p> <table border="1"> <thead> <tr> <th rowspan="2">Frequency ranges (MHz)</th> <th colspan="2">Limit (dBμV)</th> </tr> <tr> <th>QP</th> <th>Average</th> </tr> </thead> <tbody> <tr> <td>0.15 ~ 0.5</td> <td>66 – 56</td> <td>56 – 46</td> </tr> <tr> <td>0.5 ~ 5</td> <td>56</td> <td>46</td> </tr> <tr> <td>5 ~ 30</td> <td>60</td> <td>50</td> </tr> </tbody> </table>	Frequency ranges (MHz)	Limit (dB μ V)		QP	Average	0.15 ~ 0.5	66 – 56	56 – 46	0.5 ~ 5	56	46	5 ~ 30	60	50	<input checked="" type="checkbox"/>
Frequency ranges (MHz)	Limit (dB μ V)																
	QP	Average															
0.15 ~ 0.5	66 – 56	56 – 46															
0.5 ~ 5	56	46															
5 ~ 30	60	50															
Test Setup	 <p>Note: 1. Support units were connected to second LISN. 2. Both of LISNs (AMN) are 80cm from EUT and at least 80cm from other units and other metal planes support units.</p>																
Procedure	<ol style="list-style-type: none"> The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m x 1m x 0.8m high, non-metallic table. The power supply for the EUT was fed through a 50W/50mH EUT LISN, connected to filtered mains. The RF OUT of the EUT LISN was connected to the EMI test receiver via a low-loss 																

	coaxial cable. 4. All other supporting equipment were powered separately from another main supply. 5. The EUT was switched on and allowed to warm up to its normal operating condition. 6. A scan was made on the NEUTRAL line (for AC mains) or Earth line (for DC power) over the required frequency range using an EMI test receiver. 7. High peaks, relative to the limit line, The EMI test receiver was then tuned to the selected frequencies and the necessary measurements made with a receiver bandwidth setting of 10 kHz. 8. Step 7 was then repeated for the LIVE line (for AC mains) or DC line (for DC power).
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data Yes N/A

Test Plot Yes (See below) N/A

Test Mode: Transmitting Mode




Test Data

Phase Line Plot at 120Vac, 60Hz

No.	P/L	Frequency (MHz)	Reading (dB μ V)	Detector	Corrected (dB)	Result (dB μ V)	Limit (dB μ V)	Margin (dB)
1	L1	0.1656	28.31	QP	10.03	38.34	65.18	-26.84
2	L1	0.1656	10.14	AVG	10.03	20.17	55.18	-35.01
3	L1	0.5634	27.80	QP	10.03	37.83	56.00	-18.17
4	L1	0.5634	17.15	AVG	10.03	27.18	46.00	-18.82
5	L1	0.9144	19.10	QP	10.03	29.13	56.00	-26.87
6	L1	0.9144	8.38	AVG	10.03	18.41	46.00	-27.59
7	L1	2.2209	21.25	QP	10.05	31.30	56.00	-24.70
8	L1	2.2209	6.80	AVG	10.05	16.85	46.00	-29.15
9	L1	11.3616	23.59	QP	10.17	33.76	60.00	-26.24
10	L1	11.3616	10.05	AVG	10.17	20.22	50.00	-29.78
11	L1	20.4837	26.45	QP	10.31	36.76	60.00	-23.24
12	L1	20.4837	7.25	AVG	10.31	17.56	50.00	-32.44

Test Mode: Transmitting Mode




Test Data

Phase Neutral Plot at 120Vac, 60Hz

No.	P/L	Frequency (MHz)	Reading (dB μ V)	Detector	Corrected (dB)	Result (dB μ V)	Limit (dB μ V)	Margin (dB)
1	N	0.1607	31.65	QP	10.02	41.67	65.43	-23.76
2	N	0.1607	10.99	AVG	10.02	21.01	55.43	-34.42
3	N	0.2475	27.74	QP	10.02	37.76	61.84	-24.08
4	N	0.2475	8.63	AVG	10.02	18.65	51.84	-33.19
5	N	0.5712	19.74	QP	10.02	29.76	56.00	-26.24
6	N	0.5712	6.43	AVG	10.02	16.45	46.00	-29.55
7	N	2.2248	15.58	QP	10.04	25.62	56.00	-30.38
8	N	2.2248	2.97	AVG	10.04	13.01	46.00	-32.99
9	N	4.1271	17.49	QP	10.06	27.55	56.00	-28.45
10	N	4.1271	1.01	AVG	10.06	11.07	46.00	-34.93
11	N	19.7154	25.17	QP	10.26	35.43	60.00	-24.57
12	N	19.7154	6.26	AVG	10.26	16.52	50.00	-33.48


Test Mode: Transmitting Mode



Phase Line Plot at 240Vac, 60Hz

No.	P/L	Frequency (MHz)	Reading (dB μ V)	Detector	Corrected (dB)	Result (dB μ V)	Limit (dB μ V)	Margin (dB)
1	L1	0.2280	38.71	QP	10.03	48.74	62.52	-13.78
2	L1	0.2280	30.86	AVG	10.03	40.89	52.52	-11.63
3	L1	0.3567	29.69	QP	10.03	39.72	58.80	-19.08
4	L1	0.3567	23.20	AVG	10.03	33.23	48.80	-15.57
5	L1	1.2654	23.41	QP	10.03	33.44	56.00	-22.56
6	L1	1.2654	6.19	AVG	10.03	16.22	46.00	-29.78
7	L1	4.1466	21.03	QP	10.07	31.10	56.00	-24.90
8	L1	4.1466	2.97	AVG	10.07	13.04	46.00	-32.96
9	L1	11.1159	25.49	QP	10.17	35.66	60.00	-24.34
10	L1	11.1159	8.25	AVG	10.17	18.42	50.00	-31.58
11	L1	15.1056	24.27	QP	10.23	34.50	60.00	-25.50
12	L1	15.1056	10.25	AVG	10.23	20.48	50.00	-29.52

Test Mode: Transmitting Mode



Test Data

Phase Neutral Plot at 240Vac, 60Hz


No.	P/L	Frequency (MHz)	Reading (dB μ V)	Detector	Corrected (dB)	Result (dB μ V)	Limit (dB μ V)	Margin (dB)
1	N	0.2280	38.88	QP	10.02	48.90	62.52	-13.62
2	N	0.2280	30.02	AVG	10.02	40.04	52.52	-12.48
3	N	0.3567	27.87	QP	10.02	37.89	58.80	-20.91
4	N	0.3567	21.40	AVG	10.02	31.42	48.80	-17.38
5	N	0.5634	23.88	QP	10.02	33.90	56.00	-22.10
6	N	0.5634	12.27	AVG	10.02	22.29	46.00	-23.71
7	N	1.6086	21.98	QP	10.04	32.02	56.00	-23.98
8	N	1.6086	11.38	AVG	10.04	21.42	46.00	-24.58
9	N	6.0615	20.69	QP	10.08	30.77	60.00	-29.23
10	N	6.0615	9.27	AVG	10.08	19.35	50.00	-30.65
11	N	10.9638	26.33	QP	10.15	36.48	60.00	-23.52
12	N	10.9638	12.48	AVG	10.15	22.63	50.00	-27.37

6.7 Radiated Spurious Emissions & Restricted Band

Temperature	22 °C
Relative Humidity	54%
Atmospheric Pressure	1021mbar
Test date :	February 21, 2017
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable										
47CFR§15. 247(d), RSS210 (A8.5)	a)	<p>Except higher limit as specified elsewhere in other section, the emissions from the low-power radio-frequency devices shall not exceed the field strength levels specified in the following table and the level of any unwanted emissions shall not exceed the level of the fundamental emission. The tighter limit applies at the band edges</p> <table border="1"> <thead> <tr> <th>Frequency range (MHz)</th> <th>Field Strength (µV/m)</th> </tr> </thead> <tbody> <tr> <td>30 – 88</td> <td>100</td> </tr> <tr> <td>88 – 216</td> <td>150</td> </tr> <tr> <td>216 – 960</td> <td>200</td> </tr> <tr> <td>Above 960</td> <td>500</td> </tr> </tbody> </table>	Frequency range (MHz)	Field Strength (µV/m)	30 – 88	100	88 – 216	150	216 – 960	200	Above 960	500	<input checked="" type="checkbox"/>
Frequency range (MHz)	Field Strength (µV/m)												
30 – 88	100												
88 – 216	150												
216 – 960	200												
Above 960	500												
b)	<p>For non-restricted band, In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB or 30dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, determined by the measurement method on output power to be used. Attenuation below the general limits specified in § 15.209(a) is not required</p> <p><input checked="" type="checkbox"/> 20 dB down <input type="checkbox"/> 30 dB down</p>	<input checked="" type="checkbox"/>											
	c)	or restricted band, emission must also comply with the radiated emission limits specified in 15.209	<input checked="" type="checkbox"/>										


Test Setup	 <p>The diagram illustrates the test setup. A Turn Table is positioned on a Ground Plane. A vertical Ant. Tower is mounted on the Turn Table, with a 1-4m Variable height adjustment. A horizontal distance of 3m is indicated between the EUT & Support Units and the Ant. Tower. The EUT & Support Units are mounted on the Turn Table at a height of 0.8/1.5m. A Test Receiver is connected to the Ant. Tower to measure emissions.</p>
Procedure	<ol style="list-style-type: none"> 1. The EUT was switched on and allowed to warm up to its normal operating condition. 2. The test was carried out at the selected frequency points obtained from the EUT characterization. Maximization of the emissions, was carried out by rotating the EUT, changing the antenna polarization, and adjusting the antenna height in the following manner: <ol style="list-style-type: none"> a. Vertical or horizontal polarization (whichever gave the higher emission level over a full rotation of the EUT) was chosen. b. The EUT was then rotated to the direction that gave the maximum emission. c. Finally, the antenna height was adjusted to the height that gave the maximum emission. 3. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasiy Peak detection at frequency below 1GHz. 4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz with Peak detection for Peak measurement at frequency above 1GHz. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz with Peak detection for Average Measurement as below at frequency above 1GHz. 5. Steps 2 and 3 were repeated for the next frequency point, until all selected frequency points were measured.
Remark	<p>Different RF configuration has been evaluated but not much difference was found. The data presented here is the worst case data with EUT under 802.11n – HT20-2437MHz mode.</p>
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data Yes N/A

Test Plot Yes (See below) N/A

Test Mode: Transmitting Mode


(Below 1GHz)



Vertical Polarity Plot @3m

No.	P/L	Frequency	Reading	Detect or	Ant_F	PA_G	Cab_L	Result	Limit	Margin	Height	Degr ee
		(MHz)	(dBuV/m)		(dB/m)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	()
1	H	83.5222	42.19	peak	7.74	22.38	1.06	28.61	40.00	-11.39	200	136
2	H	135.5062	36.02	peak	12.89	22.40	1.24	27.75	43.50	-15.75	100	327
3	H	199.9856	36.82	peak	12.10	22.38	1.54	28.08	43.50	-15.42	100	149
4	H	294.1137	40.79	peak	13.34	22.29	1.78	33.62	46.00	-12.38	300	196
5	H	750.1083	36.21	peak	20.80	21.25	2.87	38.63	46.00	-7.37	300	231
6	H	851.0353	39.20	QP	21.96	21.01	2.87	43.02	46.00	-2.98	100	131

(Below 1GHz)



Test Data

Horizontal Polarity Plot @3m

No.	P/L	Frequency	Reading	Detect or	Ant_F	PA_G	Cab_L	Result	Limit	Margin	Height	Degr ee
		(MHz)	(dBuV/m)		(dB/m)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	()
1	V	55.4147	52.72	QP	7.80	22.40	0.78	38.90	40.00	-1.10	300	341
2	V	67.2022	47.29	peak	7.66	22.39	0.92	33.48	40.00	-6.52	200	14
3	V	82.0706	50.86	QP	7.68	22.40	1.06	37.20	40.00	-2.80	100	323
4	V	135.9822	44.70	QP	12.86	22.40	1.24	36.40	43.50	-7.10	300	231
5	V	651.9417	34.87	peak	19.67	21.47	2.63	35.70	46.00	-10.30	100	79
6	V	896.9965	34.12	QP	22.47	20.89	3.06	38.76	46.00	-7.24	100	230

Above 1GHz

Test Mode:	Transmitting Mode
------------	-------------------

Low Channel (2412 MHz) (b mode worst case)

Frequency (MHz)	S.A. Reading (dB μ V)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord Amp. (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
4824	39.02	AV	V	33.8	6.86	32.69	46.99	54	-7.01
4824	38.76	AV	H	33.8	6.86	32.69	46.73	54	-7.27
4824	47.65	PK	V	33.8	6.86	32.69	55.62	74	-18.38
4824	47.12	PK	H	33.8	6.86	32.69	55.09	74	-18.91
17893	23.57	AV	V	45.12	11.57	32.11	48.15	54	-5.85
17893	23.15	AV	H	45.12	11.57	32.11	47.73	54	-6.27
17893	40.28	PK	V	45.12	11.57	32.11	64.86	74	-9.14
17893	39.44	PK	H	45.12	11.57	32.11	64.02	74	-9.98

Middle Channel (2437 MHz) (b mode worst case)

Frequency (MHz)	S.A. Reading (dB μ V)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord Amp. (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
4874	38.75	AV	V	33.6	6.82	32.71	46.46	54	-7.54
4874	37.13	AV	H	33.6	6.82	32.71	44.84	54	-9.16
4874	48.61	PK	V	33.6	6.82	32.71	56.32	74	-17.68
4874	47.95	PK	H	33.6	6.82	32.71	55.66	74	-18.34
17925	24.33	AV	V	45.17	11.63	32.18	48.95	54	-5.05
17925	23.67	AV	H	45.17	11.63	32.18	48.29	54	-5.71
17925	41.02	PK	V	45.17	11.63	32.18	65.64	74	-8.36
17925	40.38	PK	H	45.17	11.63	32.18	65	74	-9

High Channel (2462 MHz) (b mode worst case)

Frequency (MHz)	S.A. Reading (dB μ V)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord Amp. (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
4924	39.28	AV	V	33.83	6.95	32.79	47.27	54	-6.73
4924	38.46	AV	H	33.83	6.95	32.79	46.45	54	-7.55
4924	48.55	PK	V	33.83	6.95	32.79	56.54	74	-17.46
4924	47.31	PK	H	33.83	6.95	32.79	55.3	74	-18.7
17904	23.84	AV	V	45.19	11.61	32.24	48.4	54	-5.6
17904	22.61	AV	H	45.19	11.61	32.24	47.17	54	-6.83
17904	40.38	PK	V	45.19	11.61	32.24	64.94	74	-9.06
17904	39.71	PK	H	45.19	11.61	32.24	64.27	74	-9.73

Note:

- 1, The testing has been conformed to $10 \times 2462\text{MHz} = 24,620\text{MHz}$
- 2, All other emissions more than 30 dB below the limit
- 3, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case.

Annex A. TEST INSTRUMENT

Instrument	Model	Serial #	Cal Date	Cal Due	In use
AC Line Conducted					
EMI test receiver	ESCS30	8471241027	09/16/2016	09/15/2017	<input checked="" type="checkbox"/>
Line Impedance	LI-125A	191106	09/24/2016	09/23/2017	<input checked="" type="checkbox"/>
Line Impedance	LI-125A	191107	09/24/2016	09/23/2017	<input checked="" type="checkbox"/>
LISN	ISN T800	34373	09/24/2016	09/23/2017	<input checked="" type="checkbox"/>
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71283	09/23/2016	09/22/2017	<input checked="" type="checkbox"/>
Transient Limiter	LIT-153	531118	08/31/2016	08/30/2017	<input checked="" type="checkbox"/>
RF conducted test					
Agilent ESA-E SERIES	E4407B	MY45108319	09/16/2016	09/15/2017	<input checked="" type="checkbox"/>
Power Splitter	1#	1#	08/31/2016	08/30/2017	<input checked="" type="checkbox"/>
DC Power Supply	E3640A	MY40004013	09/16/2016	09/15/2017	<input checked="" type="checkbox"/>
Radiated Emissions					
EMI test receiver	ESL6	100262	09/16/2016	09/15/2017	<input checked="" type="checkbox"/>
Positioning Controller	UC3000	MF780208282	11/18/2016	11/17/2017	<input checked="" type="checkbox"/>
OPT 010 AMPLIFIER (0.1-1300MHz)	8447E	2727A02430	08/31/2016	08/30/2017	<input checked="" type="checkbox"/>
Microwave Preamplifier (1 ~ 26.5GHz)	8449B	3008A02402	03/24/2016	03/23/2017	<input checked="" type="checkbox"/>
Bilog Antenna (30MHz~6GHz)	JB6	A110712	09/20/2016	09/19/2017	<input checked="" type="checkbox"/>
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71283	09/23/2016	09/22/2017	<input checked="" type="checkbox"/>
Universal Radio Communication Tester	CMU200	121393	09/24/2016	09/23/2017	<input checked="" type="checkbox"/>


Annex B. EUT and Test Setup Photographs

Annex B.i. Photograph: EUT External Photo

Whole Package View



Adapter - Front View



Test Report No.	17070084-FCC-R3 V1
Page	44 of 57

EUT - Front View




EUT - Rear View




Test Report No.	17070084-FCC-R3 V1
Page	45 of 57

EUT - Top View




EUT - Bottom View



Annex B.ii. Photograph: EUT Internal Photo

Cover Off - Top View 1




Cover Off - Top View 2




Test Report No.	17070084-FCC-R3 V1
Page	47 of 57


Battery - Front View




Battery - Rear View



Mainboard with Shielding - Front View




Mainboard without Shielding - Front View




Test Report No.	17070084-FCC-R3 V1
Page	49 of 57

Mainboard - Rear View




LCD – Front View



Test Report No.	17070084-FCC-R3 V1
Page	50 of 57


LCD – Rear View



WIFI/BT - Antenna View




Annex B.iii. Photograph: Test Setup Photo




Annex C. TEST SETUP AND SUPPORTING EQUIPMENT

Annex C.ii. TEST SET UP BLOCK


Block Configuration Diagram for AC Line Conducted Emissions



Block Configuration Diagram for Radiated Emissions (Below 1GHz) .



Block Configuration Diagram for Radiated Emissions (Above 1GHz) .



Annex C. ii. SUPPORTING EQUIPMENT DESCRIPTION

The following is a description of supporting equipment and details of cables used with the EUT.

Supporting Equipment:

Manufacturer	Equipment Description	Model	Serial No
Global Regency Ltd.	Adapter	JML-0500200-LW	C053146

Supporting Cable:

Cable type	Shield Type	Ferrite Core	Length	Serial No
USB Cable	Un-shielding	No	0.8m	C053146

Test Report No.	17070084-FCC-R3 V1
Page	56 of 57

Annex D. User Manual / Block Diagram / Schematics / Partlist

Please see the attachment

Test Report No.	17070084-FCC-R3 V1
Page	57 of 57

Annex E. DECLARATION OF SIMILARITY

N/A