



FCC Part 15B TEST REPORT

Report No.: STS2205083E03

Issued for

Shanghai Unihertz E-Commerce Co., Ltd

Room 308, Building C, 508 Chundong Rd, Minhang district
Shanghai, China 201108

Product Name:	Smart phone
Brand Name:	Unihertz
Model Name:	Jelly 2E
Series Model:	N/A
FCC ID:	2AK6CJELLY2E
Test Standard:	FCC 47 CFR Part 15: Subpart B

Any reproduction of this document must be done in full. No single part of this document may be reproduced without permission from STS. All Test Data Presented in this report is only applicable to presented Test sample.



**TEST RESULT CERTIFICATION**

Applicant's Name : Shanghai Unihertz E-Commerce Co., Ltd

Address : Room 308, Building C, 508 Chundong Rd, Minhang district
Shanghai, China 201108

Manufacture's Name : OBLUE Communication Technology Co.,Ltd.

Address : 7th floor, building B, dayou industrial and trade industrial park, heping
yonghe road, fuyong street, baoan district, Shenzhen, China

Product Description :

Product Name : Smart phone

Brand Name : Unihertz

Model Name : Jelly 2E

Series Model : N/A

Standards : FCC 47 CFR Part 15: Subpart B

Test Procedure : ANSI C63.4-2014

This device described above has been tested by STS, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of STS, this document may be altered or revised by STS, personal only, and shall be noted in the revision of the document.

Date of Test :

Date of Receipt of Test Item : 05 May 2022

Date of Performance of Tests : 05 May 2022 ~ 20 June 2022

Date of Issue : 20 June 2022

Test Result : **Pass**

Testing Engineer :

(Jane Chen)

Technical Manager :

(Bulun)

Authorized Signatory :

(Bovey Yang)





Table of Contents

1. SUMMARY OF THE TEST RESULTS	5
1.1 TEST FACTORY	5
1.2 MEASUREMENT UNCERTAINTY	5
2. GENERAL INFORMATION	6
2.1 GENERAL DESCRIPTION OF THE EUT	6
2.2 DESCRIPTION OF THE TEST MODES	8
2.3 DESCRIPTION OF THE TEST SETUP	9
2.4 EQUIPMENTS LIST FOR ALL TEST ITEMS	10
3. EMC EMISSION TEST	11
3.1 CONDUCTED EMISSION MEASUREMENT	11
3.2 RADIATED EMISSION MEASUREMENT	



**Revision History**

Rev.	Issue Date	Report No.	Effect Page	Contents
00	20 June 2022	STS2205083E03	ALL	Initial Issue





1. SUMMARY OF THE TEST RESULTS

Test procedures according to the technical standards:

EMISSION			
Standard	Item	Result	Remarks
FCC 47 CFR Part 15: Subpart B	Conducted Emission	PASS	Meet Class B limit
	Radiated Emission	PASS	Meet Class B limit

NOTE:

(1) N/A=Not Applicable.

1.1 TEST FACTORY

Company Name:	SHENZHEN STS TEST SERVICES CO.,LTD.
Address:	A 1/F, Building B, Zhuoke Science Park, No.190 Chongqing Road, HepingShequ, Fuyong Sub-District, Bao'an District, Shenzhen, Guang Dong, China
Telephone:	+86-755 3688 6288
Fax:	+86-755 3688 6277
Registration No.:	FCC test Firm Registration Number: 625569
	IC test Firm Registration Number: 12108A
	A2LA Certificate No.: 4338.01

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 % .

No.	Item	Uncertainty
1	Conducted Emission (9KHz-30MHz)	$\pm 2.73\text{dB}$
2	All emissions, radiated(<1G) 30MHz-1000MHz	$\pm 4.09\text{dB}$
3	All emissions, radiated(>1G) 1GHz-6GHz	$\pm 4.92\text{dB}$
4	All emissions, radiated(>1G) 6GHz-18GHz	$\pm 5.49\text{dB}$



2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF THE EUT

Product Name	Smart phone	
Brand Name	Unihertz	
Model Name	Jelly 2E	
Series Model	N/A	
Model Difference	N/A	
Product Description	<p>The EUT is a Smart phone</p> <p>ITE equipment having a primary function of either (or a combination of) entry, storage, display, retrieval, transmission, processing, switching, or control of data and/or telecommunication messages and which may be equipped with one or more ports typically for information transfer.</p>	
Frequency Bands	GSM	850: 824 MHz to 849 MHz 1900: 1850 MHz to 1910 MHz
	WCDMA	Band 2: 1850 MHz to 1910 MHz Band 4: 1710 MHz to 1755 MHz Band 5: 824 MHz to 849 MHz
	LTE	Band 2: 1850 MHz to 1910 MHz Band 4: 1710 MHz to 1755 MHz Band 5: 824 MHz to 849 MHz Band 7: 2500 MHz to 2570 MHz Band 12: 699 MHz to 716 MHz Band 17: 704 MHz to 716 MHz Band 25: 1850 MHz to 1915 MHz Band 26: 821 MHz to 824 MHz/824 MHz to 849 MHz Band 38: 2570 MHz to 2620 MHz Band 40: 2305 MHz to 2315 MHz /2350 MHz to 2360 MHz Band 41: 2555 MHz to 2655 MHz
	Bluetooth	2402 MHz to 2480 MHz
	2.4G WLAN	802.11b/g/n 20: 2412~2462 MHz 802.11n(40MHz):2422~2452MHz
	5G WLAN	802.11a/n/ac (20MHz): 5180~5700MHz 802.11n/ac(40MHz):5190~5670MHz 802.11ac(80MHz):5210~5610MHz
	5.8G WLAN	802.11a/n/ac (20MHz): 5745~5825MHz 802.11n /ac(40MHz):5755~5795MHz 802.11ac (80MHz):5775MHz
	GPS	1575.42MHz
	GLONASS	1602 MHz
	Galileo	1575.42 MHz
	BDS	1561.098MHz



	FM	87.5-108MHz
Modulation Mode	GSM	GMSK for GSM/GPRS; GMSK and 8PSK for EDGE
	WCDMA	QPSK; HSDPA:QPSK/16QAM; HSUPA:BPSK
	LTE	QPSK/16QAM
	Bluetooth	BT(1Mbps): GFSK BT EDR(2Mbps): π/4-DQPSK BT EDR(3Mbps): 8DPSK
	BLE	GFSK
	2.4G WLAN	802.11b(DSSS):CCK,DQPSK,DBPSK 802.11g/n(OFDM):BPSK,QPSK,16-QAM,64-QAM
	5G/5.8G WLAN	802.11a/n(OFDM):BPSK,QPSK,16-QAM,64-QAM 802.11ac(OFDM): BPSK,QPSK,16-QAM,64-QAM,256-QAM
	GPS	BPSK
	GLONASS	FDMA
	Galileo	CBOC
	BDS	QPSK
	FM	FM
Rating	Input:100-240V-50/60HZ 0.3A Output: 5.0V-1.5A	
Battery	Rated Voltage:3.85V ChargeLimit Voltage:4.4V Capacity: 2000mAh	
Hardware Version Number	G55L_V1.1	
Software Version Number	Jelly 2E_20220505	

Note: For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.



2.2 DESCRIPTION OF THE TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possibly have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	PC+USB Transmitting+SD Card
Mode 2	Charging + Audio + Video + Earphone
Mode 3	Charging + FM
Mode 4	Adapter + Rear Camera + Earphone
Mode 5	Adapter + Front-facing camera + Earphone

For Conducted Test	
Final Test Mode	Description
Mode 1	PC+USB Transmitting+SD Card

For Radiated Test	
Final Test Mode	Description
Mode 1	PC+USB Transmitting+SD Card

Note:

1. We have be tested for all available U.S. voltage and frequencies (For 120V, 50/60Hz) for which the device is capable of operation.



2.3 DESCRIPTION OF THE TEST SETUP

The EUT has been tested with associated equipment below and the test setup please refer to appendix 1 - test setup.

Necessary accessories

Item	Equipment	Mfr/Brand	Model/Type No.	Length	Note
/	USB Cable	N/A	N/A	80cm	NO

Support units

Item	Equipment	Mfr/Brand	Model/Type No.	Length	Note
/	Notebook Adapter	DELL	HSTNN-CA15	N/A	N/A
/	Notebook	DELL	500-320cx	N/A	N/A
/	Adapter	SZTY	TPA-46050100VU	N/A	N/A
/	Earphone	N/A	N/A	80cm	N/A
/	Keyboard	Acer	SK-9624	N/A	N/A
/	Mouse	HP	MODGUO	N/A	N/A
/	Printer	LENOVO	LJ2400L	N/A	N/A
/	USB Cable	N/A	N/A	110cm	NO
/	DC Cable	N/A	N/A	110cm	NO
/	USB Cable	N/A	N/A	110cm	NO
/	USB Cable	N/A	N/A	110cm	NO
/	USB Cable	N/A	N/A	110cm	NO

Note:

- (1) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (2) "YES" is means "with core"; "NO" is means "without core".



2.4 EQUIPMENTS LIST FOR ALL TEST ITEMS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Radiation Test equipment

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last Calibration	Calibrated Until
EMI Test Receiver	R&S	ESCI	101427	2021.09.30	2022.09.29
Bi-log Antenna	TESEQ	CBL6111D	45873	2021.10.08	2023.10.07
Horn Antenna	SCHWARZBECK	BBHA 9120D	1343	2020.10.12	2022.10.11
Pre-amplifier(1-26.5G)	Agilent	8449B	3008A02383	2021.10.09	2022.10.08
Pre-amplifier(0.1M-3GHz)	EM	EM330	060665	2021.10.09	2022.10.08
Spectrum Analyzer	Agilent	N9020A	MY49100060	2021.09.30	2022.09.29
RE Cable (9K-1G)	N/A	R01	N/A	2021.10.09	2022.10.08
RE Cable (1-26G)	N/A	R02	N/A	2021.10.09	2022.10.08
Temperature & Humidity	Mieo	HH660	N/A	2021.10.09	2022.10.08
Horn Antenna(18-40G)	A-INFO	LB-180400-K F	J211020657	2020.10.12	2022.10.11
Testing Software			EZ-EMC(Ver.STSLAB-03A1 RE)		

Conduction Test equipment

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last Calibration	Calibrated Until
EMI Test Receiver	R&S	ESCI	101427	2021.09.30	2022.09.29
LISN	R&S	ENV216	101242	2021.09.30	2022.09.29
LISN	ETS	3810/2NM	00023625	2021.09.30	2022.09.29
Absorbing Clamp	R&S	MDS-21	100668	2022.03.02	2023.03.01
CE Cable	N/A	C01	N/A	2021.09.30	2022.09.29
Temperature & Humidity	Mieo	HH660	N/A	2021.10.09	2022.10.08
Testing Software			EZ-EMC(Ver.STSLAB-03A1 CE)		



3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION LIMITS

FREQUENCY (MHz)	□Class A (dB μ V)		☒Class B (dB μ V)	
	Quasi-peak	Average	Quasi-peak	Average
0.15 ~ 0.5	79.00	66.00	66 - 56 *	56 - 46 *
0.5 ~ 5	73.00	60.00	56.00	46.00
5 ~ 30	73.00	60.00	60.00	50.00

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz


3.1.2 TEST PROCEDURE

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.1.3 DEVIATION FROM TEST STANDARD

No deviation

3.1.4 TEST SETUP



Note:

1. Support units were connected to second LISN.
2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

3.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.




3.1.6 TEST RESULTS

Temperature:	26.1°C	Relative Humidity:	60%
Phase:	L	Test Mode:	Mode 1
Test Voltage:	AC 120V/60Hz	Test Date:	2022.05.16

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1540	35.15	20.30	55.45	65.78	-10.33	QP
2	0.1540	15.18	20.30	35.48	55.78	-20.30	AVG
3	0.5660	18.16	20.45	38.61	56.00	-17.39	QP
4	0.5660	8.34	20.45	28.79	46.00	-17.21	AVG
5	1.6020	22.24	20.35	42.59	56.00	-13.41	QP
6	1.6020	14.90	20.35	35.25	46.00	-10.75	AVG
7	2.1420	22.36	20.39	42.75	56.00	-13.25	QP
8	2.1420	12.95	20.39	33.34	46.00	-12.66	AVG
9	4.9780	16.45	20.53	36.98	56.00	-19.02	QP
10	4.9780	5.08	20.53	25.61	46.00	-20.39	AVG
11	7.0500	14.07	20.59	34.66	60.00	-25.34	QP
12	7.0500	3.06	20.59	23.65	50.00	-26.35	AVG

Remark:

1. All readings are Quasi-Peak and Average values
2. Margin = Result (Result = Reading + Factor)–Limit
3. Factor = Insertion loss + Cable loss






Temperature:	26.1 °C	Relative Humidity:	60%
Phase:	N	Test Mode:	Mode 1
Test Voltage:	AC 120V/60Hz	Test Date:	2022.05.16

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1540	35.15	20.30	55.45	65.78	-10.33	QP
2	0.1540	15.18	20.30	35.48	55.78	-20.30	AVG
3	0.5660	18.16	20.45	38.61	56.00	-17.39	QP
4	0.5660	8.34	20.45	28.79	46.00	-17.21	AVG
5	1.6020	22.24	20.35	42.59	56.00	-13.41	QP
6	1.6020	14.90	20.35	35.25	46.00	-10.75	AVG
7	2.1420	22.36	20.39	42.75	56.00	-13.25	QP
8	2.1420	12.95	20.39	33.34	46.00	-12.66	AVG
9	4.9780	16.45	20.53	36.98	56.00	-19.02	QP
10	4.9780	5.08	20.53	25.61	46.00	-20.39	AVG
11	7.0500	14.07	20.59	34.66	60.00	-25.34	QP
12	7.0500	3.06	20.59	23.65	50.00	-26.35	AVG

Remark:

1. All readings are Quasi-Peak and Average values
2. Margin = Result (Result = Reading + Factor)–Limit
3. Factor = Insertion loss + Cable loss





3.2 RADIATED EMISSION MEASUREMENT

3.2.1 RADIATED EMISSION LIMITS

Below 1 GHz

Measurement Method and Applied Limits:

ANSI C63.4:

Frequency (MHz)	<input type="checkbox"/> Class A		<input checked="" type="checkbox"/> Class B
	Field strength (dBuV/m) (at 10m)	Field strength (dBuV/m) (at 3m)	Field strength (dBuV/m) (at 3m)
30 ~ 88	39	49.5	40
88 ~ 216	43.5	54	43.5
216 ~ 960	46.4	56.9	46
Above 960	49.5	60	54

Above 1 GHz

Measurement Method and Applied Limits:

ANSI C63.4:

Frequency (MHz)	<input type="checkbox"/> Class A				<input checked="" type="checkbox"/> Class B	
	(dBuV/m) (at 3m)		(dBuV/m) (at 10m)		(dBuV/m) (at 3m)	
	Peak	Average	Peak	Average	Peak	Average
Above 1000	80	60	69.5	49.5	74	54

Frequency Range of Radiated Disturbance Measurement

Highest frequency generated or Upper frequency of measurement used in the device or on which the device operates or tunes (MHz)	Range (MHz)
Below 1.705	30
1.705 ~ 108	1000
108 ~ 500	2000
500 ~ 1000	5000
Above 1000	5th harmonic of the highest frequency or 40 GHz, whichever is lower

Note:

- (1) The limit for radiated test was performed in the following: FCC PART 15B.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m) = 20log Emission level (uV/m).



3.2.2 TEST PROCEDURE

- a. The EUT was placed on the top of a rotating table 0.8 meter above the ground at a 3 meter semi-anechoic chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. EUT as the center to the edge of the auxiliary device, the distance from the maximum edge to the center of the antenna is 3 meter.
- c. The height of antenna is varied from 1 meter to 4 meter above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meter and the rotatable table was turned from 0 degrees to 360 degree to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1GHz.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.


Note: Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

3.2.3 DEVIATION FROM TEST STANDARD


No deviation

3.2.4 TEST SETUP

(A) Radiated Emission Test-Up Frequency Below 1 GHz



(B) Radiated Emission Test-Up Frequency Above 1GHz



3.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 described unless otherwise a special operating condition is specified in the following during the testing.

3.2.6 TEST RESULTS


30MHz - 1000MHz

Temperature:	24.9°C	Relative Humidity:	50%
Phase:	Horizontal	Test Mode:	Mode 1
Test Voltage:	DC 5V From PC	Test Date:	2022.05.13

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	80.3620	52.33	-22.92	29.41	40.00	-10.59	QP
2	85.5977	58.29	-22.18	36.11	40.00	-3.89	QP
3	182.5592	49.88	-21.02	28.86	43.50	-14.64	QP
4	261.9753	47.33	-14.97	32.36	46.00	-13.64	QP
5	305.6800	44.66	-15.80	28.86	46.00	-17.14	QP
6	986.0716	31.13	-2.13	29.00	54.00	-25.00	QP

Remark:

1. All readings are Quasi-Peak
2. Margin = Result (Result =Reading + Factor)–Limit
3. Factor= Cable Loss +Antenna Factor-Amplifier Gain






Temperature:	24.9°C	Relative Humidity:	50%
Phase:	Vertical	Test Mode:	Mode 1
Test Voltage:	DC 5V From PC	Test Date:	2022.05.13

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	48.3318	41.29	-20.81	20.48	40.00	-19.52	QP
2	85.8983	58.82	-22.13	36.69	40.00	-3.31	QP
3	96.7750	48.76	-20.48	28.28	43.50	-15.22	QP
4	257.4221	41.28	-15.38	25.90	46.00	-20.10	QP
5	543.2741	37.49	-9.00	28.49	46.00	-17.51	QP
6	986.0716	35.54	-2.13	33.41	54.00	-20.59	QP

Remark:

1. All readings are Quasi-Peak
2. Margin = Result (Result = Reading + Factor)–Limit
3. Factor= Cable Loss +Antenna Factor-Amplifier Gain






(1 GHz - 18GHz)

Temperature:	25.3°C	Relative Humidity:	53%
Phase:	Horizontal	Test Mode:	Mode 1
Test Voltage:	DC 5V From PC	Test Date:	2022.05.13

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	3601.000	39.77	2.99	42.76	74.00	-31.24	Peak
2	3601.000	31.07	2.99	34.06	54.00	-19.94	AVG
3	5964.000	36.10	7.56	43.66	74.00	-30.34	Peak
4	5964.000	28.69	7.56	36.25	54.00	-17.75	AVG
5	8786.000	32.08	13.36	45.44	74.00	-28.56	Peak
6	8786.000	23.32	13.36	36.68	54.00	-17.32	AVG
7	12381.500	31.09	15.36	46.45	74.00	-27.55	Peak
8	12381.500	22.92	15.36	38.28	54.00	-15.72	AVG
9	15254.500	32.15	17.62	49.77	74.00	-24.23	Peak
10	15254.500	23.44	17.62	41.06	54.00	-12.94	AVG
11	17983.000	28.55	24.47	53.02	74.00	-20.98	Peak
12	17983.000	19.01	24.47	43.48	54.00	-10.52	AVG

Remark:

1. All readings are Peak and Average values
2. Margin = Result (Result =Reading + Factor)–Limit
3. Factor= Cable Loss +Antenna Factor-Amplifier Gain






Temperature:	25.3°C	Relative Humidity:	53%
Phase:	Vertical	Test Mode:	Mode 1
Test Voltage:	DC 5V From PC	Test Date:	2022.05.13

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	3380.000	42.31	2.28	44.59	74.00	-29.41	Peak
2	3380.000	33.81	2.28	36.09	54.00	-17.91	AVG
3	5556.000	38.36	7.52	45.88	74.00	-28.12	Peak
4	5556.000	29.57	7.52	37.09	54.00	-16.91	AVG
5	8913.500	32.71	13.38	46.09	74.00	-27.91	Peak
6	8913.500	24.69	13.38	38.07	54.00	-15.93	AVG
7	12279.500	33.94	15.20	49.14	74.00	-24.86	Peak
8	12279.500	24.89	15.20	40.09	54.00	-13.91	AVG
9	14838.000	31.85	17.92	49.77	74.00	-24.23	Peak
10	14838.000	23.79	17.92	41.71	54.00	-12.29	AVG
11	17813.000	28.08	24.39	52.47	74.00	-21.53	Peak
12	17813.000	20.25	24.39	44.64	54.00	-9.36	AVG

Remark:

1. All readings are Peak and Average values
2. Margin = Result (Result =Reading + Factor)–Limit
3. Factor= Cable Loss +Antenna Factor-Amplifier Gain



*****END OF THE REPORT*****