



RF TEST REPORT

Product Name: TANK

Model Name: TANK 01

FCC ID: 2AK6CTANK01

Issued For : Shanghai Unihertz E-Commerce Co., Ltd

Room 308, Building C, 508Chundong Rd, Minhang district
Shanghai, China 201108

Issued By : Shenzhen LGT Test Service Co., Ltd.

Room 205, Building 13, Zone B, Chen Hsong Industrial Park,
No.177 Renmin West Road, Jinsha Community, Kengzi
Street, Pingshan New District, Shenzhen, China

Report Number: LGT22J019RF13

Sample Received Date: October 14, 2022

Date of Tested: October 14, 2022 – October 25, 2022

Date of Issue: October 31, 2022

The test report is effective only with both signature and specialized stamp. This report shall not be reproduced except in full without the written approval of the Laboratory. The results in this report only apply to the tested sample.



TEST REPORT CERTIFICATION

Applicant Shanghai Unihertz E-Commerce Co., Ltd
Address Room 308, Building C, 508Chundong Rd, Minhang district
Shanghai, China 201108
Manufacturer OBLUE Communication Technology Co., Ltd.
Address Room 702, Hepingdayou industrial and trade industrial
park, No. 41, Yonghe Road, Heping Community, Fuhai
Street, Baoan District, Shenzhen City, China
Product Name TANK
Trademark Unihertz
Model Name TANK 01
Sample Status: Normal

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
FCC Part 15.407, Subpart E ANSI C63.10-2013	PASS

Prepared by:

Zane Shan

Zane Shan
Engineer

Approved by:

Vita Li

Vita Li
Technical Director





Table of Contents	Page
1 . SUMMARY OF TEST RESULTS	6
1.1 TEST FACTORY	7
1.2 MEASUREMENT UNCERTAINTY	7
2 . GENERAL INFORMATION	8
2.1 GENERAL DESCRIPTION OF THE EUT	8
2.2 DESCRIPTION OF TEST MODES	11
2.3 TEST SOFTWARE AND POWER LEVEL	12
2.4 DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS	13
2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS	14
3 . EMC EMISSION TEST	15
3.1 CONDUCTED EMISSION MEASUREMENT	15
3.2 RADIATED EMISSION AND (BANDEGE) MEASUREMENT	19
4. POWER SPECTRAL DENSITY TEST	64
4.1 LIMIT	64
4.2 TEST PROCEDURE	64
4.3 DEVIATION FROM STANDARD	64
4.4 TEST SETUP	64
4.5 EUT OPERATION CONDITIONS	65
4.6 TEST RESULTS	65
5. BANDWIDTH MEASUREMENT	66
5.1 EMISSION BANDWIDTH (EBW) 26 BANDWID PROCEDURES / LIMIT	66
5.2 OCCUPIED BANDWIDTH (99%) TEST APPLIED PROCEDURES / LIMIT	67
5.3 MINIMUM EMISSION BANDWIDTH(6 DB) PROCEDURES / LIMIT	68
6. MAXIMUM CONDUCTED OUTPUT POWER	69
6.1 LIMIT	69
6.2 TEST PROCEDURE	69
6.3 DEVIATION FROM STANDARD	69
6.4 TEST SETUP	69
6.5 EUT OPERATION CONDITIONS	69
6.6 TEST RESULTS	70
7. AUTOMATICALLY DISCONTINUE TRANSMISSION	71
7.1 LIMIT OF AUTOMATICALLY DISCONTINUE TRANSMISSION	71
7.2 TEST RESULT OF AUTOMATICALLY DISCONTINUE TRANSMISSION	71
8. ANTENNA REQUIREMENT	72



Table of Contents	Page
8.1 STANDARD REQUIREMENT	72
8.2 EUT ANTENNA	72
APPENDIX I:TEST RESULTS	73
DUTY CYCLE	73
MAXIMUM CONDUCTED OUTPUT POWER	105
-26DB BANDWIDTH	137
OCCUPIED CHANNEL BANDWIDTH	161
MAXIMUM POWER SPECTRAL DENSITY LEVEL	194
-6DB BANDWIDTH	227
APPENDIX II:PHOTOS OF TEST SETUP	235



Revision History

Rev.	Issue Date	Contents
00	Oct. 31, 2022	Initial Issue



1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

Part 15.407, KDB 789033 D02 General U-NII Test Procedures New Rules v02r01

FCC Part 15.407		
FCC standard	Test Item	Results
15.207	AC Conducted Emission	PASS
15.407 (a) /15.407 (e)	26dB/6dB &99% Bandwidth	PASS
15.407(a)	Maximum Conducted Output Power	PASS
15.407(b)/15.205/15.209	Radiated Emission And (bandedge Emissions) Measurement	PASS
15.407(a)	Power Spectral Density	PASS
15.407(c)	Automatically Discontinue Transmission	PASS
15.203/15.204	Antenna Requirement	PASS

NOTE:

(1) 'N/A' denotes test is not applicable in this Test Report.

(2) All tests are according to ANSI C63.10-2013.



1.1 TEST FACTORY

Company Name:	Shenzhen LGT Test Service Co., Ltd.
Address:	Room 205, Building 13, Zone B, Chen Hsong Industrial Park, No.177 Renmin West Road, Jinsha Community, Kengzi Street, Pingshan New District, Shenzhen, China
Accreditation Certificate	FCC Registration No.: 746540
	A2LA Certificate No.: 6727.01

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	RF output power, conducted	$\pm 0.68\text{dB}$
2	Unwanted Emissions, conducted	$\pm 2.988\text{dB}$
3	All emissions, radiated 9K-30MHz	$\pm 2.84\text{dB}$
4	All emissions, radiated 30M-1GHz	$\pm 4.39\text{dB}$
5	All emissions, radiated 1G-6GHz	$\pm 5.10\text{dB}$
6	All emissions, radiated >6G	$\pm 5.48\text{dB}$
7	Conducted Emission (9KHz-150KHz)	$\pm 2.79\text{dB}$
8	Conducted Emission (150KHz-30MHz)	$\pm 2.80\text{dB}$



2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF THE EUT

Product Name	TANK								
Trademark	Unihertz								
Model Name	TANK 01								
Series Model	N/A								
Model Difference	N/A								
Product Description	The EUT is a TANK <table border="1"> <tr> <td>Operation Frequency:</td><td> IEEE 802.11a/n(HT20)/ac(VHT20): 5.180GHz-5.240GHz IEEE 802.11n(HT40)/ac(VHT40): 5.190GHz-5.230GHz IEEE 802.11ac(VHT80): 5.210GHz IEEE 802.11a/n(HT20)/ac(VHT20): 5.260GHz-5.320GHz IEEE 802.11 n(HT40)/ac(VHT40): 5.270GHz-5.310GHz IEEE 802.11ac(VHT80): 5.290GHz I IEEE 802.11a/n(HT20)/ac(VHT20): 5.500GHz-5.700GHz IEEE 802.11 n(HT40)/ac(VHT40): 5.510GHz-5.670GHz IEEE 802.11ac(VHT80): 5.530GHz-5.610GHz I IEEE 802.11a/n(HT20)/ac(VHT20): 5.745GHz-5.825GHz IEEE 802.11a/n(HT40)/ac(VHT40): 5.755GHz-5.795GHz IEEE 802.11ac(VHT80): 5.775GHz </td></tr> <tr> <td>Modulation Type:</td><td> 802.11a(OFDM): BPSK, QPSK, 16-QAM, 64-QAM 802.11n(OFDM): BPSK, QPSK, 16-QAM, 64-QAM 802.11ac (OFDM): BPSK, QPSK, 16-QAM, 64-QAM, 256-QAM </td></tr> <tr> <td>Antenna Designation:</td><td>Please refer to the Note 3.</td></tr> <tr> <td>Antenna Gain(dBi)</td><td>1.5</td></tr> </table> More details of EUT technical specification, please refer to the User Manual.	Operation Frequency:	IEEE 802.11a/n(HT20)/ac(VHT20): 5.180GHz-5.240GHz IEEE 802.11n(HT40)/ac(VHT40): 5.190GHz-5.230GHz IEEE 802.11ac(VHT80): 5.210GHz IEEE 802.11a/n(HT20)/ac(VHT20): 5.260GHz-5.320GHz IEEE 802.11 n(HT40)/ac(VHT40): 5.270GHz-5.310GHz IEEE 802.11ac(VHT80): 5.290GHz I IEEE 802.11a/n(HT20)/ac(VHT20): 5.500GHz-5.700GHz IEEE 802.11 n(HT40)/ac(VHT40): 5.510GHz-5.670GHz IEEE 802.11ac(VHT80): 5.530GHz-5.610GHz I IEEE 802.11a/n(HT20)/ac(VHT20): 5.745GHz-5.825GHz IEEE 802.11a/n(HT40)/ac(VHT40): 5.755GHz-5.795GHz IEEE 802.11ac(VHT80): 5.775GHz	Modulation Type:	802.11a(OFDM): BPSK, QPSK, 16-QAM, 64-QAM 802.11n(OFDM): BPSK, QPSK, 16-QAM, 64-QAM 802.11ac (OFDM): BPSK, QPSK, 16-QAM, 64-QAM, 256-QAM	Antenna Designation:	Please refer to the Note 3.	Antenna Gain(dBi)	1.5
Operation Frequency:	IEEE 802.11a/n(HT20)/ac(VHT20): 5.180GHz-5.240GHz IEEE 802.11n(HT40)/ac(VHT40): 5.190GHz-5.230GHz IEEE 802.11ac(VHT80): 5.210GHz IEEE 802.11a/n(HT20)/ac(VHT20): 5.260GHz-5.320GHz IEEE 802.11 n(HT40)/ac(VHT40): 5.270GHz-5.310GHz IEEE 802.11ac(VHT80): 5.290GHz I IEEE 802.11a/n(HT20)/ac(VHT20): 5.500GHz-5.700GHz IEEE 802.11 n(HT40)/ac(VHT40): 5.510GHz-5.670GHz IEEE 802.11ac(VHT80): 5.530GHz-5.610GHz I IEEE 802.11a/n(HT20)/ac(VHT20): 5.745GHz-5.825GHz IEEE 802.11a/n(HT40)/ac(VHT40): 5.755GHz-5.795GHz IEEE 802.11ac(VHT80): 5.775GHz								
Modulation Type:	802.11a(OFDM): BPSK, QPSK, 16-QAM, 64-QAM 802.11n(OFDM): BPSK, QPSK, 16-QAM, 64-QAM 802.11ac (OFDM): BPSK, QPSK, 16-QAM, 64-QAM, 256-QAM								
Antenna Designation:	Please refer to the Note 3.								
Antenna Gain(dBi)	1.5								
Test Channel	Please refer to the Note 2.								
Adapter	Model: HJ-PD66W-US Input: 100-240V, 50/60Hz, 1.5A Output: 5V, 3A 15W or 9V, 3A 27W or 12V, 3A 36W or 15V, 3A 45W or 20V, 3.25A 65W or 11V, 6A 66W MAX								
Battery	Capacity: 22000mAh Rated Voltage: 3.87V								
Hardware Version Number	G86_V1.1								
Software Version Number	TANK 01_20221103								
Connecting I/O Port(s)	Please refer to the Note 1.								

Note

1. For a more detailed features description, please refer to the manufacturer's specifications or the User Manual.

2.

Operation Frequency of channel			
5.180GHz-5.240GHz		5.500GHz-5.720GHz	
Channel	Frequency	Channel	Frequency
36	5180	100	5500
38	5190	102	5510
40	5200	104	5520
42	5210	106	5530
44	5220	108	5540
46	5230	110	5550
48	5240	112	5560
		116	5580
5.260GHz-5.320GHz		118	5590
Channel	Frequency	120	5600
52	5260	122	5610
54	5270	124	5620
56	5280	126	5630
58	5290	128	5640
60	5300	132	5660
62	5310	134	5670
64	5320	136	5680
		140	5700
5.745GHz-5.825GHz			
Channel	Frequency		
149	5745		
151	5755		
153	5765		
157	5785		
159	5795		
161	5805		
165	5825		

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Carrier Frequency Channel

5GHz:

For 802.11a/n(HT20)/ac(VHT20)			
Channel	Freq.(MHz)	Channel	Freq.(MHz)
36	5180	52	5260
40	5200	60	5300
48	5240	64	5320

For 802.11a/n(HT20)/ac(VHT20)			
Channel	Freq.(MHz)	Channel	Freq.(MHz)
100	5500	149	5745
116	5580	157	5785
140	5700	165	5825



For 802.11 n(HT40)/ac(VHT40)			
Channel	Freq.(MHz)	Channel	Freq.(MHz)
38	5190	54	5270
46	5230	62	5310

For 802.11 n(HT40)/ac(VHT40)			
Channel	Freq.(MHz)	Channel	Freq.(MHz)
102	5510	151	5755
110	5550	159	5795
134	5670		

For 802.11ac (VHT80)			
Channel	Freq.(MHz)	Channel	Freq.(MHz)
42	5210	58	5290

3. KDB 662911 D01 Multiple Transmitter Output v02r01

2) Directional Gain Calculations for In-Band Measurements

a) Basic methodology with NANT transmit antennas, each with the same directional gain G_{ANT} dBi, being driven by NANT transmitter outputs of equal power. Directional gain is to be computed

Ant	Brand	Model Name	Ant Type	Connector	Gain (dBi)	NOTE
1	Unihertz	TANK	PIFA antenna	N/A	1.5	WLAN Ant

Note: The antenna information refer the manufacturer provide report, applicable only to the tested sample identified in the report.



2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generated from EUT, the test system was pre-scanning tested based on the consideration of following EUT operation mode or test configuration mode which possibly have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Worst Mode	Description	Data Rate
Mode 1	TX IEEE 802.11a HT20 CH36&CH40&CH48	6 Mbps
Mode 2	TX IEEE 802.11a HT20 CH52&CH60&CH64	6 Mbps
Mode 3	TX IEEE 802.11a HT20 CH100&CH116&CH140	6 Mbps
Mode 4	TX IEEE 802.11a HT20 CH149&CH157&CH165	6 Mbps
Mode 5	TX IEEE 802.11n HT20 CH36&CH40&CH48	MCS 0
Mode 6	TX IEEE 802.11ac HT20 CH36&CH40&CH48	NSS1 MCS0
Mode 7	TX IEEE 802.11n HT20 CH52&CH60&CH64	MCS 0
Mode 8	TX IEEE 802.11ac HT20 CH52&CH60&CH64	NSS1 MCS0
Mode 9	TX IEEE 802.11n HT20 CH100&CH116&CH140	MCS 0
Mode 10	TX IEEE 802.11ac HT20 CH100&CH116&CH140	NSS1 MCS0
Mode 11	TX IEEE 802.11n HT20 CH149&CH157&CH165	MCS 0
Mode 12	TX IEEE 802.11ac HT20 CH149&CH157&CH165	NSS1 MCS0
Mode 13	TX IEEE 802.11n HT40 CH38&CH46	MCS 0
Mode 14	TX IEEE 802.11ac HT40 CH38&CH46	NSS1 MCS0
Mode 15	TX IEEE 802.11n HT40 CH54 &CH62	MCS 0
Mode 16	TX IEEE 802.11ac HT40 CH54 &CH62	NSS1 MCS0
Mode 17	TX IEEE 802.11n HT40 CH102&CH110&CH134	MCS 0
Mode 18	TX IEEE 802.11ac HT40 CH102&CH110&CH134	NSS1 MCS0
Mode 19	TX IEEE 802.11n HT40 CH151&CH159	MCS 0
Mode 20	TX IEEE 802.11ac HT40 CH151&CH159	NSS1 MCS0
Mode 21	TX IEEE 802.11ac HT80 CH42	NSS1 MCS0
Mode 22	TX IEEE 802.11ac HT80 CH58	NSS1 MCS0
Mode 23	TX IEEE 802.11ac HT80 CH106&122	NSS1 MCS0
Mode 24	TX IEEE 802.11ac HT80 CH155	NSS1 MCS0

- Note: (1) The measurements are performed at the highest, middle, lowest available channels.
(2) The measurements are performed at all Bit Rate of Transmitter, the worst data was reported.
(3) We have been tested for all available U.S. voltage and frequencies (For 120V, 50/60Hz and 240V, 50/60Hz) for which the device is capable of operation.
(4) The battery is fully-charged during the radiated and RF conducted test.



AC Conducted Emission

Test Case	
AC Conducted Emission	Mode 25: TX Mode

2.3 TEST SOFTWARE AND POWER LEVEL

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level.

RF Function	Type	Mode Or Modulation type	ANT Gain(dBi)	ANT_A Power Class	Software For Testing
WIFI(5G)	5G WIFI Band1 (5150MHz-5250MHz)	802.11a	1.5	20	Engineering mode
		802.11n(HT20)		18	
		802.11n(HT40)		18	
		802.11ac(VHT20)		15	
		802.11ac(VHT40)		15	
		802.11ac(VHT80)		15	

RF Function	Type	Mode Or Modulation type	ANT Gain(dBi)	ANT_A Power Class	Software For Testing
WIFI(5G)	5G WIFI Band2 (5250MHz-5350MHz)	802.11a	1.5	15	Engineering mode
		802.11n(HT20)		15.5	
		802.11n(HT40)		15.5	
		802.11ac(VHT20)		12.5	
		802.11ac(VHT40)		12.5	
		802.11ac(VHT80)		12.5	

RF Function	Type	Mode Or Modulation type	ANT Gain(dBi)	ANT_A Power Class	Software For Testing
WIFI(5G)	5G WIFI Band3 (5470MHz-5725MHz)	802.11a	1.5	15	Engineering mode
		802.11n(HT20)		15.5	
		802.11n(HT40)		15.5	
		802.11ac(VHT20)		12.5	
		802.11ac(VHT40)		12.5	
		802.11ac(VHT80)		12.5	

RF Function	Type	Mode Or Modulation type	ANT Gain(dBi)	ANT_A Power Class	Software For Testing
WIFI(5G)	5G WIFI Band4 (5725MHz-5850MHz)	802.11a	1.5	15	Engineering mode
		802.11n(HT20)		15	
		802.11n(HT40)		15	
		802.11ac(VHT20)		15	
		802.11ac(VHT40)		15	
		802.11ac(VHT80)		15	



2.4 DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Accessories Equipment

Description	Manufacturer	Model	S/N	Rating
Type-C Cable	N/A	N/A	N/A	1m
Adapter	Huajin	HJ-PD66W-EU	N/A	Input: 100-240V ~ 50/60Hz 1.5A Output: 5V@3A 9V@3A 12V@3A 15V@3A 20V@3A 11V@6A

Auxiliary Equipment

Description	Manufacturer	Model	S/N	Rating
Earphone	N/A	39630078	N/A	N/A

Note:

(1) For detachable type I/O cable should be specified the length in cm in 『Length』 column.



2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

Conducted Emission

Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Until
EMI Test Receiver	R&S	ESU	100372	2022.04.12	2023.04.11
LISN	COM-POWER	LI-115	02032	2022.04.13	2023.04.12
LISN	SCHWARZBECK	NNLK 8121	00847	2022.08.19	2023.08.18
CE Cable	N.A	C01	N.A	2022.05.05	2023.05.04
Transient Limiter	CYBERTEK	EM5010A	E2250100049	2022.06.02	2023.06.01
Temperature & Humidity	KTJ	TA218B	N.A	2022.05.05	2023.05.04
Testing Software	EMC-I_V1.4.0.3_SKET				

Radiation Test equipment

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
EMI Test Receiver	R&S	ESU	100372	2022.04.12	2023.04.11
Spectrum Analyzer	Kesight	N9010B	MY60242508	2022.04.29	2023.04.28
Bilog Antenna	SCHAFFNER	CBL6112B	270S	2022.06.05	2025.06.04
Horn Antenna(18GHz)	SCHWARZBECK	3115	10SL0060	2022.06.02	2025.06.01
Horn Antenna(40 GHz)	A-INFO	LB-180400-KF	J211060273	2022.03.28	2025.03.27
Pre-amplifier(3GHz)	HP	8447D	2727A05655	2022.04.11	2023.04.10
Pre-amplifier(26.5G)	Agilent	8449B	3008A4722	2022.04.12	2023.04.11
Pre-amplifier(40 GHz)	com-mw	LNPA_18-40-01	18050001	2022.06.08	2023.06.07
RE Cable (9K-1G)	N.A	R01	N.A	2022.05.05	2023.05.04
RE Cable (1-26G)	N.A	R02	N.A	2022.05.05	2023.05.04
Temperature & Humidity	KTJ	TA218B	N.A	2022.05.05	2023.05.04
Testing Software	EMC-I_V1.4.0.3_SKET				

RF Connected Test equipment

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
Signal Generator	Keysight	N5182B	MY59100717	2022.04.30	2023.04.29
Signal Analyzer	Keysight	N9010B	MY60242508	2022.04.29	2023.04.28
Temperature & Humidity	KTJ	TA218B	N/A	2022.05.05	2023.05.04
Temperature& Humidity test chamber	AISRY	LX-1000L	171200018	2022.05.10	2023.05.09
Attenuator	eastsheep	90db	N/A	2022.04.29	2023.04.28
Testing Software	MTS 8310_2.0.0.0_MWRF-TEST				



3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Class B (dBuV)		Standard
	Quasi-peak	Average	
0.15 -0.5	66 - 56 *	56 - 46 *	CISPR
0.50 -5.0	56.00	46.00	CISPR
5.0 -30.0	60.00	50.00	CISPR

0.15 -0.5	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	56.00	46.00	FCC
5.0 -30.0	60.00	50.00	FCC

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of “ * ” marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz


3.1.2 TEST PROCEDURE

- The EUT is 0.8 m from the horizontal ground plane and 0.4 m from the vertical ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments are powered from additional LISN(s). The LISN provides 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN is at least 80 cm from the nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.1.3 DEVIATION FROM TEST STANDARD

No deviation

3.1.4 TEST SETUP



Note: 1. Support units were connected to second LISN.

2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes support units.


3.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.



3.1.6 TEST RESULTS


Project: LGT22J019	Test Engineer: Dylan.shi
EUT: Smart phone	Temperature: 24.1℃
M/N: TANK 01	Humidity: 42%RH
Test Voltage: AC 120V/60Hz	Test Data: 2022-10-19
Test Mode: TX 5G WIFI	
Note:	



No.	Frequency	Reading dBuV	Factor dB	Level dBuV	Limit dBuV	Margin dB	Detector	Polar
1*	846.000kHz	30.08	10.52	40.60	56.00	-15.40	PK	L1
2*	10.522MHz	17.13	10.96	28.09	60.00	-31.91	PK	L1
3*	19.010MHz	14.35	11.09	25.44	60.00	-34.56	PK	L1
4*	910.000kHz	18.06	10.52	28.58	46.00	-17.42	AV	L1
5*	10.710MHz	7.29	10.97	18.26	50.00	-31.74	AV	L1
6*	18.906MHz	5.16	11.09	16.25	50.00	-33.75	AV	L1



Project: LGT22J019	Test Engineer: Dylan.shi
EUT: Smart phone	Temperature: 24.1℃
M/N: TANK 01	Humidity: 42%RH
Test Voltage: AC 120V/60Hz	Test Data: 2022-10-19
Test Mode: TX 5G WIFI	
Note:	



No.	Frequency	Reading dBuV	Factor dB	Level dBuV	Limit dBuV	Margin dB	Detector	Polar
1*	278.000kHz	28.52	10.50	39.02	60.88	-21.86	PK	N
2*	7.570MHz	18.88	10.90	29.78	60.00	-30.22	PK	N
3*	13.922MHz	15.73	11.02	26.75	60.00	-33.25	PK	N
4*	202.000kHz	18.49	10.50	28.99	53.53	-24.54	AV	N
5*	7.602MHz	10.72	10.90	21.62	50.00	-28.38	AV	N
6*	13.910MHz	7.16	11.02	18.18	50.00	-31.82	AV	N



3.2 RADIATED EMISSION AND (BANDEGE) MEASUREMENT

3.2.1 RADIATED EMISSION LIMITS (Frequency Range 9kHz-1000MHz)

In case the emission fall within the restricted band specified on 15.407(b)7&15.205/209(a), then the limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	68.2	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15E.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

LIMITS OF RESTRICTED FREQUENCY BANDS

FREQUENCY (MHz)	FREQUENCY (MHz)	FREQUENCY (MHz)	FREQUENCY (GHz)
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	Above 38.6
13.36-13.41			

Note: In case the emission radiated emission above 1000MHz fall within the restricted band the restricted frequency bands, the peak limit is 74 dBuV/m.



LIMITS OF EMISSIONS OUTSIDE OF THE FREQUENCY BANDS

Undesirable emission limits. Except as shown in paragraph (b)(7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

- (1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (4) For transmitters operating in the 5.725-5.85 GHz band:
 - (i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

Note: dBuV/m(at 3M) = EIRP(dBm) + 95.3.

Peak Limit = -27dBm/MHz + 95.3 = 68.3 dBuV/m.

Spectrum Parameter	Setting
Attenuation	Auto
Detector	Peak
Start Frequency	1000 MHz(Peak/AV)
Stop Frequency	10th carrier harmonic (Peak/AV)
RB / VB (emission in restricted band)	1 MHz / 1 MHz, AV=1 MHz /3 MHz

For Band edge

Spectrum Parameter	Setting
Detector	Peak
RB / VB (emission in restricted band)	1 MHz / 1 MHz, AV=1 MHz /3 MHz

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~90kHz / RB 200Hz for PK & AV
Start ~ Stop Frequency	90kHz~110kHz / RB 200Hz for QP
Start ~ Stop Frequency	110kHz~490kHz / RB 200Hz for PK & AV
Start ~ Stop Frequency	490kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP



3.2.2 TEST PROCEDURE

- The measuring distance at 3 m shall be used for measurements at frequency 0.009MHz up to 1GHz, and above 1GHz.
- The EUT was placed on the top of a rotating table 0.8 m (above 1GHz is 1.5 m) above the ground at a 3 m anechoic chamber test site. The table was rotated 360 degree to determine the position of the highest radiation.
- The height of the equipment shall be 0.8 m (above 1GHz is 1.5 m); the height of the test antenna shall vary between 1 m to 4 m. Horizontal and vertical polarization of the antenna are set to make the measurement.
- The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and QuasiPeak detector mode will be re-measured.
- If the Peak Mode measured value is compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and no additional QP Mode measurement was performed.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported.

3.2.2 DEVIATION FROM TEST STANDARD


No deviation

3.2.3 TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz





3.2.4 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

3.2.5 FIELD STRENGTH CALCULATION

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CL - AG$$

Where

FS = Field Strength

CL = Cable Attenuation Factor (Cable Loss)

RA = Reading Amplitude

AG = Amplifier Gain

AF = Antenna Factor

For example


Frequency (MHz)	FS (dB μ V/m)	RA (dB μ V/m)	AF (dB)	CL (dB)	AG (dB)	Factor (dB)
300	40	58.1	12.2	1.6	31.9	-18.1

$$\text{Factor} = \text{AF} + \text{CL} - \text{AG}$$



3.2.6 TEST RESULTS


Project: LGT22J019	Test Engineer: Dylan.shi
EUT: Smart phone	Temperature: 28.4°C
M/N: TANK 01	Humidity: 42%RH
Test Voltage: Power by Battery	Test Data: 2022-10-25
Test Mode: TX 5G WIFI	
Note:	



No.	Frequency	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	32.668MHz	4.83	12.97	17.80	40.00	-22.20	PK	Hor
2*	51.098MHz	4.01	13.70	17.71	40.00	-22.29	PK	Hor
3*	161.556MHz	3.50	14.16	17.66	43.50	-25.84	PK	Hor
4*	415.454MHz	3.93	17.48	21.41	46.00	-24.59	PK	Hor
5*	622.306MHz	5.32	22.64	27.96	46.00	-18.04	PK	Hor
6*	987.390MHz	5.29	27.86	33.15	54.00	-20.85	PK	Hor




Project: LGT22J019	Test Engineer: Dylan.shi
EUT: Smart phone	Temperature: 28.4°C
M/N: TANK 01	Humidity: 42%RH
Test Voltage: Power by Battery	Test Data: 2022-10-25
Test Mode: TX 5G WIFI	
Note:	



No.	Frequency	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	46.975MHz	4.14	13.73	17.87	40.00	-22.13	PK	Ver
2*	110.268MHz	4.56	11.19	15.75	43.50	-27.75	PK	Ver
3*	141.671MHz	4.55	13.50	18.05	43.50	-25.45	PK	Ver
4*	446.373MHz	4.39	18.40	22.79	46.00	-23.21	PK	Ver
5*	717.488MHz	6.79	24.03	30.82	46.00	-15.18	PK	Ver
6*	942.043MHz	5.67	27.55	33.22	46.00	-12.78	PK	Ver




Project: LGT22J019	Test Engineer: Dylan.shi
EUT: Smart phone	Humidity: 41%RH
Temperature: 24.3℃	Test Voltage: Power by Battery
M/N: TANK 01	Test Data: 2022-10-26
Test Mode: 802.11a 5180	
Note:	



No.	Frequency	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	5.186GHz	/	/	/	/	/	PK	Hor
2*	10.356GHz	58.81	-0.18	58.63	74.00	-15.37	PK	Hor
3*	14.296GHz	49.98	5.90	55.88	74.00	-18.12	PK	Hor
4*	17.898GHz	49.86	8.45	58.31	74.00	-15.69	PK	Hor
5*	10.365GHz	49.82	-0.15	49.67	54.00	-4.33	AV	Hor
6*	14.296GHz	39.50	5.90	45.40	54.00	-8.60	AV	Hor
7*	17.898GHz	40.05	8.45	48.50	54.00	-5.50	AV	Hor




Project: LGT22J019	Test Engineer: Dylan.shi
EUT: Smart phone	Humidity: 41%RH
Temperature: 24.3℃	Test Voltage: Power by Battery
M/N: TANK 01	Test Data: 2022-10-26
Test Mode: 802.11a 5180	
Note:	



No.	Frequency	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	2.615GHz	56.83	-10.38	46.45	74.00	-27.55	PK	Ver
!2*	5.178GHz	/	/	/	/	/	PK	Ver
3*	10.363GHz	57.85	-0.16	57.69	74.00	-16.30	PK	Ver
4*	17.896GHz	45.95	8.45	54.40	74.00	-19.60	PK	Ver
5*	2.615GHz	46.68	-10.38	36.30	54.00	-17.70	AV	Ver
6*	10.363GHz	50.57	-0.16	50.41	54.00	-3.60	AV	Ver
7*	17.896GHz	39.15	8.45	47.60	54.00	-6.40	AV	Ver




Project: LGT22J019	Test Engineer: Dylan.shi
EUT: Smart phone	Humidity: 41%RH
Temperature: 24.3°C	Test Voltage: Power by Battery
M/N: TANK 01	Test Data: 2022-10-26
Test Mode: 802.11a 5200	
Note:	



No.	Frequency	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	5.205GHz	/	/	/	/	/	PK	Hor
2*	10.397GHz	55.68	-0.07	55.61	74.00	-18.39	PK	Hor
3*	14.305GHz	50.03	5.90	55.93	74.00	-18.07	PK	Hor
4*	17.951GHz	49.06	8.49	57.55	74.00	-16.45	PK	Hor
5*	10.403GHz	47.51	-0.05	47.46	54.00	-6.54	AV	Hor
6*	14.305GHz	38.90	5.90	44.80	54.00	-9.20	AV	Hor
7*	17.951GHz	39.61	8.49	48.10	54.00	-5.90	AV	Hor




Project: LGT22J019	Test Engineer: Dylan.shi
EUT: Smart phone	Humidity: 41%RH
Temperature: 24.3℃	Test Voltage: Power by Battery
M/N: TANK 01	Test Data: 2022-10-26
Test Mode: 802.11a 5200	
Note:	



No.	Frequency	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	2.615GHz	56.03	-10.38	45.65	74.00	-28.35	PK	Ver
2*	5.205GHz	/	/	/	/	/	PK	Ver
3*	10.403GHz	59.96	-0.05	59.91	74.00	-14.09	PK	Ver
4*	17.915GHz	47.81	8.46	56.27	74.00	-17.73	PK	Ver
5*	2.615GHz	45.58	-10.38	35.20	54.00	-18.80	AV	Ver
6*	10.399GHz	50.44	-0.06	50.38	54.00	-3.62	AV	Ver
7*	17.915GHz	39.54	8.46	48.00	54.00	-6.00	AV	Ver




Project: LGT22J019	Test Engineer: Dylan.shi
EUT: Smart phone	Humidity: 41%RH
Temperature: 24.3°C	Test Voltage: Power by Battery
M/N: TANK 01	Test Data: 2022-10-26
Test Mode: 802.11a 5240	
Note:	



No.	Frequency	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
!1*	5.246GHz	/	/	/	/	/	PK	Hor
2*	10.484GHz	56.44	0.18	56.62	74.00	-17.38	PK	Hor
3*	14.405GHz	48.39	5.91	54.30	74.00	-19.70	PK	Hor
4*	17.936GHz	48.05	8.48	56.53	74.00	-17.47	PK	Hor
5*	10.486GHz	47.89	0.19	48.08	54.00	-5.92	AV	Hor
6*	14.405GHz	38.99	5.91	44.90	54.00	-9.10	AV	Hor
7*	17.936GHz	38.42	8.48	46.90	54.00	-7.10	AV	Hor




Project: LGT22J019	Test Engineer: Dylan.shi
EUT: Smart phone	Humidity: 41%RH
Temperature: 24.3℃	Test Voltage: Power by Battery
M/N: TANK 01	Test Data: 2022-10-26
Test Mode: 802.11a 5240	
Note:	



No.	Frequency	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	5.237GHz	/	/	/	/	/	PK	Ver
2*	10.482GHz	54.22	0.17	54.39	74.00	-19.61	PK	Ver
3*	14.428GHz	48.37	5.91	54.28	74.00	-19.72	PK	Ver
4*	17.941GHz	47.70	8.48	56.18	74.00	-17.82	PK	Ver
5*	10.484GHz	44.99	0.18	45.17	54.00	-8.83	AV	Ver
6*	14.428GHz	38.49	5.91	44.40	54.00	-9.60	AV	Ver
7*	17.941GHz	38.92	8.48	47.40	54.00	-6.60	AV	Ver




Project: LGT22J019	Test Engineer: Dylan.shi
EUT: Smart phone	Humidity: 41%RH
Temperature: 24.3°C	Test Voltage: Power by Battery
M/N: TANK 01	Test Data: 2022-10-26
Test Mode: 802.11a 5260	
Note:	



No.	Frequency	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	5.259GHz	/	/	/	/	/	PK	Hor
2*	10.516GHz	55.19	0.27	55.46	74.00	-18.54	PK	Hor
3*	14.407GHz	48.60	5.91	54.51	74.00	-19.49	PK	Hor
4*	17.928GHz	48.70	8.47	57.17	74.00	-16.83	PK	Hor
5*	10.522GHz	45.00	0.29	45.29	54.00	-8.71	AV	Hor
6*	14.407GHz	38.79	5.91	44.70	54.00	-9.30	AV	Hor
7*	17.928GHz	38.13	8.47	46.60	54.00	-7.40	AV	Hor




Project: LGT22J019	Test Engineer: Dylan.shi
EUT: Smart phone	Humidity: 41%RH
Temperature: 24.3℃	Test Voltage: Power by Battery
M/N: TANK 01	Test Data: 2022-10-26
Test Mode: 802.11a 5260	
Note:	



No.	Frequency	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	5.259GHz	/	/	/	/	/	PK	Ver
2*	10.520GHz	52.63	0.28	52.91	74.00	-21.09	PK	Ver
3*	14.719GHz	49.53	5.93	55.46	74.00	-18.54	PK	Ver
4*	17.917GHz	49.45	8.46	57.91	74.00	-16.09	PK	Ver
5*	10.518GHz	43.96	0.28	44.24	54.00	-9.76	AV	Ver
6*	14.719GHz	38.57	5.93	44.50	54.00	-9.50	AV	Ver
7*	17.917GHz	39.54	8.46	48.00	54.00	-6.00	AV	Ver




Project: LGT22J019	Test Engineer: Dylan.shi
EUT: Smart phone	Humidity: 41%RH
Temperature: 24.3°C	Test Voltage: Power by Battery
M/N: TANK 01	Test Data: 2022-10-26
Test Mode: 802.11a 5300	
Note:	



No.	Frequency	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	5.305GHz	/	/	/	/	/	PK	Hor
2*	10.599GHz	54.82	0.50	55.32	74.00	-18.68	PK	Hor
3*	14.400GHz	48.26	5.91	54.17	74.00	-19.83	PK	Hor
4*	17.943GHz	48.38	8.48	56.86	74.00	-17.14	PK	Hor
5*	10.607GHz	45.13	0.53	45.66	54.00	-8.34	AV	Hor
6*	14.400GHz	38.89	5.91	44.80	54.00	-9.20	AV	Hor
7*	17.943GHz	38.82	8.48	47.30	54.00	-6.70	AV	Hor




Project: LGT22J019	Test Engineer: Dylan.shi
EUT: Smart phone	Humidity: 41%RH
Temperature: 24.3℃	Test Voltage: Power by Battery
M/N: TANK 01	Test Data: 2022-10-26
Test Mode: 802.11a 5300	
Note:	



No.	Frequency	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	5.297GHz	/	/	/	/	/	PK	Ver
2*	10.597GHz	55.38	0.50	55.88	74.00	-18.12	PK	Ver
3*	14.417GHz	49.27	5.91	55.18	74.00	-18.82	PK	Ver
4*	17.781GHz	49.81	8.37	58.18	74.00	-15.82	PK	Ver
5*	10.601GHz	46.09	0.51	46.60	54.00	-7.40	AV	Ver
6*	14.417GHz	40.39	5.91	46.30	54.00	-7.70	AV	Ver
7*	17.781GHz	39.03	8.37	47.40	54.00	-6.60	AV	Ver




Project: LGT22J019	Test Engineer: Dylan.shi
EUT: Smart phone	Humidity: 41%RH
Temperature: 24.3°C	Test Voltage: Power by Battery
M/N: TANK 01	Test Data: 2022-10-26
Test Mode: 802.11a 5320	
Note:	



No.	Frequency	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
!1*	5.322GHz	/	/	/	/	/	PK	Hor
2*	10.643GHz	53.26	0.63	53.89	74.00	-20.11	PK	Hor
3*	14.411GHz	48.45	5.91	54.36	74.00	-19.64	PK	Hor
4*	17.785GHz	48.14	8.37	56.51	74.00	-17.49	PK	Hor
5*	10.639GHz	44.08	0.62	44.70	54.00	-9.30	AV	Hor
6*	14.411GHz	39.79	5.91	45.70	54.00	-8.30	AV	Hor
7*	17.785GHz	38.93	8.37	47.30	54.00	-6.70	AV	Hor




Project: LGT22J019	Test Engineer: Dylan.shi
EUT: Smart phone	Humidity: 41%RH
Temperature: 24.3℃	Test Voltage: Power by Battery
M/N: TANK 01	Test Data: 2022-10-26
Test Mode: 802.11a 5320	
Note:	



No.	Frequency	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	5.316GHz	/	/	/	/	/	PK	Ver
2*	10.645GHz	55.02	0.63	55.65	74.00	-18.35	PK	Ver
3*	14.417GHz	49.88	5.91	55.79	74.00	-18.21	PK	Ver
4*	17.972GHz	49.49	8.50	57.99	74.00	-16.01	PK	Ver
5*	10.643GHz	45.56	0.63	46.19	54.00	-7.81	AV	Ver
6*	14.417GHz	40.29	5.91	46.20	54.00	-7.80	AV	Ver
7*	17.972GHz	39.00	8.50	47.50	54.00	-6.50	AV	Ver




Project: LGT22J019	Test Engineer: Dylan.shi
EUT: Smart phone	Humidity: 41%RH
Temperature: 24.3℃	Test Voltage: Power by Battery
M/N: TANK 01	Test Data: 2022-10-26
Test Mode: 802.11n40 5510	
Note:	



No.	Frequency	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	5.516GHz	/	/	/	/	/	PK	Hor
2*	8.931GHz	55.21	-1.37	53.84	74.00	-20.16	PK	Hor
3*	11.022GHz	53.86	1.64	55.50	74.00	-18.50	PK	Hor
4*	17.951GHz	49.60	8.49	58.09	74.00	-15.91	PK	Hor
5*	8.931GHz	44.87	-1.37	43.50	54.00	-10.50	AV	Hor
6*	11.024GHz	44.40	1.64	46.04	54.00	-7.96	AV	Hor
7*	17.951GHz	39.01	8.49	47.50	54.00	-6.50	AV	Hor




Project: LGT22J019	Test Engineer: Dylan.shi
EUT: Smart phone	Humidity: 41%RH
Temperature: 24.3℃	Test Voltage: Power by Battery
M/N: TANK 01	Test Data: 2022-10-26
Test Mode: 802.11n40 5510	
Note:	



No.	Frequency	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
!1*	5.514GHz	/	/	/	/	/	PK	Ver
2*	8.933GHz	55.20	-1.36	53.84	74.00	-20.16	PK	Ver
3*	11.017GHz	52.84	1.64	54.48	74.00	-19.52	PK	Ver
4*	17.966GHz	49.71	8.50	58.21	74.00	-15.79	PK	Ver
5*	8.933GHz	45.16	-1.36	43.80	54.00	-10.20	AV	Ver
6*	11.032GHz	43.09	1.65	44.74	54.00	-9.26	AV	Ver
7*	17.966GHz	39.20	8.50	47.70	54.00	-6.30	AV	Ver




Project: LGT22J019	Test Engineer: Dylan.shi
EUT: Smart phone	Humidity: 41%RH
Temperature: 24.3℃	Test Voltage: Power by Battery
M/N: TANK 01	Test Data: 2022-10-26
Test Mode: 802.11n40 5550	
Note:	



No.	Frequency	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	5.548GHz	/	/	/	/	/	PK	Hor
2*	9.005GHz	54.91	-1.17	53.74	74.00	-20.26	PK	Hor
3*	11.096GHz	55.05	1.69	56.74	74.00	-17.26	PK	Hor
4*	17.792GHz	48.67	8.37	57.04	74.00	-16.96	PK	Hor
5*	9.005GHz	44.47	-1.17	43.30	54.00	-10.70	AV	Hor
6*	11.100GHz	46.83	1.69	48.52	54.00	-5.48	AV	Hor
7*	17.792GHz	39.03	8.37	47.40	54.00	-6.60	AV	Hor




Project: LGT22J019	Test Engineer: Dylan.shi
EUT: Smart phone	Humidity: 41%RH
Temperature: 24.3℃	Test Voltage: Power by Battery
M/N: TANK 01	Test Data: 2022-10-26
Test Mode: 802.11n40 5550	
Note:	



No.	Frequency	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
!1*	5.550GHz	/	/	/	/	/	PK	Ver
2*	9.018GHz	54.78	-1.17	53.61	74.00	-20.39	PK	Ver
3*	11.115GHz	55.04	1.70	56.74	74.00	-17.26	PK	Ver
4*	17.909GHz	48.84	8.46	57.30	74.00	-16.70	PK	Ver
5*	9.018GHz	44.27	-1.17	43.10	54.00	-10.90	AV	Ver
6*	11.100GHz	46.49	1.69	48.18	54.00	-5.82	AV	Ver
7*	17.909GHz	39.24	8.46	47.70	54.00	-6.30	AV	Ver




Project: LGT22J019	Test Engineer: Dylan.shi
EUT: Smart phone	Humidity: 41%RH
Temperature: 24.3°C	Test Voltage: Power by Battery
M/N: TANK 01	Test Data: 2022-10-26
Test Mode: 802.11n40 5670	
Note:	



No.	Frequency	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	5.675GHz	/	/	/	/	/	PK	Hor
2*	8.999GHz	53.21	-1.17	52.04	74.00	-21.96	PK	Hor
3*	11.340GHz	56.55	1.83	58.38	74.00	-15.62	PK	Hor
4*	17.898GHz	48.93	8.45	57.38	74.00	-16.62	PK	Hor
5*	8.999GHz	44.27	-1.17	43.10	54.00	-10.90	AV	Hor
6*	11.340GHz	47.47	1.83	49.30	54.00	-4.70	AV	Hor
7*	17.898GHz	38.15	8.45	46.60	54.00	-7.40	AV	Hor




Project: LGT22J019	Test Engineer: Dylan.shi
EUT: Smart phone	Humidity: 41%RH
Temperature: 24.3℃	Test Voltage: Power by Battery
M/N: TANK 01	Test Data: 2022-10-26
Test Mode: 802.11n40 5670	
Note:	



No.	Frequency	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	5.688GHz	/	/	/	/	/	PK	Ver
2*	9.449GHz	54.42	-1.17	53.25	74.00	-20.75	PK	Ver
3*	11.347GHz	57.89	1.83	59.72	74.00	-14.28	PK	Ver
4*	17.964GHz	49.52	8.49	58.01	74.00	-15.99	PK	Ver
5*	9.449GHz	42.97	-1.17	41.80	54.00	-12.20	AV	Ver
6*	11.349GHz	48.91	1.84	50.75	54.00	-3.25	AV	Ver
7*	17.964GHz	38.91	8.49	47.40	54.00	-6.60	AV	Ver




Project: LGT22J019	Test Engineer: Dylan.shi
EUT: Smart phone	Humidity: 41%RH
Temperature: 24.3°C	Test Voltage: Power by Battery
M/N: TANK 01	Test Data: 2022-10-26
Test Mode: 802.11n40 5755	
Note:	



No.	Frequency	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	5.758GHz	/	/	/	/	/	PK	Hor
2*	8.952GHz	54.79	-1.31	53.48	74.00	-20.52	PK	Hor
3*	11.508GHz	56.44	1.93	58.37	74.00	-15.63	PK	Hor
4*	17.881GHz	49.63	8.44	58.07	74.00	-15.93	PK	Hor
5*	8.952GHz	44.11	-1.31	42.80	54.00	-11.20	AV	Hor
6*	11.510GHz	47.25	1.93	49.18	54.00	-4.82	AV	Hor
7*	17.881GHz	39.46	8.44	47.90	54.00	-6.10	AV	Hor




Project: LGT22J019	Test Engineer: Dylan.shi
EUT: Smart phone	Humidity: 41%RH
Temperature: 24.3℃	Test Voltage: Power by Battery
M/N: TANK 01	Test Data: 2022-10-26
Test Mode: 802.11n40 5755	
Note:	



No.	Frequency	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
!1*	5.754GHz	/	/	/	/	/	PK	Ver
2*	8.926GHz	54.61	-1.38	53.23	74.00	-20.77	PK	Ver
3*	11.508GHz	56.74	1.93	58.67	74.00	-15.33	PK	Ver
4*	17.934GHz	48.81	8.47	57.28	74.00	-16.72	PK	Ver
5*	8.926GHz	44.88	-1.38	43.50	54.00	-10.50	AV	Ver
6*	11.506GHz	48.93	1.93	50.86	54.00	-3.14	AV	Ver
7*	17.934GHz	39.33	8.47	47.80	54.00	-6.20	AV	Ver




Project: LGT22J019	Test Engineer: Dylan.shi
EUT: Smart phone	Humidity: 41%RH
Temperature: 24.3℃	Test Voltage: Power by Battery
M/N: TANK 01	Test Data: 2022-10-26
Test Mode: 802.11n40 5795	
Note:	



No.	Frequency	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	5.798GHz	/	/	/	/	/	PK	Hor
2*	8.771GHz	54.16	-1.82	52.34	74.00	-21.66	PK	Hor
3*	11.574GHz	55.34	1.97	57.31	74.00	-16.69	PK	Hor
4*	17.913GHz	49.33	8.46	57.79	74.00	-16.21	PK	Hor
5*	8.771GHz	43.62	-1.82	41.80	54.00	-12.20	AV	Hor
6*	11.580GHz	46.00	1.97	47.97	54.00	-6.03	AV	Hor
7*	17.913GHz	38.84	8.46	47.30	54.00	-6.70	AV	Hor



Project: LGT22J019	Test Engineer: Dylan.shi
EUT: Smart phone	Humidity: 41%RH
Temperature: 24.3℃	Test Voltage: Power by Battery
M/N: TANK 01	Test Data: 2022-10-26
Test Mode: 802.11n40 5795	
Note:	




No.	Frequency	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	5.790GHz	/	/	/	/	/	PK	Ver
2*	8.890GHz	54.86	-1.48	53.38	74.00	-20.62	PK	Ver
3*	11.585GHz	52.85	1.97	54.82	74.00	-19.18	PK	Ver
4*	17.783GHz	50.49	8.37	58.86	74.00	-15.14	PK	Ver
5*	8.890GHz	44.48	-1.48	43.00	54.00	-11.00	AV	Ver
6*	11.593GHz	45.24	1.98	47.22	54.00	-6.78	AV	Ver
7*	17.783GHz	39.03	8.37	47.40	54.00	-6.60	AV	Ver



3.2.7 TEST RESULTS(Band edge Requirements)


Project: LGT22J019	Test Engineer: Dylan.shi
EUT: Smart phone	Humidity: 48%RH
Temperature: 25.5℃	Test Voltage: Power by Battery
M/N: TANK 01	Test Data: 2022-10-27
Test Mode: 802.11a 5180	
Note:	



No.	Frequency	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	4.820GHz	58.30	-6.00	52.30	74.00	-21.70	PK	Hor
2*	5.150GHz	57.72	-6.62	51.10	74.00	-22.90	PK	Hor




Project: LGT22J019	Test Engineer: Dylan.shi
EUT: Smart phone	Humidity: 48%RH
Temperature: 25.5℃	Test Voltage: Power by Battery
M/N: TANK 01	Test Data: 2022-10-27
Test Mode: 802.11a 5180	
Note:	



No.	Frequency	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	4.772GHz	58.22	-5.96	52.26	74.00	-21.74	PK	Ver
2*	5.150GHz	57.12	-6.62	50.50	74.00	-23.50	PK	Ver




Project: LGT22J019	Test Engineer: Dylan.shi
EUT: Smart phone	Humidity: 48%RH
Temperature: 25.5℃	Test Voltage: Power by Battery
M/N: TANK 01	Test Data: 2022-10-27
Test Mode: 802.11a 5240	
Note:	



No.	Frequency	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	5.350GHz	55.56	-7.26	48.30	74.00	-25.70	PK	Hor
2*	5.364GHz	58.36	-7.31	51.05	74.00	-22.95	PK	Hor




Project: LGT22J019	Test Engineer: Dylan.shi
EUT: Smart phone	Humidity: 48%RH
Temperature: 25.5℃	Test Voltage: Power by Battery
M/N: TANK 01	Test Data: 2022-10-27
Test Mode: 802.11a 5240	
Note:	



No.	Frequency	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	5.350GHz	56.06	-7.26	48.80	74.00	-25.20	PK	Ver
2*	5.358GHz	58.30	-7.28	51.02	74.00	-22.98	PK	Ver




Project: LGT22J019	Test Engineer: Dylan.shi
EUT: Smart phone	Humidity: 48%RH
Temperature: 25.5°C	Test Voltage: Power by Battery
M/N: TANK 01	Test Data: 2022-10-27
Test Mode: 802.11a 5260	
Note:	



No.	Frequency	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	4.829GHz	57.99	-6.01	51.98	74.00	-22.00	PK	Hor
2*	5.150GHz	55.92	-6.62	49.30	74.00	-24.70	PK	Hor




Project: LGT22J019	Test Engineer: Dylan.shi
EUT: Smart phone	Humidity: 48%RH
Temperature: 25.5℃	Test Voltage: Power by Battery
M/N: TANK 01	Test Data: 2022-10-27
Test Mode: 802.11a 5260	
Note:	



No.	Frequency	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	4.817GHz	58.00	-6.00	52.00	74.00	-22.00	PK	Ver
2*	5.150GHz	57.42	-6.62	50.80	74.00	-23.20	PK	Ver




Project: LGT22J019	Test Engineer: Dylan.shi
EUT: Smart phone	Humidity: 48%RH
Temperature: 25.5°C	Test Voltage: Power by Battery
M/N: TANK 01	Test Data: 2022-10-27
Test Mode: 802.11a 5320	
Note:	



No.	Frequency	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	5.350GHz	55.86	-7.26	48.60	74.00	-25.40	PK	Hor
2*	5.359GHz	57.95	-7.29	50.66	74.00	-23.34	PK	Hor




Project: LGT22J019	Test Engineer: Dylan.shi
EUT: Smart phone	Humidity: 48%RH
Temperature: 25.5°C	Test Voltage: Power by Battery
M/N: TANK 01	Test Data: 2022-10-27
Test Mode: 802.11a 5320	
Note:	



No.	Frequency	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	5.350GHz	55.26	-7.26	48.00	74.00	-26.00	PK	Ver
2*	5.366GHz	58.29	-7.31	50.98	74.00	-23.02	PK	Ver




Project: LGT22J019	Test Engineer: Dylan.shi
EUT: Smart phone	Humidity: 48%RH
Temperature: 25.5℃	Test Voltage: Power by Battery
M/N: TANK 01	Test Data: 2022-10-27
Test Mode: 802.11n40 5510	
Note:	



No.	Frequency	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	5.362GHz	57.71	-7.30	50.41	74.00	-23.59	PK	Hor
2*	5.460GHz	53.11	-7.61	45.50	74.00	-28.50	PK	Hor




Project: LGT22J019	Test Engineer: Dylan.shi
EUT: Smart phone	Humidity: 48%RH
Temperature: 25.5°C	Test Voltage: Power by Battery
M/N: TANK 01	Test Data: 2022-10-27
Test Mode: 802.11n40 5510	
Note:	



No.	Frequency	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	5.362GHz	58.62	-7.30	51.32	74.00	-22.68	PK	Ver
2*	5.460GHz	54.31	-7.61	46.70	74.00	-27.30	PK	Ver




Project: LGT22J019	Test Engineer: Dylan.shi
EUT: Smart phone	Humidity: 48%RH
Temperature: 25.5℃	Test Voltage: Power by Battery
M/N: TANK 01	Test Data: 2022-10-27
Test Mode: 802.11n40 5670	
Note:	



No.	Frequency	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	7.250GHz	55.69	-4.99	50.70	74.00	-23.30	PK	Hor
2*	7.705GHz	58.76	-4.17	54.59	74.00	-19.41	PK	Hor
3*	7.705GHz	47.07	-4.17	42.90	54.00	-11.10	AV	Hor




Project: LGT22J019	Test Engineer: Dylan.shi
EUT: Smart phone	Humidity: 48%RH
Temperature: 25.5℃	Test Voltage: Power by Battery
M/N: TANK 01	Test Data: 2022-10-27
Test Mode: 802.11n40 5670	
Note:	



No.	Frequency	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	7.250GHz	56.49	-4.99	51.50	74.00	-22.50	PK	Ver
2*	7.585GHz	58.58	-4.25	54.33	74.00	-19.67	PK	Ver
3*	7.585GHz	47.74	-4.24	43.50	54.00	-10.50	AV	Ver




Project: LGT22J019	Test Engineer: Dylan.shi
EUT: Smart phone	Humidity: 48%RH
Temperature: 25.5°C	Test Voltage: Power by Battery
M/N: TANK 01	Test Data: 2022-10-27
Test Mode: 802.11n40 5755	
Note:	



No.	Frequency	Reading dBuV	Factor dB	Level dBuV	Limit dBuV	Margin dB	Detector	Polar
1*	5.611GHz	57.88	-7.70	50.18	68.20	-18.02	PK	Hor
2*	5.699GHz	61.92	-7.66	54.26	104.60	-50.34	PK	Hor
3*	5.725GHz	61.25	-7.65	53.60	122.20	-68.60	PK	Hor
4*	5.850GHz	53.20	-7.60	45.60	122.20	-76.60	PK	Hor
5*	5.899GHz	57.31	-7.58	49.73	87.49	-37.77	PK	Hor
6*	5.942GHz	56.90	-7.56	49.34	68.20	-18.86	PK	Hor




Project: LGT22J019	Test Engineer: Dylan.shi
EUT: Smart phone	Humidity: 48%RH
Temperature: 25.5°C	Test Voltage: Power by Battery
M/N: TANK 01	Test Data: 2022-10-27
Test Mode: 802.11n40 5755	
Note:	



No.	Frequency	Reading dBuV	Factor dB	Level dBuV	Limit dBuV	Margin dB	Detector	Polar
1*	5.614GHz	57.51	-7.69	49.82	68.20	-18.38	PK	Ver
2*	5.673GHz	59.09	-7.67	51.42	84.90	-33.48	PK	Ver
3*	5.725GHz	58.45	-7.65	50.80	122.20	-71.40	PK	Ver
4*	5.850GHz	54.10	-7.60	46.50	122.20	-75.70	PK	Ver
5*	5.896GHz	57.85	-7.58	50.27	89.75	-39.47	PK	Ver
6*	5.966GHz	57.02	-7.55	49.47	68.20	-18.73	PK	Ver




Project: LGT22J019	Test Engineer: Dylan.shi
EUT: Smart phone	Humidity: 48%RH
Temperature: 25.5°C	Test Voltage: Power by Battery
M/N: TANK 01	Test Data: 2022-10-27
Test Mode: 802.11n40 5795	
Note:	



No.	Frequency	Reading dBuV	Factor dB	Level dBuV	Limit dBuV	Margin dB	Detector	Polar
1*	5.638GHz	57.69	-7.69	50.00	68.20	-18.20	PK	Hor
2*	5.695GHz	59.29	-7.66	51.63	101.84	-50.21	PK	Hor
3*	5.725GHz	55.65	-7.65	48.00	122.20	-74.20	PK	Hor
4*	5.850GHz	54.50	-7.60	46.90	122.20	-75.30	PK	Hor
5*	5.898GHz	58.15	-7.58	50.57	87.84	-37.27	PK	Hor
6*	5.943GHz	56.74	-7.56	49.18	68.20	-19.02	PK	Hor



Project: LGT22J019	Test Engineer: Dylan.shi
EUT: Smart phone	Humidity: 48%RH
Temperature: 25.5℃	Test Voltage: Power by Battery
M/N: TANK 01	Test Data: 2022-10-27
Test Mode: 802.11n40 5795	
Note:	



No.	Frequency	Reading dBuV	Factor dB	Level dBuV	Limit dBuV	Margin dB	Detector	Polar
1*	5.634GHz	57.75	-7.69	50.06	68.20	-18.14	PK	Ver
2*	5.692GHz	58.83	-7.66	51.17	99.21	-48.04	PK	Ver
3*	5.725GHz	56.05	-7.65	48.40	122.20	-73.80	PK	Ver
4*	5.850GHz	53.70	-7.60	46.10	122.20	-76.10	PK	Ver
5*	5.893GHz	58.75	-7.58	51.17	91.97	-40.80	PK	Ver
6*	5.973GHz	57.08	-7.55	49.53	68.20	-18.67	PK	Ver



4. POWER SPECTRAL DENSITY TEST

4.1 LIMIT

1. For mobile and portable client devices in the 5.15-5.25 GHz band, , the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.
2. For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.
3. For the band 5.725-5.850 GHz, the peak power spectral density shall not exceed 30 dBm in any 500KHz band. If transmitting antenna directional gain is greater than 6 dBi, both the maximum conducted output power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

4.2 TEST PROCEDURE

1. The setting follows Method SA-1 of FCC KDB 789033 D02 General U-NII Test Procedures New Rules v02r01.

For devices operating in the band, the rules specify a measurement bandwidth of 500 kHz. Many spectrum analyzers do not have 500 kHz RBW, thus a narrower RBW may need to be used. The rules permit the use of a RBWs less than 1 MHz, or 500 kHz, “provided that the measured power is integrated over the full reference bandwidth” to show the total power over the specified measurement bandwidth (*i.e.*, 1 MHz, or 500 kHz). If measurements are performed using a reduced resolution bandwidth (< 1 MHz, or < 500 kHz) and integrated over 1 MHz, or 500 KHz bandwidth, the following adjustments to the procedures apply:

- a) Set $RBW \geq 1/T$, where T is defined in section II.B.I.a).
- b) Set $VBW \geq 3 RBW$.
- c) If measurement bandwidth of Maximum PSD is specified in 500 kHz, add $10 \log (500\text{kHz}/RBW)$ to the measured result, whereas $RBW (< 500 \text{ kHz})$ is the reduced resolution bandwidth of the spectrum analyzer set during measurement.
- d) If measurement bandwidth of Maximum PSD is specified in 1 MHz, add $10 \log (1\text{MHz}/RBW)$ to the measured result, whereas $RBW (< 1 \text{ MHz})$ is the reduced resolution bandwidth of spectrum analyzer set during measurement.
- e) Care must be taken to ensure that the measurements are performed during a period of continuous transmission or are corrected upward for duty cycle.

Note: As a practical matter, it is recommended to use reduced RBW of 100 kHz for the sections 5.c) and 5.d) above, since $RBW=100 \text{ KHz}$ is available on nearly all spectrum analyzers.

4.3 DEVIATION FROM STANDARD

No deviation.

4.4 TEST SETUP



4.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.1 Unless otherwise a special operating condition is specified in the follows during the testing.

4.6 TEST RESULTS

For the measurement records, refer to the appendix I.



5. BANDWIDTH MEASUREMENT

5.1 EMISSION BANDWIDTH (EBW) 26 BANDWID PROCEDURES / LIMIT

The following procedure shall be used for measuring 26 bandwidth.

5.1.1 TEST PROCEDURE

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
2. Set RBW = approximately 1% of the emission bandwidth.
3. Set the VBW $\geq$ RBW.
4. Detector = Peak.
5. Trace mode = max hold.
6. Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

5.1.2 DEVIATION FROM STANDARD

No deviation.

5.1.3 TEST SETUP



5.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

5.1.5 TEST RESULTS

For the measurement records, refer to the appendix I.



5.2 OCCUPIED BANDWIDTH (99%) TEST APPLIED PROCEDURES / LIMIT

The following procedure shall be used for measuring (99 %) power bandwidth.

5.2.1 TEST PROCEDURE

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures v02r01. The following procedure shall be used for measuring (99 %) power bandwidth:
1. Set center frequency to the nominal EUT channel center frequency.
2. Set span = 1.5 times to 5.0 times the OBW.
3. Set RBW = 1 % to 5 % of the OBW
4. Set VBW $\geq 3 \cdot$ RBW
5. Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
6. Use the 99 % power bandwidth function of the instrument (if available).
7. If the instrument does not have a 99 % power bandwidth function, the trace data points are recovered and directly summed in power units. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5 % of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5 % of the total is reached; that frequency is recorded as the upper frequency. The 99% occupied bandwidth is the difference between these two frequencies.

5.2.2 DEVIATION FROM STANDARD

No deviation.

5.2.3 TEST SETUP



5.2.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

5.2.5 TEST RESULTS

For the measurement records, refer to the appendix I.



5.3 MINIMUM EMISSION BANDWIDTH(6 DB) PROCEDURES / LIMIT

Section 15.407(e) specifies the minimum 6 dB emission bandwidth of at least 500 KHz for the band 5.725-5.85 GHz. The following procedure shall be used for measuring this bandwidth.

5.3.1 TEST PROCEDURE

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures v02r01.
 - a) Set RBW = 100 kHz.
 - b) Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
 - c) Detector = Peak.
 - d) Trace mode = max hold.
 - e) Sweep = auto couple.
 - f) Allow the trace to stabilize.
 - g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

5.3.2 DEVIATION FROM STANDARD

No deviation.

5.3.3 TEST SETUP



5.3.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

5.3.5 TEST RESULTS

For the measurement records, refer to the appendix I.



6. MAXIMUM CONDUCTED OUTPUT POWER

6.1 LIMIT

For mobile and portable client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or $11 \text{ dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in megahertz, If transmitting antennas of directional gain greater than 6 dBi are used.

For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. If transmitting antennas of directional gain greater than 6 dBi are used.

FCC Part15 (15.407) , Subpart E				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.407(a) (1) (iv)	Peak Output Power	0.25 watt	5150-5250	PASS
		The lesser of 250 mW or $11 \text{ dBm} + 10 \log (26 \text{ dB emission bandwidth})$	5250-5350 5470-5725	
15.407(a) (3)		1 watt	5725-5825	


6.2 TEST PROCEDURE

The EUT was directly connected to the Power Sensor&PC

6.3 DEVIATION FROM STANDARD

No deviation.

6.4 TEST SETUP



6.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 5 Unless otherwise a special operating condition is specified in the follows during the testing.



6.6 TEST RESULTS

For the measurement records, refer to the appendix I.



7. AUTOMATICALLY DISCONTINUE TRANSMISSION

7.1 LIMIT OF AUTOMATICALLY DISCONTINUE TRANSMISSION

The device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. These provisions are not intended to preclude the transmission of control or signaling information or the use of repetitive codes used by certain digital technologies to complete frame or burst intervals. Applicants shall include in their application for equipment authorization to describe how this requirement is met.

7.2 TEST RESULT OF AUTOMATICALLY DISCONTINUE TRANSMISSION

During no any information transmission, the EUT can automatically discontinue transmission and become standby mode for power saving. The EUT can detect the controlling signal of ACK message transmitting from remote device and verify whether it shall resend or discontinue transmission



8. ANTENNA REQUIREMENT

8.1 STANDARD REQUIREMENT

Part 15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

8.2 EUT ANTENNA

The EUT antenna is PIFA Antenna with RP-SMA connector. It comply with the standard requirement.



APPENDIX I:TEST RESULTS

DUTY CYCLE

Condition	Mode	Frequency (MHz)	Antenna	Duty Cycle (%)	Correction Factor (dB)	1/T (kHz)
NVNT	a	5180	Ant1	97.55	0.11	0.72
NVNT	a	5200	Ant1	97.55	0.11	0.72
NVNT	a	5240	Ant1	97.55	0.11	0.72
NVNT	a	5260	Ant1	97.55	0.11	0.72
NVNT	a	5300	Ant1	97.55	0.11	0.72
NVNT	a	5320	Ant1	97.55	0.11	0.72
NVNT	a	5500	Ant1	97.55	0.11	0.72
NVNT	a	5580	Ant1	97.55	0.11	0.72
NVNT	a	5700	Ant1	97.55	0.11	0.72
NVNT	a	5745	Ant1	97.55	0.11	0.72
NVNT	a	5785	Ant1	97.55	0.11	0.72
NVNT	a	5825	Ant1	97.48	0.11	0.72
NVNT	n20	5180	Ant1	97.38	0.12	0.77
NVNT	n20	5200	Ant1	97.31	0.12	0.77
NVNT	n20	5240	Ant1	97.38	0.12	0.77
NVNT	n20	5260	Ant1	97.38	0.12	0.77
NVNT	n20	5300	Ant1	97.38	0.12	0.77
NVNT	n20	5320	Ant1	97.31	0.12	0.77
NVNT	n20	5500	Ant1	97.38	0.12	0.77
NVNT	n20	5580	Ant1	97.38	0.12	0.77
NVNT	n20	5700	Ant1	97.38	0.12	0.77
NVNT	n20	5745	Ant1	97.38	0.12	0.77
NVNT	n20	5785	Ant1	97.38	0.12	0.77
NVNT	n20	5825	Ant1	97.38	0.12	0.77
NVNT	n40	5190	Ant1	95.15	0.22	1.53
NVNT	n40	5230	Ant1	95.15	0.22	1.53
NVNT	n40	5270	Ant1	95.15	0.22	1.53
NVNT	n40	5310	Ant1	95.17	0.21	1.53
NVNT	n40	5510	Ant1	95.2	0.21	1.53
NVNT	n40	5550	Ant1	95.19	0.21	1.53
NVNT	n40	5670	Ant1	95.2	0.21	1.53
NVNT	n40	5755	Ant1	95.2	0.21	1.53
NVNT	n40	5795	Ant1	95.2	0.21	1.53
NVNT	ac20	5180	Ant1	97.4	0.11	0.76
NVNT	ac20	5200	Ant1	97.4	0.11	0.76
NVNT	ac20	5240	Ant1	97.4	0.11	0.76
NVNT	ac20	5260	Ant1	97.4	0.11	0.76
NVNT	ac20	5300	Ant1	97.4	0.11	0.76
NVNT	ac20	5320	Ant1	97.4	0.11	0.76
NVNT	ac20	5500	Ant1	97.4	0.11	0.76
NVNT	ac20	5580	Ant1	97.4	0.11	0.76
NVNT	ac20	5700	Ant1	97.4	0.11	0.76
NVNT	ac20	5745	Ant1	97.4	0.11	0.76




NVNT	ac20	5785	Ant1	97.4	0.11	0.76
NVNT	ac20	5825	Ant1	97.4	0.11	0.76
NVNT	ac40	5190	Ant1	95.2	0.21	1.53
NVNT	ac40	5230	Ant1	95.19	0.21	1.53
NVNT	ac40	5270	Ant1	95.2	0.21	1.53
NVNT	ac40	5310	Ant1	95.2	0.21	1.53
NVNT	ac40	5510	Ant1	95.24	0.21	1.53
NVNT	ac40	5550	Ant1	95.2	0.21	1.53
NVNT	ac40	5670	Ant1	95.15	0.22	1.53
NVNT	ac40	5755	Ant1	95.11	0.22	1.53
NVNT	ac40	5795	Ant1	95.15	0.22	1.53
NVNT	ac80	5210	Ant1	90.79	0.42	3.07
NVNT	ac80	5290	Ant1	90.79	0.42	3.07
NVNT	ac80	5530	Ant1	90.88	0.42	3.07
NVNT	ac80	5610	Ant1	90.79	0.42	3.07
NVNT	ac80	5690	Ant1	90.8	0.42	3.07
NVNT	ac80	5775	Ant1	90.79	0.42	3.07




Test Graphs

Duty Cycle NVNT a 5180MHz Ant1




Duty Cycle NVNT a 5200MHz Ant1






Duty Cycle NVNT a 5240MHz Ant1




Duty Cycle NVNT a 5260MHz Ant1






Duty Cycle NVNT a 5300MHz Ant1




Duty Cycle NVNT a 5320MHz Ant1






Duty Cycle NVNT a 5500MHz Ant1




Duty Cycle NVNT a 5580MHz Ant1





Duty Cycle NVNT a 5700MHz Ant1




Duty Cycle NVNT a 5745MHz Ant1






Duty Cycle NVNT a 5785MHz Ant1




Duty Cycle NVNT a 5825MHz Ant1






Duty Cycle NVNT n20 5180MHz Ant1




Duty Cycle NVNT n20 5200MHz Ant1






Duty Cycle NVNT n20 5240MHz Ant1




Duty Cycle NVNT n20 5260MHz Ant1






Duty Cycle NVNT n20 5300MHz Ant1




Duty Cycle NVNT n20 5320MHz Ant1






Duty Cycle NVNT n20 5500MHz Ant1




Duty Cycle NVNT n20 5580MHz Ant1






Duty Cycle NVNT n20 5700MHz Ant1




Duty Cycle NVNT n20 5745MHz Ant1





Duty Cycle NVNT n20 5785MHz Ant1




Duty Cycle NVNT n20 5825MHz Ant1






Duty Cycle NVNT n40 5190MHz Ant1




Duty Cycle NVNT n40 5230MHz Ant1






Duty Cycle NVNT n40 5270MHz Ant1




Duty Cycle NVNT n40 5310MHz Ant1






Duty Cycle NVNT n40 5510MHz Ant1




Duty Cycle NVNT n40 5550MHz Ant1






Duty Cycle NVNT n40 5670MHz Ant1




Duty Cycle NVNT n40 5755MHz Ant1






Duty Cycle NVNT n40 5795MHz Ant1




Duty Cycle NVNT ac20 5180MHz Ant1






Duty Cycle NVNT ac20 5200MHz Ant1




Duty Cycle NVNT ac20 5240MHz Ant1






Duty Cycle NVNT ac20 5260MHz Ant1




Duty Cycle NVNT ac20 5300MHz Ant1






Duty Cycle NVNT ac20 5320MHz Ant1




Duty Cycle NVNT ac20 5500MHz Ant1






Duty Cycle NVNT ac20 5580MHz Ant1




Duty Cycle NVNT ac20 5700MHz Ant1






Duty Cycle NVNT ac20 5745MHz Ant1




Duty Cycle NVNT ac20 5785MHz Ant1






Duty Cycle NVNT ac20 5825MHz Ant1




Duty Cycle NVNT ac40 5190MHz Ant1






Duty Cycle NVNT ac40 5230MHz Ant1




Duty Cycle NVNT ac40 5270MHz Ant1






Duty Cycle NVNT ac40 5310MHz Ant1




Duty Cycle NVNT ac40 5510MHz Ant1






Duty Cycle NVNT ac40 5550MHz Ant1




Duty Cycle NVNT ac40 5670MHz Ant1






Duty Cycle NVNT ac40 5755MHz Ant1




Duty Cycle NVNT ac40 5795MHz Ant1






Duty Cycle NVNT ac80 5210MHz Ant1




Duty Cycle NVNT ac80 5290MHz Ant1






Duty Cycle NVNT ac80 5530MHz Ant1




Duty Cycle NVNT ac80 5610MHz Ant1






Duty Cycle NVNT ac80 5690MHz Ant1



Duty Cycle NVNT ac80 5775MHz Ant1





MAXIMUM CONDUCTED OUTPUT POWER

Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Duty Factor (dB)	Total Power (dBm)	Limit (dBm)	Verdict
NVNT	a	5180	Ant1	12.03	0.11	12.14	24	Pass
NVNT	a	5200	Ant1	12.63	0.11	12.74	24	Pass
NVNT	a	5240	Ant1	12.73	0.11	12.84	24	Pass
NVNT	a	5260	Ant1	12.77	0.11	12.88	24	Pass
NVNT	a	5300	Ant1	13.18	0.11	13.29	24	Pass
NVNT	a	5320	Ant1	13.59	0.11	13.7	24	Pass
NVNT	a	5500	Ant1	10.3	0.11	10.41	24	Pass
NVNT	a	5580	Ant1	10.07	0.11	10.18	24	Pass
NVNT	a	5700	Ant1	9.79	0.11	9.9	24	Pass
NVNT	a	5745	Ant1	9.71	0.11	9.82	30	Pass
NVNT	a	5785	Ant1	10.11	0.11	10.22	30	Pass
NVNT	a	5825	Ant1	9.71	0.11	9.82	30	Pass
NVNT	n20	5180	Ant1	10.42	0.12	10.54	24	Pass
NVNT	n20	5200	Ant1	11.4	0.12	11.52	24	Pass
NVNT	n20	5240	Ant1	11.16	0.12	11.28	24	Pass
NVNT	n20	5260	Ant1	10.69	0.12	10.81	24	Pass
NVNT	n20	5300	Ant1	11.67	0.12	11.79	24	Pass
NVNT	n20	5320	Ant1	11.44	0.12	11.56	24	Pass
NVNT	n20	5500	Ant1	10.99	0.12	11.11	24	Pass
NVNT	n20	5580	Ant1	10.32	0.12	10.44	24	Pass
NVNT	n20	5700	Ant1	10.7	0.12	10.82	24	Pass
NVNT	n20	5745	Ant1	10.44	0.12	10.56	30	Pass
NVNT	n20	5785	Ant1	10.7	0.12	10.82	30	Pass
NVNT	n20	5825	Ant1	10.22	0.12	10.34	30	Pass
NVNT	n40	5190	Ant1	10.7	0.22	10.92	24	Pass
NVNT	n40	5230	Ant1	11.04	0.22	11.26	24	Pass
NVNT	n40	5270	Ant1	10.86	0.22	11.08	24	Pass
NVNT	n40	5310	Ant1	11.16	0.21	11.37	24	Pass
NVNT	n40	5510	Ant1	12.68	0.21	12.89	24	Pass
NVNT	n40	5550	Ant1	10.14	0.21	10.35	24	Pass
NVNT	n40	5670	Ant1	11.01	0.21	11.22	24	Pass
NVNT	n40	5755	Ant1	10.28	0.21	10.49	30	Pass
NVNT	n40	5795	Ant1	10.47	0.21	10.68	30	Pass
NVNT	ac20	5180	Ant1	7.3	0.11	7.41	24	Pass
NVNT	ac20	5200	Ant1	7.84	0.11	7.95	24	Pass
NVNT	ac20	5240	Ant1	8.23	0.11	8.34	24	Pass
NVNT	ac20	5260	Ant1	8.25	0.11	8.36	24	Pass
NVNT	ac20	5300	Ant1	8.17	0.11	8.28	24	Pass
NVNT	ac20	5320	Ant1	8.01	0.11	8.12	24	Pass
NVNT	ac20	5500	Ant1	7.43	0.11	7.54	24	Pass
NVNT	ac20	5580	Ant1	7.22	0.11	7.33	24	Pass
NVNT	ac20	5700	Ant1	7.74	0.11	7.85	24	Pass
NVNT	ac20	5745	Ant1	7.47	0.11	7.58	30	Pass
NVNT	ac20	5785	Ant1	7.72	0.11	7.83	30	Pass
NVNT	ac20	5825	Ant1	7.08	0.11	7.19	30	Pass



NVNT	ac40	5190	Ant1	7.46	0.21	7.67	24	Pass
NVNT	ac40	5230	Ant1	7.74	0.21	7.95	24	Pass
NVNT	ac40	5270	Ant1	8.01	0.21	8.22	24	Pass
NVNT	ac40	5310	Ant1	7.57	0.21	7.78	24	Pass
NVNT	ac40	5510	Ant1	8.66	0.21	8.87	24	Pass
NVNT	ac40	5550	Ant1	8.82	0.21	9.03	24	Pass
NVNT	ac40	5670	Ant1	7.25	0.22	7.47	24	Pass
NVNT	ac40	5755	Ant1	6.93	0.22	7.15	30	Pass
NVNT	ac40	5795	Ant1	6.97	0.22	7.19	30	Pass
NVNT	ac80	5210	Ant1	7.21	0.42	7.63	24	Pass
NVNT	ac80	5290	Ant1	7.22	0.42	7.64	24	Pass
NVNT	ac80	5530	Ant1	8.61	0.42	9.03	24	Pass
NVNT	ac80	5610	Ant1	8.67	0.42	9.09	24	Pass
NVNT	ac80	5690	Ant1	8.52	0.42	8.94	24	Pass
NVNT	ac80	5775	Ant1	9.2	0.42	9.62	30	Pass

