



RADIO TEST REPORT

Report No: STS1908166W19

Issued for

Shanghai Unihertz E-Commerce Co., Ltd

Room 302, No. 5, Lane 59, Shennan Rd, Minhang district, Shanghai, China 201108

Product Name:	Smart phone	
Brand Name:	Unihertz	
Model Name:	Titan	
Series Model:	N/A	
FCC ID:	2AK6CTITAN	
Test Standard:	FCC Part 15.225	

Any reproduction of this document must be done in full. No single part of this document may be reproduced with permission from STS, All Test Data Presented in this report is only applicable to presented test sample.





TEST REPORT CERTIFICATION

Applicant's Name..... Shanghai Unihertz E-Commerce Co., Ltd

Shanghai, China 201108

Manufacture's Name OBLUE Communication Technology Co.,Ltd.

Industry Park, Nanshan district, shenzhen, China 201108

Product Description

Product Name.....: Smart phone

Brand Name Unihertz

Model Name: Titan

Series Model..... N/A

Test Standards FCC Part15.225

Test Procedure...... ANSI C63.10: 2013, ANSI C63.4: 2014

This device described above has been tested by STS, the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of STS, thidocument only be altered or revised by STS, personal only, and shall be noted in the revision of the document.

Date of Test

Date (s) of performance of tests 07 Aug. 2019 ~ 06 Sept. 2019

Date of Issue...... 06 Sept. 2019

Test Result..... Pass

Testing Engineer

(Chris Chen)

Technical Manager

Authorized Signatory:

(Sunday Hu)

Mari

(Vita Li)

1/F., Building B, Zhuoke Science Park, No.190, Chongqing Road, Fuyong Street, Bao'an District, Shenzhen, Guangdong, China Tel: +86-755 3688 6288 Fax:+86-755 3688 6277 Http://www.stsapp.com E-mail: sts@stsapp.com



TABLE OF CONTENTS		
1. SUMMARY OF TEST RESULTS	5	
1.1 TEST FACTORY	5	
1.2 MEASUREMENT UNCERTAINTY	5	
2. GENERAL INFORMATION	6	
2.1 GENERAL DESCRIPTION OF THE EUT	6	
2.2 DESCRIPTION OF THE TEST MODES	7	
2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	8	
2.4 DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS	9	
2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS	10	
3. EMC EMISSION TEST	11	
3.1 CONDUCTED EMISSION MEASUREMENT	11	
3.2 TEST PROCEDURE	12	
3.3 TEST SETUP	12	
3.4 EUT OPERATING CONDITIONS	12	
3.5 TEST RESULTS	13	
4. RADIATED EMISSION MEASUREMENT	15	
4.1 RADIATED EMISSION LIMITS	15	
4.2 TEST PROCEDURE	16	
4.3 TEST SETUP	17	
4.4 EUT OPERATING CONDITIONS	17	
5. FREQUENCY TOLERANCE	22	
5.1 REQUIREMENT	22	
5.2 TEST PROCEDURE	22	
5.3 TEST SETUP	22	
5.4 EUT OPERATION CONDITIONS	22	
5.5 TEST RESULTS	23	
6. 20DB BANDWIDTH	24	
6.1 APPLIED PROCEDURES / LIMIT	24	
6.2 TEST PROCEDURE	24	
6.3 TEST SETUP	24	
6.4 EUT OPERATION CONDITIONS	24	
6.5 TEST RESULTS	25	



TABLE OF CONTENTS	Page
7. ANTENNA REQUIREMENT	26
7.1 STANDARD REQUIREMENT	26
7.2 EUT ANTENNA	26
APPENDIX 1- PHOTOS OF TEST SETUP	27





1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 15.225 , Subpart C						
Standard Section	Judgment	Remark				
15.207	Conducted Emission PA					
15.209 15.225(a)(b)(c)(d)	Radiated Emission	PASS				
15.225(e)	Frequency Tolerance	PASS				
15.203	Antenna Requirement	PASS				
15.215	20dB Bandwidth	PASS				

NOTE: (1)" N/A" denotes test is not applicable in this Test Report

(2) All tests are according to ANSI C63.4-2014 and ANSI C63.10-2013

1.1 TEST FACTORY

SHENZHEN STS TEST SERVICES CO., LTD

Add.: A 1/F, Building B, Zhuoke Science Park, No.190 Chongqing Road, HepingShequ,

Fuyong Sub-District, Bao'an District, Shenzhen, Guang Dong, China

FCC test Firm Registration Number: 625569

IC test Firm Registration Number: 12108A

A2LA Certificate No.: 4338.01

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $\mathbf{y} \pm \mathbf{U}$, where expended uncertainty \mathbf{U} is based on a standard uncertainty multiplied by a coverage factor of $\mathbf{k=2}$, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	RF output power, conducted	±0.71dB
2	Unwanted Emissions, conducted	±0.63dB
3	All emissions, radiated 30-200MHz	±3.43dB
4	All emissions, radiated 200MHz-1GHz	±3.57dB
5	All emissions, radiated>1G	±4.13dB
6	Conducted Emission (9KHz-150KHz)	±3.18dB
7	Conducted Emission (150KHz-30MHz)	±2.70dB



2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF THE EUT

Product Name	Smart phone		
Trade Name	Unihertz		
Model Name	Titan		
Serial Model	N/A		
Model Difference	N/A		
Product Description	The EUT is a Smart phone Operation Frequency: 13.56MHz Modulation Type: FSK Antenna Designation: Please see Note 3. Antenna Gain (dBi) 0dBi		
Adapter	Input: 100-240V, 50/60Hz, 0.6A Output: 5V, 2.0A 9V, 2.0A 12V, 1.5A		
Battery	Rated Voltage: 3.85V Charge Limit: 4.4V Capacity: 6000mAh		
Hardware version number	G61_V2.0		
Software version number	Titan_20190629		
Connecting I/O Port(s)	Please refer to the User's Manual		

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

2. Table for filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	NOTE
Α	Unihertz	Titan	PIFA	N/A	0	ANT



2.2 DESCRIPTION OF THE TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	TX Mode

	For Conducted Test
Final Test Mode	Description
Mode 1	TX Mode

	For Radiated Emission
Final Test Mode	Description
Mode 1	TX Mode

Note:

We have be tested for all avaiable U.S. voltage and frequencies(For 120V,50/60Hz and 240V, 50/60Hz) for which the device is capable of operation.




2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Radiated Spurious Emission Test

E-1 EUT

Conducted Emission Test





2.4 DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Necessary accessories

Item	Equipment	Mfr/Brand	Model/Type No.	Serial No.	Note
E-2	Adapter	Unihertz	HJ-FC010K7-US	N/A	N/A
C-2	DC Cable	N/A	110cm	N/A	N/A

Support units

Item	Equipment	Mfr/Brand	Model/Type No.	Serial No.	Note
N/A	N/A	N/A	N/A	N/A	N/A
	/				

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2)For detachable type I/O cable should be specified the length in cm in <code>"Length_"</code> column.



2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation Test equipment

Radiation Test equipment						
Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	
Test Receiver	R&S	ESCI	101427	2018.10.13	2019.10.12	
Signal Analyzer	Agilent	N9020A	MY51110105	2019.03.02	2020.03.01	
Active loop Antenna	ZHINAN	ZN30900C	16035	2018.03.11	2021.03.10	
Bilog Antenna	TESEQ	CBL6111D	34678	2017.11.02	2020.11.1	
Horn Antenna	SCHWARZBECK	BBHA 9120D(1201)	9120D-1343	2018.10.19	2021.10.18	
SHF-EHF Horn Antenna (18G-40GHz)	A-INFO	LB-180400-KF	J211020657	2018.03.11	2021.03.10	
Pre-Amplifier(0.1M-3G Hz)	EM	EM330	060665	2018.10.13	2019.10.12	
Pre-Amplifier (1G-18GHz)	SKET	LNPA-01018G-45	SK201808090 1	2018.10.13	2019.10.12	
Temperature & Humidity	HH660	Mieo	N/A	2018.10.11	2019.10.10	
turn table	EM	SC100_1	60531	N/A	N/A	
Antenna mast	EM	SC100	N/A	N/A	N/A	
Test SW	FARAD	EZ-EMC(Ver.STSLAB-03A1 RE)				

Conduction Test equipment

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
Test Receiver	R&S	ESCI	101427	2018.10.13	2019.10.12
LISN	R&S	ENV216	101242	2018.10.11	2019.10.10
LISN	EMCO	3810/2NM	23625	2018.10.11	2019.10.10
Temperature & Humidity	HH660	Mieo N/A 2018.10.11 2019.10.10			
Test SW	FARAD	EZ-EMC(Ver.STSLAB-03A1 CE)			

RF Connected Test

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
USB RF power sensor	DARE	RPR3006W	15I00041SNO03	2018.10.13	2019.10.12
Signal Analyzer	Agilent	N9020A	MY49100060	2018.10.13	2019.10.12
Temperature & Humidity	HH660	Mieo N/A 2018.10.11 2019.10			
Test SW	FARAD	LZ-RF /LzRf-3A3			



3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION LIMITS

Operating frequency band. In case the emission fall within the restricted band specified on Part 15. 207(a) limit in the table below has to be followed.

EDEOLIENOV (MU-)	Class B	Standard		
FREQUENCY (MHz)	Quasi-peak	Average	Standard	
0.15 -0.5	66 - 56 *	56 - 46 *	CISPR	
0.50 -5.0	56.00	46.00	CISPR	
5.0 -30.0	60.00	50.00	CISPR	

0.15 -0.5	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	56.00	46.00	FCC
5.0 -30.0	60.00	50.00	FCC

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver


Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz



3.2 TEST PROCEDURE

- a.The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b.Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c.I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d.LISN at least 80 cm from nearest part of EUT chassis.
- e.For the actual test configuration, please refer to the related Item -EUT Test Photos.

3.3 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

3.4 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.




3.5 TEST RESULTS

Temperature:	26(C)	Relative Humidity:	60%RH
Test Voltage:	AC 120V/60Hz	Phase:	L
Test Mode:	Mode 1		

No.	Frequen cy	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	Factor(d B)	(dBuV)	(dBuV)	(dB)	
1	0.1524	48.41	9.79	58.20	65.87	-7.67	QP
2	0.1524	33.28	9.79	43.07	55.87	-12.80	AVG
3	0.2260	40.06	9.90	49.96	62.60	-12.64	QP
4	0.2260	25.96	9.90	35.86	52.60	-16.74	AVG
5	0.4340	33.62	10.03	43.65	57.18	-13.53	QP
6	0.4340	20.01	10.03	30.04	47.18	-17.14	AVG
7	1.2460	31.23	9.80	41.03	56.00	-14.97	QP
8	1.2460	16.57	9.80	26.37	46.00	-19.63	AVG
9	2.3980	28.76	9.80	38.56	56.00	-17.44	QP
10	2.3980	16.49	9.80	26.29	46.00	-19.71	AVG
11	13.0260	35.35	10.22	45.57	60.00	-14.43	QP
12	13.0260	21.65	10.22	31.87	50.00	-18.13	AVG

Remark:

- 1. All readings are Quasi-Peak and Average values.
- 2. Margin = Result (Result = Reading + Factor)-Limit






Temperature:	26(C)	Relative Humidity:	60%RH
Test Voltage:	AC 120V/60Hz	Phase:	N
Test Mode:	Mode 1		

No.	Frequen cy	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	Factor(d B)	(dBuV)	(dBuV)	(dB)	
1	0.1500	48.86	9.79	58.65	66.00	-7.35	QP
2	0.1500	32.78	9.79	42.57	56.00	-13.43	AVG
3	0.2260	38.56	9.90	48.46	62.60	-14.14	QP
4	0.2260	24.46	9.90	34.36	52.60	-18.24	AVG
5	0.5540	32.86	9.98	42.84	56.00	-13.16	QP
6	0.5540	16.25	9.98	26.23	46.00	-19.77	AVG
7	1.2460	31.73	9.80	41.53	56.00	-14.47	QP
8	1.2460	17.50	9.80	27.30	46.00	-18.70	AVG
9	2.7780	30.04	9.81	39.85	56.00	-16.15	QP
10	2.7780	13.91	9.81	23.72	46.00	-22.28	AVG
11	12.5100	34.76	10.22	44.98	60.00	-15.02	QP
12	12.5100	20.63	10.22	30.85	50.00	-19.15	AVG

Remark:

- 1. All readings are Quasi-Peak and Average values.





4. RADIATED EMISSION MEASUREMENT

4.1 RADIATED EMISSION LIMITS

- (a) The field strength of any emissions within the band 13.553-13.567 MHz shall not exceed 15.848 microvolts/meter at 30 meters.
- (b) Within the bands 13.410-13.553 MHz and 13.567-13.710 MHz, the field strength of any emissions shall not exceed 334 microvolts/meter at 30 meters.
- (c) Within the bands 13.110-13.410 MHz and 13.710-14.010 MHz the field strength of any emissions shall not exceed 106 microvolts/meter at 30 meters.
- (d) The field strength of any emissions appearing outside of the 13.110-14.010 MHz band shall not exceed the general radiated emission limits in §15.209.

(Radiated Emission <30MHz (9KHz-30MHz, H-field)

According to FCC section 15.225, for <30MHz, Radiated emissions were measured according to ANSIC63.4. The EUT was set to transmit at the highest output power. The EUT was set 30 meter away from the measuring antenna. The loop antenna was positioned 1 meter above the ground from the center of the loop. The measuring bandwidth was set to 10KHz. (Note: During testing the receive antenna was rotated about its axis to maximize the emission from the EUT)

There was no detected Restricted bands and Radiated suprious emission below 30MHz. The 30m limit was converted to 3m Limit using square factor(x) as it was found by measurements as follows;

3 m Limit(dBuV/m) = 20log(X)+40log(30/3)=20log(15,848)+40log(30/3)=124dBuV

3 m Limit(dBuV/m) = 20log(X) + 40log(30/3) = 20log(334) + 40log(30/3) = 90.47dBuV

3 m Limit(dBuV/m) = 20log(X) + 40log(30/3) = 20log(106) + 40log(30/3) = 80.506dBuV

3 m Limit(dBuV/m) = 20log(X)+40log(30/3)=20log(30)+40log(30/3)=69.54dBuV

Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

LIMITS OF RADIATED EMISSION MEASUREMENT (Frequency Range 9kHz-1000MHz)

Fraguency range (MHz)	Field Strength	@30m	Field Strength@3m
Frequency range (MHz)	μV/m	dBµV/m	dBµV/m
Below 13.110	30	29.5	69.5
13.110 ~ 13.410	106	40.5	80.5
13.410 ~ 13.553	334	50.5	90.5
13.553 ~13.567	15.848	84	124.0
13.567 ~ 13.710	334	50.5	90.5
13.710 ~14.010	106	40.5	80.5
Above 14.010	30	29.5	69.5

NOTE:

- a) Field Strength (dBμV/m) = 20*log[Field Strength (μV/m)].
- b) In the emission tables above, the tighter limit applies at the Band edge.
 Radiated Emission >30MHz (30MHz-1GHz, E-field)
 According to FCC section 15.205, the field strength of radiated emissions from intentional radiators at a distance of 3 meters shall not exceed the following values:

3

3



Frequencies	Field Strength	Measurement Distance
(MHz)	(micorvolts/meter)	(meters)
30~88	100	3
88~216	150	3

200

500

Page 16 of 27

Receiver Parameter	Setting	
Attenuation	Auto	
Start ~ Stop Frequency	9kHz~90kHz / RB 200Hz for PK & AV	
Start ~ Stop Frequency	90kHz~110kHz / RB 200Hz for QP	
Start ~ Stop Frequency	110kHz~490kHz / RB 200Hz for PK & AV	
Start ~ Stop Frequency	490kHz~30MHz / RB 9kHz for QP	
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP	

4.2 TEST PROCEDURE

216~960

Above 960

- a. The test is performed in a 3m Semi-Anechoic Chamber; the antenna factor, cable loss and so on of the site (factors) is calculated to correct the reading. The EUT is placed on a 0.8m high insulating Turn Table, and keeps 3m away from the Test Antenna, which is mounted on a variable-height antenna master tower. For the test Antenna
- b. In the frequency range of 9KHz to 30MHz, magnetic field is measured with Loop Test Antenna. The Test Antenna is positioned with its plane vertical at 1m distance from the EUT. The center of the Loop Test Antenna is 1m above the ground. During the measurement the Loop Test Antenna rotates about its vertical axis for maximum response at each azimuth about the EUT.
- c. In the frequency range above 30MHz, Bi-Log Test Antenna (30MHz to 1GHz) used. Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength. The emission levels at both horizontal and vertical polarizations should be tested.
- f. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- g. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- h. For the actual test configuration, please refer to the related Item –EUT Test Photos.


NOTE:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported




4.3 TEST SETUP

(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



4.4 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.



4.5 FIELD STRENGTH CALCULATION

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

FS = RA + AF + CL - AG

Where

FS = Field Strength

CL = Cable Attenuation Factor (Cable Loss)

RA = Reading Amplitude

AG = Amplifier Gain

AF = Antenna Factor

For example

Frequency	FS	RA	AF	CL	AG	Factor
(MHz)	(dBµV/m)	(dBµV/m)	(dB)	(dB)	(dB)	(dB)
300	40	58.1	12.2	1.6	31.9	-18.1

Factor=AF+CL-AG



4.6 TEST RESULTS

(Radiated Emission<30MHz (9KHz-30MHz, H-field))

Temperature:	20.2(C)	Relative Humidtity:	51%RH
Test Voltage:	DC 3.85V from battery	Polarization:	
Test Mode:	Mode 1		

Note: Horizontal is the worst polarization.

Freq.	Reading	Limit	Margin	Detector	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	(PK/QP/AV)	P/F
12.12	60.22	69.54	-9.32	QP	PASS
13.33	61.38	80.51	-19.13	QP	PASS
13.45	61.26	90.47	-29.21	QP	PASS
13.56	97.85	124.00	-26.15	QP	PASS
13.67	62.19	90.47	-28.28	QP	PASS
13.89	62.36	80.51	-18.15	QP	PASS
15.21	62.25	69.54	-7.29	QP	PASS

Note:15.31(f)(2) f < 30 MHz, extrapolation factor of 40 dB/decade of distance




Between 30-1000MHz

Temperature:	20.2(C)	Relative Humidity:	51%RH
Test Voltage:	DC 3.85V from battery	Phase:	Horizontal
Test Mode:	Mode 1		

No.	Frequenc y	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	Factor(dB/ m)	(dBuV/m)	(dBuV/m)	(dB)	
1	38.7518	40.28	-17.37	22.91	40.00	-17.09	QP
2	50.4090	48.68	-23.44	25.24	40.00	-14.76	QP
3	87.1116	50.49	-21.85	28.64	40.00	-11.36	QP
4	229.2931	49.75	-19.15	30.60	46.00	-15.40	QP
5	468.8761	31.30	-9.05	22.25	46.00	-23.75	QP
6	955.4380	36.04	1.68	37.72	46.00	-8.28	QP

Remark:

1. Margin = Result (Result = Reading + Factor)-Limit






Temperature:	20.2(C)	Relative Humidity:	51%RH
Test Voltage:	DC 3.85V from battery	Phase:	Vertical
Test Mode:	Mode 1		

No.	Frequenc y	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	Factor(dB/ m)	(dBuV/m)	(dBuV/m)	(dB)	
1	49.3594	44.39	-22.93	21.46	40.00	-18.54	QP
2	71.0802	51.04	-24.67	26.37	40.00	-13.63	QP
3	228.4903	43.07	-19.17	23.90	46.00	-22.10	QP
4	547.0977	36.31	-6.09	30.22	46.00	-15.78	QP
5	701.7610	35.37	-4.12	31.25	46.00	-14.75	QP
6	942.1304	37.95	1.43	39.38	46.00	-6.62	QP

Remark:

1. Margin = Result (Result = Reading + Factor)—Limit





5. FREQUENCY TOLERANCE


5.1 REQUIREMENT

According to FCC section 15.225, the devices operating in the 13.553-13.567 MHz shall maintain the carrier frequency within 0.01% of the operating frequency over the temperature variation of -20°C to +50°C using an environmental chamber. The primary supply voltage is varied from 85% to 115% of the voltage normally at the input to the device or at the power supply terminals if cables are not normally supplied.

5.2 TEST PROCEDURE

According to FCC section 15.225(e), The frequency tolerance of the carrier signal shall be maintained within ±0.01% of the operating frequency over a temperature variation of -20 degrees to + 50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

5.3 TEST SETUP



The EUT which is powered by the Battery, is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 500hm; the path loss as the factor is calibrated to correct the reading.

5.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.



5.5 TEST RESULTS

Temperature:	25 ℃	Relative Humidity:	50%
Test Voltage:	DC 3.85V from battery	Test Mode:	TX Mode

13.56MHz

	Test	Conditions				
VOLTAGE(%)	Power (VDC)	Temperature (°C)	Frequency(Hz)	Deviation(%)	Limit	Verdict
100		+20°C(Ref)	13560752	0.00555	±0.01%	
100		-20	13560754	0.00556	±0.01%	
100		-10	13560754	0.00556	±0.01%	
100		0	13560751	0.00554	±0.01%	
100	3.85	10	13560755	0.00557	±0.01%	
100	3.00	20	13560752	0.00555	±0.01%	
100		25	13560750	0.00553	±0.01%	PASS
100		30	13560752	0.00555	±0.01%	
100		40	13560754	0.00556	±0.01%	
100		50	13560753	0.00555	±0.01%	
Battery End Point	3.55	20	13560752	0.00555	±0.01%	
115	4.4	20	13560751	0.00554	±0.01%	



6. 20DB BANDWIDTH

6.1 APPLIED PROCEDURES / LIMIT

According to FCC section 15.215(c), the 20dB bandwidth should be contained within the frequency band designated in the rule section under which the EUT is operated, it was measured with a spectrum analyzer connected the EUT while the EUT is operating in transmission mode.

6.2 TEST PROCEDURE

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §13.553-13.567 MHz and in subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated. In the case of intentional radiators operating under the provisions of subpart E, the emission bandwidth may span across multiple contiguous frequency bands identified in that subpart. The requirement to contain the designated bandwidth of the emission within the specified frequency band includes the effects from frequency sweeping, frequency hopping and other modulation techniques that may be employed as well as the frequency stability of the transmitter over expected variations in temperature and supply voltage. If a frequency stability is not specified in the regulations, it is recommended that the fundamental emission be kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of-band operation.

- 1. Set RBW = 1 kHz.
- 2. Set the video Mobile Phonewidth (VBW) ≥ 3 RBW.
- 3. Detector = Peak.
- 4. Trace mode = max hold.
- 5. Sweep = auto couple.
- Allow the trace to stabilize.
- 7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 d B relative to the maximum level measured in the fundamental emission.

6.3 TEST SETUP

EUT	SPECTRUM
	ANALYZER

6.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.



6.5 TEST RESULTS

Temperature:	25 ℃	Relative Humidity:	60%
Test Voltage:	DC 3.85V from battery	Test Mode:	TX Mode

13.56MH

	Measurement		
Centre Frequency	20dB Bandwidth	99% Bandwidth	Frequency Range (MHz)
	(KHz)	(KHz)	
13.56MHz	2.566	2.335	13.553-13.567





7. ANTENNA REQUIREMENT

7.1 STANDARD REQUIREMENT

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

7.2 EUT ANTENNA

The EUT antenna is PIFA Antenna. It comply with the standard requirement.





APPENDIX 1- PHOTOS OF TEST SETUP

Note: See test photos in setup photo document for the actual connections between Product and support equipment.

* * * * * END OF THE REPORT * * * *

