



RADIO TEST REPORT

Report No.:STS2103175W25

Issued for

Shanghai Unihertz E-Commerce Co., Ltd

Room 302, No. 5, Lane 59, Shennan Rd, Minhang district,
Shanghai, China 201108

Product Name:	Smart phone
Brand Name:	Unihertz
Model Name:	Titan pocket
Series Model:	N/A
FCC ID:	2AK6CTITANPOCKET
Test Standard:	FCC Part 15.407

Any reproduction of this document must be done in full. No single part of this document may be reproduced without permission from STS, all test data presented in this report is only applicable to presented test sample.

Shenzhen STS Test Services Co., Ltd.
A 1/F, Building B, Zhuoke Science Park, No.190 Chongqing Road, HepingShequ,
Fuyong Sub-District, Bao'an District, Shenzhen, Guang Dong, China
TEL: +86-755 3688 6288 FAX: +86-755 3688 6277 E-mail:sts@stsapp.com





TEST RESULT CERTIFICATION

Applicant's Name..... : Shanghai Unihertz E-Commerce Co., Ltd
Address : Room 302, No. 5, Lane 59, Shennan Rd, Minhang district, Shanghai, China 201108
Manufacturer's Name : OBLUE Communication Technology Co., Ltd.
Address : 7th floor, building B, dayou industrial and trade industrial park, heping yonghe road, fuyong street, baoan district, Shenzhen, China

Product Description

Product Name..... : Smart phone
Brand Name : Unihertz
Model Name : Titan pocket
Series Model..... : N/A

Test Standards..... : FCC Part15.407

Test Procedure..... ANSI C63.10-2013

This device described above has been tested by STS, the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of STS, this document only be altered or revised by STS, personal only, and shall be noted in the revision of the document.

Date of Test..... :

Date of receipt of test item : 26 Mar. 2021

Date (s) of performance of tests : 26 Mar. 2021 ~ 21 May 2021

Date of Issue..... : 21 May 2021

Test Result..... : **Pass**

Testing Engineer :

(Chris Chen)

Technical Manager :

(Sean she)

Authorized Signatory :

(Vita Li)





Table of Contents	Page
1 . SUMMARY OF TEST RESULTS	6
1.1 TEST FACTORY	7
1.2 MEASUREMENT UNCERTAINTY	7
2 . GENERAL INFORMATION	8
2.1 GENERAL DESCRIPTION OF THE EUT	8
2.2 DESCRIPTION OF TEST MODES	11
2.3 TEST SOFTWARE AND POWER LEVEL	12
2.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	13
2.5 DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS	14
2.6 EQUIPMENTS LIST FOR ALL TEST ITEMS	15
3 . EMC EMISSION TEST	16
3.1 CONDUCTED EMISSION MEASUREMENT	16
3.2 RADIATED EMISSION AND (BANDEGE) MEASUREMENT	20
4. POWER SPECTRAL DENSITY TEST	57
4.1 LIMIT	57
4.2 TEST PROCEDURE	57
4.3 DEVIATION FROM STANDARD	57
4.4 TEST SETUP	58
4.5 EUT OPERATION CONDITIONS	58
4.6 TEST RESULTS	59
5. BANDWIDTH MEASUREMENT	63
5.1 EMISSION BANDWIDTH (EBW) 26 BANDWID PROCEDURES / LIMIT	63
5.2 OCCUPIED BANDWIDTH (99%) TEST APPLIED PROCEDURES / LIMIT	66
5.3 MINIMUM EMISSION BANDWIDTH(6 DB) PROCEDURES / LIMIT	69
6. MAXIMUM CONDUCTED OUTPUT POWER	71
6.1 LIMIT	71
6.2 TEST PROCEDURE	71
6.3 DEVIATION FROM STANDARD	71
6.4 TEST SETUP	71
6.5 EUT OPERATION CONDITIONS	71
6.6 TEST RESULTS	72
7. AUTOMATICALLY DISCONTINUE TRANSMISSION	82
7.1 LIMIT OF AUTOMATICALLY DISCONTINUE TRANSMISSION	82
7.2 TEST RESULT OF AUTOMATICALLY DISCONTINUE TRANSMISSION	82



Table of Contents	Page
8. ANTENNA REQUIREMENT	83
8.1 STANDARD REQUIREMENT	83
8.2 EUT ANTENNA	83
APPENDIX - PHOTOS OF TEST SETUP	84



**Revision History**

Rev.	Issue Date	Report NO.	Effect Page	Contents
00	21 May 2021	STS2103175W25	ALL	Initial Issue





1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

§ 15.407, KDB 789033 D02 General U-NII Test Procedures New Rules v02r01

FCC Part 15.407		
FCC standard	Test Item	Results
15.207	AC Conducted Emission	PASS
15.407 (a) /15.407 (e)	26dB/6dB &99% Bandwidth	PASS
15.407(a)	Maximum Conducted Output Power	PASS
15.407(b)/15.205/15.209	Radiated Emission And (bandedge Emissions) Measurement	PASS
15.407(a)	Power Spectral Density	PASS
15.407(c)	Automatically Discontinue Transmission	PASS
15.203	Antenna Requirement	PASS

NOTE:

- (1) "N/A" denotes test is not applicable in this Test Report.
- (2) All tests are according to ANSI C63.10-2013.



1.1 TEST FACTORY

SHENZHEN STS TEST SERVICES CO., LTD

Add. : A 1/F, Building B, Zhuoke Science Park, No.190 Chongqing Road, HepingShequ, Fuyong Sub-District, Bao'an District, Shenzhen, Guang Dong, China

FCC test Firm Registration Number: 625569

IC test Firm Registration Number: 12108A

A2LA Certificate No.: 4338.01

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately **95 %**.

No.	Item	Uncertainty
1	RF output power, conducted	$\pm 0.68\text{dB}$
2	Unwanted Emissions, conducted	$\pm 2.988\text{dB}$
3	All emissions, radiated 9K-30MHz	$\pm 2.68\text{dB}$
4	All emissions, radiated 30M-1GHz	$\pm 4.39\text{dB}$
5	All emissions, radiated 1G-6GHz	$\pm 5.10\text{dB}$
6	All emissions, radiated >6G	$\pm 5.48\text{dB}$
7	Conducted Emission (9KHz-150KHz)	$\pm 2.79\text{dB}$
8	Conducted Emission (150KHz-30MHz)	$\pm 2.80\text{dB}$



2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF THE EUT

Product Name	Smart phone								
Trade Name	Unihertz								
Model Name	Titan pocket								
Series Model	N/A								
Model Difference	N/A								
Product Description	The EUT is a Smart phone <table><tr><td>Operation Frequency:</td><td>IEEE 802.11a/ n(HT20)/ac(VHT20): 5.180GHz-5.240GHz IEEE 802.11n(HT40)/ac(VHT40): 5.190GHz-5.310GHz IEEE 802.11ac(VHT80): 5.210GHz IEEE 802.11a/ n(HT20)/ac(VHT20): 5.260GHz-5.320GHz IEEE 802.11n(HT40)/ac(VHT40): 5.270GHz-5.310GHz IEEE 802.11ac(VHT80): 5.290GHz IEEE 802.11a/ n(HT20)/ac(VHT20): 5.500GHz-5.700GHz IEEE 802.11n(HT40)/ac(VHT40): 5.510GHz-5.670GHz IEEE 802.11ac(VHT80): 5.530GHz-5.610GHz IEEE 802.11a/ n(HT20)/ac(VHT20): 5.745GHz-5.825GHz IEEE 802.11n(HT40)/ac(VHT40): 5.755GHz-5.795GHz IEEE 802.11ac(VHT80): 5.775GHz</td></tr><tr><td>Modulation Type:</td><td>802.11a(OFDM): BPSK,QPSK,16-QAM,64-QAM 802.11n(OFDM): BPSK,QPSK,16-QAM,64-QAM 802.11ac(OFDM): BPSK,QPSK,16-QAM,64-QAM,256-QAM</td></tr><tr><td>Antenna Designation:</td><td>Please refer to the Note 3.</td></tr><tr><td>Max.Output Power(Conducted):</td><td>7.23 dBm</td></tr></table> More details of EUT technical specification, please refer to the User Manual.	Operation Frequency:	IEEE 802.11a/ n(HT20)/ac(VHT20): 5.180GHz-5.240GHz IEEE 802.11n(HT40)/ac(VHT40): 5.190GHz-5.310GHz IEEE 802.11ac(VHT80): 5.210GHz IEEE 802.11a/ n(HT20)/ac(VHT20): 5.260GHz-5.320GHz IEEE 802.11n(HT40)/ac(VHT40): 5.270GHz-5.310GHz IEEE 802.11ac(VHT80): 5.290GHz IEEE 802.11a/ n(HT20)/ac(VHT20): 5.500GHz-5.700GHz IEEE 802.11n(HT40)/ac(VHT40): 5.510GHz-5.670GHz IEEE 802.11ac(VHT80): 5.530GHz-5.610GHz IEEE 802.11a/ n(HT20)/ac(VHT20): 5.745GHz-5.825GHz IEEE 802.11n(HT40)/ac(VHT40): 5.755GHz-5.795GHz IEEE 802.11ac(VHT80): 5.775GHz	Modulation Type:	802.11a(OFDM): BPSK,QPSK,16-QAM,64-QAM 802.11n(OFDM): BPSK,QPSK,16-QAM,64-QAM 802.11ac(OFDM): BPSK,QPSK,16-QAM,64-QAM,256-QAM	Antenna Designation:	Please refer to the Note 3.	Max.Output Power(Conducted):	7.23 dBm
Operation Frequency:	IEEE 802.11a/ n(HT20)/ac(VHT20): 5.180GHz-5.240GHz IEEE 802.11n(HT40)/ac(VHT40): 5.190GHz-5.310GHz IEEE 802.11ac(VHT80): 5.210GHz IEEE 802.11a/ n(HT20)/ac(VHT20): 5.260GHz-5.320GHz IEEE 802.11n(HT40)/ac(VHT40): 5.270GHz-5.310GHz IEEE 802.11ac(VHT80): 5.290GHz IEEE 802.11a/ n(HT20)/ac(VHT20): 5.500GHz-5.700GHz IEEE 802.11n(HT40)/ac(VHT40): 5.510GHz-5.670GHz IEEE 802.11ac(VHT80): 5.530GHz-5.610GHz IEEE 802.11a/ n(HT20)/ac(VHT20): 5.745GHz-5.825GHz IEEE 802.11n(HT40)/ac(VHT40): 5.755GHz-5.795GHz IEEE 802.11ac(VHT80): 5.775GHz								
Modulation Type:	802.11a(OFDM): BPSK,QPSK,16-QAM,64-QAM 802.11n(OFDM): BPSK,QPSK,16-QAM,64-QAM 802.11ac(OFDM): BPSK,QPSK,16-QAM,64-QAM,256-QAM								
Antenna Designation:	Please refer to the Note 3.								
Max.Output Power(Conducted):	7.23 dBm								
Test Channel	Please refer to the Note 2.								
Adapter	Input: 100-240V 50/60Hz 0.6A Output: 6V 3.0A 9V 2.0A 12V 1.5A								
Battery	Rated Voltage:3.85V Charge Limit Voltage:4.4V Capacity: 4000MAH								
Hardware version number	G66_V2.5								
Software version number	Titan_pocket_20210326								
Connecting I/O Port(s)	Please refer to the Note 1.								



Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User Manual.

Operation Frequency of channel			
5.180GHz-5.240GHz		5.500GHz-5.720GHz	
Channel	Frequency	Channel	Frequency
36	5180	100	5500
38	5190	102	5510
40	5200	104	5520
42	5210	106	5530
44	5220	108	5540
46	5230	110	5550
48	5240	112	5560
		116	5580
		118	5590
5.260GHz-5.320GHz		120	5600
Channel	Frequency	122	5610
52	5260	124	5620
54	5270	126	5630
56	5280	128	5640
58	5290	132	5660
60	5300	134	5670
62	5310	136	5680
64	5320	140	5700
5.745GHz-5.825GHz			
Channel	Frequency		
149	5745		
151	5755		
153	5765		
155	5775		
157	5785		
159	5795		
161	5805		
165	5825		

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Carrier Frequency Channel

5GHz:

For 802.11a/n(HT20) /ac (VHT20)			
Channel	Freq.(MHz)	Channel	Freq.(MHz)
36	5180	52	5260
40	5200	60	5300
48	5240	64	5320



For 802.11a/n(HT20) /ac (VHT20)

Channel	Freq.(MHz)	Channel	Freq.(MHz)
100	5500	149	5745
116	5580	157	5785
140	5700	165	5825

For 802.11n(HT40) /ac (VHT40)

Channel	Freq.(MHz)	Channel	Freq.(MHz)
38	5190	54	5270
46	5230	62	5310

For 802.11n(HT40) /ac (VHT40)

Channel	Freq.(MHz)	Channel	Freq.(MHz)
102	5510	151	5755
110	5550	159	5795
134	5670		

For 802.11ac (VHT80)

Channel	Freq.(MHz)	Channel	Freq.(MHz)
42	5210	155	5775

For 802.11ac (VHT80)

Channel	Freq.(MHz)	Channel	Freq.(MHz)
106	5530	155	5775
122	5610		

3.	Ant	Brand	Model Name	Ant Type	Connector	Gain (dBi)	NOTE
	A	Unihertz	Titan pocket	PIFA	N/A	5.2GWIFI: 1.11dBi 5.3GWIFI: 0.56dBi 5.6GWIFI: 3.9dBi 5.8GWIFI: 4.94dBi	WLAN Ant

Note: The antenna information refer the manufacturer provide report, applicable only to the tested sample identified in the report.



2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generated from EUT, the test system was pre-scanning tested based on the consideration of following EUT operation mode or test configuration mode which possibly have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Worst Mode	Description	Data Rate
Mode 1	TX IEEE 802.11a HT20 CH36&CH40&CH48	6 Mbps
Mode 2	TX IEEE 802.11a HT20 CH52&CH60&CH64	6 Mbps
Mode 3	TX IEEE 802.11a HT20 CH100&CH116&CH140	6 Mbps
Mode 4	TX IEEE 802.11a HT20 CH149&CH157&CH165	6 Mbps
Mode 5	TX IEEE 802.11n HT20 CH36&CH40&CH48	MCS 0
Mode 6	TX IEEE 802.11ac HT20 CH36&CH40&CH48	NSS1 MCS0
Mode 7	TX IEEE 802.11n HT20 CH52&CH60&CH64	MCS 0
Mode 8	TX IEEE 802.11ac HT20 CH52&CH60&CH64	NSS1 MCS0
Mode 9	TX IEEE 802.11n HT20 CH100&CH116&CH140	MCS 0
Mode 10	TX IEEE 802.11ac HT20 CH100&CH116&CH140	NSS1 MCS0
Mode 11	TX IEEE 802.11n HT20 CH149&CH157&CH165	MCS 0
Mode 12	TX IEEE 802.11ac HT20 CH149&CH157&CH165	NSS1 MCS0
Mode 13	TX IEEE 802.11n HT40 CH38&CH46	MCS 0
Mode 14	TX IEEE 802.11ac HT40 CH38&CH46	NSS1 MCS0
Mode 15	TX IEEE 802.11n HT40 CH54 &CH62	MCS 0
Mode 16	TX IEEE 802.11ac HT40 CH54 &CH62	NSS1 MCS0
Mode 17	TX IEEE 802.11n HT40 CH102&CH110&CH134	MCS 0
Mode 18	TX IEEE 802.11ac HT40 CH102&CH110&CH134	NSS1 MCS0
Mode 19	TX IEEE 802.11n HT40 CH151&CH159	MCS 0
Mode 20	TX IEEE 802.11ac HT40 CH151&CH159	NSS1 MCS0
Mode 21	TX IEEE 802.11ac HT80 CH42	NSS1 MCS0
Mode 22	TX IEEE 802.11ac HT80 CH58	NSS1 MCS0
Mode 23	TX IEEE 802.11ac HT80 CH106&122	NSS1 MCS0
Mode 24	TX IEEE 802.11ac HT80 CH155	NSS1 MCS0

- Note: (1) The measurements are performed at the highest, middle, lowest available channels.
(2) The measurements are performed at all Bit Rate of Transmitter, the worst data was reported.
(3) We have been tested for all available U.S. voltage and frequencies (For 120V, 50/60Hz and 240V, 50/60Hz) for which the device is capable of operation.
(4) The battery is fully-charged during the radiated and RF conducted test.



AC Conducted Emission

Test Case	
AC Conducted Emission	Mode 25: Keeping TX + WLAN Link

2.3 TEST SOFTWARE AND POWER LEVEL

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level.

RF Function	Type	Mode Or Modulation type	ANT Gain(dBi)	Power Class	Software For Testing
WIFI(5G)	5G WIFI Band1 (5150MHz-5250MHz)	802.11a	1.11	10	Engineering mode
		802.11n(HT20)		10	
		802.11n(HT40)		12	
		802.11ac(VHT20)		11	
		802.11ac(VHT40)		12	
		802.11ac(VHT80)		12	
RF Function	Type	Mode Or Modulation type	ANT Gain(dBi)	Power Class	Software For Testing
WIFI(5G)	5G WIFI Band2 (5250MHz-5350MHz)	802.11a	0.56	10	Engineering mode
		802.11n(HT20)		10	
		802.11n(HT40)		12	
		802.11ac(VHT20)		10	
		802.11ac(VHT40)		12	
		802.11ac(VHT80)		12	
RF Function	Type	Mode Or Modulation type	ANT Gain(dBi)	Power Class	Software For Testing
WIFI(5G)	5G WIFI Band3 (5470MHz-5725MHz)	802.11a	3.9	10	Engineering mode
		802.11n(HT20)		10	
		802.11n(HT40)		10	
		802.11ac(VHT20)		10	
		802.11ac(VHT40)		10	
		802.11ac(VHT80)		12	




RF Function	Type	Mode Or Modulation type	ANT Gain(dBi)	Power Class	Software For Testing
WIFI(5G)	5G WIFI Band4 (5725MHz-5875MHz)	802.11a	1.4	17	Engineering mode
		802.11n(HT20)		17	
		802.11n(HT40)		17	
		802.11ac(VHT20)		17	
		802.11ac(VHT40)		17	
		802.11ac(VHT80)		18	

2.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Radiated Spurious EmissionTest



Conducted Emission Test





2.5 DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Necessary accessories

Item	Equipment	Mfr/Brand	Model/Type No.	Length	Note
E-1	Adapter	Unihertz	TPA-10120150UU	N/A	N/A
C-1	DC Cable	N/A	N/A	100cm	NO

Support units

Item	Equipment	Mfr/Brand	Model/Type No.	Length	Note
N/A	N/A	N/A	N/A	N/A	N/A

Note:

- (1) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (2) “YES” is means “with core”; “NO” is means “without core”.

**2.6 EQUIPMENTS LIST FOR ALL TEST ITEMS****Radiation Test equipment**

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
Test Receiver	R&S	ESCI	101427	2020.10.12	2021.10.11
Signal Analyzer	R&S	FSV 40-N	101823	2020.10.10	2021.10.09
Active loop Antenna	ZHINAN	ZN30900C	16035	2019.07.11	2021.07.10
Bilog Antenna	TESEQ	CBL6111D	34678	2020.10.12	2022.10.11
Horn Antenna	SCHWARZBECK	BBHA 9120D	02014	2019.10.15	2021.10.14
SHF-EHF Horn Antenna (18G-40GHz)	A-INFO	LB-180400-KF	J211020657	2020.10.12	2022.10.11
Pre-Amplifier(0.1M-3G Hz)	EM	EM330	060665	2020.10.12	2021.10.11
Pre-Amplifier (1G-18GHz)	SKET	LNPA-01018G-45	SK2018080901	2020.10.12	2021.10.11
Pre-Amplifier (18G-40GHz)	SKET	LNPA-1840-50	SK2018101801	2020.10.10	2021.10.09
Temperature & Humidity	HH660	Mieo	N/A	2020.10.13	2021.10.12
Turn table	EM	SC100_1	60531	N/A	N/A
Antenna mast	EM	SC100	N/A	N/A	N/A
Test SW	FARAD	EZ-EMC(Ver.STSLAB-03A1 RE)			

Conduction Test equipment

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
Test Receiver	R&S	ESCI	101427	2020.10.12	2021.10.11
LISN	R&S	ENV216	101242	2020.10.12	2021.10.11
LISN	EMCO	3810/2NM	23625	2020.10.12	2021.10.11
Temperature & Humidity	HH660	Mieo	N/A	2020.10.13	2021.10.12
Test SW	FARAD	EZ-EMC(Ver.STSLAB-03A1 CE)			

RF Connected Test

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
Power Sensor	Keysight	U2021XA	MY55520005	2020.10.10	2021.10.09
			MY55520006	2020.10.10	2021.10.09
			MY56120038	2020.10.10	2021.10.09
			MY56280002	2020.10.10	2021.10.09
Signal Analyzer	Agilent	N9020A	MY51110105	2021.03.04	2022.03.03
Temperature & Humidity	HH660	Mieo	N/A	2020.10.13	2021.10.12
Test SW	FARAD	EZ-EMC(Ver.STSLAB-03A1 RE)			



3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Class B (dBuV)		Standard
	Quasi-peak	Average	
0.15 -0.5	66 - 56 *	56 - 46 *	CISPR
0.50 -5.0	56.00	46.00	CISPR
5.0 -30.0	60.00	50.00	CISPR

0.15 -0.5	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	56.00	46.00	FCC
5.0 -30.0	60.00	50.00	FCC

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz


3.1.2 TEST PROCEDURE

- The EUT is 0.8 m from the horizontal ground plane and 0.4 m from the vertical ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments are powered from additional LISN(s). The LISN provides 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN is at least 80 cm from the nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.1.3 DEVIATION FROM TEST STANDARD

No deviation

3.1.4 TEST SETUP



Note: 1. Support units were connected to second LISN.

2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes support units.

3.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.



3.1.6 TEST RESULTS


Temperature:	21.8(C)	Relative Humidity:	54%RH
Test Voltage:	AC 120V/60Hz	Phase:	L
Test Mode :	Mode 25		

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1500	29.68	20.33	50.01	66.00	-15.99	QP
2	0.1500	12.03	20.33	32.36	56.00	-23.64	AVG
3	0.6460	28.52	20.40	48.92	56.00	-7.08	QP
4	0.6460	15.30	20.40	35.70	46.00	-10.30	AVG
5	1.9420	18.86	20.30	39.16	56.00	-16.84	QP
6	1.9420	4.50	20.30	24.80	46.00	-21.20	AVG
7	3.9900	17.43	20.40	37.83	56.00	-18.17	QP
8	3.9900	1.95	20.40	22.35	46.00	-23.65	AVG
9	8.6740	19.62	20.92	40.54	60.00	-19.46	QP
10	8.6740	3.80	20.92	24.72	50.00	-25.28	AVG
11	17.3620	25.79	22.28	48.07	60.00	-11.93	QP
12	17.3620	13.71	22.28	35.99	50.00	-14.01	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Margin = Result (Result = Reading + Factor) - Limit
3. Factor = LISN factor + Cable loss + Limiter (10dB)

100.0 dBuV






Temperature:	21.8(C)	Relative Humidity:	54%RH
Test Voltage	AC 120V/60Hz	Phase:	N
Test Mode	Mode 25		

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1500	30.51	20.33	50.84	66.00	-15.16	QP
2	0.1500	13.59	20.33	33.92	56.00	-22.08	AVG
3	0.6620	23.70	20.39	44.09	56.00	-11.91	QP
4	0.6620	11.60	20.39	31.99	46.00	-14.01	AVG
5	1.3220	15.52	20.30	35.82	56.00	-20.18	QP
6	1.3220	2.16	20.30	22.46	46.00	-23.54	AVG
7	3.7780	13.58	20.39	33.97	56.00	-22.03	QP
8	3.7780	-0.21	20.39	20.18	46.00	-25.82	AVG
9	8.7300	15.07	20.94	36.01	60.00	-23.99	QP
10	8.7300	0.83	20.94	21.77	50.00	-28.23	AVG
11	19.9100	22.73	22.88	45.61	60.00	-14.39	QP
12	19.9100	8.79	22.88	31.67	50.00	-18.33	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Margin = Result (Result = Reading + Factor) - Limit
3. Factor = LISN factor + Cable loss + Limiter (10dB)





3.2 RADIATED EMISSION AND (BANDEDGE) MEASUREMENT

3.2.1 RADIATED EMISSION LIMITS (Frequency Range 9kHz-1000MHz)

In case the emission fall within the restricted band specified on 15.407(b)7&15.205/209(a), then the limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (microvolt/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	68.2	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15E.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

LIMITS OF RESTRICTED FREQUENCY BANDS

FREQUENCY (MHz)	FREQUENCY (MHz)	FREQUENCY (MHz)	FREQUENCY (GHz)
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	Above 38.6
13.36-13.41			

Note: In case the emission radiated emission above 1000MHz fall within the restricted band the restricted frequency bands, the peak limit is 74 dBuV/m.



LIMITS OF EMISSIONS OUTSIDE OF THE FREQUENCY BANDS

Undesirable emission limits. Except as shown in paragraph (b)(7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

- (1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (4) For transmitters operating in the 5.725-5.85 GHz band:
 - (i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

Note: dBuV/m(at 3M) = EIRP(dBm) + 95.2.

Peak Limit = -27dBm/MHz + 95.2 = 68.2 dBuV/m.

Spectrum Parameter	Setting
Attenuation	Auto
Detector	Peak
Start Frequency	1000 MHz (Peak/AV)
Stop Frequency	10th carrier harmonic (Peak/AV)
RB / VB (emission in restricted band)	1 MHz / 1 MHz, AV=1 MHz /3 MHz

For Band edge

Spectrum Parameter	Setting
Detector	Peak
RB / VB (emission in restricted band)	1 MHz / 1 MHz, AV=1 MHz /3 MHz

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~90kHz / RB 200Hz for PK & AV
Start ~ Stop Frequency	90kHz~110kHz / RB 200Hz for QP
Start ~ Stop Frequency	110kHz~490kHz / RB 200Hz for PK & AV
Start ~ Stop Frequency	490kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP



3.2.2 TEST PROCEDURE

- a. The measuring distance at 3 m shall be used for measurements at frequency 0.009MHz up to 1GHz, and above 1GHz.
- b. The EUT was placed on the top of a rotating table 0.8 m (above 1GHz is 1.5 m) above the ground at a 3 m anechoic chamber test site. The table was rotated 360 degree to determine the position of the highest radiation.
- c. The height of the equipment shall be 0.8 m (above 1GHz is 1.5 m); the height of the test antenna shall vary between 1 m to 4 m. Horizontal and vertical polarization of the antenna are set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and QuasiPeak detector mode will be re-measured.
- e. If the Peak Mode measured value is compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and no additional QP Mode measurement was performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported.

3.2.2 DEVIATION FROM TEST STANDARD


No deviation

3.2.3 TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz





3.2.4 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

3.2.5 FIELD STRENGTH CALCULATION

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CL - AG$$

Where

FS = Field Strength

CL = Cable Attenuation Factor (Cable Loss)

RA = Reading Amplitude

AG = Amplifier Gain

AF = Antenna Factor

For example

Frequency	FS	RA	AF	CL	AG	Factor
(MHz)	(dBμV/m)	(dBμV/m)	(dB)	(dB)	(dB)	(dB)
300	40	58.1	12.2	1.6	31.9	-18.1

$$\text{Factor} = \text{AF} + \text{CL} - \text{AG}$$

**3.2.6 TEST RESULTS (Between 9KHz – 30 MHz)**

Temperature:	23.1(C)	Relative Humidity:	60%RH
Test Voltage :	DC 3.85V	Polarization :	--
Test Mode :	TX Mode		

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	PASS
--	--	--	--	PASS

Note:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log (\text{specific distance/test distance})$ (dB);

Limit line = specific limits(dBuV) + distance extrapolation factor.


**3.2.7 TEST RESULTS (Between 30MHz – 1GHz)**

Temperature	23.1(C)	Relative Humidity:	60%RH
Test Voltage	DC 3.85V	Polarization:	Horizontal
Test Mode	Mode 1~24(Mode 21 worst mode)		

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	36.7900	27.52	-16.39	11.13	40.00	-28.87	QP
2	390.8400	38.37	-11.54	26.83	46.00	-19.17	QP
3	552.8300	27.07	-5.69	21.38	46.00	-24.62	QP
4	733.2500	29.34	-2.35	26.99	46.00	-19.01	QP
5	841.8900	26.99	-0.42	26.57	46.00	-19.43	QP
6	973.8100	26.64	2.25	28.89	54.00	-25.11	QP

Remark:

1. Margin = Result (Result =Reading + Factor)-Limit
2. Factor= Antenna factor+Cable attenuation factor(cable loss)-Amplifier gain






Temperature	23.1(C)	Relative Humidity:	60%RH
Test Voltage	DC 3.85V	Polarization:	Vertical
Test Mode	Mode 1~24(Mode 21 worst mode)		

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	98.8700	34.88	-20.31	14.57	43.50	-28.93	QP
2	281.2300	28.36	-15.56	12.80	46.00	-33.20	QP
3	411.2100	30.00	-10.51	19.49	46.00	-26.51	QP
4	566.4100	28.96	-5.57	23.39	46.00	-22.61	QP
5	767.2000	30.48	-2.29	28.19	46.00	-17.81	QP
6	965.0800	27.99	1.89	29.88	54.00	-24.12	QP

Remark:

1. Margin = Result (Result = Reading + Factor) - Limit
2. Factor = Antenna factor + Cable attenuation factor (cable loss) - Amplifier gain



**3.2.8 TEST RESULTS (Above 1000 MHz)****Band I 5150-5250MHz**

Frequency (MHz)	Reading (dBuV)	Amplifier (dB)	Loss (dB)	Antenna Factor (dB/m)	Orrected Factor (dB)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Comment
(802.11ac(VHT80)/ 5210 MHz)										
3264.59	45.27	44.70	6.70	28.20	-9.80	35.47	68.20	-32.73	Pk	Vertical
3264.59	41.76	44.70	6.70	28.20	-9.80	31.96	54.00	-22.04	AV	Vertical
3275.97	44.00	44.70	6.70	28.20	-9.80	34.20	68.20	-34.00	Pk	Horizontal
3275.97	41.68	44.70	6.70	28.20	-9.80	31.88	54.00	-22.12	AV	Horizontal
4014.24	38.97	44.20	7.90	29.70	-6.60	32.37	68.20	-35.83	Pk	Vertical
4014.24	36.18	44.20	7.90	29.70	-6.60	29.58	54.00	-24.42	AV	Vertical
4019.11	39.66	44.20	7.90	29.70	-6.60	33.06	68.20	-35.14	Pk	Horizontal
4019.11	36.71	44.20	7.90	29.70	-6.60	30.11	54.00	-23.89	AV	Horizontal
7265.24	36.62	43.50	11.40	35.50	3.40	40.02	68.20	-28.18	Pk	Vertical
7265.24	33.63	43.50	11.40	35.50	3.40	37.03	54.00	-16.97	AV	Vertical
7276.86	36.69	43.50	11.40	35.50	3.40	40.09	68.20	-28.11	Pk	Horizontal
7276.86	34.24	43.50	11.40	35.50	3.40	37.64	54.00	-16.36	AV	Horizontal
10420.37	40.22	44.50	13.80	38.80	8.10	48.32	68.20	-19.88	Pk	Vertical
10420.37	36.66	44.50	13.80	38.80	8.10	44.76	54.00	-9.24	AV	Vertical
10419.98	39.23	44.50	13.80	38.80	8.10	47.33	68.20	-20.87	Pk	Horizontal
10419.98	35.92	44.50	13.80	38.80	8.10	44.02	54.00	-9.98	AV	Horizontal
11092.60	32.81	43.60	14.30	39.50	10.20	43.01	68.20	-25.19	Pk	Vertical
11092.60	30.00	43.60	14.30	39.50	10.20	40.20	54.00	-13.80	AV	Vertical
11080.93	33.97	43.60	14.30	39.50	10.20	44.17	68.20	-24.03	Pk	Horizontal
11080.93	31.03	43.60	14.30	39.50	10.20	41.23	54.00	-12.77	AV	Horizontal
13359.36	31.79	42.60	15.90	38.90	12.20	43.99	68.20	-24.21	Pk	Vertical
13359.36	28.88	42.60	15.90	38.90	12.20	41.08	54.00	-12.92	AV	Vertical
13376.90	31.85	42.60	15.90	38.90	12.20	44.05	68.20	-24.15	Pk	Horizontal
13376.90	30.08	42.60	15.90	38.90	12.20	42.28	54.00	-11.72	AV	Horizontal

Remark:

- Factor = Antenna Factor + Cable Loss – Pre-amplifier.
- Scan with 802.11a,802.11n (HT-20),802.11n (HT-40), 802.11ac (VHT-20),802.11ac (VHT-40), 802.11ac (VHT-80) the worst case is 802.11ac (VHT-80).
- The frequency emission of peak points that did not show above the forms are at least 20dB below the limit, the frequency emission is mainly from the environment noise.

**Band II 5250-5350MHz**

Frequency (MHz)	Reading (dBuV)	Amplifier (dB)	Loss (dB)	Antenna Factor (dB/m)	Orrected Factor (dB)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Comment
Low Channel (802.11ac(VHT40)/ 5270 MHz)										
3260.88	44.47	44.70	6.70	28.20	-9.80	34.67	68.20	-33.53	Pk	Vertical
3260.88	42.06	44.70	6.70	28.20	-9.80	32.26	54.00	-21.74	AV	Vertical
3263.84	45.17	44.70	6.70	28.20	-9.80	35.37	68.20	-32.83	Pk	Horizontal
3263.84	40.89	44.70	6.70	28.20	-9.80	31.09	54.00	-22.91	AV	Horizontal
3995.09	38.99	44.20	7.90	29.70	-6.60	32.39	68.20	-35.81	Pk	Vertical
3995.09	36.07	44.20	7.90	29.70	-6.60	29.47	54.00	-24.53	AV	Vertical
4004.90	39.28	44.20	7.90	29.70	-6.60	32.68	68.20	-35.52	Pk	Horizontal
4004.90	35.75	44.20	7.90	29.70	-6.60	29.15	54.00	-24.85	AV	Horizontal
7242.08	37.32	43.50	11.40	35.50	3.40	40.72	68.20	-27.48	Pk	Vertical
7242.08	34.56	43.50	11.40	35.50	3.40	37.96	54.00	-16.04	AV	Vertical
7248.94	37.07	43.50	11.40	35.50	3.40	40.47	68.20	-27.73	Pk	Horizontal
7248.94	34.18	43.50	11.40	35.50	3.40	37.58	54.00	-16.42	AV	Horizontal
10540.27	39.92	44.50	13.90	38.80	8.20	48.12	68.20	-20.08	Pk	Vertical
10540.27	36.56	44.50	13.90	38.80	8.20	44.76	54.00	-9.24	AV	Vertical
10540.17	39.46	44.50	13.90	38.80	8.20	47.66	68.20	-20.54	Pk	Horizontal
10540.17	35.89	44.50	13.90	38.80	8.20	44.09	54.00	-9.91	AV	Horizontal
11056.93	32.87	43.60	14.30	39.50	10.20	43.07	68.20	-25.13	Pk	Vertical
11056.93	30.83	43.60	14.30	39.50	10.20	41.03	54.00	-12.97	AV	Vertical
11042.57	34.23	43.60	14.30	39.50	10.20	44.43	68.20	-23.77	Pk	Horizontal
11042.57	30.80	43.60	14.30	39.50	10.20	41.00	54.00	-13.00	AV	Horizontal
13322.71	31.81	42.60	15.90	38.90	12.20	44.01	68.20	-24.19	Pk	Vertical
13322.71	29.91	42.60	15.90	38.90	12.20	42.11	54.00	-11.89	AV	Vertical
13313.28	32.01	42.60	15.90	38.90	12.20	44.21	68.20	-23.99	Pk	Horizontal
13313.28	29.80	42.60	15.90	38.90	12.20	42.00	54.00	-12.00	AV	Horizontal
High Channel (802.11ac(VHT40)/ 5310 MHz)										
3257.06	44.96	44.70	6.70	28.20	-9.80	35.16	68.20	-33.04	Pk	Vertical
3257.06	41.03	44.70	6.70	28.20	-9.80	31.23	54.00	-22.77	AV	Vertical
3256.71	43.68	44.70	6.70	28.20	-9.80	33.88	68.20	-34.32	Pk	Horizontal
3256.71	41.09	44.70	6.70	28.20	-9.80	31.29	54.00	-22.71	AV	Horizontal
3976.10	38.97	44.20	7.90	29.70	-6.60	32.37	68.20	-35.83	Pk	Vertical
3976.10	36.22	44.20	7.90	29.70	-6.60	29.62	54.00	-24.38	AV	Vertical
3976.45	38.82	44.20	7.90	29.70	-6.60	32.22	68.20	-35.98	Pk	Horizontal
3976.45	35.82	44.20	7.90	29.70	-6.60	29.22	54.00	-24.78	AV	Horizontal
7209.38	36.54	43.50	11.40	35.50	3.40	39.94	68.20	-28.26	Pk	Vertical
7209.38	34.74	43.50	11.40	35.50	3.40	38.14	54.00	-15.86	AV	Vertical
7215.64	37.73	43.50	11.40	35.50	3.40	41.13	68.20	-27.07	Pk	Horizontal
7215.64	34.62	43.50	11.40	35.50	3.40	38.02	54.00	-15.98	AV	Horizontal
10620.07	39.81	44.50	13.80	38.80	8.10	47.91	68.20	-20.29	Pk	Vertical
10620.07	35.94	44.50	13.80	38.80	8.10	44.04	54.00	-9.96	AV	Vertical
10620.29	38.63	44.50	13.80	38.80	8.10	46.73	68.20	-21.47	Pk	Horizontal
10620.29	35.69	44.50	13.80	38.80	8.10	43.79	54.00	-10.21	AV	Horizontal
11009.67	33.61	43.60	14.30	39.50	10.20	43.81	68.20	-24.39	Pk	Vertical
11009.67	29.77	43.60	14.30	39.50	10.20	39.97	54.00	-14.03	AV	Vertical
11007.24	33.29	43.60	14.30	39.50	10.20	43.49	68.20	-24.71	Pk	Horizontal
11007.24	30.46	43.60	14.30	39.50	10.20	40.66	54.00	-13.34	AV	Horizontal
13261.43	31.83	42.70	18.00	37.10	12.40	44.23	68.20	-23.97	Pk	Vertical
13261.43	29.19	42.70	18.00	37.10	12.40	41.59	54.00	-12.41	AV	Vertical
13264.72	31.48	42.70	18.00	37.10	12.40	43.88	68.20	-24.32	Pk	Horizontal
13264.72	28.74	42.70	18.00	37.10	12.40	41.14	54.00	-12.86	AV	Horizontal

Remark:

- Factor = Antenna Factor + Cable Loss – Pre-amplifier.
- Scan with 802.11a,802.11n (HT-20),802.11n (HT-40), 802.11ac (VHT-20),802.11ac (VHT-40), 802.11ac (VHT-80) the worst case is 802.11ac (VHT-40).
- The frequency emission of peak points that did not show above the forms are at least 20dB below the limit, the frequency emission is mainly from the environment noise.

**Band III 5470-5725MHz**

Frequency (MHz)	Reading (dBuV)	Amplifier (dB)	Loss (dB)	Antenna Factor (dB/m)	Orrected Factor (dB)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Comment
Low Channel (802.11ac(VHT80)/ 5530 MHz)										
3273.41	45.20	44.70	6.70	28.20	-9.80	35.40	68.20	-32.80	Pk	Vertical
3273.41	41.54	44.70	6.70	28.20	-9.80	31.74	54.00	-22.26	AV	Vertical
3265.60	45.26	44.70	6.70	28.20	-9.80	35.46	68.20	-32.74	Pk	Horizontal
3265.60	42.45	44.70	6.70	28.20	-9.80	32.65	54.00	-21.35	AV	Horizontal
4002.65	39.55	44.20	7.90	29.70	-6.60	32.95	68.20	-35.25	Pk	Vertical
4002.65	36.16	44.20	7.90	29.70	-6.60	29.56	54.00	-24.44	AV	Vertical
4007.35	40.13	44.20	7.90	29.70	-6.60	33.53	68.20	-34.67	Pk	Horizontal
4007.35	35.87	44.20	7.90	29.70	-6.60	29.27	54.00	-24.73	AV	Horizontal
7266.84	37.20	43.50	11.40	35.50	3.40	40.60	68.20	-27.60	Pk	Vertical
7266.84	33.92	43.50	11.40	35.50	3.40	37.32	54.00	-16.68	AV	Vertical
7257.03	37.80	43.50	11.40	35.50	3.40	41.20	68.20	-27.00	Pk	Horizontal
7257.03	34.08	43.50	11.40	35.50	3.40	37.48	54.00	-16.52	AV	Horizontal
10404.12	39.24	44.50	13.80	38.80	8.10	47.34	68.20	-20.86	Pk	Vertical
10404.12	36.69	44.50	13.80	38.80	8.10	44.79	54.00	-9.21	AV	Vertical
10415.11	39.63	44.50	13.80	38.80	8.10	47.73	68.20	-20.47	Pk	Horizontal
10415.11	36.94	44.50	13.80	38.80	8.10	45.04	54.00	-8.96	AV	Horizontal
11060.39	32.96	43.60	14.30	39.50	10.20	43.16	68.20	-25.04	Pk	Vertical
11060.39	31.24	43.60	14.30	39.50	10.20	41.44	54.00	-12.56	AV	Vertical
11059.98	34.04	43.60	14.30	39.50	10.20	44.24	68.20	-23.96	Pk	Horizontal
11059.98	30.85	43.60	14.30	39.50	10.20	41.05	54.00	-12.95	AV	Horizontal
13352.53	32.53	42.60	15.90	38.90	12.20	44.73	68.20	-23.47	Pk	Vertical
13352.53	30.16	42.60	15.90	38.90	12.20	42.36	54.00	-11.64	AV	Vertical
13363.30	32.04	42.60	15.90	38.90	12.20	44.24	68.20	-23.96	Pk	Horizontal
13363.30	28.91	42.60	15.90	38.90	12.20	41.11	54.00	-12.89	AV	Horizontal
High Channel (802.11ac(VHT80)/ 5610 MHz)										
3209.95	43.90	44.70	6.70	28.20	-9.80	34.10	68.20	-34.10	Pk	Vertical
3209.95	40.29	44.70	6.70	28.20	-9.80	30.49	54.00	-23.51	AV	Vertical
3210.05	43.34	44.70	6.70	28.20	-9.80	33.54	68.20	-34.66	Pk	Horizontal
3210.05	40.14	44.70	6.70	28.20	-9.80	30.34	54.00	-23.66	AV	Horizontal
3925.45	39.16	44.20	7.90	29.70	-6.60	32.56	68.20	-35.64	Pk	Vertical
3925.45	36.12	44.20	7.90	29.70	-6.60	29.52	54.00	-24.48	AV	Vertical
3935.33	38.79	44.20	7.90	29.70	-6.60	32.19	68.20	-36.01	Pk	Horizontal
3935.33	35.35	44.20	7.90	29.70	-6.60	28.75	54.00	-25.25	AV	Horizontal
7108.28	36.40	43.50	11.40	35.50	3.40	39.80	68.20	-28.40	Pk	Vertical
7108.28	33.96	43.50	11.40	35.50	3.40	37.36	54.00	-16.64	AV	Vertical
7117.84	36.06	43.50	11.40	35.50	3.40	39.46	68.20	-28.74	Pk	Horizontal
7117.84	33.35	43.50	11.40	35.50	3.40	36.75	54.00	-17.25	AV	Horizontal
10298.02	39.07	44.50	13.80	38.80	8.10	47.17	68.20	-21.03	Pk	Vertical
10298.02	36.57	44.50	13.80	38.80	8.10	44.67	54.00	-9.33	AV	Vertical
10297.36	38.54	44.50	13.80	38.80	8.10	46.64	68.20	-21.56	Pk	Horizontal
10297.36	35.47	44.50	13.80	38.80	8.10	43.57	54.00	-10.43	AV	Horizontal
11219.94	33.49	43.60	14.30	39.50	10.20	43.69	68.20	-24.51	Pk	Vertical
11219.94	29.92	43.60	14.30	39.50	10.20	40.12	54.00	-13.88	AV	Vertical
11219.97	33.21	43.60	14.30	39.50	10.20	43.41	68.20	-24.79	Pk	Horizontal
11219.97	30.32	43.60	14.30	39.50	10.20	40.52	54.00	-13.48	AV	Horizontal
13078.70	32.10	42.60	15.90	38.90	12.20	44.30	68.20	-23.90	Pk	Vertical
13078.70	28.80	42.60	15.90	38.90	12.20	41.00	54.00	-13.00	AV	Vertical
13073.86	31.59	42.60	15.90	38.90	12.20	43.79	68.20	-24.41	Pk	Horizontal
13073.86	28.76	42.60	15.90	38.90	12.20	40.96	54.00	-13.04	AV	Horizontal

Remark:

- Factor = Antenna Factor + Cable Loss – Pre-amplifier.
- Scan with 802.11a,802.11n (HT-20),802.11n (HT-40), 802.11ac (VHT-20),802.11ac (VHT-40), 802.11ac (VHT-80) the worst case is 802.11ac (VHT-80).
- The frequency emission of peak points that did not show above the forms are at least 20dB below the limit, the frequency emission is mainly from the environment noise.



Band IV(5.725-5.850) GHz

Frequency (MHz)	Reading (dBuV)	Amplifier (dB)	Loss (dB)	Antenna Factor (dB/m)	Orrected Factor (dB)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Comment
Low Channel (802.11a20 5745 MHz)										
3252.73	44.97	44.70	6.70	28.20	-9.80	35.17	68.20	-33.03	Pk	Vertical
3252.73	41.11	44.70	6.70	28.20	-9.80	31.31	54.00	-22.69	AV	Vertical
3249.10	44.59	44.70	6.70	28.20	-9.80	34.79	68.20	-33.41	Pk	Horizontal
3249.10	41.97	44.70	6.70	28.20	-9.80	32.17	54.00	-21.83	AV	Horizontal
3998.74	39.52	44.20	7.90	29.70	-6.60	32.92	68.20	-35.28	Pk	Vertical
3998.74	36.31	44.20	7.90	29.70	-6.60	29.71	54.00	-24.29	AV	Vertical
3986.25	38.79	44.20	7.90	29.70	-6.60	32.19	68.20	-36.01	Pk	Horizontal
3986.25	36.36	44.20	7.90	29.70	-6.60	29.76	54.00	-24.24	AV	Horizontal
7225.73	37.83	43.50	11.40	35.50	3.40	41.23	68.20	-26.97	Pk	Vertical
7225.73	34.63	43.50	11.40	35.50	3.40	38.03	54.00	-15.97	AV	Vertical
7216.99	37.24	43.50	11.40	35.50	3.40	40.64	68.20	-27.56	Pk	Horizontal
7216.99	33.66	43.50	11.40	35.50	3.40	37.06	54.00	-16.94	AV	Horizontal
10514.14	39.67	44.50	13.90	38.80	8.20	47.87	68.20	-20.33	Pk	Vertical
10514.14	36.15	44.50	13.90	38.80	8.20	44.35	54.00	-9.65	AV	Vertical
10512.92	38.91	44.50	13.90	38.80	8.20	47.11	68.20	-21.09	Pk	Horizontal
10512.92	36.87	44.50	13.90	38.80	8.20	45.07	54.00	-8.93	AV	Horizontal
11490.20	32.76	43.60	14.30	39.50	10.20	42.96	68.20	-25.24	Pk	Vertical
11490.20	29.82	43.60	14.30	39.50	10.20	40.02	54.00	-13.98	AV	Vertical
11490.03	33.58	43.60	14.30	39.50	10.20	43.78	68.20	-24.42	Pk	Horizontal
11490.03	30.62	43.60	14.30	39.50	10.20	40.82	54.00	-13.18	AV	Horizontal
13288.30	33.02	42.60	15.90	38.90	12.20	45.22	68.20	-22.98	Pk	Vertical
13288.30	29.72	42.60	15.90	38.90	12.20	41.92	54.00	-12.08	AV	Vertical
13282.45	32.40	42.60	15.90	38.90	12.20	44.60	68.20	-23.60	Pk	Horizontal
13282.45	28.62	42.60	15.90	38.90	12.20	40.82	54.00	-13.18	AV	Horizontal
Mid Channel (802.11a20/ 5785 MHz)										
3254.92	44.88	44.70	6.70	28.20	-9.80	35.08	68.20	-33.12	Pk	Vertical
3254.92	41.95	44.70	6.70	28.20	-9.80	32.15	54.00	-21.85	AV	Vertical
3259.26	44.88	44.70	6.70	28.20	-9.80	35.08	68.20	-33.12	Pk	Horizontal
3259.26	41.21	44.70	6.70	28.20	-9.80	31.41	54.00	-22.59	AV	Horizontal
3990.40	39.88	44.20	7.90	29.70	-6.60	33.28	68.20	-34.92	Pk	Vertical
3990.40	36.21	44.20	7.90	29.70	-6.60	29.61	54.00	-24.39	AV	Vertical
3990.44	39.89	44.20	7.90	29.70	-6.60	33.29	68.20	-34.91	Pk	Horizontal
3990.44	36.86	44.20	7.90	29.70	-6.60	30.26	54.00	-23.74	AV	Horizontal
7235.17	36.54	43.50	11.40	35.50	3.40	39.94	68.20	-28.26	Pk	Vertical
7235.17	34.32	43.50	11.40	35.50	3.40	37.72	54.00	-16.28	AV	Vertical
7230.92	37.93	43.50	11.40	35.50	3.40	41.33	68.20	-26.87	Pk	Horizontal
7230.92	34.21	43.50	11.40	35.50	3.40	37.61	54.00	-16.39	AV	Horizontal
10596.79	39.90	44.50	13.80	38.80	8.10	48.00	68.20	-20.20	Pk	Vertical
10596.79	37.09	44.50	13.80	38.80	8.10	45.19	54.00	-8.81	AV	Vertical
10586.20	39.34	44.50	13.80	38.80	8.10	47.44	68.20	-20.76	Pk	Horizontal
10586.20	35.74	44.50	13.80	38.80	8.10	43.84	54.00	-10.16	AV	Horizontal
11570.24	32.94	43.60	14.30	39.50	10.20	43.14	68.20	-25.06	Pk	Vertical
11570.24	30.94	43.60	14.30	39.50	10.20	41.14	54.00	-12.86	AV	Vertical
11570.30	32.71	43.60	14.30	39.50	10.20	42.91	68.20	-25.29	Pk	Horizontal
11570.30	30.81	43.60	14.30	39.50	10.20	41.01	54.00	-12.99	AV	Horizontal
13298.24	31.60	42.60	15.90	38.90	12.20	43.80	68.20	-24.40	Pk	Vertical
13298.24	29.27	42.60	15.90	38.90	12.20	41.47	54.00	-12.53	AV	Vertical
13290.73	32.25	42.60	15.90	38.90	12.20	44.45	68.20	-23.75	Pk	Horizontal
13290.73	28.98	42.60	15.90	38.90	12.20	41.18	54.00	-12.82	AV	Horizontal



High Channel (802.11a20/ 5825 MHz)										
3262.81	45.02	44.70	6.70	28.20	-9.80	35.22	68.20	-32.98	Pk	Vertical
3262.81	41.16	44.70	6.70	28.20	-9.80	31.36	54.00	-22.64	AV	Vertical
3256.71	45.12	44.70	6.70	28.20	-9.80	35.32	68.20	-32.88	Pk	Horizontal
3256.71	41.88	44.70	6.70	28.20	-9.80	32.08	54.00	-21.92	AV	Horizontal
3989.60	38.85	44.20	7.90	29.70	-6.60	32.25	68.20	-35.95	Pk	Vertical
3989.60	36.70	44.20	7.90	29.70	-6.60	30.10	54.00	-23.90	AV	Vertical
3998.43	39.25	44.20	7.90	29.70	-6.60	32.65	68.20	-35.55	Pk	Horizontal
3998.43	36.33	44.20	7.90	29.70	-6.60	29.73	54.00	-24.27	AV	Horizontal
7218.17	37.62	43.50	11.40	35.50	3.40	41.02	68.20	-27.18	Pk	Vertical
7218.17	34.86	43.50	11.40	35.50	3.40	38.26	54.00	-15.74	AV	Vertical
7225.57	37.29	43.50	11.40	35.50	3.40	40.69	68.20	-27.51	Pk	Horizontal
7225.57	33.88	43.50	11.40	35.50	3.40	37.28	54.00	-16.72	AV	Horizontal
10628.46	39.09	44.50	13.80	38.80	8.10	47.19	68.20	-21.01	Pk	Vertical
10628.46	36.43	44.50	13.80	38.80	8.10	44.53	54.00	-9.47	AV	Vertical
10640.35	39.08	44.50	13.80	38.80	8.10	47.18	68.20	-21.02	Pk	Horizontal
10640.35	35.78	44.50	13.80	38.80	8.10	43.88	54.00	-10.12	AV	Horizontal
11649.95	33.50	43.60	14.30	39.50	10.20	43.70	68.20	-24.50	Pk	Vertical
11649.95	29.98	43.60	14.30	39.50	10.20	40.18	54.00	-13.82	AV	Vertical
11650.31	33.43	43.60	14.30	39.50	10.20	43.63	68.20	-24.57	Pk	Horizontal
11650.31	30.25	43.60	14.30	39.50	10.20	40.45	54.00	-13.55	AV	Horizontal
13290.48	31.76	42.70	18.00	37.10	12.40	44.16	68.20	-24.04	Pk	Vertical
13290.48	29.30	42.70	18.00	37.10	12.40	41.70	54.00	-12.30	AV	Vertical
13285.27	31.94	42.70	18.00	37.10	12.40	44.34	68.20	-23.86	Pk	Horizontal
13285.27	29.80	42.70	18.00	37.10	12.40	42.20	54.00	-11.80	AV	Horizontal

Remark:


1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.
2. Scan with 802.11a,802.11n (HT-20),802.11n (HT-40), 802.11ac (VHT-20),802.11ac (VHT-40), 802.11ac (VHT-80) the worst case is 802.11a.
3. The frequency emission of peak points that did not show above the forms are at least 20dB below the limit, the frequency emission is mainly from the environment noise.



3.2.9 RESTRICTED FREQUENCY BANDS AND BAND EDGE


Band I 5150-5250MHz

802.11n20-L-H



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4836.750	51.89	-7.08	44.81	68.20	-23.39	peak
2	5150.000	50.59	-5.73	44.86	68.20	-23.34	peak


802.11n20-L-V



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4747.500	52.11	-7.29	44.82	68.20	-23.38	peak
2	5150.000	49.97	-5.73	44.24	68.20	-23.96	peak




802.11n20-H-H



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	50.14	-5.23	44.91	68.20	-23.29	peak
2	5367.040	51.50	-5.24	46.26	68.20	-21.94	peak


802.11n20-H-V



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	50.08	-5.23	44.85	68.20	-23.35	peak
2	5415.760	52.11	-5.22	46.89	68.20	-21.31	peak




802.11n40-L-H



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4990.400	51.41	-6.25	45.16	68.20	-23.04	peak
2	5150.000	58.07	-5.73	52.34	68.20	-15.86	peak


802.11n40-L-V



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4969.600	51.09	-6.39	44.70	68.20	-23.50	peak
2	5150.000	55.00	-5.73	49.27	68.20	-18.93	peak




802.11n40-H-H



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	51.06	-5.23	45.83	68.20	-22.37	peak
2	5413.240	51.88	-5.22	46.66	68.20	-21.54	peak


802.11n40-H-V



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	50.08	-5.23	44.85	68.20	-23.35	peak
2	5428.360	51.87	-5.19	46.68	68.20	-21.52	peak




802.11ac80-L-H



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5047.300	51.97	-5.97	46.00	68.20	-22.20	peak
2	5150.000	62.14	-5.73	56.41	68.20	-11.79	peak
3	5150.000	50.03	-5.73	44.30	54.00	-9.70	AVG


802.11ac80-L-V



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4880.800	52.57	-6.91	45.66	68.20	-22.54	peak
2	5150.000	59.49	-5.73	53.76	68.20	-14.44	peak




802.11ac80-H-H



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	50.30	-5.23	45.07	68.20	-23.13	peak
2	5394.590	51.95	-5.24	46.71	68.20	-21.49	peak

802.11ac80-H-V




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	50.24	-5.23	45.01	68.20	-23.19	peak
2	5442.640	52.42	-5.16	47.26	68.20	-20.94	peak

Note: All modes have been tested. Only the worst mode shown in the report.




Band II 5250-5350MHz

802.11n20-L-H



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5035.500	51.63	-6.03	45.60	68.20	-22.60	peak
2	5150.000	50.91	-5.73	45.18	68.20	-23.02	peak


802.11n20-L-V



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4985.350	51.52	-6.29	45.23	68.20	-22.97	peak
2	5150.000	50.02	-5.73	44.29	68.20	-23.91	peak




802.11n20-H-H



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	51.09	-5.23	45.86	68.20	-22.34	peak
2	5384.400	51.87	-5.24	46.63	68.20	-21.57	peak


802.11n20-H-V



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	50.80	-5.23	45.57	68.20	-22.63	peak
2	5379.000	52.14	-5.24	46.90	68.20	-21.30	peak




802.11n40-L-H



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4925.850	51.93	-6.67	45.26	68.20	-22.94	peak
2	5150.000	50.71	-5.73	44.98	68.20	-23.22	peak


802.11n40-L-V



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5018.500	51.42	-6.11	45.31	68.20	-22.89	peak
2	5150.000	50.78	-5.73	45.05	68.20	-23.15	peak




802.11n40-H-H



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	59.71	-5.23	54.48	68.20	-13.72	peak
2	5350.000	47.32	-5.23	42.09	54.00	-11.91	AVG
3	5384.800	53.06	-5.24	47.82	68.20	-20.38	peak


802.11n40-H-V



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	57.79	-5.23	52.56	68.20	-15.64	peak
2	5426.400	52.66	-5.19	47.47	68.20	-20.73	peak




802.11ac80-L-H



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4901.200	51.73	-6.83	44.90	68.20	-23.30	peak
2	5150.000	51.29	-5.73	45.56	68.20	-22.64	peak


802.11ac80-L-V



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4934.350	57.33	-6.62	50.71	68.20	-17.49	peak
2	5150.000	50.57	-5.73	44.84	68.20	-23.36	peak




802.11ac80-H-H



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	61.39	-5.23	56.16	68.20	-12.04	peak
2	5350.000	48.02	-5.23	42.79	54.00	-11.21	AVG
3	5392.140	54.90	-5.25	49.65	68.20	-18.55	peak

802.11ac80-H-V




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	59.19	-5.23	53.96	68.20	-14.24	peak
2	5389.540	53.15	-5.25	47.90	68.20	-20.30	peak

Note: All modes have been tested. Only the worst mode shown in the report.




Band III 5470-5725MHz

802.11n20-L-H



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5395.980	52.90	-5.25	47.65	68.20	-20.55	peak
2	5460.000	51.19	-5.11	46.08	68.20	-22.12	peak
3	5470.000	52.75	-5.09	47.66	68.20	-20.54	peak


802.11n20-L-V



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5414.600	51.74	-5.22	46.52	68.20	-21.68	peak
2	5460.000	51.23	-5.11	46.12	68.20	-22.08	peak
3	5470.000	50.87	-5.09	45.78	68.20	-22.42	peak




802.11n20-H-H



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5725.000	54.74	-4.57	50.17	68.20	-18.03	peak
2	5873.600	51.49	-3.99	47.50	68.20	-20.70	peak


802.11n20-H-V



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5725.000	50.88	-4.57	46.31	68.20	-21.89	peak
2	5898.400	51.73	-3.88	47.85	68.20	-20.35	peak




802.11n40-L-H



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5418.780	52.27	-5.20	47.07	68.20	-21.13	peak
2	5460.000	55.45	-5.11	50.34	68.20	-17.86	peak
3	5470.000	58.71	-5.09	53.62	68.20	-14.58	peak


802.11n40-L-V



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5394.650	52.34	-5.24	47.10	68.20	-21.10	peak
2	5460.000	54.45	-5.11	49.34	68.20	-18.86	peak
3	5470.000	58.68	-5.09	53.59	68.20	-14.61	peak




802.11n40-H-H



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5725.000	48.24	-4.57	43.67	68.20	-24.53	peak
2	5858.800	50.91	-4.07	46.84	68.20	-21.36	peak


802.11n40-H-V



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5725.000	51.60	-4.57	47.03	68.20	-21.17	peak
2	5849.600	51.39	-4.10	47.29	68.20	-20.91	peak




802.11ac80-L-H



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5421.250	57.57	-5.20	52.37	68.20	-15.83	peak
2	5460.000	64.05	-5.11	58.94	68.20	-9.26	peak
3	5460.000	48.30	-5.11	43.19	54.00	-10.81	AVG
4	5470.000	65.18	-5.09	60.09	68.20	-8.11	peak
5	5470.000	48.37	-5.09	43.28	54.00	-10.72	AVG


802.11ac80-L-V



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5421.500	56.37	-5.20	51.17	68.20	-17.03	peak
2	5460.000	62.44	-5.11	57.33	68.20	-10.87	peak
3	5460.000	47.70	-5.11	42.59	54.00	-11.41	AVG
4	5470.000	63.10	-5.09	58.01	68.20	-10.19	peak
5	5470.000	47.48	-5.09	42.39	54.00	-11.61	AVG




802.11ac80-H-H



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5725.000	51.44	-4.57	46.87	68.20	-21.33	peak
2	5864.500	51.51	-4.04	47.47	68.20	-20.73	peak

802.11ac80-H-V




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5725.000	50.43	-4.57	45.86	68.20	-22.34	peak
2	5802.500	52.11	-4.31	47.80	68.20	-20.40	peak

Note: All modes have been tested. Only the worst mode shown in the report.




Band IV(5.725-5.85 GHz)

802.11n20-L-H



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5653.813	54.69	-4.67	50.02	71.02	-21.00	peak
2	5710.625	66.77	-4.62	62.15	108.17	-46.02	peak
3	5725.000	77.86	-4.57	73.29	122.20	-48.91	peak


802.11n20-L-V



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5643.875	52.97	-4.68	48.29	68.20	-19.91	peak
2	5718.688	71.05	-4.60	66.45	110.43	-43.98	peak
3	5725.000	75.35	-4.57	70.78	122.20	-51.42	peak




802.11n20-H-H



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5850.000	71.75	-4.10	67.65	122.20	-54.55	peak
2	5877.850	57.36	-3.98	53.38	103.09	-49.71	peak
3	5927.575	53.49	-3.93	49.56	68.20	-18.64	peak


802.11n20-H-V



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5850.000	68.56	-4.10	64.46	122.20	-57.74	peak
2	5875.413	56.69	-3.99	52.70	104.89	-52.19	peak
3	5926.600	52.68	-3.93	48.75	68.20	-19.45	peak




802.11ac40-L-H



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5653.250	53.54	-4.67	48.87	70.61	-21.74	peak
2	5699.375	65.71	-4.66	61.05	104.74	-43.69	peak
3	5725.000	76.93	-4.57	72.36	122.20	-49.84	peak


802.11ac40-L-V



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5642.563	52.25	-4.68	47.57	68.20	-20.63	peak
2	5711.938	70.48	-4.62	65.86	108.54	-42.68	peak
3	5725.000	74.02	-4.57	69.45	122.20	-52.75	peak




802.11ac40-H-H



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5850.000	64.69	-4.10	60.59	122.20	-61.61	peak
2	5875.900	57.51	-3.99	53.52	104.53	-51.01	peak
3	5927.390	52.83	-3.93	48.90	68.20	-19.30	peak


802.11ac40-H-V



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5850.000	63.31	-4.10	59.21	122.20	-62.99	peak
2	5875.140	55.52	-3.99	51.53	105.10	-53.57	peak
3	5930.050	51.41	-3.93	47.48	68.20	-20.72	peak




802.11ac80-H



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5619.950	51.37	-4.69	46.68	68.20	-21.52	peak
2	5680.150	51.54	-4.67	46.87	90.51	-43.64	peak
3	5725.000	50.19	-4.57	45.62	119.20	-73.58	peak
4	5850.000	50.06	-4.10	45.96	119.20	-73.24	peak
5	5873.000	51.40	-4.00	47.40	105.80	-58.40	peak
6	5928.300	50.86	-3.92	46.94	68.20	-21.26	peak



802.11ac80-V



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5654.600	62.68	-4.68	58.00	71.60	-13.60	peak
2	5700.800	72.44	-4.66	67.78	105.42	-37.64	peak
3	5725.000	74.52	-4.57	69.95	122.20	-52.25	peak
4	5850.000	74.66	-4.10	70.56	122.20	-51.64	peak
5	5880.700	66.07	-3.96	62.11	100.98	-38.87	peak
6	5921.300	59.12	-3.92	55.20	70.94	-15.74	peak

Note: All modes have been tested. Only the worst mode shown in the report.



4. POWER SPECTRAL DENSITY TEST

4.1 LIMIT

1. For mobile and portable client devices in the 5.15-5.25 GHz band, , the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.
2. For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.
3. For the band 5.725-5.850 GHz, the peak power spectral density shall not exceed 30 dBm in any 500KHz band. If transmitting antenna directional gain is greater than 6 dBi, both the maximum conducted output power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

4.2 TEST PROCEDURE

1. The setting follows Method SA-2 of FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
2. Set span to encompass the EBW
3. Set RBW = 1MHz.
4. Set the VBW $\geq$ 3MHz.
5. Number of points in sweep $\geq 2 \times \text{span} / \text{RBW}$. (This ensures that bin-to-bin spacing is $\leq \text{RBW}/2$, so that narrowband signals are not lost between frequency bins.)
6. Sweep time = auto.
7. Detector = power averaging (rms), if available. Otherwise, use sample detector mode
8. Trace average at least 100 traces in power averaging (rms) mode; however, the number of traces to be averaged shall be increased above 100 as needed to ensure that the average accurately represents the true average over the on and off periods of the transmitter.

4.3 DEVIATION FROM STANDARD

No deviation.

4.4 TEST SETUP



4.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.1 Unless otherwise a special operating condition is specified in the follows during the testing.



**4.6 TEST RESULTS**

5150-5250MHz					
Frequency	Direct measurement Power Density (dBm)	Duty cycle factor (dB)	Final Power Density (dBm)	Limit (dBm)	Result
802.11a					
5180	-6.149	0.049	-6.100	11	PASS
5200	-6.129	0.049	-6.080	11	PASS
5240	-6.085	0.049	-6.036	11	PASS
802.11n20					
5180	-6.376	0.065	-6.311	11	PASS
5200	-6.111	0.065	-6.046	11	PASS
5240	-6.227	0.065	-6.162	11	PASS
802.11n40					
5190	-7.018	0.168	-6.850	11	PASS
5230	-7.647	0.168	-7.479	11	PASS
802.11ac20					
5180	5.817	0.064	5.881	11	PASS
5200	-5.531	0.064	-5.467	11	PASS
5240	-4.820	0.064	-4.756	11	PASS
802.11ac40					
5190	-7.560	0.180	-7.380	11	PASS
5230	-7.581	0.180	-7.401	11	PASS
802.11ac80					
5210	-11.216	0.365	-10.851	11	PASS



5250-5350MHz					
Frequency	Direct measurement Power Density (dBm)	Duty cycle factor (dB)	Final Power Density (dBm)	Limit (dBm)	Result
802.11a					
5260	-6.107	0.074	-6.033	11	PASS
5300	-6.431	0.074	-6.357	11	PASS
5320	-6.796	0.074	-6.722	11	PASS
802.11n20					
5260	-6.721	0.079	-6.642	11	PASS
5300	-6.865	0.079	-6.786	11	PASS
5320	-6.947	0.079	-6.868	11	PASS
802.11n40					
5270	-8.295	0.182	-8.113	11	PASS
5310	-8.070	0.182	-7.888	11	PASS
802.11ac20					
5260	-6.456	0.052	-6.404	11	PASS
5300	-6.597	0.052	-6.545	11	PASS
5320	-7.436	0.052	-7.384	11	PASS
802.11ac40					
5270	-8.141	0.167	-7.974	11	PASS
5310	-7.995	0.167	-7.828	11	PASS
802.11ac80					
5290	-11.362	0.379	-10.983	11	PASS



5470-5725MHz					
Frequency	Direct measurement Power Density (dBm)	Duty cycle factor (dB)	Final Power Density (dBm)	Limit (dBm)	Result
802.11a					
5500	-5.928	0.037	-5.891	11	PASS
5580	-6.420	0.037	-6.383	11	PASS
5700	-6.777	0.037	-6.740	11	PASS
802.11n20					
5500	-6.120	0.078	-6.042	11	PASS
5580	-6.715	0.078	-6.637	11	PASS
5700	-7.263	0.078	-7.185	11	PASS
802.11n40					
5510	-9.362	0.155	-9.207	11	PASS
5550	-9.464	0.155	-9.309	11	PASS
5670	-10.024	0.155	-9.869	11	PASS
802.11ac20					
5500	-6.518	0.091	-6.427	11	PASS
5580	-7.090	0.091	-6.999	11	PASS
5700	-6.985	0.091	-6.894	11	PASS
802.11ac40					
5510	-9.353	0.180	-9.173	11	PASS
5550	-9.533	0.180	-9.353	11	PASS
5670	-10.438	0.180	-10.258	11	PASS
802.11ac80					
5530	-11.252	0.391	-10.861	11	PASS
5610	-11.993	0.391	-11.602	11	PASS



5725-5850MHz						
Frequency	Use RBW 510KHz direct measurement Direct measurement Power Density (dBm)	Convert to RBW 500KHz direct measurement Power Density (dBm)	Duty cycle factor (dB)	Final Power Density (dBm)	Limit (dBm)	Result
802.11a						
5745	-4.129	-4.215	0.073	-4.142	30	PASS
5785	-4.123	-4.209	0.073	-4.136	30	PASS
5825	-3.880	-3.966	0.073	-3.893	30	PASS
802.11n20						
5745	-3.709	-3.795	0.092	-3.703	30	PASS
5785	-4.818	-4.904	0.092	-4.812	30	PASS
5825	-4.158	-4.244	0.092	-4.152	30	PASS
802.11n40						
5755	-8.326	-8.412	0.193	-8.219	30	PASS
5795	-8.682	-8.768	0.193	-8.575	30	PASS
802.11ac20						
5745	-3.728	-3.814	0.078	-3.736	30	PASS
5785	-4.395	-4.481	0.078	-4.403	30	PASS
5825	-4.750	-4.836	0.078	-4.758	30	PASS
802.11ac40						
5755	-8.675	-8.761	0.179	-8.582	30	PASS
5795	-8.742	-8.828	0.179	-8.649	30	PASS
802.11ac80						
5775	-10.396	-10.482	0.404	-10.078	30	PASS

Note: 1. RB conversion formula: $10 \cdot \log(500\text{KHz}/\text{RBW})$

2. Test plots see Attachment A.

5. BANDWIDTH MEASUREMENT

5.1 EMISSION BANDWIDTH (EBW) 26 BANDWID PROCEDURES / LIMIT

The following procedure shall be used for measuring 26 bandwidth.

5.1.1 TEST PROCEDURE

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01
2. Set RBW = approximately 1% of the emission bandwidth.
3. Set the VBW $\geq$ RBW.
4. Detector = Peak.
5. Trace mode = max hold.
6. Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

5.1.2 DEVIATION FROM STANDARD

No deviation.

5.1.3 TEST SETUP



5.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

**5.1.5 TEST RESULTS**

Frequency (MHz)	26dB Bandwidth (MHz)	Pass/Fail
802.11a		
5180	19.95	Pass
5200	19.81	Pass
5240	19.96	Pass
802.11n(HT20)		
5180	19.97	Pass
5200	20.01	Pass
5240	20.01	Pass
802.11n(HT40)		
5190	40.15	Pass
5230	40.42	Pass
802.11ac(VHT20)		
5180	20.12	Pass
5200	20.06	Pass
5240	20.01	Pass
802.11ac(VHT40)		
5190	40.03	Pass
5230	39.96	Pass
802.11ac(VHT80)		
5210	81.17	Pass

Frequency (MHz)	26dB Bandwidth (MHz)	Pass/Fail
802.11a		
5260	19.97	Pass
5300	19.85	Pass
5320	20.05	Pass
802.11n(HT20)		
5260	20.05	Pass
5300	20.14	Pass
5320	20.10	Pass
802.11n(HT40)		
5270	40.23	Pass
5310	40.39	Pass
802.11ac(VHT20)		
5260	20.12	Pass
5300	20.21	Pass
5320	20.11	Pass
802.11ac(VHT40)		
5270	40.52	Pass
5310	40.33	Pass
802.11ac(VHT80)		
5290	88.57	Pass



Frequency (MHz)	26dB Bandwidth (MHz)	Pass/Fail
802.11a		
5500	19.90	Pass
5580	19.78	Pass
5700	19.93	Pass
802.11n(HT20)		
5500	20.11	Pass
5580	19.90	Pass
5700	19.96	Pass
802.11n(HT40)		
5510	40.36	Pass
5550	40.23	Pass
5670	40.17	Pass
802.11ac(VHT20)		
5500	20.08	Pass
5580	19.89	Pass
5700	19.99	Pass
802.11ac(VHT40)		
5510	40.15	Pass
5550	40.19	Pass
5670	40.49	Pass
802.11ac(VHT80)		
5530	81.50	Pass
5610	81.42	Pass

Frequency (MHz)	26dB Bandwidth (MHz)	Pass/Fail
802.11a		
5745	20.32	Pass
5785	20.34	Pass
5825	21.72	Pass
802.11n(HT20)		
5745	20.23	Pass
5785	20.66	Pass
5825	20.56	Pass
802.11n(HT40)		
5755	40.88	Pass
5795	42.65	Pass
802.11ac(VHT20)		
5745	20.20	Pass
5785	20.06	Pass
5825	20.24	Pass
802.11ac(VHT40)		
5755	40.02	Pass
5795	40.29	Pass
802.11ac(VHT80)		
5775	99.43	Pass

Test plot see Attachment B.

5.2 OCCUPIED BANDWIDTH (99%) TEST APPLIED PROCEDURES / LIMIT

The following procedure shall be used for measuring (99 %) power bandwidth.

5.2.1 TEST PROCEDURE

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures v02r01.

The following procedure shall be used for measuring (99 %) power bandwidth:

1. Set center frequency to the nominal EUT channel center frequency.
2. Set span = 1.5 times to 5.0 times the OBW.
3. Set RBW = 1 % to 5 % of the OBW
4. Set VBW $\geq 3 \cdot$ RBW
5. Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
6. Use the 99 % power bandwidth function of the instrument (if available).
7. If the instrument does not have a 99 % power bandwidth function, the trace data points are recovered and directly summed in power units. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5 % of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5 % of the total is reached; that frequency is recorded as the upper frequency. The 99% occupied bandwidth is the difference between these two frequencies.

5.2.2 DEVIATION FROM STANDARD

No deviation.

5.2.3 TEST SETUP



5.2.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

**5.2.5 TEST RESULTS**

Frequency (MHz)	99% Bandwidth (MHz)	Pass/Fail
802.11a		
5180	16.45	Pass
5200	16.46	Pass
5240	16.45	Pass
802.11n(HT20)		
5180	17.48	Pass
5200	17.48	Pass
5240	17.49	Pass
802.11n(HT40)		
5190	35.89	Pass
5230	35.87	Pass
802.11ac(VHT20)		
5180	17.49	Pass
5200	17.49	Pass
5240	17.49	Pass
802.11ac(VHT40)		
5190	35.85	Pass
5230	35.88	Pass
802.11ac(VHT80)		
5210	75.72	Pass

Frequency (MHz)	99% Bandwidth (MHz)	Pass/Fail
802.11a		
5260	16.48	Pass
5300	16.48	Pass
5320	16.50	Pass
802.11n(HT20)		
5260	17.50	Pass
5300	17.51	Pass
5320	17.52	Pass
802.11n(HT40)		
5270	35.97	Pass
5310	35.98	Pass
802.11ac(VHT20)		
5260	17.50	Pass
5300	17.51	Pass
5320	17.52	Pass
802.11ac(VHT40)		
5270	35.95	Pass
5310	35.94	Pass
802.11ac(VHT80)		
5290	75.88	Pass



Frequency (MHz)	99% Bandwidth (MHz)	Pass/Fail
802.11a		
5500	16.46	Pass
5580	16.44	Pass
5700	16.46	Pass
802.11n(HT20)		
5500	17.48	Pass
5580	17.49	Pass
5700	17.50	Pass
802.11n(HT40)		
5510	35.91	Pass
5550	35.92	Pass
5670	35.89	Pass
802.11ac(VHT20)		
5500	17.49	Pass
5580	17.48	Pass
5700	17.48	Pass
802.11ac(VHT40)		
5510	35.88	Pass
5550	35.84	Pass
5670	35.88	Pass
802.11ac(VHT80)		
5530	75.71	Pass
5610	75.74	Pass

Frequency (MHz)	99% Bandwidth (MHz)	Pass/Fail
802.11a		
5745	16.50	Pass
5785	16.51	Pass
5825	16.52	Pass
802.11n(HT20)		
5745	17.52	Pass
5785	17.52	Pass
5825	17.53	Pass
802.11n(HT40)		
5755	36.00	Pass
5795	35.98	Pass
802.11ac(VHT20)		
5745	17.52	Pass
5785	17.52	Pass
5825	17.52	Pass
802.11ac(VHT40)		
5755	35.92	Pass
5795	35.95	Pass
802.11ac(VHT80)		
5775	75.95	Pass

Test plot See Attachment B.

5.3 MINIMUM EMISSION BANDWIDTH(6 DB) PROCEDURES / LIMIT

Section 15.407(e) specifies the minimum 6 dB emission bandwidth of at least 500 KHz for the band 5.725-5.85 GHz. The following procedure shall be used for measuring this bandwidth.

5.3.1 TEST PROCEDURE

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures v02r01.
 - a) Set RBW = 100 kHz.
 - b) Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
 - c) Detector = Peak.
 - d) Trace mode = max hold.
 - e) Sweep = auto couple.
 - f) Allow the trace to stabilize.
 - g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

5.3.2 DEVIATION FROM STANDARD

No deviation.

5.3.3 TEST SETUP



5.3.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

**5.3.5 TEST RESULTS**

Frequency (MHz)	6dB Bandwidth (MHz)	Pass/Fail
802.11a		
5745	15.07	Pass
5785	15.06	Pass
5825	15.05	Pass
802.11n(HT20)		
5745	15.01	Pass
5785	15.10	Pass
5825	15.10	Pass
802.11n(HT40)		
5755	35.11	Pass
5795	35.10	Pass
802.11ac(VHT20)		
5745	15.09	Pass
5785	15.08	Pass
5825	15.07	Pass
802.11ac(VHT40)		
5755	35.06	Pass
5795	35.05	Pass
802.11ac(VHT80)		
5775	76.31	Pass

Test plots see Attachment C.

6. MAXIMUM CONDUCTED OUTPUT POWER

6.1 LIMIT

For mobile and portable client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or 11 dBm + 10 log B, where B is the 26 dB emission bandwidth in megahertz, If transmitting antennas of directional gain greater than 6 dBi are used.

For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. If transmitting antennas of directional gain greater than 6 dBi are used.

FCC Part15 (15.407) , Subpart E				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.407(a) (1) (iv)	Peak Output Power	0.25 watt	5150-5250	PASS
		The lesser of 250 mW or 11 dBm + 10 log (26 dB emission bandwidth)	5250-5350 5470-5725	
15.407(a) (3)		1 watt	5725-5825	


6.2 TEST PROCEDURE

The EUT was directly connected to the Power Sensor&PC

6.3 DEVIATION FROM STANDARD

No deviation.

6.4 TEST SETUP



6.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 5 Unless otherwise a special operating condition is specified in the follows during the testing.



6.6 TEST RESULTS

Band I (5.15-5.25GHz)					
Test Channel	Frequency (MHz)	Direct measurement AV Power (dBm)	Duty cycle factor (dB)	Final AV Power (dBm)	LIMIT (dBm)
802.11a					
36	5180	5.71	0.049	5.76	23.98
40	5200	5.75	0.049	5.80	23.98
48	5240	5.61	0.049	5.66	23.98
802.11n(HT20)					
36	5180	6.98	0.065	7.05	23.98
40	5200	6.93	0.065	7.00	23.98
48	5240	6.91	0.065	6.98	23.98
802.11n(HT40)					
38	5190	6.35	0.168	6.52	23.98
46	5230	6.85	0.168	7.02	23.98
802.11ac(VHT20)					
36	5180	6.22	0.064	6.28	23.98
40	5200	6.78	0.064	6.84	23.98
48	5240	5.93	0.064	5.99	23.98
802.11ac(VHT40)					
38	5190	6.78	0.180	6.96	23.98
46	5230	6.81	0.180	6.99	23.98
802.11ac(VHT80)					
42	5210	6.87	0.365	7.23	23.98



Band II(5.25-5.35GHz)					
Test Channel	Frequency (MHz)	Direct measurement AV Power (dBm)	Duty cycle factor (dB)	Final AV Power (dBm)	LIMIT (dBm)
802.11a					
52	5260	5.39	0.074	5.46	23.98
60	5300	5.44	0.074	5.51	23.98
64	5320	5.36	0.074	5.43	23.98
802.11n(HT20)					
52	5260	5.41	0.079	5.49	23.98
60	5300	5.47	0.079	5.55	23.98
64	5320	5.30	0.079	5.38	23.98
802.11n(HT40)					
54	5270	6.65	0.182	6.83	23.98
62	5310	6.78	0.182	6.96	23.98
802.11ac(VHT20)					
52	5260	5.37	0.052	5.42	23.98
60	5300	5.37	0.052	5.42	23.98
64	5320	5.32	0.052	5.37	23.98
802.11ac(VHT40)					
54	5270	6.93	0.167	7.10	23.98
62	5310	6.79	0.167	6.96	23.98
802.11ac(VHT80)					
58	5290	6.63	0.379	7.01	23.98



Band III(5.47-5.725GHz)					
Test Channel	Frequency (MHz)	Direct measurement AV Power (dBm)	Duty cycle factor (dB)	Final AV Power (dBm)	LIMIT (dBm)
802.11a					
100	5500	5.68	0.037	5.72	23.98
116	5580	4.97	0.037	5.01	23.96
140	5700	1.41	0.037	1.45	23.98
802.11n(HT20)					
100	5500	5.49	0.078	5.57	23.98
116	5580	4.78	0.078	4.86	23.98
140	5700	1.28	0.078	1.36	23.98
802.11n(HT40)					
102	5510	5.31	0.155	5.47	23.98
110	5550	4.35	0.155	4.51	23.98
134	5670	1.98	0.155	2.14	23.98
802.11ac(VHT20)					
100	5500	5.40	0.091	5.49	23.98
116	5580	4.84	0.091	4.93	23.98
140	5700	2.04	0.091	2.13	23.98
802.11ac(VHT40)					
102	5510	5.25	0.180	5.43	23.98
110	5550	4.65	0.180	4.83	23.98
134	5670	1.98	0.180	2.16	23.98
802.11ac(VHT80)					
106	5530	6.21	0.391	6.60	23.98
122	5610	5.32	0.391	5.71	23.98



Band IV (5.725-5.85GHz)					
Test Channel	Frequency (MHz)	Direct measurement AV Power (dBm)	Duty cycle factor (dB)	Final AV Power (dBm)	LIMIT (dBm)
802.11a					
149	5745	6.39	0.073	6.46	30.00
157	5785	5.71	0.073	5.78	30.00
165	5825	5.53	0.073	5.60	30.00
802.11n(HT20)					
149	5745	6.26	0.092	6.35	30.00
157	5785	5.34	0.092	5.43	30.00
165	5825	5.44	0.092	5.53	30.00
802.11n(HT40)					
151	5755	4.98	0.193	5.17	30.00
159	5795	3.37	0.193	3.56	30.00
802.11ac(VHT20)					
149	5745	5.99	0.078	6.07	30.00
157	5785	4.12	0.078	4.20	30.00
165	5825	3.83	0.078	3.91	30.00
802.11ac(VHT40)					
151	5755	4.97	0.179	5.15	30.00
159	5795	3.39	0.179	3.57	30.00
802.11ac(VHT80)					
155	5775	5.02	0.404	5.42	30.00



5210MHz



5290MHz



5530MHz



5610MHz



5775MHz



Duty Cycle

Band1				
Mode	Ton(ms)	Tp(ms)	Duty cycle(%)	Duty factor(dB)
a	1.412	1.428	98.88%	0.049
n20	1.320	1.340	98.51%	0.065
n40	0.660	0.686	96.21%	0.168
ac20	1.340	1.360	98.53%	0.064
ac40	0.662	0.690	95.94%	0.180
ac80	0.331	0.360	91.94%	0.365
Band2				
Mode	Ton(ms)	Tp(ms)	Duty cycle(%)	Duty factor(dB)
a	1.404	1.428	98.32%	0.074
n20	1.312	1.336	98.20%	0.079
n40	0.656	0.684	95.91%	0.182
ac20	1.328	1.344	98.81%	0.052
ac40	0.662	0.688	96.22%	0.167
ac80	0.329	0.359	91.64%	0.379
Band3				
Mode	Ton(ms)	Tp(ms)	Duty cycle(%)	Duty factor(dB)
a	1.420	1.432	99.16%	0.037
n20	1.316	1.340	98.21%	0.078
n40	0.660	0.684	96.49%	0.155
ac20	1.324	1.352	97.93%	0.091
ac40	0.660	0.688	95.93%	0.180
ac80	0.329	0.360	91.39%	0.391
Band4				
Mode	Ton(ms)	Tp(ms)	Duty cycle(%)	Duty factor(dB)
a	1.408	1.432	98.32%	0.073
n20	1.308	1.336	97.90%	0.092
n40	0.660	0.690	95.65%	0.193
ac20	1.320	1.344	98.21%	0.078
ac40	0.664	0.692	95.95%	0.179
ac80	0.328	0.360	91.11%	0.404



Band 1-a20



Band 1-n20



Band 1-n40



Band 1-ac20



Band 1-ac40



Band 1-ac80



Band 2-a20



Band 2-n20



Band 2-n40



Band 2-ac20



Band 2-ac40



Band 2-ac80




Band 3-a20



Band 3-n20



Band 3-n40



Band 3-ac20



Band 3-ac40



Band 3-ac80



Band 4-a20



Band 4-n20



Band 4-n40



Band 4-ac20



Band 4-ac40



Band 4-ac80



7. AUTOMATICALLY DISCONTINUE TRANSMISSION

7.1 LIMIT OF AUTOMATICALLY DISCONTINUE TRANSMISSION

The device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. These provisions are not intended to preclude the transmission of control or signaling information or the use of repetitive codes used by certain digital technologies to complete frame or burst intervals. Applicants shall include in their application for equipment authorization to describe how this requirement is met.

7.2 TEST RESULT OF AUTOMATICALLY DISCONTINUE TRANSMISSION

During no any information transmission, the EUT can automatically discontinue transmission and become standby mode for power saving. The EUT can detect the controlling signal of ACK message transmitting from remote device and verify whether it shall resend or discontinue transmission





8. ANTENNA REQUIREMENT

8.1 STANDARD REQUIREMENT

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

8.2 EUT ANTENNA

The EUT antenna is PIFA Antenna. It comply with the standard requirement.



**APPENDIX - PHOTOS OF TEST SETUP**

Note: See test photos in setup photo document for the actual connections between Product and support equipment.

※※※※※END OF THE REPORT※※※※※

