

RF Test Report

Project Number: 5028090**Offer Number: SUW-202302004095****Report Number: 5028090EMC05****Revision Level: 1****Client: UTEC, Inc.****Equipment Under Test: Refrigerated Shipping Container Controller****Product Name: Micro-Link 5 Controller****Model: MICROLINK5B****FCC ID: 2AK6N-MICROLINK5B****IC: 703A-MICROLINK5B****Applicable Standards: FCC Part 15 Subpart C, § 15.247****RSS-247, Issue 3, August 2023****RSS-GEN, Issue 5, February 2021, Amendment 2****ANSI C63.10:2013****Report issued on: 17 November 2023****Test Result: Compliant**


FOR THE SCOPE OF ACCREDITATION UNDER CERTIFICATE NUMBER: 3212.01

This report must not be used by the client to claim product certification, approval, or endorsement by A2LA, NIST, or any agency of the Federal Government.

Prepared by:


Dan Alvarez, RF/EMC Sr. Staff Engineer

Reviewed by:


Martin Taylor, EMC/RF Project Engineer

Remarks: This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx>. And for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/terms-e-document.aspx>.

Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful, and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for a maximum of 30 days only.

Table of Contents

1	SUMMARY OF TEST RESULTS	4
1.1	MODIFICATIONS REQUIRED FOR COMPLIANCE	4
2	GENERAL INFORMATION.....	5
2.1	CLIENT INFORMATION	5
2.2	TEST LABORATORY	5
2.3	GENERAL INFORMATION OF EUT	5
2.4	OPERATING MODES AND CONDITIONS	5
2.5	EUT CONNECTION BLOCK DIAGRAM – CONDUCTED MEASUREMENTS.....	6
2.6	EUT CONNECTION BLOCK DIAGRAM – RADIATED MEASUREMENTS	6
2.7	SYSTEM CONFIGURATIONS	6
2.8	CABLE LIST	6
3	BANDWIDTH	7
3.1	TEST RESULT.....	7
3.2	TEST METHODS	7
3.3	TEST SITE	7
3.4	TEST EQUIPMENT	7
3.5	TEST DATA – DTS BANDWIDTH (6dB)	7
3.6	TEST DATA – 99% OCCUPIED BANDWIDTH.....	10
4	OUTPUT POWER	12
4.1	TEST RESULT.....	12
4.2	TEST METHOD.....	12
4.3	TEST SITE	12
4.4	TEST EQUIPMENT	12
4.5	TEST DATA.....	12
5	POWER SPECTRAL DENSITY	15
5.1	TEST RESULT.....	15
5.2	TEST METHOD.....	15
5.3	TEST SITE	15
5.4	TEST EQUIPMENT	15
5.5	TEST DATA.....	15
6	CONDUCTED SPURIOUS EMISSIONS / BAND EDGE.....	18
6.1	TEST RESULT.....	18
6.2	TEST METHOD.....	18
6.3	TEST SITE	18
6.4	TEST EQUIPMENT	18
6.5	TEST DATA – DTS BAND EDGE.....	19
6.6	TEST DATA – DTS CONDUCTED SPURIOUS EMISSIONS	20
7	EMISSIONS IN RESTRICTED FREQUENCY BANDS	22
7.1	TEST RESULT.....	22
7.2	TEST METHOD.....	22
7.3	TEST SITE	22
7.4	TEST EQUIPMENT	23
7.5	TEST DATA.....	24
8	BAND EDGE EMISSIONS IN RESTRICTED FREQUENCY BANDS.....	31
8.1	TEST RESULT.....	31
8.2	TEST METHOD.....	31

8.3	TEST SITE	31
8.4	TEST EQUIPMENT	31
8.5	TEST DATA.....	32
9	AC POWERLINE CONDUCTED EMISSIONS.....	33
9.1	TEST RESULT.....	33
9.2	TEST METHOD.....	33
9.3	TEST SITE	33
9.4	TEST EQUIPMENT	33
9.5	TEST DATA.....	34
10	MEASUREMENT UNCERTAINTY.....	36
11	REVISION HISTORY	37

1 Summary of Test Results

Test Description	Test Specification		Test Result
Bandwidth	15.247(a)(2)	RSS-247 S5.2 (a) RSS-GEN S6.7	Compliant
Output Power	15.247(b)(3)	RSS-247 S5.4 (d)	Compliant
Power Spectral Density	15.247(e)	RSS-247 S5.2 (b)	Compliant
Conducted Spurious Emissions / Band Edge	15.247(d)	RSS-247 S5.5	Compliant
Emissions in Restricted Frequency Bands	15.247(d) 15.205, 15.209	RSS-247 S5.5 RSS-GEN S8.9, S8.10	Compliant
Band Edge Emissions in Restricted Frequency Bands	15.205, 15.209	RSS-GEN S8.9, S8.10	Compliant
AC Powerline Conducted Emissions	15.207	RSS-GEN S8.8	Compliant
Antenna Requirement	15.203	RSS-GEN S6.8	Compliant ⁽¹⁾

(1) The device uses a PCB trace PIFA antenna which cannot be replaced by the end user.

1.1 Modifications Required for Compliance

None.

2 General Information

2.1 Client Information

Company Name: UTEC, Inc.
Address: 111 E. Wayne St., Suite 800
City, State, Zip, Country: Fort Wayne, Indiana 46802, USA

2.2 Test Laboratory

Name: SGS North America, Inc.
Address: 620 Old Peachtree Road NW, Suite 100
City, State, Zip, Country: Suwanee, GA 30024, USA

Accrediting Body: A2LA
Type of lab: Testing Laboratory
Certificate Number: 3212.01
CAB ID: US0186

2.3 General Information of EUT

Equipment Under Test: Refrigerated Shipping Container Controller
Product Name: Micro-Link 5 Controller
Model: MICROLINK5B
Serial Numbers: 4120W008381 (Conducted Sample)
3821W039479 (Radiated Sample)
FCC ID: 2AK6N-MICROLINK5B
IC: 703A-MICROLINK5B

Frequency Range: 2402 – 2480 MHz
Data Modes: Bluetooth Low Energy (BLE) – GFSK
Antenna: PCB Trace PIFA (4.54dBi gain)

Rated Voltage: 5V_{DC} to Micro Board USB port or
Dual phase 18V_{AC} to IO Board
Test Voltage: 5V_{DC} to Micro Board USB port (for Conducted Measurements)
Dual phase 18V_{AC} to IO Board (for Radiated Measurements)


Sample Received Date: 03 February 2023
Dates of testing: 15 March to 13 April 2023

2.4 Operating Modes and Conditions


The EUT was running test mode firmware with TI tools which allowed the following:

- 1) selecting low, middle and high BLE channels;
- 2) selecting the modulation scheme as used in normal operation, but with 100% duty cycle;
- 3) setting the power level. [The maximum power setting of 7 was used for all tests.]

2.5 EUT Connection Block Diagram – Conducted Measurements



2.6 EUT Connection Block Diagram – Radiated Measurements



2.7 System Configurations

Device Reference	Manufacturer	Description	Model Number	Serial Number
A	UTEC, Inc.	Micro-Link 5 Controller (EUT)	MICROLINK5B	4120W008381 3821W039479
B	Lenovo	Laptop Computer	T420	R8-X9XFV
C	UTEC, Inc.	Transformer Box	(none)	(none)

2.8 Cable List

Cable reference	Port Name	Start	End	Cable Length (m)	Ferrite installed?	Shielded?
1	USB	EUT	Laptop Computer	1.0	N	N
2	AC Power (5-wire harness)	EUT	Transformer Box	0.7	N	N

3 Bandwidth

3.1 Test Result

Test Description	Test Specification		Test Result
DTS Bandwidth (6dB)	15.247(a)(2)	RSS-247 S5.2 (a)	Compliant
Occupied Bandwidth (99%)	2.1049	RSS-GEN S6.7	Reported

3.2 Test Methods

The DTS 6dB bandwidth measurements were performed using the procedure from ANSI C63.10 clause 11.8.1, and the 99% occupied bandwidth measurements were performed using the procedure from ANSI C63.10 clause 6.9.3. These procedures are referenced in KDB 558074 D01 15.247 Meas Guidance v05r02.

The BLE 1Mbps data mode was used for these tests.

Limit

The minimum 6dB bandwidth shall be at least 500 kHz.

3.3 Test Site

SGS EMC Laboratory, Suwanee, GA

Environmental Conditions

Temperature: 19.2 °C

Relative Humidity: 51.2 %

Atmospheric Pressure: 98.2 kPa

3.4 Test Equipment



Test End Date: 15-Mar-2023


Tester: DA

Equipment	Model	Manufacturer	Asset	Cal Date	Cal Due Date
SIGNAL ANALYZER (TS8997)	FSV30	ROHDE & SCHWARZ	B085749	7-Dec-2022	7-Dec-2023
RF CABLE (TS8997)	141	HUBER & SUHNER	B095588	5-Jul-2022	5-Jul-2023
TSTPASS SWITCHBOX	SB1	TSTPASS	20168	CNR	CNR
USB WIDEBAND POWER SENSOR	U2021XA	TSTPASS (KEYSIGHT TECHNOLOGIES)	20168C	24-Aug-2022	24-Aug-2023

3.5 Test Data – DTS Bandwidth (6dB)


Test Mode	Frequency (MHz)	TX Type	ANT No.	6dB Bandwidth	Verdict
				Test Result (MHz)	
1M	2402	SISO	1	0.710	PASS
	2440	SISO	1	0.713	PASS
	2480	SISO	1	0.714	PASS







3.6 Test Data – 99% Occupied Bandwidth

Test Mode	Frequency (MHz)	TX Type	ANT No.	99% Occupied Bandwidth	
				Test Result (MHz)	
1M	2402	SISO	1	1.027	Only for Report Use
	2440	SISO	1	1.029	Only for Report Use
	2480	SISO	1	1.027	Only for Report Use





4 Output Power

4.1 Test Result

Test Description	Test Specification		Test Result
Fundamental Emission Output Power	15.247(b)(3)	RSS-247 S5.4 (d)	Compliant

4.2 Test Method

Fundamental maximum peak conducted output power measurements were performed using the method described in ANSI C63.10:2013 clause 11.9.1.1. This procedure is referenced in KDB 558074 D01 15.247 Meas Guidance v05r02.

The BLE 1Mbps data mode was used for this test.

Limit

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. For using antennas with greater than 6dBi of gain, the limit is reduced in dB by the amount the gain exceeds 6dBi (e.g. for a 7.4dBi antenna, the limit is reduced from 30dBm to 28.6dBm). Also, the e.i.r.p. shall not exceed 4 Watts (36 dBm) based on RSS-247 S5.4 (d).

4.3 Test Site

SGS EMC Laboratory, Suwanee, GA

Environmental Conditions

Temperature: 19.2 °C
Relative Humidity: 51.2 %
Atmospheric Pressure: 98.2 kPa

4.4 Test Equipment



Test End Date: 15-Mar-2023


Tester: DA

Equipment	Model	Manufacturer	Asset	Cal Date	Cal Due Date
SIGNAL ANALYZER (TS8997)	FSV30	ROHDE & SCHWARZ	B085749	7-Dec-2022	7-Dec-2023
RF CABLE (TS8997)	141	HUBER & SUHNER	B095588	5-Jul-2022	5-Jul-2023
TSTPASS SWITCHBOX	SB1	TSTPASS	20168	CNR	CNR
USB WIDEBAND POWER SENSOR	U2021XA	TSTPASS (KEYSIGHT TECHNOLOGIES)	20168C	24-Aug-2022	24-Aug-2023

4.5 Test Data

Test Mode	Frequency (MHz)	Tx Type	Measured Peak Output Power (dBm)	Limits (dBm)	Verdict
			Ant 1		
1M	2402	SISO	2.73	30	PASS
	2440	SISO	3.26	30	PASS
	2480	SISO	3.53	30	PASS





5 Power Spectral Density

5.1 Test Result

Test Description	Test Specification		Test Result
Power Spectral Density	15.247(e)	RSS-247 S5.2 (b)	Compliant

5.2 Test Method

Peak power spectral density measurements were performed using the procedures from ANSI C63.10: 2013 clause 11.10.2. These procedures are referenced in KDB 558074 D01 15.247 Meas Guidance v05r02.

The BLE 1Mbps data mode was used for this test.

Limit

The maximum limit is 8 dBm / 3 kHz.

5.3 Test Site

SGS EMC Laboratory, Suwanee, GA

Environmental Conditions

Temperature: 19.2 °C

Relative Humidity: 51.2 %

Atmospheric Pressure: 98.2 kPa

5.4 Test Equipment



Test End Date: 15-Mar-2023


Tester: DA

Equipment	Model	Manufacturer	Asset	Cal Date	Cal Due Date
SIGNAL ANALYZER (TS8997)	FSV30	ROHDE & SCHWARZ	B085749	7-Dec-2022	7-Dec-2023
RF CABLE (TS8997)	141	HUBER & SUHNER	B095588	5-Jul-2022	5-Jul-2023
TSTPASS SWITCHBOX	SB1	TSTPASS	20168	CNR	CNR
USB WIDEBAND POWER SENSOR	U2021XA	TSTPASS (KEYSIGHT TECHNOLOGIES)	20168C	24-Aug-2022	24-Aug-2023

5.5 Test Data

Test Mode	Frequency (MHz)	Tx Type	Maximum Power Spectral Density (dBm/3KHz)	Limits (dBm/3kHz)	Verdict
			Ant 1		
1M	2402	SISO	-14.53	≤8	PASS
	2440	SISO	-14.03	≤8	PASS
	2480	SISO	-13.88	≤8	PASS





6 Conducted Spurious Emissions / Band Edge

6.1 Test Result

Test Description	Test Specification		Test Result
Conducted Spurious and Band Edge Emissions	15.247(d)	RSS-247 S5.5	Compliant

6.2 Test Method

Conducted band edge and spurious band emissions in non-restricted frequency bands were measured using the method defined in ANSI C63.10 clause 11.11. This procedure is referenced in KDB 558074 D01 15.247 Meas Guidance v05r02.

The device does not utilize BLE 2Mbps data mode, so only BLE 1Mbps mode was tested.

Limit

Because the maximum peak conducted output power was used to determine compliance with the output power limits, the limit in any 100 kHz band outside of the authorized band is 20 dB below the maximum in-band peak level.

6.3 Test Site

SGS EMC Laboratory, Suwanee, GA

Environmental Conditions

Temperature: 19.2 °C

Relative Humidity: 51.2 %

Atmospheric Pressure: 98.2 kPa

6.4 Test Equipment


Test End Date: 15-Mar-2023

Tester: DA


Equipment	Model	Manufacturer	Asset	Cal Date	Cal Due Date
SIGNAL ANALYZER (TS8997)	FSV30	ROHDE & SCHWARZ	B085749	7-Dec-2022	7-Dec-2023
RF CABLE (TS8997)	141	HUBER & SUHNER	B095588	5-Jul-2022	5-Jul-2023
TSTPASS SWITCHBOX	SB1	TSTPASS	20168	CNR	CNR
USB WIDEBAND POWER SENSOR	U2021XA	TSTPASS (KEYSIGHT TECHNOLOGIES)	20168C	24-Aug-2022	24-Aug-2023

6.5 Test Data – DTS Band Edge

BLE - Lower band edge




BLE - Upper band edge




6.6 Test Data – DTS Conducted Spurious Emissions


Conducted Spurs – BLE Channel 0



Conducted Spurs – BLE Channel 19



Conducted Spurs – BLE Channel 39



7 Emissions in Restricted Frequency Bands

7.1 Test Result

Test Description	Test Specification		Test Result
Emissions in Restricted Frequency Bands	15.247(d) 15.205, 15.209	RSS-247 S5.5 RSS-GEN S8.9, S8.10	Compliant

7.2 Test Method

Radiated emissions in restricted frequency bands were measured using methods defined in ANSI C63.10 clause 11.12. These procedures are referenced in KDB 558074 D01 15.247 Meas Guidance v05r02.

Lowest, middle and highest channels were investigated – the device was commanded to continuously transmit on channels 0, 19 and 39.

Test distances for radiated tests:

- 9k to 30 MHz – Near field prescan to determine if there were any emissions
- 30 to 1000 MHz - The EUT to measurement antenna distance was 3 meters
- 1 to 18 GHz - The EUT to measurement antenna distance was 3 meters
- 18 to 26 GHz - The EUT to measurement antenna distance was 3 meters

Limits within restricted bands of operation:

Frequency	Limits ⁽¹⁾		Peak Limits dBuV/m
	Microvolts/m	dBuV/m	
30 - 88 MHz	100	40 ⁽²⁾	--
88 - 216 MHz	150	43.5 ⁽²⁾	--
216 - 960 MHz	200	46 ⁽²⁾	--
960 - 1000 MHz	500	54 ⁽²⁾	--
1 - 40 GHz	500	54 ⁽³⁾	74

(1) These limits are applicable to emissions outside of the intentional transmit frequency band.

(2) Quasi-peak limit

(3) Average limit

7.3 Test Site

3m Absorber Lined Shielded Enclosure (ALSE), Suwanee, GA

10m Absorber Lined Shielded Enclosure (ALSE), Suwanee, GA

Environmental Conditions	30-1000MHz	1-18GHz
Temperature:	21.3 °C	25.7 °C
Relative Humidity:	49.3 %	44.3 %
Atmospheric Pressure:	97.9 kPa	98.3 kPa

7.4 Test Equipment

30-1000MHz

Test End Date: 4-Apr-2023

Tester: ZH

Equipment	Model	Manufacturer	Asset	Cal Date	Cal Due Date
ANTENNA, BILOG	JB6	SUNOL	B079689	26-May-2022	26-May-2024
N to N RF Cable	TR-48-25P	Echelon	23007	31-Mar-2023	31-Mar-2024
RF CABLE NM TO NM, 0.01-12GHZ	90-078-079	TELEDYNE STORM MICROWAVE	20115	15-Mar-2023	15-Mar-2024
RF CABLE NM TO NM, 0.01-18GHZ	90-195-079	TELEDYNE STORM MICROWAVE	20123	9-Feb-2023	9-Feb-2024
RF CABLE RIGHT ANGLE NM TO NM, 0.01-18GHZ	90-076-020	TELEDYNE STORM MICROWAVE	20131	13-Mar-2023	13-Mar-2024
LOW NOISE AMPLIFIER	ZKL-2+	MINI-CIRCUITS	B079817	25-Aug-2022	25-Aug-2023
EMI TEST RECEIVER	ESW44	ROHDE & SCHWARZ	22027	13-Sep-2022	13-Sep-2023

1-18GHz

Test End Date: 5-Apr-2023

Tester: ZH

6-Apr-2023

Equipment	Model	Manufacturer	Asset	Cal Date	Cal Due Date
ANTENNA, DRG HORN (MEDIUM)	3117	ETS LINDGREN	B079691	15-Aug-2022	15-Aug-2024
RF CABLE NM TO NF, 0.01-18GHZ	TR-48-25P	TELEDYNE STORM MICROWAVE	20118	13-Mar-2023	13-Mar-2024
RF CABLE, NM TO NM.	90-195-157	TELEDYNE STORM MICROWAVE	21019	14-Mar-2023	14-Mar-2024
RF CABLE RIGHT ANGLE NM TO NM, 0.01-18GHZ	90-076-020	TELEDYNE STORM MICROWAVE	20132	13-Mar-2023	13-Mar-2024
LOW NOISE AMPLIFIER	TS-PR18	ROHDE & SCHWARZ	B094463	13-Jul-2022	13-Jul-2023
EMI TEST RECEIVER	ESW44	ROHDE & SCHWARZ	22032	24-Nov-2022	24-Nov-2023
FILTER, HIGH PASS, >2800MHZ	HPM50111	MICRO-TRONICS	22017	16-Jun-2022	16-Jun-2023



Software: "RSE 30-1000 MHz T7 220318" TILE 7! profile dated Mar 2022
"RSE 1-18 GHz T7 210212" TILE 7! profile dated Feb 2021

7.5 Test Data

No emissions were detected in the 9kHz to 30MHz frequency range.

7.5.1 30-1000 MHz


There was no significant deviation based on axis or channel in the 30-1000MHz frequency range.




Emissions in above plots do not fall in restricted bands and so do not need to meet FCC 15.209 limits.

7.5.2 1-3 GHz


1-3GHz Vertical Low Channel




1-3 GHz Horizontal Low Channel




1-3 GHz Vertical Mid Channel




1-3 GHz Horizontal Mid Channel



1-3 GHz Vertical High Channel




1-3 GHz Horizontal High Channel




7.5.3 3-18 GHz


3-18 GHz Vertical Low Channel




3-18 GHz Horizontal Low Channel




3-18GHz Vertical Mid Channel




3-18 GHz Horizontal Mid Channel



3-18 GHz Vertical High Channel



3-18GHz Horizontal High Channel



There were no emissions in the 18-26GHz frequency range.

8 Band Edge Emissions in Restricted Frequency Bands

8.1 Test Result

Test Description	Test Specification		Test Result
Band Edge Emissions in Restricted Frequency Bands	15.205, 15.209	RSS-GEN S8.9, 8.10	Compliant

8.2 Test Method

Field strength measurements were performed at the restricted band edges of 2390MHz and 2483.5MHz. Measurements were made using the conducted methods defined in ANSI C63.10: 2013 clause 11.12.2. The measurements were converted to a radiated field strength equivalent using the equations defined in that section. Both peak and average measurements were performed at the antenna port. These procedures are referenced in KDB 558074 D01 15.247 Meas Guidance v05r02.

A reference level offset was applied to the spectrum analyzer so that conducted measurements represent field strength measurements in dBμV/m.

The device does not utilize BLE 2Mbps data mode, so only BLE 1Mbps mode was tested.

8.3 Test Site

SGS EMC Laboratory, Suwanee, GA

Environmental Conditions

Temperature: 24.6 °C

Relative Humidity: 45.4 %

Atmospheric Pressure: 97.9 kPa

8.4 Test Equipment


Test End Date: 7-Apr-2023

Tester: DA


Equipment	Model	Manufacturer	Asset	Cal Date	Cal Due Date
SIGNAL ANALYZER (TS8997)	FSV30	ROHDE & SCHWARZ	B085749	7-Dec-2022	7-Dec-2023
RF CABLE (TS8997)	141	HUBER & SUHNER	B095588	5-Jul-2022	5-Jul-2023
TSTPASS SWITCHBOX	SB1	TSTPASS	20168	CNR	CNR
USB WIDEBAND POWER SENSOR	U2021XA	TSTPASS (KEYSIGHT TECHNOLOGIES)	20168C	24-Aug-2022	24-Aug-2023

8.5 Test Data

BLE – Low Channel – Plot



BLE – High Channel – Plot



9 AC Powerline Conducted Emissions

9.1 Test Result

Test Description	Test Specification		Test Result
AC Powerline Conducted Emissions	15.207	RSS-GEN S8.8	Compliant

9.2 Test Method

With the receiver's resolution bandwidth was set to 9 kHz, exploratory scans were performed over the measuring frequency range (0.15 MHz to 30 MHz) using a max hold mode incorporating a Peak detector and Average detector and using the TILE! software. The final test data was measured using a Quasi-Peak detector and Average detector and compared against the limits indicated in the table below.

Frequency Range	Limits (dBuV)
0.15 to 0.5 MHz	Avg 56 to 46 QP 66 to 56
0.5 to 5 MHz	Avg 46 Pk 56
5 to 30 MHz	Avg 50 Pk 60

9.3 Test Site

SGS EMC Laboratory, Suwanee, GA

Environmental Conditions:

Temperature: 22.7 °C

Relative Humidity: 38.8 %

Atmospheric Pressure 97.8 kPa

9.4 Test Equipment


Test End Date: 13-Apr-2023

Tester: EW


Equipment	Model	Manufacturer	Asset	Cal Date	Cal Due Date
LINE IMPEDANCE STABILIZATION NETWORK	NNB 51	TESEQ	B085882	15-Apr-2022	15-Apr-2023
RF CABLE	UC-N-MM-78	MAURY MICROWAVE	17017	25-Aug-2022	25-Aug-2023
EMI TEST RECEIVER	ESW44	ROHDE & SCHWARZ	22032	24-Nov-2022	24-Nov-2023

Software: Conducted Emissions 230206.til

9.5 Test Data



Frequency MHz	QP Value dBuV	QP Limit dBuV	QP Margin dB	Avg Value dBuV	Avg Limit dBuV	Avg Margin dB
0.361	23.7	58.7	-34.9	5.3	48.7	-43.3
0.700	15.9	56.0	-40.1	5.6	46.0	-40.4
18.244	25.7	60.0	-34.3	22.4	50.0	-27.6
19.098	26.8	60.0	-33.2	25.0	50.0	-25.0
19.708	28.2	60.0	-31.8	21.0	50.0	-29.0
20.323	27.9	60.0	-32.1	22.1	50.0	-27.9
20.808	30.5	60.0	-29.5	26.5	50.0	-23.5
21.113	27.2	60.0	-32.8	24.0	50.0	-26.0
21.663	29.4	60.0	-30.6	26.0	50.0	-24.0
29.235	25.6	60.0	-34.4	22.2	50.0	-27.8



Frequency MHz	QP Value dBuV	QP Limit dBuV	QP Margin dB	Avg Value dBuV	Avg Limit dBuV	Avg Margin dB
0.386	23.2	58.2	-34.9	5.0	48.2	-43.2
0.725	15.5	56.0	-40.5	5.9	46.0	-40.1
18.243	23.1	60.0	-36.9	19.8	50.0	-30.2
19.097	22.7	60.0	-37.3	20.4	50.0	-29.6
19.707	23.7	60.0	-36.3	18.9	50.0	-31.1
20.384	23.3	60.0	-36.7	18.1	50.0	-31.9
20.812	22.5	60.0	-37.5	17.9	50.0	-32.1
21.199	22.5	60.0	-37.5	21.2	50.0	-28.8
21.662	24.2	60.0	-35.8	19.8	50.0	-30.2
29.236	24.8	60.0	-35.2	21.0	50.0	-29.0

10 Measurement Uncertainty

The measurement uncertainty figures are calculated in accordance with TR 100 028-1 [2] and correspond to an expansion factor (coverage factor) $k = 2$ (which provides confidence levels of 95.45 % in the case where the distributions characterizing the actual measurement uncertainties are normal (Gaussian)).

Parameter	Expanded Uncertainty for Normal k factor equal to 2	
	Required	Laboratory Actual
Radio Frequency	$\pm 1 \times 10^{-5}$	$\pm 9.8 \times 10^{-8}$
total RF power, conducted	± 1.5 dB	± 1.2 dB
RF power density, conducted	± 3 dB	± 0.7 dB
spurious emissions, conducted	± 3 dB	± 2.1 dB
all emissions, radiated	± 6 dB	± 4.8 dB
temperature	$\pm 1^{\circ}\text{C}$	$\pm 0.5^{\circ}\text{C}$
humidity	± 5 %	$\pm 3.5\%$
DC and low frequency voltages	± 3 %	$\pm 0.4\%$
Conducted disturbance at mains port using AMN	± 3.4 dB	± 2.5 dB

11 Revision History

Revision Level	Description of changes	Revision Date
0	Initial release	31 May 2023
1	- Updated RSS-247 reference to latest issue on title page - Clarified antenna type in sections 1 & 2.3	17 November 2023