



Tengxiang Technology.Inc

东莞市腾祥电子有限公司

Product Number: AN2450-12F07BX-W

Product Name: Antenna

Specification For Approval

Date: 2023.11.23

Version: 1.0

客户名称

Customer:

赛腾

客户料号

Customer P/N:

腾祥料号

T X P/N:

AN2450-12F07BX-W

规格描述

Description :

2.4G/5G 白色天线 1.13mm 黑色线 L=350mm+IPEX

Tengxiang Checked By: 腾祥审核		Customer Approved By: 客户审核	
DRAWN 制作	路婷	TESTED BY 检测	
CHECKED BY 审核	胡超	CHECKED BY 审核	
Q.C.DEPT. 品管	梁凤珍	Q.C.DEPT. 品管	
APPROVED BY 核准	韦佳	APPROVEDBY 核准	



NO.53 Shatou ShaChong Road, ChangAn Town, Guangdong province, China

中国广东省东莞市长安镇沙头区沙涌路 53 号

TEL:86-769-81873082 FAX:86-769-82663788

<http://www.tenxiang.cn>



Tengxiang Technology.Inc

东莞市腾祥电子有限公司

Product Number: AN2450-12F07BX-W

Product Name: Antenna

Index:

1. Specification (规格)
2. Characteristics and Reliability Test (产品特性和可靠性测试标准)
3. Antenna - S Parameter Test Data (样品测试数据)
4. Antenna - Radiation Pattern Test Data (辐射模式测试数据)
5. Mechanical and Packing Drawing (图纸包装规范)


Revision History (变更履历)

Revision	Date	Change Notification	Description
1.0	2023.11.23	初版	

Product Number: AN2450-12F07BX-W

Product Name: Antenna

1. Specification

Sample Photo	
	
A. Electrical Characteristics	
Frequency 频率	2400-2500MHz/5150-5850MHz
S.W.R. 驻波比	≤ 2.0
Antenna Gain 增益	3.46dBi / 3.50dBi
Polarization 极化方式	Linear
Impedance 阻抗	50 Ohm
B. Material & Mechanical Characteristics	
Material of Plastic 塑胶材质	TPE/ABS
Cable Type 线材规格	OD1.13mm , Black
Connector Type 连接器规格	I-PEX
C. Environmental	
Storage Temperature 存储温度	- 30 °C ~ +65 °C
Operation Temperature 工作温度	- 30 °C ~ +65 °C
Antenna Color Storage life 天线颜色存储寿命	< 2 year

Product Number: AN2450-12F07BX-W

Product Name: Antenna


2. Characteristics and Reliability Test

Test Items 测试项目		Test Condition and Procedure 测试方法	Requirements 要求	Result 结果
1	V.S.W.R. 电压驻波比	Set DUT on Network Analyzer; make individual calibration to test 设置网络分析仪参数进行测试	Directive DUT specification 符合待测物规范	PASS
2	Antenna Gain 天线增益	Set DUT on Antenna Chamber; make individual calibration to test 设置天线暗室参数进行测试	Directive DUT specification 符合待测物规范	PASS
3	Pull Test 拉力	Holding with individual specification; force applied to axis of terminal 单独定义产品端子拉力	1. Directive DUT specification 2. Frequency Tol. $\leq 5\%$ 符合待测物规范; 频率偏移 $\leq 5\%$	PASS
4	Dimension 尺寸	Inspection of dimension, color, material, package, surface process. 检查尺寸, 颜色, 材料, 包装, 表面处理	Directive DUT specification 符合待测物规范	PASS
5	Salt Spray 盐雾	GB / T 2423.17-2008 Temp: 35°C; RH: $\geq 95\%$; NaCl solution: $\geq 5\%$; Time: 24H 温度 35°C; 湿度 $\geq 95\%$; 盐水浓度 $\geq 5\%$; 测试 24H	1. No Visual Damage 2. Frequency Tol. $\leq 5\%$ 无明显外观不良; 频率偏移 $\leq 5\%$	PASS
6	Temperature and Humidity Chamber 恒温恒湿	GB / T 2423.3-2006 Temp: 65°C / 12 H; -30°C / 12H RH: $\geq 90\%$; Time: 24H 温度 65°C 测试 12H 转 -30°C 测试 12H; 湿度 $\geq 90\%$; 时间 24H	After 2 Hours Recovery 1. No Visual Damage 2. Frequency Tol. $\leq 5\%$ 恢复 2H 后, 无明显外观不良; 频率偏移 $\leq 5\%$	PASS
7	Aging test 老化	GB / T 2423.2 - 2008 Temp: 65°C; Time: 24 hours 温度 65°C, 测试 24H	After 2 Hours Recovery 1. No Visual Damage 2. Frequency Tol. $\leq 5\%$ 无明显外观不良; 频率偏移 $\leq 5\%$	PASS
8	RoHS	With Reference to IEC 62321:2008 with flow chart 参考 IEC 62321 测试流程	Directive RoHS 2011/65/EU 符合 RoHS 2015/863/EU 标准	PASS

Product Number: AN2450-12F07BX-W

Product Name: Antenna

3. Antenna - S Parameter Test Data



4. Antenna - Radiation Pattern Test Data





Frequency ID	1	2	3	4	5	6	7	8	9	10	11	12
Frequency (MHz)	2400.0	2410.0	2420.0	2430.0	2440.0	2450.0	2460.0	2470.0	2480.0	2490.0	2500.0	5150.0
Gain (dBi)	3.00	3.35	3.46	3.44	3.42	3.28	3.20	3.06	3.21	3.22	3.18	3.10
Efficiency (%)	52.96	54.16	55.34	57.07	59.87	58.58	57.74	57.19	53.18	52.74	52.96	50.41

Frequency ID	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26
Frequency (MHz)	5150.0	5200.0	5250.0	5300.0	5350.0	5400.0	5450.0	5500.0	5550.0	5600.0	5650.0	5700.0	5750.0	5800.0	5850.0
Gain (dBi)	3.10	3.15	3.25	3.17	3.12	3.15	3.17	3.22	3.33	3.50	3.07	3.29	3.49	3.35	3.47
Efficiency (%)	50.41	50.89	51.24	50.22	51.15	54.94	52.61	50.39	53.47	55.64	53.84	50.08	51.35	50.40	50.10





Product Number: AN2450-12F07BX-W

Product Name: Antenna





2400MHz







2450MHz



2500MHz







5150MHz







Product Number: AN2450-12F07BX-W

Product Name: Antenna

5550MHz



5850MHz




5. Mechanical Drawing See attached files

RoHS

Compatible

SIGN	DATE	DESCRIPTION	APPROVER



Note:

1. Dimension: Take * is the important dimension
2. Tolerance: Unmarked tolerance refer to the standard tolerance please

5	CR-113-ZP-A	IPEX	Cu	Au Plated	1
4	CB-113BS	Cable	OD1.13	Black	1
3	AN9201-09B	Body 3	ABS	Black	1
2	AN9201-06B	Body 2	ABS	Black	1
1	AN9201-04B	Body 1	TPE	Black	1
No.	Part Number	Name	Material	Finish	Q'ty



Tengxiang Technology Inc.

TITLE: 2.4/5.8GHz Antenna

PART NO.: AN2450-12F07BX-W

Customer P/N:


APP BY	CHK BY	RF BY	DES BY		Tolerance
YCX	HC	WJ	DWF	UNITS: mm	X.X ±0.5
2023.11.23	2023.11.23	2023.11.23	2023.11.23	SCALE: 1/1	X.XX ±0.2
				REVISION: B	X° ±1

PACKING CRITERION

Date:2023.11.23


Part Number : AN2450-12F07BX-W	Revision : A
Name: Antenna	Customer : ALL

1 . Enter PE bag。




20pcs/ PE bag

2.PACKING 。




1000pcs/Carton

3. SEALING 。



SIDE



FRONT

