



TESTING LABORATORY
CERTIFICATE#4323.01



FCC PART 15.247 TEST REPORT

For

Waylens Inc.

2711 Centerville Road - Suite 400, Wilmington, Delaware, United States 19808

FCC ID: 2AKAF-TW02C2

Report Type: Original Report	Product Type: Secure360 4G
Test Engineer: Alisa Gao	<i>Alisa. Gao</i>
Report Number: RSHA180709001-00B	
Report Date: 2018-07-24	
Reviewed By: Oscar Ye RF Leader	<i>Oscar.Ye</i>
Prepared By: Bay Area Compliance Laboratories Corp. (Kunshan) No.248 Chenghu Road,Kunshan,Jiangsu province,China Tel: +86-0512-86175000 Fax: +86-0512-88934268 www.baclcorp.com.cn	

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

TABLE OF CONTENTS

GENERAL INFORMATION.....4

 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....4

 OBJECTIVE.....4

 RELATED SUBMITTAL(S)/GRANT(S).....4

 TEST METHODOLOGY.....4

 MEASUREMENT UNCERTAINTY.....5

 TEST FACILITY.....5

SYSTEM TEST CONFIGURATION.....6

 DESCRIPTION OF TEST CONFIGURATION.....6

 EUT EXERCISE SOFTWARE.....6

 SPECIAL ACCESSORIES.....6

 EQUIPMENT MODIFICATIONS.....6

 SUPPORT EQUIPMENT LIST AND DETAILS.....7

 EXTERNAL I/O CABLE.....7

 BLOCK DIAGRAM OF TEST SETUP.....7

SUMMARY OF TEST RESULTS.....9

TEST EQUIPMENT LIST.....10

FCC §1.1307 & §2.1091 –MAXIMUM PERMISSIBLE EXPOSURE (MPE).....11

FCC §15.203 – ANTENNA REQUIREMENT.....13

 APPLICABLE STANDARD.....13

 ANTENNA CONNECTOR CONSTRUCTION.....13

FCC §15.205, §15.209 & §15.247(d) – RADIATED EMISSIONS.....14

 APPLICABLE STANDARD.....14

 EUT SETUP.....14

 EMI TEST RECEIVER SETUP.....15

 TEST PROCEDURE.....15

 CORRECTED AMPLITUDE & MARGIN CALCULATION.....15

 TEST RESULTS SUMMARY.....15

 TEST DATA.....16

FCC §15.247(a) (1)-CHANNEL SEPARATION TEST.....27

 APPLICABLE STANDARD.....27

 TEST PROCEDURE.....27

 TEST DATA.....27

FCC §15.247(a) (1) – 20 dB EMISSION BANDWIDTH.....33

 APPLICABLE STANDARD.....33

 TEST PROCEDURE.....33

 TEST DATA.....33

FCC §15.247(a) (1) (iii)-QUANTITY OF HOPPING CHANNEL TEST.....39

 APPLICABLE STANDARD.....39

 TEST PROCEDURE.....39

 TEST DATA.....39

FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME).....42

 APPLICABLE STANDARD.....42

 TEST PROCEDURE.....42

 TEST DATA.....42

FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT.....58

 APPLICABLE STANDARD.....58

TEST PROCEDURE	58
TEST DATA	58
FCC §15.247(d) - BAND EDGES TESTING	64
APPLICABLE STANDARD	64
TEST PROCEDURE	64
TEST DATA	64

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Applicant:	Waylens Inc.
Tested Model:	TW02
Product Type:	Secure360 4G
Dimension:	60 mm (L) * 60 mm (W) * 50 mm (H)
Power Supply:	DC 12V

**All measurement and test data in this report was gathered from production sample serial number: 20180709001. (Assigned by the BACL. The EUT supplied by the applicant was received on 2018-07-09)*

Objective

This test report is prepared on behalf of *Waylens Inc.* in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commissions rules.

The tests were performed in order to determine Compliance with FCC Part 15, Subpart C, section 15.203, 15.205, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

FCC Part 15.247 DTS, Part 15.249 DXX and Part 22H/24E/27 PCB submissions with FCC ID: 2AKAF-TW02C2.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Kunshan). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Item		Uncertainty
AC Power Lines Conducted Emissions		3.19dB
RF conducted test with spectrum		0.9dB
RF Output Power with Power meter		0.5dB
Radiated emission	30MHz~1GHz	6.11dB
	1GHz~6GHz	4.45dB
	6GHz~18GHz	5.23dB
	18GHz~40GHz	5.65dB
Occupied Bandwidth		0.5kHz
Temperature		1.0°C
Humidity		6%

Test Facility

The test site used by Bay Area Compliance Laboratories Corp. (Kunshan) to collect test data is located on the No.248 Chenghu Road, Kunshan, Jiangsu province, China.

Bay Area Compliance Laboratories Corp. (Kunshan) Lab is accredited to ISO/IEC 17025 by A2LA (Lab code: 4323.01) and the FCC designation No. CN1185 under the FCC KDB 974614 D01. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2014.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

Channel list for Bluetooth V3.0:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	40	2442
1	2403
...
...	...	78	2480
39	2441	/	/

EUT was tested with Channel 0, 39 and 78.

EUT Exercise Software

RF Test software: putty

GFSK Power level: 5

π /4-DQPSK Power level: 5

8DPSK Power level: 5

Special Accessories

No special accessory.

Equipment Modifications

No modification was made to the EUT tested.

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
DELL	Notebook	GX620	D65874152
BEST	DC Power Supply	PS-1502D+	/

External I/O Cable


Cable Description	Length (m)	From Port	To
DC Cable	1.0	EUT	DC Source
USB Cable	0.2	EUT	Notebook

Block Diagram of Test Setup

For Radiated Emissions(Below 1GHz):



For Radiated Emissions(Above 1GHz):



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§1.1310 & §2.1091	MAXIMUM PERMISSIBLE EXPOSURE (MPE)	Compliant
§15.203	Antenna Requirement	Compliant
§15.207(a)	AC Line Conducted Emissions	Not Applicable (See Note)
§15.205, §15.209 & §15.247(d)	Radiated Emissions & Restricted Bands Emissions	Compliant
§15.247(a)(1)	20 dB Emission Bandwidth	Compliant
§15.247(a)(1)	Channel Separation Test	Compliant
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliant
§15.247(a)(1)(iii)	Quantity of hopping channel Test	Compliant
§15.247(b)(1)	Peak Output Power Measurement	Compliant
§15.247(d)	Band edges	Compliant

Note: The EUT is a vehicle device.

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Radiated Emission Test (Chamber 1#)					
Rohde & Schwarz	EMI Test Receiver	ESCI	100195	2017-11-12	2018-11-11
Sunol Sciences	Broadband Antenna	JB3	A090413-1	2016-12-26	2019-12-25
Sonoma Instrument	Pre-amplifier	310N	171205	2017-08-15	2018-08-14
Rohde & Schwarz	Auto test Software	EMC32	100361	/	/
MICRO-COAX	Coaxial Cable	Cable-8	008	2017-08-15	2018-08-14
MICRO-COAX	Coaxial Cable	Cable-9	009	2017-08-15	2018-08-14
MICRO-COAX	Coaxial Cable	Cable-10	010	2017-08-15	2018-08-14
BEST	DC Power Supply	PS-1502D+	/	2017-10-10	2018-10-09
Radiated Emission Test (Chamber 2#)					
Rohde & Schwarz	EMI Test Receiver	ESU40	100207	2017-08-27	2018-08-26
ETS-LINDGREN	Horn Antenna	3115	6229	2016-01-11	2019-01-10
ETS-LINDGREN	Horn Antenna	3116	00084159	2016-10-18	2019-10-17
Mini-Circuits	Amplifier	ZVA-183W-S+	220701818	2018-05-20	2019-05-19
EM Electronics Corporation	Amplifier	EM18G40G	060726	2018-03-22	2019-03-21
MICRO-TRONICS	Band notch Filter	BRM50702	/	2017-08-05	2018-08-04
Narda	Attenuator/10dB	10dB	/	2017-08-15	2018-08-14
Rohde & Schwarz	Auto test Software	EMC32	100361	/	/
MICRO-COAX	Coaxial Cable	Cable-6	006	2017-08-15	2018-08-14
MICRO-COAX	Coaxial Cable	Cable-11	011	2017-08-15	2018-08-14
MICRO-COAX	Coaxial Cable	Cable-12	012	2017-08-15	2018-08-14
MICRO-COAX	Coaxial Cable	Cable-13	013	2017-08-15	2018-08-14
BEST	DC Power Supply	PS-1502D+	/	2017-10-10	2018-10-09
RF Conducted Test					
Rohde & Schwarz	FSV40 Signal Analyzer	FSV40	101116	2017-07-22	2018-07-21
Narda	Attenuator/2dB	2dB	/	2017-08-15	2018-08-14
Waylens Inc.	RF Cable	/	/	Each Time	/

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §1.1307 & §2.1091 –MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart §2.1091 and subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission’s guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm²)	Averaging Time (minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz; * = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

Calculated Formulary:

Predication of MPE limit at a given distance

S = PG/4πR² = power density (in appropriate units, e.g. mW/cm²);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

For simultaneously transmit system, the calculated power density should comply with:

$$\sum_i \frac{S_i}{S_{Limit,i}} \leq 1$$

Calculated Data:

Mode	Frequency Range (MHz)	Antenna Gain		Tune-up Conducted Power		Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)	MPE ratio
		(dBi)	(numeric)	(dBm)	(mW)				
802.11b	2412-2462	1.50	1.41	15.50	35.48	20	0.0100	1.0000	0.0100
802.11g		1.50	1.41	18.50	70.79	20	0.0199	1.0000	0.0199
802.11n-HT20		1.50	1.41	18.50	70.79	20	0.0199	1.0000	0.0199
802.11n-HT40	2422-2452	1.50	1.41	17.50	56.23	20	0.0158	1.0000	0.0158
BLE	2402-2480	1.50	1.41	-2.00	0.63	20	0.0002	1.0000	0.0002
BT 3.0	2402-2480	1.50	1.41	0.00	1.00	20	0.0003	1.0000	0.0003
WCDMA Band V	826.4-846.6	1.00	1.26	24.00	251.19	20	0.0630	0.5509	0.1144
WCDMA Band II	1852.4-1907.6	1.50	1.41	24.00	251.19	20	0.0705	1.0000	0.0705
FDD Band 2	1850.7-1909.3	1.50	1.41	23.00	199.53	20	0.0560	1.0000	0.0560
FDD Band 4	1710.7-1754.3	1.40	1.38	23.00	199.53	20	0.0548	1.0000	0.0548
FDD Band 5	824.7-848.3	1.00	1.26	23.00	199.53	20	0.0500	0.5498	0.0909
FDD Band 12	699.7-715.3	0.80	1.20	23.00	199.53	20	0.0476	0.4665	0.1020
FDD Band 17	706.5-713.5	0.80	1.20	23.00	199.53	20	0.0476	0.4710	0.1011

Note:

1. The tune-up conducted power was declared by the manufacturer.
2. Wi-Fi, BT and WCDMA/LTE can transmit simultaneously, and the worst condition is 802.11g of Wi-Fi, BT3.0 & WDCMA Band V as below:

$$\sum_i \frac{S_i}{S_{Limit,i}} = 0.0199/1.0 + 0.0003/1.0 + 0.0630/0.5509 = 0.0199 + 0.0003 + 0.1144 = 0.1346 < 1.0$$

Result: The device meet FCC MPE at 20 cm distance.

FCC §15.203 – ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Antenna Connector Construction

The EUT has a PCB antenna for Bluetooth and the antenna gain is 1.5dBi, which was permanently attached, fulfill the requirement of this section. Please refer to the EUT photos.

Result: Compliance.


FCC §15.205, §15.209 & §15.247(d) – RADIATED EMISSIONS

Applicable Standard


FCC §15.205; §15.209; §15.247(d)

EUT Setup

Below 1 GHz:



Above 1GHz:



The radiated emission tests were performed in the 3 meters, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209 and FCC 15.247 limits.

EMI Test Receiver Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver setup was set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30 MHz – 1000 MHz	120 kHz	300 kHz	120 kHz	QP
Above 1GHz	1MHz	3 MHz	/	PK
	1MHz	3 MHz	/	Ave.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All final data was recorded in Quasi-peak detection mode for frequency range of 30 MHz -1 GHz and peak and Average detection modes for frequencies above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude (dB}\mu\text{V/m)} = \text{Meter Reading (dB}\mu\text{V)} + \text{Antenna Factor (dB/m)} + \text{Cable Loss (dB)} - \text{Amplifier Gain (dB)}$$

The “**Margin**” column of the following data tables indicates the degree of Compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin (dB)} = \text{Limit (dB}\mu\text{V/m)} - \text{Corrected Amplitude (dB}\mu\text{V/m)}$$

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Subpart C, section 15.205, 15.209 and 15.247.

Test Data

Environmental Conditions

Temperature:	23.4 °C
Relative Humidity:	49 %
ATM Pressure:	101.1 kPa


The testing was performed by Alisa Gao from 2018-07-13 to 2018-07-19.

EUT operation mode: Transmitting

Spurious Emission Test:

30MHz-1GHz:

Pre-Scan with GFSK, $\pi/4$ -DQPSK, 8DPSK modes of operation in the X,Y and Z axes of orientation, the worst case high channel of GFSK mode in X-axis of orientation was recorded



Frequency (MHz)	Corrected Amplitude	Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	Quasi-peak (dBµV/m)	Height (cm)	Polar (H/V)				
66.450150	33.52	101.0	V	89.0	-18.0	40.00	6.48
72.588400	32.25	199.0	V	300.0	-17.8	40.00	7.75
165.930850	34.71	101.0	V	288.0	-13.5	43.50	8.79
191.992100	32.18	101.0	V	214.0	-13.3	43.50	11.32
480.230900	24.32	199.0	H	293.0	-6.6	46.00	21.68
959.980050	37.74	101.0	V	32.0	1.4	46.00	8.26

1GHz-18GHz:


Pre-Scan with GFSK, π/4-DQPSK, 8DPSK modes of operation in the X,Y and Z axes of orientation, the worst case GFSK Mode in X-axis of orientation was recorded

Note:

1. This test was performed with the 2.4 - 2.5GHz notch filter.
2. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)
 Corrected Amplitude (dBμV /m) = Corrected Factor (dB/m) + Reading (dBμV)
 Margin (dB) = Limit (dBμV/m) – Corrected Amplitude (dBμV /m)

Low Channel: 2402MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV /m)	Average (dBμV /m)	Height (cm)	Polar (H/V)				
1513.400000	---	28.73	100.0	V	54.0	-1.2	54.00	25.27
1513.400000	38.83	---	100.0	V	54.0	-1.2	74.00	35.17
3009.400000	---	35.43	100.0	V	3.0	6.0	54.00	18.57
3009.400000	46.26	---	100.0	V	3.0	6.0	74.00	27.74
4804.000000	---	38.11	250.0	V	359.0	10.7	54.00	15.89
4804.000000	47.10	---	250.0	V	359.0	10.7	74.00	26.90
7206.000000	---	47.21	100.0	V	63.0	15.2	54.00	6.79
7206.000000	55.29	---	100.0	V	63.0	15.2	74.00	18.71
10720.600000	---	44.95	200.0	H	19.0	18.3	54.00	9.05
10720.600000	55.86	---	200.0	H	19.0	18.3	74.00	18.14
17751.800000	---	45.72	100.0	H	250.0	18.8	54.00	8.28
17751.800000	56.23	---	100.0	H	250.0	18.8	74.00	17.77

Middle Channel: 2441MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV /m)	Average (dBμV /m)	Height (cm)	Polar (H/V)				
1591.600000	---	32.97	150.0	V	89.0	-0.6	54.00	21.03
1591.600000	41.82	---	150.0	V	89.0	-0.6	74.00	32.18
3070.600000	---	36.51	100.0	V	125.0	6.2	54.00	17.49
3070.600000	45.62	---	100.0	V	125.0	6.2	74.00	28.38
4882.000000	---	38.90	250.0	V	330.0	11.2	54.00	15.10
4882.000000	48.45	---	250.0	V	330.0	11.2	74.00	25.55
7323.000000	---	42.92	150.0	V	322.0	15.4	54.00	11.08
7323.000000	52.43	---	150.0	V	322.0	15.4	74.00	21.57
11315.600000	---	45.56	200.0	H	17.0	18.6	54.00	8.44
11315.600000	55.72	---	200.0	H	17.0	18.6	74.00	18.28
17952.400000	---	45.39	100.0	H	257.0	19.1	54.00	8.61
17952.400000	56.32	---	100.0	H	257.0	19.1	74.00	17.68

High Channel: 2480MHz

Full Spectrum




Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV /m)	Average (dBμV /m)	Height (cm)	Polar (H/V)				
1591.600000	---	30.63	100.0	V	189.0	-0.6	54.00	23.37
1591.600000	40.08	---	100.0	V	189.0	-0.6	74.00	33.92
2972.000000	---	35.23	100.0	H	341.0	5.9	54.00	18.77
2972.000000	46.21	---	100.0	H	341.0	5.9	74.00	27.79
4960.000000	---	39.20	200.0	V	170.0	11.6	54.00	14.80
4960.000000	48.92	---	200.0	V	170.0	11.6	74.00	25.08
7440.000000	---	42.16	100.0	V	91.0	15.6	54.00	11.84
7440.000000	52.32	---	100.0	V	91.0	15.6	74.00	21.68
10693.400000	---	44.62	200.0	H	184.0	18.2	54.00	9.38
10693.400000	54.81	---	200.0	H	184.0	18.2	74.00	19.19
17629.400000	---	45.44	100.0	V	153.0	18.7	54.00	8.56
17629.400000	55.89	---	100.0	V	153.0	18.7	74.00	18.11

18GHz-25GHz:


Pre-Scan with GFSK, $\pi/4$ -DQPSK, 8DPSK modes of operation in the X,Y and Z axes of orientation, the worst case high channel of GFSK mode in X-axis of orientation was recorded

Horizontal



Date: 19.JUL.2018 18:56:51

Vertical



Date: 19.JUL.2018 18:57:47

Fundamental Test & Restricted Bands Emissions:

Pre-Scan with GFSK, π/4-DQPSK, 8DPSK modes of operation in the X, Y and Z axes of orientation, the worst case GFSK Mode in X-axis of orientation was recorded


Note:

- 1. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)
- Corrected Amplitude (dBμV /m) = Corrected Factor (dB/m) + Reading (dBμV)
- Margin (dB) = Limit (dBμV/m) – Corrected Amplitude (dBμV /m)

Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV /m)	Average (dBμV /m)	Height (cm)	Polar (H/V)				
Low Channel: 2402MHz								
2402.000000	95.74	---	150.0	V	242.0	2.9	/	/
2402.000000	---	95.40	150.0	V	242.0	2.9	/	/
2402.000000	94.07	---	250.0	H	244.0	2.9	/	/
2402.000000	---	93.69	250.0	H	244.0	2.9	/	/
2390.000000	41.29	---	150.0	V	119.0	2.8	74.00	32.71
2390.000000	---	32.79	150.0	V	119.0	2.8	54.00	21.21
Middle Channel: 2441MHz								
2441.000000	95.68	---	200.0	V	28.0	3.0	/	/
2441.000000	---	95.36	200.0	V	28.0	3.0	/	/
2441.000000	94.02	---	250.0	H	301.0	3.0	/	/
2441.000000	---	93.63	250.0	H	301.0	3.0	/	/
High Channel: 2480MHz								
2480.000000	95.94	---	150.0	V	100.0	3.0	/	/
2480.000000	---	95.57	150.0	V	100.0	3.0	/	/
2480.000000	94.29	---	250.0	H	127.0	3.0	/	/
2480.000000	---	93.88	250.0	H	127.0	3.0	/	/
2483.500000	43.21	---	200.0	V	130.0	3.0	74.00	30.79
2483.500000	---	36.74	200.0	V	130.0	3.0	54.00	17.26


Conducted Spurious Emissions at Antenna Port

BDR (GFSK): Low Channel




Date:13.JUL.2018 15:11:22

BDR (GFSK): Middle Channel




Date:13.JUL.2018 15:13:29

BDR (GFSK): High Channel




Date: 13 JUL 2018 15:14:53

EDR ($\pi/4$ -DQPSK): Low Channel




Date: 13 JUL 2018 15:10:23

EDR ($\pi/4$ -DQPSK): Middle Channel




Date: 13 JUL 2018 15:06:21

EDR ($\pi/4$ -DQPSK): High Channel




Date: 13 JUL 2018 15:05:07

EDR (8DPSK): Low Channel




Date: 13 JUL 2018 14:55:29

EDR (8DPSK): Middle Channel



Date: 13 JUL 2018 14:59:14

EDR (8DPSK): High Channel



Date: 13 JUL 2018 15:02:15

FCC §15.247(a) (1)-CHANNEL SEPARATION TEST

Applicable Standard

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW.

Test Procedure

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

- a. Span: Wide enough to capture the peaks of two adjacent channels.
- b. RBW: Start with the RBW set to approximately 30% of the channel spacing; adjust as necessary to best identify the center of each individual channel.
- c. Video (or average) bandwidth (VBW) \geq RBW.
- d. Sweep: Auto.
- e. Detector function: Peak.
- f. Trace: Max hold.
- g. Allow the trace to stabilize.

Use the marker-delta function to determine the separation between the peaks of the adjacent channels.

Test Data

Environmental Conditions

Temperature:	23.4 °C
Relative Humidity:	49 %
ATM Pressure:	101.1 kPa

The testing was performed by Alisa Gao on 2018-07-14.


EUT operation mode: Transmitting

Test Result: Compliance.

Mode	Channel	Frequency (MHz)	Channel Separation (MHz)	Limit (MHz)	Result
BDR (GFSK)	Low	2402	0.999	≥ 0.955	Pass
	Adjacent	2403			
	Middle	2441	0.999	≥ 0.960	Pass
	Adjacent	2442			
	High	2480	1.003	≥ 0.955	Pass
	Adjacent	2479			
EDR (π/4-DQPSK)	Low	2402	1.003	≥ 0.915	Pass
	Adjacent	2403			
	Middle	2441	1.003	≥ 0.912	Pass
	Adjacent	2442			
	High	2480	0.999	≥ 0.915	Pass
	Adjacent	2479			
EDR (8DPSK)	Low	2402	1.003	≥ 0.900	Pass
	Adjacent	2403			
	Middle	2441	1.003	≥ 0.903	Pass
	Adjacent	2442			
	High	2480	0.999	≥ 0.903	Pass
	Adjacent	2479			


Note: For BDR mode, Limit = 20 dB bandwidth; For EDR mode, Limit = 20 dB bandwidth*2/3

BDR (GFSK): Low Channel




Date: 14 JUL 2018 13:53:05

BDR (GFSK): Middle Channel




Date: 14 JUL 2018 13:51:20

BDR (GFSK): High Channel




Date: 14 JUL 2018 13:54:58


EDR ($\pi/4$ -DQPSK): Low Channel




EDR ($\pi/4$ -DQPSK): Middle Channel




EDR ($\pi/4$ -DQPSK): High Channel




EDR (8DPSK): Low Channel



EDR (8DPSK): Middle Channel



EDR (8DPSK): High Channel



FCC §15.247(a) (1) – 20 dB EMISSION BANDWIDTH

Applicable Standard

Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

Test Data

Environmental Conditions

Temperature:	23.2 °C
Relative Humidity:	50 %
ATM Pressure:	101.3 kPa


The testing was performed by Alisa Gao on 2018-07-13.

EUT operation mode: Transmitting

Test Result: Compliance.


Mode	Channel	Frequency (MHz)	20 dB Emission Bandwidth (MHz)
BDR (GFSK)	Low	2402	0.955
	Middle	2441	0.960
	High	2480	0.955
EDR ($\pi/4$-DQPSK)	Low	2402	1.372
	Middle	2441	1.368
	High	2480	1.372
EDR (8DPSK)	Low	2402	1.350
	Middle	2441	1.355
	High	2480	1.355

BDR (GFSK): Low Channel




Date: 13 JUL 2018 14:23:30

BDR (GFSK): Middle Channel




Date: 13 JUL 2018 14:21:45

BDR (GFSK): High Channel




Date: 13 JUL 2018 14:25:47


EDR ($\pi/4$ -DQPSK): Low Channel



EDR($\pi/4$ -DQPSK): Middle Channel




EDR ($\pi/4$ -DQPSK): High Channel




Date:13 JUL 2018 14:16:46

EDR (8DPSK): Low Channel




Date:13 JUL 2018 14:08:47

EDR (8DPSK): Middle Channel



EDR (8DPSK): High Channel



FCC §15.247(a) (1) (iii)-QUANTITY OF HOPPING CHANNEL TEST

Applicable Standard

Frequency hopping systems in the 2400 - 2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

- a. Span: The frequency band of operation. Depending on the number of channels the device supports, it may be necessary to divide the frequency range of operation across multiple spans, to allow the individual channels to be clearly seen.
- b. RBW: To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.
- c. VBW \geq RBW.
- d. Sweep: Auto.
- e. Detector function: Peak.
- f. Trace: Max hold.
- g. Allow the trace to stabilize.

It might prove necessary to break the span up into subranges to show clearly all of the hopping frequencies.

Test Data

Environmental Conditions

Temperature:	23.2 °C
Relative Humidity:	50 %
ATM Pressure:	101.3 kPa


The testing was performed by Alisa Gao on 2018-07-14.

EUT operation mode: Hopping

Test Result: Compliance.


Mode	Frequency Range (MHz)	Number of Hopping Channel (CH)	Limit (CH)
BDR (GFSK)	2400 - 2483.5	79	≥ 15
EDR (π/4-DQPSK)	2400 - 2483.5	79	≥ 15
EDR (8DPSK)	2400 - 2483.5	79	≥ 15

BDR (GFSK): Number of Hopping Channels




Date: 14 JUL 2018 15:48:44

EDR ($\pi/4$ -DQPSK): Number of Hopping Channels



Date:14 JUL 2018 15:51:14

EDR (8DPSK): Number of Hopping Channels



Date:14 JUL 2018 15:53:16

FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME)**Applicable Standard**

Frequency hopping systems in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

1 Span: Zero span, centered on a hopping channel.

2 RBW shall be \leq channel spacing and where possible RBW should be set $\geq 1 / T$, where T is the expected dwell time per channel.

3 Sweep: As necessary to capture the entire dwell time per hopping channel; where possible use a video trigger and trigger delay so that the transmitted signal starts a little to the right of the start of the plot. The trigger level might need slight adjustment to prevent triggering when the system hops on an adjacent channel; a second plot might be needed with a longer sweep time to show two successive hops on a channel.

4 Detector function: Peak.

5 Trace: Max hold.

Test Data**Environmental Conditions**


Temperature:	23.4 °C
Relative Humidity:	51 %
ATM Pressure:	101.2 kPa

The testing was performed by Alisa Gao on 2018-07-14.


EUT operation mode: Hopping

Mode		Channel	Pulse Width (ms)	Dwell Time (s)	Limit (s)	Result	
BDR (GFSK)	DH1	Low	0.410	0.131	0.4	Pass	
		Middle	0.410	0.131	0.4	Pass	
		High	0.410	0.131	0.4	Pass	
	Note: DH1:Dwell time = Pulse time*(1600/2/79)*31.6S						
	DH3	Low	1.675	0.268	0.4	Pass	
		Middle	1.680	0.269	0.4	Pass	
		High	1.680	0.269	0.4	Pass	
	Note: DH3:Dwell time = Pulse time*(1600/4/79)*31.6S						
	DH5	Low	2.933	0.313	0.4	Pass	
		Middle	2.933	0.313	0.4	Pass	
		High	2.939	0.313	0.4	Pass	
	Note: DH5:Dwell time = Pulse time*(1600/6/79)*31.6S						
	EDR (π/4-DQPSK)	2DH1	Low	0.422	0.135	0.4	Pass
			Middle	0.420	0.134	0.4	Pass
			High	0.420	0.134	0.4	Pass
Note: 2DH1:Dwell time = Pulse time*(1600/2/79)*31.6S							
2DH3		Low	1.683	0.269	0.4	Pass	
		Middle	1.683	0.269	0.4	Pass	
		High	1.683	0.269	0.4	Pass	
Note: 2DH3:Dwell time = Pulse time*(1600/4/79)*31.6S							
2DH5		Low	2.933	0.313	0.4	Pass	
		Middle	2.939	0.313	0.4	Pass	
		High	2.933	0.313	0.4	Pass	
Note: 2DH5:Dwell time = Pulse time*(1600/6/79)*31.6S							
EDR (8DPSK)		3DH1	Low	0.423	0.135	0.4	Pass
			Middle	0.422	0.135	0.4	Pass
			High	0.422	0.135	0.4	Pass
	Note:3 DH1:Dwell time = Pulse time*(1600/2/79)*31.6S						
	3DH3	Low	1.683	0.269	0.4	Pass	
		Middle	1.683	0.269	0.4	Pass	
		High	1.683	0.269	0.4	Pass	
	Note: 3DH3:Dwell time = Pulse time*(1600/4/79)*31.6S						
	3DH5	Low	2.939	0.313	0.4	Pass	
		Middle	2.939	0.313	0.4	Pass	
		High	2.939	0.313	0.4	Pass	
	Note: 3DH5:Dwell time = Pulse time*(1600/6/79)*31.6S						


BDR (GFSK): Pulse time, Low Channel, DH1



BDR (GFSK): Pulse time, Middle Channel, DH1




BDR (GFSK): Pulse time, High Channel, DH1




Date:14 JUL 2018 14:20:23

BDR (GFSK): Pulse time, Low Channel, DH3




Date:14 JUL 2018 14:27:10

BDR (GFSK): Pulse time, Middle Channel, DH3




Date:14 JUL 2018 14:26:17

BDR (GFSK): Pulse time, High Channel, DH3




Date:14 JUL 2018 14:24:58


BDR (GFSK): Pulse time, Low Channel, DH5



BDR (GFSK): Pulse time, Middle Channel, DH5




BDR (GFSK): Pulse time, High Channel, DH5




Date:14.JUL.2018 14:46:35

EDR ($\pi/4$ -DQPSK): Pulse time, Low Channel, 2DH1




Date:14.JUL.2018 14:55:12


EDR ($\pi/4$ -DQPSK):Pulse time, Middle Channel, 2DH1



EDR ($\pi/4$ -DQPSK):Pulse time, High Channel, 2DH1




EDR ($\pi/4$ -DQPSK):Pulse time, Low Channel, 2DH3




Date:14.JUL.2018 14:58:49

EDR ($\pi/4$ -DQPSK):Pulse time, Middle Channel, 2DH3




Date:14.JUL.2018 15:02:14

EDR ($\pi/4$ -DQPSK):Pulse time, High Channel, 2DH3




Date:14 JUL 2018 15:03:14

EDR ($\pi/4$ -DQPSK):Pulse time, Low Channel, 2DH5




Date:14 JUL 2018 15:08:46

EDR ($\pi/4$ -DQPSK): Pulse time, Middle Channel, 2DH5




Date: 14 JUL 2018 15:07:59

EDR ($\pi/4$ -DQPSK): Pulse time, High Channel, 2DH5




Date: 14 JUL 2018 15:07:08

EDR (8DPSK): Pulse time, Low Channel, 3DH1




Date: 14 JUL 2018 15:21:44

EDR (8DPSK): Pulse time, Middle Channel, 3DH1




Date: 14 JUL 2018 15:22:35

EDR (8DPSK): Pulse time, High Channel, 3DH1




Date:14 JUL 2018 15:23:21

EDR (8DPSK): Pulse time, Low Channel, 3DH3




Date:14 JUL 2018 15:29:04

EDR (8DPSK): Pulse time, Middle Channel, 3DH3




Date: 14 JUL 2018 15:27:51

EDR (8DPSK): Pulse time, High Channel, 3DH3




Date: 14 JUL 2018 15:26:45

EDR (8DPSK): Pulse time, Low Channel, 3DH5




Date:14.JUL.2018 15:31:16

EDR (8DPSK): Pulse time, Middle Channel, 3DH5



Date:14.JUL.2018 15:32:13

EDR (8DPSK): Pulse time, High Channel, 3DH5



Date: 14 JUL 2018 15:33:16

FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT

Applicable Standard

According to §15.247(b) (1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. And for all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts.

Test Procedure

- a. Use the following spectrum analyzer settings:
 - 1) Span: Approximately five times the 20 dB bandwidth, centered on a hopping channel.
 - 2) RBW > 20 dB bandwidth of the emission being measured.
 - 3) VBW \geq RBW.
 - 4) Sweep: Auto.
 - 5) Detector function: Peak.
 - 6) Trace: Max hold.
- b. Allow trace to stabilize.
- c. Use the marker-to-peak function to set the marker to the peak of the emission.
- d. The indicated level is the peak output power, after any corrections for external attenuators and cables.
- e. A plot of the test results and setup description shall be included in the test report.

Test Data

Environmental Conditions

Temperature:	23.2 °C
Relative Humidity:	50 %
ATM Pressure:	101.2 kPa


The testing was performed by Alisa Gao on 2018-07-13.

EUT operation mode: Transmitting


Test Result: Compliance.

Mode	Frequency (MHz)	Output Power		Limit (mW)
		(dBm)	(mW)	
BDR (GFSK)	2402	0.04	1.01	1000
	2441	-0.06	0.99	1000
	2480	0.32	1.08	1000
EDR ($\pi/4$ -DQPSK)	2402	-3.08	0.49	125
	2441	-3.16	0.48	125
	2480	-2.70	0.54	125
EDR (8DPSK)	2402	-2.45	0.57	125
	2441	-2.53	0.56	125
	2480	-2.11	0.62	125


BDR (GFSK): 2402MHz




BDR (GFSK): 2441MHz



BDR (GFSK): 2480MHz




EDR($\pi/4$ -DQPSK): 2402MHz




Date:13.JUL.2018 13:56:51

EDR($\pi/4$ -DQPSK): 2441MHz




Date:13.JUL.2018 13:56:01


EDR($\pi/4$ -DQPSK): 2480MHz



EDR(8DPSK): 2402MHz




EDR(8DPSK): 2441MHz



Date: 13 JUL 2018 13:58:42

EDR(8DPSK): 2480MHz



Date: 13 JUL 2018 13:59:29

FCC §15.247(d) - BAND EDGES TESTING

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates Compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Data

Environmental Conditions

Temperature:	23.2 °C
Relative Humidity:	50 %
ATM Pressure:	101.3 kPa


The testing was performed by Alisa Gao on 2018-07-13 & 2018-07-14.

EUT operation mode: Transmitting & Hopping


Test Result: Compliance.

Band Edge


BDR (GFSK): Left Side



BDR (GFSK): Right Side




EDR ($\pi/4$ -DQPSK): Left Side




Date: 13 JUL 2018 14:36:49

EDR ($\pi/4$ -DQPSK): Right Side




Date: 13 JUL 2018 14:40:30

EDR (8DPSK): Left Side




Date:13 JUL 2018 14:45:18

EDR (8DPSK): Right Side




Date:13 JUL 2018 14:42:15


BDR (GFSK): Left Side - Hopping



BDR (GFSK): Right Side - Hopping




EDR ($\pi/4$ -DQPSK): Left Side- Hopping




Date: 14 JUL 2018 13:23:52

EDR ($\pi/4$ -DQPSK): Right Side- Hopping




Date: 14 JUL 2018 13:19:04

EDR (8DPSK): Left Side- Hopping



Date: 14 JUL 2018 13:26:42

EDR (8DPSK): Right Side- Hopping



Date: 14 JUL 2018 13:29:07

***** END OF REPORT *****