

## RF Exposure evaluation

### **2AKAX-KOVE-179S**

According to 447498 D01 General RF Exposure Guidance v06 The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq$  50 mm are determined by:  $[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where } f(\text{GHz}) \text{ is the RF channel transmit frequency in GHz}$

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

For Bluetooth not BLE

pt=5.96dBm=3.945mW at 2480MHz

So  $(3.945\text{mW}/5\text{mm}) \cdot \sqrt{2.480\text{GHz}} = 1.24 < 3$

Then SAR evaluation is not required

For Bluetooth LE

pt=2.69dBm=1.858mW at 2480MHz

So  $(1.858\text{mW}/5\text{mm}) \cdot \sqrt{2.480\text{GHz}} = 0.59 < 3$

Then SAR evaluation is not required