

## Analysis Report

The Equipment Under Test (EUT) is a Smarter Coffee Model: SMC01-US, that equips with WiFi connectivity feature. The Smarter Coffee can be controlled by the corresponding smartphone apps to grind coffee bean and boil coffee. The EUT is powered 120VAC only.

For Maximum Permissible Exposure (MPE) evaluation of the Smarter Coffee, the maximum power density at 20 cm from this mobile transmitter shall be less than the Uncontrolled MPE limit in OET Bulletin 65.

For the Smarter Coffee, Model of SMC01-US, the maximum conducted power (including production tolerance) is 21.5 dBm (141.25 mW). The antenna gain is 2.24dBi (num gain = 1.675). And the maximum source-based time-averaging duty factor is 100%. From these data, the exposed power density at a distance (R) of 20cm from the center of radiation of the antenna can be calculated according to OET Bulletin 65 as follow:

$$\begin{aligned}\text{The radiated power} &= \text{conducted power} * \text{antenna gain} \\ &= (141.25 * 1.675) \text{ mW} \\ &= 236.59 \text{ mW}\end{aligned}$$

$$\begin{aligned}\text{The radiated (EIRP) source-based time-averaging output power} &= (236.59 * 1) \text{ mW} \\ &= 236.59 \text{ mW}\end{aligned}$$

$$\begin{aligned}\text{The power density at 20 cm from the antenna} &= \text{EIRP} / 4\pi R^2 \\ &= 0.047 \text{ mW cm}^{-2}\end{aligned}$$

In the frequency range of 1,500 - 100,000MHz, the MPE limit is 1.0 mWcm-2 for uncontrolled exposure. As the measured power density at 20cm from the transmitter is lower than the MPE limit, the compliance to the MPE limit can be ensured by indicating the minimum 20cm separation between the transmitter's radiating structures and body of the user or nearby persons. The following RF exposure statement is proposed to be included in the user manual:

### **“FCC RF Radiation Exposure Statement**

**Caution: To maintain compliance with the FCC’s RF exposure guidelines, place the unit at least 20cm from nearby persons.”**