7. RADIO FREQUENCY EXPOSURE

7.1. Limit

According to §1.1310 and §2.1091 RF exposure is calculated.

Table: Limits for General Population/Uncontrolled Exposure

Frequency Range	Power Density (S)		
(MHz)	(mW/cm2)		
0.3-1.34	*(100)		
1.34–30	*(180/f ²)		
30–300	0.2		
300-1500	f/1500		
1500-100,000	1.0		

F = frequency in MHz

Maximum Permissible Exposure

The MPE was calculated at 20cm to show compliance with the power density limit.

 $S = PG/4\pi R^2$

S = Power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna.

Note:

- 1. Manufacturer declared that the maximum antenna gain is 2.0dBi(Max.).
- 2. Manufacturer declared that the nearest distance between human and the EUT is 20cm.
- 3. Only record worst case data.

^{* =} Plane-wave equivalent power density

Test Mode	Channel	Frequency (MHz)	Power (dBm, Peak)	Power Tune Up (dBm)
802.11b	Low	2412	18.75	18.0±1.0
	Middle	2437	19.70	19.0±1.0
	High	2462	19.46	19.0±1.0
802.11g	Low	2412	19.05	19.0±1.0
	Middle	2437	20.24	20.0±1.0
	High	2462	17.86	17.0±1.0
802.11n HT20	Low	2412	16.54	16.0±1.0
	Middle	2437	17.06	17.0±1.0
	High	2462	16.55	16.0±1.0

7.2 Test Results

Test Mode	Channel	Max. Tune Up Power (dBm, Peak)	Max. Tune Up Power (mW)	MPE (mW/cm²)	Limit (mW/cm²)
802.11b	Low	19.0	79.43	0.0250	1.0
	Middle	20.0	100.00	0.0314	1.0
	High	20.0	100.00	0.0314	1.0
802.11g	Low	20.0	100.00	0.0314	1.0
	Middle	21.0	125.89	0.0396	1.0
	High	18.0	63.10	0.0198	1.0
802.11n HT20	Low	17.0	50.12	0.0126	1.0
	Middle	18.0	63.10	0.0198	1.0
	High	17.0	50.12	0.0158	1.0

Antenna Gain (typical): 2.0dBi, 1.58(numeric)

Prediction distance: >=20cm

The power density level worst case at 20 cm is below the uncontrolled exposure limit.