4 FCC §15.247(i) & 1.1310 &2.1091 - MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Report No.: RTWA161014001-00B

4.1 Applicable Standard

According to subpart 15.247(i)and subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure									
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm²)	Averaging Time (minutes)					
0.3-1.34	614	1.63	*(100)	30					
1.34–30	824/f	2.19/f	*(180/f²)	30					
30–300	27.5	0.073	0.2	30					
300–1500	/	/	f/1500	30					
1500-100,000	/	/	1.0	30					

f = frequency in MHz; * = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

Calculated Formulary:

Predication of MPE limit at a given distance

 $S = PG/4\pi R^2 = power density (in appropriate units, e.g. mW/cm^2);$

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

For simultaneously transmit system, the calculated power density should comply with:

$$\sum_{i} \frac{S_{i}}{S_{Limit,i}} \le 1$$

FCC Part 15.247 Page 11 of 43

4.2 Calculated Data:

3G Modwle FCC ID: RI7HE910GL.

Worse case:

MPE evaluation for single transmission:

Mode	Frequency Range (MHz)	Antenna Gain		Tune up Power		Evaluation	D D '	NAME AND A STATE OF
		(dBi)	(numeric)	(dBm)	(mW)	Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)
BT	2402-2480	1.927	1.558	6.5	4.467	20	0.00138	1.0
BLE	2402-2480	3.45	2.213	0	1.000	20	0.00044	1.0
3G	824-849	1.74	1.493	24.00	251.189	20	0.07460	0.56
3G	1850-1910	2.37	1.726	24.00	251.189	20	0.08624	1.0
3G	1710-1755	0.64	1.159	24.00	251.189	20	0.05791	1.0

Report No.: RTWA161014001-00B

MPE evaluation for simultaneous transmission:

BT ,BLE and 3G can transmit at the same time, MPE evaluation is as below formula:

PD1/Limit1+PD2/Limit2+.....<1, PD (Power Density)

Worse case MPE evaluation= MPE of BT/1 + MPE of 3G/0.56 = 0.00138/1+0.00044/1+ 0.07460/0.56=0.13503<1.0

Result: RF exposure evaluation of single and simultaneous transmission meet FCC limt at 20 cm distance.

FCC Part 15.247 Page 12 of 43