

FCC ID: 2AKEQ-T8267T

Statement of compliance to Maximum Permissible Exposure (MPE)

Applicant : NINGBO DONGXING ELECTRIC CO.,LTD.

Fenglin Industrial Development Zone, Qiaotou Town,

Cixi, Ningbo, Zhejiang, China

Manufacturer site : NINGBO DONGXING ELECTRIC CO.,LTD.

Fenglin Industrial Development Zone, Qiaotou Town,

Cixi, Ningbo, Zhejiang, China

Product Name : BLE module

Type/Model: T8267T

TEST RESULT : PASS

According to \$2.1091, \$2.1093 and \$1.1307(b), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Date of issue: December 18, 2016

Nem li

Prepared by: Approved by:

Nemo Li (Project engineer) Daniel Zhao (Reviewer)



FCC ID: 2AKEQ-T8267T

Power density (S) is calculated according to the formula:

 $S = PG / (4\pi R ?)$

Where $S = power density in mW/cm^2$

P = transmit power in mW

G = numeric gain of transmit antenna (numeric gain=Log-1(dB antenna gain/10))

R = distance (cm)

As we can see from the test report 161101315SHA-001:

Frequency band	Power	Antenna Gain	R	S	Limits
(MHz)	dBm	dBi	(cm)	(mW/cm2)	(mW/cm2)
2400 -2483.5	6.022	0.0	20	0.0008	1

Note: 1 mW/cm2 from 1.310 Table 1



FCC ID: 2AKEQ-T8267T

Appendix I

Definition below must be outlined in the User Manual:

To satisfy FCC RF exposure requirements, a separation distance of 20 cm or more should be maintained between the antenna of this device and persons during device operation. To ensure compliance, operations at closer than this distance is not recommended.