



FCC TEST REPORT

Test report On Behalf of The Art of Utility AB

For

Bluetooth Earbuds

Model No.: Defunc Earbud BT Basic Hybird, Defunc Earbud BT **Basic Music, Defunc Earbud BT Basci Sport**

FCC ID: 2AKFED043

Prepared for: The Art of Utility AB

Danderydsgatn 28, 114 26, STOCKHOLM, Sweden

Prepared By: Shenzhen HUAK Testing Technology Co., Ltd.

1F, B2 Building, Junfeng Zhongcheng Zhizao Innovation Park, Fuhai Street,

Bao'an District, Shenzhen City, China

Oct. 17, 2018 ~ Oct. 23, 2018 Date of Test:

Oct. 23, 2018 Date of Report:

HK1810171344-E **Report Number:**



TEST RESULT CERTIFICATION

Applicant's name:	The Art of Utility AB
Address:	Danderydsgatn 28, 114 26, STOCKHOLM, Sweden
Manufacture's Name:	TOPALONG LEAN SUPPLY(H.K.)LTD
Address:	Block 27, San Jiang Industrial zone, HengLi Twon, DongGuan City, GuangDong Province, PRC.
Product description	
Trade Mark:	defunc
Product name:	Bluetooth Earbuds
Model and/or type reference :	Defunc Earbud BT Basic Hybird, Defunc Earbud BT Basic Music Defunc Earbud BT Basci Sport
Standards:	FCC Rules and Regulations Part 15 Subpart C Section 15.249 ANSI C63.10: 2013

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen HUAK Testing Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen HUAK Testing Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Testing Engineer : Good Final (Gary Qian)

Technical Manager : Edan Hu

(Eden Hu)

Authorized Signatory: Jason 2Nou

(Jason Zhou)






Table of Contents	Page
1 . TEST SUMMARY	4
2 . GENERAL INFORMATION	5
2.1 GENERAL DESCRIPTION OF EUT	5
2.2 Operation of EUT during testing	6
2.3 DESCRIPTION OF TEST SETUP	7
2.4 MEASUREMENT INSTRUMENTS LIST	8
3. CONDUCTED EMISSIONS TEST	9
3.1 Conducted Power Line Emission Limit	9
3.2 Test Setup	9
3.3 Test Procedure	9
3.4 Test Result	9
4 RADIATED EMISSION TEST	12
4.1 Radiation Limit	12
4.2 Test Setup	12
4.3 Test Procedure	13
4.4 Test Result	13
5 BAND EDGE	19
5.1 Limits	19
5.2 Test Procedure	19
5.3 Test Result	20
6 OCCUPIED BANDWIDTH MEASUREMENT	22
6.1 Test Setup	22
6.2 Test Procedure	22
6.3 Measurement Equipment Used	22
6.4 Test Result	22
7 ANTENNA REQUIREMENT	28
8 PHOTOGRAPH OF TEST	29
Radiated Emission	29
Conducted Emission	30

1.1 TEST PROCEDURES AND RESULTS

DESCRIPTION OF TEST	RESULT
CONDUCTED EMISSIONS TEST	COMPLIANT
RADIATED EMISSION TEST	COMPLIANT
BAND EDGE	COMPLIANT
OCCUPIED BANDWIDTH MEASUREMENT	COMPLIANT
ANTENNA REQUIREMENT	COMPLIANT

Report No.: HK1810171344-E

1.2 TEST FACILITY

1. TEST SUMMARY

Test Firm : Shenzhen HUAK Testing Technology Co., Ltd.

Address 1F, B2 Building, Junfeng Zhongcheng Zhizao Innovation Park, Fuhai

Street, Bao'an District, Shenzhen City, China

1.3 MEASUREMENT UNCERTAINTY

Measurement Uncertainty

Conducted Emission Expanded Uncertainty = 2.23dB, k=2
Radiated emission expanded uncertainty(9kHz-30MHz) = 3.08dB, k=2
Radiated emission expanded uncertainty(30MHz-1000MHz) = 4.42dB, k=2
Radiated emission expanded uncertainty(Above 1GHz) = 4.06dB, k=2



2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Equipment	Bluetooth Earbuds
Model Name	Defunc Earbud BT Basic Hybird
Serial No	Defunc Earbud BT Basic Music, Defunc Earbud BT Basci Sport
Model Difference	All model's the function, software and electric circuit are the same, only with a product color and model named different. Test sample model: Defunc Earbud BT Basic Hybird.
FCC ID	2AKFED043
Antenna Type	PCB Antenna
Antenna Gain	0 dBi
BT Operation frequency	2402-2480MHz
Number of Channels	79CH
Modulation Type	GFSK, π/4DQPSK, 8DPSK
Power Source	DC3.7V From Battery or DC5V From Micro USB
Power Rating	DC3.7V From Battery or DC5V From Micro USB





2.1.1 Carrier Frequency of Channels

Channel List									
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)				
00	2402	27	2429	54	2456				
01	2403	28	2430	55	2457				
02	2404	29	2431	56	2458				
03	2405	30	2432	57	2459				
04	2406	31	2433	58	2460				
05	2407	32	2434	59	2461				
06	2408	33	2435	60	2462				
07	2409	34	2436	61	2463				
08	2410	35	2437	62	2464				
09	2411	36	2438	63	2465				
10	2412	37	2439	64	2466				
11	2413	38	2440	65	2467				
12	2414	39	2441	66	2468				
13	2415	40	2442	67	2469				
14	2416	41	2443	68	2470				
15	2417	42	2444	69	2471				
16	2418	43	2445	70	2472				
17	2419	44	2446	71	2473				
18	2420	45	2447	72	2474				
19	2421	46	2448	73	2475				
20	2422	47	2449	74	2476				
21	2423	48	2450	75	2477				
22	2424	49	2451	76	2478				
23	2425	50	2452	77	2479				
24	2426	51	2453	78	2480				
25	2427	52	2454						
26	2428	53	2455						

2.2 Operation of EUT during testing

Operating Mode The mode is used: **Transmitting mode**

Low Channel: 2402MHz Middle Channel: 2441MHz High Channel: 2480MHz





2.3 DESCRIPTION OF TEST SETUP

Operation of EUT during conducted testing and Radiation testing:



Operation of EUT Above1GHz Radiation testing:

EUT

Adapter information

Model: HW-050500DFQ

Input: 100-240V~, 50/60Hz, 0.5A

Output: 5VDC



2.4 MEASUREMENT INSTRUMENTS LIST

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal.
1.	L.I.S.N. Artificial Mains Network	R&S	ENV216	HKE-002	Dec. 28, 2017	1 Year
2.	Receiver	R&S	ESCI 7	HKE-010	Dec. 28, 2017	1 Year
3.	RF automatic control unit	Tonscend	JS0806-2	HKE-060	Dec. 28, 2017	1 Year
4.	Spectrum analyzer	R&S	FSP40	HKE-025	Dec. 28, 2017	1 Year
5.	Spectrum analyzer	Agilent	N9020A	HKE-048	Dec. 28, 2017	1 Year
6.	Preamplifier	Schwarzbeck	BBV 9743	HKE-006	Dec. 28, 2017	1 Year
7.	EMI Test Receiver	Rohde & Schwarz	ESCI 7	HKE-010	Dec. 28, 2017	1 Year
8.	Bilog Broadband Antenna	Schwarzbeck	VULB9163	HKE-012	Dec. 28, 2017	1 Year
9.	Loop Antenna	Schwarzbeck	FMZB 1519 B	HKE-014	Dec. 28, 2017	1 Year
10.	Horn Antenna	Schewarzbeck	9120D	HKE-013	Dec. 28, 2017	1 Year
11.	Pre-amplifier	EMCI	EMC051845 SE	HKE-015	Dec. 28, 2017	1 Year
12.	Pre-amplifier	Agilent	83051A	HKE-016	Dec. 28, 2017	1 Year
13.	EMI Test Software EZ-EMC	Tonscend	JS1120-B Version	HKE-083	Dec. 28, 2017	N/A
14.	Power Sensor	Agilent	E9300A	HKE-086	Dec. 28, 2017	1 Year
15.	Spectrum analyzer	Agilent	N9020A	HKE-048	Dec. 28, 2017	1 Year
16.	Signal generator	Agilent	N5182A	HKE-029	Dec. 28, 2017	1 Year
17.	Signal Generator	Agilent	83630A	HKE-028	Dec. 28, 2017	1 Year
18.	Shielded room	Shiel Hong	4*3*3	HKE-039	Dec. 28, 2017	3 Year





CONDUCTED EMISSIONS TEST


3.1 Conducted Power Line Emission Limit

For unintentional device, according to § 15.107(a) Line Conducted Emission Limits is as following

Eroguenev	Maximum RF Line Voltage (dBμV)					
Frequency (MHz)	CLAS	SS A	CLASS B			
(11112)	Q.P.	Ave.	Q.P.	Ave.		
0.15 - 0.50	79	66	66-56*	56-46*		
0.50 - 5.00	73	60	56	46		
5.00 - 30.0	73	60	60	50		

^{*} Decreasing linearly with the logarithm of the frequency
For intentional device, according to §15.207(a) Line Conducted Emission Limit is same as above table.

3.2 Test Setup



3.3 Test Procedure

- 1, The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10.
- 2, Support equipment, if needed, was placed as per ANSI C63.10.
- 3, All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
- 4, If a EUT received DC power from the USB Port of Notebook PC, the PC's adapter received AC120V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
- 5, All support equipments received AC power from a second LISN, if any.
- 6, The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7, Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.


3.4 Test Result

PASS

All the test modes completed for test. only the worst result of 8DPSK High Channel was reported as below:



Test Specification: Line




Suspected List									
NO.	Freq.	Level [dBµV]	Factor [dB]	Limit [dΒμV]	Margin [dB]	Detector			
1	0.1545	40.98	10.03	65.75	24.77	PK			
2	0.2760	36.43	10.04	60.94	24.51	PK			
3	0.4155	35.67	10.03	57.54	21.87	PK			
4	0.6450	32.76	10.05	56.00	23.24	PK			
5	1.6800	33.20	10.13	56.00	22.80	PK			
6	12.5385	39.53	9.98	60.00	20.47	PK			

Remark: Transd = Cable lose + Antenna factor - Pre-amplifier; Margin = Limit – Level



Test Specification: Neutral



Suspected List									
NO.	Freq.	Level [dBμV]	Factor [dB]	Limit [dBμ√]	Margin [dB]	Detector			
1	0.1500	41.24	10.03	66.00	24.76	PK			
2	0.2850	35.12	10.04	60.67	25.55	PK			
3	0.4245	33.94	10.04	57.36	23.42	PK			
4	1.0185	32.00	10.07	56.00	24.00	PK			
5	2.2335	30.49	10.17	56.00	25.51	PK			
6	13.3350	35.09	9.96	60.00	24.91	PK			

Remark: Transd = Cable lose + Antenna factor - Pre-amplifier; Margin = Limit – Level



4 RADIATED EMISSION TEST

4.1 Radiation Limit


For unintentional device, according to § 15.109(a), except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency (MHz)	Distance (Meters)	Radiated (dBµV/m)	Radiated (µV/m)
0.009-0.49	3	20log(2400/F(KHz))+40log(300/3)	2400/F(KHz)
0.49-1.705	3	20log(24000/F(KHz))+ 40log(30/3)	24000/F(KHz)
1.705-30	3	20log(30)+ 40log(30/3)	30
30-88	3	40.0	100
88-216	3	43.5	150
216-960	3	46.0	200
Above 960	3	54.0	500


For intentional device, according to § 15.209(a), the general requirement of field strength of radiated emissions from intentional radiators at a distance of 3 meters shall not exceed the above table.

4.2 Test Setup

(1) Radiated Emission Test-Up Frequency Below 30MHz




(2) Radiated Emission Test-Up Frequency 30MHz~1GHz





(3) Radiated Emission Test-Up Frequency Above 1GHz



4.3 Test Procedure

- 1. Below 1GHz measurement the EUT is placed on turntable which is 0.8m above ground plane. And above 1GHz measurement EUT was placed on low permittivity and low tangent turn table which is 1.5m above ground plane.
- 2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
- 3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
- 4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
- 5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
- 6. Repeat above procedures until the measurements for all frequencies are complete.
- 7. The test frequency range from 9KHz to 25GHz per FCC PART 15.33(a).

Note:

For battery operated equipment, the equipment tests shall be performed using a new battery.


4.4 Test Result

PASS

All the test modes completed for test. only the worst result of 8DPSK Low Channel was reported as below:




Below 1GHz Test Results: Antenna polarity: H



Susp	Suspected List								
NO.	Freq.	Level	Factor	Limit	Margin	Height	Angle	Polarity	
IVO.	[MHz]	[dBµV/m]	[dB]	[dBµV/m]	[dB]	[cm]	[°]	Folanty	
1	49.4000	18.18	-13.65	40.00	21.82	100	344	Horizontal	
2	104.690	16.35	-15.41	43.50	27.15	100	350	Horizontal	
3	239.520	23.84	-13.88	46.00	22.16	100	201	Horizontal	
4	359.800	40.72	-11.35	46.00	5.28	100	157	Horizontal	
5	419.940	34.94	-10.04	46.00	11.06	100	150	Horizontal	
6	750.710	28.90	-3.70	46.00	17.10	100	96	Horizontal	

Remark: Transd = Cable lose + Antenna factor - Pre-amplifier; Margin = Limit – Level

Report No.: HK1810171344-E Antenna polarity: V



Suspe	Suspected List									
NO	Freq.	Level	Factor	Limit	Margin	Height	Angle	Dolority		
NO.	[MHz]	[dBµV/m]	[dB]	[dBµV/m]	[dB]	[cm]	[°]	Polarity		
1	50.3700	18.17	-13.71	40.00	21.83	100	185	Vertical		
2	68.8000	16.65	-17.37	40.00	23.35	100	316	Vertical		
3	98.8700	16.87	-15.59	43.50	26.63	100	277	Vertical		
4	170.650	15.80	-17.27	43.50	27.70	100	348	Vertical		
5	419.940	25.32	-10.04	46.00	20.68	100	254	Vertical		
6	579.990	27.34	-6.59	46.00	18.66	100	335	Vertical		

Remark: Transd = Cable lose + Antenna factor - Pre-amplifier; Margin = Limit – Level

Remark:

- (1) Measuring frequencies from 9 KHz to the 1 GHz, Radiated emission test from 9KHz to 30MHz was verified, and no any emission was found except system noise floor.
- (2) * denotes emission frequency which appearing within the Restricted Bands specified in provision of 15.205, then the general radiated emission limits in 15.209 apply.
- (3) The IF bandwidth of EMI Test Receiver between 30MHz to 1GHz was 120KHz, 1 MHz for measuring above 1 GHz, below 30MHz was 10KHz.



Above 1 GHz Test Results:

CH Low (2402MHz)

Horizontal:

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin]
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Detector Type
2402	112.27	-5.81	106.46	114.00	-7.54	peak
2402	86.65	-5.81	80.84	94.00	-13.16	AVG
4804	55.93	-3.65	52.28	74.00	-21.72	peak
4804	46.14	-3.65	42.49	54.00	-11.51	AVG
7206	57.72	-0.95	56.77	74.00	-17.23	peak
7206	41.56	-0.95	40.61	54.00	-13.39	AVG
emark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.						

Vertical:

Meter Reading	Factor	Emission Level	Limits	Margin	
(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Detector Type
111.41	-5.81	105.60	114.00	-8.40	peak
85.90	-5.81	80.09	94.00	-13.91	AVG
55.39	-3.65	51.74	74.00	-22.26	peak
45.95	-3.65	42.30	54.00	-11.70	AVG
56.62	-0.95	55.67	74.00	-18.33	peak
40.54	-0.95	39.59	54.00	-14.41	AVG
	(dBμV) 111.41 85.90 55.39 45.95 56.62	(dBμV) (dB) 111.41 -5.81 85.90 -5.81 55.39 -3.65 45.95 -3.65 56.62 -0.95	(dBμV) (dB) (dBμV/m) 111.41 -5.81 105.60 85.90 -5.81 80.09 55.39 -3.65 51.74 45.95 -3.65 42.30 56.62 -0.95 55.67	(dBμV) (dB) (dBμV/m) (dBμV/m) 111.41 -5.81 105.60 114.00 85.90 -5.81 80.09 94.00 55.39 -3.65 51.74 74.00 45.95 -3.65 42.30 54.00 56.62 -0.95 55.67 74.00	(dBμV) (dB) (dBμV/m) (dBμV/m) (dBμV/m) 111.41 -5.81 105.60 114.00 -8.40 85.90 -5.81 80.09 94.00 -13.91 55.39 -3.65 51.74 74.00 -22.26 45.95 -3.65 42.30 54.00 -11.70 56.62 -0.95 55.67 74.00 -18.33

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.




CH Middle (2441MHz)

Horizontal:

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin			
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Detector Type		
2441	109.66	-5.73	103.93	114.00	-10.07	peak		
2441	86.31	-5.73	80.58	94.00	-13.42	AVG		
4882	55.91	-3.54	52.37	74.00	-21.63	peak		
4882	46.13	-3.54	42.59	54.00	-11.41	AVG		
7323	55.54	-0.81	54.73	74.00	-19.27	peak		
7323	40.22	-0.81	39.41	54.00	-14.59	AVG		
Remark: Facto	Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.							

Vertical:

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin			
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Detector Type		
2441	109.19	-5.73	103.46	114.00	-10.54	peak		
2441	86.33	-5.73	80.60	94.00	-13.40	AVG		
4882	55.37	-3.54	51.83	74.00	-22.17	peak		
4882	45.02	-3.54	41.48	54.00	-12.52	AVG		
7323	55.35	-0.81	54.54	74.00	-19.46	peak		
7323	39.78	-0.81	38.97	54.00	-15.03	AVG		
Remark: Facto	emark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.							





CH High (2480MHz)

Horizontal:

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Detector Type
2480	108.89	-5.63	103.26	114.00	-10.74	peak
2480	85.91	-5.63	80.28	94.00	-13.72	AVG
4960	54.84	-3.43	51.41	74.00	-22.59	peak
4960	44.65	-3.44	41.21	54.00	-12.79	AVG
7440	56.49	-0.77	55.72	74.00	-18.28	peak
7440	39.79	-0.77	39.02	54.00	-14.98	AVG

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Vertical:

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Datastas	
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Detector Type	
2480	108.41	-5.63	102.78	114.00	-11.22	peak	
2480	85.20	-5.63	79.57	94.00	-14.43	AVG	
4960	54.63	-3.43	51.20	74.00	-22.80	peak	
4960	44.16	-3.44	40.72	54.00	-13.28	AVG	
7440	56.07	-0.77	55.30	74.00	-18.70	peak	
7440	38.42	-0.77	37.65	54.00	-16.35	AVG	
Remark: Fac	Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.						

Remark

- (1) Measuring frequencies from 1 GHz to the 25 GHz •
- (2) "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency.
- (3) * denotes emission frequency which appearing within the Restricted Bands specified in provision of 15.205, then the general radiated emission limits in 15.209 apply.
- (4) Data of measurement within this frequency range shown "--- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) The IF bandwidth of EMI Test Receiver between 30MHz to 1GHz was 120KHz, 1 MHz for measuring above 1 GHz, below 30MHz was 10KHz. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for peak measurement with peak detector at frequency above 1GHz. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average measurement with peak
- detection at frequency above 1GHz.
- (6) When the test results of Peak Detected below the limits of Average Detected, the Average Detected is not need completed. For example: Top Channel at Fundamental 73.16dBuV/m(PK Value) <93.98(AV Limit), at harmonic 53.20 dBuV/m(PK Value) <54 dBuV/m(AV Limit), the Average Detected not need to completed.
- (7)All modes of operation were investigated and the worst-case emissions are reported.





5 BAND EDGE

5.1 Limits

FCC PART 15.249(d) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

5.2 Test Procedure

The band edge compliance of RF radiated emission should be measured by following the guidance in ANSI C63.10 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization etc. Set RBW to 100KHz and VBM to 300KHz to measure the peak field strength and set RBW to 1MHz and VBW to 10Hz to measure the average radiated field strength. The conducted RF band edge was measured by using a spectrum analyzer. Set span wide enough to capture the highest in-band emission and the emission at the band edge. Set RBW to 100 KHz and VBW to 300 KHz, to measure the conducted peak band edge.



5.3 Test Result

PASS

All the test modes completed for test. The worst case of Band Edge is GFSK; the test data of this mode was reported.

Radiated Band Edge Test:

Operation Mode: TX CH Low (2402MHz)


Horizontal (Worst case)

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector		
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Туре		
2310	56.81	-5.81	51	74	-23	peak		
2310	1	-5.81	1	54	1	AVG		
2390	55.45	-5.84	49.61	74	-24.39	peak		
2390	1	-5.84	1	54	1	AVG		
2400	55.27	-5.84	49.43	74	-24.57	peak		
2400	/	-5.84	1	54	1	AVG		
Remark: Facto	Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.							

Vertical:

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector		
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Туре		
2310	56.64	-5.81	50.83	74	-23.17	peak		
2310	1	-5.81	1	54	/	AVG		
2390	55.48	-5.84	49.64	74	-24.36	peak		
2390	1	-5.84	1	54	1	AVG		
2400	53.29	-5.84	47.45	74	-26.55	peak		
2400	1	-5.84	1	54	1	AVG		
December 5	Domarky Factor - Antenna Factor I Cable Loca Dra amplifier							

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.





Operation Mode: TX CH High (2480MHz)

Horizontal (Worst case)

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Туре
2483.50	56.87	-5.81	51.06	74	-22.94	peak
2483.50	1	-5.81	1	54	1	AVG
2500.00	54.53	-6.06	48.47	74	-25.53	peak
2500.00	1	-6.06	1	54	1	AVG

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Vertical:

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Туре
2483.50	55.91	-5.81	50.1	74	-23.9	peak
2483.50	1	-5.81	1	54	1	AVG
2500.00	53.66	-6.06	47.6	74	-26.4	peak
2500.00	1	-6.06	1	54	1	AVG

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Remark: All the other emissions not reported were too low to read and deemed to comply with FCC limit.



6 OCCUPIED BANDWIDTH MEASUREMENT

6.1 Test Setup

Same as Radiated Emission Measurement

6.2 Test Procedure

- 1. The EUT was placed on a turn table which is 0.8m above ground plane.
- 2. Set EUT as normal operation.
- 3. Based on ANSI C63.10 section 6.9.2: RBW= 30KHz. VBW= 100 KHz, Span=2MHz.
- 4. The useful radiated emission from the EUT was detected by the spectrum analyser with peak detector.

6.3 Measurement Equipment Used

Same as Radiated Emission Measurement

6.4 Test Result

PASS

Test Mode	Frequency	20dB Bandwidth (MHz)	Result
	2402 MHz	0.8336	PASS
GFSK	2441 MHz	0.8337	PASS
	2480 MHz	0.8226	PASS
	2402 MHz	1.118	PASS
π/4DQPSK	2441 MHz	1.123	PASS
	2480 MHz	1.119	PASS
	2402 MHz	1.125	PASS
8DPSK	2441 MHz	1.145	PASS
	2480 MHz	1.118	PASS



Test Mode: GFSK

CH: 2402MHz



CH: 2441MHz





CH: 2480MHz



Test Mode: π/4DQPSK

CH: 2402MHz





CH: 2441MHz



CH: 2480MHz





Test Mode: 8DPSK

CH: 2402MHz



CH: 2441MHz





CH: 2480MHz





7 ANTENNA REQUIREMENT


Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.249, if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

Antenna Connected Construction


The antenna used in this product is a PCB Antenna, The directional gains of antenna used for transmitting is 0dBi.

ANTENNA





Radiated Emission







Conducted Emission

