



TEST REPORT

Report Reference No...... : **TRE1609006101** R/C.....:91606

FCC ID..... : 2AKFJ-278RTW-TX

Applicant's name..... : **Shenzhen Allied Control System Co.,LTD**

Address..... : 6-7th floor,Blk.C,Junxing Industrial Area B,HePing,Fuyong Town,Bao An District,Shenzhen City,Guangdong Province ,P.R..China

Manufacturer..... : Shenzhen Allied Control System Co.,LTD

Address..... : 6-7th floor,Blk.C,Junxing Industrial Area B,HePing,Fuyong Town,Bao An District,Shenzhen City,Guangdong Province ,P.R..China

Test item description : **WIFI Thermostat**

Trade Mark : RADIANT Cloudwarm

Model/Type reference..... : HRT-278RTW-TX

Listed Model(s) : -

Standard : **FCC CFR Title 47 Part 15 Subpart C Section 15.247**

Date of receipt of test sample..... : Sept. 13,2016

Date of testing..... : Sept. 14,2016 - Oct. 31,2016

Date of issue..... : Nov. 14,2016

Result..... : **PASS**

Compiled by
(position+printedname+signature)....: File administrators Becky Liang

Supervised by
(position+printedname+signature)....: Project Engineer Jeff Sun

Approved by
(position+printedname+signature)....: RF Manager Hans Hu

Testing Laboratory Name : **Shenzhen Huatongwei International Inspection Co., Ltd.**

Address..... : 1/F, Bldg 3, Hongfa Hi-tech Industrial Park, Genyu Road, Tianliao, Gongming, Shenzhen, China

Shenzhen Huatongwei International Inspection Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Huatongwei International Inspection Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Huatongwei International Inspection Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Contents

<u>1.</u>	<u>TEST STANDARDS AND REPORT VERSION</u>	<u>3</u>
1.1.	Applicable Standards	3
1.2.	Report version	3
<u>2.</u>	<u>TEST DESCRIPTION</u>	<u>4</u>
<u>3.</u>	<u>SUMMARY</u>	<u>5</u>
3.1.	Client Information	5
3.2.	Product Description	5
3.3.	Operation state	6
3.4.	EUT configuration	6
3.5.	Modifications	6
<u>4.</u>	<u>TEST ENVIRONMENT</u>	<u>7</u>
4.1.	Address of the test laboratory	7
4.2.	Test Facility	7
4.3.	Equipments Used during the Test	8
4.4.	Environmental conditions	9
4.5.	Statement of the measurement uncertainty	9
<u>5.</u>	<u>TEST CONDITIONS AND RESULTS</u>	<u>10</u>
5.1.	Antenna requirement	10
5.2.	Conducted Emission (AC Main)	11
5.3.	Conducted Peak Output Power	14
5.4.	Power Spectral Density	15
5.5.	6dB bandwidth and	19
5.6.	Restricted band	23
5.7.	Band edge and Spurious Emission (conducted)	26
5.8.	Spurious Emission (radiated)	31
<u>6.</u>	<u>TEST SETUP PHOTOS OF THE EUT</u>	<u>42</u>
<u>7.</u>	<u>EXTERNAL AND INTERNAL PHOTOS OF THE EUT</u>	<u>44</u>

1. Test standards and Report version

1.1. Applicable Standards

The tests were performed according to following standards:

[FCC Rules Part 15.247](#): Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz.

[ANSI C63.10:2013](#): American National Standard for Testing Unlicensed Wireless Devices

[KDB558074 D01 DTS Meas Guidance v03r05](#): Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating under § 15.247

1.2. Report version

Version No.	Date of issue	Description
00	Nov. 14, 2016	Original

2. Test Description

Test Item	Section in CFR 47	Result
Antenna requirement	15.203/15.247 (c)	Pass
Line Conducted Emission (AC Main)	15.207	Pass
Conducted Peak Output Power	15.247 (b)(3)	Pass
Power Spectral Density	15.247 (e)	Pass
6dB Bandwidth	15.247 (a)(2)	Pass
Restricted band	15.247(d)/15.205	Pass
Spurious Emission	15.247(d)/15.209	Pass

Note: The measurement uncertainty is not included in the test result.

3. Summary

3.1. Client Information

Applicant:	Shenzhen Allied Control System Co.,LTD
Address:	6-7th floor,Blk.C,Junxing Industrial Area B,HePing,Fuyong Town,Bao An District,Shenzhen City,Guangdong Province ,P.R..China
Manufacturer:	Shenzhen Allied Control System Co.,LTD
Address:	6-7th floor,Blk.C,Junxing Industrial Area B,HePing,Fuyong Town,Bao An District,Shenzhen City,Guangdong Province ,P.R..China

3.2. Product Description

Name of EUT	WIFI Thermostat			
Trade Mark:	RADIANT Cloudwarm			
Model No.:	HRT-278RTW-TX			
Listed Model(s):	-			
Power supply:	AC 120V/60Hz			
Adapter information:	Model: S005ANV0500100 Input: 100-240Va.c., 50/60Hz, 200mA; Output: 5.0Vd.c., 1000mA			
WIFI				
Supported type:	☒ 802.11b	☒ 802.11g	☒ 802.11n(H20)	☒ 802.11n(H40)
Modulation:	<u>DSSS</u> for 802.11b <u>OFDM</u> for 802.11g/802.11n(H20)/802.11n(H40)			
Operation frequency:	<u>2412MHz~2462MHz</u> for 802.11b/802.11g/802.11n(H20) <u>2422MHz~2452MHz</u> for 802.11n(H40)			
Channel number:	<u>11</u> for 802.11b/802.11g/802.11n(H20) <u>7</u> for 802.11n(H40)			
Channel separation:	5MHz			
Antenna type:	Integral antenna			
Antenna gain:	2.18dBi			

3.3. Operation state

➤ Test frequency list

According to section 15.31(m), regards to the operating frequency range over 10 MHz, must select three channel which were tested. the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, please see the above gray bottom.

802.11b/g/n(H20)		802.11n(H40)	
Channel	Frequency (MHz)	Channel	Frequency (MHz)
01	2412	01	-
02	2417	02	-
03	2422	03	2422
04	2427	04	2427
05	2432	05	2432
06	2437	06	2437
07	2442	07	2442
08	2447	08	2447
09	2452	09	2452
10	2457	10	-
11	2462	11	-

➤ Test mode

For RF test items
The engineering test program was provided and enabled to make EUT continuous transmit.
For AC power line conducted emissions:
The EUT was set to connect with large package sizes transmission.

3.4. EUT configuration

The following peripheral devices and interface cables were connected during the measurement:

- - supplied by the manufacturer
- - supplied by the lab

○		Manufacturer :	/
		Model No. :	/
○		Manufacturer :	/
		Model No. :	/

3.5. Modifications

No modifications were implemented to meet testing criteria.

4. Test Environment

4.1. Address of the test laboratory

Laboratory: Shenzhen Huatongwei International Inspection Co., Ltd.

Address: 1/F, Bldg 3, Hongfa Hi-tech Industrial Park, Genyu Road, Tianliao, Gongming, Shenzhen, China

Phone: 86-755-26748019 Fax: 86-755-26748089

4.2. Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L1225

Shenzhen Huatongwei International Inspection Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories

(identical to ISO/IEC17025: 2005 General Requirements) for the Competence of Testing and Calibration Laboratories, Date of Registration: February 28, 2015. Valid time is until February 27, 2018.

A2LA-Lab Cert. No. 3902.01

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing. Valid time is until December 31, 2016.

FCC-Registration No.: 317478

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. Registration 317478, Renewal date Jul. 18, 2014, valid time is until Jul. 18, 2017.

IC-Registration No.: 5377A&5377B

The 3m Alternate Test Site of Shenzhen Huatongwei International Inspection Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for the performance of radiated measurements with Registration No. 5377A on Dec. 31, 2013, valid time is until Dec. 31, 2016.

Two 3m Alternate Test Site of Shenzhen Huatongwei International Inspection Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for the performance of radiated measurements with Registration No. 5377B on Dec.03, 2014, valid time is until Dec.03, 2017.

ACA

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory can also perform testing for the Australian C-Tick mark as a result of our A2LA accreditation.

4.3. Equipments Used during the Test

Line Conducted Emission (AC Main)					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal.
1	EMI Test Receiver	R&S	ESCI	101247	2015/11/03
2	Artificial Mains	Shwarzbeck	NNLK 8121	573	2015/11/03
3	Pulse Limiter	R&S	ESH3-Z2	101488	2015/11/03
4	Test Software	R&S	ES-K1	N/A	N/A
5	Test cable	ENVIROFLEX	3651	1101902	2015/12/05

Maximum Peak Output Power / Power Spectral Density / 6dB Bandwidth / Band Edge Compliance of RF Emission / Spurious RF Conducted Emission					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal
1	Spectrum Analyzer	Rohde&Schwarz	FSP	1164.4391.40	2015/11/02
2	Power Meter	Anritsu	ML2480B	100798	2015/11/02
3	Power Sensor	Anritsu	MA2411B	100258	2015/12/05
4	Test cable	FARPU	MCX-J	N/A	2015/12/05
5	Temporary antenna connector	D-LENP	NJ-SMAK	N/A	2015/12/05

Radiated Emission					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal.
1	EMI Test Receiver	Rohde&Schwarz	ESI 26	100009	2015/11/02
2	RF Test Panel	Rohde&Schwarz	TS / RSP	335015/0017	N/A
3	EMI Test Software	Rohde&Schwarz	ESK1	N/A	N/A
4	Loop Antenna	Rohde&Schwarz	HZ-9	838622\013	2015/11/08
5	Ultra-Broadband Antenna	ShwarzBeck	VULB9163	538	2015/11/08
6	Horn Antenna	ShwarzBeck	9120D	1011	2015/11/08
7	Broadband Horn Antenna	Shwarzbeck	BBHA9170	BBHA917047 2	2015/11/08
8	Preamplifier	Shwarzbeck	BBV9742	9742-196	2015/11/02
9	Broadband Preamplifier	Shwarzbeck	BBV 9721	9721-102	2015/11/02
10	Broadband Preamplifier	Shwarzbeck	BBV 9718	9718-247	2015/11/02
11	Turn Table	MATURO	TT2.0	/	N/A
12	Antenna Mast	MATURO	TAM-4.0-P	/	N/A
13	EMI Test Software	Audix	E3	N/A	N/A
14	Test Software	R&S	ES-K1	N/A	N/A
15	Test cable	Siva Cables Italy	RG 58A/U	W14.02	2015/12/05

The Cal.Interval was one year

4.4. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15~35°C
Relative Humidity:	30~60 %
Air Pressure:	950~1050mba

4.5. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report according to TR-100028-01 "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 1" and TR-100028-02 "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 2" and is documented in the Shenzhen Huatongwei International Inspection Co., Ltd quality system according to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen Huatongwei laboratory is reported:

Test Items	Measurement Uncertainty	Notes
Transmitter power conducted	0.57 dB	(1)
Transmitter power Radiated	2.20 dB	(1)
Conducted spurious emission 9KHz-40 GHz	1.60 dB	(1)
Radiated spurious emission 9KHz-40 GHz	2.20 dB	(1)
Conducted Emission 9KHz-30MHz	3.39 dB	(1)
Radiated Emission 30~1000MHz	4.24 dB	(1)
Radiated Emission 1~18GHz	5.16 dB	(1)
Radiated Emission 18-40GHz	5.54 dB	(1)
Occupied Bandwidth	-----	(1)

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=1.96$.

5. Test Conditions and Results

5.1. Antenna requirement

REQUIREMENT:

FCC CFR Title 47 Part 15 Subpart C Section 15.203:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.


FCC CFR Title 47 Part 15 Subpart C Section 15.247(c) (1)(i):

(i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.

TEST RESULTS

☒ Passed ☐ Not Applicable

The antenna is integral antenna, the best case gain of the antenna is 2.18dBi, please refer to the below antenna photo.



5.2. Conducted Emission (AC Main)


LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.207:

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

TEST CONFIGURATION



TEST PROCEDURE

1. The EUT was setup according to ANSI C63.10:2013 for compliance to FCC 47CFR 15.247 requirements.
2. The EUT was placed on a platform of nominal size, 1 m by 1.5 m, raised 80 cm above the conducting ground plane. The vertical conducting plane was located 40 cm to the rear of the EUT. All other surfaces of EUT were at least 80 cm from any other grounded conducting surface.
3. The EUT and simulators are connected to the main power through a line impedance stabilization network (LISN). The LISN provides a 50 ohm /50uH coupling impedance for the measuring equipment.
4. The peripheral devices are also connected to the main power through a LISN. (Please refer to the block diagram of the test setup and photographs)
5. Each current-carrying conductor of the EUT power cord, except the ground (safety) conductor, was individually connected through a LISN to the input power source.
6. The excess length of the power cord between the EUT and the LISN receptacle were folded back and forth at the center of the lead to form a bundle not exceeding 40 cm in length.
7. Conducted emissions were investigated over the frequency range from 0.15 MHz to 30 MHz using a receiver bandwidth of 9 kHz.
8. During the above scans, the emissions were maximized by cable manipulation.

TEST MODE:


Please refer to the clause 3.3

TEST RESULTS

☒ Passed ☐ Not Applicable

Test Line:

L

**MEASUREMENT RESULT: "GM1609215015_fin"**

9/21/2016 1:28PM

Frequency MHz	Level dBuV	Transd dB	Limit dBuV	Margin dB	Detector	Line	PE
0.321000	30.60	10.2	60	29.1	QP	L1	GND
0.406500	38.80	10.2	58	18.9	QP	L1	GND
0.609000	29.60	10.2	56	26.4	QP	L1	GND
1.036500	28.50	10.3	56	27.5	QP	L1	GND
1.288500	29.50	10.3	56	26.5	QP	L1	GND
2.854500	23.80	10.4	56	32.2	QP	L1	GND


MEASUREMENT RESULT: "GM1609215015_fin2"

9/21/2016 1:28PM

Frequency MHz	Level dBuV	Transd dB	Limit dBuV	Margin dB	Detector	Line	PE
0.343500	21.90	10.2	49	27.2	AV	L1	GND
0.388500	27.90	10.2	48	20.2	AV	L1	GND
0.397500	16.40	10.2	48	31.5	AV	L1	GND
0.411000	29.50	10.2	48	18.1	AV	L1	GND
0.613500	20.80	10.2	46	25.2	AV	L1	GND
1.360500	19.30	10.3	46	26.7	AV	L1	GND

Test Line:

N

**MEASUREMENT RESULT: "GM1609215016_fin"**

9/21/2016 1:32PM

Frequency MHz	Level dBuV	Transd dB	Limit dBuV	Margin dB	Detector	Line	PE
0.366000	23.00	10.2	59	35.6	QP	N	GND
0.406500	34.90	10.2	58	22.8	QP	N	GND
1.023000	26.40	10.3	56	29.6	QP	N	GND
2.193000	23.20	10.3	56	32.8	QP	N	GND
5.343000	15.20	10.5	60	44.8	QP	N	GND
23.131500	24.00	10.8	60	36.0	QP	N	GND

MEASUREMENT RESULT: "GM1609215016_fin2"

9/21/2016 1:32PM


Frequency MHz	Level dBuV	Transd dB	Limit dBuV	Margin dB	Detector	Line	PE
0.321000	21.80	10.2	50	27.9	AV	N	GND
0.388500	29.10	10.2	48	19.0	AV	N	GND
0.411000	29.80	10.2	48	17.8	AV	N	GND
1.360500	18.90	10.3	46	27.1	AV	N	GND
2.197500	16.20	10.3	46	29.8	AV	N	GND
23.131500	23.40	10.8	50	26.6	AV	N	GND

5.3. Conducted Peak Output Power

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (b)(3): **30dBm**:

TEST CONFIGURATION



TEST PROCEDURE

1. The EUT was tested according to ANSI C63.10: 2013 and KDB 558074 D01 for compliance to FCC 47CFR 15.247 requirements.
2. The maximum peak conducted output power may be measured using a broadband peak RF power meter.
3. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector
4. Record the measurement data.

TEST MODE:

Please refer to the clause 3.3

TEST RESULTS

☒ **Passed** ☐ **Not Applicable**

Type	Channel	Output power (dBm)	Limit (dBm)	Result
802.11b	01	8.21	30.00	Pass
	06	8.09		
	11	7.83		
802.11g	01	7.87	30.00	Pass
	06	7.51		
	11	7.38		
802.11n(H20)	01	5.96	30.00	Pass
	06	5.75		
	11	6.16		
802.11n(H40)	03	7.52	30.00	Pass
	06	7.25		
	09	7.13		


5.4. Power Spectral Density

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (e):

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

TEST CONFIGURATION



TEST PROCEDURE

1. Connect the antenna port(s) to the spectrum analyzer input,
2. Configure the spectrum analyzer as shown below:
Center frequency = DTS channel center frequency
Span = 1.5 times the DTS bandwidth
 $RBW = 3 \text{ kHz} \leq RBW \leq 100 \text{ kHz}$, $VBW \geq 3 \times RBW$
Sweep time = auto couple
Detector = peak
Trace mode = max hold
3. Place the radio in continuous transmit mode, allow the trace to stabilize, view the transmitter waveform on the spectrum analyzer.
4. Use the peak marker function to determine the maximum amplitude level within the RBW.
5. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

TEST MODE:


Please refer to the clause 3.3

TEST RESULTS


☒ Passed ☐ Not Applicable

Type	Channel	Power Spectral Density(dBm/3KHz)	Limit (dBm/3KHz)	Result
802.11b	01	-20.56	8.00	Pass
	06	-22.72		
	11	-22.15		
802.11g	01	-25.85	8.00	Pass
	06	-25.44		
	11	-26.07		
802.11n(H20)	01	-25.08	8.00	Pass
	06	-25.41		
	11	-24.98		
802.11n(H40)	03	-27.51	8.00	Pass
	06	-28.36		
	09	-26.90		


Test plot as follows:




802.11n(H20)



CH01




CH06




CH11

No Plot


802.11n(H40)



CH03



CH06



CH09

No Plot


5.5. 6dB bandwidthand

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(2):

For digital modulation systems, the minimum 6 dB bandwidth shall be at least 500 kHz.

TEST CONFIGURATION



TEST PROCEDURE

1. Connect the antenna port(s) to the spectrum analyzer input.
2. Configure the spectrum analyzer as shown below (enter all losses between the transmitter output and the spectrum analyzer).
Center Frequency = DTS channel center frequency
Span = 2 x DTS bandwidth
RBW = 100 kHz, VBW $\geq 3 \times$ RBW
Sweep time = auto couple
Detector = Peak
Trace mode = max hold
3. Place the radio in continuous transmit mode, allow the trace to stabilize, view the transmitter waveform on the spectrum analyzer.
4. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission, and record the pertinent measurements.

TEST MODE:

Please refer to the clause 3.3


TEST RESULTS

☒ Passed ☐ Not Applicable


Type	Channel	6dB Bandwidth (MHz)	Limit (KHz)	Result
802.11b	01	9.88	≥ 500	Pass
	06	10.06		
	11	9.88		
802.11g	01	16.56	≥ 500	Pass
	06	16.61		
	11	16.61		
802.11n(H20)	01	17.12	≥ 500	Pass
	06	16.77		
	11	17.12		
802.11n(H40)	03	36.19	≥ 500	Pass
	06	36.25		
	09	36.36		

Test plot as follows:


802.11b



CH01




CH06




CH11

No Plot


802.11g



CH01




CH06




CH11

No Plot


802.11n(H20)



CH01




CH06




CH11

No Plot


802.11n(H40)



CH03



CH06



CH09

No Plot


5.6. Restricted band

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (d):

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

TEST CONFIGURATION



TEST PROCEDURE

- 1) The EUT was setup and tested according to ANSI C63.10:2013 for compliance to FCC 47CFR 15.247 requirements.
- 2) The EUT is placed on a turn table which is 1.5 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
- 3) The EUT was positioned such that the distance from antenna to the EUT was 3 meters.
- 4) The antenna is scanned from 1 meter to 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10:2013 on radiated measurement.
- 5) The receiver set as follow:
 RBW=1MHz, VBW=3MHz Peak detector for Peak value
 RBW=1MHz, VBW=3MHz RMS detector for Average value.

TEST MODE:

Please refer to the clause 3.3

TEST RESULTS

☒ **Passed** ☐ **Not Applicable**

Note:

- 1) *Final level = Read level + Antenna Factor + Cable Loss - Preamp Factor*

802.11b					CH01				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin Limit (dB)	Polarization	Test value
2389.99	19.15	27.53	6.81	0.00	53.49	74.00	-20.51	Vertical	Peak
2389.99	16.99	27.53	6.81	0.00	51.33	74.00	-22.67	Horizontal	
2389.99	11.31	27.53	6.81	0.00	45.71	54.00	-8.29	Vertical	Average
2389.99	10.55	27.53	6.81	0.00	44.89	54.00	-9.11	Horizontal	

802.11b					CH11				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin Limit (dB)	Polarization	Test value
2483.49	17.62	27.85	6.96	0.00	52.43	74.00	-21.57	Vertical	Peak
2483.49	18.89	27.85	6.96	0.00	53.70	74.00	-20.30	Horizontal	
2483.49	11.94	27.85	6.96	0.00	46.75	54.00	-7.25	Vertical	Average
2483.49	11.11	27.85	6.96	0.00	45.92	54.00	-8.08	Horizontal	

802.11g					CH01				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin Limit (dB)	Polarization	Test value
2389.99	17.07	27.53	6.81	0.00	51.41	74.00	-22.59	Vertical	Peak
2389.99	16.91	27.53	6.81	0.00	51.25	74.00	-22.75	Horizontal	
2389.99	11.00	27.53	6.81	0.00	45.34	54.00	-8.66	Vertical	Average
2389.99	10.76	27.53	6.81	0.00	45.10	54.00	-8.90	Horizontal	

802.11g					CH11				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin Limit (dB)	Polarization	Test value
2483.49	17.98	27.85	6.96	0.00	52.79	74.00	-21.21	Vertical	Peak
2483.49	18.57	27.85	6.96	0.00	53.38	74.00	-20.62	Horizontal	
2483.49	12.84	27.85	6.96	0.00	47.65	54.00	-6.35	Vertical	Average
2483.49	12.31	27.85	6.96	0.00	47.12	54.00	-6.88	Horizontal	

802.11n(H20)					CH01				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin Limit (dB)	Polarization	Test value
2389.99	19.59	27.53	6.81	0.00	53.93	74.00	-20.07	Vertical	Peak
2389.99	18.00	27.53	6.81	0.00	52.34	74.00	-21.66	Horizontal	
2389.99	12.65	27.53	6.81	0.00	46.99	54.00	-7.01	Vertical	Average
2389.99	10.84	27.53	6.81	0.00	45.18	54.00	-8.82	Horizontal	

802.11n(H20)					CH11				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin Limit (dB)	Polarization	Test value
2483.48	23.53	27.85	6.96	0.00	58.34	74.00	-15.66	Vertical	Peak
2483.48	19.19	27.85	6.96	0.00	54.00	74.00	-20.00	Horizontal	
2483.48	15.14	27.85	6.96	0.00	49.95	54.00	-4.05	Vertical	Average
2483.48	14.26	27.85	6.96	0.00	49.07	54.00	-4.93	Horizontal	

802.11n(H40)					CH03				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin Limit (dB)	Polarization	Test value
2389.99	28.01	27.53	6.81	0.00	62.35	74.00	-11.65	Vertical	Peak
2389.99	18.10	27.53	6.81	0.00	52.44	74.00	-21.56	Horizontal	
2389.99	13.40	27.53	6.81	0.00	47.74	54.00	-6.26	Vertical	Average
2389.99	11.89	27.53	6.81	0.00	46.23	54.00	-7.77	Horizontal	

802.11n(H40)					CH09				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin Limit (dB)	Polarization	Test value
2483.49	23.17	27.85	6.96	0.00	57.98	74.00	-16.02	Vertical	Peak
2483.49	19.27	27.85	6.96	0.00	54.08	74.00	-19.92	Horizontal	
2483.49	14.42	27.85	6.96	0.00	49.23	54.00	-4.77	Vertical	Average
2483.49	12.62	27.85	6.96	0.00	47.43	54.00	-6.57	Horizontal	


5.7. Band edge and Spurious Emission (conducted)

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (d):

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

TEST CONFIGURATION



TEST PROCEDURE

1. Connect the antenna port(s) to the spectrum analyzer input.
2. Establish a reference level by using the following procedure
Center frequency = DTS channel center frequency
The span = 1.5 times the DTS bandwidth.
RBW = 100 kHz, VBW ≥ 3 x RBW
Detector = peak, Sweep time = auto couple, Trace mode = max hold
Allow trace to fully stabilize
Use the peak marker function to determine the maximum PSD level

Note: the channel found to contain the maximum PSD level can be used to establish the reference level.


3. Emission level measurement
Set the center frequency and span to encompass frequency range to be measured
RBW = 100 kHz, VBW ≥ 3 x RBW
Detector = peak, Sweep time = auto couple, Trace mode = max hold
Allow trace to fully stabilize
Use the peak marker function to determine the maximum amplitude level.
4. Place the radio in continuous transmit mode, allow the trace to stabilize, view the transmitter waveform on the spectrum analyzer.
5. Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band excluding restricted frequency bands) are attenuated by at least the minimum requirements specified (at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz). Report the three highest emissions relative to the limit.

TEST MODE:


Please refer to the clause 3.3

TEST RESULTS


☒ Passed ☐ Not Applicable




802.11g



CH01-SE




CH01-Bandedge




CH06

No Plot




CH11-SE





CH11-Bandedge


802.11n (H20)



802.11n (H40)




CH03-SE




CH03-Bandedge

No Plot

CH06



-



CH09-SE

CH09-Bandedge

5.8. Spurious Emission (radiated)


LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.209


Frequency	Limit (dBuV/m @3m)	Value
30MHz-88MHz	40.00	Quasi-peak
88MHz-216MHz	43.50	Quasi-peak
216MHz-960MHz	46.00	Quasi-peak
960MHz-1GHz	54.00	Quasi-peak
Above 1GHz	54.00	Average
	74.00	Peak

TEST CONFIGURATION


➤ 9KHz ~30MHz



➤ 30MHz ~ 1GHz



➤ Above 1GHz



TEST PROCEDURE

1. The EUT was tested according to ANSI C63.10:2013 for compliance to FCC 47CFR 15.247 requirements.
2. The EUT is placed on a turn table which is 0.8 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
3. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.
4. The antenna is scanned from 1 meter to 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna.
5. Use the following spectrum analyzer settings
 - (1) Span shall be wide enough to fully capture the emission being measured;
 - (2) Below 1GHz, RBW=120KHz, VBW=300KHz, Sweep=auto, Detector function=QP, Trace=max hold;
If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
 - (3) Above 1GHz, RBW=1MHz, VBW=3MHz Peak detector for Peak value
RBW=1MHz, VBW=3MHz RMS detector for Average value.

TEST MODE:

Please refer to the clause 3.3

TEST RESULTS

☒ **Passed** ☐ **Not Applicable**

Note:

- 1) *Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor*
- 2) *"**", means this data is too weak; instrument of signal is unable to test.*
- 3) *The emission levels of other frequencies are very lower than the limit and not shown in test report.*


➤ **9kHz ~ 30MHz**

The EUT was pre-scanned the frequency band (9kHz~30MHz), found the radiated level lower than the limit, so don't show on the report.

➤ 30MHz ~ 1GHz

Polarization:

Vertical


**MEASUREMENT RESULT: "GM1609266083_red"**

9/26/2016 5:53PM

Frequency MHz	Level dBμV/m	Transd dB	Limit dBμV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
565.440000	35.50	-4.1	46.0	10.5	QP	100.0	147.00	VERTICAL
590.660000	34.50	-3.1	46.0	11.5	QP	100.0	168.00	VERTICAL
639.160000	34.20	-2.4	46.0	11.8	QP	100.0	179.00	VERTICAL
662.440000	34.40	-2.1	46.0	11.6	QP	100.0	320.00	VERTICAL
685.720000	35.10	-1.9	46.0	10.9	QP	100.0	331.00	VERTICAL
734.220000	33.70	-1.0	46.0	12.3	QP	100.0	359.00	VERTICAL

Polarization:

Horizontal

**MEASUREMENT RESULT: "GM1609266082_red"**

9/26/2016 5:51PM

Frequency MHz	Level dBμV/m	Transd dB	Limit dBμV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
470.380000	27.70	-8.3	46.0	18.3	QP	100.0	0.00	HORIZONTAL
565.440000	29.40	-4.1	46.0	16.6	QP	300.0	22.00	HORIZONTAL
710.940000	32.00	-1.5	46.0	14.0	QP	100.0	207.00	HORIZONTAL
734.220000	32.60	-1.0	46.0	13.4	QP	100.0	231.00	HORIZONTAL
759.440000	34.00	-0.5	46.0	12.0	QP	300.0	197.00	HORIZONTAL
903.000000	35.70	2.7	46.0	10.3	QP	100.0	171.00	HORIZONTAL

➤ Above 1GHz

802.11b					CH01				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin Limit (dB)	Polarization	Test value
2999.187	40.89	28.5	8.17	37.99	39.57	74	-34.43	Vertical	Peak
3299.344	42.87	28.62	8.56	37.99	42.06	74	-31.94	Vertical	
3693.033	41.26	29.02	8.72	37.99	41.01	74	-32.99	Vertical	
4495.125	40.36	30.9	8.98	38.33	41.91	74	-32.09	Vertical	
4831.962	41.39	31.1	9.22	38.55	43.16	74	-30.84	Vertical	
7200.309	35.58	35.97	10.85	38.1	44.3	74	-29.7	Vertical	
1224.247	37.06	24.45	4.59	36.54	29.56	74	-44.44	Horizontal	
1653.55	37.11	25.18	5.51	36.97	30.83	74	-43.17	Horizontal	
3693.033	41.74	29.02	8.72	37.99	41.49	74	-32.51	Horizontal	
4831.962	47.45	31.1	9.22	38.55	49.22	74	-24.78	Horizontal	
8943.274	31.84	37.83	11.64	37.96	43.35	74	-30.65	Horizontal	
9285.71	33.19	38.02	11.86	38.01	45.06	74	-28.94	Horizontal	

802.11b					CH06				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin Limit (dB)	Polarization	Test value
2999.187	40.67	28.5	8.17	37.99	39.35	74	-34.65	Vertical	Peak
3299.344	40.61	28.62	8.56	37.99	39.8	74	-34.2	Vertical	
3693.033	41.29	29.02	8.72	37.99	41.04	74	-32.96	Vertical	
4495.125	40.38	30.9	8.98	38.33	41.93	74	-32.07	Vertical	
4888.151	41.58	31.14	9.26	38.58	43.4	74	-30.6	Vertical	
7476.006	34.76	36.18	10.96	38.15	43.75	74	-30.25	Vertical	
2999.187	36.93	28.5	8.17	37.99	35.61	74	-38.39	Horizontal	
3693.033	40.21	29.02	8.72	37.99	39.96	74	-34.04	Horizontal	
4888.151	46.2	31.14	9.26	38.58	48.02	74	-25.98	Horizontal	
6545.263	32.61	35.16	10.39	37.99	40.17	74	-33.83	Horizontal	
7966.832	32.48	36.68	11.23	38.25	42.14	74	-31.86	Horizontal	
10453.97	33.09	38.66	12.83	38.14	46.44	74	-27.56	Horizontal	

802.11b					CH11				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin Limit (dB)	Polarization	Test value
1629.825	35.96	25.11	5.46	36.95	29.58	74	-44.42	Vertical	Peak
2999.187	40.9	28.5	8.17	37.99	39.58	74	-34.42	Vertical	
3693.033	41.05	29.02	8.72	37.99	40.8	74	-33.2	Vertical	
4495.125	40.56	30.9	8.98	38.33	42.11	74	-31.89	Vertical	
4944.993	40.76	31.17	9.31	38.62	42.62	74	-31.38	Vertical	
7200.309	34.82	35.97	10.85	38.1	43.54	74	-30.46	Vertical	
1199.726	36.78	24.43	4.53	36.51	29.23	74	-44.77	Horizontal	
1792.937	36.14	25.57	5.78	37.09	30.4	74	-43.6	Horizontal	
3299.344	38.7	28.62	8.56	37.99	37.89	74	-36.11	Horizontal	
3693.033	41.01	29.02	8.72	37.99	40.76	74	-33.24	Horizontal	
4944.993	44.46	31.17	9.31	38.62	46.32	74	-27.68	Horizontal	
8416.584	31.89	37.13	11.25	38.12	42.15	74	-31.85	Horizontal	

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The peak level is lower than average limit (54 dBuV/m), this data is the too weak instrument of signal is unable to test.
3. The emission levels of other frequencies are very lower than the limit and not show in test report.

802.11g					CH01				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin Limit (dB)	Polarization	Test value
2990.531	41.45	28.49	8.15	37.98	40.11	74	-33.89	Vertical	Peak
3299.344	41.35	28.62	8.56	37.99	40.54	74	-33.46	Vertical	
3693.033	43.19	29.02	8.72	37.99	42.94	74	-31.06	Vertical	
4495.125	38.54	30.9	8.98	38.33	40.09	74	-33.91	Vertical	
4818.016	39.76	31.09	9.21	38.54	41.52	74	-32.48	Vertical	
5031.499	38.45	31.27	9.36	38.63	40.45	74	-33.55	Vertical	
1777.458	34.52	25.53	5.76	37.08	28.73	74	-45.27	Horizontal	
3034.063	34.31	28.52	8.22	37.99	33.06	74	-40.94	Horizontal	
4341.886	33.51	30.48	8.87	38.23	34.63	74	-39.37	Horizontal	
6717.762	31.77	35.41	10.53	38.02	39.69	74	-34.31	Horizontal	
7454.429	30.69	36.17	10.95	38.15	39.66	74	-34.34	Horizontal	
9152.479	32.04	37.96	11.78	37.98	43.8	74	-30.2	Horizontal	

802.11g					CH06				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin Limit (dB)	Polarization	Test value
1300.858	37.48	24.53	4.77	36.63	30.15	74	-43.85	Vertical	Peak
1824.302	36.53	25.65	5.84	37.12	30.9	74	-43.1	Vertical	
3693.033	40.28	29.02	8.72	37.99	40.03	74	-33.97	Vertical	
4888.151	42.5	31.14	9.26	38.58	44.32	74	-29.68	Vertical	
8539.102	33.45	37.27	11.27	38.08	43.91	74	-30.09	Vertical	
9641.257	33.83	38.18	12.14	38.07	46.08	74	-27.92	Vertical	
1323.614	36.11	24.55	4.81	36.65	28.82	74	-45.18	Horizontal	
3299.344	39.75	28.62	8.56	37.99	38.94	74	-35.06	Horizontal	
3693.033	40.59	29.02	8.72	37.99	40.34	74	-33.66	Horizontal	
4888.151	39.91	31.14	9.26	38.58	41.73	74	-32.27	Horizontal	
7454.429	32.36	36.17	10.95	38.15	41.33	74	-32.67	Horizontal	
11012.25	31.98	39.2	13.24	38.14	46.28	74	-27.72	Horizontal	

802.11g					CH11				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin Limit (dB)	Polarization	Test value
1203.199	36.97	24.43	4.53	36.52	29.41	74	-44.59	Vertical	Peak
1834.878	35.89	25.68	5.87	37.12	30.32	74	-43.68	Vertical	
3693.033	40.58	29.02	8.72	37.99	40.33	74	-33.67	Vertical	
4930.721	39.18	31.16	9.3	38.61	41.03	74	-32.97	Vertical	
8563.818	32.76	37.31	11.3	38.07	43.3	74	-30.7	Vertical	
11975.1	31.73	39.1	13.71	37.63	46.91	74	-27.09	Vertical	
1382.262	37.08	24.6	4.95	36.72	29.91	74	-44.09	Horizontal	
2144.825	35.51	26.66	6.41	37.38	31.2	74	-42.8	Horizontal	
3693.033	43.11	29.02	8.72	37.99	42.86	74	-31.14	Horizontal	
4495.125	39.26	30.9	8.98	38.33	40.81	74	-33.19	Horizontal	
7347.474	32.56	36.08	10.91	38.13	41.42	74	-32.58	Horizontal	
9258.909	33.44	38.01	11.84	38	45.29	74	-28.71	Horizontal	

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The peak level is lower than average limit (54 dBuV/m), this data is too weak instrument of signal is unable to test.
3. The emission levels of other frequencies are very lower than the limit and not show in test report.

802.11n(H20)					CH01				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin Limit (dB)	Polarization	Test value
1304.623	35.32	24.53	4.78	36.63	28	74	-46	Vertical	Peak
1711.909	36.17	25.34	5.63	37.03	30.11	74	-43.89	Vertical	
3693.033	42.14	29.02	8.72	37.99	41.89	74	-32.11	Vertical	
4831.962	36.71	31.1	9.22	38.55	38.48	74	-35.52	Vertical	
7966.832	31.16	36.68	11.23	38.25	40.82	74	-33.18	Vertical	
10423.8	32.18	38.65	12.81	38.14	45.5	74	-28.5	Vertical	
1084.295	37.1	24.3	4.23	36.37	29.26	74	-44.74	Horizontal	
1587.975	35.42	24.98	5.38	36.92	28.86	74	-45.14	Horizontal	
3693.033	41.69	29.02	8.72	37.99	41.44	74	-32.56	Horizontal	
4831.962	39.62	31.1	9.22	38.55	41.39	74	-32.61	Horizontal	
7305.122	32.07	36.05	10.89	38.12	40.89	74	-33.11	Horizontal	
10393.71	33.29	38.63	12.78	38.14	46.56	74	-27.44	Horizontal	

802.11n(H20)					CH06				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin Limit (dB)	Polarization	Test value
1168.92	37.56	24.39	4.45	36.47	29.93	74	-44.07	Vertical	Peak
2059.767	34.45	26.33	6.26	37.3	29.74	74	-44.26	Vertical	
3693.033	41.71	29.02	8.72	37.99	41.46	74	-32.54	Vertical	
4888.151	39.24	31.14	9.26	38.58	41.06	74	-32.94	Vertical	
7497.646	36	36.2	10.97	38.16	45.01	74	-28.99	Vertical	
11400.91	32.15	39.12	13.44	37.93	46.78	74	-27.22	Vertical	
1182.513	36.19	24.41	4.49	36.49	28.6	74	-45.4	Horizontal	
1592.571	34.94	24.99	5.39	36.92	28.4	74	-45.6	Horizontal	
3693.033	39.9	29.02	8.72	37.99	39.65	74	-34.35	Horizontal	
4888.151	41.66	31.14	9.26	38.58	43.48	74	-30.52	Horizontal	
6507.536	33.77	35.1	10.35	37.98	41.24	74	-32.76	Horizontal	
7584.833	32.15	36.29	11.01	38.18	41.27	74	-32.73	Horizontal	

802.11n(H20)					CH11				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin Limit (dB)	Polarization	Test value
1165.546	36.94	24.39	4.45	36.47	29.31	74	-44.69	Vertical	Peak
1741.856	34.98	25.43	5.68	37.05	29.04	74	-44.96	Vertical	
3299.344	37.09	28.62	8.56	37.99	36.28	74	-37.72	Vertical	
3693.033	41.1	29.02	8.72	37.99	40.85	74	-33.15	Vertical	
7035.727	31.68	35.83	10.78	38.07	40.22	74	-33.78	Vertical	
10545.01	31.8	38.73	12.91	38.14	45.3	74	-28.7	Vertical	
1293.359	35.56	24.52	4.75	36.62	28.21	74	-45.79	Horizontal	
1762.112	34.94	25.48	5.72	37.07	29.07	74	-44.93	Horizontal	
3693.033	39.9	29.02	8.72	37.99	39.65	74	-34.35	Horizontal	
4944.993	41.56	31.17	9.31	38.62	43.42	74	-30.58	Horizontal	
7541.114	32.38	36.25	11	38.17	41.46	74	-32.54	Horizontal	
10126.82	32.21	38.47	12.58	38.14	45.12	74	-28.88	Horizontal	

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The peak level is lower than average limit (54 dBuV/m), this data is too weak instrument of signal is unable to test.
3. The emission levels of other frequencies are very lower than the limit and not show in test report.

802.11n(H40)					CH03				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin Limit (dB)	Polarization	Test value
1044.309	36.48	24.25	4.12	36.31	28.54	74	-45.46	Vertical	Peak
1721.834	35.91	25.37	5.65	37.03	29.9	74	-44.1	Vertical	
3661.149	41.03	28.97	8.74	37.99	40.75	74	-33.25	Vertical	
5797.032	32.49	32.88	9.71	38.04	37.04	74	-36.96	Vertical	
8588.607	32.36	37.34	11.32	38.07	42.95	74	-31.05	Vertical	
12044.52	31.15	39.11	13.74	37.63	46.37	74	-27.63	Vertical	
1138.904	36.03	24.36	4.37	36.44	28.32	74	-45.68	Horizontal	
1736.829	35.33	25.41	5.68	37.05	29.37	74	-44.63	Horizontal	
3661.149	37.65	28.97	8.74	37.99	37.37	74	-36.63	Horizontal	
5615.62	32.33	32.59	9.66	38.17	36.41	74	-37.59	Horizontal	
8764.146	33.38	37.59	11.47	38.02	44.42	74	-29.58	Horizontal	
10980.47	31.75	39.17	13.21	38.14	45.99	74	-28.01	Horizontal	

802.11n(H40)					CH06				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin Limit (dB)	Polarization	Test value
1145.507	36.45	24.37	4.39	36.45	28.76	74	-45.24	Vertical	Peak
1547.199	36.4	24.85	5.29	36.88	29.66	74	-44.34	Vertical	
3661.149	39.69	28.97	8.74	37.99	39.41	74	-34.59	Vertical	
6267.553	31.57	34.22	10.07	37.95	37.91	74	-36.09	Vertical	
7476.006	31.87	36.18	10.96	38.15	40.86	74	-33.14	Vertical	
12044.52	30.95	39.11	13.74	37.63	46.17	74	-27.83	Vertical	
1227.791	36.4	24.45	4.6	36.55	28.9	74	-45.1	Horizontal	
1331.288	35.86	24.55	4.83	36.66	28.58	74	-45.42	Horizontal	
1840.189	35.3	25.69	5.87	37.13	29.73	74	-44.27	Horizontal	
3299.344	40.21	28.62	8.56	37.99	39.4	74	-34.6	Horizontal	
4888.151	38.73	31.14	9.26	38.58	40.55	74	-33.45	Horizontal	
9285.71	33.01	38.02	11.86	38.01	44.88	74	-29.12	Horizontal	

802.11n(H40)					CH09				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin Limit (dB)	Polarization	Test value
1172.303	35.5	24.4	4.46	36.48	27.88	74	-46.12	Vertical	Peak
1711.909	34.57	25.34	5.63	37.03	28.51	74	-45.49	Vertical	
3661.149	39.05	28.97	8.74	37.99	38.77	74	-35.23	Vertical	
6756.708	30.6	35.46	10.57	38.02	38.61	74	-35.39	Vertical	
8943.274	31.03	37.83	11.64	37.96	42.54	74	-31.46	Vertical	
11975.1	29.96	39.1	13.71	37.63	45.14	74	-28.86	Vertical	
1047.332	36.45	24.26	4.13	36.32	28.52	74	-45.48	Horizontal	
1751.955	35.87	25.46	5.7	37.06	29.97	74	-44.03	Horizontal	
3661.149	38.19	28.97	8.74	37.99	37.91	74	-36.09	Horizontal	
4930.721	39.6	31.16	9.3	38.61	41.45	74	-32.55	Horizontal	
7562.942	32.27	36.27	11.01	38.17	41.38	74	-32.62	Horizontal	
10854.25	32.57	39.04	13.14	38.14	46.61	74	-27.39	Horizontal	

Remark:


1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The peak level is lower than average limit (54 dBuV/m), this data is too weak instrument of signal is unable to test.
3. The emission levels of other frequencies are very lower than the limit and not show in test report.


6. Test Setup Photos of the EUT

Conducted Emission(AC Mains)




Radiated Emission









7. External and Internal Photos of the EUT


External photos





Internal photos





.....End of Report.....