

ELECTROMAGNETIC EMISSION COMPLIANCE REPORT FOR LOW-POWER, NON-LICENSED TRANSMITTER

Test Report No. : OT-199-RWD-044
AGR No. : A195A-069
Applicant : BBB Inc.
Address : 28, Yatap-ro, Bundang-gu, Seongnam-si, Gyeonggi-do, Republic of Korea
Manufacturer : BBB Inc.
Address : 28, Yatap-ro, Bundang-gu, Seongnam-si, Gyeonggi-do, Republic of Korea
Type of Equipment : Immunoassay Analyzer
FCC ID. : 2AKGP-MB100
Model Name : MB-100
Multiple Model Name : N/A
Serial number : N/A
Total page of Report : 9 pages (including this page)
Date of Incoming : May 13, 2019
Date of issue : September 24, 2019

SUMMARY

The equipment complies with the regulation; **FCC PART 15 SUBPART C Section 15.247**

This test report only contains the result of a single test of the sample supplied for the examination.

It is not a generally valid assessment of the features of the respective products of the mass-production.

Reviewed by:


Ha-Ram Lee / Assistant Manager
ONETECH Corp.

Approved by:


Jae-Ho Lee / Chief Engineer
ONETECH Corp.

CONTENTS

	PAGE
1. VERIFICATION OF COMPLIANCE	4
2. GENERAL INFORMATION	5
2.1 PRODUCT DESCRIPTION	5
2.2 ALTERNATIVE TYPE(S)/MODEL(S); ALSO COVERED BY THIS TEST REPORT	6
3. EUT MODIFICATIONS	6
4. RF EXPOSURE EVALUATION	7
4.1 RF EXPOSURE CALCULATION	7
4.2 EUT DESCRIPTION	7
4.3 TEST RESULT OF SAR EXCLUSION FOR DEVICES	8
4.4 CALCULATION RESULT OF SIMULTANEOUS RF POWER	9

Revision History

Rev. No.	Issue Report No.	Issued Date	Revisions	Section Affected
0	OT-199-RWD-044	September 24, 2019	Initial Issue	All

1. VERIFICATION OF COMPLIANCE

Applicant : BBB Inc.
Address : 28, Yatap-ro, Bundang-gu, Seongnam-si, Gyeonggi-do, Republic of Korea
Contact Person : Jaekyu Choi / CEO
Telephone No. : +82-2-565-9653
FCC ID : 2AKGP-MB100
Model Name : MB-100
Brand Name : markB Analyzer
Serial Number : N/A
Date : September 24, 2019

EQUIPMENT CLASS	DTS – DIGITAL TRANSMISSION SYSTEM
E.U.T. DESCRIPTION	Immunoassay Analyzer
THIS REPORT CONCERNS	Original Grant
MEASUREMENT PROCEDURES	ANSI C63.10: 2013
TYPE OF EQUIPMENT TESTED	Pre-Production
KIND OF EQUIPMENT	Certification
AUTHORIZATION REQUESTED	
EQUIPMENT WILL BE OPERATED UNDER FCC RULES PART(S)	FCC PART 15 SUBPART C Section 15.247
Modifications on the Equipment to Achieve Compliance	None
Final Test was Conducted On	3 m, Semi Anechoic Chamber

- The above equipment was tested by ONETECH Corp. for compliance with the requirement set forth in the FCC Rules and Regulations. This said equipment in the configuration described in this report, shows the maximum emission levels emanating from equipment are within the compliance requirements.

2. GENERAL INFORMATION

2.1 Product Description

The BBB Inc., Model MB-100 (referred to as the EUT in this report) is an Immunoassay Analyzer. The product specification described herein was obtained from product data sheet or user's manual.

Device Type	Immunoassay Analyzer	
Operating Frequency	Bluetooth LE	2 402 MHz ~ 2 480 MHz
	WLAN	2 412 MHz ~ 2 462 MHz (802.11b/g/n(HT20))
	2.4 GHz Band	2 422 MHz ~ 2 452 MHz (802.11n(HT40))
	NFC	13.56 MHz
RF Output Power	Bluetooth LE	-6.78 dBm
	WLAN	802.11b (13.13 dBm) 802.11g (10.67 dBm)
	2.4 GHz Band	802.11n(HT20) (11.01 dBm) 802.11n(HT40) (10.81 dBm)
Number of Channel	Bluetooth LE	40 Channels
	WLAN	11 Channels
	2.4 GHz Band	
Modulation Type	NFC	1 Channel
	Bluetooth LE	DSSS Modulation(GFSK)
	WLAN	DSSS Modulation(DBPSK/DQPSK/CCK) OFDM Modulation(BPSK/QPSK/16QAM/64QAM)
	2.4 GHz Band	
Antenna Type	NFC	ASK
	Bluetooth LE	FPC Antenna
	WLAN	
Antenna Gain	2.4 GHz Band	
	NFC	PCB Antenna
List of each Osc. or crystal Freq.(Freq. >= 1 MHz)	Bluetooth LE	1.74 dBi
	WLAN	
	2.4 GHz Band	
Rated Supply Voltage	DC 3.8 V	

Note: Bluetooth and WLAN do not operate simultaneously.

2.2 Alternative type(s)/model(s); also covered by this test report.

- None

3. EUT MODIFICATIONS

- None

4. RF Exposure Evaluation

4.1 RF Exposure Calculation

According to 1.1307 (b)(1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

7.5 - the limit for extremity is being used. Extremity limit is being used since the device has a touch pad and not a handheld device.

4.2 EUT Description

Kind of EUT	Immunoassay Analyzer	
Operating Frequency Band	<input type="checkbox"/> Wireless Microphone: 494.000 MHz ~ 501.000 MHz and 498.200 MHz ~ 505.200 MHz <input checked="" type="checkbox"/> WLAN: 2 412 MHz ~ 2 462 MHz <input checked="" type="checkbox"/> WLAN: 2 422 MHz ~ 2 452 MHz <input type="checkbox"/> WLAN: 5 180 MHz ~ 5 240 MHz <input type="checkbox"/> WLAN: 5 745 MHz ~ 5 825 MHz <input type="checkbox"/> Bluetooth: 2 402 MHz ~ 2 480 MHz <input checked="" type="checkbox"/> Bluetooth BLE: 2 402 MHz ~ 2 480 MHz <input checked="" type="checkbox"/> NFC : 13.56 MHz	
MAX. RF OUTPUT POWER	Bluetooth LE	-6.78 dBm
Antenna Gain	1.74 dBi	
Exposure Evaluation Applied	<input type="checkbox"/> MPE <input type="checkbox"/> SAR <input checked="" type="checkbox"/> SAR Test Exclusion Evaluation	


4.3 Test Result of SAR Exclusion for Devices

According to the procedure, KDB 447498 D01, the standalone SAR test exclusion threshold is

$$[(\text{Max. Power of channel, including tune-up tolerance, mW}) / (\text{Min. test separation distance, mm})] \times [\sqrt{f(\text{GHz})}] < 7.5$$
$$= (8.89/5) \times \sqrt{2.42} = 2.78$$

Conclusion: The SAR test exclusion threshold is less than 7.5, so the device meets the RF Exposure Requirement and excluded SAR Test.

Mode	Frequency (MHz)	Target Power W/tolerance (dBm)	Max tune up power (dBm)	Max tune up power (mW)	Separation distance (mm)	RF exposure
BLE	2 402	-6.78 ± 0.5	-6.28	0.24	5	0.07



Tested by: Yu-Seog, Sim / Assistant Manager

4.4 Calculation Result of Simultaneous RF Power

Bluetooth transmit simultaneously with NFC.

Simultaneous RF Power = Power of BLE(Worst Case) + EIRP of NFC

0.24 + 0.000 000 010 9 = 0.240 000 010 9 mW

[(Simultaneous RF Power, mW)/(Mim. test separation distance, mm)] X [$\sqrt{f(\text{GHz})}$] < 7.5

= (0.240 000 010 9 /5) X $\sqrt{2.402}$ = 0.07

- Therefore the maximum calculations of above situations are less than the "7.5" limit.

Note 1. Power of BLE(Worst Case) = 0.24 mW

Note 2. EIRP of NFC = $E (\text{dB}\mu\text{V/m}) + 20 \log D - 104.8$; where D is the measurement distance in meters.

= 15.64 $\text{dB}\mu\text{V/m} + 20\log(3) - 104.8$

= -79.62 dBm

= 0.000 000 010 9 mW



Tested by: Yu-Seog, Sim / Assistant Manager