

EXHIBIT C - RF EXPOSURE EVALUATION

Applicable Standard

According to subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500	/	/	f/1500	30
1500–100,000	/	/	1.0	30

f = frequency in MHz; * = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

Calculation formula:

Prediction of power density at the distance of the applicable MPE limit

$S = PG/4\pi R^2$ = power density (in appropriate units, e.g. mW/cm²);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

Calculated Data:

Radio	Operation Modes	Frequency (MHz)	Antenna Gain		Conducted output power including Tune-up Tolerance [▲]		Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)
			(dBi)	(numeric)	(dBm)	(mW)			
WLAN/ BT Module	BT	2402-2480	0.73	1.18	6	3.98	20.00	0.001	1.0
	BLE	2402-2480	0.73	1.18	6	3.98	20.00	0.001	1.0
	WiFi 2.4G	2412-2462	0.73	1.18	20	100.00	20.00	0.024	1.0
	WiFi 5G (UNII-1)	5150-5250	1.14	1.30	19	79.43	20.00	0.021	1.0
	WiFi 5G (UNII-2A)	5250-5350	1.00	1.26	19	79.43	20.00	0.020	1.0
	WiFi 5G (UNII-2C)	5470-5725	0.6	1.15	19	79.43	20.00	0.018	1.0
	WiFi 5G (UNII-3)	5725-5850	0.95	1.24	19	79.43	20.00	0.020	1.0
WWAN Module	WCDMA Band II	1850-1910	3.5	2.24	25	316.23	20.00	0.141	1.0
	WCDMA Band IV	1710-1755	-2.8	0.52	25	316.23	20.00	0.033	1.0
	WCDMA Band V	824-849	-3.5	0.45	25	316.23	20.00	0.028	0.55
	LTE Band 2	1850-1910	3.5	2.24	25	316.23	20.00	0.141	1.0
	LTE Band 4	1710-1755	-2.8	0.52	25	316.23	20.00	0.033	1.0
	LTE Band 5	824-849	-3.5	0.45	25	316.23	20.00	0.028	0.55
	LTE Band 12	699-716	-4.1	0.39	25	316.23	20.00	0.024	0.47
	LTE Band 13	777-787	-3.5	0.45	25	316.23	20.00	0.028	0.52
	LTE Band 14	788-798	-3.5	0.45	25	316.23	20.00	0.026	0.53
	LTE Band 66	1710-1780	-2.8	0.52	25	316.23	20.00	0.033	1.0
	LTE Band 71	663-698	-3.9	0.41	25	316.23	20.00	0.026	0.44
NFC	NFC	13.56	/	/	-15.4	0.029	20.00	<<0.001	0.98
Note: The device built in a certified WLAN(BT/WiFi) module, FCC ID: XMR2023FCS960K. The device built in a certified WWAN module, FCC ID: XMR202008EC25AFXD.									

Note:

1. The Conducted output power including Tune-up Tolerance provided by manufacturer

2. EIRP(dBm)=E(dBuV/m)-95.2 for 3 meters distance

NFC E Field = 79.8dBuV/m@3m

==> EIRP= -15.4dBm

Simultaneous transmission:

BT and WiFi can't transmit [simultaneously](#), WiFi/BT, WWAN Module and NFC can transmit [simultaneously](#):

$$\sum_i \frac{S_i}{S_{Limit,i}} \leq 1$$

$$S_{WiFi}/S_{limit-WiFi} + S_{WWAN}/S_{limit-WWAN} + S_{NFC}/S_{limit-NFC}$$

$$= 0.024/1.0 + 0.141/1.0 + 0.001/0.98$$

$$= 0.166$$

$$< 1.0$$

Result: Compliant. The device compliant RF Exposure at 20cm distances.

******* END OF REPORT *******