

# FCC RF Exposure Evaluation

Report Number:

**F240384E6**

Equipment under Test (EUT):

**Two Wire Transmitter  
Liquiline CM42B**

Applicant:

**Endress+Hauser Conducta GmbH+Co.KG**

Manufacturer:

**Endress+Hauser Conducta GmbH+Co.KG**



Deutsche  
Akkreditierungsstelle  
D-PL-17186-01-00

## References

- [1] **CFR 47 Rule part 1** Practice and Procedure
- [2] **CFR 47 Rule part 2** Frequency Allocations and Radio Treaty Matters; General Rules and Regulations
- [3] **KDB 447498 D04 Interim General RF Exposure Guidance v01**

Assessed and  
written by:

Signature

Reviewed and  
approved by:

Signature

**This test report is only valid in its original form.**

Any reproduction of its contents in extracts without written permission of the accredited test laboratory PHOENIX TESTLAB GmbH is prohibited.

The test results herein refer only to the tested sample. PHOENIX TESTLAB GmbH is not responsible for any generalisations or conclusions drawn from these test results concerning further samples. Any modification of the tested samples is prohibited and leads to the invalidity of this test report. Each page necessarily contains the PHOENIX TESTLAB Logo and the TEST REPORT NUMBER.

| <b>Contents:</b>                                                            | <b>Page</b> |
|-----------------------------------------------------------------------------|-------------|
| 1 Identification .....                                                      | 4           |
| 1.1 Applicant.....                                                          | 4           |
| 1.2 Manufacturer .....                                                      | 4           |
| 1.3 Test Laboratory .....                                                   | 4           |
| 1.4 EUT (Equipment under Test) .....                                        | 5           |
| 1.5 Technical Data of Equipment .....                                       | 5           |
| 2 Evaluation methods .....                                                  | 7           |
| 2.1 RF exposure test exemptions for single sources .....                    | 7           |
| 2.2 RF exposure test exemptions for simultaneous transmission sources ..... | 9           |
| 3 Results of evaluation.....                                                | 11          |
| 3.1 Used evaluation methods.....                                            | 11          |
| 3.2 Evaluation Distance.....                                                | 11          |
| 3.3 BLE 2.4 GHz emissions .....                                             | 12          |
| 4 Conclusion.....                                                           | 12          |
| 5 Report History.....                                                       | 12          |

# 1 Identification

## 1.1 Applicant

|                                                                |                                     |
|----------------------------------------------------------------|-------------------------------------|
| Name:                                                          | Endress+Hauser Conducta GmbH+Co. KG |
| Address:                                                       | Dieselstrasse 24, 70839 Gerlingen   |
| Country:                                                       | Germany                             |
| Name for contact purposes:                                     | Mr. Henryk HOFMANN                  |
| Phone:                                                         | +49 7156 209 10211                  |
| eMail address:                                                 | henryk.hofmann@endress.com          |
| Applicant represented during the test by the following person: | -                                   |

## 1.2 Manufacturer

|                                                                   |                                     |
|-------------------------------------------------------------------|-------------------------------------|
| Name:                                                             | Endress+Hauser Conducta GmbH+Co. KG |
| Address:                                                          | Dieselstrasse 24, 70839 Gerlingen   |
| Country:                                                          | Germany                             |
| Name for contact purposes:                                        | Mr. Henryk HOFMANN                  |
| Phone:                                                            | +49 7156 209 10211                  |
| eMail address:                                                    | henryk.hofmann@endress.com          |
| Manufacturer represented during the test by the following person: | -                                   |

## 1.3 Test Laboratory

The tests were carried out by: **PHOENIX TESTLAB GmbH**  
**Königswinkel 10**  
**32825 Blomberg**  
**Germany**

accredited by Deutsche Akkreditierungsstelle GmbH (DAkkS) according to DIN EN ISO/IEC 17025:2018. The accreditation is only valid for the scope of accreditation listed in the annex of the certificate D-PL-17186-01-00. FCC Test Firm Designation Number DE0004, FCC Test Firm Registration Number 469623, CAB Identifier DE0003 and ISED# 3469A.

## 1.4 EUT (Equipment under Test)

|                            |                                                                   |
|----------------------------|-------------------------------------------------------------------|
| Test object: *             | Two Wire Transmitter                                              |
| Model name: *              | Liquiline CM42B                                                   |
| Model number: *            | CM42B                                                             |
| Order number: *            | CM42B                                                             |
| FCC ID: *                  | 2AKGY-CM42B<br>(FCC company number 2AKGY, Product number: -CM42B) |
| IC certification number: * | 22173-CM42B<br>(IC company number: 22173, Product number: CM42B)  |
| PMN: *                     | CM42B                                                             |
| HVIN: *                    | CM42B                                                             |
| FVIN: *                    | SoftDevice S132 Version: 7.2.0                                    |

\* Declared by the applicant

|                     |         | EUT number                        |   |
|---------------------|---------|-----------------------------------|---|
|                     |         | 1                                 | 2 |
| Serial number: *    |         | WB000805G00                       | - |
| PCB identifier: *   | Board 1 | VXCM1                             | - |
|                     | Board 2 | VICO1                             | - |
|                     | Board 3 | VD2W1                             | - |
| Hardware version: * | Board 1 | Vx.04.xx                          |   |
|                     | Board 2 | Vx.03.xx                          |   |
|                     | Board 3 | Vx.04.xx                          |   |
| Software version: * |         | SoftDevice S132<br>Version: 7.2.0 | - |

\* Declared by the applicant

## 1.5 Technical Data of Equipment

| General EUT data                     |                               |                               |                               |
|--------------------------------------|-------------------------------|-------------------------------|-------------------------------|
| Power supply EUT: *                  | DC                            |                               |                               |
| Supply voltage EUT: *                | $U_{nom} = 24 \text{ V}_{DC}$ | $U_{min} = 17 \text{ V}_{DC}$ | $U_{max} = 30 \text{ V}_{DC}$ |
| Temperature range: *                 | -30 °C to +70 °C              |                               |                               |
| Lowest / highest internal frequency: | 32 kHz * / 2480 MHz           |                               |                               |

\* Declared by the applicant

| Bluetooth® low energy frequencies |          |            |          |
|-----------------------------------|----------|------------|----------|
| Channel 00                        | 2402 MHz | Channel 01 | 2404 MHz |
| Channel 02                        | 2406 MHz | Channel 03 | 2408 MHz |
| ...                               | ...      | ...        | ...      |
| ...                               | ...      | ...        | ...      |
| Channel 18                        | 2438 MHz | Channel 19 | 2440 MHz |
| ...                               | ...      | ...        | ...      |
| ...                               | ...      | ...        | ...      |
| Channel 36                        | 2474 MHz | Channel 37 | 2476 MHz |
| Channel 38                        | 2478 MHz | Channel 39 | 2480 MHz |

| Bluetooth® low energy radio mode |                                                                      |
|----------------------------------|----------------------------------------------------------------------|
| Fulfil radio specification: *1   | Bluetooth® low energy (BLE) 5.4                                      |
| Radio chip: *1                   | Nordic nRF 52832                                                     |
| Antenna type: *1                 | PCB Trace Antenna                                                    |
| Antenna name: *1                 | Folded lambda / 4 monopole                                           |
| Antenna gain: *2                 | -1.5 dBi                                                             |
| Antenna connector: *1            | -                                                                    |
| Supply voltage radio module: *1  | $U_{nom} = 3.0 V_{DC}$ $U_{min} = 1.7 V_{DC}$ $U_{max} = 3.5 V_{DC}$ |
| Type of modulation: *1           | BLE (1 Mbps PHY)      GFSK                                           |
| Operating frequency range: *1    | BLE (1 Mbps PHY)      2402 – 2480 MHz                                |
| Number of channels: *1           | BLE (1 Mbps PHY)      40 (2 MHz channel spacing)                     |

\*1 declared by the applicant

\*2 based on the antenna test report F240384E8 by PHOENIX TESTLAB GmbH

## 2 Evaluation methods

### 2.1 RF exposure test exemptions for single sources

#### 2.1.1 General exemption CFR 47 §1.1307(b)(3)(i)(A)

The available maximum time-averaged power is no more than 1 mW, regardless of separation distance. This exemption may not be used in conjunction with other exemption criteria other than those in paragraph (b)(3)(ii)(A) of this section. Medical implant devices may only use this exemption and that in paragraph (b)(3)(ii)(A);

#### 2.1.2 SAR based exemption CFR 47 §1.1307(b)(3)(i)(B)

The available maximum time-averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold  $P_{th}$  (mW) described in the following formula. This method shall only be used at separation distances (cm) from 0.5 cm to 40 cm and at frequencies from 0.3 GHz to 6 GHz inclusive.

For the following separation distances [d] and frequency ranges  $P_{th}$  is given by the following formulas:

|                             | 0.5 cm $\leq d \leq 20$ cm                                                                                                                       | 20 cm $< d \leq 40$ cm                              |
|-----------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------|
| 0.2 GHz $\leq f < 1.5$ GHz  | $P_{th}(mW) = ERP_{20cm} \left( \frac{d}{20} \right)^x$ $ERP_{20cm} (mW) = 2040f$ $x = -\log_{10} \left( \frac{60}{ERP_{20cm} \sqrt{f}} \right)$ | $P_{th}(mW) = ERP_{20cm}$ $ERP_{20cm} (mW) = 2040f$ |
| 1.5 GHz $\leq f \leq 6$ GHz | $P_{th}(mW) = ERP_{20cm} \left( \frac{d}{20} \right)^x$ $ERP_{20cm} (mW) = 3060$ $x = -\log_{10} \left( \frac{60}{ERP_{20cm} \sqrt{f}} \right)$  | $P_{th}(mW) = ERP_{20cm}$ $ERP_{20cm} (mW) = 3060$  |

#### 2.1.3 MPE based exemption CFR 47 §1.1307(b)(3)(i)(C)

By using Table 1 and the minimum separation distance (d in meters) from the body of a nearby person for the frequency (f in MHz) at which the source operates, the ERP (watts) is no more than the calculated value prescribed for that frequency. For the exemption in Table 1 to apply, d must be at least  $\lambda/2\pi$ , where  $\lambda$  is the free-space operating wavelength in meters. If the ERP of a single RF source is not easily obtained, then the available maximum time-averaged power may be used in lieu of ERP if the physical dimensions of the radiating structure(s) do not exceed the electrical length of  $\lambda/4$  or if the antenna gain is less than that of a half-wave dipole (1.64 linear value).

| RF Source frequency [MHz] | Threshold ERP [W] |
|---------------------------|-------------------|
| 0.3 - 1.34                | $1920 d^2$        |
| 1.34 - 30                 | $3450 d^2/f^2$    |
| 30 - 300                  | $3.83 d^2$        |
| 300 - 1500                | $0.0128 d^2/f$    |
| 1500 - 100000             | $19.2 d^2$        |

d: Minimal separation distance from antenna to the user

#### 2.1.4 Standalone MPE evaluation limits

The human exposure to RF emissions from such devices could be evaluated based on the MPE limits adopted by the FCC for electric and magnetic field strength and / or power density. The limits for General Population / Uncontrolled Exposure are given in the following table from CFR 47 §1.1310(e)1:

| Frequency range<br>[MHz]                                  | Electric field<br>strength (E)<br>[V/m] | Magnetic field<br>strength (H)<br>[A/m] | Power density (S)<br>[mW/cm <sup>2</sup> ] | Averaging time<br>[min] |
|-----------------------------------------------------------|-----------------------------------------|-----------------------------------------|--------------------------------------------|-------------------------|
| (i)Limits for Occupational/Controlled Exposure            |                                         |                                         |                                            |                         |
| 0.3 – 3.0                                                 | 614                                     | 1.63                                    | *(100)                                     | ≤6                      |
| 3.0 – 30                                                  | 1842/f                                  | 4.89/f                                  | *(900/f <sup>2</sup> )                     | <6                      |
| 30 – 300                                                  | 61.4                                    | 0.163                                   | 1.0                                        | <6                      |
| 300 – 1,500                                               |                                         |                                         | f/300                                      | <6                      |
| 1,500 – 100,000                                           |                                         |                                         | 5                                          | <6                      |
| (ii)Limits for General Population / Uncontrolled Exposure |                                         |                                         |                                            |                         |
| 0.3 – 1.34                                                | 614                                     | 1.63                                    | *(100)                                     | < 30                    |
| 1.34 – 30                                                 | 824/f                                   | 2.19/f                                  | *(180/f <sup>2</sup> )                     | < 30                    |
| 30 – 300                                                  | 27.5                                    | 0.073                                   | 0.2                                        | < 30                    |
| 300 – 1500                                                |                                         |                                         | f/1500                                     | < 30                    |
| 1500 – 100,000                                            |                                         |                                         | 1.0                                        | < 30                    |

Note: f = frequency in MHz; \* Plane – wave equivalent power density

The power density is calculated as follows:

$$S = \frac{P \cdot G \cdot D}{4 \cdot \pi \cdot d^2}$$

Where:

P: conducted power

G: Antenna gain (linear)

D: Duty Cycle

d: Minimal separation distance from antenna to the user



## 2.2 RF exposure test exemptions for simultaneous transmission sources

### 2.2.1 1 mW Test Exemption for simultaneous transmission sources

As discussed in CFR 47 §1.1307(b)(3)(ii)(A) [1] the 1 mW exemption intended for single transmitters may be also applied to simultaneous transmission conditions, within the same host device, according one of the following criteria:

- When the maximum available power each individual transmitting antenna with the same time averaging period is  $\leq 1$  mW, and the nearest parts of the antenna structures of the simultaneously operating transmitters are separated by at least 2 cm
- When the aggregate maximum available power of all transmitting antennas is  $\leq 1$  mW in the same time-averaging period

This exemption may not be combined with any other exemption.

### 2.2.2 Simultaneous transmission SAR based and MPE based test exemptions

Although this is not a module integration in the sense of product approval, the procedure for simultaneous transmission specified in KDB 447498 D04 Interim General RF Exposure Guidance v01 [3] in chapter 2.2 was taken into account:

According to the RF exposure KDB 447498 D04 General RF Exposure Guidance v01 [3] in chapter 2.2.2: This case is described in detail in CFR 47 §1.1307(b)(3)(ii)(B) and covers the situations where both SAR-based and MPE-based exemption may be considered for test exemption in fixed, mobile, or portable device exposure conditions. For these cases, a device with multiple RF sources transmitting simultaneously will be considered an RF exempt device if the condition of the following formula is satisfied.

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k} \leq 1$$

For these test exemptions to apply, the maximum output power, duty factor, and other applicable parameters used in the standalone ERP determination tests, must be the same, or corresponding to a more conservative choice, than those required for simultaneous transmission.

Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneously transmitting antennas incorporated in a host device is  $\leq 1.0$ , according to calculated/estimated, numerically modelled, or measured field strengths or power density. The MPE ratio of each antenna is determined at the minimum test separation distance required by the operating configurations and exposure conditions of the host device, according to the ratio of field strengths or power density to the MPE limit at the test frequency.

### 2.2.3 Test exemption based on the SAR to Peak Location Separation Ratio

When the ERP-based condition in the previous section does not apply, a test exemption may be still applicable based on the SAR to peak location separation ratio (SPLSR) procedure.

In this case, the simultaneously transmitting antennas in each operating mode and exposure condition combination must be considered one pair at a time to determine the SPLSR that qualifies for the additional test exemption.

This ratio is defined as:

$$SPLSR = (SAR_1 + SAR_2)^{\frac{1.5}{R_i}}$$

Where:  $SAR_1$  and  $SAR_2$  = highest reported SAR or estimated SAR values for the two sources in the pair  $i$ , and  $R_i$  is their distance in mm.

When  $SPLSR \leq 0.0.4$  (rounded to two decimal digits), for all antenna pairs in the configuration, then the device qualifies for 1 g SAR test exemption.

When 10 g SAR applies (e.g. for extremities) the corresponding test exemption condition is  $SPLSR \leq 0.10$ .

If any antenna pair does not qualify for simultaneous transmission SAR test exemption, then the device must be tested for SAR compliance, according to the enlarged zoom scan and volume scan post-processing procedures in KDB Pub. 865664 D01.

### 3 Results of evaluation

#### 3.1 Used evaluation methods

| RF Exposure test exemptions for single sources |                                                     |                |         |
|------------------------------------------------|-----------------------------------------------------|----------------|---------|
| Used                                           | Method                                              | See sub-clause | Comment |
| <input type="checkbox"/>                       | General exemption acc. CFR 47 §1.1307(b)(3)(i)(A)   | 2.1.1          | -       |
| <input type="checkbox"/>                       | SAR based exemption acc. CFR 47 §1.1307(b)(3)(i)(B) | 2.1.2          | -       |
| <input checked="" type="checkbox"/>            | MPE based exemption acc. CFR 47 §1.1307(b)(3)(i)(C) | 2.1.3          | -       |
| <input type="checkbox"/>                       | MPE calculation                                     | 2.1.4          | -       |

| RF Exposure test exemptions for simultaneous transmission sources |                                                      |                |                                       |
|-------------------------------------------------------------------|------------------------------------------------------|----------------|---------------------------------------|
| Used                                                              | Method                                               | See sub-clause | Comment                               |
| <input checked="" type="checkbox"/>                               | Not applicable                                       | -              | No simultaneous transmission possible |
| <input type="checkbox"/>                                          | 1 mW test exemption acc. 2.2.1 [3]                   | 2.2.1          | -                                     |
| <input type="checkbox"/>                                          | SAR based exemption acc. 2.2.2 [3]                   | 2.2.2          | -                                     |
| <input type="checkbox"/>                                          | MPE based exemption acc. 2.2.2 [3]                   | 2.2.2          | -                                     |
| <input type="checkbox"/>                                          | SAR to Peak location separation ratio acc. 2.2.3 [3] | 2.2.3          | -                                     |

#### 3.2 Evaluation Distance

According to the CFR47 §2.1091 the device as declared by the applicant is mounted in such a way, that the following separation distance between the device and the users normally is maintained:

| Antenna   | Min separation distance as declared by the applicant |
|-----------|------------------------------------------------------|
| Antenna 1 | 20 cm                                                |

### 3.3 BLE 2.4 GHz emissions

The following information are based on the test-report F240384E4 by PHOENIX TESTLAB GmbH.

#### MPE Based Exemption CFR 47 §1.1307(b)(3)(i)(C)

| $P_{con}^{*1}$<br>[dBm] | $P_{con}^{*1}$<br>[mW] | Antenna<br>gain $^{*2}$<br>[dBi] | Cable<br>attenuation<br>[dB] | $P_{e.i.r.p}$<br>[dBm] | $P_{e.i.r.p}$<br>[mW] | $P_{e.r.p}$<br>[dBm] | $P_{e.r.p}$<br>[mW] |
|-------------------------|------------------------|----------------------------------|------------------------------|------------------------|-----------------------|----------------------|---------------------|
| 7.1                     | 5.13                   | -1.5                             | 0                            | 5.6                    | 3.63                  | 3.45                 | 2.21                |

\*1 Maximum output power including tune up range as declared by the applicant

\*2 The antenna gain was calculated according to antenna report F240384E8 by PHOENIX TESTLAB GmbH

| Frequency<br>[GHz] | Wavelength $\lambda$<br>[cm] | $\lambda/2\pi$<br>[cm] | d<br>[cm] | d > $\lambda/2\pi$ |
|--------------------|------------------------------|------------------------|-----------|--------------------|
| 2.440              | 12.29                        | 1.96                   | 20        | <b>fulfilled</b>   |

| Frequency [MHz] | d<br>[cm] | Threshold ERP<br>[mW] | $P_{e.r.p.}$<br>[mW] | Result          |
|-----------------|-----------|-----------------------|----------------------|-----------------|
| 2440            | 20        | <b>768</b>            | <b>2.21</b>          | <b>exempted</b> |

The separation distance d is larger than the wavelength divided by  $2\pi$ . Therefore, the MPE Exemption could be used.

Due to the fact that for separation distances larger than d the value for  $P_{e.r.p}$  is lower than the threshold ERP this emission is exempted from SAR Evaluation

## 4 Conclusion

The EUT complies in all operational modes to the limits given in CFR 47 §1.1310(e)1 in a separation distance of 20 cm.

## 5 Report History

| Report Number | Date       | Comment             |
|---------------|------------|---------------------|
| F240384E6     | 10.02.2025 | Initial Test Report |
| -             | -          | -                   |
| -             | -          | -                   |

--- end of test report ---