

FCC REPORT

Applicant: DONGGUAN EPROPULSION INTELLIGENCE TECHNOLOGY LIMITED

Address of Applicant: Room 202, Bldg. 17A, Headquater NO.1, 4th Xinzhu Rd, Songshan Lake District, Dongguan City China

Equipment Under Test (EUT)

Product Name: LAGOON

Model No.: LAGOON, LAGOONS

Trade Mark: EPROPULSION

FCC ID: 2AKHE-LAGOON

Applicable standards: FCC CFR Title 47 Part 15 Subpart C Section 15.249:2015

Date of sample receipt: December 01, 2016

Date of Test: December 02-08, 2016

Date of report issued: December 09, 2016

Test Result : PASS *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



The image shows a circular logo for GTS Global Testing Services Co., Ltd. with the text 'GTS GLOBAL TESTING SERVICES CO., LTD.' around the perimeter. Overlaid on the logo is a handwritten signature in black ink, which appears to be 'Robinson Lo'.

Robinson Lo

Laboratory Manager

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product and does not permit the use of the GTS product certification mark. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of GTS or testing done by GTS in connection with, distribution or use of the product described in this report must be approved by GTS in writing.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

2 Version

Version No.	Date	Description
00	December 09, 2016	Original

Prepared By: Yang Liu **Date:** December 09, 2016
Project Engineer

Check By: Andy Wu **Date:** December 09, 2016
Reviewer

3 Contents

	Page
1 COVER PAGE.....	1
2 VERSION.....	2
3 CONTENTS	3
4 TEST SUMMARY	4
4.1 MEASUREMENT UNCERTAINTY	4
5 GENERAL INFORMATION.....	5
5.1 CLIENT INFORMATION	5
5.2 GENERAL DESCRIPTION OF EUT	5
5.3 TEST MODE	7
5.4 DESCRIPTION OF SUPPORT UNITS	7
5.5 TEST FACILITY.....	7
5.6 TEST LOCATION	7
5.7 OTHER INFORMATION REQUESTED BY THE CUSTOMER	7
6 TEST INSTRUMENTS LIST	8
7 TEST RESULTS AND MEASUREMENT DATA.....	9
7.1 ANTENNA REQUIREMENT	9
7.2 RADIATED EMISSION METHOD.....	10
7.2.1 <i>Field Strength of The Fundamental Signal</i>	12
7.2.2 <i>Spurious emissions</i>	13
7.2.3 <i>Bandedge emissions</i>	17
7.3 20dB OCCUPY BANDWIDTH.....	18
8 TEST SETUP PHOTO	20
9 EUT CONSTRUCTIONAL DETAILS	21

4 Test Summary

Test Item	Section in CFR 47	Result
Antenna requirement	15.203	Pass
AC Power Line Conducted Emission	15.207	N/A
Field strength of the fundamental signal	15.249 (a)	Pass
Spurious emissions	15.249 (a) (d)/15.209	Pass
Band edge	15.249 (d)/15.205	Pass
20dB Occupied Bandwidth	15.215 (c)	Pass

Pass: The EUT complies with the essential requirements in the standard.

Remark : Test according to ANSI C63.4:2014 and ANSI C63.10:2013.

4.1 Measurement Uncertainty

Test Item	Frequency Range	Measurement Uncertainty	Notes
Radiated Emission	9kHz ~ 30MHz	± 4.34dB	(1)
Radiated Emission	30MHz ~ 1000MHz	± 4.24dB	(1)
Radiated Emission	1GHz ~ 26.5GHz	± 4.68dB	(1)
AC Power Line Conducted Emission	0.15MHz ~ 30MHz	± 3.45dB	(1)

Note (1): The measurement uncertainty is for coverage factor of k=2 and a level of confidence of 95%.

5 General Information

5.1 Client Information

Applicant:	DONGGUAN EPROPULSION INTELLIGENCE TECHNOLOGY LIMITED
Address of Applicant:	Room 202, Bldg. 17A, Headquater NO.1, 4th Xinzhu Rd, Songshan Lake District, Dongguan City China

5.2 General Description of EUT

Product Name:	LAGOON
Model No.:	LAGOON, LAGOONS
Operation Frequency:	2402MHz~2477MHz
Channel numbers:	76
Channel separation:	1MHz
Modulation type:	GFSK
Antenna Type:	PCB antenna
Antenna gain:	0.8 dBi(declare by Applicant)
Power supply:	DC 3.0V, "CR 2032" Lithium Battery

Remark: The system works in the frequency range of 2402MHz to 2477MHz. This band has been divided to 76 independent channels. Each radio system uses 3 different channels, the minimum channel separation is ≥ 1 MHz. By using various switch-on times, hopping scheme and channel frequencies, the system can guarantee a jamming free radio transmission. The channel list is below.

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2402MHz	20	2421MHz	40	2443MHz	60	2461MHz
2	2403MHz	21	2422MHz	41	2444MHz	61	2462MHz
⋮	⋮	⋮	⋮	⋮	⋮	⋮	⋮
18	2419MHz	38	2441MHz	58	2459MHz	76	2477MHz
19	2420MHz	39	2442MHz	59	2460MHz		

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency
The lowest channel	2402MHz
The middle channel	2442MHz
The highest channel	2477MHz

5.3 Test mode

Transmitting mode	Keep the EUT in continuously transmitting mode
<i>Remark: During the test, the duty cycle >98%, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. New battery is used during all test.</i>	

Pre-test mode:

We have verified the construction and function in typical operation, The EUT was placed on three different polar directions; i.e. X axis, Y axis, Z axis. which was shown in this test report and defined as follows:

Axis	X	Y	Z
Field Strength(dBuV/m)	88.90	89.12	88.89

Final Test Mode:

According to ANSI C63.4 standards, the test results are both the “worst case” and “worst setup”:
Y axis (see the test setup photo)

5.4 Description of Support Units

None.

5.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **FCC —Registration No.: 600491**

Global United Technology Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in files. Registration 600491, June 22, 2016.

- **Industry Canada (IC) —Registration No.: 9079A-2**

The 3m Semi-anechoic chamber of Global United Technology Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 9079A-2, August 15, 2016

5.6 Test Location

All tests were performed at:

Global United Technology Services Co., Ltd.

No. 301-309, 3/F., Jinyuan Business Building, No.2, Laodong Industrial Zone, Xixiang Road, Baoan District, Shenzhen, Guangdong, China 518102

Tel: 0755-27798480

Fax: 0755-27798960

5.7 Other Information Requested by the Customer

None.


6 Test Instruments list

Radiated Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	3m Semi- Anechoic Chamber	ZhongYu Electron	9.2(L)*6.2(W)* 6.4(H)	GTS250	July 03 2015	July 02 2020
2	Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	GTS251	N/A	N/A
3	Spectrum Analyzer	Agilent	E4440A	GTS533	June 29 2016	June 28 2017
4	EMI Test Receiver	Rohde & Schwarz	ESU26	GTS203	June 29 2016	June 28 2017
5	BiConiLog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9163	GTS214	June 29 2016	June 28 2017
6	Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	9120D-829	GTS208	June 29 2016	June 28 2017
7	Horn Antenna	ETS-LINDGREN	3160	GTS217	June 29 2016	June 28 2017
8	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
9	Coaxial Cable	GTS	N/A	GTS213	June 29 2016	June 28 2017
10	Coaxial Cable	GTS	N/A	GTS211	June 29 2016	June 28 2017
11	Coaxial cable	GTS	N/A	GTS210	June 29 2016	June 28 2017
12	Coaxial Cable	GTS	N/A	GTS212	June 29 2016	June 28 2017
13	Amplifier(100kHz-3GHz)	HP	8347A	GTS204	June 29 2016	June 28 2017
14	Amplifier(2GHz-20GHz)	HP	8349B	GTS206	June 29 2016	June 28 2017
15	Amplifier (18-26GHz)	Rohde & Schwarz	AFS33-18002 650-30-8P-44	GTS218	June 29 2016	June 28 2017
16	Band filter	Amindeon	82346	GTS219	June 29 2016	June 28 2017
17	Power Meter	Anritsu	ML2495A	GTS540	June 29 2016	June 28 2017
18	Power Sensor	Anritsu	MA2411B	GTS541	June 29 2016	June 28 2017

General used equipment:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Barometer	ChangChun	DYM3	GTS257	June 29 2016	June 28 2017

7 Test results and Measurement Data

7.1 Antenna requirement

Standard requirement:	FCC Part15 C Section 15.203
<p>15.203 requirement:</p> <p>An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.</p>	
<p>EUT Antenna:</p>	
<p><i>The antenna is PCB antenna, the best case gain of the antenna is 0.8dBi</i></p>  <p>Antenna</p>	

7.2 Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209				
Test Method:	ANSI C63.10:2013				
Test Frequency Range:	30MHz to 25GHz				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Remark
	30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak Value
	Above 1GHz	Peak	1MHz	3MHz	Peak Value
		Peak	1MHz	10Hz	Average Value
Limit: (Field strength of the fundamental signal)	Frequency	Limit (dBuV/m @3m)		Remark	
	2400MHz-2483.5MHz	94.00		Average Value	
		114.00		Peak Value	
Limit: (Spurious Emissions)	Frequency	Limit (dBuV/m @3m)		Remark	
	30MHz-88MHz	40.00		Quasi-peak Value	
	88MHz-216MHz	43.50		Quasi-peak Value	
	216MHz-960MHz	46.00		Quasi-peak Value	
	960MHz-1GHz	54.00		Quasi-peak Value	
	Above 1GHz	54.00		Average Value	
		74.00		Peak Value	
Limit: (band edge)	Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.				
Test setup:	Below 1GHz				
	<p>The diagram illustrates the test setup for frequencies below 1GHz. It shows an Equipment Under Test (EUT) placed on a turn table, which is positioned 80cm above the ground. A test antenna is located 3m away from the EUT and is mounted on a stand that is 1m to 4m high. The antenna is connected to a receiver and a preamplifier. The entire setup is enclosed within a shielded chamber, indicated by the hatched lines on the walls.</p>				
	Above 1GHz				

<p>Test Procedure:</p>	<ol style="list-style-type: none"> 1. The EUT was placed on the top of a rotating table (0.8m for below 1G and 1.5m for above 1G) above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
<p>Test Instruments:</p>	<p>Refer to section 6.0 for details</p>
<p>Test mode:</p>	<p>Refer to section 5.3 for details</p>
<p>Test results:</p>	<p>Pass</p>

Measurement data:

7.2.1 Field Strength of The Fundamental Signal

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
2402.00	89.86	27.58	5.39	34.01	88.82	114.00	-25.18	Vertical
2402.00	84.93	27.58	5.39	34.01	83.89	114.00	-30.11	Horizontal
2442.00	90.17	27.48	5.43	33.96	89.12	114.00	-24.88	Vertical
2442.00	84.29	27.48	5.43	33.96	83.24	114.00	-30.76	Horizontal
2477.00	89.34	27.52	5.47	33.92	88.41	114.00	-25.59	Vertical
2477.00	83.60	27.52	5.47	33.92	82.67	114.00	-31.33	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
2402.00	80.23	27.58	5.39	34.01	79.19	94.00	-14.81	Vertical
2402.00	75.24	27.58	5.39	34.01	74.20	94.00	-19.80	Horizontal
2442.00	80.18	27.48	5.43	33.96	79.13	94.00	-14.87	Vertical
2442.00	73.69	27.48	5.43	33.96	72.64	94.00	-21.36	Horizontal
2477.00	79.19	27.52	5.47	33.92	78.26	94.00	-15.74	Vertical
2477.00	73.84	27.52	5.47	33.92	72.91	94.00	-21.09	Horizontal

Remark: RBW 3MHz, VBW 10MHz , peak detector for PK value, RBW 3MHz, VBW 10MHz AV detector for AV value

7.2.2 Spurious emissions

■ Below 1GHz

Frequency (MHz)	Read Level (dBUV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBUV/m)	Limit Line (dBUV/m)	Over Limit (dB)	polarization
55.03	34.86	15.02	0.82	29.96	20.74	40.00	-19.26	Vertical
129.47	47.98	11.03	1.43	29.51	30.93	43.50	-12.57	Vertical
189.07	39.85	12.48	1.78	29.24	24.87	43.50	-18.63	Vertical
250.30	35.95	14.07	2.12	29.65	22.49	46.00	-23.51	Vertical
336.04	42.65	15.99	2.55	29.80	31.39	46.00	-14.61	Vertical
413.27	42.25	17.35	2.92	29.47	33.05	46.00	-12.95	Vertical
56.00	37.95	14.95	0.83	29.95	23.78	40.00	-16.22	Horizontal
129.02	41.46	11.12	1.43	29.52	24.49	43.50	-19.01	Horizontal
190.41	44.82	12.56	1.79	29.23	29.94	43.50	-13.56	Horizontal
251.18	41.26	14.07	2.13	29.65	27.81	46.00	-18.19	Horizontal
336.04	41.90	15.99	2.55	29.80	30.64	46.00	-15.36	Horizontal
414.72	41.48	17.35	2.92	29.47	32.28	46.00	-13.72	Horizontal

■ Above 1GHz

Test channel:	Lowest channel
---------------	----------------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4804.00	37.14	31.78	8.60	32.09	45.43	74.00	-28.57	Vertical
7206.00	31.72	36.15	11.65	32.00	47.52	74.00	-26.48	Vertical
9608.00	31.37	37.95	14.14	31.62	51.84	74.00	-22.16	Vertical
12010.00	*					74.00		Vertical
14412.00	*					74.00		Vertical
4804.00	41.40	31.78	8.60	32.09	49.69	74.00	-24.31	Horizontal
7206.00	33.46	36.15	11.65	32.00	49.26	74.00	-24.74	Horizontal
9608.00	30.78	37.95	14.14	31.62	51.25	74.00	-22.75	Horizontal
12010.00	*					74.00		Horizontal
14412.00	*					74.00		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4804.00	25.99	31.78	8.60	32.09	34.28	54.00	-19.72	Vertical
7206.00	20.43	36.15	11.65	32.00	36.23	54.00	-17.77	Vertical
9608.00	19.51	37.95	14.14	31.62	39.98	54.00	-14.02	Vertical
12010.00	*					54.00		Vertical
14412.00	*					54.00		Vertical
4804.00	30.20	31.78	8.60	32.09	38.49	54.00	-15.51	Horizontal
7206.00	22.59	36.15	11.65	32.00	38.39	54.00	-15.61	Horizontal
9608.00	19.23	37.95	14.14	31.62	39.70	54.00	-14.30	Horizontal
12010.00	*					54.00		Horizontal
14412.00	*					54.00		Horizontal

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.
3. “*”, means this data is the too weak instrument of signal is unable to test.

Test channel:	Middle channel
---------------	----------------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4884.00	36.80	31.85	8.67	32.12	45.20	74.00	-28.80	Vertical
7326.00	31.50	36.37	11.72	31.89	47.70	74.00	-26.30	Vertical
9768.00	31.17	38.35	14.25	31.62	52.15	74.00	-21.85	Vertical
12210.00	*					74.00		Vertical
14652.00	*					74.00		Vertical
4884.00	40.98	31.85	8.67	32.12	49.38	74.00	-24.62	Horizontal
7326.00	33.21	36.37	11.72	31.89	49.41	74.00	-24.59	Horizontal
9768.00	30.55	38.35	14.25	31.62	51.53	74.00	-22.47	Horizontal
12210.00	*					74.00		Horizontal
14652.00	*					74.00		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4884.00	25.72	31.85	8.67	32.12	34.12	54.00	-19.88	Vertical
7326.00	20.25	36.37	11.72	31.89	36.45	54.00	-17.55	Vertical
9768.00	19.35	38.35	14.25	31.62	40.33	54.00	-13.67	Vertical
12210.00	*					54.00		Vertical
14652.00	*					54.00		Vertical
4884.00	29.89	31.85	8.67	32.12	38.29	54.00	-15.71	Horizontal
7326.00	22.39	36.37	11.72	31.89	38.59	54.00	-15.41	Horizontal
9768.00	19.04	38.35	14.25	31.62	40.02	54.00	-13.98	Horizontal
12210.00	*					54.00		Horizontal
14652.00	*					54.00		Horizontal

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.
3. “*”, means this data is the too weak instrument of signal is unable to test.

Test channel:	Highest channel
---------------	-----------------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4954.00	35.91	31.93	8.73	32.16	44.41	74.00	-29.59	Vertical
7431.00	30.91	36.59	11.79	31.78	47.51	74.00	-26.49	Vertical
9908.00	30.65	38.81	14.38	31.88	51.96	74.00	-22.04	Vertical
12385.00	*					74.00		Vertical
14862.00	*					74.00		Vertical
4954.00	39.91	31.93	8.73	32.16	48.41	74.00	-25.59	Horizontal
7431.00	32.54	36.59	11.79	31.78	49.14	74.00	-24.86	Horizontal
9908.00	29.94	38.81	14.38	31.88	51.25	74.00	-22.75	Horizontal
12385.00	*					74.00		Horizontal
14862.00	*					74.00		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4954.00	25.03	31.93	8.73	32.16	33.53	54.00	-20.47	Vertical
7431.00	19.78	36.59	11.79	31.78	36.38	54.00	-17.62	Vertical
9908.00	18.94	38.81	14.38	31.88	40.25	54.00	-13.75	Vertical
12385.00	*					54.00		Vertical
14862.00	*					54.00		Vertical
4954.00	29.11	31.93	8.73	32.16	37.61	54.00	-16.39	Horizontal
7431.00	21.86	36.59	11.79	31.78	38.46	54.00	-15.54	Horizontal
9908.00	18.56	38.81	14.38	31.88	39.87	54.00	-14.13	Horizontal
12385.00	*					54.00		Horizontal
14862.00	*					54.00		Horizontal

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.
3. “*”, means this data is the too weak instrument of signal is unable to test.

7.2.3 Bandedge emissions

All of the restriction bands were tested, and only the data of worst case was exhibited.

Test channel:	Lowest channel
---------------	----------------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2390.00	38.16	27.59	5.38	30.18	40.95	74.00	-33.05	Horizontal
2400.00	54.28	27.58	5.39	30.18	57.07	74.00	-16.93	Horizontal
2390.00	38.26	27.59	5.38	30.18	41.05	74.00	-32.95	Vertical
2400.00	55.81	27.58	5.39	30.18	58.60	74.00	-15.40	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2390.00	29.78	27.59	5.38	30.18	32.57	54.00	-21.43	Horizontal
2400.00	40.73	27.58	5.39	30.18	43.52	54.00	-10.48	Horizontal
2390.00	29.39	27.59	5.38	30.18	32.18	54.00	-21.82	Vertical
2400.00	41.93	27.58	5.39	30.18	44.72	54.00	-9.28	Vertical

Test channel:	Highest channel
---------------	-----------------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	39.70	27.53	5.47	29.93	42.77	74.00	-31.23	Horizontal
2500.00	39.77	27.55	5.49	29.93	42.88	74.00	-31.12	Horizontal
2483.50	39.76	27.53	5.47	29.93	42.83	74.00	-31.17	Vertical
2500.00	40.32	27.55	5.49	29.93	43.43	74.00	-30.57	Vertical


Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	32.55	27.53	5.47	29.93	35.62	54.00	-18.38	Horizontal
2500.00	31.22	27.55	5.49	29.93	34.33	54.00	-19.67	Horizontal
2483.50	33.37	27.53	5.47	29.93	36.44	54.00	-17.56	Vertical
2500.00	30.75	27.55	5.49	29.93	33.86	54.00	-20.14	Vertical

Remark:

- Final Level = Receiver Read level + Antenna Factor + Cable Loss – Pre-amplifier Factor


7.3 20dB Occupy Bandwidth

Test Requirement:	FCC Part15 C Section 15.249/15.215
Test Method:	ANSI C63.10:2013
Limit:	Operation Frequency range 2400MHz~2483.5MHz
Test setup:	
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.3 for details
Test results:	Pass


Measurement Data

Test channel	20dB bandwidth(MHz)	Result
Lowest	1.728	Pass
Middle	1.840	Pass
Highest	1.064	Pass


Test plot as follows:



Lowest channel





Middle channel




Highest channel



8 Test Setup Photo


Radiated Emission





9 EUT Constructional Details











-----End-----