



MPE TEST REPORT

Report No: STS1611247F02

Issued for

Shenzhen Junlei Technology Co.,Ltd.

Room 216, Xinda Building, Fenghuanggang the first
Industrial Zone, Xixiang, Bao'an District, Shenzhen China

Product Name:	Wireless Charging Navigational Bracket
Brand Name:	N/A
Model Name:	JL--01
Series Model:	N/A
FCC ID:	2AKI6-JL-01
Test Standard:	FCC CFR 47 part 1, 1.1310

Any reproduction of this document must be done in full. No single part of this document may be reproduced without permission from STS. All Test Data Presented in this report is only applicable to presented Test sample.

Shenzhen STS Test Services Co., Ltd.
1/F., Building B, Zhuoke Science Park, No.190, Chongqing Road,
Fuyong Street, Bao'an District, Shenzhen, Guangdong, China
TEL: +86-755 3688 6288 FAX: +86-755 3688 6277 E-mail:sts@stsapp.com



**TEST RESULT CERTIFICATION****Applicant's name :**

Shenzhen Junlei Technology Co.,Ltd.

Address :

Room 216, Xinda Building, Fenghuanggang the first Industrial Zone, Xixiang, Bao'an District, Shenzhen China

Manufacture's Name :

Shenzhen Junlei Technology Co.,Ltd.

Address :

Room 216, Xinda Building, Fenghuanggang the first Industrial Zone, Xixiang, Bao'an District, Shenzhen China

Product description

Product name : Wireless Charging Navigational Bracket

Brand name : N/A

Model and/or type reference : JL-01

Standards : FCC CFR 47 part 1, 1.1310

Test Procedure : 680106 D01 RF Exposure Wireless Charging Apps v02

This device described above has been tested by STS, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of STS, this document may be altered or revised by STS, personal only, and shall be noted in the revision of the document.

Date of performance of tests: 30 Nov. 2016 ~12 Dec. 2016

Date of Issue : 13 Dec. 2016

Test Result : **Pass**

Testing Engineer :

(Sean she)

Technical Manager :

(Tony Liu)

Authorized Signatory :

(Bovey Yang)





Table of Contents

Page

1. SUMMARY OF TEST RESULTS	5
1.1 TEST FACTORY	5
1.2 MEASUREMENT UNCERTAINTY	5
1.3 GENERAL DESCRIPTION OF EUT	6
1.4 EQUIPMENTS LIST FOR ALL TEST ITEMS	7
2. MAXIMUM PERMISSIBLE EXPOSURE	8
2.1 MAXIMUM PERMISSIBLE EXPOSURE	8
2.2 TEST PROCEDURE	9
2.3 TEST SETUP	9
2.4 RESULT OF MAXIMUM PERMISSIBLE EXPOSURE	9



**Revision History**

Rev.	Issue Date	Report NO.	Effect Page	Contents
00	13 Dec. 2016	STS1611247F02	ALL	Initial Issue





1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:
FCC KDB 680106 D01 RF Exposure Wireless Charging Apps v02

FCC CFR 47			
Standard Section	Test Item	Judgment	Remark
FCC CFR 47 part1, 1.1310 KDB680106 D01v02 (3)(3)	Electric Field Strength (E) (V/m)	PASS	
	Magnetic Field Strength (H) (A/m)	PASS	

1.1 TEST FACTORY

Shenzhen STS Test Services Co., Ltd.
Add. : 1/F., Building B, Zhuoke Science Park, No.190, Chongqing Road,
Fuyong Street, Bao'an District, Shenzhen, Guangdong, China
FCC Registration No.: 842334; IC Registration No.: 12108A-1

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expended uncertainty **U** is based on a standard uncertainty multiplied by a coverage factor of **k=2** , providing a level of confidence of approximately **95 %** .

No.	Item	Uncertainty
1	All emissions, radiated(<30M)(9KHz-30MHz)	$\pm 2.45\text{dB}$
2	Temperature	$\pm 0.5^\circ\text{C}$
3	Humidity	$\pm 2\%$



1.3 GENERAL DESCRIPTION OF EUT

Equipment	Wireless Charging Navigational Bracket
Trade Name	N/A
Model Name	JL--01
Series Model	N/A
Model Difference	N/A
Equipment Category	Non-ISM frequency
Operating frequency	123.1KHz
Modulation Type	ASK
Power rating	DC 5V
Hardware version number	N/A
Software version number	N/A

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.
- 2.

Channel List	
Channel	Frequency(KHz)
01	123.1

3. Table for Filed Antenna

Ant	Brand	Model Name	Antenna Type	Connector	NOTE
1	N/A	JL--01	COIL	NA	Antenna

The EUT antenna is COIL Antenna. No antenna other than that furnished by the responsible party shall be used with the device.



1.4 EQUIPMENTS LIST FOR ALL TEST ITEMS

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
EMF Meter	NARDA	ELT-400	N-0342	2016.10.23	2017.10.22
EMF probe	NARDA	B-Field Probe	M-0779	2016.10.23	2017.10.22
Broadband field meter NARDA NBM	550	Broadband field meter NARDA NBM	E-1275	2016.11.24	2017.11.23
Broadband field probe NARDA EF	0391	Broadband field probe NARDA EF	D-0894	2016.06.06	2017.06.05





2. MAXIMUM PERMISSIBLE EXPOSURE

2.1 MAXIMUM PERMISSIBLE EXPOSURE

Limit of Maximum Permissible Exposure

Limits for Occupational / Controlled Exposure				
Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

Limits for General Population / Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180 / f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1	30

Note 1: f = frequency in MHz ; *Plane-wave equivalent power density


Note 2: For the applicable limit, see FCC 1.1310, 680106 D01 RF Exposure Wireless Charging Apps v02

Note 3: Emissions between 100 kHz to 300 kHz should be assessed versus the limits at 300 kHz in Table 1 of Section 1.1310: 614 V/m and 1.63 A/m. A KDB inquiry is required to determine the applicable exposure limits below 100 kHz.

2.2 TEST PROCEDURE

a. For devices designed for typical desktop applications, such a wireless charging pads, RF exposure evaluation should be conducted assuming a user separation distance of 10 cm. E and H field strength measurements or numerical modeling may be used to demonstrate compliance. Measurements should be made from all sides and the top of the primary/client pair, with the 10 cm measured from the center of the probe(s) to the edge of the device.


2.3 TEST SETUP



2.4 RESULT OF MAXIMUM PERMISSIBLE EXPOSURE

Maximum Permissible Exposure				
Charging	Separation	Probe from EUT Side	E-field (V/m)	H-field (A/m)
< 1% Battery	10cm	A	1.35	0.346
< 1% Battery	10cm	B	1.40	0.355
< 1% Battery	10cm	C	1.55	0.332
< 1% Battery	10cm	D	1.46	0.345
< 1% Battery	10cm	E	5.22	0.337
Limit			614	1.63
Margin Limit (%)			0.85%	21.78%

MPE SETUP PHOTO



*****END OF THE REPORT*****