FCC 47 CFR PART 15 SUBPART C

Report No.: C161101Z02-RP1-1

for

GDU Byrd

Model: MGP01-P2.0

Brand: N/A

Test Report Number: C161101Z02-RP1-1

Issued for

Prodrone Technology (Shenzhen) Co.,Ltd

11th floor, Tower 1,Novel Park,4078 Dong Bin Road , Nanshan District,
Shenzhen

Issued by:

Compliance Certification Services (Shenzhen) Inc.

No.10-1, Mingkeda Logistics Park, No.18 Huanguan South Rd., Guan Lan Town, Baoan District, Shenzhen, China

> TEL: 86-755-28055000 FAX: 86-755-28055221

E-Mail: service@ccssz.com

Issued Date: November 24, 2016



Note: This report shall not be reproduced except in full, without the written approval of Compliance Certification Services (Shenzhen) Inc. This document may be altered or revised by Compliance Certification Services (Shenzhen) Inc. personnel only, and shall be noted in the revision section of the document. The client should not use it to claim product endorsement by TAF, A2LA, NVLAP, NIST, CNAS or any government agencies. The test results in the report only apply to the tested sample.

Revision History

Rev.	Issue Data	Revisions	Effect Page	Revised By
00	November 24, 2016	Initial Issue	ALL	Amzula Chen

1 T	EST CERTIFICATION	. 4
2 T	EST RESULT SUMMARY	. 5
3 E	UT DESCRIPTION	. 6
	EST METHODOLOGY	
	DESCRIPTION OF TEST MODES	
	ETUP OF EQUIPMENT UNDER TEST	
5.1.	DESCRIPTION OF SUPPORT UNITS	. 8
5.2.	CONFIGURATION OF SYSTEM UNDER TEST	. 8
6 F	ACILITIES AND ACCREDITATIONS	9
6.1.	FACILITIES	. 9
	ACCREDITATIONS	
6.3.	MEASUREMENT UNCERTAINTY	10
7 F	CC PART 15.247 REQUIREMENTS	11
	POWER LINE CONDUCTED EMISSIONS MEASUREMENT	
	SPURIOUS EMISSIONS MEASUREMENT	
	6dB BANDWIDTH MEASUREMENT	
	ANTENNA GAIN	
	PEAK OUTPUT POWER	
	BAND EDGES MEASUREMENT	
7.7.	PEAK POWER SPECTRAL DENSITY MEASUREMENT	49

TABLE OF CONTENTS

1 TEST CERTIFICATION

Product	GDU Byrd
Model	MGP01-P2.0
Brand N/A	
Tested	November 1~ November 24, 2016
Applicant	Prodrone Technology (Shenzhen) Co.,Ltd 11th floor, Tower 1,Novel Park,4078 Dong Bin Road , Nanshan District, Shenzhen
Manufacturer	Prodrone Technology (Shenzhen) Co.,Ltd 11th floor, Tower 1,Novel Park,4078 Dong Bin Road , Nanshan District, Shenzhen

APPLICABLE STANDARDS						
Standard	Test Type	Test Type				
15.207(a)	Power Line Conducted Emissions	15.247(d) 15.209(a)	Spurious EmissionsConducted MeasurementRadiated Emissions			
15.247(a)(2)	6dB Bandwidth Measurement	15.247(b)(3) 15.247(b)(4)	Peak Power Measurement			
15.247(d)	Band Edges Measurement	15.247(e)	Peak Power Spectral Density			

We hereby certify that:

The above equipment was tested by Compliance Certification Services (Shenzhen) Inc. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in **ANSI C63.10: 2013** and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules Part 15.207, 15.209, 15.247.

The test results of this report relate only to the tested sample EUT identified in this report.

Approved by:

Reviewed by:

Sunday Hu

Supervisor of EMC Dept.

Sunday. My

Compliance Certification Services (Shenzhen) Inc.

Ruby Zhang

Supervisor of Report Dept.

Compliance Certification Services (Shenzhen) Inc.

2 TEST RESULT SUMMARY

	APPLICABLE STANDARDS							
Standard	Test Type	Result	Remark					
15.247(a)(2)	6dB Bandwidth Measurement	Pass	Meet the requirement of limit.					
15.247(b)(3) 15.247(b)(4)	Peak Power Measurement	Pass	Meet the requirement of limit.					
15.247(d)	Band Edges Measurement	Pass	Meet the requirement of limit.					
15.247(e)	Peak Power Spectral Density	Pass	Meet the requirement of limit.					
15.247(d) 15.209(a)	Spurious EmissionsConducted MeasurementRadiated Emissions	Pass	Meet the requirement of limit.					
15.207(a)	Power line Conducted Emissions	N/A	Not applicable, since the EUT received DC power from Battery.					

Note: 1. The statements of test result on the above are decided by the request of test standard only; the measurement uncertainties are not factored into this compliance determination.

^{2.} The information of measurement uncertainty is available upon the customer's request.

3 EUT DESCRIPTION

Product	GDU Byrd
Model	MGP01-P2.0
Brand	N/A
Model Discrepancy	N/A
Identify Number	C161101Z02-RP1-1
Received Date	November 1, 2016
Power Supply	DC14.8V powered by battery
Battery specification	Model: PD1-6700mAh-4S Voltage: 14.8V Energy: 99.16mAh Capacity:6700mAh
Frequency Range	2424MHz ~2466MHz
Transmit Power	26.58dBm(MIMO)
Modulation Technique	GFSK
Number of Channels	8 Channels
Antenna Specification	Antenna 1: Dipole Antenna with 2dBi gain (Max) Antenna 2: Dipole Antenna with 2dBi gain (Max)
Temperature Range	-20°C ~ +60°C

Note: 1. The sample selected for test was engineering sample that approximated to production product and was provided by manufacturer.

^{2.} This submittal(s) (test report) is intended for <u>FCC ID: 2AKIE-PD-BYRD-0201</u> filing to comply with Section 15.207, 15.209 and 15.247of the FCC Part 15, Subpart C Rules.

4 TEST METHODOLOGY

4.1. DESCRIPTION OF TEST MODES

The EUT has been tested under operating condition.

Software used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

Report No.: C161101Z02-RP1-1

<u> </u>		
Test Item	Test mode	Worse mode
Conducted Emission	Not applicable, since the EUT received DC power from Battery.	
Radiated Emission	Mode 1: TX	

After verification, all tests were carried out with the worst case test modes as shown below except radiated spurious emission below 1GHz, which worst case was in normal link mode only.

5 SETUP OF EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Report No.: C161101Z02-RP1-1

No	. Equipment	Model No.	Serial No.	FCC	Brand	Data Cable	Power Cord
1	Notebook	Probook 5310M	N/A	DoC	НР	Shielded 2.30m	Shielded 1.70m (AC Cable) Unshielded 1.80m (DC Cable)

Note:

Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

5.2. CONFIGURATION OF SYSTEM UNDER TEST

See test photographs attached in Appendix II for the actual connections between EUT and support equipment.

6 FACILITIES AND ACCREDITATIONS

6.1. FACILITIES

All measurement facilities used to collect the measurement data are located at No. 10-1, Mingkeda Logistics Park, No.18 Huanguan South RD. Guan Lan Town, Baoan District, Shenzhen China

The sites are constructed in conformance with the requirements of ANSI C63.10, ANSI C63.7 and CISPR Publication 22. All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

Report No.: C161101Z02-RP1-1

6.2. ACCREDITATIONS

Our laboratories are accredited and approved by the following accreditation body according to ISO/IEC 17025.

USA A2LA China CNAS

The measuring facility of laboratories has been authorized or registered by the following approval agencies.

USA FCC

Japan VCCI(C-4815, R-4320, T-2317, G-10624)

Canada INDUSTRY CANADA

Copies of granted accreditation certificates are available for downloading from our web site, http://www.ccssz.com

6.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Report No.: C161101Z02-RP1-1

Parameter	Uncertainty
Radiated Emission, 30 to 200 MHz Test Site : 966(2)	+/-3.6880dB
Radiated Emission, 200 to 1000 MHz Test Site : 966(2)	+/-3.6695dB
Radiated Emission, 1 to 8 GHz	+/-5.1782dB
Radiated Emission, 8 to 18 GHz	+/-5.2173dB
Conducted Emissions	+/-3.6836dB
Band Width	178kHz
Peak Output Power MU	+/-1.906dB
Band Edge MU	+/-0.182dB
Channel Separation MU	416.178Hz
Duty Cycle MU	0.054ms
Frequency Stability MU	226Hz

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

The measured result is above (below) the specification limit by a margin less than the measurement uncertainty; it is therefore not possible to state compliance based on the 95% level of confidence. However, the result indicates that compliance (non-compliance) is more probable than non-compliance) with the specification limit.

7 FCC PART 15.247 REQUIREMENTS

7.1. POWER LINE CONDUCTED EMISSIONS MEASUREMENT

7.1.1. LIMITS OF CONDUCTED EMISSIONS MEASUREMENT

According to §15.207(a), except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Report No.: C161101Z02-RP1-1

Frequency Range		nits ⊱µV)
(MHz)	Quasi-peak	Average
0.15 to 0.50	66 to 56*	56 to 46*
0.50 to 5	56	46
5 to 30	60	50

NOTE:

- (1) The lower limit shall apply at the transition frequencies.
- (2) The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.
- (3) All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

7.1.2. TEST INSTRUMENTS

	Conducted Emission Test Site									
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration					
EMI TEST RECEIVER	ROHDE&SCHWARZ	ESCI	100783	02/21/2016	02/20/2017					
LISN(EUT)	ROHDE&SCHWARZ	ENV216	101543-WX	02/21/2016	02/20/2017					
LISN	EMCO	3825/2	8901-1459	02/21/2016	02/20/2017					
Temp. / Humidity Meter	VICTOR	HTC-1	N/A	02/21/2016	02/20/2017					
Test S/W	FARAD		EZ-EMC/ CCS-3A	1-CE						

NOTE: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.


2. N.C.R = No Calibration Request.

7.1.3. TEST PROCEDURES (please refer to measurement standard)

• The EUT and Support equipment, if needed, was placed on a non-conducted table, which is 0.8m above the ground plane and 0.4m away from the conducted wall.

- The test equipment EUT installed received AC main power, through a Line Impedance Stabilization Network (LISN), which supplied power source and was grounded to the ground plane. All support equipment power received from a second LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- The EUT test program was started. Emissions were measured on each current carrying line of the EUT using an EMI Test Receiver connected to the LISN powering the EUT.
- The frequency range from 150 kHz to 30 MHz was searched. The test data of the worst-case condition(s) was recorded. Emission levels under limit 20dB were not recorded.

7.1.4. TEST SETUP



Report No.: C161101Z02-RP1-1

For the actual test configuration, please refer to the related item - Photographs of the Test Configuration.

7.1.5. DATA SAMPLE

Frequency (MHz)		Average Reading (dBuV)		QuasiPeak Result (dBuV)	Average Result (dBuV)	QuasiPeak Limit (dBuV)	Average Limit (dBuV)	QuasiPeak Margin (dB)	Margin	Remark (Pass/Fail)
X.XXXX	34.99	19.33	10.15	45.14	29.48	65.99	56.00	-20.85	-26.52	Pass

Factor = Insertion loss of LISN + Cable Loss

Result = Quasi-peak Reading/ Average Reading + Factor

Limit = Limit stated in standard Margin = Result (dBuV) – Limit (dBuV)

7.1.6. TEST RESULTS

Not applicable, since the EUT received DC power from Battery.

7.2. SPURIOUS EMISSIONS MEASUREMENT

7.2.1. CONDUCTED EMISSIONS MEASUREMENT

7.2.1.1. LIMITS OF CONDUCTED EMISSIONS MEASUREMENT

According to §15.247(d), in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator in operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in 15.209(a) (see Section 15.205(c)).

Report No.: C161101Z02-RP1-1

7.2.1.2. TEST INSTRUMENTS

	Name of Equipment	Manufacturer	Model	Serial Number	Last Calibration	Due Calibration
S	pectrum Analyzer	Agilent	N9010A	MY55370330	02/21/2016	02/20/2017


7.2.1.3. TEST PROCEDURE (please refer to measurement standard)


Conducted RF measurements of the transmitter output were made to confirm that the EUT antenna port conducted emissions meet the specified limit and to identify any spurious signals that require further investigation or measurements on the radiated emissions site. The transmitter output is connected to the spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 300 kHz.


Measurements are made over the 10MHz to 26.5GHz range with the transmitter set to the lowest, middle, and highest channels. No emission found between lowest internal used/generated frequency to 10MHz, it is only recorded 10MHz to 26GHz.

7.2.1.4. TEST RESULTS


Test Plot Antenna 1









Antenna 2







7.2.2. RADIATED EMISSIONS MEASUREMENT

7.2.2.1. LIMITS OF RADIATED EMISSIONS MEASUREMENT

According to §15.209(a), except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Report No.: C161101Z02-RP1-1

Frequency (MHz)	Field Strength (mV/m)	Measurement Distance (m)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100*	3
88-216	150*	3
216-960	200*	3
Above 960	500	3

Remark: Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

1. In the emission table above, the tighter limit applies at the band edges.

Frequency (MHz)	Field Strength (μV/m at 3-meter)	Field Strength (dBµV/m at 3-meter)
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54

NOTE: (1) The lower limit shall apply at the transition frequencies.

(2) Emission level (dBuV/m) = 20 log Emission level (uV/m).

7.2.2.2. TEST INSTRUMENTS

Radiated Emission Test Site 966(2)											
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration						
PSA Series Spectrum Analyzer	Agilent	E4446A	US44300399	02/21/2016	02/20/2017						
EMI TEST RECEIVER	ROHDE&SCHWARZ	ESCI	100783	02/21/2016	02/20/2017						
Amplifier	EMEC	EM330	060661	03/18/2016	03/17/2017						
High Noise Amplifier	Agilent	8449B	3008A01838	02/21/2016	02/20/2017						
Loop Antenna	COM-POWER	AL-130	121044	09/25/2016	09/24/2017						
Bilog Antenna	SCHAFFNER	CBL6143	5082	02/21/2016	02/20/2017						
Horn Antenna	SCHWARZBECK	BBHA9120	D286	02/28/2016	02/27/2017						
Board-Band Horn Antenna	Schwarzbeck	BBHA 9170	9170-497	02/28/2016	02/27/2017						
Turn Table	N/A	N/A	N/A	N.C.R	N.C.R						
Antenna Tower	SUNOL	TLT2	N/A	N.C.R	N.C.R						
Controller	Sunol Sciences	SC104V	022310-1	N.C.R	N.C.R						
Controller	СТ	N/A	N/A	N.C.R	N.C.R						
Temp. / Humidity Meter	Anymetre	JR913	N/A	02/21/2016	02/20/2017						
Test S/W	FARAD		LZ-RF / CCS	S-SZ-3A2							

NOTE: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

- 2. The FCC Site Registration number is 101879.
- 3. N.C.R = No Calibration Required.

7.2.2.3. Measuring Instruments and Setting

The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (Emission in restricted	1MHz / 1MHz for Peak, 1 MHz /10Hz for
band)	Average
RB / VB (Emission in non-restricted	1MHz / 1MHz for Peak, 1 MHz / 10Hz for
band)	Average

Report No.: C161101Z02-RP1-1

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP/AVG
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP/AVG
Start ~ Stop Frequency	30MHz~1000MHz / RB 100kHz for QP

7.2.2.4. TEST PROCEDURE (please refer to measurement standard)

1) Sequence of testing 9 kHz to 30 MHz

Setup:

- --- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- --- If the EUT is a tabletop system, a rotatable table with 0.8 m height is used.
- --- If the EUT is a floor standing device, it is placed on the ground.
- --- Auxiliary equipment and cables were positioned to simulate normal operation conditions.
- --- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- --- The measurement distance is 3 meter.
- --- The EUT was set into operation.

Pre measurement:

- --- The turntable rotates from 0° to 315° using 45° steps.
- --- The antenna height is 0.8 meter.
- --- At each turntable position the analyzer sweeps with peak detection to find the maximum of all emissions

Final measurement:

- --- Identified emissions during the pre measurement the software maximizes by rotating the turntable position (0 $^{\circ}$ to 360 $^{\circ}$) and by rotating the elevation axes (0 $^{\circ}$ to 360 $^{\circ}$).
- --- The final measurement will be done in the position (turntable and elevation) causing the highest emissions with QPK detector.

Report No.: C161101Z02-RP1-1

--- The final levels, frequency, measuring time, bandwidth, turntable position, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the pre measurement and the limit will be stored.

2) Sequence of testing 30 MHz to 1 GHz

Setup:

- --- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- --- If the EUT is a tabletop system, a table with 0.8 m height is used, which is placed on the ground plane.
- --- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- --- Auxiliary equipment and cables were positioned to simulate normal operation conditions
- --- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- --- The measurement distance is 3 meter.
- --- The EUT was set into operation.

Pre measurement:

- --- The turntable rotates from 0° to 315° using 45° steps.
- --- The antenna is polarized vertical and horizontal.
- --- The antenna height changes from 1 to 3 meter.
- --- At each turntable position, antenna polarization and height the analyzer sweeps three times in peak to find the maximum of all emissions.

Final measurement:

- --- The final measurement will be performed with minimum the six highest peaks.
- --- According to the maximum antenna and turntable positions of premeasurement the software maximize the peaks by changing turntable position (± 45°) and antenna movement between 1 and 4 meter.

Report No.: C161101Z02-RP1-1

- --- The final measurement will be done with QP detector with an EMI receiver.
- --- The final levels, frequency, measuring time, bandwidth, antenna height, antenna polarization, turntable angle, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement with marked maximum final measurements and the limit will be stored.

3) Sequence of testing 1 GHz to 18 GHz

Setup:

- --- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- --- If the EUT is a tabletop system, a rotatable table with 1.5 m height is used.
- --- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- --- Auxiliary equipment and cables were positioned to simulate normal operation
- --- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- --- The measurement distance is 3 meter.
- --- The EUT was set into operation.

Pre measurement:

- --- The turntable rotates from 0° to 315° using 45° steps.
- --- The antenna is polarized vertical and horizontal.
- --- The antenna height scan range is 1 meter to 2.5 meter.
- --- At each turntable position and antenna polarization the analyzer sweeps with peak detection to find the maximum of all emissions.

Final measurement:

- --- The final measurement will be performed with minimum the six highest peaks.
- --- According to the maximum antenna and turntable positions of premeasurement the software maximize the peaks by changing turntable position (± 45°) and antenna movement between 1 and 4 meter. This procedure is repeated for both antenna polarizations.

Report No.: C161101Z02-RP1-1

- --- The final measurement will be done in the position (turntable, EUT-table and antenna polarization) causing the highest emissions with Peak and Average detector.
- --- The final levels, frequency, measuring time, bandwidth, turntable position, EUT-table position, antenna polarization, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the pre measurement with marked maximum final measurements and the limit will be stored.

4) Sequence of testing above 18 GHz Setup:

- --- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- --- If the EUT is a tabletop system, a rotatable table with 1.5 m height is used.
- --- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- --- Auxiliary equipment and cables were positioned to simulate normal operation conditions
- --- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- --- The measurement distance is 1 meter.
- --- The EUT was set into operation.

Pre measurement:


--- The antenna is moved spherical over the EUT in different polarisations of the antenna.

Final measurement:


- --- The final measurement will be performed at the position and antenna orientation for all detected emissions that were found during the premeasurements with Peak and Average detector.
- --- The final levels, frequency, measuring time, bandwidth, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement and the limit will be stored.

7.2.2.5. TEST SETUP


Below 30MHz



Below 1 GHz



Above 1 GHz



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

7.2.2.6. DATA SAMPLE

Below 1GHz

Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
XXX.XXXX	53.41	-18.63	34.78	43.50	-8.72	V	QP

Report No.: C161101Z02-RP1-1

Frequency (MHz) = Emission frequency in MHz

Reading (dBuV) = Uncorrected Analyzer / Receiver reading
Correct Factor (dB/m) = Antenna factor + Cable loss – Amplifier gain
Result (dBuV/m) = Reading (dBuV) + Corr. Factor (dB/m)

Limit (dBuV/m) = Limit stated in standard

Margin (dB) = Result (dBuV/m) – Limit (dBuV/m)

Q.P. = Quasi-peak Reading

Above 1GHz

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
XXXX.XXXX	62.09	-11.42	50.67	74.00	-23.33	V	Peak
XXXX.XXXX	49.78	-11.42	38.36	54.00	-15.64	V	AVG

Frequency (MHz) = Emission frequency in MHz

Reading (dBuV) = Uncorrected Analyzer / Receiver reading Correction Factor (dB/m) = Antenna factor + Cable loss – Amplifier gain Result (dBuV/m) = Reading (dBuV) + Corr. Factor (dB/m)

Limit (dBuV/m) = Limit stated in standard

Margin (dB) = Result (dBuV/m) – Limit (dBuV/m)

Peak = Peak Reading AVG = Average Reading

Calculation Formula

Margin (dB) = Result (dBuV/m) – Limits (dBuV/m) Result (dBuV/m) = Reading (dBuV) + Correction Factor

7.2.2.7. TEST RESULTS

Below 1 GHz

Test Mode: TX (CH High) Tested by: Jacksan Luo

Report No.: C161101Z02-RP1-1

Ambient temperature: 24°C Relative humidity: 52% RH Date: November 8, 2016

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
74.6200	58.15	-26.15	32.00	40.00	-8.00	V	QP
218.1800	53.58	-20.56	33.02	46.00	-12.98	V	QP
441.2800	54.13	-15.65	38.48	46.00	-7.52	V	QP
482.9900	54.27	-14.36	39.91	46.00	-6.09	V	QP
669.2300	51.53	-12.14	39.39	46.00	-6.61	V	QP
762.3500	52.49	-11.05	41.44	46.00	-4.56	V	QP
30.0000	49.34	-11.64	37.70	40.00	-2.30	Н	QP
167.7400	58.56	-22.83	35.73	43.50	-7.77	Н	QP
382.1100	50.37	-16.45	33.92	46.00	-12.08	Н	QP
482.9900	54.19	-14.36	39.83	46.00	-6.17	Н	QP
701.2400	51.98	-11.94	40.04	46.00	-5.96	Н	QP
825.4000	51.58	-10.49	41.09	46.00	-4.91	Н	QP

^{**}Remark: 1. No emission found between lowest internal used/generated frequency to 30MHz.

Notes:

- 1. Radiated emissions measured in frequency range from 9kHz to 1GHz were made with an instrument using Quasi-peak detector mode.
- 2. Data of measurement within this frequency range shown "---" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 3. The IF bandwidth of Receiver between 30MHz to 1GHz was 120kHz.

4. Frequency (MHz). = Emission frequency in MHz

Reading $(dB\mu V/m)$ = Receiver reading

Correction Factor (dB) = Antenna factor + Cable loss – Amplifier gain


 $Limit (dB\mu V/m)$ = Limit stated in standard

Margin (dB) = Measured (dB μ V/m) – Limits (dB μ V/m)


Antenna Pol e(H/V) = Current carrying line of reading

^{2.} Pre-scan all mode and recorded the worst case results in this report

Vertical



Horizontal



Above 1 GHz

Test Mode: CH Low(MIMO) Tested by: Jacksan Luo

Ambient temperature: 24°C Relative humidity: 52% RH Date: November 19, 2016

Frequency (MHz)	Reading (dBµV)	Correction Factor (dB/m)	Result (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
1036.000	55.37	-8.42	46.95	74.00	-27.05	V	peak
1738.000	53.13	-6.40	46.73	74.00	-27.27	V	peak
2422.000	53.18	-2.69	50.49	74.00	-23.51	V	peak
3673.000	42.52	0.21	42.73	74.00	-31.27	V	peak
4852.000	56.93	4.50	61.43	74.00	-12.57	V	peak
4852.000	45.08	4.50	49.58	54.00	-4.42	V	AVG
5572.000	41.01	5.90	46.91	74.00	-27.09	V	peak
1099.000	54.83	-8.18	46.65	74.00	-27.35	Н	peak
1603.000	50.38	-6.69	43.69	74.00	-30.31	Н	peak
2422.000	49.53	-2.69	46.84	74.00	-27.16	Н	peak
3637.000	42.83	0.06	42.89	74.00	-31.11	Н	peak
4852.000	52.80	4.50	57.30	74.00	-16.70	Н	peak
4852.000	41.17	4.50	45.67	54.00	-8.33	Н	AVG
5617.000	41.41	5.92	47.33	74.00	-26.67	Н	peak

REMARKS:

- 1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- 2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
- 3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
- 4. Data of measurement within this frequency range shown "---" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with "N/A" remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
- 6. Margin (dB) = Remark result (dBuV/m) Average limit (dBuV/m).

Test Mode: CH Mid(MIMO) **Tested by:** Jacksan Luo

Ambient temperature: <u>24°C</u> Relative humidity: <u>52% RH</u> Date: November 8, 2016

Frequency (MHz)	Reading (dBµV)	Correction Factor (dB/m)	Result (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
1054.000	55.50	-8.35	47.15	74.00	-26.85	V	peak
1198.000	52.74	-7.80	44.94	74.00	-29.06	V	peak
2449.000	51.16	-2.54	48.62	74.00	-25.38	V	peak
3196.000	44.46	-1.03	43.43	74.00	-30.57	V	peak
3997.000	42.95	1.58	44.53	74.00	-29.47	V	peak
4897.000	55.18	4.64	59.82	74.00	-14.18	V	peak
4897.000	44.12	4.64	48.76	54.00	-5.24	V	AVG
1072.000	54.39	-8.28	46.11	74.00	-27.89	Н	peak
2242.000	46.38	-3.67	42.71	74.00	-31.29	Н	peak
2512.000	45.93	-2.24	43.69	74.00	-30.31	Н	peak
3214.000	44.40	-1.00	43.40	74.00	-30.60	Н	peak
4195.000	42.00	2.28	44.28	74.00	-29.72	Н	peak
4897.000	53.26	4.64	57.90	74.00	-16.10	Н	peak
4897.000	40.48	4.64	45.12	54.00	-8.88	Н	AVG

REMARKS:

- 1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- 2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
- 3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
- 4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with "N/A" remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
- 6. Margin (dB) = Remark result (dBuV/m) Average limit (dBuV/m).

Test Mode: CH High(MIMO) Tested by: Jacksan Luo

Ambient temperature: 24°C Relative humidity: 52% RH Date: November 8, 2016

Frequency (MHz)	Reading (dBµV)	Correction Factor (dB/m)	Result (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
1054.000	55.82	-8.35	47.47	74.00	-26.53	V	peak
1198.000	52.60	-7.80	44.80	74.00	-29.20	V	peak
1756.000	50.84	-6.36	44.48	74.00	-29.52	V	peak
2467.000	49.80	-2.44	47.36	74.00	-26.64	V	peak
3835.000	42.79	0.89	43.68	74.00	-30.32	V	peak
4933.000	53.48	4.76	58.24	74.00	-15.76	V	peak
4933.000	42.50	4.76	47.26	54.00	-6.74	V	AVG
1027.000	55.12	-8.45	46.67	74.00	-27.33	Н	peak
1198.000	53.36	-7.80	45.56	74.00	-28.44	Н	peak
2242.000	46.59	-3.67	42.92	74.00	-31.08	Н	peak
2467.000	47.76	-2.44	45.32	74.00	-28.68	Н	peak
3718.000	42.37	0.40	42.77	74.00	-31.23	Н	peak
4933.000	50.64	4.76	55.40	74.00	-18.60	Н	peak
4933.000	41.59	4.76	46.35	54.00	-7.65	Н	AVG

REMARKS:

- 1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- 2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
- 3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
- 4. Data of measurement within this frequency range shown "---" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with "N/A" remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
- 6. Margin (dB) = Remark result (dBuV/m) Average limit (dBuV/m).

7.3. 6dB BANDWIDTH MEASUREMENT

7.3.1. LIMITS

According to §15.247(a)(2), systems using digital modulation techniques may operate in the 902 - 928 MHz, 2400 - 2483.5MHz. The minimum 6 dB bandwidth shall be at least 500 kHz.

Report No.: C161101Z02-RP1-1

7.3.2. TEST INSTRUMENTS


Name of Equipment	Manufacturer	Model	Serial Number	Last Calibration	Calibration Due
Spectrum Analyzer	Agilent	N9010A	MY55370330	02/21/2016	02/20/2017

7.3.3. TEST PROCEDURES (please refer to measurement standard)

8.1 Option 2:

The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 dB, if the functionality described above (i.e., RBW = 100 kHz, VBW $\geq 3 \text{ RBW}$, peak detector with maximum hold) is implemented by the instrumentation function. When using this capability, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be $\geq 6 \text{ dB}$.

7.3.4. TEST SETUP



7.3.5. TEST RESULTS

No non-compliance noted

Test Data

Antenna 1

Channel	Frequency (MHz)	Bandwidth (kHz)	Limit (kHz)	Margin (kHz)
Low	2424	5783		PASS
Mid	2448	5744	>500	PASS
High	2466	5753		PASS


Report No.: C161101Z02-RP1-1


Antenna 2

Channel	Frequency (MHz)	Bandwidth (kHz)	Limit (kHz)	Margin (kHz)
Low	2424	5741		PASS
Mid	2448	5753	>500	PASS
High	2466	5767		PASS


Test Plot


Antenna 1





Antenna 2





7.4. ANTENNA GAIN

MEASUREMENT

The antenna gain of the complete system is calculated by the difference of radiated power in EIRP and the conducted power of the module. For normal BT devices, the GFSK mode is used.

MEASUREMENT PARAMETERS

Measurement parameter					
Detector	Peak				
Sweep time	Auto				
Resolution bandwidth	3 MHz				
Video bandwidth	3 MHz				
Trace-Mode	Max hold				

LIMITS

FCC	IC					
Antenna Gain						
6 dBi						

TEST RESULTS

			Antenna 1		Antenna 2		
T _{nom}	V _{nom}	Lowest channel 2424MHz	Middle channel 2448MHz	Highest channel 2466MHz	Lowest channel 2424MHz	Middle channel 2448MHz	Highest channel 2466MHz
Conducted power [dBm] Measured with zigbee modulation		23.17	23.82	23.26	23.31	23.82	22.29
Radiated power [dBm] Measured with zigbee modulation		25.04	25.64	25.01	25.13	25.63	24.08
Gain [dBi] Calculated		1.87	1.82	1.75	1.82	1.81	1.79
Measurement u	ncertainty		± 1.5	dB (cond.) / ±	3 dB (rad.)		

7.5. PEAK OUTPUT POWER

7.5.1. LIMITS

The maximum peak output power of the intentional radiator shall not exceed the following:

- 1. According to §15.247(b)(3), for systems using digital modulation in the bands of 902-928 MHz, 2400-2483.5 MHz: 1 Watt.
- 2. According to §15.247(b)(4), the conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

7.5.2. TEST INSTRUMENTS

Name of Equipment	Manufacturer	Model	Serial Number	Last Calibration	Calibration Due
Power Meter	Anritsu	ML2495A	1204003	02/21/2016	02/20/2017
Power Sensor	Anritsu	MA2411B	1126150	02/21/2016	02/20/2017

7.5.3. TEST PROCEDURES (please refer to measurement standard)

9.1.1 RBW ≥ DTS bandwidth


This procedure shall be used when the measurement instrument has available a resolution bandwidth that is greater than the *DTS* bandwidth.

- a) Set the RBW ≥ DTS bandwidth.
- b) Set VBW ≥ 3 RBW.
- c) Set span ≥ 3 x RBW
- d) Sweep time = auto couple.
- e) Detector = peak.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use peak marker function to determine the peak amplitude level.

9.1.2 PKPM1 Peak power meter method

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.

7.5.4. TEST SETUP



7.5.5. TEST RESULTS

No non-compliance noted

Test Data

Combine with Antenna 1 and Antenna 2

Channel	Frequency (MHz)	Oı	Output Power Output (dBm) Power		-	Limit (W)	Peak /	Result
	(141112)	Antenna 1	Antenna 2	Total	(W)	(**)	AVO	
Low	2424	23.17	23.26	26.23	3 0.41933			PASS
Mid	2448	23.82	23.31	26.58	0.45528	1	Peak	PASS
High	2466	23.15	22.29	25.75	0.37597			PASS
Low	2424	13.22	12.97	16.11	0.04080		PASS	
Mid	2448	13.81	13.36	16.60	0.04572	1	AVG	PASS
High	2466	13.17	12.26	15.75	0.03758			PASS

7.6. BAND EDGES MEASUREMENT

7.6.1. LIMITS

According to §15.247(d), in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator in operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in 15.209(a) (see Section 15.205(c)).

7.6.2. TEST INSTRUMENTS

	Radiated I	Emission Test	Site 966(2)		
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration
PSA Series Spectrum Analyzer	Agilent	N9010A	MY55370330	02/21/2016	02/20/2017
EMI TEST RECEIVER	ROHDE&SCHWARZ	ESCI	100783	02/21/2016	02/20/2017
Amplifier	EMEC	EM330	060661	03/18/2016	03/17/2017
High Noise Amplifier	Agilent	8449B	3008A01838	02/21/2016	02/20/2017
Loop Antenna	COM-POWER	AL-130	121044	09/25/2016	09/24/2017
Bilog Antenna	SCHAFFNER	CBL6143	5082	02/21/2016	02/20/2017
Horn Antenna	SCHWARZBECK	BBHA9120	D286	02/28/2016	02/27/2017
Board-Band Horn Antenna	Schwarzbeck	BBHA 9170	9170-497	02/28/2016	02/27/2017
Turn Table	N/A	N/A	N/A	N.C.R	N.C.R
Antenna Tower	SUNOL	TLT2	N/A	N.C.R	N.C.R
Controller	Sunol Sciences	SC104V	022310-1	N.C.R	N.C.R
Controller CT		N/A	N/A	N.C.R	N.C.R
Temp. / Humidity Meter	Anymetre	JR913	N/A	02/21/2016	02/20/2017
Test S/W	FARAD		LZ-RF / CCS	S-SZ-3A2	


NOTE: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

- 2. The FCC Site Registration number is 101879.
- 3. N.C.R = No Calibration Required.

7.6.3. TEST PROCEDURES (please refer to measurement standard)


- 1. The EUT is placed on a turntable, which is 1.5m above the ground plane.
- 2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
- 3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.
- 4. Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission:
 - (a) PEAK: RBW=1MHz / VBW=3MHz / Sweep=AUTO
 - (b) AVERAGE: RBW=1MHz / VBW=10Hz / Sweep=AUTO
- 5. Repeat the procedures until all the PEAK and AVERAGE versus POLARIZATION are

7.6.4. TEST SETUP




7.6.5. TEST RESULTS

Test Plot Band Edges (CH Low) (MIMO)




No.	Frequency (MHz)	Reading (dBuV)	Corrected (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Pole
1	2390.0000	52.59	-6.60	59.19	74.00	-14.81	Peak	Vertical
2	2390.0000	40.50	-6.60	47.10	54.00	-6.90	Average	Vertical




No.	Frequency (MHz)	Reading (dBuV)	Corrected (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Pole
1	2390.0000	54.34	-6.60	60.94	74.00	-13.06	Peak	Horizontal
2	2390.0000	40.49	-6.60	47.09	54.00	-6.91	Average	Horizontal





No.	Frequency (MHz)	Reading (dBuV)	Corrected (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Pole
1	2483.5000	52.90	-6.24	59.14	74.00	-14.86	Peak	Vertical
2	2483.5000	41.40	-6.24	47.64	54.00	-6.36	Average	Vertical



No.	Frequency (MHz)	Reading (dBuV)	Corrected (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Pole
1	2483.5000	53.10	-6.24	59.34	74.00	-14.66	Peak	Horizontal
2	2483.5000	41.39	-6.24	47.63	54.00	-6.37	Average	Horizontal

7.7. PEAK POWER SPECTRAL DENSITY MEASUREMENT

7.7.1. LIMITS

According to §15.247(e), for digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

According to §15.247(f), the digital modulation operation of the hybrid system, with the frequency hopping turned off, shall comply with the power density requirements of paragraph (d) of this section.


7.7.2. TEST INSTRUMENTS

Name of Equipment	Manufacturer	Model	Serial Number	Last Calibration	Calibration Due
Spectrum Analyzer	Agilent	N9010A	MY55370330	02/21/2016	02/20/2017

7.7.3. TEST PROCEDURES (please refer to measurement standard)

- 1. Set analyzer center frequency to DTS channel center frequency.
- 2. Set the span to 1.5 times the DTS bandwidth.
- 3. Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- 4. Set the VBW ≥ 3 RBW.
- 5. Detector = peak.
- 6. Sweep time = auto couple.
- 7. Trace mode = max hold.
- 8. Allow trace to fully stabilize.
- 9. Use the peak marker function to determine the maximum amplitude level within the RBW.
- 10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

7.7.4. TEST SETUP



7.7.5. TEST RESULTS


No non-compliance noted


Test Data

Combine with Antenna 1 and Antenna 2

Channel	Frequency (MHz)		PPSD (dBm)		Limit (dBm)	Test Result
	(1411 12)	Antenna 1	Antenna 2	Total	(dBiii)	
Low	2424	-4.642	-6.253	-2.363		PASS
Mid	2448	-5.874	-5.977	-2.915	8	PASS
High	2466	-6.128	-6.992	-3.528		PASS

Test Plot Antenna 1





Antenna 2

