

4 FCC §2.1091 - RF Exposure

4.1 Applicable Standards

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for General Population/Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

Note: f = frequency in MHz

* = Plane-wave equivalent power density

4.2 MPE Prediction

Predication of MPE limit at a given distance, Equation from OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S = power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

4.3 Test Results

Maximum peak output power at antenna input terminal (dBm): 28.75

Maximum peak output power at antenna input terminal (mW): 749.8942

Prediction distance (cm): 20

Prediction frequency (MHz): 2132.6

Antenna Gain, typical (dBi): 3

Maximum Antenna Gain (numeric): 1.995

Power density at predication frequency and distance (mW/cm²): 0.2976

MPE limit for uncontrolled exposure at predication frequency (mW/cm²): 1.0

The device is compliant with the requirement MPE limit for uncontrolled exposure. The maximum power density at the distance of 20 cm is 0.2976 mW/cm². Limit is 1.0 mW/cm². The percentage is 0.2976 mW/1.0mW = 29.76%. The total percentage is 29.76% (WWAN) + 4.55% (WLAN) = 34.31%.