

Ø90mm

**Bluetooth Ceiling Speaker**

**MASTER**

Bluetooth System:	Bluetooth V4.1
Bluetooth Range:	>10m (33ft)
RMS Power:	2x30W @ 8 ohms
Power Input:	DC 24V/2.5A
Frequency Response:	60Hz - 20kHz
Impedance(ohm):	8
Product Diameter(mm):	225 (8.9")
Cutout Diameter(mm):	210 (8.3")
Product Depth(mm):	98 (3.9")

**FCC ID: 2AKKHFLC**

This device complies with part 15 of the FCC Rules.  
Operation is subject to the following two conditions:

(1) This device may not cause harmful interference,  
and (2) this device must accept any interference  
received, including interference that may cause  
undesired operation.

**FLC-6BT(KV+TI)**

Ø90mm

**Bluetooth Ceiling Speaker**

**MASTER**

Bluetooth System:	Bluetooth V4.1
Bluetooth Range:	>10m (33ft)
RMS Power:	2x30W @ 8 ohms
Power Input:	DC 24V/2.5A
Frequency Response:	60Hz - 20kHz
Impedance(ohm):	8
Product Diameter(mm):	225 (8.9")
Cutout Diameter(mm):	210 (8.3")
Product Depth(mm):	98 (3.9")

**FCC ID: 2AKKHFLC**

This device complies with part 15 of the FCC Rules.  
Operation is subject to the following two conditions:

(1) This device may not cause harmful interference,  
and (2) this device must accept any interference  
received, including interference that may cause  
undesired operation.

**FLC-6BTS(KV+TI)**

Ø90mm

**Bluetooth Ceiling Speaker**

**SLAVE**

Frequency Response:	60Hz - 20kHz
Impedance(ohm):	8
Product Diameter(mm):	225 (8.9")
Cutout Diameter(mm):	210 (8.3")
Product Depth(mm):	87 (3.4")

**FCC ID: 2AKKHFLC**

This device complies with part 15 of the FCC Rules.  
Operation is subject to the following two conditions:  
(1) This device may not cause harmful interference,  
and (2) this device must accept any interference  
received, including interference that may cause  
undesired operation.

**FLC-6BTS(KV+TI)**