

RF EXPOSURE REPORT



Report No.: 17020664-FCC-H1

Supersede Report No.: N/A

Applicant	Ningbo Lumiaudio Electronic Technology LTD		
Product Name	Bluetooth ceiling speaker		
Model No.	FLC-6BTS		
Serial Model	FLC-6BT, 24760		
Test Standard	FCC 2.1091		
Test Date	June 12 to June 28, 2017		
Issue Date	June 28, 2017		
Test Result	<input checked="" type="checkbox"/> Pass	<input type="checkbox"/> Fail	
Equipment complied with the specification	<input checked="" type="checkbox"/>		
Equipment did not comply with the specification	<input type="checkbox"/>		
Trety Lu	Deon Dai		
Trety Lu Test Engineer	Deon Dai Engineer Reviewer		
<p>This test report may be reproduced in full only Test result presented in this test report is applicable to the tested sample only</p>			

Issued by:

SIEMIC (Nanjing-China) Laboratories

2-1 Longcang Avenue Yuhua Economic and
Technology Development Park, Nanjing, China

Tel:+86(25)86730128/86730129 Fax:+86(25)86730127 Email: China@siemic.com.cn

Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

Accreditations for Conformity Assessment

Country/Region	Scope
USA	EMC, RF/Wireless, SAR, Telecom
Canada	EMC, RF/Wireless, SAR, Telecom
Taiwan	EMC, RF, Telecom, SAR, Safety
Hong Kong	RF/Wireless, SAR, Telecom
Australia	EMC, RF, Telecom, SAR, Safety
Korea	EMI, EMS, RF, SAR, Telecom, Safety
Japan	EMI, RF/Wireless, SAR, Telecom
Singapore	EMC, RF, SAR, Telecom
Europe	EMC, RF, SAR, Telecom, Safety

This page has been left blank intentionally.

CONTENTS

1	REPORT REVISION HISTORY.....	5
2	CUSTOMER INFORMATION	5
3	TEST SITE INFORMATION.....	5
4	EQUIPMENT UNDER TEST (EUT) INFORMATION	6
5	FCC §2.1091 - MAXIMUM PERMISSIBLE EXPOSURE (MPE).....	7

1 Report Revision History

Report No.	Report Version	Description	Issue Date
17020664-FCC-H1	NONE	Original	June 28, 2017

2 Customer information

Applicant Name	Ningbo Lumiaudio Electronic Technology LTD
Applicant Add	22/F., Building 1,Lisi Plaza, Huifeng East Road ,Ningbo,China 315100
Manufacturer	Ningbo Lumiaudio Electronic Technology LTD
Manufacturer Add	22/F., Building 1,Lisi Plaza, Huifeng East Road ,Ningbo,China 315100

3 Test site information

Lab performing tests	SIEMIC (Nanjing-China) Laboratories
Lab Address	2-1 Longcang Avenue Yuhua Economic and Technology Development Park, Nanjing, China
FCC Test Site No.	986914
IC Test Site No.	4842B-1
Test Software	EZ_EMC (Ver.ICP-03A1)

4 Equipment under Test (EUT) Information

Description of EUT: Bluetooth ceiling speaker

Main Model: FLC-6BTS

Serial Model: FLC-6BT, 24760

Date EUT received: June 08,2017

Test Date(s): June 12 to June 28, 2017

Antenna Gain: 0 dBi

Type of Modulation: BT:GFSK, π/4DQPSK, 8DPSK

RF Operating Frequency (ies): BT:2402-2480 MHz

Number of Channels: BT:79 CH

Port: Power Port、 Earphone Port

Input Power: Adapter
Input:100-240V 50/60Hz 1.6A
Output:24V/2.5A

Trade Name : N/A

FCC ID: 2AKKHFLC

5 FCC §2.1091 - Maximum Permissible exposure (MPE)

Applicable Standard

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to §1.1310 and §2.1091 RF exposure is calculated.

Limits for General Population/Uncontrolled Exposure

Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz

* = Plane-wave equivalent power density

Test Data

Predication of MPE limit at a given distance

$$S = \frac{PG}{4\pi R^2}$$

Where: S = power density (in appropriate units, e.g. mW/cm²)

P = power input to the antenna (in appropriate units, e.g., mW).

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain.

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

Type	Test mode	CH	Freq (MHz)	Conducted Power (dBm)	Tune Up Power (dBm)
Output power	GFSK	Low	2402	-1.877	-2.5±1
	π/4DQPSK	Low	2402	-3.145	
	8DPSK	Low	2402	-2.879	

For the antenna manufacturer provide only used limited to ERP/EIRP or radiated spurious emission test. The MPE evaluation as below:

GFSK

The maximum peak output power (turn-up power) in low channel of BT is -1.5dBm

Maximum peak output power (turn-up power) at antenna input terminal: 0.708 (mW)

Prediction distance: >20 (cm)

Predication frequency: 2402(MHz) lowest frequency

Antenna Gain (typical): 0 (dBi)

Antenna Gain (typical): 1 (numeric)

The worst case is power density at predication frequency at 20 cm: 0.00014 (mW/cm²)

MPE limit for general population exposure at prediction frequency: 1 (mW/cm²)

0.00014 (mW/cm²) < 1(mW/cm²)

π/4DQPSK

The maximum peak output power (turn-up power) in Middle channel of BT is -1.5dBm

Maximum peak output power (turn-up power) at antenna input terminal: 0.708 (mW)

Prediction distance: >20 (cm)

Predication frequency: 2402(MHz) lowest frequency

Antenna Gain (typical): 0 (dBi)

Antenna Gain (typical): 1 (numeric)

The worst case is power density at predication frequency at 20 cm: 0.00014 (mW/cm²)

MPE limit for general population exposure at prediction frequency: 1 (mW/cm²)

0.00014 (mW/cm²) < 1(mW/cm²)

8DPSK

The maximum peak output power (turn-up power) in High channel of BT is -1.5 dBm

Maximum peak output power (turn-up power) at antenna input terminal: 0.708 (mW)

Prediction distance: >20 (cm)

Predication frequency: 2402(MHz) lowest frequency

Antenna Gain (typical): 0 (dBi)

Antenna Gain (typical): 1 (numeric)

The worst case is power density at predication frequency at 20 cm: 0.00014 (mW/cm²)

MPE limit for general population exposure at prediction frequency: 1 (mW/cm²)

0.00014 (mW/cm²) < 1(mW/cm²)

Result: Pass