

## FCC PART 15 SUBPART C TEST REPORT

### FCC PART 15 SUBPART E 15.407

**Report Reference No.**..... : **MAX250329010P01-R01**

**FCC ID**..... : **2AKLL-AD5X**

Compiled by  
( position+printed name+signature)... : Engineer/ Cindy Zheng

*Cindy Zheng*

Supervised by  
( position+printed name+signature)... : Manager/Haley Wen

*Haley Wen*

Approved by  
( position+printed name+signature)... : RF Manager/ Vivian Jiang

*Vivian Jiang*

Date of issue..... : April 17, 2025

**Testing Laboratory Name**..... : **MAX Testing Co.,Ltd.**

Address..... : 1/F, Building B, Xinshidai GR Park, Shiyan Street, Bao'an District, Shenzhen, Guangdong, 518052, People's Republic of China

**Applicant's name**..... : **Zhejiang Flashforge 3D Technology CO., Ltd.**

Address..... : No. 518, Xianyuan Road, Jinhua, Zhejiang, China

**Test specification**..... :

**FCC CFR Title 47 Part 15 Subpart C Section 15.407**

Standard..... : **ANSI C63.10:2020**

**KDB 789033 D02 v02r01**

**MAX Testing Co.,Ltd. All rights reserved.**

This publication may be reproduced in whole or in part for non-commercial purposes as long as the MAX Testing Co.,Ltd. is acknowledged as copyright owner and source of the material. MAX Testing Co.,Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

**Test item description**..... : **3D Printer**

Trade Mark..... :  **FLASHFORGE**

Manufacturer..... : Dongguan Flashforge 3d Technology Co., Ltd.

Model/Type reference..... : AD5X

Listed Models ..... : N/A

Modulation Type..... : OFDM

Operation Frequency..... : From 5180MHz-5240MHz, 5745MHz-5825MHz

Rating..... : AC100~120V/200~240V, 50-60Hz, 650W

Result..... : **PASS**

## TEST REPORT

**Equipment under Test** : **3D Printer**

**Model /Type** : **AD5X**

**Series Model No.** **N/A**

**Model Declaration** : **N/A**

**Applicant** : **Zhejiang Flashforge 3D Technology CO., Ltd.**

**Address** : **No. 518, Xianyuan Road, Jinhua, Zhejiang, China**

**Manufacturer** : **Dongguan Flashforge 3d Technology Co., Ltd.**

**Address** : **Room 304, Building 2, No. 1 Jianlang Road, Tangxia Town,  
Dongguan City, Guangdong China**

|                     |             |
|---------------------|-------------|
| <b>Test Result:</b> | <b>PASS</b> |
|---------------------|-------------|

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

## Contents

|                                                              |           |
|--------------------------------------------------------------|-----------|
| <b>1 TEST STANDARDS .....</b>                                | <b>4</b>  |
| <b>2 SUMMARY .....</b>                                       | <b>5</b>  |
| 2.1 General Remarks.....                                     | 5         |
| 2.2 Product Description.....                                 | 5         |
| 2.3 Equipment Under Test.....                                | 6         |
| 2.4 Short description of the Equipment under Test (EUT)..... | 6         |
| 2.5 EUT operation mode.....                                  | 6         |
| 2.6 Block Diagram of Test Setup.....                         | 6         |
| 2.7 Related Submittal(s) / Grant (s).....                    | 6         |
| 2.8 Modifications.....                                       | 6         |
| <b>3 TEST ENVIRONMENT .....</b>                              | <b>7</b>  |
| 3.1 Address of the test laboratory.....                      | 7         |
| 3.2 Test Facility.....                                       | 7         |
| 3.3 Environmental conditions.....                            | 7         |
| 3.4 Test Description.....                                    | 8         |
| 3.5 Statement of the measurement uncertainty.....            | 8         |
| 3.6 Equipments Used during the Test.....                     | 10        |
| <b>4 TEST CONDITIONS AND RESULTS .....</b>                   | <b>12</b> |
| 4.1 AC Power Conducted Emission.....                         | 12        |
| 4.2 Radiated Emission.....                                   | 21        |
| 4.3 Maximum Peak Conducted Output Power.....                 | 38        |
| 4.4 Power Spectral Density.....                              | 41        |
| 4.5 Emission Bandwidth (26dBm Bandwidth).....                | 48        |
| 4.6 Minimum Emission Bandwidth (6dBm Bandwidth).....         | 55        |
| 4.7 Conducted Out Of Band Emission.....                      | 59        |
| 4.8 SPURIOUS RF CONDUCTED EMISSIONS.....                     | 78        |
| 4.9 Frequency Stability.....                                 | 79        |
| 4.10 Antenna Requiremen.....                                 | 81        |
| <b>5 TEST SETUP PHOTOS OF THE EUT .....</b>                  | <b>82</b> |
| <b>6 PHOTOS OF THE EUT .....</b>                             | <b>83</b> |



**MAX Testing Co.,Ltd.**

Report No.: MAX250329010P01-R01

## **1 TEST STANDARDS**

The tests were performed according to following standards:

[CC Rules Part 15 Subpart E](#)—Unlicensed National Information Infrastructure Devices

[ANSI C63.10-2020](#): American National Standard for Testing Unlicensed Wireless Devices

[KDB789033 D02](#): General UNII Test Procedures New Rules v02r01

## 2 SUMMARY

### 2.1 General Remarks

|                                |   |                |
|--------------------------------|---|----------------|
| Date of receipt of test sample | : | March 27, 2025 |
| Testing commenced on           | : | March 27, 2025 |
| Testing concluded on           | : | April 15, 2025 |

### 2.2 Product Description

|                          |                                                                                                                                               |                                    |                    |               |
|--------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------|--------------------|---------------|
| Product Name:            | 3D Printer                                                                                                                                    |                                    |                    |               |
| Model/Type reference:    | AD5X                                                                                                                                          |                                    |                    |               |
| Power supply:            | AC100~120V/200~240V, 50-60Hz, 650W                                                                                                            |                                    |                    |               |
| Adapter information      | N/A                                                                                                                                           |                                    |                    |               |
| testing sample ID:       | MAX250329010P01-R01-1# (Engineer sample),<br>MAX250329010P01-R01-2# (Normal sample)                                                           |                                    |                    |               |
| Hardware version:        | V1.0                                                                                                                                          |                                    |                    |               |
| Software version:        | V1.0                                                                                                                                          |                                    |                    |               |
| Built-in power supply 1: | A-150FGZ-24                                                                                                                                   |                                    |                    |               |
| Built-in power supply 2: | AM150-B24                                                                                                                                     |                                    |                    |               |
| WIFI :                   |                                                                                                                                               |                                    |                    |               |
| Supported type:          | 20MHz system                                                                                                                                  | 40MHz system                       | 80MHz system       | 160MHz system |
|                          | 802.11a<br>802.11n<br>802.11ac                                                                                                                | 802.11n<br>802.11ac                | 802.11ac           | N/A           |
| Modulation:              | 5180MHz-5240MHz<br>5745MHz-5825MHz                                                                                                            | 5190MHz-5230MHz<br>5755MHz-5795MHz | 5210MHz<br>5775MHz | N/A           |
| Operation frequency:     | OFDM                                                                                                                                          | OFDM                               | OFDM               | N/A           |
| Channel number:          | 9                                                                                                                                             | 4                                  | 2                  | N/A           |
| Channel separation:      | 20MHz                                                                                                                                         | 40MHz                              | 80MHz              | N/A           |
| Data Rate:               | 802.11a: 6,9,12,18,24,36,48, 54Mbps;<br>802.11n(HT20/HT40):MCS0-MCS7;<br>802.11ac(HT20): Ncc1 MCS0-Ncc1 MCS8<br>802.11ac(HT40/HT80):MCS0-MCS9 |                                    |                    |               |
| Antenna type:            | FPC antenna                                                                                                                                   |                                    |                    |               |
| Antenna gain:            | 4.9 dBi                                                                                                                                       |                                    |                    |               |

## 2.3 Equipment Under Test

### Power supply system utilised

|                      |   |                                                        |                                              |
|----------------------|---|--------------------------------------------------------|----------------------------------------------|
| Power supply voltage | : | <input type="radio"/> 230V / 50 Hz                     | <input checked="" type="radio"/> 120V / 60Hz |
|                      |   | <input type="radio"/> 5 V DC                           | <input type="radio"/> 24 V DC                |
|                      |   | <input type="radio"/> Other (specified in blank below) |                                              |

## 2.4 Short description of the Equipment under Test (EUT)

This is 3D Printer.

For more details, refer to the user's manual of the EUT.

## 2.5 EUT operation mode

The Applicant provides communication tools software (AT command) to control the EUT for staying in continuous transmitting (Duty Cycle more than 98%) and receiving mode for testing.


All test performed at the low, middle and high of operational frequency range of each mode.

Operation Frequency List WIFI on 5G Band:

| Operating band               | 20MHz   |                 | 40MHz   |                 | 80MHz   |                 |
|------------------------------|---------|-----------------|---------|-----------------|---------|-----------------|
|                              | Channel | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) |
| U-NII 1<br>(5150MHz-5250MHz) | 36      | 5180            | 38      | 5190            | 42      | 5210            |
|                              | 40      | 5200            |         |                 |         |                 |
|                              | 44      | 5220            | 46      | 5230            |         |                 |
|                              | 48      | 5240            |         |                 |         |                 |
| U-NII 3<br>(5725MHz-5850MHz) | 149     | 5745            | 151     | 5755            | 155     | 5775            |
|                              | 153     | 5765            |         |                 |         |                 |
|                              | 157     | 5785            | 159     | 5795            |         |                 |
|                              | 161     | 5805            |         |                 |         |                 |
|                              | 165     | 5825            | --      | --              | --      | --              |

Note: The line display in grey is those Channels/Frequencies select to test in this report for each operation mode.

## 2.6 Block Diagram of Test Setup



## 2.7 Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for filing to comply with Section 15.407 of the FCC Part 15, Subpart E Rules.

## 2.8 Modifications

No modifications were implemented to meet testing criteria.

### **3 TEST ENVIRONMENT**

#### **3.1 Address of the test laboratory**

**MAX Testing Co.,Ltd.**

1/F, Building B, Xinshidai GR Park, Shiyan Street, Bao'an District, Shenzhen, Guangdong, 518052, People's Republic of China

#### **3.2 Test Facility**

**FCC-Registration No.: 562200 Designation Number: CN1338**

MAX Testing Co.,Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements.

**Industry Canada Registration Number. Is: 11093A CAB identifier: CN0019**

The Laboratory has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing.

**A2LA-Lab Cert. No.: 4707.01**

MAX Testing Co.,Ltd. has been listed by American Association for Laboratory Accreditation to perform electromagnetic emission measurement.

The 3m-Semi anechoic test site fulfils CISPR 16-1-4 according to ANSI C63.10 and CISPR 16-1-4:2010.

#### **3.3 Environmental conditions**

During the measurement the environmental conditions were within the listed ranges:

Radiated Emission:

|                       |              |
|-----------------------|--------------|
| Temperature:          | 25 ° C       |
|                       |              |
| Humidity:             | 45 %         |
|                       |              |
| Atmospheric pressure: | 950-1050mbar |

Conducted testing:

|                       |              |
|-----------------------|--------------|
| Temperature:          | 25 ° C       |
|                       |              |
| Humidity:             | 44 %         |
|                       |              |
| Atmospheric pressure: | 950-1050mbar |

AC Power Conducted Emission

|                       |              |
|-----------------------|--------------|
| Temperature:          | 24 ° C       |
|                       |              |
| Humidity:             | 44 %         |
|                       |              |
| Atmospheric pressure: | 950-1050mbar |

### 3.4 Test Description

| FCC Requirement                                          |                                            |                       |
|----------------------------------------------------------|--------------------------------------------|-----------------------|
| FCC Part 15.207                                          | AC Power Conducted Emission                | PASS                  |
| FCC Part 15.407(a)                                       | Emission Bandwidth(26dBm Bandwidth)        | PASS <sup>Note1</sup> |
| FCC Part 15.407(e)                                       | Minimum Emission Bandwidth(6dBm Bandwidth) | PASS <sup>Note2</sup> |
| FCC Part 15.407(a)                                       | Maximum Conducted Output Power             | PASS                  |
| FCC Part 15.407(a)                                       | Peak Power Spectral Density                | PASS                  |
| FCC Part 15.407(g)                                       | Frequency Stability                        | PASS                  |
| FCC Part 15.407(b)                                       | Undesirable emission                       | PASS                  |
| FCC Part 15.407(b)/15.205/15.209                         | Radiated Emissions                         | PASS                  |
| 15.407(b)(1)/ 15.407(b)(2)<br>15.407(b)(3)/ 15.407(b)(4) | Band Edge                                  | PASS                  |
| 15.407(b)                                                | Spurious Emissions at Antenna Terminals    | PASS                  |
| FCC Part 15.407(h)                                       | Dynamic Frequency Selection                | N/A <sup>Note 3</sup> |
| FCC Part 15.203/15.247(b)                                | Antenna Requirement                        | PASS                  |
| FCC Part 15.407(c)                                       | Automatically discontinue transmission     | PASS <sup>Note4</sup> |

Note 1: Apply to U-NII 1, U-NII 2A, and U-NII 2C band.

Note 2: Apply to U-NII 3 band only.

Note 3: This device not work in DFS band.

Note 4: While the EUT is not transmitting any information, the EUT can automatically discontinue transmission and become standby mode for power saving. The EUT can detect the controlling signal of ASK message transmitting from remote device and verify whether it shall resend or discontinue transmission. (Manufacturer declare)

#### Data Rate Used:

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

| Test Items                                                                                                                                                                                    | Mode                        | Data Rate |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------|-----------|
| MMaximum Conducted Output Power<br>Power Spectral Density<br>Emission Bandwidth(26dBm Bandwidth)<br>Minimum Emission Bandwidth(6dBm Bandwidth)<br>Undesirable emission<br>Frequency Stability | 11a/OFDM                    | 6 Mbps    |
|                                                                                                                                                                                               | 11n(20MHz),11ac(20MHz)/OFDM | 7.2 Mbps  |
|                                                                                                                                                                                               | 11n(40MHz),11ac(40MHz)/OFDM | 15.0Mbps  |
|                                                                                                                                                                                               | 11ac(80MHz)/OFDM            | 65.0Mbps  |

### 3.5 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to TR-100028-01 "Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics; Part 1" and TR-100028-02 "Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics; Part 2 " and is documented in the MAX Testing Co.,Ltd. quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for MAX Testing Co.,Ltd.

| Test item                                              | Uncertainty                                    |
|--------------------------------------------------------|------------------------------------------------|
| Bandwidth                                              | 1.1%                                           |
| Peak Output Power (Conducted) (Spectrum analyzer)      | 0.86 dB(10 MHz $\leq$ f < 3.6 GHz);            |
|                                                        | 1.38 dB(3.6 GHz $\leq$ f < 8 GHz)              |
| Peak Output Power (Conducted)(Power Sensor)            | 0.74 dB                                        |
| Power Spectral Density                                 | 0.74 dB(10 MHz $\leq$ f < 3.6 GHz);            |
|                                                        | 1.38 dB(3.6 GHz $\leq$ f < 8 GHz)              |
| Frequencies Stability                                  | 6.7 x 10 <sup>-8</sup> (Antenna couple method) |
|                                                        | 5.5x 10 <sup>-8</sup> (Conducted method)       |
| Conducted spurious emissions                           | 0.86 dB(10 MHz $\leq$ f < 3.6 GHz);            |
|                                                        | 1.40 dB(3.6 GHz $\leq$ f < 8 GHz)              |
|                                                        | 1.66 dB (8 GHz $\leq$ f < 26.5 GHz)            |
| Uncertainty for radio frequency (RBW <20 kHz)          | 3x10 <sup>-8</sup>                             |
| Temperature                                            | 0.4℃                                           |
| Humidity                                               | 2%                                             |
| Uncertainty for Radiation Emission test (9 kHz-30 MHz) | 3.44 dB                                        |
| Uncertainty for Radiation Emission test (30 MHz-1GHz)  | 4.70 dB (Antenna Polarize:V)                   |
|                                                        | 4.84 dB(Antenna Polarize:H)                    |
| Uncertainty for Radiation Emission test (1GHz-40GHz)   | 4.10 dB(1-6 GHz)                               |
|                                                        | 4.40 dB(6 GHz- 18 GHz)                         |
|                                                        | 3.54 dB(18 GHz- 26 GHz)                        |
|                                                        | 4.30 dB(26 GHz-40 GHz)                         |
| Uncertainty for Power line conduction emission test    | 3.34dB(150KHz-30MHz)                           |
|                                                        | 3.72dB(9KHz-150KHz)                            |

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

### 3.6 Equipments Used during the Test

| Conducted Emission        |                         |                      |            |              |            |
|---------------------------|-------------------------|----------------------|------------|--------------|------------|
| Test Equipment            | Manufacturer            | Model                | Serial No. | Date of Cal. | Due Date   |
| Shielding Room            | ZhongYu Electron        | 7.3(L)x3.1(W)x2.9(H) | MAX252     | 2024-10-27   | 2025-10-26 |
| EMI Test Receiver         | R&S                     | ESCI 7               | MAX552     | 2024-10-27   | 2025-10-26 |
| Coaxial Switch            | ANRITSU CORP            | MP59B                | MAX225     | 2024-10-27   | 2025-10-26 |
| ENV216 2-L-V-NETZNACHB.DE | ROHDE&SCHWARZ           | ENV216               | MAX226     | 2024-10-27   | 2025-10-26 |
| Coaxial Cable             | MAX                     | N/A                  | MAX227     | N/A          | N/A        |
| EMI Test Software         | AUDIX                   | E3                   | N/A        | N/A          | N/A        |
| Thermo meter              | KTJ                     | TA328                | MAX233     | 2024-10-27   | 2025-10-26 |
| Absorbing clamp           | Elektronik-Feinmechanik | MDS21                | MAX229     | 2024-10-27   | 2025-10-26 |
| LISN                      | R&S                     | ENV216               | 308        | 2024-10-27   | 2025-10-26 |
| LISN                      | R&S                     | ENV216               | 314        | 2024-10-27   | 2025-10-26 |

| Radiation Test equipment            |                             |                          |            |              |            |
|-------------------------------------|-----------------------------|--------------------------|------------|--------------|------------|
| Test Equipment                      | Manufacturer                | Model                    | Serial No. | Date of Cal. | Due Date   |
| 3m Semi- Anechoic Chamber           | ZhongYu Electron            | 9.2(L)*6.2(W)* 6.4(H)    | MAX250     | 2024-10-27   | 2025-10-26 |
| Control Room                        | ZhongYu Electron            | 6.2(L)*2.5(W)* 2.4(H)    | MAX251     | N/A          | N/A        |
| EMI Test Receiver                   | Rohde & Schwarz             | ESU26                    | MAX203     | 2024-10-27   | 2025-10-26 |
| BiConiLog Antenna                   | SCHWARZBECK MESS-ELEKTRONIK | VULB9163                 | MAX214     | 2024-10-27   | 2025-10-26 |
| Double -ridged waveguide horn       | SCHWARZBECK MESS-ELEKTRONIK | BBHA 9120 D              | MAX208     | 2024-10-27   | 2025-10-26 |
| Horn Antenna                        | ETS-LINDGREN                | 3160                     | MAX217     | 2024-10-27   | 2025-10-26 |
| EMI Test Software                   | AUDIX                       | E3                       | N/A        | N/A          | N/A        |
| Coaxial Cable                       | MAX                         | N/A                      | MAX213     | 2024-10-27   | 2025-10-26 |
| Coaxial Cable                       | MAX                         | N/A                      | MAX211     | 2024-10-27   | 2025-10-26 |
| Coaxial cable                       | MAX                         | N/A                      | MAX210     | 2024-10-27   | 2025-10-26 |
| Coaxial Cable                       | MAX                         | N/A                      | MAX212     | 2024-10-27   | 2025-10-26 |
| Amplifier(100kHz-3GHz)              | HP                          | 8347A                    | MAX204     | 2024-10-27   | 2025-10-26 |
| Amplifier(2GHz-20GHz)               | HP                          | 84722A                   | MAX206     | 2024-10-27   | 2025-10-26 |
| Amplifier (18-26GHz)                | Rohde & Schwarz             | AFS33-18002 650-30-8P-44 | MAX218     | 2024-10-27   | 2025-10-26 |
| Band filter                         | Amindeon                    | 82346                    | MAX219     | 2024-10-27   | 2025-10-26 |
| Power Meter                         | Anritsu                     | ML2495A                  | MAX540     | 2024-10-27   | 2025-10-26 |
| Power Sensor                        | Anritsu                     | MA2411B                  | MAX541     | 2024-10-27   | 2025-10-26 |
| Wideband Radio Communication Tester | Rohde & Schwarz             | CMW500                   | MAX575     | 2024-10-27   | 2025-10-26 |


|                                 |                 |           |        |            |            |
|---------------------------------|-----------------|-----------|--------|------------|------------|
| Splitter                        | Agilent         | 11636B    | MAX237 | 2024-10-27 | 2025-10-26 |
| Loop Antenna                    | ZHINAN          | ZN30900A  | MAX534 | 2024-10-27 | 2025-10-26 |
| Breitband<br>hornantenne        | SCHWARZBECK     | BBHA 9170 | MAX579 | 2024-10-27 | 2025-10-26 |
| Amplifier                       | TDK             | PA-02-02  | MAX574 | 2024-10-27 | 2025-10-26 |
| Amplifier                       | TDK             | PA-02-03  | MAX576 | 2024-10-27 | 2025-10-26 |
| PSA Series Spectrum<br>Analyzer | Rohde & Schwarz | FSP       | MAX578 | 2024-10-27 | 2025-10-26 |
| Antenna tower                   | SKET            | BK-4AT    | MAX589 | 2024-10-27 | 2025-10-26 |

| RF Conducted Test:                                   |              |                  |            |              |            |
|------------------------------------------------------|--------------|------------------|------------|--------------|------------|
| Test Equipment                                       | Manufacturer | Model            | Serial No. | Date of Cal. | Due Date   |
| MXA Signal Analyzer                                  | Agilent      | N9020A           | MAX566     | 2024-10-27   | 2025-10-26 |
| EMI Test Receiver                                    | R&S          | ESCI 7           | MAX552     | 2024-10-27   | 2025-10-26 |
| Spectrum Analyzer                                    | Agilent      | E4440A           | MAX533     | 2024-10-27   | 2025-10-26 |
| MXG vector Signal<br>Generator                       | Agilent      | N5182A           | MAX567     | 2024-10-27   | 2025-10-26 |
| ESG Analog Signal<br>Generator                       | Agilent      | E4428C           | MAX568     | 2024-10-27   | 2025-10-26 |
| USB RF Power<br>Sensor                               | DARE         | RPR3006W         | MAX569     | 2024-10-27   | 2025-10-26 |
| RF Switch Box                                        | Shongyi      | RFSW3003328      | MAX571     | 2024-10-27   | 2025-10-26 |
| Programmable<br>Constant Temp &<br>Humi Test Chamber | WEWON        | WHTH-150L-40-880 | MAX572     | 2024-10-27   | 2025-10-26 |

## 4 TEST CONDITIONS AND RESULTS

### 4.1 AC Power Conducted Emission

#### TEST CONFIGURATION



#### TEST PROCEDURE

- 1 The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10-2013.
- 2 Support equipment, if needed, was placed as per ANSI C63.10-2013
- 3 All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10-2013
- 4 The EUT received power from adapter, the adapter received AC120V/60Hz and AC 240V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
- 5 All support equipments received AC power from a second LISN, if any.
- 6 The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7 Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
- 8 During the above scans, the emissions were maximized by cable manipulation.

#### AC Power Conducted Emission Limit


For intentional device, according to § 15.207(a) AC Power Conducted Emission Limits is as following :

| Frequency range (MHz) | Limit (dBuV) |           |
|-----------------------|--------------|-----------|
|                       | Quasi-peak   | Average   |
| 0.15-0.5              | 66 to 56*    | 56 to 46* |
| 0.5-5                 | 56           | 46        |
| 5-30                  | 60           | 50        |

\* Decreases with the logarithm of the frequency.

#### TEST RESULTS

|                        |              |              |          |
|------------------------|--------------|--------------|----------|
| Power supply:          | AC 120V/60Hz | Polarization | L        |
| Built-in power supply: | A-150FGZ-24  | Test Mode:   | TX(5.2G) |




| No.  | Frequency (MHz) | Reading (dBuV) | Factor (dB) | Level (dBuV) | Limit (dBuV) | Margin (dB) | Detector | P/F |
|------|-----------------|----------------|-------------|--------------|--------------|-------------|----------|-----|
| 1    | 0.2040          | 26.36          | 16.72       | 43.08        | 63.45        | -20.37      | QP       | P   |
| 2    | 0.2085          | 16.15          | 16.72       | 32.87        | 53.26        | -20.39      | AVG      | P   |
| 3    | 0.4200          | 23.61          | 16.69       | 40.30        | 57.45        | -17.15      | QP       | P   |
| 4    | 0.4200          | 12.20          | 16.69       | 28.89        | 47.45        | -18.56      | AVG      | P   |
| 5    | 1.6755          | 9.96           | 16.53       | 26.49        | 46.00        | -19.51      | AVG      | P   |
| 6    | 1.8375          | 23.47          | 16.51       | 39.98        | 56.00        | -16.02      | QP       | P   |
| 7    | 3.0210          | 16.22          | 16.34       | 32.56        | 56.00        | -23.44      | QP       | P   |
| 8    | 3.0435          | 6.36           | 16.33       | 22.69        | 46.00        | -23.31      | AVG      | P   |
| 9    | 15.5580         | 28.45          | 18.77       | 47.22        | 60.00        | -12.78      | QP       | P   |
| 10 * | 15.8370         | 21.87          | 18.85       | 40.72        | 50.00        | -9.28       | AVG      | P   |

Note:1).Level (dBuV)= Reading (dBuV)+ Factor (dB)

2). Factor (dB)=insertion loss of LISN (dB) + Cable loss (dB)

3). Margin(dB) = Limit (dBuV) - Level (dBuV)

|                        |              |              |          |
|------------------------|--------------|--------------|----------|
| Power supply:          | AC 120V/60Hz | Polarization | N        |
| Built-in power supply: | A-150FGZ-24  | Test Mode:   | TX(5.2G) |




| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB) | Level (dBuV) | Limit (dBuV) | Margin (dB) | Detector | P/F |
|-----|-----------------|----------------|-------------|--------------|--------------|-------------|----------|-----|
| 1   | 0.2490          | 13.66          | 17.53       | 31.19        | 51.79        | -20.60      | AVG      | P   |
| 2   | 0.2760          | 24.62          | 17.52       | 42.14        | 60.94        | -18.80      | QP       | P   |
| 3   | 1.7970          | 21.30          | 17.48       | 38.78        | 56.00        | -17.22      | QP       | P   |
| 4   | 1.8150          | 9.95           | 17.48       | 27.43        | 46.00        | -18.57      | AVG      | P   |
| 5   | 7.3320          | 19.99          | 17.75       | 37.74        | 60.00        | -22.26      | QP       | P   |
| 6   | 7.3320          | 13.48          | 17.75       | 31.23        | 50.00        | -18.77      | AVG      | P   |
| 7   | 13.8390         | 22.83          | 18.72       | 41.55        | 50.00        | -8.45       | AVG      | P   |
| 8   | 13.9020         | 30.41          | 18.73       | 49.14        | 60.00        | -10.86      | QP       | P   |
| 9 * | 15.2205         | 34.28          | 18.93       | 53.21        | 60.00        | -6.79       | QP       | P   |
| 10  | 18.2580         | 21.79          | 19.16       | 40.95        | 50.00        | -9.05       | AVG      | P   |

Note: 1). Level (dBuV) = Reading (dBuV) + Factor (dB)

2). Factor (dB) = insertion loss of LISN (dB) + Cable loss (dB)

3). Margin (dB) = Limit (dBuV) - Level (dBuV)

|                        |              |              |          |
|------------------------|--------------|--------------|----------|
| Power supply:          | AC 120V/60Hz | Polarization | L        |
| Built-in power supply: | A-150FGZ-24  | Test Mode:   | TX(5.8G) |




| No.  | Frequency (MHz) | Reading (dBuV) | Factor (dB) | Level (dBuV) | Limit (dBuV) | Margin (dB) | Detector | P/F |
|------|-----------------|----------------|-------------|--------------|--------------|-------------|----------|-----|
| 1    | 0.2130          | 26.76          | 16.72       | 43.48        | 63.09        | -19.61      | QP       | P   |
| 2    | 0.2130          | 17.54          | 16.72       | 34.26        | 53.09        | -18.83      | AVG      | P   |
| 3    | 1.6845          | 21.99          | 16.53       | 38.52        | 56.00        | -17.48      | QP       | P   |
| 4    | 1.7115          | 9.67           | 16.53       | 26.20        | 46.00        | -19.80      | AVG      | P   |
| 5    | 2.9895          | 15.05          | 16.34       | 31.39        | 56.00        | -24.61      | QP       | P   |
| 6    | 3.6735          | 3.58           | 16.26       | 19.84        | 46.00        | -26.16      | AVG      | P   |
| 7    | 8.2005          | 5.38           | 16.77       | 22.15        | 50.00        | -27.85      | AVG      | P   |
| 8    | 8.2680          | 14.14          | 16.78       | 30.92        | 60.00        | -29.08      | QP       | P   |
| 9    | 14.2575         | 13.25          | 18.40       | 31.65        | 50.00        | -18.35      | AVG      | P   |
| 10 * | 14.7075         | 25.15          | 18.52       | 43.67        | 60.00        | -16.33      | QP       | P   |

Note:1).Level (dBuV)= Reading (dBuV)+ Factor (dB)

2). Factor (dB)=insertion loss of LISN (dB) + Cable loss (dB)

3). Margin(dB) = Limit (dBuV) - Level (dBuV)

|                        |              |              |          |
|------------------------|--------------|--------------|----------|
| Power supply:          | AC 120V/60Hz | Polarization | N        |
| Built-in power supply: | A-150FGZ-24  | Test Mode:   | TX(5.8G) |




| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB) | Level (dBuV) | Limit (dBuV) | Margin (dB) | Detector | P/F |
|-----|-----------------|----------------|-------------|--------------|--------------|-------------|----------|-----|
| 1   | 0.2085          | 26.42          | 17.53       | 43.95        | 63.26        | -19.31      | QP       | P   |
| 2 * | 0.2130          | 20.06          | 17.53       | 37.59        | 53.09        | -15.50      | AVG      | P   |
| 3   | 1.8150          | 20.64          | 17.48       | 38.12        | 56.00        | -17.88      | QP       | P   |
| 4   | 1.8150          | 9.90           | 17.48       | 27.38        | 46.00        | -18.62      | AVG      | P   |
| 5   | 8.1240          | 3.72           | 17.87       | 21.59        | 50.00        | -28.41      | AVG      | P   |
| 6   | 8.1915          | 15.79          | 17.88       | 33.67        | 60.00        | -26.33      | QP       | P   |
| 7   | 14.2485         | 13.41          | 18.79       | 32.20        | 50.00        | -17.80      | AVG      | P   |
| 8   | 14.5410         | 20.82          | 18.83       | 39.65        | 60.00        | -20.35      | QP       | P   |
| 9   | 22.8974         | 10.85          | 19.08       | 29.93        | 50.00        | -20.07      | AVG      | P   |
| 10  | 26.3940         | 19.03          | 19.01       | 38.04        | 60.00        | -21.96      | QP       | P   |

Note:1).Level (dBuV)= Reading (dBuV)+ Factor (dB)

2). Factor (dB)=insertion loss of LISN (dB) + Cable loss (dB)

3). Margin(dB) = Limit (dBuV) - Level (dBuV)

|                        |              |              |          |
|------------------------|--------------|--------------|----------|
| Power supply:          | AC 120V/60Hz | Polarization | L        |
| Built-in power supply: | AM150-B24    | Test Mode:   | TX(5.2G) |




| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB) | Level (dBuV) | Limit (dBuV) | Margin (dB) | Detector | P/F |
|-----|-----------------|----------------|-------------|--------------|--------------|-------------|----------|-----|
| 1 * | 0.4380          | 24.64          | 10.03       | 34.67        | 47.10        | -12.43      | AVG      | P   |
| 2   | 0.4425          | 33.35          | 10.03       | 43.38        | 57.01        | -13.63      | QP       | P   |
| 3   | 0.5505          | 23.74          | 10.03       | 33.77        | 56.00        | -22.23      | QP       | P   |
| 4   | 0.8970          | 24.78          | 10.04       | 34.82        | 56.00        | -21.18      | QP       | P   |
| 5   | 1.2075          | 11.69          | 10.04       | 21.73        | 46.00        | -24.27      | AVG      | P   |
| 6   | 1.3110          | 22.74          | 10.04       | 32.78        | 56.00        | -23.22      | QP       | P   |
| 7   | 1.7700          | 12.63          | 10.05       | 22.68        | 46.00        | -23.32      | AVG      | P   |
| 8   | 1.8690          | 22.81          | 10.05       | 32.86        | 56.00        | -23.14      | QP       | P   |
| 9   | 2.6295          | 20.74          | 10.05       | 30.79        | 56.00        | -25.21      | QP       | P   |
| 10  | 3.1020          | 9.15           | 10.05       | 19.20        | 46.00        | -26.80      | AVG      | P   |
| 11  | 4.4610          | 3.42           | 10.08       | 13.50        | 46.00        | -32.50      | AVG      | P   |

Note:1).Level (dBuV)= Reading (dBuV)+ Factor (dB)

2). Factor (dB)=insertion loss of LISN (dB) + Cable loss (dB)

3). Margin(dB) = Limit (dBuV) - Level (dBuV)


|                        |              |              |          |
|------------------------|--------------|--------------|----------|
| Power supply:          | AC 120V/60Hz | Polarization | N        |
| Built-in power supply: | AM150-B24    | Test Mode:   | TX(5.2G) |



| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB) | Level (dBuV) | Limit (dBuV) | Margin (dB) | Detector | P/F |
|-----|-----------------|----------------|-------------|--------------|--------------|-------------|----------|-----|
| 1   | 0.2355          | 31.57          | 10.00       | 41.57        | 62.25        | -20.68      | QP       | P   |
| 2   | 0.4335          | 31.52          | 10.00       | 41.52        | 57.19        | -15.67      | QP       | P   |
| 3 * | 0.4380          | 23.44          | 10.00       | 33.44        | 47.10        | -13.66      | AVG      | P   |
| 4   | 0.6900          | 27.46          | 10.00       | 37.46        | 56.00        | -18.54      | QP       | P   |
| 5   | 0.8610          | 16.19          | 10.01       | 26.20        | 46.00        | -19.80      | AVG      | P   |
| 6   | 1.2345          | 25.98          | 10.01       | 35.99        | 56.00        | -20.01      | QP       | P   |
| 7   | 1.2705          | 14.29          | 10.01       | 24.30        | 46.00        | -21.70      | AVG      | P   |
| 8   | 1.6845          | 24.46          | 10.02       | 34.48        | 56.00        | -21.52      | QP       | P   |
| 9   | 1.7115          | 12.14          | 10.02       | 22.16        | 46.00        | -23.84      | AVG      | P   |
| 10  | 2.2065          | 12.28          | 10.02       | 22.30        | 46.00        | -23.70      | AVG      | P   |
| 11  | 2.2244          | 24.06          | 10.02       | 34.08        | 56.00        | -21.92      | QP       | P   |
| 12  | 3.6105          | 8.80           | 10.03       | 18.83        | 46.00        | -27.17      | AVG      | P   |

Note: 1). Level (dBuV) = Reading (dBuV) + Factor (dB)  
 2). Factor (dB) = insertion loss of LISN (dB) + Cable loss (dB)  
 3). Margin (dB) = Limit (dBuV) - Level (dBuV)

|                        |              |              |          |
|------------------------|--------------|--------------|----------|
| Power supply:          | AC 120V/60Hz | Polarization | L        |
| Built-in power supply: | AM150-B24    | Test Mode:   | TX(5.8G) |




| No. | Frequency (MHz) | Reading (dBμV) | Factor (dB) | Level (dBμV) | Limit (dBμV) | Margin (dB) | Detector | P/F |
|-----|-----------------|----------------|-------------|--------------|--------------|-------------|----------|-----|
| 1   | 0.4110          | 17.86          | 10.03       | 27.89        | 47.63        | -19.74      | AVG      | P   |
| 2   | 0.4200          | 27.22          | 10.03       | 37.25        | 57.45        | -20.20      | QP       | P   |
| 3 * | 0.6134          | 27.31          | 10.03       | 37.34        | 56.00        | -18.66      | QP       | P   |
| 4   | 1.1220          | 25.23          | 10.04       | 35.27        | 56.00        | -20.73      | QP       | P   |
| 5   | 1.6620          | 25.64          | 10.05       | 35.69        | 56.00        | -20.31      | QP       | P   |
| 6   | 2.9400          | 14.03          | 10.05       | 24.08        | 46.00        | -21.92      | AVG      | P   |
| 7   | 3.1695          | 24.73          | 10.05       | 34.78        | 56.00        | -21.22      | QP       | P   |
| 8   | 4.6860          | 14.33          | 10.08       | 24.41        | 46.00        | -21.59      | AVG      | P   |
| 9   | 4.9785          | 25.09          | 10.09       | 35.18        | 56.00        | -20.82      | QP       | P   |

Note:1).Level (dBμV)= Reading (dBμV)+ Factor (dB)

2). Factor (dB)=insertion loss of LISN (dB) + Cable loss (dB)

3). Margin(dB) = Limit (dBμV) - Level (dBμV)

|                        |              |              |          |
|------------------------|--------------|--------------|----------|
| Power supply:          | AC 120V/60Hz | Polarization | N        |
| Built-in power supply: | AM150-B24    | Test Mode:   | TX(5.8G) |



| No. | Frequency (MHz) | Reading (dBμV) | Factor (dB) | Level (dBμV) | Limit (dBμV) | Margin (dB) | Detector | P/F |
|-----|-----------------|----------------|-------------|--------------|--------------|-------------|----------|-----|
| 1   | 0.3840          | 26.67          | 10.00       | 36.67        | 58.19        | -21.52      | QP       | P   |
| 2 * | 0.6090          | 15.10          | 10.00       | 25.10        | 46.00        | -20.90      | AVG      | P   |
| 3   | 0.8790          | 24.64          | 10.01       | 34.65        | 56.00        | -21.35      | QP       | P   |
| 4   | 1.0184          | 12.79          | 10.01       | 22.80        | 46.00        | -23.20      | AVG      | P   |
| 5   | 1.1849          | 21.69          | 10.01       | 31.70        | 56.00        | -24.30      | QP       | P   |
| 6   | 1.6620          | 22.05          | 10.02       | 32.07        | 56.00        | -23.93      | QP       | P   |
| 7   | 4.4565          | 12.96          | 10.05       | 23.01        | 46.00        | -22.99      | AVG      | P   |
| 8   | 4.8390          | 20.22          | 10.06       | 30.28        | 56.00        | -25.72      | QP       | P   |
| 9   | 9.6765          | 24.01          | 10.10       | 34.11        | 60.00        | -25.89      | QP       | P   |
| 10  | 9.8025          | 14.85          | 10.10       | 24.95        | 50.00        | -25.05      | AVG      | P   |
| 11  | 10.8195         | 14.38          | 10.10       | 24.48        | 50.00        | -25.52      | AVG      | P   |

Note: 1). Level (dBμV) = Reading (dBμV) + Factor (dB)

2). Factor (dB) = insertion loss of LISN (dB) + Cable loss (dB)

3). Margin (dB) = Limit (dBμV) - Level (dBμV)

## 4.2 Radiated Emission

### Limit

The maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

- (1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (4) For transmitters operating in the 5.725-5.85 GHz band: All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

#### Undesirable emission limits

| Requirement  | Limit(EIRP)     | Limit (Field strength at 3m) <sup>Note1</sup> |
|--------------|-----------------|-----------------------------------------------|
| 15.407(b)(1) | PK:-27(dBm/MHz) | PK:68.2(dBμV/m)                               |
| 15.407(b)(2) |                 |                                               |
| 15.407(b)(3) |                 |                                               |
| 15.407(b)(4) |                 |                                               |

Note1: The following formula is used to convert the equipment isotropic radiated power (eirp) to field strength:

$$E = \frac{1000000\sqrt{30P}}{3} \mu\text{V/m, where P is the eirp (Watts)}$$


- (5) Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in §15.209
- (6) In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a)

#### Radiated emission limits


| Frequency (MHz) | Distance (Meters) | Radiated (dBμV/m)                          | Radiated (μV/m)       |
|-----------------|-------------------|--------------------------------------------|-----------------------|
| 0.009-0.49      | 3                 | $20\log(2400/F(\text{KHz}))+40\log(300/3)$ | $2400/F(\text{KHz})$  |
| 0.49-1.705      | 3                 | $20\log(24000/F(\text{KHz}))+40\log(30/3)$ | $24000/F(\text{KHz})$ |
| 1.705-30        | 3                 | $20\log(30)+40\log(30/3)$                  | 30                    |
| 30-88           | 3                 | 40.0                                       | 100                   |
| 88-216          | 3                 | 43.5                                       | 150                   |
| 216-960         | 3                 | 46.0                                       | 200                   |
| Above 960       | 3                 | 54.0                                       | 500                   |

## **TEST CONFIGURATION**


(A) Radiated Emission Test Set-Up, Frequency Below 30MHz



(B) Radiated Emission Test Set-Up, Frequency below 1000MHz



(C) Radiated Emission Test Set-Up, Frequency above 1000MHz



## **TEST PROCEDURE**

- Below 1GHz measurement the EUT is placed on a turntable which is 0.8m above ground plane, and above 1GHz measurement EUT was placed on a low permittivity and low loss tangent turn table which is 1.5m above ground plane.
- Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0° to 360° to acquire the highest emissions from EUT
- And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
- Repeat above procedures until all frequency measurements have been completed.
- Radiated emission test frequency band from 9KHz to 40GHz.
- The distance between test antenna and EUT as following table states:

| Test Frequency range | Test Antenna Type   | Test Distance |
|----------------------|---------------------|---------------|
| 9KHz-30MHz           | Active Loop Antenna | 3             |
| 30MHz-1GHz           | Bilog Antenna       | 3             |
| 1GHz-18GHz           | Horn Antenna        | 3             |
| 18GHz-25GHz          | Horn Antenna        | 1             |

- Setting test receiver/spectrum as following table states:

| Test Frequency range | Test Receiver/Spectrum Setting                                                                            | Detector |
|----------------------|-----------------------------------------------------------------------------------------------------------|----------|
| 9KHz-150KHz          | RBW=200Hz/VBW=3KHz, Sweep time=Auto                                                                       | QP       |
| 150KHz-30MHz         | RBW=9KHz/VBW=100KHz, Sweep time=Auto                                                                      | QP       |
| 30MHz-1GHz           | RBW=120KHz/VBW=1000KHz, Sweep time=Auto                                                                   | QP       |
| 1GHz-40GHz           | Peak Value: RBW=1MHz/VBW=3MHz,<br>Sweep time=Auto<br>Average Value: RBW=1MHz/VBW=10Hz,<br>Sweep time=Auto | Peak     |


## **TEST RESULTS**

Between 9KHz – 30MHz

The emission from 9 kHz to 30MHz was pre-tested and found the result was 20dB lower than the limit, and according to 15.31(o) & RSS-Gen 6.13, the test result no need to reported.

**For 30MHz-1GHz**

|                        |             |                    |              |
|------------------------|-------------|--------------------|--------------|
| Temperature:           | 25℃         | Relative Humidity: | 54%          |
| Pressure:              | 101 kPa     | Test Voltage:      | AC 120V/60Hz |
| Test Mode:             | TX(5.2G)    |                    |              |
| Built-in power supply: | A-150FGZ-24 |                    |              |




| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | Height (cm) | Azimuth (deg.) | P/F |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|-------------|----------------|-----|
| 1 * | 49.8813         | 48.95          | -16.39        | 32.56          | 40.00          | -7.44       | peak     | 100         | 360            | P   |
| 2   | 129.9225        | 47.51          | -17.21        | 30.30          | 43.50          | -13.20      | peak     | 100         | 360            | P   |
| 3   | 232.5318        | 51.87          | -18.35        | 33.52          | 46.00          | -12.48      | peak     | 100         | 360            | P   |
| 4   | 558.7300        | 46.19          | -9.05         | 37.14          | 46.00          | -8.86       | peak     | 100         | 360            | P   |
| 5   | 682.3482        | 43.52          | -6.69         | 36.83          | 46.00          | -9.17       | peak     | 100         | 360            | P   |
| 6   | 962.1621        | 46.13          | -3.07         | 43.06          | 54.00          | -10.94      | peak     | 100         | 360            | P   |

Note:1).Level (dBuV/m)= Reading (dBuV)+ Factor (dB/m)

2). Factor(dB/m)=Antenna Factor (dB/m) + Cable loss (dB) - Pre Amplifier gain (dB)

3). Margin(dB) = Limit (dBuV/m) - Level (dBuV/m)




| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | Height (cm) | Azimuth (deg.) | P/F |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|-------------|----------------|-----|
| 1   | 171.3925        | 50.82          | -16.41        | 34.41          | 43.50          | -9.09       | peak     | 100         | 360            | P   |
| 2   | 241.6759        | 53.41          | -17.69        | 35.72          | 46.00          | -10.28      | peak     | 100         | 360            | P   |
| 3   | 267.5452        | 53.82          | -16.66        | 37.16          | 46.00          | -8.84       | peak     | 100         | 360            | P   |
| 4   | 403.2500        | 51.40          | -13.02        | 38.38          | 46.00          | -7.62       | peak     | 100         | 360            | P   |
| 5 * | 682.3482        | 45.67          | -6.69         | 38.98          | 46.00          | -7.02       | peak     | 100         | 360            | P   |
| 6   | 952.0937        | 36.75          | -3.03         | 33.72          | 46.00          | -12.28      | peak     | 100         | 360            | P   |

Note: 1). Level (dBuV/m) = Reading (dBuV) + Factor (dB/m)

2). Factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) - Pre Amplifier gain (dB)

3). Margin (dB) = Limit (dBuV/m) - Level (dBuV/m)

|                        |             |                    |              |
|------------------------|-------------|--------------------|--------------|
| Temperature:           | 25°C        | Relative Humidity: | 54%          |
| Pressure:              | 101 kPa     | Test Voltage:      | AC 120V/60Hz |
| Test Mode:             | TX(5.8G)    |                    |              |
| Built-in power supply: | A-150FGZ-24 |                    |              |




| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | Height (cm) | Azimuth (deg.) | P/F |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|-------------|----------------|-----|
| 1   | 171.3925        | 51.32          | -16.41        | 34.91          | 43.50          | -8.59       | peak     | 100         | 360            | P   |
| 2   | 241.6759        | 53.91          | -17.69        | 36.22          | 46.00          | -9.78       | peak     | 100         | 360            | P   |
| 3   | 267.5452        | 53.32          | -16.66        | 36.66          | 46.00          | -9.34       | peak     | 100         | 360            | P   |
| 4   | 403.2500        | 50.90          | -13.02        | 37.88          | 46.00          | -8.12       | peak     | 100         | 360            | P   |
| 5 * | 682.3482        | 44.67          | -6.69         | 37.98          | 46.00          | -8.02       | peak     | 100         | 360            | P   |
| 6   | 839.1816        | 37.58          | -4.29         | 33.29          | 46.00          | -12.71      | peak     | 100         | 360            | P   |

Note: 1). Level (dBuV/m) = Reading (dBuV) + Factor (dB/m)

2). Factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) - Pre Amplifier gain (dB)

3). Margin (dB) = Limit (dBuV/m) - Level (dBuV/m)




| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | Height (cm) | Azimuth (deg.) | P/F |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|-------------|----------------|-----|
| 1 * | 49.8813         | 48.45          | -16.39        | 32.06          | 40.00          | -7.94       | peak     | 100         | 360            | P   |
| 2   | 61.9949         | 45.55          | -17.35        | 28.20          | 40.00          | -11.80      | peak     | 100         | 360            | P   |
| 3   | 93.1131         | 48.74          | -20.41        | 28.33          | 43.50          | -15.17      | peak     | 100         | 360            | P   |
| 4   | 129.9225        | 47.01          | -17.21        | 29.80          | 43.50          | -13.70      | peak     | 100         | 360            | P   |
| 5   | 232.5318        | 51.37          | -18.35        | 33.02          | 46.00          | -12.98      | peak     | 100         | 360            | P   |
| 6   | 558.7300        | 45.19          | -9.05         | 36.14          | 46.00          | -9.86       | peak     | 100         | 360            | P   |

Note: 1). Level (dBuV/m) = Reading (dBuV) + Factor (dB/m)

2). Factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) - Pre Amplifier gain (dB)

3). Margin (dB) = Limit (dBuV/m) - Level (dBuV/m)

|                        |             |                    |              |
|------------------------|-------------|--------------------|--------------|
| Temperature:           | 25°C        | Relative Humidity: | 54%          |
| Pressure:              | 101 kPa     | Test Voltage:      | AC 120V/60Hz |
| Test Mode:             | TX(5.2G)    |                    |              |
| Built-in power supply: | A-150FGZ-24 |                    |              |




| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | Height (cm) | Azimuth (deg.) | P/F |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|-------------|----------------|-----|
| 1 * | 49.8813         | 48.45          | -16.39        | 32.06          | 40.00          | -7.94       | peak     | 100         | 360            | P   |
| 2   | 85.8983         | 46.29          | -20.64        | 25.65          | 40.00          | -14.35      | peak     | 100         | 360            | P   |
| 3   | 129.9225        | 46.51          | -17.21        | 29.30          | 43.50          | -14.20      | peak     | 100         | 360            | P   |
| 4   | 232.5318        | 50.87          | -18.35        | 32.52          | 46.00          | -13.48      | peak     | 100         | 360            | P   |
| 5   | 528.2458        | 42.40          | -9.91         | 32.49          | 46.00          | -13.51      | peak     | 100         | 360            | P   |
| 6   | 682.3482        | 42.02          | -6.69         | 35.33          | 46.00          | -10.67      | peak     | 100         | 360            | P   |

Note:1).Level (dBuV/m)= Reading (dBuV)+ Factor (dB/m)

2). Factor(dB/m)=Antenna Factor (dB/m) + Cable loss (dB) - Pre Amplifier gain (dB)

3). Margin(dB) = Limit (dBuV/m) - Level (dBuV/m)




| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | Height (cm) | Azimuth (deg.) | P/F |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|-------------|----------------|-----|
| 1   | 171.3925        | 50.32          | -16.41        | 33.91          | 43.50          | -9.59       | peak     | 100         | 360            | P   |
| 2   | 193.0944        | 52.13          | -18.94        | 33.19          | 43.50          | -10.31      | peak     | 100         | 360            | P   |
| 3   | 241.6759        | 52.91          | -17.69        | 35.22          | 46.00          | -10.78      | peak     | 100         | 360            | P   |
| 4   | 267.5452        | 52.32          | -16.66        | 35.66          | 46.00          | -10.34      | peak     | 100         | 360            | P   |
| 5   | 403.2500        | 49.40          | -13.02        | 36.38          | 46.00          | -9.62       | peak     | 100         | 360            | P   |
| 6 * | 682.3482        | 43.17          | -6.69         | 36.48          | 46.00          | -9.52       | peak     | 100         | 360            | P   |

Note:1).Level (dBuV/m)= Reading (dBuV)+ Factor (dB/m)

2). Factor(dB/m)=Antenna Factor (dB/m) + Cable loss (dB) - Pre Amplifier gain (dB)

3). Margin(dB) = Limit (dBuV/m) - Level (dBuV/m)

|                        |             |                    |              |
|------------------------|-------------|--------------------|--------------|
| Temperature:           | 25℃         | Relative Humidity: | 54%          |
| Pressure:              | 101 kPa     | Test Voltage:      | AC 120V/60Hz |
| Test Mode:             | TX(5.8G)    |                    |              |
| Built-in power supply: | A-150FGZ-24 |                    |              |




| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | Height (cm) | Azimuth (deg.) | P/F |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|-------------|----------------|-----|
| 1 * | 49.8813         | 47.95          | -16.39        | 31.56          | 40.00          | -8.44       | peak     | 100         | 360            | P   |
| 2   | 61.9949         | 45.05          | -17.35        | 27.70          | 40.00          | -12.30      | peak     | 100         | 360            | P   |
| 3   | 528.2458        | 41.90          | -9.91         | 31.99          | 46.00          | -14.01      | peak     | 100         | 360            | P   |
| 4   | 558.7300        | 43.69          | -9.05         | 34.64          | 46.00          | -11.36      | peak     | 100         | 360            | P   |
| 5   | 682.3482        | 41.52          | -6.69         | 34.83          | 46.00          | -11.17      | peak     | 100         | 360            | P   |
| 6   | 962.1621        | 44.63          | -3.07         | 41.56          | 54.00          | -12.44      | peak     | 100         | 360            | P   |

Note:1).Level (dBuV/m)= Reading (dBuV)+ Factor (dB/m)

2). Factor(dB/m)=Antenna Factor (dB/m) + Cable loss (dB) - Pre Amplifier gain (dB)

3). Margin(dB) = Limit (dBuV/m) - Level (dBuV/m)




| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | Height (cm) | Azimuth (deg.) | P/F |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|-------------|----------------|-----|
| 1   | 171.3925        | 50.82          | -16.41        | 34.41          | 43.50          | -9.09       | peak     | 100         | 360            | P   |
| 2   | 193.0944        | 52.63          | -18.94        | 33.69          | 43.50          | -9.81       | peak     | 100         | 360            | P   |
| 3   | 241.6759        | 53.41          | -17.69        | 35.72          | 46.00          | -10.28      | peak     | 100         | 360            | P   |
| 4   | 267.5452        | 52.82          | -16.66        | 36.16          | 46.00          | -9.84       | peak     | 100         | 360            | P   |
| 5   | 403.2500        | 49.90          | -13.02        | 36.88          | 46.00          | -9.12       | peak     | 100         | 360            | P   |
| 6 * | 682.3482        | 43.67          | -6.69         | 36.98          | 46.00          | -9.02       | peak     | 100         | 360            | P   |

Note: 1). Level (dBuV/m) = Reading (dBuV) + Factor (dB/m)

2). Factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) - Pre Amplifier gain (dB)

3). Margin (dB) = Limit (dBuV/m) - Level (dBuV/m)

|                        |           |                    |              |
|------------------------|-----------|--------------------|--------------|
| Temperature:           | 25°C      | Relative Humidity: | 54%          |
| Pressure:              | 101 kPa   | Test Voltage:      | AC 120V/60Hz |
| Test Mode:             | TX(5.2G)  |                    |              |
| Built-in power supply: | AM150-B24 |                    |              |




| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | Height (cm) | Azimuth (deg.) | P/F |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|-------------|----------------|-----|
| 1   | 135.9822        | 36.22          | -16.94        | 19.28          | 43.50          | -24.22      | peak     | 100         | 360            | P   |
| 2   | 432.5457        | 35.02          | -12.16        | 22.86          | 46.00          | -23.14      | peak     | 100         | 360            | P   |
| 3   | 528.2458        | 36.26          | -9.91         | 26.35          | 46.00          | -19.65      | peak     | 100         | 360            | P   |
| 4   | 601.4265        | 39.89          | -7.83         | 32.06          | 46.00          | -13.94      | peak     | 100         | 360            | P   |
| 5 * | 793.3960        | 49.45          | -4.69         | 44.76          | 46.00          | -1.24       | peak     | 100         | 360            | P   |
| 6   | 912.8620        | 38.98          | -3.59         | 35.39          | 46.00          | -10.61      | peak     | 100         | 360            | P   |

Note:1).Level (dBuV/m)= Reading (dBuV)+ Factor (dB/m)

2). Factor(dB/m)=Antenna Factor (dB/m) + Cable loss (dB) - Pre Amplifier gain (dB)

3). Margin(dB) = Limit (dBuV/m) - Level (dBuV/m)




| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | Height (cm) | Azimuth (deg.) | P/F |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|-------------|----------------|-----|
| 1   | 52.7600         | 28.08          | -16.63        | 11.45          | 40.00          | -28.55      | peak     | 100         | 0              | P   |
| 2   | 56.7917         | 27.64          | -16.91        | 10.73          | 40.00          | -29.27      | peak     | 100         | 0              | P   |
| 3   | 144.8418        | 28.15          | -16.36        | 11.79          | 43.50          | -31.71      | peak     | 100         | 0              | P   |
| 4   | 397.6334        | 36.25          | -13.16        | 23.09          | 46.00          | -22.91      | peak     | 100         | 0              | P   |
| 5   | 625.0780        | 40.60          | -7.45         | 33.15          | 46.00          | -12.85      | peak     | 100         | 0              | P   |
| 6 * | 793.3960        | 42.70          | -4.69         | 38.01          | 46.00          | -7.99       | peak     | 100         | 0              | P   |

Note: 1). Level (dBuV/m) = Reading (dBuV) + Factor (dB/m)

2). Factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) - Pre Amplifier gain (dB)

3). Margin (dB) = Limit (dBuV/m) - Level (dBuV/m)

|                        |           |                    |              |
|------------------------|-----------|--------------------|--------------|
| Temperature:           | 25°C      | Relative Humidity: | 54%          |
| Pressure:              | 101 kPa   | Test Voltage:      | AC 120V/60Hz |
| Test Mode:             | TX(5.8G)  |                    |              |
| Built-in power supply: | AM150-B24 |                    |              |




| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|
| 1   | 58.8185         | 49.82          | -16.98        | 32.84          | 40.00          | -7.16       | peak     |
| 2   | 99.5279         | 54.62          | -19.92        | 34.70          | 43.50          | -8.80       | peak     |
| 3 * | 131.7576        | 57.43          | -17.13        | 40.30          | 43.50          | -3.20       | peak     |
| 4   | 319.9368        | 41.87          | -15.07        | 26.80          | 46.00          | -19.20      | peak     |
| 5   | 401.8383        | 46.15          | -13.04        | 33.11          | 46.00          | -12.89      | peak     |
| 6   | 807.4289        | 34.00          | -4.55         | 29.45          | 46.00          | -16.55      | peak     |

Note:1).Level (dBuV/m)= Reading (dBuV)+ Factor (dB/m)

2). Factor(dB/m)=Antenna Factor (dB/m) + Cable loss (dB) - Pre Amplifier gain (dB)

3). Margin(dB) = Limit (dBuV/m) - Level (dBuV/m)



Note: 1). Level (dBuV/m) = Reading (dBuV) + Factor (dB/m)

2). Factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) - Pre Amplifier gain (dB)

3). Margin (dB) = Limit (dBuV/m) - Level (dBuV/m)

**For 1GHz to 40GHz**

Note: All 802.11a/n/ac (HT20), 802.11n/ac (HT40) and 802.11ac (HT80) modes have been tested for above 1GHz test, only the worst case 802.11a(HT20) was recorded.

**U-NII 1 & 802.11a Mode (above 1GHz)**

| Tested Channel | Frequency (MHz) | Emission Limit (dBuV/m) | Detector Mode | ANT Pol | Limit (dBuV/m) | Margin (dB) | Raw Value (dBuV) | Antenna Factor (dB/m) | Cable Factor (dB) | Pre-amplifier (dB) | Correction Factor (dB/m) |
|----------------|-----------------|-------------------------|---------------|---------|----------------|-------------|------------------|-----------------------|-------------------|--------------------|--------------------------|
| 36<br>5158MHz  | 5150.00         | 53.24                   | PK            | H       | 68.20          | 14.96       | 50.25            | 32.40                 | 5.11              | 34.52              | 2.99                     |
|                | 5150.00         | 45.51                   | AV            | H       | 54.00          | 8.49        | 42.52            | 32.40                 | 5.11              | 34.52              | 2.99                     |
|                | 10360.00        | 39.72                   | PK            | H       | 68.20          | 28.48       | 32.56            | 36.51                 | 5.86              | 35.21              | 7.16                     |
|                | --              | --                      | --            | --      | --             | --          | --               | --                    | --                | --                 | --                       |
| 40<br>5200MHz  | 10400.00        | 40.94                   | PK            | H       | 68.20          | 27.26       | 33.65            | 36.58                 | 5.96              | 35.25              | 7.29                     |
|                | --              | --                      | --            | --      | --             | --          | --               | --                    | --                | --                 | --                       |
| 48<br>5240MHz  | 5350.50         | 39.56                   | PK            | H       | 68.20          | 28.64       | 36.52            | 32.45                 | 5.22              | 34.63              | 3.04                     |
|                | 10480.00        | 38.00                   | PK            | H       | 68.20          | 30.20       | 30.65            | 36.68                 | 6.21              | 35.54              | 7.35                     |
|                | --              | --                      | --            | --      | --             | --          | --               | --                    | --                | --                 | --                       |

| Tested Channel | Frequency (MHz) | Emission Limit (dBuV/m) | Detector Mode | ANT Pol | Limit (dBuV/m) | Margin (dB) | Raw Value (dBuV) | Antenna Factor (dB/m) | Cable Factor (dB) | Pre-amplifier (dB) | Correction Factor (dB/m) |
|----------------|-----------------|-------------------------|---------------|---------|----------------|-------------|------------------|-----------------------|-------------------|--------------------|--------------------------|
| 36<br>5158MHz  | 5150.00         | 54.25                   | PK            | V       | 68.20          | 13.95       | 51.26            | 32.40                 | 5.11              | 34.52              | 2.99                     |
|                | 5150.00         | 43.35                   | AV            | V       | 54.00          | 10.65       | 40.36            | 32.40                 | 5.11              | 34.52              | 2.99                     |
|                | 10360.00        | 43.40                   | PK            | V       | 68.20          | 24.80       | 36.24            | 36.51                 | 5.86              | 35.21              | 7.16                     |
|                | --              | --                      | --            | --      | --             | --          | --               | --                    | --                | --                 | --                       |
| 40<br>5200MHz  | 10400.00        | 39.85                   | PK            | V       | 68.20          | 28.35       | 32.56            | 36.58                 | 5.96              | 35.25              | 7.29                     |
|                | --              | --                      | --            | --      | --             | --          | --               | --                    | --                | --                 | --                       |
| 48<br>5240MHz  | 5350.50         | 44.30                   | PK            | V       | 68.20          | 23.90       | 41.26            | 32.45                 | 5.22              | 34.63              | 3.04                     |
|                | 10480.00        | 43.77                   | PK            | V       | 68.20          | 24.43       | 36.42            | 36.68                 | 6.21              | 35.54              | 7.35                     |
|                | --              | --                      | --            | --      | --             | --          | --               | --                    | --                | --                 | --                       |

**U-NII 3 & 802.11a Mode (above 1GHz)**

| Tested Channel | Frequency (MHz) | Emission Limit (dBuV/m) | Detector Mode | ANT Pol | Limit (dBuV/m) | Margin (dB) | Raw Value (dBuV) | Antenna Factor (dB/m) | Cable Factor (dB) | Pre-amplifier (dB) | Correction Factor (dB/m) |
|----------------|-----------------|-------------------------|---------------|---------|----------------|-------------|------------------|-----------------------|-------------------|--------------------|--------------------------|
| 149<br>5745MHz | 5720.00         | 56.06                   | PK            | H       | 68.20          | 12.14       | 51.26            | 34.21                 | 5.11              | 34.52              | 4.80                     |
|                | 5720.00         | 45.15                   | AV            | H       | 54.00          | 8.85        | 40.35            | 34.21                 | 5.11              | 34.52              | 4.80                     |
|                | 11490.00        | 44.42                   | PK            | H       | 68.20          | 23.78       | 35.42            | 38.35                 | 5.86              | 35.21              | 9.00                     |
|                | --              | --                      | --            | --      | --             | --          | --               | --                    | --                | --                 | --                       |
| 157<br>5785MHz | 11570.00        | 41.57                   | PK            | H       | 68.20          | 26.63       | 32.25            | 38.61                 | 5.96              | 35.25              | 9.32                     |
|                | --              | --                      | --            | --      | --             | --          | --               | --                    | --                | --                 | --                       |
| 165<br>5825MHz | 5855.00         | 42.78                   | PK            | H       | 68.20          | 25.42       | 37.63            | 34.56                 | 5.22              | 34.63              | 5.15                     |
|                | 11650.00        | 42.87                   | PK            | H       | 68.20          | 25.33       | 33.42            | 38.78                 | 6.21              | 35.54              | 9.45                     |
|                | --              | --                      | --            | --      | --             | --          | --               | --                    | --                | --                 | --                       |

| Tested Channel | Frequency (MHz) | Emission Limit (dBuV/m) | Detector Mode | ANT Pol | Limit (dBuV/m) | Margin (dB) | Raw Value (dBuV) | Antenna Factor (dB/m) | Cable Factor (dB) | Pre-amplifier (dB) | Correction Factor (dB/m) |
|----------------|-----------------|-------------------------|---------------|---------|----------------|-------------|------------------|-----------------------|-------------------|--------------------|--------------------------|
| 149<br>5745MHz | 5720.00         | 55.67                   | PK            | V       | 68.20          | 12.53       | 50.87            | 34.21                 | 5.11              | 34.52              | 4.80                     |
|                | 5720.00         | 46.06                   | AV            | V       | 54.00          | 7.94        | 41.26            | 34.21                 | 5.11              | 34.52              | 4.80                     |
|                | 11490.00        | 43.63                   | PK            | V       | 68.20          | 24.57       | 34.63            | 38.35                 | 5.86              | 35.21              | 9.00                     |
|                | --              | --                      | --            | --      | --             | --          | --               | --                    | --                | --                 | --                       |
| 157<br>5785MHz | 11570.00        | 42.84                   | PK            | V       | 68.20          | 25.36       | 33.52            | 38.61                 | 5.96              | 35.25              | 9.32                     |
|                | --              | --                      | --            | --      | --             | --          | --               | --                    | --                | --                 | --                       |
| 165<br>5825MHz | 5855.00         | 48.41                   | PK            | V       | 68.20          | 19.79       | 43.26            | 34.56                 | 5.22              | 34.63              | 5.15                     |
|                | 11650.00        | 49.66                   | PK            | V       | 68.20          | 18.54       | 40.21            | 38.78                 | 6.21              | 35.54              | 9.45                     |

|  |    |    |    |    |    |    |    |    |    |    |    |
|--|----|----|----|----|----|----|----|----|----|----|----|
|  | -- | -- | -- | -- | -- | -- | -- | -- | -- | -- | -- |
|--|----|----|----|----|----|----|----|----|----|----|----|

**REMARKS:**

1. Emission level (dBuV/m) =Raw Value (dBuV)+Correction Factor (dB/m)
2. Correction Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
3. Margin value = Limit value- Emission level.
4. -- Mean the other emission levels were very low against the limit.
5. RBW1MHz VBW3MHz Peak detector is for PK value; RBW 1MHz VBW10Hz Peak detector is for AV value.
6. Worst case data at 54Mbps at IEEE 802.11a; MCS7 at IEEE 802.11n(HT20); MCS7 at IEEE 802.11n(HT40); Ncc1 MCS8 at IEEE 802.11ac(HT20); MCS7 at IEEE 802.11ac(HT40); MCS9 at IEEE 802.11ac(HT80);

### 4.3 Maximum Peak Conducted Output Power

#### Limit

##### **For the band 5.15-5.25 GHz.**

(i) For an outdoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi.

(ii) For an indoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi.

(iii) For fixed point-to-point access points operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W.

(iv) For client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi.

**For the 5.25-5.35 GHz and 5.47-5.725 GHz bands**, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or 11 dBm + 10 log B, where B is the 26 dB emission bandwidth in megahertz.

**For the band 5.725-5.85 GHz**, the maximum conducted output power over the frequency band of operation shall not exceed 1W

#### Test Procedure

Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the power sensor.

#### Test Configuration



**Test Results**

**U-NII 1**

| Type           | Channel | Output power (dBm) | Limit (dBm) | Result |
|----------------|---------|--------------------|-------------|--------|
| 802.11a        | 36      | 8.756              | 23.98       | Pass   |
|                | 40      | 8.651              |             |        |
|                | 48      | 8.562              |             |        |
| 802.11n(HT20)  | 36      | 7.562              | 23.98       | Pass   |
|                | 40      | 7.234              |             |        |
|                | 48      | 7.124              |             |        |
| 802.11n(HT40)  | 38      | 5.245              | 23.98       | Pass   |
|                | 46      | 5.324              |             |        |
| 802.11ac(HT20) | 36      | 6.241              | 23.98       | Pass   |
|                | 40      | 6.451              |             |        |
|                | 48      | 6.345              |             |        |
| 802.11ac(HT40) | 38      | 4.652              | 23.98       | Pass   |
|                | 46      | 4.865              |             |        |
| 802.11ac(HT80) | 42      | 3.241              | 23.98       | Pass   |

**U-NII 3**

| Type           | Channel | Output power (dBm) | Limit (dBm) | Result |
|----------------|---------|--------------------|-------------|--------|
| 802.11a        | 149     | 9.652              | 30.00       | Pass   |
|                | 157     | 9.452              |             |        |
|                | 165     | 9.365              |             |        |
| 802.11n(HT20)  | 149     | 8.541              | 30.00       | Pass   |
|                | 157     | 8.654              |             |        |
|                | 165     | 8.241              |             |        |
| 802.11n(HT40)  | 151     | 6.562              | 30.00       | Pass   |
|                | 159     | 6.251              |             |        |
| 802.11ac(HT20) | 149     | 7.542              | 30.00       | Pass   |
|                | 157     | 7.245              |             |        |
|                | 165     | 7.631              |             |        |
| 802.11ac(HT40) | 151     | 5.532              | 30.00       | Pass   |
|                | 159     | 5.421              |             |        |
| 802.11ac(HT80) | 155     | 3.251              | 30.00       | Pass   |

**Note:**

- 1) Measured output power at difference data rate for each mode and recorded worst case for each mode.
- 2) Test results including cable loss.
- 3) Worst case data at 54Mbps at IEEE 802.11a; MCS7 at IEEE 802.11n(HT20); MCS7 at IEEE 802.11n(HT40); Ncc1 MCS8 at IEEE 802.11ac(HT20); MCS7 at IEEE 802.11ac(HT40); MCS9 at IEEE 802.11ac(HT80);