

No. 1 Workshop, M-10, Middle section, Science & Technology Park,

Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053 Report No.: SZEM180300226604

Fax: +86 (0) 755 2671 0594 Page: 1 of 53

TEST REPORT

Application No.: SZEM1803002266CR

Applicant: Kingstate Electronics(Dongguan) Co., Ltd

Address of Applicant: Shi Chong Industrial Park, Shi Chong Avenue, Xiang Xi Village, Shi Pai

Town, Dong Guan City, Guang Dong Province, China

Manufacturer: Kingstate Electronics(Dongguan) Co., Ltd

Address of Manufacturer: Shi Chong Industrial Park, Shi Chong Avenue, Xiang Xi Village, Shi Pai

Town, Dong Guan City, Guang Dong Province, China

Factory: Kingstate Electronics(Dongguan)Co.,Ltd

Address of Factory: Shi Chong Industrial Park, Shi Chong Avenue, Xiang Xi Village, Shi Pai

Town, Dong Guan City, Guang Dong Province, China.

Equipment Under Test (EUT):

EUT Name: WIRELESS HEADPHONES

Model No.: HA-XC70BT

Earphone side: Left

FCC ID: 2AKMBHA-XC70BT

Trade mark: JVC

Standard(s): 47 CFR Part 15, Subpart C 15.247

Date of Receipt: 2018-04-03

Date of Test: 2018-04-13 to 2018-04-16

Date of Issue: 2018-04-17

Test Result: Pass*



EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sqs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sqs.com/en/Terms-en-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's indigns at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) are retained for 30 days only.

^{*} In the configuration tested, the EUT complied with the standards specified above.



Report No.: SZEM180300226604

Page: 2 of 53

	Revision Record							
Version Chapter Date Modifier Re								
01		2018-04-17		Original				

Authorized for issue by:		
	Hany Ul	
	Harry Wu /Project Engineer	
	EvicFu	
	Eric Fu /Reviewer	



Report No.: SZEM180300226604

Page: 3 of 53

2 Test Summary

Radio Spectrum Technical Requirement						
Item Standard Method Requirement Result						
Antenna Requirement	47 CFR Part 15, Subpart C 15.247	N/A	47 CFR Part 15, Subpart C 15.203 & 15.247(c)	Pass		

Radio Spectrum Matter Part						
Item	Standard	Method	Requirement	Result		
Minimum 6dB Bandwidth	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.8.1	47 CFR Part 15, Subpart C 15.247a(2)	Pass		
Conducted Peak Output Power	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.9.1	47 CFR Part 15, Subpart C 15.247(b)(3)	Pass		
Power Spectrum Density	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.10.2	47 CFR Part 15, Subpart C 15.247(e)	Pass		
Conducted Band Edges Measurement	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.13.3.2	47 CFR Part 15, Subpart C 15.247(d)	Pass		
Conducted Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.11	47 CFR Part 15, Subpart C 15.247(d)	Pass		
Radiated Emissions which fall in the restricted bands	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.10.5	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass		
Radiated Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.4,6.5,6.6	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass		



Report No.: SZEM180300226604

Page: 4 of 53

3 Contents

			Page
1	COVE	R PAGE	1
2	TEST	SUMMARY	3
3	CONT	ENTS	4
3	CONT	EN13	
4	GENE	RAL INFORMATION	6
	4.1 [DETAILS OF E.U.T	6
		DESCRIPTION OF SUPPORT UNITS	
4		MEASUREMENT UNCERTAINTY	
4	4.4	FEST LOCATION	7
4		FEST FACILITY	
		DEVIATION FROM STANDARDS	
4	4.7 A	ABNORMALITIES FROM STANDARD CONDITIONS	7
5	EQUII	PMENT LIST	8
6	RADIO	O SPECTRUM TECHNICAL REQUIREMENT	11
(6.1	ANTENNA REQUIREMENT	11
	6.1.1	Test Requirement:	11
	6.1.2	Conclusion	11
7	RADIO	O SPECTRUM MATTER TEST RESULTS	12
		MINIMUM 6DB BANDWIDTH	
	7.1.1	E.U.T. Operation	
	7.1.2	Test Setup Diagram	
	7.1.3	Measurement Procedure and Data	
-	7.2 (CONDUCTED PEAK OUTPUT POWER	
	7.2.1	E.U.T. Operation	
	7.2.2	Test Setup Diagram	
	7.2.3	Measurement Procedure and Data	
-		Power Spectrum Density	
	7.3.1	E.U.T. Operation	
	7.3.2	Test Setup Diagram	
	7.3.3	Measurement Procedure and Data	
	7.4 (7.4.1	CONDUCTED BAND EDGES MEASUREMENT	
	7.4.1 7.4.2	Test Setup Diagram	
	7.4.3	Measurement Procedure and Data	
		CONDUCTED SPURIOUS EMISSIONS	
	7.5.1	E.U.T. Operation	
	7.5.2	Test Setup Diagram	
	7.5.3	Measurement Procedure and Data	
-	7.6 F	RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS	20
	7.6.1	E.U.T. Operation	
	7.6.2	Test Setup Diagram	
	7.6.3	Measurement Procedure and Data	
-		RADIATED SPURIOUS EMISSIONS	
	7.7.1	E.U.T. Operation	
	7.7.2	Test Setup Diagram	28

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sqs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sqs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



Report No.:	SZEM180300226604
-------------	------------------

Page: 5 of 53

8	APPE	NDIX3	9-53
	7.7.3	Measurement Procedure and Data	29



Report No.: SZEM180300226604

Page: 6 of 53

4 General Information

4.1 Details of E.U.T.

Earphone: DC 3.7V 60mAh Rechargeable Batteries;
Charging Case: DC3.7V 520mAh rechargeable battery can be charged by Micro USB port
USB Cable: 30cm, Unshielded
V4.2
-2.09dBi
Monopole
2MHz
GFSK
40
2402MHz to 2480MHz

4.2 Description of Support Units

The EUT has been tested as an independent unit.

4.3 Measurement Uncertainty

No.	ltem	Measurement Uncertainty
1	Radio Frequency	7.25 x 10 ⁻⁸
2	Duty cycle	0.37%
3	Occupied Bandwidth	3%
4	RF conducted power	0.75dB
5	RF power density	2.84dB
6	Conducted Spurious emissions	0.75dB
7	DE Dadieted a consu	4.5dB (below 1GHz)
7	RF Radiated power	4.8dB (above 1GHz)
0	Dedisted Consisses assisting to the	4.5dB (Below 1GHz)
8	Radiated Spurious emission test	4.8dB (Above 1GHz)
9	Temperature test	1℃
10	Humidity test	3%
11	Supply voltages	1.5%
12	Time	3%



Report No.: SZEM180300226604

Page: 7 of 53

4.4 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China. 518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

4.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

· CNAS (No. CNAS L2929)

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC

Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

A2LA (Certificate No. 3816.01)

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

VCCI

The 3m Fully-anechoic chamber for above 1GHz, 10m Semi-anechoic chamber for below 1GHz, Shielded Room for Mains Port Conducted Interference Measurement and Telecommunication Port Conducted Interference Measurement of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-20026, R-14188, C-12383 and T-11153 respectively.

• FCC -Designation Number: CN1178

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1178. Test Firm Registration Number: 406779.

Industry Canada (IC)

Two 3m Semi-anechoic chambers and the 10m Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1, 4620C-2, 4620C-3.

4.6 Deviation from Standards

None

4.7 Abnormalities from Standard Conditions

None



Report No.: SZEM180300226604

Page: 8 of 53

5 Equipment List

Minimum 6dB Bandwidth						
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date	
DC Power Supply	ZhaoXin	RXN-305D	SEM011-02	2017-09-27	2018-09-26	
Spectrum Analyzer	Rohde & Schwarz	FSP	SEM004-06	2017-09-27	2018-09-26	
Measurement Software	JS Tonscend	JS1120-2 BT/WIFI V2.	N/A	N/A	N/A	
Coaxial Cable	SGS	N/A	SEM031-02	2017-07-13	2018-07-12	
Attenuator	Weinschel Associates	WA41	SEM021-09	N/A	N/A	
Signal Generator	KEYSIGHT	N5173B	SEM006-05	2017-09-27	2018-09-26	
Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2017-09-27	2018-09-26	

Conducted Peak Output Power						
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date	
DC Power Supply	ZhaoXin	RXN-305D	SEM011-02	2017-09-27	2018-09-26	
Spectrum Analyzer	Rohde & Schwarz	FSP	SEM004-06	2017-09-27	2018-09-26	
Measurement Software	JS Tonscend	JS1120-2 BT/WIFI V2.	N/A	N/A	N/A	
Coaxial Cable	SGS	N/A	SEM031-02	2017-07-13	2018-07-12	
Attenuator	Weinschel Associates	WA41	SEM021-09	N/A	N/A	
Signal Generator	KEYSIGHT	N5173B	SEM006-05	2017-09-27	2018-09-26	
Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2017-09-27	2018-09-26	

Power Spectrum Density						
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date	
DC Power Supply	ZhaoXin	RXN-305D	SEM011-02	2017-09-27	2018-09-26	
Spectrum Analyzer	Rohde & Schwarz	FSP	SEM004-06	2017-09-27	2018-09-26	
Measurement Software	JS Tonscend	JS1120-2 BT/WIFI V2.	N/A	N/A	N/A	
Coaxial Cable	SGS	N/A	SEM031-02	2017-07-13	2018-07-12	
Attenuator	Weinschel Associates	WA41	SEM021-09	N/A	N/A	
Signal Generator	KEYSIGHT	N5173B	SEM006-05	2017-09-27	2018-09-26	
Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2017-09-27	2018-09-26	

Conducted Band Edges Measurement										
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date					
DC Power Supply	ZhaoXin	RXN-305D	SEM011-02	2017-09-27	2018-09-26					
Spectrum Analyzer	Rohde & Schwarz	FSP	SEM004-06	2017-09-27	2018-09-26					
Measurement Software	JS Tonscend	JS1120-2 BT/WIFI V2.	N/A	N/A	N/A					
Coaxial Cable	SGS	N/A	SEM031-02	2017-07-13	2018-07-12					
Attenuator	Weinschel Associates	WA41	SEM021-09	N/A	N/A					
Signal Generator	KEYSIGHT	N5173B	SEM006-05	2017-09-27	2018-09-26					

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sqs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sqs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



Report No.: SZEM180300226604

Page: 9 of 53

Power Meter R	ohde & Schwarz	NRVS	SEM014-02	2017-09-27	2018-09-26	ĺ
---------------	----------------	------	-----------	------------	------------	---

Conducted Spurious Emissions										
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date					
DC Power Supply	ZhaoXin	RXN-305D	SEM011-02	2017-09-27	2018-09-26					
Spectrum Analyzer	Rohde & Schwarz	FSP	SEM004-06	2017-09-27	2018-09-26					
Measurement Software	JS Tonscend	JS1120-2 BT/WIFI V2.	N/A	N/A	N/A					
Coaxial Cable	SGS	N/A	SEM031-02	2017-07-13	2018-07-12					
Attenuator	Weinschel Associates	WA41	SEM021-09	N/A	N/A					
Signal Generator	KEYSIGHT	N5173B	SEM006-05	2017-09-27	2018-09-26					
Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2017-09-27	2018-09-26					

Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
3m Semi-Anechoic Chamber	AUDIX	N/A	SEM001-02	2017-05-02	2020-05-01
Measurement Software	AUDIX	e3 V8.2014-6- 27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM026-01	2017-07-13	2018-07-12
Spectrum Analyzer	Rohde & Schwarz	FSU43	SEM004-08	2018-04-02	2019-04-01
BiConiLog Antenna (26- 3000MHz)	ETS-Lindgren	3142C	SEM003-01	2017-06-27	2020-06-26
Horn Antenna (1- 18GHz)	Rohde & Schwarz	HF907	SEM003-07	2015-06-14	2018-06-13
Horn Antenna(15GHz- 40GHz)	Schwarzbeck	BBHA 9170	SEM003-15	2017-10-17	2020-10-16
Pre-amplifier (0.1- 1300MHz)	HP	8447D	SEM005-02	2017-09-27	2018-09-26
Low Noise Amplifier(100MHz- 18GHz)	Black Diamond Series	BDLNA-0118- 352810	SEM005-05	2017-09-27	2018-09-27
Pre-amplifier(18-26GHz)	Rohde & Schwarz	CH14-H052	SEM005-17	2018-04-02	2019-04-01
Pre-amplifier(26GHz- 40GHz)	Compliance Directions Systems Inc.	PAP-2640-50	SEM005-08	2018-04-02	2019-04-01
DC Power Supply	Zhao Xin	RXN-305D	SEM011-02	2017-09-27	2018-09-26
Active Loop Antenna	ETS-Lindgren	6502	SEM003-08	2017-08-22	2020-08-21
Band filter	N/A	N/A	SEM023-01	N/A	N/A



Report No.: SZEM180300226604

Page: 10 of 53

Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
3m Semi-Anechoic Chamber	AUDIX	N/A	SEM001-02	2017-05-02	2020-05-01
Measurement Software	AUDIX	e3 V8.2014-6- 27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM026-01	2017-07-13	2018-07-12
Spectrum Analyzer	Rohde & Schwarz	FSU43	SEM004-08	2018-04-02	2019-04-01
BiConiLog Antenna (26- 3000MHz)	ETS-Lindgren	3142C	SEM003-01	2017-06-27	2020-06-26
Horn Antenna (1- 18GHz)	Rohde & Schwarz	HF907	SEM003-07	2015-06-14	2018-06-13
Horn Antenna(15GHz- 40GHz)	Schwarzbeck	BBHA 9170	SEM003-15	2017-10-17	2020-10-16
Pre-amplifier (0.1- 1300MHz)	HP	8447D	SEM005-02	2017-09-27	2018-09-26
Low Noise Amplifier(100MHz- 18GHz)	Black Diamond Series	BDLNA-0118- 352810	SEM005-05	2017-09-27	2018-09-27
Pre-amplifier(18-26GHz)	Rohde & Schwarz	CH14-H052	SEM005-17	2018-04-02	2019-04-01
Pre-amplifier(26GHz- 40GHz)	Compliance Directions Systems Inc.	PAP-2640-50	SEM005-08	2018-04-02	2019-04-01
DC Power Supply	Zhao Xin	RXN-305D	SEM011-02	2017-09-27	2018-09-26
Active Loop Antenna	ETS-Lindgren	6502	SEM003-08	2017-08-22	2020-08-21
Band filter	N/A	N/A	SEM023-01	N/A	N/A

General used equipment										
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date					
Humidity/ Temperature Indicator	Shanghai Meteorological Industry Factory	ZJ1-2B	SEM002-03	2017-09-29	2018-09-28					
Humidity/ Temperature Indicator	Shanghai Meteorological Industry Factory	ZJ1-2B	SEM002-04	2017-09-29	2018-09-28					
Humidity/ Temperature Indicator	Mingle	N/A	SEM002-08	2017-09-29	2018-09-28					
Barometer	Changchun Meteorological Industry Factory	DYM3	SEM002-01	2017-04-18	2018-04-17					



Report No.: SZEM180300226604

Page: 11 of 53

6 Radio Spectrum Technical Requirement

6.1 Antenna Requirement

6.1.1 Test Requirement:

47 CFR Part 15, Subpart C 15.203 & 15.247(c)

6.1.2 Conclusion

Standard Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

EUT Antenna:

The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is -2.09dBi.



Report No.: SZEM180300226604

Page: 12 of 53

7 Radio Spectrum Matter Test Results

7.1 Minimum 6dB Bandwidth

Test Requirement 47 CFR Part 15, Subpart C 15.247a(2)
Test Method: ANSI C63.10 (2013) Section 11.8.1

Limit: ≥500 kHz

7.1.1 E.U.T. Operation

Operating Environment:

Temperature: 24.1 °C Humidity: 53.1 % RH Atmospheric Pressure: 1015 mbar Pretest these d:TX mode(Left Ear)_Keep the EUT in continuously transmitting mode with GFSK


modes to find modulation

the worst case:

The worst case d:TX mode(Left Ear)_Keep the EUT in continuously transmitting mode with GFSK

for final test: modulation

7.1.2 Test Setup Diagram



Ground Reference Plane

7.1.3 Measurement Procedure and Data

The detailed test data see: Appendix 15.247



Report No.: SZEM180300226604

Page: 13 of 53

7.2 Conducted Peak Output Power

Test Requirement 47 CFR Part 15, Subpart C 15.247(b)(3)
Test Method: ANSI C63.10 (2013) Section 11.9.1

Limit:

Frequency range(MHz)	Output power of the intentional radiator(watt)					
	1 for ≥50 hopping channels					
902-928	0.25 for 25≤ hopping channels <50					
	1 for digital modulation					
	1 for ≥75 non-overlapping hopping channels					
2400-2483.5	0.125 for all other frequency hopping systems					
	1 for digital modulation					
5725-5850	1 for frequency hopping systems and digital modulation					



Report No.: SZEM180300226604

Page: 14 of 53

7.2.1 E.U.T. Operation

Operating Environment:

Temperature: 24.1 °C Humidity: 53.2 % RH Atmospheric Pressure: 1015 mbar Pretest these d:TX mode(Left Ear)_Keep the EUT in continuously transmitting mode with GFSK


modes to find modulation

the worst case:

The worst case d:TX mode(Left Ear)_Keep the EUT in continuously transmitting mode with GFSK

for final test: modulation

7.2.2 Test Setup Diagram



Ground Reference Plane

7.2.3 Measurement Procedure and Data

The detailed test data see: Appendix 15.247



Report No.: SZEM180300226604

Page: 15 of 53

7.3 Power Spectrum Density

Test Requirement 47 CFR Part 15, Subpart C 15.247(e)
Test Method: ANSI C63.10 (2013) Section 11.10.2

Limit: ≤8dBm in any 3 kHz band during any time interval of continuous

transmission

7.3.1 E.U.T. Operation

Operating Environment:

Temperature: 24.1 °C Humidity: 53 % RH Atmospheric Pressure: 1015 mbar Pretest these d:TX mode(Left Ear)_Keep the EUT in continuously transmitting mode with GFSK


modes to find modulation

the worst case:

The worst case d:TX mode(Left Ear) Keep the EUT in continuously transmitting mode with GFSK

for final test: modulation

7.3.2 Test Setup Diagram



Ground Reference Plane

7.3.3 Measurement Procedure and Data

The detailed test data see: Appendix 15.247



Report No.: SZEM180300226604

Page: 16 of 53

7.4 Conducted Band Edges Measurement

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)
Test Method: ANSI C63.10 (2013) Section 11.13.3.2

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in

§15.209(a) (see §15.205(c)



Report No.: SZEM180300226604

Page: 17 of 53

7.4.1 E.U.T. Operation

Operating Environment:

Temperature: 24.1 °C Humidity: 53 % RH Atmospheric Pressure: 1015 mbar Pretest these d:TX mode(Left Ear)_Keep the EUT in continuously transmitting mode with GFSK


modes to find modulation

the worst case:

The worst case d:TX mode(Left Ear)_Keep the EUT in continuously transmitting mode with GFSK

for final test: modulation

7.4.2 Test Setup Diagram



Ground Reference Plane

7.4.3 Measurement Procedure and Data

The detailed test data see: Appendix 15.247



Report No.: SZEM180300226604

Page: 18 of 53

7.5 Conducted Spurious Emissions

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)
Test Method: ANSI C63.10 (2013) Section 11.11

Limit: In any 100 kHz bandwidth outside the frequency band in which the spread

spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition,

radiated emissions which fall in the restricted bands, as defined in

§15.205(a), must also comply with the radiated emission limits specified in

§15.209(a) (see §15.205(c)



Report No.: SZEM180300226604

Page: 19 of 53

7.5.1 E.U.T. Operation

Operating Environment:

Temperature: 24.1 °C Humidity: 53 % RH Atmospheric Pressure: 1015 mbar Pretest these d:TX mode(Left Ear)_Keep the EUT in continuously transmitting mode with GFSK


modes to find modulation

the worst case:

The worst case d:TX mode(Left Ear)_Keep the EUT in continuously transmitting mode with GFSK

for final test: modulation

7.5.2 Test Setup Diagram



Ground Reference Plane

7.5.3 Measurement Procedure and Data

The detailed test data see: Appendix 15.247



Report No.: SZEM180300226604

Page: 20 of 53

7.6 Radiated Emissions which fall in the restricted bands

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2013) Section 6.10.5

Measurement Distance: 3m

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.



Report No.: SZEM180300226604

Page: 21 of 53

7.6.1 E.U.T. Operation

Operating Environment:

Temperature: 23.5 °C Humidity: 51.6 % RH Atmospheric Pressure: 1015 mbar Pretest these d:TX mode(Left Ear)_Keep the EUT in continuously transmitting mode with GFSK


modes to find modulation


the worst case:

The worst case d:TX mode(Left Ear)_Keep the EUT in continuously transmitting mode with GFSK

for final test: modulation

7.6.2 Test Setup Diagram





30MHz-1GHz Above 1GHz



Report No.: SZEM180300226604

Page: 22 of 53

7.6.3 Measurement Procedure and Data


- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.
- Remark 1: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor
- Remark 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.



Report No.: SZEM180300226604

Page: 23 of 53

Mode:d; Polarization:Horizontal; Modulation:GFSK; ; Channel:Low



Condition: 3m HORIZONTAL
Job No : 02266CR/02267CR
Mode : 2402 Band edge


	Freq			Preamp Factor					Remark
-	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
2	2370.395 2390.000 2402.000	5.47	32.06	41.87	46.38	42.04	74.00	-31.96	peak



Report No.: SZEM180300226604

Page: 24 of 53

Mode:d; Polarization:Vertical; Modulation:GFSK; ; Channel:Low



Condition: 3m VERTICAL
Job No : 02266CR/02267CR
Mode : 2402 Band edge


Freq			Preamp Factor					Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
2337.871 2390.000 2402.000	5.47	32.06	41.87	46.48	42.14	74.00	-31.86	peak



Report No.: SZEM180300226604

Page: 25 of 53

Mode:d; Polarization:Horizontal; Modulation:GFSK; ; Channel:High



Condition: 3m HORIZONTAL
Job No : 02266CR/02267CR
Mode : 2480 Band edge


	_			Preamp					
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Kemark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 pp	2480.000	5.59	32.26	41.91	91.23	87.17	74.00	13.17	peak
2	2483.500	5.60	32.26	41.91	53.25	49.20	74.00	-24.80	peak
3	2483.821	5.60	32.27	41.91	54.60	50.56	74.00	-23.44	peak



Report No.: SZEM180300226604

Page: 26 of 53

Mode:d; Polarization:Vertical; Modulation:GFSK; ; Channel:High



Condition: 3m VERTICAL
Job No : 02266CR/02267CR
Mode : 2480 Band edge

	Cable	Ant	Preamp	Read		Limit	0ver	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 pp 2480.000	5.59	32.26	41.91	93.98	89.92	74.00	15.92	peak
2 av 2483.500	5.60	32.26	41.91	45.50	41.45	54.00	-12.55	Average
3 2483.500	5.60	32.26	41.91	58.90	54.85	74.00	-19.15	peak
4 2483.846	5.60	32.27	41.91	56.24	52.20	74.00	-21.80	peak



Report No.: SZEM180300226604

Page: 27 of 53

7.7 Radiated Spurious Emissions

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209
Test Method: ANSI C63.10 (2013) Section 6.4,6.5,6.6

Measurement Distance: 3m

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.



Report No.: SZEM180300226604

Page: 28 of 53

7.7.1 E.U.T. Operation

Operating Environment:

Temperature: 22.9 °C Humidity: 56.6 % RH Atmospheric Pressure: 1015 mbar Pretest these d:TX mode(Left Ear)_Keep the EUT in continuously transmitting mode with GFSK


modes to find modulation

the worst case:


The worst case d:TX mode(Left Ear)_Keep the EUT in continuously transmitting mode with GFSK

for final test: modulation

7.7.2 Test Setup Diagram



Below 30MHz 30MHz-1GHz



Above 1GHz



Report No.: SZEM180300226604

Page: 29 of 53

7.7.3 Measurement Procedure and Data

a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.

- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Remark:

- 1) For emission below 1GHz, through pre-scan found the worst case is the lowest channel. Only the worst case is recorded in the report.
- 2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level =Receiver Reading + Antenna Factor + Cable Factor - Preamplifier Factor

- 3) Scan from 9kHz to 25GHz, the disturbance above 18GHz and below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
- 4) For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.




Report No.: SZEM180300226604

Page: 30 of 53

30MHz~1GHz

QP value:

Mode:d; Polarization:Horizontal;



Condition: 3m HORIZONTAL

Job No. : 02266CR

Test mode: d


		Cable	Ant	Preamp	Read		Limit	0ver
	Freq Loss I		Factor	Factor Factor		Level Level		Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	30.00	0.60	22.50	27.67	23.52	18.95	40.00	-21.05
2	46.34	0.73	15.32	27.61	23.41	11.85	40.00	-28.15
3	89.28	1.10	13.02	27.50	25.64	12.26	43.50	-31.24
4	200.69	1.40	16.53	27.53	24.17	14.57	43.50	-28.93
5	393.47	2.18	22.24	27.72	24.23	20.93	46.00	-25.07
6 рр	620.71	2.75	26.89	27.67	25.95	27.92	46.00	-18.08



Report No.: SZEM180300226604

Page: 31 of 53

Mode:d; Polarization:Vertical



Condition: 3m VERTICAL Job No. : 02266CR

Test mode: d

		Cable	Ant	Preamp	Read		Limit	0ver
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	30.96	0.60	21.95	27.67	24.59	19.47	40.00	-20.53
2	62.87	0.80	13.08	27.55	24.53	10.86	40.00	-29.14
3	135.51	1.29	13.57	27.52	24.91	12.25	43.50	-31.25
4	245.95	1.65	18.89	27.53	23.27	16.28	46.00	-29.72
5	399.03	2.20	22.38	27.73	23.83	20.68	46.00	-25.32
6 pp	758.04	3.08	28.26	27.47	25.22	29.09	46.00	-16.91




Report No.: SZEM180300226604

Page: 32 of 53

Above 1GHz

Mode:d; Polarization:Horizontal; Modulation:GFSK; ; Channel:Low



Condition: 3m HORIZONTAL Job No : 02266CR/02267CR

Mode : 2402 TX SE


			Cable	Ant	Preamp	Read		Limit	0ver	
		Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
		MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1		1667.951	5.27	28.95	41.51	46.81	39.52	74.00	-34.48	peak
2		4430.628	7.48	33.68	42.41	48.30	47.05	74.00	-26.95	peak
3		4804.000	7.89	33.99	42.47	51.38	50.79	74.00	-23.21	peak
4	рр	6507.536	11.52	35.50	41.21	47.61	53.42	74.00	-20.58	peak
5		7206.000	10.08	35.80	40.71	46.06	51.23	74.00	-22.77	peak
6		9608.000	10.75	36.89	37.74	42.78	52.68	74.00	-21.32	peak



Report No.: SZEM180300226604

Page: 33 of 53

Mode:d; Polarization:Vertical; Modulation:GFSK; ; Channel:Low



Condition: 3m VERTICAL Job No : 02266CR/02267CR

Mode : 2402 TX SE


			Cable	Ant	Preamp	Read		Limit	0ver	
		Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
		MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1		1615.754	5.33	28.58	41.48	46.20	38.63	74.00	-35.37	peak
2		4482.150	7.54	33.77	42.41	47.74	46.64	74.00	-27.36	peak
3		4804.000	7.89	33.99	42.47	50.73	50.14	74.00	-23.86	peak
4	pp	6507.536	11.52	35.50	41.21	47.73	53.54	74.00	-20.46	peak
5		7206.000	10.08	35.80	40.71	46.17	51.34	74.00	-22.66	peak
6		9608.000	10.75	36.89	37.74	41.62	51.52	74.00	-22.48	peak



Report No.: SZEM180300226604

Page: 34 of 53

Mode:d; Polarization:Horizontal; Modulation:GFSK; ; Channel:middle



Condition: 3m HORIZONTAL Job No : 02266CR/02267CR

Mode : 2440 TX SE


		Cable	Ant	Preamp	Read		Limit	0ver	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
		u.	ub/	40	abar	abav,	abav,	u.b	
4	4404 553	F 43	27 67	44 30	46 07	20 67	74.00	25 22	
1	1481.553	5.42	2/.6/	41.39	46.97	38.6/	74.00	-35.33	реак
2	4495.125	7.55	33.79	42.42	47.83	46.75	74.00	-27.25	peak
3	4880.000	7.97	34.03	42.48	52.83	52.35	74.00	-21.65	peak
4 pp	6776.265	10.75	35.67	41.01	48.35	53.76	74.00	-20.24	peak
5	7320.000	10.05	35.80	40.63	45.78	51.00	74.00	-23.00	peak
6	9760.000	10.82	37.28	37.53	41.85	52.42	74.00	-21.58	peak



Report No.: SZEM180300226604

Page: 35 of 53

Mode:d; Polarization:Vertical; Modulation:GFSK; ; Channel:middle



Condition: 3m VERTICAL Job No : 02266CR/02267CR

Mode : 2440 TX SE


			Cable	Ant	Preamp	Read		Limit	0ver	
		Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
		•								
	-	MHz	dB	dR/m	dB	dRuV	dRuV/m	dBuV/m	dB	
		1112	u.b	ub/ III	40	aba.	abav,	abav, iii	u.b	
4		1602 221	F 24	20 12	44 50	45 20	20 42	74.00	25 07	
1		1692.231	5.24	29.13	41.53	45.29	38.13	74.00	-35.8/	peak
2		4417.841	7.47	33.66	42.40	47.20	45.93	74.00	-28.07	peak
3		4880.000	7.97	34.03	42.48	52.67	52.19	74.00	-21.81	peak
4	pp	6874.906	10.47	35.73	40.94	48.42	53.68	74.00	-20.32	peak
5		7320.000	10.05	35.80	40.63	45.96	51.18	74.00	-22.82	peak
6		9760.000	10.82	37.28	37.53	42.27	52.84	74.00	-21.16	peak



Report No.: SZEM180300226604

Page: 36 of 53

Mode:d; Polarization:Horizontal; Modulation:GFSK; ; Channel:High



Condition: 3m HORIZONTAL Job No : 02266CR/02267CR

Mode : 2480 TX SE


			Cable	Ant	Preamp	Read		Limit	0ver	
		Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	-	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
				,						
1		1677.621	5.25	29.02	41.52	45.83	38.58	74.00	-35.42	peak
2		4456.315								-
3		4960.000	8.05	34.08	42.49	51.28	50.92	74.00	-23.08	peak
4	pp	6583.209	11.30	35.55	41.15	47.81	53.51	74.00	-20.49	peak
5		7440.000	10.02	35.80	40.56	45.30	50.56	74.00	-23.44	peak
6		9920.000	10.90	37.70	37.31	41.52	52.81	74.00	-21.19	peak



Report No.: SZEM180300226604

Page: 37 of 53

Mode:d; Polarization:Vertical; Modulation:GFSK; ; Channel:High



Condition: 3m VERTICAL Job No : 02266CR/02267CR

Mode : 2480 TX SE

Note :

		Cable	Ant	Preamp	Read		Limit	0ver	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1658.337	5.28	28.89	41.51	45.95	38.61	74.00	-35.39	peak
2	4495.125	7.55	33.79	42.42	47.12	46.04	74.00	-27.96	peak
3	pp 4960.000	8.05	34.08	42.49	53.56	53.20	74.00	-20.80	peak
4	6432.732	11.41	35.51	41.27	47.44	53.09	74.00	-20.91	peak
5	7440.000	10.02	35.80	40.56	45.76	51.02	74.00	-22.98	peak
6	9920.000	10.90	37.70	37.31	41.90	53.19	74.00	-20.81	neak



Report No.: SZEM180300226604

Page: 38 of 53

Remark:

1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level =Receiver Reading + Antenna Factor + Cable Factor - Preamplifier Factor

- 2) Scan from 9kHz to 25GHz, the disturbance above 18GHz and below 30MHz was very low, and the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
- 3) As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. So, only the peak measurements were shown in the report.



Report No.: SZEM180300226604

Page: 39 of 53

8 Appendix

Appendix 15.247


1.6dB Bandwidth

Test Mode	Test Channel	Ant	EBW[MHz]	Limit[MHz]	Verdict
BLE	2402 Ant1		0.687	>=0.5	PASS
BLE	2440	Ant1	0.684	>=0.5	PASS
BLE	2480	Ant1	0.687	>=0.5	PASS



Report No.: SZEM180300226604

Page: 40 of 53




This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sqs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sqs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



Report No.: SZEM180300226604

Page: 41 of 53





Report No.: SZEM180300226604

Page: 42 of 53


3.Maximum peak conducted output power

Test Mode	Test Channel	Ant Power[dBm]		Limit[dBm]	Verdict
BLE	2402	Ant1	1.85	<30	PASS
BLE	2440	Ant1	3.19	<30	PASS
BLE	2480	Ant1	3.64	<30	PASS



Report No.: SZEM180300226604

Page: 43 of 53



This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sqs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sqs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



Report No.: SZEM180300226604

Page: 44 of 53




4. Maximum Peak power spectral density

Test Mode	Test Channel	Ant	PSD[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
BLE	2402	Ant1	-12.73	<8.00	PASS
BLE	2440	Ant1	-11.64	<8.00	PASS
BLE	2480	Ant1	-11.23	<8.00	PASS



Report No.: SZEM180300226604

Page: 45 of 53



This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sqs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sqs.com/en/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawfull and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) are retained for 30 days only.



Report No.: SZEM180300226604

Page: 46 of 53




5.Band-edge for RF Conducted Emissions

Test Mode	Test Channel	Ant	Carrier Power[dBm]	Max. Spurious Level [dBm]	Limit [dBm]	Verdict
BLE	2402	Ant1	0.880	-65.596	<-19.12	PASS
BLE	2480	Ant1	2.610	-42.487	<-17.39	PASS



Report No.: SZEM180300226604

Page: 47 of 53



This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sqs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sqs.com/en/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawfull and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) are retained for 30 days only.



Report No.: SZEM180300226604

Page: 48 of 53


6.RF Conducted Spurious Emissions

Test Mode	Test Channel	StartFre [MHz]	StopFre [MHz]	RBW [kHz]	VBW [kHz]	Pref[dBm]	Max. Level [dBm]	Limit [dBm]	Verdict
BLE	2402	30	10000	1000	3000	0.89	-49.130	<- 19.11	PASS
BLE	2402	10000	25000	1000	3000	0.89	-65.760	<- 19.11	PASS
BLE	2440	30	10000	1000	3000	2.25	-47.280	<- 17.75	PASS
BLE	2440	10000	25000	1000	3000	2.25	-65.450	<- 17.75	PASS
BLE	2480	30	10000	1000	3000	2.71	-45.910	<- 17.29	PASS
BLE	2480	10000	25000	1000	3000	2.71	-64.930	<- 17.29	PASS



Report No.: SZEM180300226604


Page: 49 of 53





Report No.: SZEM180300226604


Page: 50 of 53





Report No.: SZEM180300226604


Page: 51 of 53





Report No.: SZEM180300226604


Page: 52 of 53





Report No.: SZEM180300226604

Page: 53 of 53



- End of the Report -