

TEST REPORT

Application No.: SZEM2007007054CR
Applicant: Kingstate Electronics(DongGuan)Co.,Ltd.
Address of Applicant: Shi Chong Industrial Park, Shi Chong Avenue, Xiang Xi Village, Shi Pai Town, Dongguan, China.
Manufacturer: Kingstate Electronics(DongGuan)Co.,Ltd.
Address of Manufacturer: Shi Chong Industrial Park, Shi Chong Avenue, Xiang Xi Village, Shi Pai Town, Dongguan, China.
Factory: Kingstate Electronics(DongGuan)Co.,Ltd.
Address of Factory: Shi Chong Industrial Park, Shi Chong Avenue, Xiang Xi Village, Shi Pai Town, Dongguan, China.
Equipment Under Test (EUT):
EUT Name: Truly wireless Earphones
Model No.: TW-E3B
Trade Mark: YAMAHA
FCC ID: 2AKMBTWE3B
Standard(s) : 47 CFR Part 15, Subpart C 15.247
Date of Receipt: 2020-07-25
Date of Test: 2020-08-01 to 2020-08-03
Date of Issue: 2020-08-27

Test Result:	Pass*
---------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.

Keny Xu

Keny Xu
EMC Laboratory Manager



Revision Record				
Version	Chapter	Date	Modifier	Remark
01		2020-08-27		Original

Authorized for issue by:			
			
		Harry Wu /Project Engineer	
			
		Eric Fu /Reviewer	



2 Test Summary

Radio Spectrum Technical Requirement				
Item	Standard	Method	Requirement	Result
Antenna Requirement	47 CFR Part 15, Subpart C 15.247	N/A	47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)	Pass

Radio Spectrum Matter Part				
Item	Standard	Method	Requirement	Result
Minimum 6dB Bandwidth	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.8.1	47 CFR Part 15, Subpart C 15.247a(2)	Pass
Conducted Peak Output Power	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.9.1	47 CFR Part 15, Subpart C 15.247(b)(3)	Pass
Power Spectrum Density	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.10.2	47 CFR Part 15, Subpart C 15.247(e)	Pass
Conducted Band Edges Measurement	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.13.3.2	47 CFR Part 15, Subpart C 15.247(d)	Pass
Conducted Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.11	47 CFR Part 15, Subpart C 15.247(d)	Pass
Radiated Emissions which fall in the restricted bands	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.10.5	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Radiated Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.4,6.5,6.6	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass



3 Contents

	Page
1 COVER PAGE	1
2 TEST SUMMARY	3
3 CONTENTS	4
4 GENERAL INFORMATION	6
4.1 DETAILS OF E.U.T.	6
4.2 DESCRIPTION OF SUPPORT UNITS	6
4.3 DETAILS OF SAMPLE SETTING	6
4.4 MEASUREMENT UNCERTAINTY	6
4.5 TEST LOCATION	7
4.6 TEST FACILITY	7
4.7 DEVIATION FROM STANDARDS	7
4.8 ABNORMALITIES FROM STANDARD CONDITIONS	7
5 EQUIPMENT LIST	8
6 RADIO SPECTRUM TECHNICAL REQUIREMENT	13
6.1 ANTENNA REQUIREMENT	13
6.1.1 <i>Test Requirement:</i>	13
6.1.2 <i>Conclusion</i>	13
7 RADIO SPECTRUM MATTER TEST RESULTS	14
7.1 MINIMUM 6DB BANDWIDTH	14
7.1.1 <i>E.U.T. Operation</i>	14
7.1.2 <i>Test Setup Diagram</i>	14
7.1.3 <i>Measurement Procedure and Data</i>	14
7.2 CONDUCTED PEAK OUTPUT POWER	15
7.2.1 <i>E.U.T. Operation</i>	16
7.2.2 <i>Test Setup Diagram</i>	16
7.2.3 <i>Measurement Procedure and Data</i>	16
7.3 POWER SPECTRUM DENSITY	17
7.3.1 <i>E.U.T. Operation</i>	17
7.3.2 <i>Test Setup Diagram</i>	17
7.3.3 <i>Measurement Procedure and Data</i>	17
7.4 CONDUCTED BAND EDGES MEASUREMENT	18
7.4.1 <i>E.U.T. Operation</i>	19
7.4.2 <i>Test Setup Diagram</i>	19
7.4.3 <i>Measurement Procedure and Data</i>	19
7.5 CONDUCTED SPURIOUS EMISSIONS	20
7.5.1 <i>E.U.T. Operation</i>	21
7.5.2 <i>Test Setup Diagram</i>	21
7.5.3 <i>Measurement Procedure and Data</i>	21
7.6 RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS	22
7.6.1 <i>E.U.T. Operation</i>	23



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 83071443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch (SGS-CSTC Laboratory)

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

7.6.2	Test Setup Diagram.....	23
7.6.3	Measurement Procedure and Data.....	24
7.7	RADIATED SPURIOUS EMISSIONS	41
7.7.1	E.U.T. Operation	42
7.7.2	Test Setup Diagram.....	42
7.7.3	Measurement Procedure and Data.....	43
8	PHOTOGRAPHS.....	72
8.1	TEST SETUP.....	72
8.2	EUT CONSTRUCTIONAL DETAILS (EUT PHOTOS).....	72
9	APPENDIX.....	73
9.1	APPENDIX 15.247 – LEFT	73
9.2	APPENDIX 15.247 – RIGHT	94-114



4 General Information

4.1 Details of E.U.T.

Power Supply:	Earphone: Lithium Battery: DC3.7V,50mAh Charge Case: Lithium Battery: DC3.7V,520mAh or DC5V, 0.5A
Cable:	Type C cable, 30cm, unshielded
Serial No.:	Z015200UW
Operation Frequency:	2402MHz to 2480MHz
Bluetooth Version:	V5.0
Modulation Type:	GFSK
Number of Channels:	40
Channel Spacing:	2MHz
Data Rate:	1Mb/s, 2Mb/s
Antenna Type:	Chip Antenna
Antenna Gain:	-4.69dBi

4.2 Description of Support Units

The EUT has been tested as an independent unit.

4.3 Details of Sample setting.

RF software:	Bluetest 3.2
Software Power setting:	Tx Power: Default (The peak output power refer to Appendix 15-247)

4.4 Measurement Uncertainty

No.	Item	Measurement Uncertainty
1	Radio Frequency	$\pm 7.25 \times 10^{-8}$
2	Duty cycle	$\pm 0.37\%$
3	Occupied Bandwidth	$\pm 3\%$
4	RF conducted power	$\pm 0.75\text{dB}$
5	RF power density	$\pm 2.84\text{dB}$
6	Conducted Spurious emissions	$\pm 0.75\text{dB}$
7	RF Radiated power	$\pm 4.5\text{dB}$ (Below 1GHz)
		$\pm 4.8\text{dB}$ (Above 1GHz)
8	Radiated Spurious emission test	$\pm 4.5\text{dB}$ (Below 1GHz)
		$\pm 4.8\text{dB}$ (Above 1GHz)
9	Temperature test	$\pm 1^\circ\text{C}$
10	Humidity test	$\pm 3\%$
11	Supply voltages	$\pm 1\%$
12	Time	$\pm 3\%$



4.5 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China. 518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

4.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **A2LA (Certificate No. 3816.01)**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

- **VCCI**

The 3m Fully-anechoic chamber for above 1GHz, 10m Semi-anechoic chamber for below 1GHz, Shielded Room for Mains Port Conducted Interference Measurement and Telecommunication Port Conducted Interference Measurement of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-20026, R-14188, C-12383 and T-11153 respectively.

- **FCC –Designation Number: CN1178**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1178. Test Firm Registration Number: 406779.

- **Innovation, Science and Economic Development Canada**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0006.

IC#: 4620C.

4.7 Deviation from Standards

None

4.8 Abnormalities from Standard Conditions

None



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.
Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch EMC Laboratory.

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

5 Equipment List

Minimum 6dB Bandwidth					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Shielding Room	SAEMC	MSR733	SEM001-09	2019-06-13	2022-06-12
DC Power Supply	Rohde & Schwarz	NGSM 32/10	SEM011-04	2020-03-24	2021-03-23
Spectrum Analyzer	Rohde & Schwarz	FSP	SEM004-06	2019-09-24	2020-09-23
Measurement Software	TST	TST PASS V1.0.5	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM031-02	2020-07-10	2021-07-09
Attenuator	Huber+Suhner	6620_SMA-50-1	SEM021-09	N/A	N/A
Signal Generator	KEYSIGHT	N5173B	SEM006-05	2019-09-24	2020-09-23
Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2019-09-24	2020-09-23
Electric and Magnetic Field Analyzer	Narda	EHP-50F	SEM022-05	2019-11-28	2020-11-27

Conducted Peak Output Power					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Shielding Room	SAEMC	MSR733	SEM001-09	2019-06-13	2022-06-12
DC Power Supply	Rohde & Schwarz	NGSM 32/10	SEM011-04	2020-03-24	2021-03-23
Spectrum Analyzer	Rohde & Schwarz	FSP	SEM004-06	2019-09-24	2020-09-23
Measurement Software	TST	TST PASS V1.0.5	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM031-02	2020-07-10	2021-07-09
Attenuator	Huber+Suhner	6620_SMA-50-1	SEM021-09	N/A	N/A
Signal Generator	KEYSIGHT	N5173B	SEM006-05	2019-09-24	2020-09-23
Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2019-09-24	2020-09-23
Electric and Magnetic Field Analyzer	Narda	EHP-50F	SEM022-05	2019-11-28	2020-11-27



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 83071443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch (SGS-CSTC Laboratory)

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Power Spectrum Density					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Shielding Room	SAEMC	MSR733	SEM001-09	2019-06-13	2022-06-12
DC Power Supply	Rohde & Schwarz	NGSM 32/10	SEM011-04	2020-03-24	2021-03-23
Spectrum Analyzer	Rohde & Schwarz	FSP	SEM004-06	2019-09-24	2020-09-23
Measurement Software	TST	TST PASS V1.0.5	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM031-02	2020-07-10	2021-07-09
Attenuator	Huber+Suhner	6620_SMA-50-1	SEM021-09	N/A	N/A
Signal Generator	KEYSIGHT	N5173B	SEM006-05	2019-09-24	2020-09-23
Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2019-09-24	2020-09-23
Electric and Magnetic Field Analyzer	Narda	EHP-50F	SEM022-05	2019-11-28	2020-11-27

Conducted Band Edges Measurement					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Shielding Room	SAEMC	MSR733	SEM001-09	2019-06-13	2022-06-12
DC Power Supply	Rohde & Schwarz	NGSM 32/10	SEM011-04	2020-03-24	2021-03-23
Spectrum Analyzer	Rohde & Schwarz	FSP	SEM004-06	2019-09-24	2020-09-23
Measurement Software	TST	TST PASS V1.0.5	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM031-02	2020-07-10	2021-07-09
Attenuator	Huber+Suhner	6620_SMA-50-1	SEM021-09	N/A	N/A
Signal Generator	KEYSIGHT	N5173B	SEM006-05	2019-09-24	2020-09-23
Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2019-09-24	2020-09-23
Electric and Magnetic Field Analyzer	Narda	EHP-50F	SEM022-05	2019-11-28	2020-11-27



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report and certificate, please contact us at telephone: (86-755) 83071443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch (SGS-CSTC Laboratory)

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Conducted Spurious Emissions					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Shielding Room	SAEMC	MSR733	SEM001-09	2019-06-13	2022-06-12
DC Power Supply	Rohde & Schwarz	NGSM 32/10	SEM011-04	2020-03-24	2021-03-23
Spectrum Analyzer	Rohde & Schwarz	FSP	SEM004-06	2019-09-24	2020-09-23
Measurement Software	TST	TST PASS V1.0.5	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM031-02	2020-07-10	2021-07-09
Attenuator	Huber+Suhner	6620_SMA-50-1	SEM021-09	N/A	N/A
Signal Generator	KEYSIGHT	N5173B	SEM006-05	2019-09-24	2020-09-23
Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2019-09-24	2020-09-23
Electric and Magnetic Field Analyzer	Narda	EHP-50F	SEM022-05	2019-11-28	2020-11-27

Radiated Emissions which fall in the restricted bands					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
3m Semi-Anechoic Chamber	AUDIX	N/A	SEM001-02	2018-03-13	2021-03-12
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM026-01	2020-07-10	2021-07-09
EXA Spectrum Analyzer	AgilentTechnologies Inc	N9010A	SEM004-12	2020-04-09	2021-04-08
Horn Antenna	Rohde & Schwarz	HF907	SEM003-07	2018-04-13	2021-04-12
Horn Antenna	Schwarzbeck	BBHA 9170	SEM003-15	2017-10-17	2020-10-16
Pre-Amplifier	Compliance Directions Systems Inc.	PAP-0126	SEM004-11	2019-09-24	2020-09-23
Pre-amplifier	Rohde & Schwarz	CH14-H052	SEM005-17	2020-04-01	2021-03-31
Pre-amplifier	Compliance Directions Systems Inc.	PAP-2640-50	SEM005-08	2020-04-01	2021-03-31
DC Power Supply	Zhao Xin	KXN-6020D	SEM011-08	2019-09-24	2020-09-23
Active Loop Antenna	ETS-Lindgren	6502	SEM003-08	2020-08-14	2023-08-13

Radiated Spurious Emissions					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
3m Semi-Anechoic Chamber	AUDIX	N/A	SEM001-02	2018-03-13	2021-03-12
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM026-01	2020-07-10	2021-07-09
EXA Spectrum Analyzer	Agilent Technologies Inc	N9010A	SEM004-12	2020-04-09	2021-04-08
Horn Antenna	Rohde & Schwarz	HF907	SEM003-07	2018-04-13	2021-04-12
Horn Antenna	Schwarzbeck	BBHA 9170	SEM003-15	2017-10-17	2020-10-16
Pre-Amplifier	Compliance Directions Systems Inc.	PAP-0126	SEM004-11	2019-09-24	2020-09-23
Pre-amplifier	Rohde & Schwarz	CH14-H052	SEM005-17	2020-04-01	2021-03-31
Pre-amplifier	Compliance Directions Systems Inc.	PAP-2640-50	SEM005-08	2020-04-01	2021-03-31
DC Power Supply	Zhao Xin	KXN-6020D	SEM011-08	2019-09-24	2020-09-23
Active Loop Antenna	ETS-Lindgren	6502	SEM003-08	2020-08-14	2023-08-13

Radiated Emissions Below 1GHz					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
3m Semi-Anechoic Chamber	ETS-LINDGREN	N/A	SEM001-01	2020-07-19	2023-07-18
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM025-01	2020-07-10	2021-07-09
MXE EMI receiver	KEYSIGHT	N9038A	SEM004-15	2019-12-16	2020-12-15
BiConiLog Antenna	ETS-LINDGREN	3142C	SEM003-02	2019-05-24	2022-05-23
Pre-amplifier	Agilent Technologies	8447D	SEM005-01	2020-04-01	2021-03-31

General used equipment					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Humidity/ Temperature Indicator	Shanghai Meteorological Industry Factory	ZJ1-2B	SEM002-03	2019-09-26	2020-09-25
Humidity/ Temperature Indicator	Shanghai Meteorological Industry Factory	ZJ1-2B	SEM002-04	2019-09-26	2020-09-25
Humidity/ Temperature Indicator	Mingle	N/A	SEM002-08	2019-09-26	2020-09-25
Barometer	Changchun Meteorological Industry Factory	DYM3	SEM002-01	2020-04-07	2021-04-06



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 83071443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch (China Center) EEC Laboratory.

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

6 Radio Spectrum Technical Requirement

6.1 Antenna Requirement

6.1.1 Test Requirement:

47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)

6.1.2 Conclusion

Standard Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

EUT Antenna:

The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is -4.69dBi.

Antenna location: Refer to internal photo.



7 Radio Spectrum Matter Test Results

7.1 Minimum 6dB Bandwidth

Test Requirement 47 CFR Part 15, Subpart C 15.247a(2)
Test Method: ANSI C63.10 (2013) Section 11.8.1
Limit: ≥ 500 kHz


7.1.1 E.U.T. Operation

Operating Environment:

Temperature: 29.8 °C Humidity: 41.2 % RH Atmospheric Pressure: 1010 mbar

Test modes: c:TX mode(Left Earphone,1Mb/s)_Keep the EUT in continuously transmitting mode with GFSK modulation
g:TX mode(Right Earphone,1Mb/s)_Keep the EUT in continuously transmitting mode with GFSK modulation
h:TX mode(Left Earphone,2Mb/s)_Keep the EUT in continuously transmitting mode with GFSK modulation
i:TX mode(Right Earphone,2Mb/s)_Keep the EUT in continuously transmitting mode with GFSK modulation

7.1.2 Test Setup Diagram



7.1.3 Measurement Procedure and Data

The detailed test data see: Appendix 15.247

7.2 Conducted Peak Output Power

Test Requirement 47 CFR Part 15, Subpart C 15.247(b)(3)

Test Method: ANSI C63.10 (2013) Section 11.9.1

Limit:

Frequency range(MHz)	Output power of the intentional radiator(watt)
902-928	1 for ≥ 50 hopping channels
	0.25 for $25 \leq$ hopping channels < 50
	1 for digital modulation
2400-2483.5	1 for ≥ 75 non-overlapping hopping channels
	0.125 for all other frequency hopping systems
	1 for digital modulation
5725-5850	1 for frequency hopping systems and digital modulation



7.2.1 E.U.T. Operation


Operating Environment:

Temperature: 29.8 °C Humidity: 41.2 % RH Atmospheric Pressure: 1010 mbar

Test modes:

- c:TX mode(Left Earphone,1Mb/s)_Keep the EUT in continuously transmitting mode with GFSK modulation
- g:TX mode(Right Earphone,1Mb/s)_Keep the EUT in continuously transmitting mode with GFSK modulation
- h:TX mode(Left Earphone,2Mb/s)_Keep the EUT in continuously transmitting mode with GFSK modulation
- i:TX mode(Right Earphone,2Mb/s)_Keep the EUT in continuously transmitting mode with GFSK modulation

7.2.2 Test Setup Diagram



7.2.3 Measurement Procedure and Data

The detailed test data see: Appendix 15.247



7.3 Power Spectrum Density

Test Requirement 47 CFR Part 15, Subpart C 15.247(e)
Test Method: ANSI C63.10 (2013) Section 11.10.2
Limit: $\leq 8\text{dBm}$ in any 3 kHz band during any time interval of continuous transmission


7.3.1 E.U.T. Operation

Operating Environment:

Temperature: 29.8 °C Humidity: 41.2 % RH Atmospheric Pressure: 1010 mbar

Test modes:
c:TX mode(Left Earphone,1Mb/s)_Keep the EUT in continuously transmitting mode with GFSK modulation
g:TX mode(Right Earphone,1Mb/s)_Keep the EUT in continuously transmitting mode with GFSK modulation
h:TX mode(Left Earphone,2Mb/s)_Keep the EUT in continuously transmitting mode with GFSK modulation
i:TX mode(Right Earphone,2Mb/s)_Keep the EUT in continuously transmitting mode with GFSK modulation

7.3.2 Test Setup Diagram



7.3.3 Measurement Procedure and Data

The detailed test data see: Appendix 15.247

7.4 Conducted Band Edges Measurement

Test Requirement	47 CFR Part 15, Subpart C 15.247(d)
Test Method:	ANSI C63.10 (2013) Section 11.13.3.2
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c))



7.4.1 E.U.T. Operation


Operating Environment:

Temperature: 29.8 °C Humidity: 41.1 % RH Atmospheric Pressure: 1010 mbar

Test modes:

- c:TX mode(Left Earphone,1Mb/s)_Keep the EUT in continuously transmitting mode with GFSK modulation
- g:TX mode(Right Earphone,1Mb/s)_Keep the EUT in continuously transmitting mode with GFSK modulation
- h:TX mode(Left Earphone,2Mb/s)_Keep the EUT in continuously transmitting mode with GFSK modulation
- i:TX mode(Right Earphone,2Mb/s)_Keep the EUT in continuously transmitting mode with GFSK modulation

7.4.2 Test Setup Diagram



7.4.3 Measurement Procedure and Data

The detailed test data see: Appendix 15.247



7.5 Conducted Spurious Emissions

Test Requirement	47 CFR Part 15, Subpart C 15.247(d)
Test Method:	ANSI C63.10 (2013) Section 11.11
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c))



7.5.1 E.U.T. Operation


Operating Environment:

Temperature: 29.8 °C Humidity: 41.1 % RH Atmospheric Pressure: 1010 mbar

Test modes:

- c:TX mode(Left Earphone,1Mb/s)_Keep the EUT in continuously transmitting mode with GFSK modulation
- g:TX mode(Right Earphone,1Mb/s)_Keep the EUT in continuously transmitting mode with GFSK modulation
- h:TX mode(Left Earphone,2Mb/s)_Keep the EUT in continuously transmitting mode with GFSK modulation
- i:TX mode(Right Earphone,2Mb/s)_Keep the EUT in continuously transmitting mode with GFSK modulation

7.5.2 Test Setup Diagram



7.5.3 Measurement Procedure and Data

The detailed test data see: Appendix 15.247



7.6 Radiated Emissions which fall in the restricted bands

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2013) Section 6.10.5

Measurement Distance: 3m

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.



7.6.1 E.U.T. Operation

Operating Environment:

Temperature: 23.4 °C Humidity: 58.1 % RH Atmospheric Pressure: 1010 mbar


Test modes: c:TX mode(Left Earphone,1Mb/s)_Keep the EUT in continuously transmitting mode with GFSK modulation

g:TX mode(Right Earphone,1Mb/s)_Keep the EUT in continuously transmitting mode with GFSK modulation

h:TX mode(Left Earphone,2Mb/s)_Keep the EUT in continuously transmitting mode with GFSK modulation

i:TX mode(Right Earphone,2Mb/s)_Keep the EUT in continuously transmitting mode with GFSK modulation

7.6.2 Test Setup Diagram




7.6.3 Measurement Procedure and Data

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Remark 1: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor

Remark 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

Mode:c; Polarization:Horizontal; Modulation:GFSK; ; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 07054CR/07055CR
Mode : 2402 Band edge
Note : BLE1M L

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2382.278	4.33	28.51	40.97	58.19	50.06	74.00	-23.94	peak
2	2390.000	4.34	28.52	40.97	56.75	48.64	74.00	-25.36	peak
3 *	2402.000	4.36	28.54	40.98	97.31	89.23	74.00	15.23	peak



Mode:c; Polarization:Vertical; Modulation:GFSK; ; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 07054CR/07055CR
Mode : 2402 Band edge
Note : BLE1M L

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2387.736	4.34	28.51	40.97	58.07	49.95	74.00	-24.05	peak
2	2390.000	4.34	28.52	40.97	56.10	47.99	74.00	-26.01	peak
3 *	2402.000	4.36	28.54	40.98	93.66	85.58	74.00	11.58	peak



Mode:c; Polarization:Horizontal; Modulation:GFSK; ; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 07054CR/07055CR
Mode : 2480 Band edge
Note : BLE1M L

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 *	2480.000	4.49	28.67	41.01	101.90	94.05	74.00	20.05	peak
2	2483.500	4.49	28.67	41.01	57.44	49.59	74.00	-24.41	peak
3	2484.720	4.50	28.68	41.01	59.17	51.34	74.00	-22.66	peak



Mode:c; Polarization:Vertical; Modulation:GFSK; ; Channel:High




Site : chamber
Condition: 3m VERTICAL
Job No : 07054CR/07055CR
Mode : 2480 Band edge
Note : BLE1M L

	Freq	Cable Loss	Ant Factor	Preamplifier Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 *	2480.000	4.49	28.67	41.01	95.69	87.84	74.00	13.84	peak
2	2483.500	4.49	28.67	41.01	56.28	48.43	74.00	-25.57	peak
3	2489.719	4.50	28.68	41.01	58.60	50.77	74.00	-23.23	peak



Mode:g; Polarization:Horizontal; Modulation:GFSK; ; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 07054CR/07055CR
Mode : 2402 Band edge
Note : BLE1M R

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2369.189	4.31	28.48	40.96	58.50	50.33	74.00	-23.67	peak
2	2390.000	4.34	28.52	40.97	56.14	48.03	74.00	-25.97	peak
3 *	2402.000	4.36	28.54	40.98	101.42	93.34	74.00	19.34	peak



Mode:g; Polarization:Vertical; Modulation:GFSK; ; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 07054CR/07055CR
Mode : 2402 Band edge
Note : BLE1M R

	Freq	Cable Loss	Ant Factor	Preamplifier Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2311.469	4.21	28.38	40.94	58.75	50.40	74.00	-23.60	peak
2	2390.000	4.34	28.52	40.97	56.30	48.19	74.00	-25.81	peak
3 *	2402.000	4.36	28.54	40.98	97.19	89.11	74.00	15.11	peak



Mode:g; Polarization:Horizontal; Modulation:GFSK; ; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 07054CR/07055CR
Mode : 2480 Band edge
Note : BLE1M R

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 * 2480.000	4.49	28.67	41.01	104.22	96.37	74.00	22.37	peak
2 2483.500	4.49	28.67	41.01	57.23	49.38	74.00	-24.62	peak
3 2484.221	4.50	28.67	41.01	59.30	51.46	74.00	-22.54	peak



Mode:g; Polarization:Vertical; Modulation:GFSK; ; Channel:High




Site : chamber
Condition: 3m VERTICAL
Job No : 07054CR/07055CR
Mode : 2480 Band edge
Note : BLE1M R

	Freq	Cable Loss	Ant Factor	Preamplifier Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 *	2480.000	4.49	28.67	41.01	97.17	89.32	74.00	15.32	peak
2	2483.500	4.49	28.67	41.01	55.90	48.05	74.00	-25.95	peak
3	2492.824	4.51	28.69	41.01	57.96	50.15	74.00	-23.85	peak



Mode:h; Polarization:Horizontal; Modulation:GFSK; ; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 07054CR/07055CR
Mode : 2480 Band edge
Note : BLE2M L

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 *	2480.000	4.49	28.67	41.01	101.92	94.07	74.00	20.07	peak
2	2483.500	4.49	28.67	41.01	60.35	52.50	74.00	-21.50	peak
3	2484.545	4.50	28.67	41.01	59.03	51.19	74.00	-22.81	peak



Mode:h; Polarization:Vertical; Modulation:GFSK; ; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 07054CR/07055CR
Mode : 2480 Band edge
Note : BLE2M L

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 *	2480.000	4.49	28.67	41.01	95.76	87.91	74.00	13.91	peak
2	2483.500	4.49	28.67	41.01	57.59	49.74	74.00	-24.26	peak
3	2489.369	4.50	28.68	41.01	58.64	50.81	74.00	-23.19	peak



Mode:h; Polarization:Horizontal; Modulation:GFSK; ; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 07054CR/07055CR
Mode : 2402 Band edge
Note : BLE2M L

	Freq	Cable Loss	Ant Factor	Preamplifier Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2381.874	4.33	28.50	40.97	58.72	50.58	74.00	-23.42	peak
2	2390.000	4.34	28.52	40.97	57.44	49.33	74.00	-24.67	peak
3 *	2402.000	4.36	28.54	40.98	97.27	89.19	74.00	15.19	peak



Mode:h; Polarization:Vertical; Modulation:GFSK; ; Channel:High




Site : chamber
Condition: 3m VERTICAL
Job No : 07054CR/07055CR
Mode : 2402 Band edge
Note : BLE2M L

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2333.714	4.25	28.42	40.95	58.37	50.09	74.00	-23.91	peak
2	2390.000	4.34	28.52	40.97	57.40	49.29	74.00	-24.71	peak
3 *	2402.000	4.36	28.54	40.98	93.79	85.71	74.00	11.71	peak



Mode:i; Polarization:Horizontal; Modulation:GFSK; ; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 07054CR/07055CR
Mode : 2402 Band edge
Note : BLE2M R

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2370.696	4.31	28.49	40.96	58.35	50.19	74.00	-23.81	peak
2	2390.000	4.34	28.52	40.97	56.90	48.79	74.00	-25.21	peak
3 *	2402.000	4.36	28.54	40.98	101.55	93.47	74.00	19.47	peak



Mode:i; Polarization:Vertical; Modulation:GFSK; ; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 07054CR/07055CR
Mode : 2402 Band edge
Note : BLE2M R

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2364.575	4.30	28.48	40.96	58.49	50.31	74.00	-23.69	peak
2	2390.000	4.34	28.52	40.97	56.35	48.24	74.00	-25.76	peak
3 *	2402.000	4.36	28.54	40.98	97.25	89.17	74.00	15.17	peak



Mode:i; Polarization:Horizontal; Modulation:GFSK; ; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 07054CR\07055CR
Mode : 2480 Band edge
Note : BLE 2M R

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 *	2480.000	4.49	28.67	41.01	99.43	91.58	74.00	17.58	peak
2	2483.500	4.49	28.67	41.01	59.52	51.67	74.00	-22.33	peak
3	2498.970	4.52	28.70	41.02	59.20	51.40	74.00	-22.60	peak



Mode:i; Polarization:Vertical; Modulation:GFSK; ; Channel:High



Site : chamber
Condition: 3m VERTICAL
Job No : 07054CR\07055CR
Mode : 2480 Band edge
Note : BLE 2M R

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 *	2480.000	4.49	28.67	41.01	93.14	85.29	74.00	11.29 peak
2	2483.500	4.49	28.67	41.01	57.98	50.13	74.00	-23.87 peak
3	2493.952	4.51	28.69	41.02	58.57	50.75	74.00	-23.25 peak



7.7 Radiated Spurious Emissions

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2013) Section 6.4,6.5,6.6

Measurement Distance: 3m

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.



7.7.1 E.U.T. Operation


Operating Environment:

Temperature: 25.1 °C Humidity: 64.3 % RH Atmospheric Pressure: 1010 mbar

Test modes:

- c:TX mode(Left Earphone,1Mb/s)_Keep the EUT in continuously transmitting mode with GFSK modulation
- g:TX mode(Right Earphone,1Mb/s)_Keep the EUT in continuously transmitting mode with GFSK modulation
- h:TX mode(Left Earphone,2Mb/s)_Keep the EUT in continuously transmitting mode with GFSK modulation
- i:TX mode(Right Earphone,2Mb/s)_Keep the EUT in continuously transmitting mode with GFSK modulation

7.7.2 Test Setup Diagram



Below 30MHz

30MHz-1GHz

Above 1GHz



7.7.3 Measurement Procedure and Data

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Remark:


- 1) For emission below 1GHz, through pre-scan found the worst case is the lowest channel. Only the worst case is recorded in the report.
- 2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor
- 3) Scan from 9kHz to 25GHz, the disturbance above 18GHz and below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
- 4) For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

Left Earphone:

30MHz~1GHz

QP value:

Mode: c; Polarization: Horizontal;




Condition: 3m HORIZONTAL

Job No. : 07054CR

Mode : c

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	30.96	0.61	21.95	27.73	25.03	19.86	40.00	-20.14	QP
2	99.53	1.11	13.96	27.61	24.53	11.99	43.50	-31.51	QP
3	230.10	1.48	18.03	27.05	26.87	19.33	46.00	-26.67	QP
4	369.40	2.22	21.63	27.25	25.48	22.08	46.00	-23.92	QP
5	638.37	2.78	27.12	28.04	26.38	28.24	46.00	-17.76	QP
6 pp	932.27	3.53	29.97	27.00	24.87	31.37	46.00	-14.63	QP

Mode :c; Polarization: Vertical



Condition: 3m VERTICAL

Job No. : 07054CR


Mode : c

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	32.86	0.63	20.92	27.73	24.05	17.87	40.00	-22.13	QP
2	91.17	1.28	13.21	27.62	24.69	11.56	43.50	-31.94	QP
3	239.99	1.56	18.80	27.02	24.30	17.64	46.00	-28.36	QP
4	440.20	2.39	23.34	27.57	25.09	23.25	46.00	-22.75	QP
5 pp	726.81	3.01	28.07	27.86	25.02	28.24	46.00	-17.76	QP
6	965.54	3.57	30.13	26.83	24.75	31.62	54.00	-22.38	QP



Above 1GHz

Mode:c; Polarization:Horizontal; Modulation:GFSK; ; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 07054CR\07055CR
Mode : 2402 TX SE
Note : BLE 1M L

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1697.129	3.43	26.66	40.63	47.34	36.80	74.00	-37.20	peak
2	4443.453	6.71	33.50	42.51	48.68	46.38	74.00	-27.62	peak
3	4804.000	7.10	33.97	42.77	47.74	46.04	74.00	-27.96	peak
4	6815.551	8.45	35.79	41.78	48.35	50.81	74.00	-23.19	peak
5	7206.000	8.74	36.07	41.58	47.21	50.44	74.00	-23.56	peak
6	9608.000	10.81	37.67	38.57	43.45	53.36	74.00	-20.64	peak



Mode:c; Polarization:Vertical; Modulation:GFSK; ; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 07054CR\07055CR
Mode : 2402 TX SE
Note : BLE 1M L

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1606.441	3.35	26.28	40.57	47.89	36.95	74.00	-37.05	peak
2	4469.214	6.73	33.55	42.53	48.39	46.14	74.00	-27.86	peak
3	4804.000	7.10	33.97	42.77	46.93	45.23	74.00	-28.77	peak
4	6564.209	8.31	35.64	41.92	49.43	51.46	74.00	-22.54	peak
5	7206.000	8.74	36.07	41.58	47.80	51.03	74.00	-22.97	peak
6	9608.000	10.81	37.67	38.57	43.18	53.09	74.00	-20.91	peak



Mode:c; Polarization:Horizontal; Modulation:GFSK; ; Channel:middle




Site : chamber
Condition: 3m HORIZONTAL
Job No : 07054CR\07055CR
Mode : 2440 TX SE
Note : BLE 1M L

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1702.042	3.43	26.68	40.63	46.70	36.18	74.00	-37.82	peak
2	4304.400	6.58	33.26	42.40	49.61	47.05	74.00	-26.95	peak
3	4880.000	7.18	34.06	42.82	47.40	45.82	74.00	-28.18	peak
4	6640.542	8.36	35.69	41.87	48.45	50.63	74.00	-23.37	peak
5	7320.000	8.84	36.16	41.52	46.90	50.38	74.00	-23.62	peak
6	9760.000	10.76	37.76	38.35	43.64	53.81	74.00	-20.19	peak



Mode:c; Polarization:Vertical; Modulation:GFSK; ; Channel:middle




Site : chamber
Condition: 3m VERTICAL
Job No : 07054CR\07055CR
Mode : 2440 TX SE
Note : BLE 1M L

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1692.231	3.42	26.64	40.63	47.94	37.37	74.00	-36.63	peak
2	4430.628	6.70	33.48	42.50	48.95	46.63	74.00	-27.37	peak
3	4880.000	7.18	34.06	42.82	47.98	46.40	74.00	-27.60	peak
4	6621.375	8.34	35.67	41.88	48.86	50.99	74.00	-23.01	peak
5	7320.000	8.84	36.16	41.52	46.91	50.39	74.00	-23.61	peak
6	9760.000	10.76	37.76	38.35	43.10	53.27	74.00	-20.73	peak



Mode:c; Polarization:Horizontal; Modulation:GFSK; ; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 07054CR\07055CR
Mode : 2480 TX SE
Note : BLE 1M L

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1697.129	3.43	26.66	40.63	47.01	36.47	74.00	-37.53	peak
2	4392.376	6.66	33.42	42.47	49.00	46.61	74.00	-27.39	peak
3	4960.000	7.26	34.15	42.87	47.85	46.39	74.00	-27.61	peak
4	6526.373	8.29	35.62	41.94	49.27	51.24	74.00	-22.76	peak
5	7440.000	8.96	36.25	41.46	47.14	50.89	74.00	-23.11	peak
6	9920.000	10.71	37.85	38.12	43.05	53.49	74.00	-20.51	peak



Mode:c; Polarization:Vertical; Modulation:GFSK; ; Channel:High




Site : chamber
Condition: 3m VERTICAL
Job No : 07054CR\07055CR
Mode : 2480 TX SE
Note : BLE 1M L

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1677.621	3.41	26.58	40.62	48.05	37.42	74.00	-36.58	peak
2	3328.077	5.30	31.44	41.55	47.52	42.71	74.00	-31.29	peak
3	4960.000	7.26	34.15	42.87	48.34	46.88	74.00	-27.12	peak
4	6995.172	8.54	35.90	41.69	48.09	50.84	74.00	-23.16	peak
5	7440.000	8.96	36.25	41.46	46.98	50.73	74.00	-23.27	peak
6	9920.000	10.71	37.85	38.12	42.29	52.73	74.00	-21.27	peak



Mode:h; Polarization:Horizontal; Modulation:GFSK; ; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 07054CR\07055CR
Mode : 2402 TX SE
Note : BLE 2M L

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1663.137	3.40	26.52	40.61	49.78	39.09	74.00	-34.91	peak
2	4417.841	6.68	33.46	42.49	49.46	47.11	74.00	-26.89	peak
3	4804.000	7.10	33.97	42.77	47.27	45.57	74.00	-28.43	peak
4	6756.708	8.42	35.76	41.81	49.26	51.63	74.00	-22.37	peak
5	7206.000	8.74	36.07	41.58	47.62	50.85	74.00	-23.15	peak
6	9608.000	10.81	37.67	38.57	43.49	53.40	74.00	-20.60	peak



Mode:h; Polarization:Vertical; Modulation:GFSK; ; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 07054CR\07055CR
Mode : 2402 TX SE
Note : BLE 2M L

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1658.337	3.40	26.50	40.61	49.15	38.44	74.00	-35.56	peak
2	4367.058	6.64	33.37	42.45	49.43	46.99	74.00	-27.01	peak
3	4804.000	7.10	33.97	42.77	48.38	46.68	74.00	-27.32	peak
4	6894.806	8.49	35.84	41.74	47.93	50.52	74.00	-23.48	peak
5	7206.000	8.74	36.07	41.58	47.32	50.55	74.00	-23.45	peak
6	9608.000	10.81	37.67	38.57	43.22	53.13	74.00	-20.87	peak



Mode:h; Polarization:Horizontal; Modulation:GFSK; ; Channel:middle




Site : chamber
Condition: 3m HORIZONTAL
Job No : 07054CR\07055CR
Mode : 2440 TX SE
Note : BLE 2M L

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1697.129	3.43	26.66	40.63	47.13	36.59	74.00	-37.41	peak
2	4354.454	6.63	33.35	42.44	49.34	46.88	74.00	-27.12	peak
3	4880.000	7.18	34.06	42.82	48.12	46.54	74.00	-27.46	peak
4	6795.879	8.44	35.78	41.79	48.66	51.09	74.00	-22.91	peak
5	7320.000	8.84	36.16	41.52	47.25	50.73	74.00	-23.27	peak
6	9760.000	10.76	37.76	38.35	42.98	53.15	74.00	-20.85	peak



Mode:h; Polarization:Vertical; Modulation:GFSK; ; Channel:middle




Site : chamber
Condition: 3m VERTICAL
Job No : 07054CR\07055CR
Mode : 2440 TX SE
Note : BLE 2M L

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1663.137	3.40	26.52	40.61	49.15	38.46	74.00	-35.54	peak
2	4367.058	6.64	33.37	42.45	49.24	46.80	74.00	-27.20	peak
3	4880.000	7.18	34.06	42.82	47.83	46.25	74.00	-27.75	peak
4	6340.436	8.27	35.44	42.04	49.11	50.78	74.00	-23.22	peak
5	7320.000	8.84	36.16	41.52	46.26	49.74	74.00	-24.26	peak
6	9760.000	10.76	37.76	38.35	43.49	53.66	74.00	-20.34	peak



Mode:h; Polarization:Horizontal; Modulation:GFSK; ; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 07054CR\07055CR
Mode : 2480 TX SE
Note : BLE 2M L

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1692.231	3.42	26.64	40.63	46.70	36.13	74.00	-37.87	peak
2	4482.150	6.74	33.57	42.54	49.10	46.87	74.00	-27.13	peak
3	4960.000	7.26	34.15	42.87	47.92	46.46	74.00	-27.54	peak
4	6303.890	8.27	35.41	42.06	48.72	50.34	74.00	-23.66	peak
5	7440.000	8.96	36.25	41.46	47.25	51.00	74.00	-23.00	peak
6	9920.000	10.71	37.85	38.12	42.30	52.74	74.00	-21.26	peak



Mode:h; Polarization:Vertical; Modulation:GFSK; ; Channel:High



Site : chamber
Condition: 3m VERTICAL
Job No : 07054CR\07055CR
Mode : 2480 TX SE
Note : BLE 2M L

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1145.507	2.66	24.34	40.24	52.20	38.96	74.00	-35.04	peak
2	4304.400	6.58	33.26	42.40	49.41	46.85	74.00	-27.15	peak
3	4960.000	7.26	34.15	42.87	48.51	47.05	74.00	-26.95	peak
4	6934.778	8.51	35.86	41.72	48.28	50.93	74.00	-23.07	peak
5	7440.000	8.96	36.25	41.46	47.70	51.45	74.00	-22.55	peak
6	9920.000	10.71	37.85	38.12	42.92	53.36	74.00	-20.64	peak




Right Earphone

30MHz~1GHz

QP value:

Mode: g; Polarization: Horizontal;




Condition: 3m HORIZONTAL

Job No. : 07054CR

Mode : g

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	31.18	0.61	21.83	27.73	24.83	19.54	40.00	-20.46	QP
2	90.54	1.29	13.15	27.62	25.25	12.07	43.50	-31.43	QP
3	157.01	1.17	15.25	27.31	25.26	14.37	43.50	-29.13	QP
4	223.73	1.42	17.51	27.07	25.20	17.06	46.00	-28.94	QP
5	449.56	2.40	23.55	27.61	25.46	23.80	46.00	-22.20	QP
6 pp	906.48	3.51	29.83	27.13	27.32	33.53	46.00	-12.47	QP

Mode :g; Polarization: Vertical



Condition: 3m VERTICAL

Job No. : 07054CR


Mode : g

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	35.38	0.66	19.64	27.72	24.22	16.80	40.00	-23.20	QP
2	90.54	1.29	13.15	27.62	25.16	11.98	43.50	-31.52	QP
3	258.33	1.70	19.08	26.97	23.67	17.48	46.00	-28.52	QP
4	394.85	2.29	22.27	27.37	25.81	23.00	46.00	-23.00	QP
5	694.42	2.89	27.83	27.93	25.32	28.11	46.00	-17.89	QP
6 pp	903.31	3.50	29.82	27.15	25.21	31.38	46.00	-14.62	QP



Above 1GHz

Mode:g; Polarization:Horizontal; Modulation:GFSK; ; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 07054CR\07055CR
Mode : 2402 TX SE
Note : BLE 1M R

	Freq	Cable Loss	Ant Factor	Preamplifier Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1687.347	3.42	26.62	40.62	49.54	38.96	74.00	-35.04	peak
2	4495.125	6.76	33.59	42.55	49.67	47.47	74.00	-26.53	peak
3	4804.000	7.10	33.97	42.77	46.69	44.99	74.00	-29.01	peak
4	6974.982	8.53	35.89	41.70	47.96	50.68	74.00	-23.32	peak
5	7206.000	8.74	36.07	41.58	47.47	50.70	74.00	-23.30	peak
6	9608.000	10.81	37.67	38.57	43.33	53.24	74.00	-20.76	peak



Mode:g; Polarization:Vertical; Modulation:GFSK; ; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 07054CR\07055CR
Mode : 2402 TX SE
Note : BLE 1M R

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1663.137	3.40	26.52	40.61	50.07	39.38	74.00	-34.62	peak
2	4206.011	6.48	33.08	42.32	49.31	46.55	74.00	-27.45	peak
3	4804.000	7.10	33.97	42.77	47.22	45.52	74.00	-28.48	peak
4	6679.040	8.38	35.71	41.85	48.96	51.20	74.00	-22.80	peak
5	7206.000	8.74	36.07	41.58	46.55	49.78	74.00	-24.22	peak
6	9608.000	10.81	37.67	38.57	43.47	53.38	74.00	-20.62	peak



Mode:g; Polarization:Horizontal; Modulation:GFSK; ; Channel:middle




Site : chamber
Condition: 3m HORIZONTAL
Job No : 07054CR\07055CR
Mode : 2440 TX SE
Note : BLE 1M R

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1653.550	3.39	26.48	40.60	47.78	37.05	74.00	-36.95	peak
2	4367.058	6.64	33.37	42.45	49.72	47.28	74.00	-26.72	peak
3	4880.000	7.18	34.06	42.82	47.61	46.03	74.00	-27.97	peak
4	6432.732	8.28	35.54	41.99	48.95	50.78	74.00	-23.22	peak
5	7320.000	8.84	36.16	41.52	47.05	50.53	74.00	-23.47	peak
6	9760.000	10.76	37.76	38.35	43.38	53.55	74.00	-20.45	peak



Mode:g; Polarization:Vertical; Modulation:GFSK; ; Channel:middle




Site : chamber
Condition: 3m VERTICAL
Job No : 07054CR\07055CR
Mode : 2440 TX SE
Note : BLE 1M R

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1611.091	3.36	26.30	40.58	50.40	39.48	74.00	-34.52	peak
2	4417.841	6.68	33.46	42.49	49.26	46.91	74.00	-27.09	peak
3	4880.000	7.18	34.06	42.82	47.52	45.94	74.00	-28.06	peak
4	6526.373	8.29	35.62	41.94	48.74	50.71	74.00	-23.29	peak
5	7320.000	8.84	36.16	41.52	46.25	49.73	74.00	-24.27	peak
6	9760.000	10.76	37.76	38.35	42.86	53.03	74.00	-20.97	peak



Mode:g; Polarization:Horizontal; Modulation:GFSK; ; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 07054CR\07055CR
Mode : 2480 TX SE
Note : BLE 1M R

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1644.019	3.38	26.44	40.60	47.62	36.84	74.00	-37.16	peak
2	4367.058	6.64	33.37	42.45	48.90	46.46	74.00	-27.54	peak
3	4960.000	7.26	34.15	42.87	47.77	46.31	74.00	-27.69	peak
4	6602.265	8.33	35.66	41.89	48.64	50.74	74.00	-23.26	peak
5	7440.000	8.96	36.25	41.46	47.31	51.06	74.00	-22.94	peak
6	9920.000	10.71	37.85	38.12	42.14	52.58	74.00	-21.42	peak



Mode:g; Polarization:Vertical; Modulation:GFSK; ; Channel:High




Site : chamber
Condition: 3m VERTICAL
Job No : 07054CR\07055CR
Mode : 2480 TX SE
Note : BLE 1M R

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1601.804	3.35	26.26	40.57	51.04	40.08	74.00	-33.92	peak
2	4367.058	6.64	33.37	42.45	48.86	46.42	74.00	-27.58	peak
3	4960.000	7.26	34.15	42.87	48.19	46.73	74.00	-27.27	peak
4	6545.263	8.30	35.63	41.93	49.06	51.06	74.00	-22.94	peak
5	7440.000	8.96	36.25	41.46	47.54	51.29	74.00	-22.71	peak
6	9920.000	10.71	37.85	38.12	42.68	53.12	74.00	-20.88	peak



Mode:i; Polarization:Horizontal; Modulation:GFSK; ; Channel:Low



Site : chamber
Condition: 3m HORIZONTAL
Job No : 07054CR\07055CR
Mode : 2402 TX SE
Note : BLE 2M R

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1644.019	3.38	26.44	40.60	48.73	37.95	74.00	-36.05	peak
2	4495.125	6.76	33.59	42.55	48.89	46.69	74.00	-27.31	peak
3	4804.000	7.10	33.97	42.77	47.50	45.80	74.00	-28.20	peak
4	6159.797	8.27	35.26	42.15	49.14	50.52	74.00	-23.48	peak
5	7206.000	8.74	36.07	41.58	47.11	50.34	74.00	-23.66	peak
6	9608.000	10.81	37.67	38.57	43.63	53.54	74.00	-20.46	peak




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.
Attention: To check the authenticity of testing / inspection report and certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch (Testing Center) EEC Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Mode:i; Polarization:Vertical; Modulation:GFSK; ; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 07054CR\07055CR
Mode : 2402 TX SE
Note : BLE 2M R

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1682.477	3.42	26.60	40.62	52.76	42.16	74.00	-31.84	peak
2	4304.400	6.58	33.26	42.40	49.97	47.41	74.00	-26.59	peak
3	4804.000	7.10	33.97	42.77	47.48	45.78	74.00	-28.22	peak
4	6974.982	8.53	35.89	41.70	47.62	50.34	74.00	-23.66	peak
5	7206.000	8.74	36.07	41.58	47.32	50.55	74.00	-23.45	peak
6	9608.000	10.81	37.67	38.57	43.66	53.57	74.00	-20.43	peak



Mode:i; Polarization:Horizontal; Modulation:GFSK; ; Channel:middle




Site : chamber
Condition: 3m HORIZONTAL
Job No : 07054CR\07055CR
Mode : 2440 TX SE
Note : BLE 2M R

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1692.231	3.42	26.64	40.63	47.36	36.79	74.00	-37.21	peak
2	4367.058	6.64	33.37	42.45	50.06	47.62	74.00	-26.38	peak
3	4880.000	7.18	34.06	42.82	47.54	45.96	74.00	-28.04	peak
4	6432.732	8.28	35.54	41.99	48.83	50.66	74.00	-23.34	peak
5	7320.000	8.84	36.16	41.52	46.36	49.84	74.00	-24.16	peak
6	9760.000	10.76	37.76	38.35	43.51	53.68	74.00	-20.32	peak



Mode:i; Polarization:Vertical; Modulation:GFSK; ; Channel:middle




Site : chamber
Condition: 3m VERTICAL
Job No : 07054CR\07055CR
Mode : 2440 TX SE
Note : BLE 2M R

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1606.441	3.35	26.28	40.57	49.46	38.52	74.00	-35.48	peak
2	4456.315	6.72	33.53	42.52	49.13	46.86	74.00	-27.14	peak
3	4880.000	7.18	34.06	42.82	47.71	46.13	74.00	-27.87	peak
4	6358.789	8.27	35.46	42.03	48.80	50.50	74.00	-23.50	peak
5	7320.000	8.84	36.16	41.52	46.33	49.81	74.00	-24.19	peak
6	9760.000	10.76	37.76	38.35	42.70	52.87	74.00	-21.13	peak



Mode:i; Polarization:Horizontal; Modulation:GFSK; ; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 07054CR\07055CR
Mode : 2480 TX SE
Note : BLE 2M R

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1625.121	3.37	26.36	40.59	49.44	38.58	74.00	-35.42	peak
2	4469.214	6.73	33.55	42.53	48.67	46.42	74.00	-27.58	peak
3	4960.000	7.26	34.15	42.87	48.34	46.88	74.00	-27.12	peak
4	6934.778	8.51	35.86	41.72	47.87	50.52	74.00	-23.48	peak
5	7440.000	8.96	36.25	41.46	47.81	51.56	74.00	-22.44	peak
6	9920.000	10.71	37.85	38.12	42.03	52.47	74.00	-21.53	peak



Mode:i; Polarization:Vertical; Modulation:GFSK; ; Channel:High



Site : chamber
Condition: 3m VERTICAL
Job No : 07054CR\07055CR
Mode : 2480 TX SE
Note : BLE 2M R

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	1601.804	3.35	26.26	40.57	47.38	36.42	74.00	-37.58 peak
2	4230.396	6.51	33.13	42.34	49.32	46.62	74.00	-27.38 peak
3	4960.000	7.26	34.15	42.87	47.97	46.51	74.00	-27.49 peak
4	6231.427	8.27	35.34	42.10	49.20	50.71	74.00	-23.29 peak
5	7440.000	8.96	36.25	41.46	46.86	50.61	74.00	-23.39 peak
6	9920.000	10.71	37.85	38.12	42.85	53.29	74.00	-20.71 peak



8 Photographs

8.1 Test Setup

Please refer to setup photos.

8.2 EUT Constructional Details (EUT Photos)

Please refer to external and internal photos for details.



9 Appendix


9.1 Appendix 15.247 – Left



1. Duty Cycle



1.1 Test Result


Test Mode	Channel Frequency(MHz)	TX Type	ANT No.	T_on (ms)	Period (ms)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)
1M	2402	SISO	1	0.392	0.625	62.72	2.03
	2440	SISO	1	0.392	0.625	62.72	2.03
	2480	SISO	1	0.392	0.625	62.72	2.03
2M	2402	SISO	1	0.206	0.625	32.96	4.82
	2440	SISO	1	0.206	0.624	33.01	4.81
	2480	SISO	1	0.206	0.624	33.01	4.81

1.2 Test Graph











2. Bandwidth

2.1 Test Result

Test Mode	Frequency (MHz)	TX Type	ANT No.	6dB Bandwidth	Verdict
				Test Result (MHz)	
1M	2402	SISO	1	0.724	PASS
	2440	SISO	1	0.718	PASS
	2480	SISO	1	0.713	PASS
2M	2402	SISO	1	1.253	PASS
	2440	SISO	1	1.257	PASS
	2480	SISO	1	1.258	PASS



2.2 Test Graph - 6dB Bandwidth





Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com








3. Maximum Conducted Output Power



3.1 Test Result


Test Mode	Frequency (MHz)	Tx Type	Measured Peak Output Power (dBm)	Limits (dBm)	Verdict
			Ant 1		
1M	2402	SISO	2.13	30	PASS
	2440	SISO	2.42	30	PASS
	2480	SISO	2.59	30	PASS
2M	2402	SISO	2.25	30	PASS
	2440	SISO	2.48	30	PASS
	2480	SISO	2.93	30	PASS

3.2 Test Graph













4. Maximum Power Spectral Density (PSD)



4.1 Test Result

Test Mode	Frequency (MHz)	Tx Type	Maximum Power Spectral Density (dBm/3KHz)	Limits (dBm/3kHz)	Verdict
			Ant 1		
1M	2402	SISO	-13.55	≤8	PASS
	2440	SISO	-13.29	≤8	PASS
	2480	SISO	-12.90	≤8	PASS
2M	2402	SISO	-16.26	≤8	PASS
	2440	SISO	-15.96	≤8	PASS
	2480	SISO	-15.47	≤8	PASS

4.2 Test Graph










5. Unwanted Emissions in Non-restricted Frequency Bands



5.1 Test Result



Test Mode	Frequency (MHz)	TX Type	ANT No.	Spurious Conducted Emission (dBm)	Limits (dBm)	Verdict
1M	2402	SISO	1	Refer to test graph	-17.76	PASS
	2440	SISO	1	Refer to test graph	-17.76	PASS
	2480	SISO	1	Refer to test graph	-17.76	PASS
2M	2402	SISO	1	Refer to test graph	-17.76	PASS
	2440	SISO	1	Refer to test graph	-17.76	PASS
	2480	SISO	1	Refer to test graph	-17.76	PASS



5.2 Test Graph



















9.2 Appendix 15.247 – Right



1. Duty Cycle



1.1 Test Result


Test Mode	Channel Frequency(MHz)	TX Type	ANT No.	T_on (ms)	Period (ms)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)
1M	2402	SISO	1	0.392	0.626	62.62	2.03
	2440	SISO	1	0.392	0.626	62.62	2.03
	2480	SISO	1	0.392	0.626	62.62	2.03
2M	2402	SISO	1	0.206	0.625	32.96	4.82
	2440	SISO	1	0.207	0.625	33.12	4.80
	2480	SISO	1	0.207	0.625	33.12	4.80

1.2 Test Graph













2. Bandwidth



2.1 Test Result

Test Mode	Frequency (MHz)	TX Type	ANT No.	6dB Bandwidth	Verdict
				Test Result (MHz)	
1M	2402	SISO	1	0.717	PASS
	2440	SISO	1	0.717	PASS
	2480	SISO	1	0.714	PASS
2M	2402	SISO	1	1.261	PASS
	2440	SISO	1	1.259	PASS
	2480	SISO	1	1.248	PASS

2.2 Test Graph - 6dB Bandwidth










3. Maximum Conducted Output Power



3.1 Test Result


Test Mode	Frequency (MHz)	Tx Type	Measured Peak Output Power (dBm)	Limits (dBm)	Verdict
			Ant 1		
1M	2402	SISO	2.56	30	PASS
	2440	SISO	2.79	30	PASS
	2480	SISO	3.20	30	PASS
2M	2402	SISO	2.60	30	PASS
	2440	SISO	2.89	30	PASS
	2480	SISO	3.23	30	PASS

3.2 Test Graph













4. Maximum Power Spectral Density (PSD)



4.1 Test Result

Test Mode	Frequency (MHz)	Tx Type	Maximum Power Spectral Density (dBm/3KHz)	Limits (dBm/3kHz)	Verdict
			Ant 1		
1M	2402	SISO	-13.64	≤8	PASS
	2440	SISO	-13.28	≤8	PASS
	2480	SISO	-12.95	≤8	PASS
2M	2402	SISO	-16.19	≤8	PASS
	2440	SISO	-16.03	≤8	PASS
	2480	SISO	-15.64	≤8	PASS

4.2 Test Graph










5. Unwanted Emissions in Non-restricted Frequency Bands



5.1 Test Result



Test Mode	Frequency (MHz)	TX Type	ANT No.	Spurious Conducted Emission (dBm)	Limits (dBm)	Verdict
1M	2402	SISO	1	Refer to test graph	-17.84	PASS
	2440	SISO	1	Refer to test graph	-17.84	PASS
	2480	SISO	1	Refer to test graph	-17.84	PASS
2M	2402	SISO	1	Refer to test graph	-17.84	PASS
	2440	SISO	1	Refer to test graph	-17.84	PASS
	2480	SISO	1	Refer to test graph	-17.84	PASS



5.2 Test Graph


















- End of the Report -

