FCC TEST REPORT

For

ShenZhen Megastek Electronics Co. Ltd.

GPS ankle tracker

Model No.: MT200

Additional Model No.: MT200X

Prepared for : ShenZhen Megastek Electronics Co. Ltd.

Address : RmB1111,Niulanqian Building,Minzhi Road,Longhua Town,Baoan

District, Shenzhen, China.

Prepared by : Shenzhen LCS Compliance Testing Laboratory Ltd.

Address : 1F., Xingyuan Industrial Park, Tongda Road, Bao'an Blvd., Bao'an District,

Shenzhen, Guangdong, China

Tel : (+86)755-82591330
Fax : (+86)755-82591332
Web : www.LCS-cert.com

Mail : webmaster@LCS-cert.com

Date of receipt of test sample : December 13, 2016

Number of tested samples : 1

Serial number : Prototype

Date of Test : December 13, 2016~January 05, 2017

Date of Report : January 05, 2017

FCC PART 22/24 TEST REPORT

FCC Part 22 /Part 24

Report Reference No...... LCS1612131594E

Date of Issue. January 05, 2017

Testing Laboratory Name Shenzhen LCS Compliance Testing Laboratory Ltd.

1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue,

Applicant's name...... ShenZhen Megastek Electronics Co. Ltd.

District, Shenzhen, China.

Test specification:

Standard FCC Part 22: PUBLIC MOBILE SERVICES

FCC Part 24: PERSONAL COMMUNICATIONS SERVICES

Test Report Form No LCSEMC-1.0

Master TRF...... Dated 2011-03

Shenzhen LCS Compliance Testing Laboratory Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen LCS Compliance Testing Laboratory Ltd. is acknowledged as copyright owner and source of the material. Shenzhen LCS Compliance Testing Laboratory Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test item description GPS ankle tracker

Trade Mark N/A

Model/Type reference...... MT200

Ratings DC 3.7V by battery(1600mAh)

Charging voltage: DC 5.0V, 1.0A

Frequency...... GSM 850MHz; PCS 1900MHz;

Result..... PASS

Compiled by:

Supervised by:

Approved by:

Dick Su/ File administrators

Glin Lu/ Technique principal

Gavin Liang/ Manager

TEST REPORT

Tost Panort No :	LCS1612131594E	January 05, 2017
Test Report No. :	E001012131334E	Date of issue

Type / Model..... : MT200 EUT.....: GPS ankle tracker Applicant..... : ShenZhen Megastek Electronics Co. Ltd. Address..... : RmB1111,Niulanqian Building,Minzhi Road,Longhua Town,Baoan District, Shenzhen, China. Telephone.....:: / Fax..... : ShenZhen Megastek Electronics Co. Ltd. Manufacturer..... Address..... : RmB1111,Niulanqian Building,Minzhi Road,Longhua Town,Baoan District, Shenzhen, China. Telephone.....:: / Fax.....: : / Factory...... ShenZhen Megastek Electronics Co. Ltd. Address.....: RmB1111, Niulangian Building, Minzhi Road, Longhua Town, Baoan District, Shenzhen, China. Telephone.....: : / Fax.....: : /

Test Result:	PASS
--------------	------

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Revison History

Revision	Issue Date	Revisions	Revised By
00	2017-01-05	Initial Issue	Gavin Liang

Contents

<u>1</u>	TEST STANDARDS	6
<u>2</u>	SUMMARY	7
_	00 m m A R T	···· /
2.1	General Remarks	7
2.1	Product Description	7
2.3	Equipment under Test	7
2.4	Short description of the Equipment under Test (EUT)	8
2.5	Internal Identification of AE used during the test	8
2.6	Normal Accessory setting	8
2.7	EUT configuration	8
2.8	Related Submittal(s) / Grant (s)	9
2.9	Modifications	9
2.10	General Test Conditions/Configurations	9
	•	
<u>3</u>	TEST ENVIRONMENT	9
3.1	Address of the test laboratory	9
3.2	Test Facility	10
3.3	Environmental conditions	10
3.4	Test Description	10
3.5	Equipments Used during the Test	12
3.6	Measurement uncertainty	13
<u>4</u>	TEST CONDITIONS AND RESULTS	14
4.1	Output Power	14
4.2	Radiated Spurious Emssion	19
4.3	Occupied Bandwidth and Emission Bandwidth	23
4.4	Band Edge Complicance	26
4.5	Spurious Emssion on Antenna Port	29
4.6	Frequency Stability Test	38
4.7	Peak-to-Average Ratio (PAR)	41
4.8	AC Power line conducted emissions	48

1 TEST STANDARDS

The tests were performed according to following standards:

FCC Part 22 (10-1-16 Edition): PRIVATE LAND MOBILE RADIO SERVICES.

FCC Part 24(10-1-16 Edition): PUBLIC MOBILE SERVICES

<u>TIA/EIA 603 D June 2010:</u> Land Mobile FM or PM Communications Equipment Measurement and Performance Standards.

47 CFR FCC Part 15 Subpart B: Unintentional Radiators

FCC Part 2: FREQUENCY ALLOCA-TIONS AND RADIO TREATY MAT-TERS; GENERAL RULES AND REG-ULATIONS

ANSI C63.4:2014: Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz

2 SUMMARY

2.1 General Remarks

Date of receipt of test sample	:	December 13, 2016
Testing commenced on	:	December 13, 2016
Testing concluded on	:	January 05, 2017

2.2 Product Description

The **ShenZhen Megastek Electronics Co. Ltd.** 's Model: MT200 or the "EUT" as referred to in this report; more general information as follows, for more details, refer to the user's manual of the EUT.

EUT : GPS ankle tracker Model Number : MT200, MT200X

Model Declaration : PCB board, structure and internal of these model(s) are the

same, So no additional models were tested

Test Model : MT200 Hardware version : 2016-11-08

Software version : ZD-01_20161205

Power Supply : DC 3.7V by battery(1600mAh)

Charging voltage: DC 5.0V, 1.0A

GSM/EDGE/GPRS Operation : GSM850/PCS1900/GPRS850/GPRS1900/EDGE850/EDGE1900

Frequency Band

GSM/EDGE/GPRS : Supported GSM/GPRS/EDGE

GSM Release Version : R99

GSM/EDGE/GPRS Power Class : GSM850:Power Class 4/ PCS1900:Power Class 1

GPRS/EDGE Multislot Class : GPRS/EDGE: Multi-slot Class 12

GPRS operation mode : Class B

Modulation Type : GMSK for GSM/GPRS, 8-PSK for EDGE

GPS function : Supported and only RX

Antenna Type : PIFA Antenna

Antenna Gain : 1.12dBi(max.) For GSM 850; 1.12dBi(max.) For PCS 1900

Extreme temp. Tolerance : -30°C to +50°C

Extreme vol. Limits : 3.40VDC to 4.20VDC (nominal: 3.70VDC)

2.3 Equipment under Test

Power supply system utilised

Power supply voltage	 0	120V / 60 Hz	0	115V / 60Hz
	0	12 V DC	0	24 V DC
	•	Other (specified in blank bel	ow)	

DC 3.70V

Test frequency list

Test Mode	TX/RX	RF Channel			
Test Mode	I A/RA	Low(L)	Middle (M)	High (H)	
	TX	Channel 128	Channel 190	Channel 251	
GSM850	IA	824.2 MHz	836.6 MHz	848.8 MHz	
GSIVIOSU	RX	Channel 128	Channel 190	Channel 251	
	r.v.	869.2 MHz	881.6 MHz	893.8 MHz	
Test Mode	TX/RX	RF Channel			
1 est Mode		Low(L)	Middle (M)	High (H)	
	TX	Channel 512	Channel 661	Channel 810	
GSM1900	1.	1850.2 MHz	1880.0 MHz	1909.8 MHz	
G3W11900	RX	Channel 512	Channel 661	Channel 810	
	rv.	1930.2 MHz	1960.0 MHz	1989.8 MHz	

2.4 Short description of the Equipment under Test (EUT)

2.4.1 General Description

MT200 is subscriber equipment in the GSM system. The GSM/GPRS/EDGE frequency band includes GSM850 and GSM900 and DCS1800 and PCS1900, but only GSM850 and PCS1900 bands test data included in this report. The tracker implements such functions as RF signal receiving/transmitting, GSM/GPRS/EDGE protocol processing, GPS. Externally it provides micro SD card interface, earphone port (to provide voice service) and SIM card interface. It also provides Bluetooth module to synchronize data between a PC and the phone, or to use the built-in modem of the phone to access the Internet with a PC, or to exchange data with other Bluetooth devices.

MT200 support PTT key, while not install related transmit modular, PTT key cannot work for the sample.

NOTE: Unless otherwise noted in the report, the functional boards installed in the units shall be selected from the below list, but not means all the functional boards listed below shall be installed in one unit.

2.5 Internal Identification of AE used during the test

AE ID*	Description
AE1	Charger

AE1

Model: GDP06AV-0501000-UL

INPUT: AC100-240V 50/60Hz 0.25A

OUTPUT: DC 5.0V 1.0A

*AE ID: is used to identify the test sample in the lab internally.

2.6 Normal Accessory setting

Fully charged battery was used during the test.

2.7 EUT configuration

The following peripheral devices and interface cables were connected during the measurement:

- supplied by the manufacturer
- O supplied by the lab

0	Power Cable	Length (m):	1
		Shield :	1

		Detachable :	1
0	Multimeter	Manufacturer:	1
		Model No. :	1

2.8 Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for **FCC ID: 2AJMFMT200** filling to comply with FCC Part 22 and Part 24 Rules

2.9 Modifications

No modifications were implemented to meet testing criteria.

2.10 General Test Conditions/Configurations

2.10.1 Test Modes

NOTE: The test mode(s) are selected according to relevant radio technology specifications.

Test Mode	Test Modes Description	
GSM/TM1	GSM system, GSM,GMSK modulation	
GSM/TM2	GSM system, GPRS, GMSK modulation	
GSM/TM3	GSM system, EDGE, 8PSK modulation	

Note:

- 1. This EUT owns 1 SIM cards
- We will only measured other items at SIM1;
- As GSM and GPRS with the same emission designator, test result recorded in this report at the worst case GSM/TM1 only after exploratory scan.

2.10.2 Test Environment

Environment Parameter	Selected Values During Tests		
Relative Humidity	Ambient		
Temperature	TN	Ambient	
	VL	3.40V	
Voltage	VN	3.70V	
	VH	4.20V	

NOTE: VL=lower extreme test voltage VN=nominal voltage VH=upper extreme test voltage TN=normal temperature

3 TEST ENVIRONMENT

3.1 Address of the test laboratory

Shenzhen LCS Compliance Testing Laboratory Ltd

1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue, Bao'an District, Shenzhen, Guangdong, China

The sites are constructed in conformance with the requirements of ANSI C63.4 (2014) and CISPR Publication 22.

3.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS Registration Number. is L4595.
FCC Registration Number. is 899208.
Industry Canada Registration Number. is 9642A-1.
VCCI Registration Number. is C-4260 and R-3804.
ESMD Registration Number. is ARCB0108.
UL Registration Number. is 100571-492.
TUV SUD Registration Number. is SCN1081.
TUV RH Registration Number. is UA 50296516-001

3.3 Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15-35 ° C
Humidity:	30-60 %
Atmospheric pressure:	950-1050mbar

3.4 Test Description

3.4.1 Cellular Band (824-849MHz paired with 869-894MHz)

	•	•	
Test Item	FCC Rule No.	Requirements	Verdict
Effective(Isotropic)	§2.1046,	FCC: ERP ≤ 7W.	Pass
Radiated Output Power	§22.913	FGG. ERF > 7W.	F 455
Modulation Characteristics	§2.1047	Digital modulation	N/A
Bandwidth	§2.1049	OBW: No limit. EBW: No limit.	Pass
Band Edges Compliance	§2.1051, §22.917	≤-13dBm/1%*EBW, in 1MHz bands immediately outside and adjacent to The frequency block.	Pass
Spurious Emission at Antenna Terminals	§2.1051, §22.917	FCC: ≤ -13dBm/100kHz, from 9kHz to 10th harmonics but outside authorized operating frequency ranges.	Pass
Field Strength of Spurious Radiation	§2.1053, §22.917	FCC: ≤ -13dBm/100kHz.	Pass
Frequency Stability	§2.1055, §22.355	≤ ±2.5ppm.	Pass
Conducted Emissions	§15.207(a)	1	Pass
NOTE 1: For the verdict, t	he "N/A" denotes	s "not applicable", the "N/T" de notes "not tested".	

3.4.2 PCS Band (1850-1915MHz paired with 1930-1995MHz)

Test Item	FCC Rule No.	Requirements	Verdict
Effective(Isotropic) Radiated Output Power	§2.1046, §24.232	EIRP ≤ 2W	Pass
Peak-Average Ratio	§2.1046, §24.232	FCC:Limit≤13dB	Pass
Modulation Characteristics	§2.1047	Digital modulation	N/A
Bandwidth	§2.1049	OBW: No limit. EBW: No limit.	Pass
Band Edges Compliance	§2.1051, §24.238	≤ -13dBm/1%*EBW, In 1MHz bands immediately outside and adjacent to The frequency block.	Pass
Spurious Emission at Antenna Terminals	§2.1051, §24.238	≤-13dBm/1MHz, from 9kHz to10th harmonics but outside authorized Operating frequency ranges.	Pass
Field Strength of Spurious Radiation	§2.1053, §24.238	≤ -13dBm/1MHz.	Pass
Frequency Stability	§2.1055, §24.235	FCC: within authorized frequency block.	Pass
NOTE 1: For the verdict, t	he "N/A" denotes	s "not applicable", the "N/T" de notes "not tested".	ļ

Remark: 1. The measurement uncertainty is not included in the test result.

Equipments Used during the Test 3.5

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Cal Date	Due Date			
EMC Receiver	R&S	ESCS 30	100174	9kHz – 2.75GHz	June 18,2016	June 17,2017			
Signal analyzer	Agilent	E4448A(External mixers to 40GHz)	US44300469	9kHz~40GHz	July 16,2016	July 15,2017			
LISN	MESS Tec	NNB-2/16Z	99079	9KHz-30MHz	June 18,2016	June 17,2017			
LISN (Support Unit)	EMCO	3819/2NM	9703-1839	9KHz-30MHz	June 18,2016	June 17,2017			
RF Cable-CON	UTIFLEX	3102-26886-4	CB049	9KHz-30MHz	June 18,2016	June 17,2017			
ISN	SCHAFFNER	ISN ST08	21653	9KHz-30MHz	June 18,2016	June 17,2017			
3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH03-HY	30M-1GHz 3m	June 18,2016	June 17,2017			
Amplifier	SCHAFFNER	COA9231A	18667	9kHz-2GHzz	June 18,2016	June 17,2017			
Amplifier	Agilent	8449B	3008A02120	1GHz-26.5GHz	July 16,2016	July 15,2017			
Amplifier	MITEQ	AMF-6F-260400	9121372	26.5GHz- 40GHz	July 16,2016	July 15,2017			
Spectrum Analyzer	Agilent	E4407B	MY41440292	9k-26.5GHz	July 16,2016	July 15,2017			
MAX Signal Analyzer	Agilent	N9020A	MY50510140	20Hz~26.5GHz	Oct. 27, 2016	Oct. 26, 2017			
Loop Antenna	R&S	HFH2-Z2	860004/001	9k-30MHz	June 18,2016	June 17,2017			
By-log Antenna	SCHWARZBECK	VULB9163	9163-470	30MHz-1GHz	June 10,2016	June 09,2017			
Horn Antenna	EMCO	3115	6741	1GHz-18GHz	June 10,2016	June 09,2017			
Horn Antenna	SCHWARZBECK	BBHA9170	BBHA9170154	15GHz-40GHz	June 10,2016	June 09,2017			
RF Cable-R03m	Jye Bao	RG142	CB021	30MHz-1GHz	June 18,2016	June 17,2017			
RF Cable-HIGH	SUHNER	SUCOFLEX 106	03CH03-HY	1GHz-40GHz	June 18,2016	June 17,2017			
Spectrum Meter	R&S	FSP 30	100023	9kHz-30GHz	July 16,2016	July 15,2017			
Power Meter	R&S	NRVS	100444	DC-40GHz	June 18,2016	June 17,2017			
Power Sensor	R&S	NRV-Z51	100458	DC-30GHz	June 18,2016	June 17,2017			
Power Sensor	R&S	NRV-Z32	10057	30MHz-6GHz	June 18,2016	June 17,2017			
RF CABLE-1m	JYE Bao	RG142	CB034-1m	20MHz-7GHz	June 18,2016	June 17,2017			
RF CABLE-2m	JYE Bao	RG142	CB035-2m	20MHz-1GHz	June 18,2016	June 17,2017			
Vector signal Generator	R&S	SMU200A	102098	100kHz~6GHz	June 18,2016	June 17,2017			
Signal Generator	R&S	SMR40	10016	10MHz~40GHz	July 16,2016	July 15,2017			
Universal Radio Communication Tester	R&S	CMU200	112012	N/A	July 18,2016	July 17,2017			
DC power Source	GW	GPC-6030D	C671845	1	June 18,2016	June 17,2017			
Temperature & Humidity Chamber	Wuhuan	HTP205	1	1	June 18,2016	June 17,2017			
EMC Test Software	Audix	E3	1	1	1	1			
Note: All equipment through GRGT EST calibration									

3.6 Measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to ETSI TR 100 028 " Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics" and is documented in the Shenzhen LCS Compliance Testing Laboratory Ltd. quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen LCS Compliance Testing Laboratory Ltd. is reported:

Test	Range	Measurement Uncertainty	Notes
Radiated Emission	30~1000MHz	3.10 dB	(1)
Radiated Emission	1~18GHz	3.70 dB	(1)
Radiated Emission	18-40GHz	3.90 dB	(1)
Conducted Disturbance	0.15~30MHz	1.63 dB	(1)
Conducted Power	9KHz~18GHz	0.61 dB	(1)
Spurious RF Conducted Emission	9KHz~40GHz	1.22 dB	(1)
Band Edge Compliance of RF Emission	9KHz~40GHz	1.22 dB	(1)
Occuiped Bandwidth	9KHz~40GHz	-	(1)

⁽¹⁾ This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=1.96.

4 TEST CONDITIONS AND RESULTS


4.1 Output Power

TEST APPLICABLE

During the process of testing, the EUT was controlled via R&S Digital Radio Communication tester (CMU200) to ensure max power transmission and proper modulation. This result contains output power and EIRP measurements for the EUT. In all cases, output power is within the specified limits.

4.1.1 Conducted Output Power

TEST CONFIGURATION



TEST PROCEDURE

Conducted Power Measurement:

- a) Place the EUT on a bench and set it in transmitting mode.
- b) Connect a low loss RF cable from the antenna port to a CMU200 by an Att.
- c) EUT Communicate with CMU200 then selects a channel for testing.
- d) Add a correction factor to the display CMU200, and then test.

TEST RESULTS

See next page

<SIM1>

		— — — — — — — — — — — — — — — — — — —				
		Burst A	verage Conducted pow	er (dBm)		
GSN	Л 850	Channel/Frequency(MHz)				
		128/824.2	190/836.6	251/848.8		
G:	SM	32.79	32.82	32.82		
	1TX slot	32.65	32.64	32.56		
GPRS	2TX slot	30.56	30.59	30.25		
(GMSK)	3TX slot	29.71	29.72	29.21		
	4TX slot	27.59	27.60	27.45		
	1TX slot	26.71	26.68	26.58		
EGPRS (8PSK)	2TX slot	23.71	23.73	23.62		
	3TX slot	22.64	22.62	22.32		
	4TX slot	20.61	20.59	20.48		

		Burst Average Conducted power (dBm) Channel/Frequency(MHz)					
GSN	/I 1900						
		512/1850.2	661/1880	810/1909.8			
G	SM	30.34	30.36	30.33			
	1TX slot	29.29	29.24	29.26			
GPRS	2TX slot	27.29	27.27	27.12			
(GMSK)	3TX slot	25.74	25.74	25.54			
	4TX slot	24.07	24.04	24.14			
	1TX slot	25.61	25.57	25.44			
EGPRS	2TX slot	23.50	23.48	23.33			
(8PSK)	3TX slot	21.54	21.56	21.62			
	4TX slot	19.09	19.08	19.51			


4.1.2 Radiated Output Power

TEST DESCRIPTION

This is the test for the maximum radiated power from the EUT.

Rule Part 24.232(c) specifies, "Mobile/portable stations are limited to 2 watts e.i.r.p. Peak power" and 24.232(e) specifies that "Peak transmit power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage." Rule Part 22.913(a) specifies "The ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 Watts."

TEST CONFIGURATION



TEST PROCEDURE

- 1. EUT was placed on a 1.50 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.50 m. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all transmit frequencies in three channels (High, Middle, Low) were measured with peak detector.
- 2. A log-periodic antenna or double-ridged waveguide horn antenna shall be substituted in place of the EUT. The log-periodic antenna will be driven by a signal generator and the level will be adjusted till the same power value on the spectrum analyzer or receiver. The level of the spurious emissions can be calculated through the level of the signal generator, cable loss, the gain of the substitution antenna and the reading of the spectrum analyzer or receiver.
- 3. The EUT is then put into continuously transmitting mode at its maximum power level during the test. Set Test Receiver or Spectrum RBW=1MHz, VBW=3MHz, And the maximum value of the receiver should be recorded as (P_r).
- 4. The EUT shall be replaced by a substitution antenna. In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power (P_{Mea}) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded (P_r). The power of signal source (P_{Mea}) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

- A amplifier should be connected to the Signal Source output port. And the cable should be connect
 between the Amplifier and the Substitution Antenna. The cable loss (P_{cl}) ,the Substitution Antenna Gain
 (G_a) and the Amplifier Gain (P_{Ag}) should be recorded after test.
 - The measurement results are obtained as described below:
 - Power(EIRP)= P_{Mea} P_{Ag} P_{cl} + G_a
- 6. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power.
- 7. ERP can be calculated from EIRP by subtracting the gain of the dipole, ERP = EIRP-2.15dBi.

TEST LIMIT

According to 22.913(a) and 24.232(c), the ERP should be not exceed following table limits:

GSM850(GPRS850,EDGE850)								
Function	Power Step	Burst Peak ERP (dBm)						
GSM	5	≤38.45dBm (7W)						
GPRS	3	≤38.45dBm (7W)						
EDGE	8	≤38.45dBm (7W)						

PCS1900(GPRS1900,EDGE1900)								
Function Power Step Burst Peak EIRP (dBm)								
GSM	0	≤33dBm (2W)						
GPRS	3	≤33dBm (2W)						
EDGE	2	≤33dBm (2W)						

TEST RESULTS

Remark:

- 1. We were tested all Configuration refer 3GPP TS151 010.
- 2. $EIRP=P_{Mea}(dBm)-P_{cl}(dB)+P_{Aq}(dB)+G_a(dBi)$
- 3. ERP = EIRP 2.15dBi as EIRP by subtracting the gain of the dipole.
- 4. Margin = Emission Level Limit
- 5. We test the H direction and V direction recorded worst case.

GSM/TM1/GSM850

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	Correction (dB)	P _{Ag} (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
824.20	-6.04	3.45	8.45	2.15	33.79	30.60	38.45	-7.85	V
836.60	-6.00	3.49	8.45	2.15	33.85	30.66	38.45	-7.79	V
848.80	-5.97	3.55	8.36	2.15	33.88	30.57	38.45	-7.88	V

GSM/TM3/EDGE850

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	Correction (dB)	P _{Aq} (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
824.20	-13.01	3.45	8.45	2.15	33.79	23.63	38.45	-14.82	V
836.60	-13.05	3.49	8.45	2.15	33.85	23.61	38.45	-14.84	V
848.80	-12.91	3.55	8.36	2.15	33.88	23.63	38.45	-14.82	V

GSM/TM1/GSM1900

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Ag} (dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1850.20	-9.00	4.03	8.38	35.51	30.86	33.00	-2.14	V
1880.00	-9.08	4.08	8.33	35.56	30.73	33.00	-2.27	V
1909.80	-9.02	4.14	8.26	35.63	30.73	33.00	-2.27	V

GSM/TM3/EDGE1900


Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Ag} (dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1850.20	-13.93	4.03	8.38	35.51	25.93	33.00	-7.07	V
1880.00	-14.05	4.08	8.33	35.56	25.76	33.00	-7.24	V
1909.80	-13.99	4.14	8.26	35.63	25.76	33.00	-7.24	V

4.2 Radiated Spurious Emssion

TEST APPLICABLE

According to the TIA/EIA 603D:2010 and FCC Part 2.1033 test method, The Receiver or Spectrum was scanned from lowest frequency frequency generated within the equipment to the 10th harmonic of the highest frequency generated within the equipment, which is the transmitted carrier that can be as high as 1910 MHz. The resolution bandwidth is set as outlined in Part 24.238 and Part 22.917. The spectrum is scanned with the mobile station transmitting at carrier frequencies that pertain to low, mid and high channels of PCS1900 and GSM850.

TEST CONFIGURATION



TEST PROCEDURE

- 1. EUT was placed on a 1.50 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.50 m. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all transmit frequencies in three channels (High, Middle, Low) were measured with peak detector.
- 2. A log-periodic antenna or double-ridged waveguide horn antenna shall be substituted in place of the EUT. The log-periodic antenna will be driven by a signal generator and the level will be adjusted till the same power value on the spectrum analyzer or receiver. The level of the spurious emissions can be calculated through the level of the signal generator, cable loss, the gain of the substitution antenna and the reading of the spectrum analyzer or receiver.
- 3. The EUT is then put into continuously transmitting mode at its maximum power level during the test. Set Test Receiver or Spectrum RBW=1MHz, VBW=3MHz, And the maximum value of the receiver should be recorded as (P_r).
- 4. The EUT shall be replaced by a substitution antenna. In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power (P_{Mea}) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver

- <u>SHENZHEN LCS COMPLIANCE TESTING LABORATORY LTD. FCC ID: 2AKMDMDKYGPS201612 Report No.: LCS1612131594E</u> reach the previously recorded (P_r). The power of signal source (P_{Mea}) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.
- 5. A amplifier should be connected to the Signal Source output port. And the cable should be connect between the Amplifier and the Substitution Antenna. The cable loss (P_{cl}), the Substitution Antenna Gain (G_a) and the Amplifier Gain (P_{Ag}) should be recorded after test. The measurement results are obtained as described below: Power(EIRP)= P_{Mea} P_{Ag} P_{cl} + G_a
- 6. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power.
- 7. ERP can be calculated from EIRP by subtracting the gain of the dipole, ERP = EIRP -2.15dBi.

8. In order to make sure test results more clearly, we set frequency range and sweep time for difference frequency range as follows table:

Working Frequency	Subrange (GHz)	RBW	VBW	Sweep time (s)
	0.00009~0.15	1KHz	3KHz	30
	0.00015~0.03	10KHz	30KHz	10
	0.03~1	100KHz	300KHz	10
TM1/GSM 850	1~2	1 MHz	3 MHz	2
	2~5	1 MHz	3 MHz	3
	5~8	1 MHz	3 MHz	3
	8~10	1 MHz	3 MHz	3
	0.00009~0.15	1KHz	3KHz	30
	0.00015~0.03	10KHz	30KHz	10
	0.03~1	100KHz	300KHz	10
	1~2	1 MHz	3 MHz	2
TM1/GSM 1900	2~5	1 MHz	3 MHz	3
11011/63101 1900	5~8	1 MHz	3 MHz	3
	8~11	1 MHz	3 MHz	3
	11~14	1 MHz	3 MHz	3
	14~18	1 MHz	3 MHz	3
	18~20	1 MHz	3 MHz	2

TEST LIMITS

According to 24.238 and 22.917 specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB.

The specification that emissions shall be attenuated below the transmitter power (P) by at least 43 + 10 log (P) dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

Frequency	Channel	Frequency Range	Verdict
-	Low	9KHz-10GHz	PASS
TM1/GSM 850	Middle	9KHz -10GHz	PASS
	High	9KHz -10GHz	PASS
	Low	9KHz -20GHz	PASS
TM1/GSM 1900	Middle	9KHz -20GHz	PASS
	High	9KHz -20GHz	PASS

TEST RESULTS

Remark:

- 1. We were tested all refer 3GPP TS151 010.
- 2. $EIRP=P_{Mea}(dBm)-P_{cl}(dB)+G_a(dBi)$
- 3. We were not recorded other points as values lower than limits.
- 4. Margin = EIRP Limit

GSM/TM1/GSM850_ Middle Channel

Eroguepey	D	D		Ga	Peak	Limit	Margin	
Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	Antenna	EIRP	(dBm)	(dB)	Polarization
((()		Gain(dB)	(dBm)	(3-11)	()	
1673.2	-41.69	3.9	3.00	8.58	-37.01	-13.00	-24.01	Н
2509.8	-44.49	4.32	3.00	6.8	-42.01	-13.00	-29.01	Н
1673.2	-38.51	3.9	3.00	8.58	-33.83	-13.00	-20.83	V
2509.8	-43.07	4.32	3.00	6.8	-40.59	-13.00	-27.59	V

GPRS/TM2/GPRS850_ Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1697.6	-47.25	3.91	3.00	9.06	-42.10	-13.00	-29.10	Н
2546.4	-47.18	4.32	3.00	6.65	-44.85	-13.00	-31.85	Н
1697.6	-42.44	3.91	3.00	9.06	-37.29	-13.00	-24.29	V
2546.4	-43.32	4.32	3.00	6.65	-40.99	-13.00	-27.99	V

EDGE/TM3/EDGE850_ Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1648.4	-48.78	3.86	3.00	8.56	-44.08	-13.00	-31.08	Н
2472.6	-48.57	4.29	3.00	6.98	-45.88	-13.00	-32.88	Н
1648.4	-42.47	3.86	3.00	8.56	-37.77	-13.00	-24.77	V
2472.6	-43.30	4.29	3.00	6.98	-40.61	-13.00	-27.61	V

GSM/TM1/GSM1900_ Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3760.0	-48.63	5.32	3.00	10.03	-43.92	-13.00	-30.92	Н
5640.0	-51.16	6.19	3.00	11.41	-45.94	-13.00	-32.94	Н
3760.0	-50.52	5.32	3.00	10.03	-45.81	-13.00	-32.81	V
5640.0	-54.62	6.19	3.00	11.41	-49.40	-13.00	-36.40	V

GPRS/TM2/GPRS1900_ Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3819.6	-49.06	5.36	3.00	9.62	-44.80	-13.00	-31.80	Н
5729.4	-52.72	6.24	3.00	11.46	-47.50	-13.00	-34.50	Н
3819.6	-50.17	5.36	3.00	9.62	-45.91	-13.00	-32.91	٧
5729.4	-56.66	6.24	3.00	11.46	-51.44	-13.00	-38.44	V

EDGE/TM3/EDGE1900_ Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3700.4	-53.40	5.26	3.00	9.88	-48.78	-13.00	-35.78	Н
5550.6	-57.60	6.11	3.00	11.36	-52.35	-13.00	-39.35	Н
3700.4	-57.84	5.26	3.00	9.88	-53.22	-13.00	-40.22	V
5550.6	-61.71	6.11	3.00	11.36	-56.46	-13.00	-43.46	V

Notes:


- 1). Measuring frequencies from 9k~10th harmonic, No emission found between lowest internal used/generated frequency to 30 MHz.
- 2). Radiated emissions measured in frequency range from 9k~10th harmonic were made with an instrument using Peak detector mode.
- 3). 6~20GHz at least have 20dB margin. No recording in the test report.

4.3 Occupied Bandwidth and Emission Bandwidth

TEST APPLICABLE

Similar to conducted emissions; occupied bandwidth measurements are only provided for selected frequencies in order to reduce the amount of submitted data. Data were taken at the extreme and mid frequencies of PCS1900 band and GSM850 band. The table below lists the measured 99% Bandwidth and -26dBc Bandwidth.

TEST CONFIGURATION



TEST PROCEDURE

- 1. The EUT was set up for the max output power with pseudo random data modulation;
- 2. The Occupied bandwidth and Emission Bandwidth were measured with Spectrum AnalyzerN9020A;
- 3. Set RBW=10KHz,VBW=30KHz,Span=1MHz,SWT=Auto;
- 4. Set SPA Max hold and View, Set 99% Occupied Bandwidth/ Set -26dBc Occupied Bandwidth
- 5. These measurements were done at 3 frequencies, 1850.20 MHz, 1880.00 MHz and 1909.80 MHz for PCS1900 band; 824.20MHz, 836.60 MHz and 848.80 MHz for GSM850 band. (Low, middle and high of operational frequency range).


TEST RESULTS

Test Mode	Channel	Frequency (MHz)	Occupied Bandwidth (99% BW) (kHz)	Emission Bandwidth (-26 dBc BW) (kHz)	Verdict
GSM/TM1	128	824.2	244.90	317.0	PASS
/GSM850	190	836.6	245.00	310.4	PASS
/G3IVI030	251	848.8	248.09	321.7	PASS
GSM/TM3	128	824.2	246.39	319.4	PASS
/EGPRS850	190	836.6	245.27	323.9	PASS
/EGPK3030	251	848.8	250.08	317.7	PASS
GSM/TM1	512	1850.2	242.29	323.0	PASS
/GSM1900	661	1880.0	244.22	322.2	PASS
/G3W11900	810	1908.8	245.80	320.0	PASS
CCM/TM2	512	1850.2	242.64	321.0	PASS
GSM/TM3 /EGPRS1900	661	1880.0	245.14	318.1	PASS
/LGF N3 1900	810	1908.8	244.80	317.5	PASS

Remark:

- 1. Test results including cable loss;
- 2. please refer to following plots;






4.4 Band Edge Complicance

TEST APPLICABLE

During the process of testing, the EUT was controlled via Digital Radio Communication tester (CMU200) to ensure max power transmission and proper modulation.

TEST CONFIGURATION



TEST PROCEDURE


- 1. The EUT was set up for the max output power with pseudo random data modulation;
- 2. The power was measured with Spectrum Analyzer N9020A;
- 3. Set RBW=3KHz,VBW=10KHz,Span=1MHz,SWT=Auto, Dector:RMS;
- 1. These measurements were done at 3 frequencies, 1850.20 MHz, 1880.00 MHz and 1909.80 MHz for PCS1900 band; 824.20 MHz, 836.60 MHz and 848.80 MHz for GSM850 band. (bottom, middle and top of operational frequency range).


TEST RESULTS

Test Mode	Channel	Frequency (MHz)	Band Edg Compliance (dBm)	Limits (dBm)	Verdict
GSM/TM1/GSM850	128	824.2	<-13dBm	-13dBm	PASS
	251	848.8	<-13dBm	-13dBm	PASS
GSM/TM3/EGPRS850	128	824.2	<-13dBm	-13dBm	PASS
GSW/TWS/EGPRS850	251	848.8	<-13dBm	-13dBm	PASS
GSM/TM1/GSM1900	512	1850.2	<-13dBm	-13dBm	PASS
GSIVI/TIVIT/GSIVIT900	810	1909.8	<-13dBm	-13dBm	PASS
GSM/TM3/EGPRS1900	512	1850.2	<-13dBm	-13dBm	PASS
G3W/ 1W3/EGPR31900	810	1909.8	<-13dBm	-13dBm	FASS

Remark

- 1. Test results including all insert loss: cable loss(1dB)+Coupler attenuation(6dB)=7dB;
- please refer to following plots;






4.5 Spurious Emssion on Antenna Port

TEST APPLICABLE

The following steps outline the procedure used to measure the conducted emissions from the EUT.

- 1. Determine frequency range for measurements: From CFR 2.1057 the spectrum should be investigated from the lowest radio frequency generated in the equipment up to at least the 10th harmonic of the carrier frequency. For the equipment of PCS1900 band, this equates to a frequency range of 9 KHz to 19.1 GHz, data taken from 30 MHz to 20 GHz. For GSM850, this equates to a frequency range of 9 KHz to 9 GHz, data taken from 30 MHz to 9 GHz.
- 2. The sweep time is set automatically by instrument itself. That should be the optimal sweep time for the span and the RBW. If the sweep time is too short, that is sweep is too fast, the sweep result is not accurate; if the sweep time is too long, that is sweep is too low, some frequency components may be lost. The instrument will give an optimal sweep time according the selected span and RBW.
- The procedure to get the conducted spurious emission is as follows:
 The trace mode is set to MaxHold to get the highest signal at each frequency;
 Wait 25 seconds;
 Get the result.
- 4. Determine EUT transmit frequencies: below outlines the band edge frequencies pertinent to conducted emissions testing.

TEST CONFIGURATION



TEST PROCEDURE

- 1. The EUT was set up for the max output power with pseudo random data modulation;
- 2. The power was measured with Spectrum Analyzer N9020A;
- 3. These measurements were done at 3 frequencies, 1850.20 MHz, 1880.00 MHz and 1909.80 MHz for PCS1900 band; 824.20 MHz, 836.60 MHz and 848.80 MHz for GSM850 band. (Low, middle and high of operational frequency range).

TEST LIMIT

Part 24.238 and Part 22.917 specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB.

The specification that emissions shall be attenuated below the transmitter power (P) by at least 43 + 10 log (P) dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.


TEST RESULTS


Test Mode	Channel	Frequency (MHz)	Reading Frequency (MHz)	Spurious RF Conducted Emission (dBm)	Limits (dBm)	Verdict
	128	824.2	405.851 752.868 1648.6 5801.8	-32.592 -33.346 -28.730 -30.670	13dBm	
GSM/TM1/GSM850	190	836.6	203.436 762.544 1673.4 5311.4	-32.053 -32.751 -29.307 -30.932	- 13dBm	PASS
	251	848.8	201.375 544.488 1697.8 5614.6	-32.712 -32.765 -29.316 -30.774	13dBm	
GSM/TM2/GPRS850	128	824.2	402.577 550.284 1648.6 3150.0	-32.915 -33.755 -29.336 -30.306	13dBm	
	190	836.6	204.406 990.979 1673.8 5039.4	-32.295 -32.935 -28.946 -31.205	-13dBm	PASS
	251	848.8	206.613 694.111 1697.8 5379.8	-32.188 -32.960 -29.158 -30.552	13dBm	
	128	824.2	704.271 872.421 1648.8	-36.620 -35.910 -29.511	-13dBm	
GSM/TM3/EDGE850	190	836.6	482.723 590.175 5974.2 397.000	-36.760 -36.492 -30.021 -34.394	-13dBm	PASS
	251	848.8	873.051 5725.6 523.633	-34.394 -34.248 -30.019 -33.338	-13dBm	
	512	1850.2	668.600 14291.450 17932.325	-33.220 -30.701 -27.683	- 13dBm	
GSM/TM1/GSM1900	661	1880.0	529.744 912.312 5684.450 17947.050	-33.237 -33.138 -32.354 -28.853	- 13dBm	PASS
	810	1908.8	478.043 938.138 15034.350 17986.000	-33.004 -32.170 -30.060 -29.098	13dBm	


GSM/TM2/GPRS1900	512	1850.2	219.368	-33.060	13dBm	PASS
			968.621	-32.367		
			6088.675	-32.722		
			17955.575	-29.243		
	661	1880.0	862.648	-31.941	-13dBm	
			170.262	-33.137		
			9458.325	-32.415		
			17922.350	-29.338		
	810	1908.8	871.693	-33.077	-13dBm	
			933.216	-32.712		
			15178.750	-29.988		
			17974.125	-28.700		
GSM/TM3/EDGE1900	512	1850.2	292.118	-36.675	-13dBm	PASS
			903.703	-36.119		
	661	1880.0	210.396	-36.827	-13dBm	
			587.896	-32.571		
	810	1908.8	290.009	-38.184	-13dBm	
			829.814	-33.140		


Remark:


- 1. Test results including cable loss;
- 2. Not recorded measured values from 9 KHz to 30 MHz as values lower than limit 20dBc;
- 3. please refer to following plots;
































4.6 Frequency Stability Test

TEST APPLICABLE


- 1. According to FCC Part 2 Section 2.1055 (a)(1), the frequency stability shall be measured with variation of ambient temperature from -30 ℃ to +50 ℃ centigrade.
- 2. According to FCC Part 2 Section 2.1055 (E) (2), for battery powered equipment, the frequency stability shall be measured with reducing primary supply voltage to the battery operating end point, which is specified by the manufacture.
- 3. Vary primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried voltage equipment and the end voltage point was 3.40V.

TEST PROCEDURE

In order to measure the carrier frequency under the condition of AFC lock, it is necessary to make measurements with the EUT in a "call mode". This is accomplished with the use of R&S CMU200 DIGITAL RADIO COMMUNICATION TESTER.

- 1. Measure the carrier frequency at room temperature;
- 2. Subject the EUT to overnight soak at -30°C;
- 3. With the EUT, powered via nominal voltage, connected to the CMU200 and in a simulated call on middle channel of PCS 1900 and GSM850, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming;
- 4. Repeat the above measurements at 10°C increments from -30°C to +50°C. Allow at least 0.5 hours at each temperature, unpowered, before making measurements;
- 5. Remeasure carrier frequency at room temperature with nominal voltage. Vary supply voltage from minimum voltage to maximum voltage, in 0.1Volt increments remeasuring carrier frequency at each voltage. Pause at nominal voltage for 0.5 hours unpowered, to allow any self-heating to stabilize, before continuing;
- Subject the EUT to overnight soak at +50°C;
- 7. With the EUT, powered via nominal voltage, connected to the CMU200 and in a simulated call on the centre channel, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming;
- 8. Repeat the above measurements at 10°C increments from +50°C to -30°C. Allow at least 0.5 hours at each temperature, unpowered, before making measurements;
- 9. At all temperature levels hold the temperature to +/- 0.5°C during the measurement procedure;

TEST CONFIGURATION



TEST LIMITS

For Hand carried battery powered equipment

According to the JTC standard the frequency stability of the carrier shall be accurate to within 0.1 ppm of the received frequency from the base station. This accuracy is sufficient to meet Sec. 24.235, Frequency Stability. The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. As this transceiver is considered "Hand carried, battery powered equipment" Section 2.1055(d)(2) applies. This requires that the lower voltage for frequency stability testing be specified by the manufacturer. This transceiver is specified to operate with an input voltage of between 3.40VDC and 4.20VDC, with a nominal voltage of 3.70DC. Operation above or below these voltage limits is prohibited by transceiver software in order to prevent improper operation as well as to protect components from overstress. These voltages represent a tolerance of -10 % and +12.5 %. For the purposes of measuring frequency stability these voltage limits are to be used.

For equipment powered by primary supply voltage

According to the JTC standard the frequency stability of the carrier shall be accurate to within 0.1 ppm of the received frequency from the base station. This accuracy is sufficient to meet Sec. 24.235, Frequency Stability. The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. For this EUT section 2.1055(d)(1) applies. This requires varying primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried battery equipment.

TEST RESULTS

	GSM/TM1/GSM850									
DC Power	Temperature (°C)	Frequency error(Hz)	Frequency error(ppm)	Limit (ppm)	Verdict					
3.40	25	17	0.020	2.50	PASS					
3.70	25	21	0.025	2.50	PASS					
4.20	25	16	0.019	2.50	PASS					
3.70	-30	15	0.018	2.50	PASS					
3.70	-20	8	0.010	2.50	PASS					
3.70	-10	14	0.017	2.50	PASS					
3.70	0	11	0.013	2.50	PASS					
3.70	10	20	0.024	2.50	PASS					
3.70	20	22	0.026	2.50	PASS					
3.70	30	22	0.026	2.50	PASS					
3.70	40	7	0.008	2.50	PASS					
3.70	50	9	0.011	2.50	PASS					

	GSM/TM3/ EGPRS850									
DC Power	Temperature (℃)	Frequency error(Hz)	Frequency error(ppm)	Limit (ppm)	Verdict					
3.40	25	14	0.017	2.50	PASS					
3.70	25	10	0.012	2.50	PASS					
4.20	25	14	0.017	2.50	PASS					
3.70	-30	15	0.018	2.50	PASS					
3.70	-20	13	0.016	2.50	PASS					
3.70	-10	21	0.025	2.50	PASS					
3.70	0	12	0.014	2.50	PASS					
3.70	10	8	0.010	2.50	PASS					
3.70	20	8	0.010	2.50	PASS					
3.70	30	15	0.018	2.50	PASS					
3.70	40	7	0.008	2.50	PASS					
3.70	50	11	0.013	2.50	PASS					

	GSM/TM1/PCS1900									
DC Power	Temperature (°C)	Frequency error(Hz)	Frequency error(ppm)	Limit (ppm)	Verdict					
3.40	25	10	0.005	2.50	PASS					
3.70	25	12	0.006	2.50	PASS					
4.20	25	16	0.009	2.50	PASS					
3.70	-30	13	0.007	2.50	PASS					
3.70	-20	11	0.006	2.50	PASS					
3.70	-10	23	0.012	2.50	PASS					
3.70	0	13	0.007	2.50	PASS					
3.70	10	10	0.005	2.50	PASS					
3.70	20	12	0.006	2.50	PASS					
3.70	30	19	0.010	2.50	PASS					
3.70	40	7	0.004	2.50	PASS					
3.70	50	13	0.007	2.50	PASS					


	GSM/TM3/ EGPRS1900										
DC Power	Temperature (°C)	Frequency error(Hz)	Frequency error(ppm)	Limit (ppm)	Verdict						
3.40	25	13	0.007	2.50	PASS						
3.70	25	14	0.007	2.50	PASS						
4.20	25	16	0.009	2.50	PASS						
3.70	-30	6	0.003	2.50	PASS						
3.70	-20	9	0.005	2.50	PASS						
3.70	-10	16	0.009	2.50	PASS						
3.70	0	11	0.006	2.50	PASS						
3.70	10	18	0.010	2.50	PASS						
3.70	20	11	0.006	2.50	PASS						
3.70	30	18	0.010	2.50	PASS						
3.70	40	10	0.005	2.50	PASS						
3.70	50	14	0.007	2.50	PASS						

4.7 Peak-to-Average Ratio (PAR)

LIMIT

The Peak-to-Average Ratio (PAR) of the transmission may not exceed 13 dB.

TEST CONFIGURATION



TEST PROCEDURE

Use spectrum to measure the total peak power and record as P_{Pk} . Use spectrum to measure the total average power and record as P_{Avg} . Both the peak and average power levels must be expressed in the same logarithmic units (e.g., dBm).


Determine the PAPR from:


 $PAPR (dB) = P_{Pk} (dBm) - P_{Avg} (dBm).$


TEST RESULTS


Test Mode	Channel	Frequency (MHz)	PAPR Value (dB)	Limits (dB)	Verdict	
	128	824.2	10.16	13.0		
GSM/TM1/GSM850	190	836.6	10.54	13.0	PASS	
	251	848.8	10.69	13.0		
	128	824.2	10.98	13.0		
GSM/TM2/GPRS850	190	836.6	10.38	13.0	PASS	
	251	848.8	11.01	13.0		
	128	824.2	10.08	13.0		
GSM/TM3/EDGE850	190	836.6	11.04	13.0	PASS	
	251	848.8	10.44	13.0		


Test Mode	Channel	Frequency (MHz)	PAPR Value (dB)	Limits (dB)	Verdict	
	512	1850.2	9.39	13.0		
GSM/TM1/GSM1900	661	1880.0	9.74	13.0	PASS	
	810	1908.8	9.91	13.0		
	512	1850.2	9.29	13.0		
GSM/TM2/GPRS1900	661	1880.0	9.36	13.0	PASS	
	810	1908.8	8.51	13.0		
	512	1850.2	9.29	13.0		
GSM/TM3/EDGE1900	661	1880.0	9.28	13.0	PASS	
	810	1908.8	9.41	13.0		
































4.8 AC Power line conducted emissions


4.8.1 Standard Applicable

According to §15.207 (a): For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed 250 microvolts (The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz). The limits at specific frequency range is listed as follows:

Frequency Range	Limits (dBμV)					
(MHz)	Quasi-peak	Average				
0.15 to 0.50	66 to 56	56 to 46				
0.50 to 5	56	46				
5 to 30	60	50				

^{*} Decreasing linearly with the logarithm of the frequency

4.8.2 Block Diagram of Test Setup




4.8.3 Test Results

PASS.


The test data please refer to following page.

Test Results for AC 120V/60Hz @ GMSK(worst case)



	Freq	Reading	LISNFac	CabLos	Aux2Fac	Measur	ed Limit	Over	Remark
	MHz	dBuV	dB	dB	dB	dB	dBuV	dBuV	dB
1	0.15	37.41	9.58	0.02	10.00	57.01	65.78	-8.77	QP
2	0.15	20.35	9.58	0.02	10.00	39.95	55.77	-15.82	Average
3	0.47	28.24	9.62	0.04	10.00	47.90	56.58	-8.68	QP
4	0.47	13.82	9.62	0.04	10.00	33.48	46.58	-13.10	Average
5	0.94	27.00	9.63	0.05	10.00	46.68	56.00	-9.32	QP
6	0.94	7.90	9.63	0.05	10.00	27.58	46.00	-18.42	Average
7	3.72	19.98	9.65	0.06	10.00	39.69	56.00	-16.31	QP
8	3.72	2.48	9.65	0.06	10.00	22.19	46.00	-23.81	Average
9	5.56	17.77	9.66	0.06	10.00	37.49	60.00	-22.51	QP
10	5.57	0.46	9.66	0.06	10.00	20.18	50.00	-29.82	Average
11	17.85	21.31	9.74	0.11	10.00	41.16	60.00	-18.84	QP
12	17.85	4.83	9.74	0.11	10.00			-25.32	Average

Remarks: 1. Measured = Reading +Cable Loss +Aux2 Fac.
2. The emission levels that are 20dB below the official limit are not reported.




	Freq	Reading	LISNFac	CabLos	Aux2Fac	Measu	red Limit	Over	Remark
	MHz	dBuV	dB	dB	dB	dB	dBuV	dBuV	dB
1	0.47	33.31	9.62	0.04	10.00	52.97	56.49	-3.52	QP
2	0.47	19.27	9.62	0.04	10.00	38.93	46.49	-7.56	Average
3	0.93	26.64	9.63	0.05	10.00	46.32	56.00	-9.68	QP
4	0.93	8.35	9.63	0.05	10.00	28.03	46.00	-17.97	Average
5	1.59	24.21	9.63	0.05	10.00	43.89	56.00	-12.11	QP
6	1.59	7.68	9.63	0.05	10.00	27.36	46.00	-18.64	Average
7	2.42	24.31	9.64	0.05	10.00	44.00	56.00	-12.00	QP
8	2.42	6.64	9.64	0.05	10.00	26.33	46.00	-19.67	Average
9	4.16	23.04	9.65	0.06	10.00	42.75	56.00	-13.25	QP
10	4.16	5.93	9.65	0.06	10.00	25.64	46.00	-20.36	Average
11	17.38	26.06	9.78	0.11	10.00	45.95	60.00	-14.05	QP
12	17.38	5.66	9.78	0.11	10.00	25.55	50.00	-24.45	Average

Remarks: 1. Measured = Reading +Cable Loss +Aux2 Fac.
2. The emission levels that are 20dB below the official


limit are not reported.

Test Results for AC 240V/60Hz @ GMSK(worst case)



	Freq	Reading	LISNFac	CabLos	Aux2Fac	Measu	red Limit	Over	Remark
	MHz	dBuV	dB	dB	dB	dB	dBuV	dBuV	dB
1	0.47	33.67	9.62	0.04	10.00	53.33	56.45	-3.12	QP
2	0.47	19.39	9.62	0.04	10.00	39.05	46.45	-7.40	Average
3	0.72	29.97	9.63	0.04	10.00	49.64	56.00	-6.36	QP
4	0.72	15.66	9.63	0.04	10.00	35.33	46.00	-10.67	Average
5	1.25	29.94	9.63	0.05	10.00	49.62	56.00	-6.38	QP
6	1.25	15.63	9.63	0.05	10.00	35.31	46.00	-10.69	Average
7	1.76	29.12	9.63	0.05	10.00	48.80	56.00	-7.20	QP
8	1.76	16.43	9.63	0.05	10.00	36.11	46.00	-9.89	Average
9	2.79	29.03	9.64	0.05	10.00	48.72	56.00	-7.28	QP
10	2.80	15.65	9.64	0.05	10.00	35.34	46.00	-10.66	Average
11	3.78	27.57	9.65	0.06	10.00	47.28	56.00	-8.72	QP
12	3.78	14.11	9.65	0.06	10.00	33.82	46.00	-12.18	Average

Remarks: 1. Measured = Reading +Cable Loss +Aux2 Fac.
2. The emission levels that are 20dB below the official limit are not reported.



	Freq	Reading	LISNFac	CabLos	Aux2Fac	: Measur	red Limit	Over	Remark
_	MHz	dBuV	dB	dB	dB	dB	dBuV	dBuV	dB
1	0.47	29.82	9.62	0.04	10.00	49.48	56.45	-6.97	QP
2	0.47	16.55	9.62	0.04	10.00	36.21	46.45	-10.24	Average
3	0.97	25.74	9.63	0.05	10.00	45.42	56.00	-10.58	QP
4	0.97	5.96	9.63	0.05	10.00	25.64	46.00	-20.36	Average
5	1.81	23.40	9.64	0.05	10.00	43.09	56.00	-12.91	QP
6	1.81	9.99	9.64	0.05	10.00	29.68	46.00	-16.32	Average
7	3.64	23.46	9.65	0.06	10.00	43.17	56.00	-12.83	QP
8	3.64	5.46	9.65	0.06	10.00	25.17	46.00	-20.83	Average
9	6.19	20.71	9.67	0.07	10.00	40.45	60.00	-19.55	QP
10	6.19	1.41	9.67	0.07	10.00	21.15	50.00	-28.85	Average
11	17.66	26.52	9.74	0.11	10.00	46.37	60.00	-13.63	QP
12	17.66	5.97	9.74	0.11	10.00	25.82	50.00	-24.18	Average

Remarks: 1. Measured = Reading +Cable Loss +Aux2 Fac.
2. The emission levels that are 20dB below the official

limit are not reported.

Note: Pre-scan all modes and recorded the worst case results in this report.

.....End of Report.....