



**129, Chungjusandan1-ro, Chungju-si,  
Chungcheongbuk-do, Republic of Korea**  
**Tel No : +82-31-218-5582**  
**Fax No : -**

<b>Applicant/Grantee</b>	<b>EVERINT Co., Ltd.</b>		
<b>FCC ID:</b>	<b>2AKMF-RFID-PBA1</b>		
<b>IC:</b>	<b>22266-RFIDPBA1</b>		
<b>Modular Transmitters</b>			
<b>Request for Modular Approval</b> <input type="checkbox"/>		<b>Request for Limited Modular Approval</b> <input checked="" type="checkbox"/>	
Requirements		EUT Conditions	
<b>Single Modular Approval Requirements</b>			
1	The radio elements of the modular transmitter must have their own shielding. The physical crystal and tuning capacitors may be located external to the shielded radio elements.	Refer to the external photo	<b>Y</b>
2	The modular transmitter must have buffered modulation/data inputs (if such inputs are provided) to ensure that the module will comply with modular approval requirements under conditions of excessive data rates or over-modulation.	All input to the modules are buffered through microprocessor inputs.	<b>Y</b>
3	The modular transmitter must have its own power supply regulation.	<u>No, The host product will provide an external power supply regulation to the module.</u>	<b>N</b>
4	The modular transmitter must comply with the antenna and transmission system requirements.	Refer to the internal photo	<b>Y</b>
5	The modular transmitter must be tested in a stand-alone configuration, <i>i.e.</i> , the module must not be inside another device during testing. Unless the transmitter module will be battery powered, it must comply with the AC line conducted requirements found in Section 15.207. AC or DC power lines and data input/output lines connected to the module must not contain ferrites, unless they will be marketed with the module (see Section 15.27(a)). The length of these lines shall be the length typical of actual use or, if that length is unknown, at least 10 centimeters to insure that there is no coupling between the case of the module and supporting equipment. Any accessories, peripherals, or support equipment connected to the module during testing shall be unmodified and commercially available (see Section 15.31(i)).	The EUT was tested in a standalone configuration.	<b>Y</b>
6	The modular transmitter must be equipped with either a permanently affixed label or must be capable of electronically displaying its FCC identification number. <i>(A) If using a permanently affixed label, the modular transmitter must be labeled with its own FCC identification number, and, if the FCC identification number is not visible when the module is installed inside another device, then the outside of the device into which the module is installed must also display a label referring to the enclosed module. This exterior label can use wording such as the following:</i> "Contains Transmitter Module FCC ID: 2AKMF-	Refer to the label and user manual	<b>Y</b>

<p><i>RFID-PBA1" or "Contains FCC ID: 2AKMF-RFID-PBA1." Any similar wording that expresses the same meaning may be used. The Grantee may either provide such a label, an example of which must be included in the application for equipment authorization, or, must provide adequate instructions along with the module which explain this requirement. In the latter case, a copy of these instructions must be included in the application for equipment authorization.</i></p> <p><i>(B) If the modular transmitter uses an electronic display of the FCC identification number, the information must be readily accessible and visible on the modular transmitter or on the device in which it is installed. If the module is installed inside another device, then the outside of the device into which the module is installed must display a label referring to the enclosed module. This exterior label can use wording such as the following:</i></p> <p><i>"Contains FCC certified transmitter module(s)." Any similar wording that expresses the same meaning may be used. The user manual must include instructions on how to access the electronic display. A copy of these instructions must be included in the application for equipment authorization.</i></p>		
7	The modular transmitter must comply with any specific rules or operating requirements that ordinarily apply to a complete transmitter and the manufacturer must provide adequate instructions along with the module to explain any such requirements. A copy of these instructions must be included in the application for equipment authorization.	Refer to the user manual
8	The modular transmitter must comply with any applicable RF exposure requirements in its final configuration.	Refer to the RF exposure statement for more details.
<p>A limited modular approval may be granted for single or split modular transmitters that do not comply with all of the above requirements, e.g., shielding, minimum signaling amplitude, buffered modulation/data inputs, or power supply regulation, if the manufacturer can demonstrate by alternative means in the application for equipment authorization that the modular transmitter meets all the applicable Limited modular approval also may be granted in those instances where compliance with RF exposure rules is demonstrated only for particular product configurations. The applicant for certification must state how control of the end product into which the module will be installed will be maintained such that full compliance of the end product is always ensured.</p>		
<b>Name and Title of the Applicant:</b>	JiSung Shin / Manager	
<b>Date:</b>	Jul. 03, 2025	
<b>Signature:</b>		