



FCC 47 CFR PART 15 SUBPART C

RF Test Report

Applicant : Nuheara Limited

Product Type : IQbuds

Trade Name : NUHEARA

Model Number · NU317

Test Specification FCC 47 CFR PART 15 SUBPART C

ANSI C63.10:2013

Receive Date : Dec. 05, 2016

Test Period : Dec. 05 ~ Dec. 19, 2016

Issue Date : Feb. 15, 2017

Issue by

A Test Lab Techno Corp.

No. 140-1, Changan Street, Bade District, Taoyuan City 33465, Taiwan (R.O.C)

Tel: +886-3-2710188 / Fax: +886-3-2710190


101 · 1000 0 27 10100 / 1 dx · 1000 0 27 10100





Taiwan Accreditation Foundation accreditation number: 1330


Note: This report shall not be reproduced except in full, without the written approval of A Test Lab Techno Corp. This document may be altered or revised by A Test Lab Techno Corp. personnel only, and shall be noted in the revision section of the document. The client should not use it to claim product endorsement by TAF, or any government agencies. The test results in the report only apply to the tested sample.





Revision History

Rev.	Issue Date	Revisions	Revised By
00	Feb. 15, 2017	Initial Issue	Snow Wang





Verification of Compliance

Issued Date: Feb. 15, 2017

Nuheara Limited Applicant

IQbuds Product Type

Trade Name **NUHEARA**

Model Number NU317

FCC ID 2AKMG00000NU317

EUT Rated Voltage DC 4.2V, 100mA

Test Voltage 120 Vac / 60 Hz, 3.7Vdc

Applicable Standard FCC 47 CFR PART 15 SUBPART C

ANSI C63.10:2013

Test Result Complied

Performing Lab. : A Test Lab Techno Corp.

No. 140-1, Changan Street, Bade District,

Taoyuan City 33465, Taiwan (R.O.C)

Tel: +886-3-2710188 / Fax: +886-3-2710190

Taiwan Accreditation Foundation accreditation number: 1330

http://www.atl-lab.com.tw/e-index.htm

A Test Lab Techno Corp. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by A Test Lab Techno Corp. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Approved By

: Reviewed By
(Fly Lu) (Testing Engineer) (Manager)






TABLE OF CONTENTS

1	General Information	5
2	EUT Description	6
	Test Methodology	
	3.1. Mode of Operation	
	3.2. EUT Exercise Software	
	3.3. Configuration of Test System Details	
	3.4. Test Site Environment	
4	AC Power Line Conducted Emission Measurement	10
5	Radiated Emission Measurement	14
6	Maximum Conducted Output Power Measurement	29
7	6dB RF Bandwidth Measurement	30
8	Maximum Power Density Measurement	33
9	Out of Band Conducted Emissions Measurement	36
10	Antenna Measurement	40





1 General Information

1.1 Summary of Test Result

Standard	Item	Result	Remark
15.207	AC Power Conducted Emission	PASS	
15.247(d)	Transmitter Radiated Emissions	PASS	
15.247(b)(3)	Max. Output Power	PASS	
15.247(a)(2)	6dB RF Bandwidth PASS		
15.247(e)	Power Spectral Density	PASS	
15.247(d)	Out of Band Conducted Spurious Emission	PASS	
15.203	Antenna Requirement	PASS	

The test results of this report relate only to the tested sample(s) identified in this report. Manufacturer or whom it may concern should recognize the pass or fail of the test result.

1.2 Measurement Uncertainty

Test Item	Frequency Range	Uncertainty (dB)	
Conducted Emission	9kHz ~ 150KHz	2.7	
Conducted Emission	150kHz ~ 30MHz	2.7	
	9kHz ~ 30MHz	1.7	
	30MHz ~ 1000MHz	5.7	
Radiated Emission	1000MHz ~ 18000MHz	5.5	
	18000MHz ~ 26500MHz	4.8	
	26500MHz ~ 40000MHz	4.8	
Conducted Output Power	+0.27 dB / -0.28 dB		
RF Bandwidth	4.96%		
Power Spectral Density	+0.71 dB / -0.77 dB		





2 **EUT Description**

Applicant	Nuheara Limited Unit 5, 28 John St, Northbridge, WA 6003, Australia			
Manufacturer	Flextronics, Zhuhai Xin Qing Science & Technology Industrial Park, Jing An, Doumen, Zhuhai, P.R. China			
Product Type	IQbuds			
Trade Name	NUHEARA			
Model No.	NU317			
FCC ID	2AKMG00000NU317			
Frequency Range	Bluetooth LE: 2402 ~ 2480 MHz			
Modulation Type	GFSK			
Antenna Type	Ceramic 1206 Antenna			
Antenna Gain	0.5 dBi			
RF Output Power	0.00429 W /6.32 dBm			



Report Number: 1702FR13

3 Test Methodology

3.1. Mode of Operation

Decision of Test ATL has verified the construction and function in typical operation. All the test modes were carried out with the EUT in normal operation, which was shown in this test report and defined as:

Test Mode	
Mode 1: Con	ntinuous TX mode
Mode 2: Blue	etooth LE Link Mode

Software used to control the EUT for staying in continuous transmitting mode was programmed.

After verification, all tests were carried out with the worst case test modes as shown below except radiated spurious emission below 1GHz and power line conducted emissions below 30MHz, which worst case was in normal link mode only.

By preliminary testing and verifying three axis (X, Y and Z) position of EUT transmitted status, it was found that "X axis" position was the worst, then the final test was executed the worst condition and test data were recorded in this report.

Note: The EUT was programmed to be in continuously transmitting mode and the transmit duty cycle is not less than 98%.

Tested System Details


The types for all equipments, plus descriptions of all cables used in the tested system (including inserted cards) are:

Product		Manufacturer	Manufacturer Model Number		Power Cord
Bluetooth Tester		R&S	СВТ	100350	NA

3.2. EUT Exercise Software

1	Setup the EUT shown on 3.3.
2	Turn on the power of all equipment.
3	Turn on Bluetooth function and link to Bluetooth tester
4	EUT run test program.

Meas	Measurement Software		
1	1 EZ-EMC Ver. ATL-03A1-1		
2	EZ-EMC Ver ATL-ITC-3A1-1		






3.3. Configuration of Test System Details

AC Power Conducted Emission Remote Site Mobile phone CBT AC Input AC Adapter Notebook Charging/Carrying Case EUT


Remote Site Mobile Phone CBT





3.4. Test Site Environment

Items	Required (IEC 60068-1)	Actual	
Temperature (°C)	15-35	26	
Humidity (%RH)	25-75	60	
Barometric pressure (mbar)	860-1060	950	





4 AC Power Line Conducted Emission Measurement

■ Limit


Frequency (MHz)	Quasi-peak	Average
0.15 - 0.5	66 to 56	56 to 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50

■ Test Instruments

Describe	Manufacturer	Model Number	Serial Number	Cal. Date	Remark
Test Receiver	R&S	ESCI	100367	05/13/2016	1 year
LISN	R&S	ENV216	101040	03/15/2016	1 year
LISN	R&S	ENV216	101041	03/07/2016	1 year
RF Cable	Woken	00100D1380194M	TE-02-02	05/31/2016	1 year
Test Site	ATL	TE02	TE02	N.C.R.	

Note: N.C.R. = No Calibration Request.

■ Test Setup





Report Number: 1702FR13

■ Test Procedure


The EUT and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a $50\,\Omega$ // 50uH coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN that provides a $50\,\Omega$ // 50uH coupling impedance with 50ohm termination.

Tabletop device shall be placed on a non-conducting platform, of nominal size 1 m by 1.5 m, raised 80 cm above the reference ground plane. The wall of screened room shall be located 40cm to the rear of the EUT. Other surfaces of tabletop or floor standing EUT shall be at least 80cm from any other ground conducting surface including one or more LISNs. For floor-standing device shall be placed under the EUT with a 12mm insulating material.

Conducted emissions were investigated over the frequency range from 0.15 MHz to 30 MHz using a resolution bandwidth of 9 kHz. The equipment under test (EUT) shall be meet the limits in section 4.1, as applicable, including the average limit and the quasi-peak limit when using respectively, an average detector and quasi-peak detector measured in accordance with the methods described of related standard. When all of peak value were complied with quasi-peak and average limit from 150kHz to 30MHz then quasi-peak and average measurement was unnecessary.

The AMN shall be placed 0,8 m from the boundary of the unit under test and bonded to a ground reference plane for AMNs mounted on top of the ground reference plane. This distance is between the closest points of the AMN and the EUT. All other units of the EUT and associated equipment shall be at least 0,8 m from the AMN. If the mains power cable is longer than 1m then the cable shall be folded back and forth at the centre of the lead to form a bundle no longer than 0.4m. All of interconnecting cables that hang closer than 40cm to the ground plane shall be folded back and forth in the center forming a bundle 30 cm to 40 cm long. All of EUT and AE shall be separate place more than 0.1m. All 50 Ω ports of the LISN shall be resistively terminated into 50 Ω loads when not connected to the measuring instrument.


If the reading of the measuring receiver shows fluctuations close to the limit, the reading shall be observed for at least 15 s at each measurement frequency; the higher reading shall be recorded with the exception of any brief isolated high reading which shall be ignored.





■ Test Result


Standard:	FCC Part 15C	Power:	AC 120V/60Hz
Test Mode:	Mode 1	Temp.(°ℂ)/Hum.(%RH):	26(°ℂ)/60%RH
Line:	L1	Date:	12/05/2016
Description:			



No.	Frequency	QP	AVG	Correction	QP	AVG	QP	AVG	QP	AVG	Remark
		reading	reading	factor	result	result	limit	limit	margin	margin	
	(MHz)	(dBuV)	(dBuV)	(dB)	(dBuV)	(dBuV)	(dBuV)	(dBuV)	(dB)	(dB)	
1	0.1500	38.16	14.62	9.60	47.76	24.22	66.00	56.00	-18.24	-31.78	Pass
2	0.1980	45.39	27.38	9.59	54.98	36.97	63.69	53.69	-8.71	-16.72	Pass
3	0.2580	38.00	18.53	9.60	47.60	28.13	61.50	51.50	-13.90	-23.37	Pass
4	0.2700	38.51	20.06	9.60	48.11	29.66	61.12	51.12	-13.01	-21.46	Pass
5	0.3260	32.58	15.69	9.60	42.18	25.29	59.55	49.55	-17.37	-24.26	Pass
6	0.3900	32.54	14.17	9.60	42.14	23.77	58.06	48.06	-15.92	-24.29	Pass
7	0.4100	32.54	15.07	9.60	42.14	24.67	57.65	47.65	-15.51	-22.98	Pass
8	2.1940	31.06	18.15	9.70	40.76	27.85	56.00	46.00	-15.24	-18.15	Pass
9	2.5860	29.15	15.13	9.71	38.86	24.84	56.00	46.00	-17.14	-21.16	Pass

Note: 1. Result (dBuV) = Correction factor (dB) + Reading(dBuV).

2. Correction factor (dB) = Cable loss (dB) + L.I.S.N. factor (dB).






 Standard:
 FCC Part 15C
 Power:
 AC 120V/60Hz

 Test Mode:
 Mode 1
 Temp.(°C)/Hum.(%RH):
 26(°C)/60%RH

 Line:
 N
 Date:
 12/05/2016


 Description:
 12/05/2016
 12/05/2016



No.	Frequency	QP	AVG	Correction	QP	AVG	QP	AVG	QP	AVG	Remark
		reading	reading	factor	result	result	limit	limit	margin	margin	
	(MHz)	(dBuV)	(dBuV)	(dB)	(dBuV)	(dBuV)	(dBuV)	(dBuV)	(dB)	(dB)	
1	0.1940	47.10	27.29	9.58	56.68	36.87	63.86	53.86	-7.18	-16.99	Pass
2	0.2060	48.09	29.05	9.58	57.67	38.63	63.37	53.37	-5.70	-14.74	Pass
3	0.2540	40.51	17.54	9.59	50.10	27.13	61.63	51.63	-11.53	-24.50	Pass
4	0.2620	43.19	20.87	9.59	52.78	30.46	61.37	51.37	-8.59	-20.91	Pass
5	0.2700	43.07	21.71	9.59	52.66	31.30	61.12	51.12	-8.46	-19.82	Pass
6	0.2780	42.98	20.79	9.59	52.57	30.38	60.88	50.88	-8.31	-20.50	Pass
7	0.3220	38.07	17.00	9.59	47.66	26.59	59.66	49.66	-12.00	-23.07	Pass
8	0.3820	38.20	14.09	9.59	47.79	23.68	58.24	48.24	-10.45	-24.56	Pass
9	0.3900	40.39	15.71	9.59	49.98	25.30	58.06	48.06	-8.08	-22.76	Pass
10	0.4100	39.75	16.24	9.59	49.34	25.83	57.65	47.65	-8.31	-21.82	Pass
11	0.5060	32.07	21.93	9.60	41.67	31.53	56.00	46.00	-14.33	-14.47	Pass
12	0.5140	35.33	14.86	9.60	44.93	24.46	56.00	46.00	-11.07	-21.54	Pass
13	0.5220	35.93	13.67	9.60	45.53	23.27	56.00	46.00	-10.47	-22.73	Pass
14	0.6380	29.44	11.99	9.60	39.04	21.59	56.00	46.00	-16.96	-24.41	Pass
15	0.6660	29.86	10.42	9.61	39.47	20.03	56.00	46.00	-16.53	-25.97	Pass
16	0.7020	29.41	12.78	9.62	39.03	22.40	56.00	46.00	-16.97	-23.60	Pass

Note: 1. Result (dBuV) = Correction factor (dB) + Reading(dBuV).

2. Correction factor (dB) = Cable loss (dB) + L.I.S.N. factor (dB).





5 Radiated Emission Measurement

■ Limit

According to §15.209(a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:


Frequency	Field Strength	Measurement Distance
(MHz)	(µV/m at meter)	(meters)
0.009 - 0.490	2400 / F (kHz)	300
0.490 – 1.705	24000 / F (kHz)	30
1.705 – 30.0	30	30
30 - 88	100**	3
88-216	150**	3
216-960	200**	3
Above 960	500	3

^{**} Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

Test Instruments

		3 Meter Chamber			
Equipment	Manufacturer	Model Number	Serial Number	Cal. Date	Cal. Period
RF Pre-selector	Agilent	N9039A	MY46520256	03/22/2016	1 year
Spectrum Analyzer Agilent		E4446A	MY46180578	03/22/2016	1 year
Pre Amplifier	Agilent	8449B	3008A02237	10/11/2016	1 year
Pre Amplifier	Agilent	8447D	2944A11119	01/11/2016	1 year
Broadband Antenna	Schwarzbeck	VULB9168	416	10/13/2016	1 year
Horn Antenna (1~18GHz)	SCHWARZBECK MESS-ELEKTRONIK	BBHA9120D	9120D-550	06/06/2016	1 year
Horn Antenna (18~40GHz)	ETS	3116	86467	09/05/2016	1 year
Loop Antenna	COM-POWER CORPORATION	AL-130	121014	02/01/2016	1 year
Microwave Cable	EMCI	EMC102-KM-KM-14000	151001	02/23/2016	1 year
Microwave Cable	EMCI	EMC-104-SM-SM-14000	140202	02/23/2016	1 year
Microwave Cable	EMCI	EMC104-SM-SM-600	140301	02/23/2016	1 year
Test Site	ATL	TE01	888001	08/29/2016	1 year


Note: N.C.R. = No Calibration Request.







■ Setup

9kHz ~ 30MHz




Below 1GHz







Above 1GHz



■ Test Procedure

Final radiation measurements were made on a three-meter, Semi Anechoic Chamber. The EUT system was placed on a nonconductive turntable which is 0.8 or 1.5 meters height(below 1GHz use 0.8m turntable / above 1GHz use 1.5m turntable), top surface 1.0 x 1.5 meter. The spectrum was examined from 250 MHz to 2.5 GHz in order to cover the whole spectrum below 10th harmonic which could generate from the EUT. During the test, EUT was set to transmit continuously & Measurements spectrum range from 9 kHz to 26.5 GHz is investigated.

For measurements below 1 GHz the resolution bandwidth is set to 100 kHz for peak detection measurements or 120 kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, and then the video bandwidth is set to 1 MHz for peak measurements and 10 Hz for average measurements when Duty cycle >98% / 1/T for average measurements when Duty cycle <98%. A nonconductive material surrounded the EUT to supporting the EUT for standing on tree orthogonal planes. At each condition, the EUT was rotated 360 degrees, and the antenna was raised and lowered from one to four meters to find the maximum emission levels. Measurements were taken using both horizontal and vertical antenna polarization.

SCHWARZBECK MESS-ELEKTRONIK Biconilog Antenna at 3 Meter and the SCHWARZBECK Double Ridged Guide Antenna was used in frequencies 1 – 26.5 GHz at a distance of 1 meter. All test results were extrapolated to equivalent signal at 3 meters utilizing an inverse linear distance extrapolation Factor (20dB/decade).



Report Number: 1702FR13

For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.

Appropriate preamplifiers were used for improving sensitivity and precautions were taken to avoid overloading or desensitizing the spectrum analyzer. No post – detector video filters were used in the test.

The spectrum analyzer's 6 dB bandwidth was set to 1 MHz, and the analyzer was operated in the peak detection mode, for frequencies both below and up 1 GHz. The average levels were obtained by subtracting the duty cycle correction factor from the peak readings.

The following procedures were used to convert the emission levels measured in decibels referenced to 1 microvolt (dBuV) into field intensity in micro volts pre meter (uV/m).

The actual field intensity in decibels referenced to 1 microvolt in to field intensity in micro colts per meter (dBuV/m).

The actual field is intensity in referenced to 1 microvolt per meter (dBuV/m) is determined by algebraically adding the measured reading in dBuV, the antenna factor (dB), and cable loss (dB) and Subtracting the gain of preamplifier (dB) is auto calculate in spectrum analyzer.

(1) Amplitude (dBuV/m) = FI (dBuV) +AF (dBuV) +CL (dBuV)-Gain (dB)

FI= Reading of the field intensity.

AF= Antenna factor.

CL= Cable loss.

P.S Amplitude is auto calculate in spectrum analyzer.

(2) Actual Amplitude (dBuV/m) = Amplitude (dBuV)-Dis(dB)

The FCC specified emission limits were calculated according the EUT operating frequency and by following linear interpolation equations:

- (a) For fundamental frequency: Transmitter Output < +30dBm
- (b) For spurious frequency: Spurious emission limits = fundamental emission limit /10

Data of measurement within this frequency range without mark in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.





■ Test Result

Below 1GHz

 Standard:
 FCC Part 15C
 Test Distance:
 3m


 Test Mode:
 Mode 1
 Power:
 DC 3.7V

 Temp.(°C)/Hum.(%RH):
 26(°C)/60%RH

 Date:
 12/18/2016

							-
Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
152.5000	21.30	-5.22	16.08	43.50	-27.42	QP	Н
282.0000	19.79	-3.88	15.91	46.00	-30.09	QP	Н
403.5000	22.09	-1.59	20.50	46.00	-25.50	QP	Н
586.0000	21.34	2.51	23.85	46.00	-22.15	QP	Н
723.0000	22.37	5.29	27.66	46.00	-18.34	QP	Н
887.0000	20.55	8.33	28.88	46.00	-17.12	QP	Н
150.0000	22.25	-5.29	16.96	43.50	-26.54	QP	V
305.0000	18.95	-3.30	15.65	46.00	-30.35	QP	V
441.0000	23.01	-0.45	22.56	46.00	-23.44	QP	V
598.5000	22.33	2.88	25.21	46.00	-20.79	QP	V
773.0000	22.93	6.33	29.26	46.00	-16.74	QP	V
921.0000	22.01	9.04	31.05	46.00	-14.95	QP	V


- 2. Correction factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) Pre-Amplifier gain (dB).
- 3. No emission found between lowest internal used/generated frequencies to 30MHz (9 kHz~30MHz).






Above 1GHz

Standard:	FCC Part 15C	Test Distance:	3m
Test item:	Harmonic	Power:	DC 3.7V
Frequency:	2402MHz	Temp.(°ℂ)/Hum.(%RH):	26(℃)/60%RH
Mode:	Mode 2	Date:	12/18/2016
Ant.Polar.:	Horizontal		



No.	Frequency	Reading	Correct Factor	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	4804.000	50.53	-8.01	42.52	74.00	-31.48	peak

- $2. Correction \ factor \ (dB/m) = Antenna \ Factor \ (dB/m) + Cable \ loss \ (dB) Pre-Amplifier \ gain \ (dB).$
- 3. When the peak results are less than average limit, so not need to evaluate the average.






Test item: Power: DC 3.7V

Frequency: 2402MHz Temp.($^{\circ}$ C)/Hum.($^{\circ}$ RH): 26($^{\circ}$ C)/60%RH


Mode: Mode 2 Date: 12/18/2016

Ant.Polar.: Vertical



Ī	No.	Frequency	Reading	Correct Factor	Result	Limit	Margin	Remark
		(MHz)	(dBuV)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
	1	4804.000	49.81	-8.01	41.80	74.00	-32.20	peak

- 2.Correction factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) Pre-Amplifier gain (dB).
- 3. When the peak results are less than average limit, so not need to evaluate the average.






Test item: Power: DC 3.7V

Frequency: 2440MHz Temp.(°ℂ)/Hum.(%RH): 26(°ℂ)/60%RH


Mode: Mode 2 Date: 12/18/2016

Ant.Polar.: Horizontal



Ī	No.	Frequency	Reading	Correct Factor	Result	Limit	Margin	Remark
		(MHz)	(dBuV)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
	1	4880.000	50.71	-7.77	42.94	74.00	-31.06	peak

- $2. Correction \ factor \ (dB/m) = Antenna \ Factor \ (dB/m) + Cable \ loss \ (dB) Pre-Amplifier \ gain \ (dB).$
- 3. When the peak results are less than average limit, so not need to evaluate the average.






Test item: Power: DC 3.7V

Frequency: 2440MHz Temp.(°ℂ)/Hum.(%RH): 26(°ℂ)/60%RH


Mode: Mode 2 Date: 12/18/2016

Ant.Polar.: Vertical



No	. Frequency	Reading	Correct Factor	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	4880.000	50.76	-7.77	42.99	74.00	-31.01	peak

- $2. Correction \ factor \ (dB/m) = Antenna \ Factor \ (dB/m) + Cable \ loss \ (dB) Pre-Amplifier \ gain \ (dB).$
- 3. When the peak results are less than average limit, so not need to evaluate the average.






Test item: Power: DC 3.7V

Frequency: 2480MHz Temp.(°ℂ)/Hum.(%RH): 26(°ℂ)/60%RH


Mode: Mode 2 Date: 12/18/2016

Ant.Polar.: Horizontal



No.	Frequency	Reading	Correct Factor	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	4960.000	50.27	-7.52	42.75	74.00	-31.25	peak

- $2. Correction \ factor \ (dB/m) = Antenna \ Factor \ (dB/m) + Cable \ loss \ (dB) Pre-Amplifier \ gain \ (dB).$
- 3. When the peak results are less than average limit, so not need to evaluate the average.






Test item: Power: DC 3.7V

Frequency: 2480MHz Temp.(°ℂ)/Hum.(%RH): 26(°ℂ)/60%RH


Mode: Mode 2 Date: 12/18/2016

Ant.Polar.: Vertical



No. Frequency		Reading	Correct Factor	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	4960.000	50.15	-7.52	42.63	74.00	-31.37	peak


- $2. Correction \ factor \ (dB/m) = Antenna \ Factor \ (dB/m) + Cable \ loss \ (dB) Pre-Amplifier \ gain \ (dB).$
- 3. When the peak results are less than average limit, so not need to evaluate the average.






Band Edge

Standard:	FCC Part 15C	Test Distance:	3m
Test item:	Band edge	Power:	DC 3.7V
Frequency:	2402MHz	Temp.(°ℂ)/Hum.(%RH):	26(°C)/60%RH
Mode:	Mode 2	Date:	12/18/2016
Ant.Polar.:	Horizontal		



No.	Frequency	Reading	Correct Factor	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	2375.340	38.52	-0.32	38.20	74.00	-35.80	peak
2	2390.000	35.99	-0.26	35.73	74.00	-38.27	peak

- 2.Correction factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) Pre-Amplifier gain (dB).
- 3. When the peak results are less than average limit, so not need to evaluate the average.






Test item: Band edge Power: DC 3.7V

Frequency: 2402MHz Temp.($^{\circ}$ C)/Hum.($^{\circ}$ RH): 26($^{\circ}$ C)/60%RH


Mode: Mode 2 Date: 12/18/2016

Ant.Polar.: Vertical



No.	Frequency	Reading	Correct Factor	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	2376.880	39.05	-0.31	38.74	74.00	-35.26	peak
2	2390.000	37.45	-0.26	37.19	74.00	-36.81	peak

- 2.Correction factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) Pre-Amplifier gain (dB).
- 3. When the peak results are less than average limit, so not need to evaluate the average.






Test item: Band edge Power: DC 3.7V

Frequency: 2480MHz Temp.($^{\circ}$ C)/Hum.($^{\circ}$ RH): 26($^{\circ}$ C)/60 $^{\circ}$ RH


Mode: Mode 2 Date: 12/18/2016

Ant.Polar.: Horizontal



No.	Frequency	Reading	Correct Factor	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	2483.500	35.84	0.11	35.95	74.00	-38.05	peak
2	2484.500	39.66	0.12	39.78	74.00	-34.22	peak

- 2.Correction factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) Pre-Amplifier gain (dB).
- 3. When the peak results are less than average limit, so not need to evaluate the average.






Test item: Band edge Power: DC 3.7V

Frequency: 2480MHz Temp.($^{\circ}$ C)/Hum.($^{\circ}$ RH): 26($^{\circ}$ C)/60%RH

Mode: Mode 2 Date: 12/18/2016

Ant.Polar.: Vertical



No.	Frequency	Reading	Correct Factor	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	2483.500	37.12	0.11	37.23	74.00	-36.77	peak
2	2485.560	41.69	0.12	41.81	74.00	-32.19	peak

- 2.Correction factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) Pre-Amplifier gain (dB).
- 3. When the peak results are less than average limit, so not need to evaluate the average.






6 Maximum Conducted Output Power Measurement

■ Limit

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm.

■ Test Setup



■ Test Instruments

Equipment	Manufacturer	Model Number	Serial Number	Cal. Date	Remark
Power Sensor	Anritsu	MA2411B	1126022	08/29/2016	1 year
Power Meter	Anritsu	ML2495A	1135009	08/29/2016	1 year
Microwave Cable	EMCI	EMC104-SM-S M-1500	140303	02/23/2016	1 year
Test Site	ATL	TE05	TE05	N.C.R.	

Note: N.C.R. = No Calibration Request.


■ Test Procedure

T he tests below are run with the EUT's transmitter set at high power in TX mode. The EUT is needed to force selection of output power level and channel number. While testing, EUT was set to transmit continuously. Remove the Subjective device's antenna and connect the RF output port to power sensor..

■ Test Result

Test Date:	12/05/2016				
Frequency	Average Power		Peak	Limit	
(MHz)	(dBm)	(W)	(dBm)	(W)	(dBm)
2402	5.83	0.00383	6.10	0.00407	< 30
2440	6.01	0.00399	6.32	0.00429	< 30
2480	5.92	0.00391	6.23	0.00420	< 30

Note: The relevant measured result has the offset with cable loss already.






7 6dB RF Bandwidth Measurement

■ Limit

6dB RF Bandwidth: Systems using digital modulation techniques may operate in the 2400–2483.5 MHz bands. The minimum 6 dB band-width shall be at least 500 kHz.

■ Test Setup



Test Instruments


Equipment	Manufacturer	Model Number	Serial Number	Cal. Date	Remark
Spectrum Analyzer	Agilent	E4445A	MY45300744	12/19/2016	1 year
Microwave Cable	EMCI	EMC104-SM-S M-1500	140303	02/23/2016	1 year
Test Site	ATL	TE05	TE05	N.C.R.	

Note: N.C.R. = No Calibration Request.

■ Test Procedure

The EUT tested to DTS test procedure of KDB558074D01 for compliance to FCC 47CFR 15.247 requirements. 6dB RF Bandwidth: The antenna port of the EUT was connected to the input of a spectrum analyzer. Analyzer RBW was set to 100 kHz. For each RF output channel investigated, the spectrum analyzer center frequency was set to the channel carrier. A peak output reading was taken, a DISPLAY line was drawn 6 dB lower than peak level. The 6 dB bandwidth was determined from where the channel output spectrum intersected the display line.


The test was performed at 3 channels (Channel low, middle, high)






■ Test Result

Test Date:	12/19/2016				
Frequency (MHz)	Measurement Results (kHz)	Limit (kHz)			
2402	701.077	> 500			
2440	706.192	> 500			
2480	708.740	> 500			





Test Graphs








8 Maximum Power Density Measurement

■ Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

■ Test Setup



■ Test Instruments


Equipment	Manufacturer	Model Number	Serial Number	Cal. Date	Remark
Spectrum Analyzer	Agilent	E4445A	MY45300744	12/19/2016	1 year
Microwave Cable	EMCI	EMC104-SM-S M-1500	140303	02/23/2016	1 year
Test Site	ATL	TE05	TE05	N.C.R.	

Note: N.C.R. = No Calibration Request.

■ Test Procedure

The EUT tested to DTS test procedure of KDB558074D01 for compliance to FCC 47CFR 15.247 requirements.


- 1. Set analyzer center frequency to DTS channel center frequency.
- 2. Set the span to 1.5 times the DTS bandwidth.
- 3. Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- 4. Set the VBW \geq 3 \times RBW.
- 5. Detector = peak.
- 6. Sweep time = auto couple.
- 7. Trace mode = max hold.
- 8. Allow trace to fully stabilize.
- 9. Use the peak marker function to determine the maximum amplitude level within the RBW.
- 10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.






■ Test Result

Test Date:	12/19/2016				
Frequency (MHz)	Measurement Results (dBm/3KHz)	Limit (dBm)			
2402	-11.120	< 8			
2440	-8.206	< 8			
2480	-8.934	< 8			





■ Test Graphs








9 Out of Band Conducted Emissions Measurement

■ Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power

■ Test Setup



■ Test Instruments


Equipment	Manufacturer	Model Number	Serial Number	Cal. Date	Remark
Spectrum Analyzer	Agilent	E4445A	MY45300744	12/19/2016	1 year
Spectrum Analyzer	Agilent	E4408B	MY45107753	08/08/2016	1 year
Microwave Cable	EMCI	EMC104-SM-S M-1500	140303	02/23/2016	1 year
Test Site	ATL	TE05	TE05	N.C.R.	

Note: N.C.R. = No Calibration Request.

■ Test Procedure


In any 100 kHz bandwidth outside the EUT pass band, the RF power produced by the modulation products of the spreading sequence, the information sequence, and the carrier frequency shall be at least 20 dB below that of the maximum in-band 100 kHz emission, antenna output of the EUT was coupled directly to spectrum analyzer; if an external attenuator and/or cable was used, these losses are compensated for with the analyzer OFFSET function. All other types of emissions from the EUT shall meet the general limits for radiated frequencies outside the pass band.


The test was performed at 3 channels.







Test Graphs




















10 Antenna Measurement

■ Limit

For intentional device, according to 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And According to 15.247 (b), if transmitting antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

■ Antenna Connector Construction

See section 2 – antenna information.