

APPLICATION FOR VERIFICATION

On Behalf of
TQL TRADING INC

SPEAKER

Model No.: TQ-LT1504, TQ-LT1512, TQ-LT1513, TQ-LT1514, TQ-LT1516,
TQ-LT1517, TQ-LT1518, TQ-LT1519, TQ-LT1520, TQ-LT1521

FCC ID: 2AKNJTQ-LT1504

Prepared for : TQL TRADING INC.
Address : 334 S LOS ANGELES ST #9002, LOS ANGELES,
CALIFORNIA, 90013, United States
Prepared by : Accurate Technology Co., Ltd.
Address : F1, Bldg. A&D, Changyuan New Material Port, Keyuan
Rd., Science & Industry Park, Nanshan District, Shenzhen
518057, P.R. China

Tel: +86-755-26503290
Fax: +86-755-26503396

Report No. : ATE20161336
Date of Test : July 01--Dec. 28, 2016
Date of Report : Dec. 29, 2016

TABLE OF CONTENTS

Description	Page
Test Report Declaration	
1. TEST RESULTS SUMMARY	4
2. GENERAL INFORMATION	5
2.1. Product of Device (EUT)	5
2.2. Test mode of EUT	5
2.3. Accessory and Auxiliary Equipment.....	6
2.4. Description of Test Facility	7
2.5. Measurement Uncertainty.....	7
3. MEASURING DEVICE AND TEST EQUIPMENT	8
4. POWER LINE CONDUCTED MEASUREMENT.....	9
4.1. Block Diagram of Test Setup and Test mode description	9
4.2. The Emission Limit.....	10
4.3. Configuration of EUT on Measurement	10
4.4. Operating Condition of EUT	11
4.5. Test Procedure	11
4.6. Power Line Conducted Emission Measurement Results.....	11
5. RADIATED EMISSION MEASUREMENT	44
5.1. Block Diagram of Test Setup	44
5.2. The Emission Limit For Section 15.109 (a).....	46
5.3. EUT Configuration on Measurement	46
5.4. Operating Condition of EUT	47
5.5. Test Procedure	47
5.6. Radiated Emission Noise Measurement Result.....	47
6. PHOTOGRAPHS.....	80
6.1. Photos of Radiated Emission Measurement.....	80
6.2. Photo of Conducted Emission Measurement	81
7. PHOTO OF EUT	82

Test Report Declaration

Applicant : TQL TRADING INC.

Manufacturer : TQL TRADING INC.

Product : SPEAKER

Model No. : TQ-LT1504, TQ-LT1512, TQ-LT1513, TQ-LT1514,
TQ-LT1516, TQ-LT1517, TQ-LT1518, TQ-LT1519,
TQ-LT1520, TQ-LT1521

(Note: they are identical in interior structure, electrical circuits and components, and Product model is different because of different Color of product appearance. So we prepare the TQ-LT1504 for test.)

Trade name : H&A

Measurement Procedure Used:

FCC Rules and Regulations Part 15 Subpart B ANSI C63.4: 2014

The device described above is tested by Accurate Technology Co., Ltd. to determine the maximum emission levels emanating from the device. The maximum emission levels are compared to the FCC Part 15 Subpart B Class B limits both radiated and conducted emissions. The measurement results are contained in this test report and Accurate Technology Co., Ltd. is assumed full responsibility for the accuracy and completeness of these measurements. Also, this report shows that the Equipment Under Test (EUT) is to be technically compliant with the FCC requirements.

This report applies to above tested sample only. This report shall not be reproduced in part without written approval of Accurate Technology Co., Ltd.

Date of Test :

July 01--Dec. 28, 2016

Date of Report :


Dec. 29, 2016

Prepared by :



(Tim.zhang, Engineer)

Approved & Authorized Signer :



(Sean Liu, Manager)

1. TEST RESULTS SUMMARY

Test Items	Test Standard	Test Results
Power Line Conducted Emission	FCC Part 15 Subpart B	Pass
Radiated Emission	FCC Part 15 Subpart B	Pass

2. GENERAL INFORMATION

2.1. Product of Device (EUT)

EUT	: SPEAKER
Model Number	: TQ-LT1504, TQ-LT1512, TQ-LT1513, TQ-LT1514, TQ-LT1516, TQ-LT1517, TQ-LT1518, TQ-LT1519, TQ-LT1520, TQ-LT1521
Power Supply	: AC 110V/60Hz-220V/50Hz Or EXTERNAL DC 12V
Trade Name	: H&A
Remark(s)	: The EUT highest operating frequency provided by Manufacturer is 202.2MHz, the radiated emission measurement shall be made up to 3 GHz.
Modulation:	: FM
Receiver Frequency	: 202.2MHz RX
Applicant	: TQL TRADING INC.
Address	: 334 S LOS ANGELES ST #9002, LOS ANGELES, CALIFORNIA, 90013, United States
Manufacturer	: TQL TRADING INC.
Address	: 334 S LOS ANGELES ST #9002, LOS ANGELES, CALIFORNIA, 90013, United States
Date of sample received	: July 01, 2016
Date of Test	: July 01--Dec. 28, 2016

2.2. Test mode of EUT

Test mode 1: TF card PLAYING
Test mode 2: SD card PLAYING
Test mode 3: AUX IN
Test mode 4: 202.2MHz RX
Test mode 5: USB PLAYING
Test mode 6: FM
Test mode 7: GUITAR IN
Test mode 8: MIC IN

2.3. Accessory and Auxiliary Equipment

FM Generator	:	Manufacturer: Rohde & Schwarz M/N: SML01 S/N: 101161
Audio Generator	:	Manufacturer: NEW AOKO M/N: GAG-810 S/N: D913311
USB Memory Disk	:	Manufacturer: Smartocean M/N: 3611 S/N: 101200005
GUITAR	:	Manufacturer: GIBSON M/N: PR-4E
MIC	:	Manufacturer: TAKSTAR M/N: PC-K600
TF CARD	:	Manufacturer: Lexar M/N: 633x
SD CARD	:	Manufacturer: SONY M/N: SR-8UY
Wireless MIC	:	Manufacturer: TQL TRADING INC M/N: TQ-LT1504

2.4. Description of Test Facility

EMC Lab : Accredited by TUV Rheinland Shenzhen, May 10, 2004

Listed by FCC
The Registration Number is 253065
Listed by FCC
The Registration Number is 752051

Listed by Industry Canada
The Registration Number is 5077A-1
Listed by Industry Canada
The Registration Number is 5077A-2

Accredited by China National Accreditation Committee for Laboratories
The Certificate Registration Number is L3193

Name of Firm : Accurate Technology Co., Ltd.
Site Location : F1, Bldg. A&D, Changyuan New Material Port, Keyuan Rd., Science & Industry Park, Nanshan District, Shenzhen 518057, P.R. China

2.5. Measurement Uncertainty

Conducted emission expanded uncertainty : U=2.23dB, k=2
Power disturbance expanded uncertainty : U=2.92dB, k=2
Radiated emission expanded uncertainty : U=3.08dB, k=2
(9kHz-30MHz)
Radiated emission expanded uncertainty : U=4.42dB, k=2
(30MHz-1000MHz)
Radiated emission expanded uncertainty : U=4.06dB, k=2
(Above 1GHz)

3. MEASURING DEVICE AND TEST EQUIPMENT


Table 1: List of Test and Measurement Equipment

Kind of equipment	Manufacturer	Type	S/N	Calibrated dates	Cal. Interval
EMI Test Receiver	Rohde&Schwarz	ESCS30	100307	Jan. 09, 2016	One Year
EMI Test Receiver	Rohde&Schwarz	ESPI3	101526/003	Jan. 09, 2016	One Year
Spectrum Analyzer	Agilent	E7405A	MY45115511	Jan. 09, 2016	One Year
Pre-Amplifier	Rohde&Schwarz	CBLU118354 0-01	3791	Jan. 09, 2016	One Year
Loop Antenna	Schwarzbeck	FMZB1516	1516131	Jan. 14, 2016	One Year
Bilog Antenna	Schwarzbeck	VULB9163	9163-323	Jan. 14, 2016	One Year
Horn Antenna	Schwarzbeck	BBHA9120D	9120D-655	Jan. 14, 2016	One Year
Horn Antenna	Schwarzbeck	BBHA9120D	9120D-1067	Jan. 14, 2016	One Year
LISN	Rohde&Schwarz	ESH3-Z5	100305	Jan. 09, 2016	One Year
LISN	Schwarzbeck	NSLK8126	8126431	Jan. 09, 2016	One Year
Highpass Filter	Wainwright Instruments	WHKX3.6/18 G-10SS	N/A	Jan. 09, 2016	One Year
Band Reject Filter	Wainwright Instruments	WRCG2400/2 485-2375/251 0-60/11SS	N/A	Jan. 09, 2016	One Year


4. POWER LINE CONDUCTED MEASUREMENT

4.1. Block Diagram of Test Setup and Test mode description


Test mode 1: TF card PLAYING




Test mode 2: SD card PLAYING




Test mode 3: AUX IN




Test mode 4: 202.2MHz RX




Test mode 5: USB PLAYING




Test mode 6: FM



Test mode 7: GUITAR IN



Test mode 8: MIC IN



4.2. The Emission Limit

4.2.1. Conducted Emission Measurement Limits According to Section 15.107(a)

Frequency (MHz)	Limit dB(μV)	
	Quasi-peak Level	Average Level
0.15 - 0.50	66.0 – 56.0 *	56.0 – 46.0 *
0.50 - 5.00	56.0	46.0
5.00 - 30.00	60.0	50.0

* Decreases with the logarithm of the frequency.

4.3. Configuration of EUT on Measurement

The following equipments are installed on Power Line Conducted Emission Measurement to meet the commission requirement and operating regulations in a manner, which tends to maximize its emission characteristics in a normal application.

4.3.1. SPEAKER (EUT)

Model Number : TQ-LT1504
Serial Number : N/A
Manufacturer : TQL TRADING INC.

4.4. Operating Condition of EUT

4.4.1. Setup the EUT and simulator as shown as Section 4.1

4.4.2. Turn on the power of all equipment.

4.4.3. Let the EUT work in test mode and measure it.

4.5. Test Procedure

The EUT is put on the plane 0.1m high above the ground by insulating support and is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC lines are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to ANSI C63.4: 2014 on Conducted Emission Measurement.

The bandwidth of test receiver (R & S ESCS30) is set at 9kHz.

The frequency range from 150kHz to 30MHz is checked.

4.6. Power Line Conducted Emission Measurement Results

PASS.

Emissions attenuated more than 20 dB below the permissible value are not reported.

The spectral diagrams are shown in the following pages.

Test mode 1


ACCURATE TECHNOLOGY CO., LTD

CONDUCTED EMISSION STANDARD FCC PART 15B

EUT: SPEAKER M/N:TQ-LT1504
 Manufacturer: TQL TRADING INC
 Operating Condition: TF CARD PLAYING
 Test Site: 1#Shielding Room
 Operator: DING
 Test Specification: N 120V/60Hz
 Comment: Report NO.:ATE20161336
 Start of Test: 7/12/2016 / 12:54:54PM

SCAN TABLE: "V 9K-30MHz fin"

Short Description: SUB STD VTERM2 1.70
 Start Stop Step Detector Meas. IF Transducer
 Frequency Frequency Width Time Bandw.
 9.0 kHz 150.0 kHz 100.0 Hz QuasiPeak 1.0 s 200 Hz NSLK8126 2008
 Average
 150.0 kHz 30.0 MHz 5.0 kHz QuasiPeak 1.0 s 9 kHz NSLK8126 2008
 Average



MEASUREMENT RESULT: "TQ-0712-06_fin"

7/12/2016 12:59PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.355000	33.40	10.6	59	25.4	QP	N	GND
0.850000	38.40	10.8	56	17.6	QP	N	GND
0.910000	34.20	10.8	56	21.8	QP	N	GND
3.370000	31.20	11.1	56	24.8	QP	N	GND
5.910000	34.10	11.2	60	25.9	QP	N	GND
12.625000	23.10	11.3	60	36.9	QP	N	GND

MEASUREMENT RESULT: "TQ-0712-06_fin2"

7/12/2016 12:59PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.355000	22.90	10.6	49	25.9	AV	N	GND
0.425000	30.40	10.7	47	16.9	AV	N	GND
1.485000	24.60	10.9	46	21.4	AV	N	GND
3.260000	21.20	11.1	46	24.8	AV	N	GND
5.900000	23.90	11.2	50	26.1	AV	N	GND
12.625000	15.00	11.3	50	35.0	AV	N	GND

ACCURATE TECHNOLOGY CO., LTD


CONDUCTED EMISSION STANDARD FCC PART 15B

EUT: SPEAKER M/N:TQ-LT1504
 Manufacturer: TQL TRADING INC
 Operating Condition: TF CARD PLAYING
 Test Site: 1#Shielding Room
 Operator: DING
 Test Specification: L 120V/60Hz
 Comment: Report NO.:ATE20161336
 Start of Test: 7/12/2016 / 12:49:47PM

SCAN TABLE: "V 9K-30MHz fin"

Short Description: SUB STD VTERM2 1.70

Start Frequency	Stop Frequency	Step Width	Detector	Meas. Time	IF Bandw.	Transducer
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	NSLK8126 2008
150.0 kHz	30.0 MHz	5.0 kHz	Average	1.0 s	9 kHz	NSLK8126 2008



MEASUREMENT RESULT: "TQ-0712-05_fin"

7/12/2016 12:54PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.360000	38.70	10.6	59	20.0	QP	L1	GND
0.675000	39.80	10.8	56	16.2	QP	L1	GND
1.135000	40.80	10.9	56	15.2	QP	L1	GND
2.340000	38.40	11.0	56	17.6	QP	L1	GND
5.870000	37.90	11.2	60	22.1	QP	L1	GND
13.255000	23.00	11.3	60	37.0	QP	L1	GND

MEASUREMENT RESULT: "TQ-0712-05_fin2"

7/12/2016 12:54PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.355000	29.40	10.6	49	19.4	AV	L1	GND
0.420000	36.90	10.7	47	10.5	AV	L1	GND
1.125000	30.10	10.9	46	15.9	AV	L1	GND
2.340000	28.10	11.0	46	17.9	AV	L1	GND
5.770000	24.70	11.2	50	25.3	AV	L1	GND
12.700000	15.00	11.3	50	35.0	AV	L1	GND

ACCURATE TECHNOLOGY CO., LTD


CONDUCTED EMISSION STANDARD FCC PART 15B

EUT: SPEAKER M/N:TQ-LT1504
 Manufacturer: TQL TRADING INC
 Operating Condition: TF CARD PLAYING
 Test Site: 1#Shielding Room
 Operator: DING
 Test Specification: L 220V/50Hz
 Comment: Report NO.:ATE20161336
 Start of Test: 7/12/2016 / 7:32:48PM

SCAN TABLE: "V 9K-30MHz fin"

Short Description: SUB STD VTERM2 1.70

Start Frequency	Stop Frequency	Step Width	Detector	Meas. Time	IF Bandw.	Transducer
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	NSLK8126 2008
Average						
150.0 kHz	30.0 MHz	5.0 kHz	QuasiPeak	1.0 s	9 kHz	NSLK8126 2008
Average						



MEASUREMENT RESULT: "TQ-0712-28_fin"

7/12/2016 7:44PM

Frequency MHz	Level dBuV	Transd dB	Limit dBuV	Margin dB	Detector	Line	PE
0.360000	35.50	10.6	59	23.2	QP	L1	GND
0.420000	42.70	10.7	57	14.7	QP	L1	GND
0.885000	35.10	10.8	56	20.9	QP	L1	GND
2.250000	33.60	11.0	56	22.4	QP	L1	GND
6.800000	33.00	11.2	60	27.0	QP	L1	GND
17.605000	26.70	11.4	60	33.3	QP	L1	GND

MEASUREMENT RESULT: "TQ-0712-28_fin2"

7/12/2016 7:44PM

Frequency MHz	Level dBuV	Transd dB	Limit dBuV	Margin dB	Detector	Line	PE
0.360000	26.20	10.6	49	22.5	AV	L1	GND
0.425000	34.50	10.7	47	12.8	AV	L1	GND
0.900000	24.50	10.8	46	21.5	AV	L1	GND
2.230000	24.50	11.0	46	21.5	AV	L1	GND
6.750000	22.50	11.2	50	27.5	AV	L1	GND
17.650000	18.20	11.4	50	31.8	AV	L1	GND

ACCURATE TECHNOLOGY CO., LTD


CONDUCTED EMISSION STANDARD FCC PART 15B

EUT: SPEAKER M/N:TQ-LT1504
 Manufacturer: TQL TRADING INC
 Operating Condition: TF CARD PLAYING
 Test Site: 1#Shielding Room
 Operator: DING
 Test Specification: N 220V/50Hz
 Comment: Report NO.:ATE20161336
 Start of Test: 7/12/2016 / 6:54:37PM

SCAN TABLE: "V 9K-30MHz fin"

Short Description: SUB STD VTERM2 1.70

Start Frequency	Stop Frequency	Step Width	Detector	Meas. Time	IF Bandw.	Transducer
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	NSLK8126 2008
150.0 kHz	30.0 MHz	5.0 kHz	Average	1.0 s	9 kHz	NSLK8126 2008



MEASUREMENT RESULT: "TQ-0712-27_fin"

7/12/2016 7:05PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.285000	36.70	10.6	61	24.0	QP	N	GND
0.425000	44.80	10.7	57	12.5	QP	N	GND
0.880000	38.30	10.8	56	17.7	QP	N	GND
2.180000	36.90	11.0	56	19.1	QP	N	GND
5.180000	34.80	11.2	60	25.2	QP	N	GND
15.205000	26.70	11.4	60	33.3	QP	N	GND

MEASUREMENT RESULT: "TQ-0712-27_fin2"

7/12/2016 7:05PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.360000	29.40	10.6	49	19.3	AV	N	GND
0.425000	37.10	10.7	47	10.2	AV	N	GND
1.085000	28.20	10.9	46	17.8	AV	N	GND
3.480000	24.20	11.1	46	21.8	AV	N	GND
5.170000	24.30	11.2	50	25.7	AV	N	GND
14.875000	18.00	11.4	50	32.0	AV	N	GND

Test mode 2

ACCURATE TECHNOLOGY CO., LTD


CONDUCTED EMISSION STANDARD FCC PART 15B

EUT: SPEAKER M/N:TQ-LT1504
Manufacturer: TQL TRADING INC
Operating Condition: SD CARD PLAYING
Test Site: 1#Shielding Room
Operator: DING
Test Specification: N 120V/60Hz
Comment: Report NO.:ATE20161336
Start of Test: 7/12/2016 / 12:39:27PM

SCAN TABLE: "V 9K-30MHz fin"

Short Description: SUB STD VTERM2 1.70

Start Frequency	Stop Frequency	Step Width	Detector	Meas. Time	IF Bandw.	Transducer
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	NSLK8126 2008
150.0 kHz	30.0 MHz	5.0 kHz	Average			
			QuasiPeak	1.0 s	9 kHz	NSLK8126 2008
			Average			



MEASUREMENT RESULT: "TQ-0712-03_fin"

7/12/2016 12:43PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.350000	36.10	10.6	59	22.9	QP	N	GND
0.430000	42.00	10.7	57	15.3	QP	N	GND
1.075000	36.50	10.9	56	19.5	QP	N	GND
2.360000	36.40	11.0	56	19.6	QP	N	GND
6.250000	34.80	11.2	60	25.2	QP	N	GND
13.180000	28.50	11.3	60	31.5	QP	N	GND

MEASUREMENT RESULT: "TQ-0712-03_fin2"

7/12/2016 12:43PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.350000	24.30	10.6	49	24.7	AV	N	GND
0.430000	30.60	10.7	47	16.7	AV	N	GND
1.430000	25.50	10.9	46	20.5	AV	N	GND
2.390000	25.20	11.0	46	20.8	AV	N	GND
6.250000	26.10	11.2	50	23.9	AV	N	GND
16.240000	19.40	11.4	50	30.6	AV	N	GND

ACCURATE TECHNOLOGY CO., LTD


CONDUCTED EMISSION STANDARD FCC PART 15B

EUT: SPEAKER M/N:TQ-LT1504
 Manufacturer: TQL TRADING INC
 Operating Condition: SD CARD PLAYING
 Test Site: 1#Shielding Room
 Operator: DING
 Test Specification: L 120V/60Hz
 Comment: Report NO.:ATE20161336
 Start of Test: 7/12/2016 / 12:44:49PM

SCAN TABLE: "V 9K-30MHz fin"

Short Description: SUB STD VTERM2 1.70

Start	Stop	Step	Detector	Meas. Time	IF Bandw.	Transducer
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	NSLK8126 2008
150.0 kHz	30.0 MHz	5.0 kHz	Average			
			QuasiPeak	1.0 s	9 kHz	NSLK8126 2008
			Average			



MEASUREMENT RESULT: "TQ-0712-04_fin"

7/12/2016 12:49PM

Frequency MHz	Level dBuV	Transd dB	Limit dBuV	Margin dB	Detector	Line	PE
0.250000	40.40	10.6	62	21.4	QP	L1	GND
0.430000	45.60	10.7	57	11.7	QP	L1	GND
1.045000	40.40	10.9	56	15.6	QP	L1	GND
2.380000	38.80	11.0	56	17.2	QP	L1	GND
5.840000	38.20	11.2	60	21.8	QP	L1	GND
12.655000	26.70	11.3	60	33.3	QP	L1	GND

MEASUREMENT RESULT: "TQ-0712-04_fin2"

7/12/2016 12:49PM

Frequency MHz	Level dBuV	Transd dB	Limit dBuV	Margin dB	Detector	Line	PE
0.350000	29.90	10.6	49	19.1	AV	L1	GND
0.425000	37.30	10.7	47	10.0	AV	L1	GND
1.090000	30.60	10.9	46	15.4	AV	L1	GND
2.300000	28.00	11.0	46	18.0	AV	L1	GND
6.810000	22.40	11.2	50	27.6	AV	L1	GND
17.020000	11.00	11.4	50	39.0	AV	L1	GND

ACCURATE TECHNOLOGY CO., LTD


CONDUCTED EMISSION STANDARD FCC PART 15B

EUT: SPEAKER M/N:TQ-LT1504
 Manufacturer: TQL TRADING INC
 Operating Condition: SD CARD PLAYING
 Test Site: 1#Shielding Room
 Operator: DING
 Test Specification: N 220V/50Hz
 Comment: Report NO.:ATE20161336
 Start of Test: 7/12/2016 / 7:50:01PM

SCAN TABLE: "V 9K-30MHz fin"

Short Description: SUB STD VTERM2 1.70

Start	Stop	Step	Detector	Meas. Time	IF Bandw.	Transducer
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	NSLK8126 2008
			Average			
150.0 kHz	30.0 MHz	5.0 kHz	QuasiPeak	1.0 s	9 kHz	NSLK8126 2008
			Average			



MEASUREMENT RESULT: "TQ-0712-30_fin"

7/12/2016 7:59PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.360000	37.40	10.6	59	21.3	QP	N	GND
0.425000	44.70	10.7	57	12.6	QP	N	GND
1.920000	35.00	11.0	56	21.0	QP	N	GND
4.560000	32.60	11.1	56	23.4	QP	N	GND
5.410000	36.30	11.2	60	23.7	QP	N	GND
14.050000	26.30	11.4	60	33.7	QP	N	GND

MEASUREMENT RESULT: "TQ-0712-30_fin2"

7/12/2016 7:59PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.360000	29.50	10.6	49	19.2	AV	N	GND
0.425000	37.40	10.7	47	9.9	AV	N	GND
1.075000	28.10	10.9	46	17.9	AV	N	GND
4.690000	25.20	11.1	46	20.8	AV	N	GND
5.370000	25.30	11.2	50	24.7	AV	N	GND
13.915000	18.00	11.4	50	32.0	AV	N	GND

ACCURATE TECHNOLOGY CO., LTD


CONDUCTED EMISSION STANDARD FCC PART 15B

EUT: SPEAKER M/N:TQ-LT1504
 Manufacturer: TQL TRADING INC
 Operating Condition: SD CARD PLAYING
 Test Site: 1#Shielding Room
 Operator: DING
 Test Specification: L 220V/50Hz
 Comment: Report NO.:ATE20161336
 Start of Test: 7/12/2016 / 7:45:10PM

SCAN TABLE: "V 9K-30MHz fin"

Short Description: SUB STD VTERM2 1.70

Start Frequency	Stop Frequency	Step Width	Detector	Meas. Time	IF Bandw.	Transducer
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	NSLK8126 2008
150.0 kHz	30.0 MHz	5.0 kHz	Average	1.0 s	9 kHz	NSLK8126 2008



MEASUREMENT RESULT: "TQ-0712-29_fin"

7/12/2016 7:49PM

Frequency MHz	Level dBuV	Transd dB	Limit dBuV	Margin dB	Detector	Line	PE
0.360000	35.60	10.6	59	23.1	QP	L1	GND
0.420000	42.80	10.7	57	14.6	QP	L1	GND
1.810000	35.00	11.0	56	21.0	QP	L1	GND
3.140000	32.10	11.1	56	23.9	QP	L1	GND
5.790000	34.10	11.2	60	25.9	QP	L1	GND
20.530000	25.90	11.4	60	34.1	QP	L1	GND

MEASUREMENT RESULT: "TQ-0712-29_fin2"

7/12/2016 7:49PM

Frequency MHz	Level dBuV	Transd dB	Limit dBuV	Margin dB	Detector	Line	PE
0.360000	26.20	10.6	49	22.5	AV	L1	GND
0.425000	34.40	10.7	47	12.9	AV	L1	GND
1.590000	22.20	10.9	46	23.8	AV	L1	GND
3.140000	22.60	11.1	46	23.4	AV	L1	GND
5.840000	24.10	11.2	50	25.9	AV	L1	GND
20.470000	17.90	11.4	50	32.1	AV	L1	GND

Test mode 3


ACCURATE TECHNOLOGY CO.,LTD

CONDUCTED EMISSION STANDARD FCC PART 15B

EUT: SPEAKER M/N:TQ-LT1504
 Manufacturer: TQL TRADING INC
 Operating Condition: AUDIO IN
 Test Site: 1#Shielding Room
 Operator: DING
 Test Specification: N 120V/60Hz
 Comment: Report NO.:ATE20161336
 Start of Test: 7/12/2016 / 1:18:10PM

SCAN TABLE: "V 9K-30MHz fin"

Short Description: SUB STD VTERM2 1.70
 Start Stop Step Detector Meas. IF Transducer
 Frequency Frequency Width Time Bandw.
 9.0 kHz 150.0 kHz 100.0 Hz QuasiPeak 1.0 s 200 Hz NSLK8126 2008
 Average
 150.0 kHz 30.0 MHz 5.0 kHz QuasiPeak 1.0 s 9 kHz NSLK8126 2008
 Average



MEASUREMENT RESULT: "TQ-0712-11_fin"

7/12/2016 1:22PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.355000	33.30	10.6	59	25.5	QP	N	GND
0.845000	37.80	10.8	56	18.2	QP	N	GND
1.270000	33.20	10.9	56	22.8	QP	N	GND
2.150000	33.00	11.0	56	23.0	QP	N	GND
5.960000	33.80	11.2	60	26.2	QP	N	GND
12.760000	23.70	11.3	60	36.3	QP	N	GND

MEASUREMENT RESULT: "TQ-0712-11_fin2"

7/12/2016 1:22PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.355000	22.70	10.6	49	26.1	AV	N	GND
0.425000	30.50	10.7	47	16.8	AV	N	GND
1.025000	23.50	10.8	46	22.5	AV	N	GND
2.760000	21.50	11.0	46	24.5	AV	N	GND
6.240000	21.90	11.2	50	28.1	AV	N	GND
12.640000	15.30	11.3	50	34.7	AV	N	GND

ACCURATE TECHNOLOGY CO., LTD


CONDUCTED EMISSION STANDARD FCC PART 15B

EUT: SPEAKER M/N:TQ-LT1504
 Manufacturer: TQL TRADING INC
 Operating Condition: AUDIO IN
 Test Site: 1#Shielding Room
 Operator: DING
 Test Specification: L 120V/60Hz
 Comment: Report NO.:ATE20161336
 Start of Test: 7/12/2016 / 1:22:53PM

SCAN TABLE: "V 9K-30MHz fin"

Short Description: SUB STD VTERM2 1.70

Start Frequency	Stop Frequency	Step Width	Detector	Meas. Time	IF Bandw.	Transducer
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	NSLK8126 2008
150.0 kHz	30.0 MHz	5.0 kHz	Average	1.0 s	9 kHz	NSLK8126 2008



MEASUREMENT RESULT: "TQ-0712-12_fin"

7/12/2016 1:27PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.335000	39.30	10.6	59	20.0	QP	L1	GND
0.420000	47.40	10.7	57	10.0	QP	L1	GND
1.130000	40.70	10.9	56	15.3	QP	L1	GND
3.230000	36.80	11.1	56	19.2	QP	L1	GND
5.880000	37.70	11.2	60	22.3	QP	L1	GND
12.715000	26.10	11.3	60	33.9	QP	L1	GND

MEASUREMENT RESULT: "TQ-0712-12_fin2"

7/12/2016 1:27PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.360000	29.60	10.6	49	19.1	AV	L1	GND
0.425000	36.90	10.7	47	10.4	AV	L1	GND
1.070000	30.30	10.9	46	15.7	AV	L1	GND
3.230000	26.50	11.1	46	19.5	AV	L1	GND
5.780000	25.00	11.2	50	25.0	AV	L1	GND
12.655000	15.20	11.3	50	34.8	AV	L1	GND

ACCURATE TECHNOLOGY CO., LTD


CONDUCTED EMISSION STANDARD FCC PART 15B

EUT: SPEAKER M/N:TQ-LT1504
 Manufacturer: TQL TRADING INC
 Operating Condition: AUDIO IN
 Test Site: 1#Shielding Room
 Operator: DING
 Test Specification: N 220V/50Hz
 Comment: Report NO.:ATE20161336
 Start of Test: 7/12/2016 / 5:59:42PM

SCAN TABLE: "V 9K-30MHz fin"

Short Description: SUB STD VTERM2 1.70

Start Frequency	Stop Frequency	Step Width	Detector	Meas. Time	IF Bandw.	Transducer
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	NSLK8126 2008
150.0 kHz	30.0 MHz	5.0 kHz	Average	1.0 s	9 kHz	NSLK8126 2008



MEASUREMENT RESULT: "TQ-0712-22_fin"

7/12/2016 6:03PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.360000	37.40	10.6	59	21.3	QP	N	GND
0.425000	44.60	10.7	57	12.7	QP	N	GND
0.880000	38.30	10.8	56	17.7	QP	N	GND
2.170000	36.80	11.0	56	19.2	QP	N	GND
6.090000	35.50	11.2	60	24.5	QP	N	GND
15.130000	25.60	11.4	60	34.4	QP	N	GND

MEASUREMENT RESULT: "TQ-0712-22_fin2"

7/12/2016 6:03PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.360000	29.30	10.6	49	19.4	AV	N	GND
0.425000	37.00	10.7	47	10.3	AV	N	GND
1.435000	28.40	10.9	46	17.6	AV	N	GND
2.230000	27.60	11.0	46	18.4	AV	N	GND
5.980000	26.10	11.2	50	23.9	AV	N	GND
15.085000	17.90	11.4	50	32.1	AV	N	GND

ACCURATE TECHNOLOGY CO., LTD


CONDUCTED EMISSION STANDARD FCC PART 15B

EUT: SPEAKER M/N:TQ-LT1504
 Manufacturer: TQL TRADING INC
 Operating Condition: AUDIO IN
 Test Site: 1#Shielding Room
 Operator: DING
 Test Specification: L 220V/50Hz
 Comment: Report NO.:ATE20161336
 Start of Test: 7/12/2016 / 5:49:49PM

SCAN TABLE: "V 9K-30MHz fin"

Short Description: SUB STD VTERM2 1.70

Start Frequency	Stop Frequency	Step Width	Detector	Meas. Time	IF Bandw.	Transducer
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	NSLK8126 2008
150.0 kHz	30.0 MHz	5.0 kHz	Average	1.0 s	9 kHz	NSLK8126 2008



MEASUREMENT RESULT: "TQ-0712-21_fin"

7/12/2016 5:59PM

Frequency MHz	Level dBuV	Transd dB	Limit dBuV	Margin dB	Detector	Line	PE
0.360000	35.40	10.6	59	23.3	QP	L1	GND
0.425000	42.70	10.7	57	14.6	QP	L1	GND
0.880000	35.40	10.8	56	20.6	QP	L1	GND
2.600000	33.20	11.0	56	22.8	QP	L1	GND
5.350000	34.60	11.2	60	25.4	QP	L1	GND
15.460000	26.10	11.4	60	33.9	QP	L1	GND

MEASUREMENT RESULT: "TQ-0712-21_fin2"

7/12/2016 5:59PM

Frequency MHz	Level dBuV	Transd dB	Limit dBuV	Margin dB	Detector	Line	PE
0.360000	26.80	10.6	49	21.9	AV	L1	GND
0.425000	34.60	10.7	47	12.7	AV	L1	GND
1.875000	24.50	11.0	46	21.5	AV	L1	GND
2.600000	24.50	11.0	46	21.5	AV	L1	GND
5.300000	23.80	11.2	50	26.2	AV	L1	GND
18.025000	18.80	11.4	50	31.2	AV	L1	GND

Test mode 4

ACCURATE TECHNOLOGY CO.,LTD


CONDUCTED EMISSION STANDARD FCC PART 15B

EUT: SPEAKER M/N:TQ-LT1504
 Manufacturer: TQL TRADING INC
 Operating Condition: 202.2MHz RX
 Test Site: 1#Shielding Room
 Operator: DING
 Test Specification: N 120V/60Hz
 Comment: Report NO.:ATE20161336
 Start of Test: 7/12/2016 / 1:13:28PM

SCAN TABLE: "V 9K-30MHz fin"

Short Description: SUB STD VTERM2 1.70

Start	Stop	Step	Detector	Meas. Time	IF Bandw.	Transducer
Frequency 9.0 kHz	Frequency 150.0 kHz	Width 100.0 Hz	QuasiPeak	1.0 s	200 Hz	NSLK8126 2008
			Average			
150.0 kHz	30.0 MHz	5.0 kHz	QuasiPeak	1.0 s	9 kHz	NSLK8126 2008
			Average			



MEASUREMENT RESULT: "TQ-0712-10_fin"

7/12/2016 1:17PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.350000	33.50	10.6	59	25.5	QP	N	GND
0.845000	37.60	10.8	56	18.4	QP	N	GND
1.265000	33.30	10.9	56	22.7	QP	N	GND
2.150000	32.90	11.0	56	23.1	QP	N	GND
5.880000	33.60	11.2	60	26.4	QP	N	GND
12.790000	23.70	11.3	60	36.3	QP	N	GND

MEASUREMENT RESULT: "TQ-0712-10_fin2"

7/12/2016 1:17PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.350000	24.90	10.6	49	24.1	AV	N	GND
0.420000	30.60	10.7	47	16.8	AV	N	GND
1.390000	21.40	10.9	46	24.6	AV	N	GND
3.190000	21.10	11.1	46	24.9	AV	N	GND
5.860000	23.90	11.2	50	26.1	AV	N	GND
12.670000	15.40	11.3	50	34.6	AV	N	GND

ACCURATE TECHNOLOGY CO., LTD


CONDUCTED EMISSION STANDARD FCC PART 15B

EUT: SPEAKER M/N:TQ-LT1504
 Manufacturer: TQL TRADING INC
 Operating Condition: 202.2MHz RX
 Test Site: 1#Shielding Room
 Operator: DING
 Test Specification: L 120V/60Hz
 Comment: Report NO.:ATE20161336
 Start of Test: 7/12/2016 / 1:08:47PM

SCAN TABLE: "V 9K-30MHz fin"

Short Description: SUB STD VTERM2 1.70

Start Frequency	Stop Frequency	Step Width	Detector	Meas. Time	IF Bandw.	Transducer
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	NSLK8126 2008
150.0 kHz	30.0 MHz	5.0 kHz	Average	1.0 s	9 kHz	NSLK8126 2008
			Average			



MEASUREMENT RESULT: "TQ-0712-09_fin"

7/12/2016 1:12PM

Frequency MHz	Level dBuV	Transd dB	Limit dBuV	Margin dB	Detector	Line	PE
0.355000	39.30	10.6	59	19.5	QP	L1	GND
0.420000	47.50	10.7	57	9.9	QP	L1	GND
1.535000	40.70	10.9	56	15.3	QP	L1	GND
2.310000	38.00	11.0	56	18.0	QP	L1	GND
5.400000	37.20	11.2	60	22.8	QP	L1	GND
13.180000	25.30	11.3	60	34.7	QP	L1	GND

MEASUREMENT RESULT: "TQ-0712-09_fin2"

7/12/2016 1:12PM

Frequency MHz	Level dBuV	Transd dB	Limit dBuV	Margin dB	Detector	Line	PE
0.355000	29.40	10.6	49	19.4	AV	L1	GND
0.420000	37.00	10.7	47	10.4	AV	L1	GND
1.065000	30.20	10.9	46	15.8	AV	L1	GND
2.380000	28.40	11.0	46	17.6	AV	L1	GND
5.310000	24.40	11.2	50	25.6	AV	L1	GND
13.060000	14.70	11.3	50	35.3	AV	L1	GND

ACCURATE TECHNOLOGY CO., LTD


CONDUCTED EMISSION STANDARD FCC PART 15B

EUT: SPEAKER M/N:TQ-LT1504
Manufacturer: TQL TRADING INC
Operating Condition: 202.2MHz RX
Test Site: 1#Shielding Room
Operator: DING
Test Specification: L 220V/50Hz
Comment: Report NO.:ATE20161336
Start of Test: 7/12/2016 / 6:13:36PM

SCAN TABLE: "V 9K-30MHz fin"

Short Description: SUB STD VTERM2 1.70

Start	Stop	Step	Detector	Meas. Time	IF Bandw.	Transducer
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	NSLK8126 2008
Average						
150.0 kHz	30.0 MHz	5.0 kHz	QuasiPeak	1.0 s	9 kHz	NSLK8126 2008
Average						



MEASUREMENT RESULT: "TQ-0712-24_fin"

7/12/2016 6:25PM

Frequency MHz	Level dBuV	Transd dB	Limit dBuV	Margin dB	Detector	Line	PE
0.360000	35.50	10.6	59	23.2	QP	L1	GND
0.415000	41.80	10.7	58	15.7	QP	L1	GND
0.890000	34.70	10.8	56	21.3	QP	L1	GND
2.470000	32.70	11.0	56	23.3	QP	L1	GND
5.830000	33.60	11.2	60	26.4	QP	L1	GND
17.620000	26.70	11.4	60	33.3	QP	L1	GND

MEASUREMENT RESULT: "TQ-0712-24_fin2"

7/12/2016 6:25PM

Frequency MHz	Level dBuV	Transd dB	Limit dBuV	Margin dB	Detector	Line	PE
0.360000	26.30	10.6	49	22.4	AV	L1	GND
0.425000	34.40	10.7	47	12.9	AV	L1	GND
1.060000	24.30	10.9	46	21.7	AV	L1	GND
2.440000	24.00	11.0	46	22.0	AV	L1	GND
7.130000	22.50	11.2	50	27.5	AV	L1	GND
17.740000	18.40	11.4	50	31.6	AV	L1	GND

ACCURATE TECHNOLOGY CO., LTD


CONDUCTED EMISSION STANDARD FCC PART 15B

EUT: SPEAKER M/N:TQ-LT1504
 Manufacturer: TQL TRADING INC
 Operating Condition: 202.2MHz RX
 Test Site: 1#Shielding Room
 Operator: DING
 Test Specification: N 220V/50Hz
 Comment: Report NO.:ATE20161336
 Start of Test: 7/12/2016 / 6:03:46PM

SCAN TABLE: "V 9K-30MHz fin"

Short Description: SUB STD VTERM2 1.70

Start Frequency	Stop Frequency	Step Width	Detector	Meas. Time	IF Bandw.	Transducer
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	NSLK8126 2008
150.0 kHz	30.0 MHz	5.0 kHz	Average	1.0 s	9 kHz	NSLK8126 2008



MEASUREMENT RESULT: "TQ-0712-23_fin"

7/12/2016 6:13PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.360000	37.40	10.6	59	21.3	QP	N	GND
0.425000	44.60	10.7	57	12.7	QP	N	GND
0.880000	38.40	10.8	56	17.6	QP	N	GND
2.180000	36.90	11.0	56	19.1	QP	N	GND
6.170000	34.70	11.2	60	25.3	QP	N	GND
16.810000	26.80	11.4	60	33.2	QP	N	GND

MEASUREMENT RESULT: "TQ-0712-23_fin2"

7/12/2016 6:13PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.360000	29.50	10.6	49	19.2	AV	N	GND
0.425000	37.20	10.7	47	10.1	AV	N	GND
1.055000	30.10	10.9	46	15.9	AV	N	GND
3.350000	26.40	11.1	46	19.6	AV	N	GND
6.130000	26.00	11.2	50	24.0	AV	N	GND
18.130000	18.00	11.4	50	32.0	AV	N	GND

Test mode 5

ACCURATE TECHNOLOGY CO., LTD


CONDUCTED EMISSION STANDARD FCC PART 15B

EUT: SPEAKER M/N:TQ-LT1504
 Manufacturer: TQL TRADING INC
 Operating Condition: USB PLAYING
 Test Site: 1#Shielding Room
 Operator: DING
 Test Specification: L 120V/60Hz
 Comment: Report NO.:ATE20161336
 Start of Test: 7/12/2016 / 10:42:13AM

SCAN TABLE: "V 9K-30MHz fin"

Short Description: SUB STD VTERM2 1.70

Start Frequency	Stop Frequency	Step Width	Detector	Meas. Time	IF Bandw.	Transducer
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	NSLK8126 2008
150.0 kHz	30.0 MHz	5.0 kHz	Average			
			QuasiPeak	1.0 s	9 kHz	NSLK8126 2008
			Average			



MEASUREMENT RESULT: "TQ-0712-01_fin"

7/12/2016 10:43AM

Frequency MHz	Level dBuV	Transd dB	Limit dBuV	Margin dB	Detector	Line	PE
0.350000	38.20	10.6	59	20.8	QP	L1	GND
0.425000	44.30	10.7	57	13.0	QP	L1	GND
1.545000	37.80	10.9	56	18.2	QP	L1	GND
2.730000	36.10	11.0	56	19.9	QP	L1	GND
5.790000	36.90	11.2	60	23.1	QP	L1	GND
12.640000	26.80	11.3	60	33.2	QP	L1	GND

MEASUREMENT RESULT: "TQ-0712-01_fin2"

7/12/2016 10:43AM

Frequency MHz	Level dBuV	Transd dB	Limit dBuV	Margin dB	Detector	Line	PE
0.345000	27.00	10.6	49	22.1	AV	L1	GND
0.420000	35.00	10.7	47	12.4	AV	L1	GND
1.860000	25.70	11.0	46	20.3	AV	L1	GND
4.400000	23.60	11.1	46	22.4	AV	L1	GND
5.860000	24.90	11.2	50	25.1	AV	L1	GND
12.910000	21.50	11.3	50	28.5	AV	L1	GND


ACCURATE TECHNOLOGY CO., LTD

CONDUCTED EMISSION STANDARD FCC PART 15B

EUT: SPEAKER M/N:TQ-LT1504
 Manufacturer: TQL TRADING INC
 Operating Condition: USB PLAYING
 Test Site: 1#Shielding Room
 Operator: DING
 Test Specification: N 120V/60Hz
 Comment: Report NO.:ATE20161336
 Start of Test: 7/12/2016 / 12:34:27PM

SCAN TABLE: "V 9K-30MHz fin"

Short Description: SUB STD VTERM2 1.70
 Start Stop Step Detector Meas. IF Transducer
 Frequency Frequency Width Time Bandw.
 9.0 kHz 150.0 kHz 100.0 Hz QuasiPeak 1.0 s 200 Hz NSLK8126 2008
 Average
 150.0 kHz 30.0 MHz 5.0 kHz QuasiPeak 1.0 s 9 kHz NSLK8126 2008
 Average



MEASUREMENT RESULT: "TQ-0712-02_fin"

7/12/2016 12:38PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.335000	35.80	10.6	59	23.5	QP	N	GND
0.420000	42.10	10.7	57	15.3	QP	N	GND
1.940000	36.10	11.0	56	19.9	QP	N	GND
2.360000	35.00	11.0	56	21.0	QP	N	GND
5.830000	36.20	11.2	60	23.8	QP	N	GND
12.745000	28.40	11.3	60	31.6	QP	N	GND

MEASUREMENT RESULT: "TQ-0712-02_fin2"

7/12/2016 12:38PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.355000	23.80	10.6	49	25.0	AV	N	GND
0.430000	31.30	10.7	47	16.0	AV	N	GND
1.135000	27.50	10.9	46	18.5	AV	N	GND
2.820000	26.90	11.0	46	19.1	AV	N	GND
5.880000	28.60	11.2	50	21.4	AV	N	GND
17.605000	20.00	11.4	50	30.0	AV	N	GND

ACCURATE TECHNOLOGY CO., LTD


CONDUCTED EMISSION STANDARD FCC PART 15B

EUT: SPEAKER M/N:TQ-LT1504
 Manufacturer: TQL TRADING INC
 Operating Condition: USB PLAYING
 Test Site: 1#Shielding Room
 Operator: DING
 Test Specification: L 220V/50Hz
 Comment: Report NO.:ATE20161336
 Start of Test: 7/12/2016 / 8:09:21PM

SCAN TABLE: "V 9K-30MHz fin"

Short Description: SUB STD VTERM2 1.70

Start Frequency	Stop Frequency	Step Width	Detector	Meas. Time	IF Bandw.	Transducer
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	NSLK8126 2008
150.0 kHz	30.0 MHz	5.0 kHz	Average	1.0 s	9 kHz	NSLK8126 2008



MEASUREMENT RESULT: "TQ-0712-32_fin"

7/12/2016 8:14PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.360000	35.70	10.6	59	23.0	QP	L1	GND
0.420000	42.90	10.7	57	14.5	QP	L1	GND
1.680000	33.30	10.9	56	22.7	QP	L1	GND
2.400000	33.00	11.0	56	23.0	QP	L1	GND
6.020000	33.80	11.2	60	26.2	QP	L1	GND
21.325000	25.40	11.4	60	34.6	QP	L1	GND

MEASUREMENT RESULT: "TQ-0712-32_fin2"

7/12/2016 8:14PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.360000	26.20	10.6	49	22.5	AV	L1	GND
0.425000	34.60	10.7	47	12.7	AV	L1	GND
1.655000	24.90	10.9	46	21.1	AV	L1	GND
4.360000	21.90	11.1	46	24.1	AV	L1	GND
6.160000	23.20	11.2	50	26.8	AV	L1	GND
17.605000	18.20	11.4	50	31.8	AV	L1	GND

ACCURATE TECHNOLOGY CO., LTD


CONDUCTED EMISSION STANDARD FCC PART 15B

EUT: SPEAKER M/N:TQ-LT1504
 Manufacturer: TQL TRADING INC
 Operating Condition: USB PLAYING
 Test Site: 1#Shielding Room
 Operator: DING
 Test Specification: N 220V/50Hz
 Comment: Report NO.:ATE20161336
 Start of Test: 7/12/2016 / 8:00:23PM

SCAN TABLE: "V 9K-30MHz fin"

Short Description: SUB STD VTERM2 1.70

Start Frequency	Stop Frequency	Step Width	Detector	Meas. Time	IF Bandw.	Transducer
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	NSLK8126 2008
Average						
150.0 kHz	30.0 MHz	5.0 kHz	QuasiPeak	1.0 s	9 kHz	NSLK8126 2008
Average						



MEASUREMENT RESULT: "TQ-0712-31_fin"

7/12/2016 8:08PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.360000	37.60	10.6	59	21.1	QP	N	GND
0.425000	44.70	10.7	57	12.6	QP	N	GND
1.145000	35.10	10.9	56	20.9	QP	N	GND
2.550000	35.90	11.0	56	20.1	QP	N	GND
7.520000	33.30	11.2	60	26.7	QP	N	GND
18.145000	26.30	11.4	60	33.7	QP	N	GND

MEASUREMENT RESULT: "TQ-0712-31_fin2"

7/12/2016 8:08PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.360000	29.40	10.6	49	19.3	AV	N	GND
0.425000	36.90	10.7	47	10.4	AV	N	GND
1.620000	27.90	10.9	46	18.1	AV	N	GND
2.550000	25.20	11.0	46	20.8	AV	N	GND
7.670000	23.80	11.2	50	26.2	AV	N	GND
18.100000	18.00	11.4	50	32.0	AV	N	GND

Test mode 6

ACCURATE TECHNOLOGY CO.,LTD


CONDUCTED EMISSION STANDARD FCC PART 15B

EUT: SPEAKER M/N:TQ-LT1504
 Manufacturer: TQL TRADING INC
 Operating Condition: FM
 Test Site: 1#Shielding Room
 Operator: DING
 Test Specification: L 120V/60Hz
 Comment: Report NO.:ATE20161336
 Start of Test: 7/12/2016 / 1:04:09PM

SCAN TABLE: "V 9K-30MHz fin"

Short Description: SUB STD VTERM2 1.70

Start	Stop	Step	Detector	Meas. Time	IF Bandw.	Transducer
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	NSLK8126 2008
150.0 kHz	30.0 MHz	5.0 kHz	Average			
			QuasiPeak	1.0 s	9 kHz	NSLK8126 2008
			Average			



MEASUREMENT RESULT: "TQ-0712-08_fin"

7/12/2016 1:08PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.360000	38.80	10.6	59	19.9	QP	L1	GND
0.425000	47.30	10.7	57	10.0	QP	L1	GND
1.090000	40.70	10.9	56	15.3	QP	L1	GND
2.390000	39.40	11.0	56	16.6	QP	L1	GND
5.910000	37.70	11.2	60	22.3	QP	L1	GND
12.790000	24.60	11.3	60	35.4	QP	L1	GND

MEASUREMENT RESULT: "TQ-0712-08_fin2"

7/12/2016 1:08PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.345000	29.90	10.6	49	19.2	AV	L1	GND
0.420000	37.10	10.7	47	10.3	AV	L1	GND
1.115000	32.10	10.9	46	13.9	AV	L1	GND
2.360000	28.50	11.0	46	17.5	AV	L1	GND
5.850000	25.00	11.2	50	25.0	AV	L1	GND
12.670000	15.00	11.3	50	35.0	AV	L1	GND


ACCURATE TECHNOLOGY CO., LTD

CONDUCTED EMISSION STANDARD FCC PART 15B

EUT: SPEAKER M/N:TQ-LT1504
 Manufacturer: TQL TRADING INC
 Operating Condition: FM
 Test Site: 1#Shielding Room
 Operator: DING
 Test Specification: N 120V/60Hz
 Comment: Report NO.:ATE20161336
 Start of Test: 7/12/2016 / 12:59:30PM

SCAN TABLE: "V 9K-30MHz fin"

Short Description: SUB STD VTERM2 1.70
 Start Stop Step Detector Meas. IF Transducer
 Frequency Frequency Width Time Bandw.
 9.0 kHz 150.0 kHz 100.0 Hz QuasiPeak 1.0 s 200 Hz NSLK8126 2008
 Average
 150.0 kHz 30.0 MHz 5.0 kHz QuasiPeak 1.0 s 9 kHz NSLK8126 2008
 Average



MEASUREMENT RESULT: "TQ-0712-07_fin"

7/12/2016 1:03PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.345000	33.40	10.6	59	25.7	QP	N	GND
0.850000	38.00	10.8	56	18.0	QP	N	GND
0.940000	33.70	10.8	56	22.3	QP	N	GND
2.130000	33.00	11.0	56	23.0	QP	N	GND
5.930000	34.30	11.2	60	25.7	QP	N	GND
12.790000	23.30	11.3	60	36.7	QP	N	GND

MEASUREMENT RESULT: "TQ-0712-07_fin2"

7/12/2016 1:03PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.350000	23.10	10.6	49	25.9	AV	N	GND
0.425000	31.80	10.7	47	15.5	AV	N	GND
1.050000	23.70	10.9	46	22.3	AV	N	GND
2.370000	22.30	11.0	46	23.7	AV	N	GND
7.270000	21.10	11.2	50	28.9	AV	N	GND
12.640000	15.20	11.3	50	34.8	AV	N	GND

ACCURATE TECHNOLOGY CO.,LTD


CONDUCTED EMISSION STANDARD FCC PART 15B

EUT: SPEAKER M/N:TQ-LT1504
 Manufacturer: TQL TRADING INC
 Operating Condition: FM
 Test Site: 1#Shielding Room
 Operator: DING
 Test Specification: N 220V/50Hz
 Comment: Report NO.:ATE20161336
 Start of Test: 7/12/2016 / 6:49:01PM

SCAN TABLE: "V 9K-30MHz fin"

Short Description: SUB STD VTERM2 1.70

Start Frequency	Stop Frequency	Step Width	Detector	Meas. Time	IF Bandw.	Transducer
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	NSLK8126 2008
150.0 kHz	30.0 MHz	5.0 kHz	Average	1.0 s	9 kHz	NSLK8126 2008



MEASUREMENT RESULT: "TQ-0712-26_fin"

7/12/2016 6:54PM

Frequency MHz	Level dBuV	Transd dB	Limit dBuV	Margin dB	Detector	Line	PE
0.360000	37.50	10.6	59	21.2	QP	N	GND
0.425000	44.70	10.7	57	12.6	QP	N	GND
1.575000	36.10	10.9	56	19.9	QP	N	GND
2.180000	36.80	11.0	56	19.2	QP	N	GND
5.880000	36.30	11.2	60	23.7	QP	N	GND
12.805000	25.80	11.3	60	34.2	QP	N	GND

MEASUREMENT RESULT: "TQ-0712-26_fin2"

7/12/2016 6:54PM

Frequency MHz	Level dBuV	Transd dB	Limit dBuV	Margin dB	Detector	Line	PE
0.360000	29.50	10.6	49	19.2	AV	N	GND
0.425000	37.00	10.7	47	10.3	AV	N	GND
1.610000	27.00	10.9	46	19.0	AV	N	GND
3.720000	25.50	11.1	46	20.5	AV	N	GND
5.500000	26.50	11.2	50	23.5	AV	N	GND
12.850000	18.70	11.3	50	31.3	AV	N	GND

ACCURATE TECHNOLOGY CO., LTD


CONDUCTED EMISSION STANDARD FCC PART 15B

EUT: SPEAKER M/N:TQ-LT1504
 Manufacturer: TQL TRADING INC
 Operating Condition: FM
 Test Site: 1#Shielding Room
 Operator: DING
 Test Specification: L 220V/50Hz
 Comment: Report NO.:ATE20161336
 Start of Test: 7/12/2016 / 6:26:21PM

SCAN TABLE: "V 9K-30MHz fin"

Short Description: SUB STD VTERM2 1.70

Start Frequency	Stop Frequency	Step Width	Detector	Meas. Time	IF Bandw.	Transducer
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	NSLK8126 2008
150.0 kHz	30.0 MHz	5.0 kHz	Average	1.0 s	9 kHz	NSLK8126 2008



MEASUREMENT RESULT: "TQ-0712-25_fin"

7/12/2016 6:47PM

Frequency MHz	Level dBuV	Transd dB	Limit dBuV	Margin dB	Detector	Line	PE
0.360000	35.50	10.6	59	23.2	QP	L1	GND
0.420000	42.80	10.7	57	14.6	QP	L1	GND
1.560000	32.50	10.9	56	23.5	QP	L1	GND
2.620000	33.20	11.0	56	22.8	QP	L1	GND
5.820000	33.70	11.2	60	26.3	QP	L1	GND
19.975000	26.30	11.4	60	33.7	QP	L1	GND

MEASUREMENT RESULT: "TQ-0712-25_fin2"

7/12/2016 6:47PM

Frequency MHz	Level dBuV	Transd dB	Limit dBuV	Margin dB	Detector	Line	PE
0.360000	26.10	10.6	49	22.6	AV	L1	GND
0.425000	34.40	10.7	47	12.9	AV	L1	GND
1.825000	24.30	11.0	46	21.7	AV	L1	GND
3.610000	22.20	11.1	46	23.8	AV	L1	GND
7.680000	21.80	11.2	50	28.2	AV	L1	GND
19.885000	18.10	11.4	50	31.9	AV	L1	GND

Test mode 7


ACCURATE TECHNOLOGY CO., LTD

CONDUCTED EMISSION STANDARD FCC PART 15B

EUT: SPEAKER M/N:TQ-LT1504
 Manufacturer: TQL TRADING INC
 Operating Condition: GT IN
 Test Site: 1#Shielding Room
 Operator: DING
 Test Specification: L 120V/60Hz
 Comment: Report NO.:ATE20161336
 Start of Test: 7/12/2016 / 1:31:28PM

SCAN TABLE: "V 9K-30MHz fin"

Short Description: SUB STD VTERM2 1.70
 Start Stop Step Detector Meas. IF Transducer
 Frequency Frequency Width Time Bandw.
 9.0 kHz 150.0 kHz 100.0 Hz QuasiPeak 1.0 s 200 Hz NSLK8126 2008
 150.0 kHz 30.0 MHz 5.0 kHz Average
 QuasiPeak 1.0 s 9 kHz NSLK8126 2008
 Average



MEASUREMENT RESULT: "TQ-0712-103_fin"

7/12/2016 1:36PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.255000	40.30	10.6	62	21.3	QP	L1	GND
0.425000	47.30	10.7	57	10.0	QP	L1	GND
1.100000	40.50	10.9	56	15.5	QP	L1	GND
2.790000	38.80	11.0	56	17.2	QP	L1	GND
5.790000	37.90	11.2	60	22.1	QP	L1	GND
12.640000	23.20	11.3	60	36.8	QP	L1	GND

MEASUREMENT RESULT: "TQ-0712-103_fin2"

7/12/2016 1:36PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.350000	29.50	10.6	49	19.5	AV	L1	GND
0.420000	37.00	10.7	47	10.4	AV	L1	GND
1.015000	29.70	10.8	46	16.3	AV	L1	GND
2.390000	28.00	11.0	46	18.0	AV	L1	GND
5.700000	25.00	11.2	50	25.0	AV	L1	GND
12.940000	14.70	11.3	50	35.3	AV	L1	GND


ACCURATE TECHNOLOGY CO., LTD

CONDUCTED EMISSION STANDARD FCC PART 15B

EUT: SPEAKER M/N:TQ-LT1504
 Manufacturer: TQL TRADING INC
 Operating Condition: GT IN
 Test Site: 1#Shielding Room
 Operator: DING
 Test Specification: N 120V/60Hz
 Comment: Report NO.:ATE20161336
 Start of Test: 7/12/2016 / 1:36:30PM

SCAN TABLE: "V 9K-30MHz fin"

Short Description: SUB STD VTERM2 1.70
 Start Stop Step Detector Meas. IF Transducer
 Frequency Frequency Width Time Bandw.
 9.0 kHz 150.0 kHz 100.0 Hz QuasiPeak 1.0 s 200 Hz NSLK8126 2008
 Average
 150.0 kHz 30.0 MHz 5.0 kHz QuasiPeak 1.0 s 9 kHz NSLK8126 2008
 Average



MEASUREMENT RESULT: "TQ-0712-14_fin"

7/12/2016 2:01PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.360000	33.20	10.6	59	25.5	QP	N	GND
0.850000	38.70	10.8	56	17.3	QP	N	GND
1.770000	32.70	11.0	56	23.3	QP	N	GND
2.150000	34.20	11.0	56	21.8	QP	N	GND
5.880000	33.90	11.2	60	26.1	QP	N	GND
13.015000	24.20	11.3	60	35.8	QP	N	GND

MEASUREMENT RESULT: "TQ-0712-14_fin2"

7/12/2016 2:01PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.355000	22.70	10.6	49	26.1	AV	N	GND
0.425000	30.60	10.7	47	16.7	AV	N	GND
1.480000	24.90	10.9	46	21.1	AV	N	GND
4.010000	21.20	11.1	46	24.8	AV	N	GND
5.770000	24.20	11.2	50	25.8	AV	N	GND
13.330000	14.80	11.3	50	35.2	AV	N	GND


ACCURATE TECHNOLOGY CO., LTD

CONDUCTED EMISSION STANDARD FCC PART 15B

EUT: SPEAKER M/N:TQ-LT1504
Manufacturer: TQL TRADING INC
Operating Condition: GT IN
Test Site: 1#Shielding Room
Operator: DING
Test Specification: L 220V/50Hz
Comment: Report NO.:ATE20161336
Start of Test: 7/12/2016 / 5:43:14PM

SCAN TABLE: "V 9K-30MHz fin"

Short Description: SUB STD VTERM2 1.70
Start Stop Step Detector Meas. IF Transducer
Frequency Frequency Width Time Bandw.
9.0 kHz 150.0 kHz 100.0 Hz QuasiPeak 1.0 s 200 Hz NSLK8126 2008
Average
150.0 kHz 30.0 MHz 5.0 kHz QuasiPeak 1.0 s 9 kHz NSLK8126 2008
Average



MEASUREMENT RESULT: "TQ-0712-20_fin"

7/12/2016 5:48PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.360000	35.40	10.6	59	23.3	QP	L1	GND
0.425000	42.70	10.7	57	14.6	QP	L1	GND
1.270000	34.10	10.9	56	21.9	QP	L1	GND
2.850000	32.60	11.0	56	23.4	QP	L1	GND
6.020000	33.70	11.2	60	26.3	QP	L1	GND
20.335000	26.70	11.4	60	33.3	QP	L1	GND

MEASUREMENT RESULT: "TQ-0712-20_fin2"

7/12/2016 5:48PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.360000	26.00	10.6	49	22.7	AV	L1	GND
0.425000	34.30	10.7	47	13.0	AV	L1	GND
1.270000	24.10	10.9	46	21.9	AV	L1	GND
2.810000	26.40	11.0	46	19.6	AV	L1	GND
6.360000	25.70	11.2	50	24.3	AV	L1	GND
18.985000	18.40	11.4	50	31.6	AV	L1	GND

ACCURATE TECHNOLOGY CO., LTD


CONDUCTED EMISSION STANDARD FCC PART 15B

EUT: SPEAKER M/N:TQ-LT1504
 Manufacturer: TQL TRADING INC
 Operating Condition: GT IN
 Test Site: 1#Shielding Room
 Operator: DING
 Test Specification: N 220V/50Hz
 Comment: Report NO.:ATE20161336
 Start of Test: 7/12/2016 / 5:35:02PM

SCAN TABLE: "V 9K-30MHz fin"

Short Description: SUB STD VTERM2 1.70

Start Frequency	Stop Frequency	Step Width	Detector	Meas. Time	IF Bandw.	Transducer
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	NSLK8126 2008
150.0 kHz	30.0 MHz	5.0 kHz	Average	1.0 s	9 kHz	NSLK8126 2008



MEASUREMENT RESULT: "TQ-0712-19_fin"

7/12/2016 5:42PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.360000	37.20	10.6	59	21.5	QP	N	GND
0.430000	44.20	10.7	57	13.1	QP	N	GND
0.880000	38.30	10.8	56	17.7	QP	N	GND
2.180000	36.80	11.0	56	19.2	QP	N	GND
6.340000	33.30	11.2	60	26.7	QP	N	GND
17.110000	25.80	11.4	60	34.2	QP	N	GND

MEASUREMENT RESULT: "TQ-0712-19_fin2"

7/12/2016 5:42PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.360000	30.50	10.6	49	18.2	AV	N	GND
0.425000	37.00	10.7	47	10.3	AV	N	GND
1.255000	29.10	10.9	46	16.9	AV	N	GND
2.410000	27.60	11.0	46	18.4	AV	N	GND
6.320000	25.50	11.2	50	24.5	AV	N	GND
17.200000	18.00	11.4	50	32.0	AV	N	GND

Test mode 8

ACCURATE TECHNOLOGY CO.,LTD


CONDUCTED EMISSION STANDARD FCC PART 15B

EUT: SPEAKER M/N:TQ-LT1504
 Manufacturer: TQL TRADING INC
 Operating Condition: MIC IN
 Test Site: 1#Shielding Room
 Operator: DING
 Test Specification: L 120V/60Hz
 Comment: Report NO.:ATE20161336
 Start of Test: 7/12/2016 / 2:08:06PM

SCAN TABLE: "V 9K-30MHz fin"

Short Description: SUB STD VTERM2 1.70

Start	Stop	Step	Detector	Meas. Time	IF Bandw.	Transducer
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	NSLK8126 2008
150.0 kHz	30.0 MHz	5.0 kHz	Average			
			QuasiPeak	1.0 s	9 kHz	NSLK8126 2008
			Average			



MEASUREMENT RESULT: "TQ-0712-16_fin"

7/12/2016 2:12PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.360000	40.50	10.6	59	18.2	QP	L1	GND
0.425000	49.60	10.7	57	7.7	QP	L1	GND
1.070000	42.40	10.9	56	13.6	QP	L1	GND
2.270000	40.70	11.0	56	15.3	QP	L1	GND
5.750000	41.30	11.2	60	18.7	QP	L1	GND
12.550000	28.00	11.3	60	32.0	QP	L1	GND

MEASUREMENT RESULT: "TQ-0712-16_fin2"

7/12/2016 2:12PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.345000	33.90	10.6	49	15.2	AV	L1	GND
0.420000	40.70	10.7	47	6.7	AV	L1	GND
1.150000	32.50	10.9	46	13.5	AV	L1	GND
2.350000	33.50	11.0	46	12.5	AV	L1	GND
5.730000	30.30	11.2	50	19.7	AV	L1	GND
15.835000	15.90	11.4	50	34.1	AV	L1	GND

ACCURATE TECHNOLOGY CO., LTD


CONDUCTED EMISSION STANDARD FCC PART 15B

EUT: SPEAKER M/N:TQ-LT1504
 Manufacturer: TQL TRADING INC
 Operating Condition: MIC IN
 Test Site: 1#Shielding Room
 Operator: DING
 Test Specification: N 120V/60Hz
 Comment: Report NO.:ATE20161336
 Start of Test: 7/12/2016 / 2:01:46PM

SCAN TABLE: "V 9K-30MHz fin"

Short Description: SUB STD VTERM2 1.70

Start Frequency	Stop Frequency	Step Width	Detector	Meas. Time	IF Bandw.	Transducer
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	NSLK8126 2008
150.0 kHz	30.0 MHz	5.0 kHz	Average	1.0 s	9 kHz	NSLK8126 2008



MEASUREMENT RESULT: "TQ-0712-15_fin"

7/12/2016 2:07PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.355000	36.90	10.6	59	21.9	QP	N	GND
0.425000	44.00	10.7	57	13.3	QP	N	GND
1.135000	37.80	10.9	56	18.2	QP	N	GND
2.480000	33.90	11.0	56	22.1	QP	N	GND
7.650000	34.00	11.2	60	26.0	QP	N	GND
12.505000	28.20	11.3	60	31.8	QP	N	GND

MEASUREMENT RESULT: "TQ-0712-15_fin2"

7/12/2016 2:07PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.345000	25.40	10.6	49	23.7	AV	N	GND
0.420000	32.90	10.7	47	14.5	AV	N	GND
1.100000	25.80	10.9	46	20.2	AV	N	GND
2.370000	25.80	11.0	46	20.2	AV	N	GND
7.590000	26.30	11.2	50	23.7	AV	N	GND
12.445000	21.80	11.3	50	28.2	AV	N	GND


ACCURATE TECHNOLOGY CO., LTD

CONDUCTED EMISSION STANDARD FCC PART 15B

EUT: SPEAKER M/N:TQ-LT1504
 Manufacturer: TQL TRADING INC
 Operating Condition: MIC IN
 Test Site: 1#Shielding Room
 Operator: DING
 Test Specification: L 220V/50Hz
 Comment: Report NO.:ATE20161336
 Start of Test: 7/12/2016 / 4:49:00PM

SCAN TABLE: "V 9K-30MHz fin"

Short Description: SUB STD VTERM2 1.70
 Start Stop Step Detector Meas. IF Transducer
 Frequency Frequency Width Time Bandw.
 9.0 kHz 150.0 kHz 100.0 Hz QuasiPeak 1.0 s 200 Hz NSLK8126 2008
 150.0 kHz 30.0 MHz 5.0 kHz Average QuasiPeak 1.0 s 9 kHz NSLK8126 2008
 Average



MEASUREMENT RESULT: "TQ-0712-17_fin"

7/12/2016 4:56PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.360000	35.40	10.6	59	23.3	QP	L1	GND
0.425000	42.80	10.7	57	14.5	QP	L1	GND
0.880000	35.10	10.8	56	20.9	QP	L1	GND
2.240000	34.60	11.0	56	21.4	QP	L1	GND
6.110000	32.60	11.2	60	27.4	QP	L1	GND
16.750000	26.90	11.4	60	33.1	QP	L1	GND

MEASUREMENT RESULT: "TQ-0712-17_fin2"

7/12/2016 4:56PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.360000	26.00	10.6	49	22.7	AV	L1	GND
0.430000	33.80	10.7	47	13.5	AV	L1	GND
1.065000	24.20	10.9	46	21.8	AV	L1	GND
3.620000	22.10	11.1	46	23.9	AV	L1	GND
5.900000	24.20	11.2	50	25.8	AV	L1	GND
16.900000	18.20	11.4	50	31.8	AV	L1	GND


ACCURATE TECHNOLOGY CO.,LTD

CONDUCTED EMISSION STANDARD FCC PART 15B

EUT: SPEAKER M/N:TQ-LT1504
Manufacturer: TQL TRADING INC
Operating Condition: MIC IN
Test Site: 1#Shielding Room
Operator: DING
Test Specification: N 220V/50Hz
Comment: Report NO.:ATE20161336
Start of Test: 7/12/2016 / 4:56:51PM

SCAN TABLE: "V 9K-30MHz fin"

Short Description: SUB STD VTERM2 1.70
Start Stop Step Detector Meas. IF Transducer
Frequency Frequency Width Time Bandw.
9.0 kHz 150.0 kHz 100.0 Hz QuasiPeak 1.0 s 200 Hz NSLK8126 2008
Average
150.0 kHz 30.0 MHz 5.0 kHz QuasiPeak 1.0 s 9 kHz NSLK8126 2008
Average



MEASUREMENT RESULT: "TQ-0712-18_fin"

7/12/2016 5:00PM

Frequency MHz	Level dBuV	Transd dB	Limit dBuV	Margin dB	Detector	Line	PE
0.360000	37.50	10.6	59	21.2	QP	N	GND
0.425000	44.60	10.7	57	12.7	QP	N	GND
0.880000	38.60	10.8	56	17.4	QP	N	GND
2.180000	36.90	11.0	56	19.1	QP	N	GND
6.570000	32.00	11.2	60	28.0	QP	N	GND
17.365000	26.20	11.4	60	33.8	QP	N	GND

MEASUREMENT RESULT: "TQ-0712-18_fin2"

7/12/2016 5:00PM

Frequency MHz	Level dBuV	Transd dB	Limit dBuV	Margin dB	Detector	Line	PE
0.360000	31.30	10.6	49	17.4	AV	N	GND
0.425000	37.30	10.7	47	10.0	AV	N	GND
1.455000	28.60	10.9	46	17.4	AV	N	GND
2.580000	26.70	11.0	46	19.3	AV	N	GND
6.570000	24.90	11.2	50	25.1	AV	N	GND
17.455000	17.50	11.4	50	32.5	AV	N	GND


5. RADIATED EMISSION MEASUREMENT

5.1. Block Diagram of Test Setup

5.1.1. Block diagram of connection between the EUT and simulators


Test mode 1: TF card PLAYING

AC or DC Mains




Test mode 2: SD card PLAYING

AC or DC Mains




Test mode 3: AUX IN

AC or DC Mains




Test mode 4: 202.2MHz RX

AC or DC Mains




Test mode 5: USB PLAYING

AC or DC Mains




Test mode 6: FM

AC or DC Mains




Test mode 7: GUITAR IN

AC or DC Mains




Test mode 8: MIC IN

AC or DC Mains




5.1.2. Block diagram of test setup (In chamber)


(A) Radiated Emission Test Set-Up, Frequency below 30MHz



(B) Radiated Emission Test Set-Up, Frequency 30-1000MHz



(C) Radiated Emission Test Set-Up, Frequency above 1GHz



5.2.The Emission Limit For Section 15.109 (a)

5.2.1.Radiation Emission Measurement Limits According to Section 15.109 (a).

Frequency MHz	Distance Meters	Field Strengths Limit	
		$\mu\text{V/m}$	$\text{dB}(\mu\text{V/m})$
30-88	3	100	40.0
88-216	3	150	43.5
216-960	3	200	46.0
960-1000	3	500	54.0

Remark: (1) Emission level $\text{dB}(\mu\text{V}) = 20 \log$ Emission level $\mu\text{V/m}$.
 (2)The smaller limit shall apply at the cross point between two frequency bands.
 (3)Distance is the distance in meters between the measuring instrument antenna and the closest point of any part of the device or system.

5.3.EUT Configuration on Measurement

The following equipment is installed on Radiated Emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

5.3.1.SPEAKER

Model Number: TQ-LT1504

Serial Number: N/A

Manufacturer: TQL TRADING INC.

5.4.Operating Condition of EUT

5.4.1.Setup the EUT and simulator as shown as Section 5.1.

5.4.2.Turn on the power of all equipment.

5.4.3.Let the EUT work in test mode and measure it.

5.5.Test Procedure

The EUT and its simulators are placed on a turntable, which is 0.1 meter high above ground. The turntable can rotate 360 degrees to determine the position of the maximum emission level. EUT is set 3.0 meters away from the receiving antenna, which is mounted on an antenna tower. The antenna can be moved up and down between 1.0 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated bilog antenna) is used as receiving antenna. Both horizontal and vertical polarizations of the antenna are set on measurement. In order to find the maximum emission levels, all of the interface cables must be manipulated according to ANSI C63.4: 2014 on radiated emission measurement.

The bandwidth of the EMI test REMOTE CONTROL (R&S ESCS30) is set at 120kHz from 30MHz to 1000MHz.

The frequency range from 30MHz to 3000MHz is checked.

5.6.Radiated Emission Noise Measurement Result

PASS.

Note: 1. We carried out two kinds of AC and DC power supply radiation test, then we recorded the worst mode(AC power supply) test data in the report.

2. We tested 3 different frequency point of FM RX test mode, and recorded the worst case data(88.1MHz) in the report.

3. The EUT highest operating frequency provided by Manufacturer is 202.2MHz, the radiated emission measurement shall be made up to 3 GHz. The frequency range from 30MHz to 3000MHz is investigated.

Emissions attenuated more than 20 dB below the permissible value are not reported.

The spectral diagrams are attached as below.

Test mode 1

Below 1GHz



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber


Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: STAR2015 #1483
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: SPEAKER
Mode: TF PLAYING
Model: TQ-LT1504
Manufacturer: TQL TRADING INC

Polarization: Horizontal
Power Source: AC 120V/60Hz
Date: 2016/07/09
Time: 18:37:53
Engineer Signature:
Distance: 3m

Note: Report NO.:ATE20161336




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	32.8637	43.04	-10.21	32.83	40.00	-7.17	QP			
2	81.2116	51.86	-16.25	35.61	40.00	-4.39	QP			
3	148.9625	52.14	-15.17	36.97	43.50	-6.53	QP			
4	188.4125	53.60	-12.66	40.94	43.50	-2.56	QP			
5	324.4561	51.21	-8.56	42.65	46.00	-3.35	QP			
6	755.3873	43.83	-0.96	42.87	46.00	-3.13	QP			

Job No.: STAR2015 #1482
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: SPEAKER
Mode: TF PLAYING
Model: TQ-LT1504
Manufacturer: TQL TRADING INC

Polarization: Vertical
Power Source: AC 120V/60Hz
Date: 2016/07/09
Time: 18:33:36
Engineer Signature:
Distance: 3m

Note: Report NO.:ATE20161336



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	32.2925	45.69	-9.61	36.08	40.00	-3.92	QP			
2	80.0806	52.40	-16.49	35.91	40.00	-4.09	QP			
3	122.4039	50.04	-13.43	36.61	43.50	-6.89	QP			
4	130.3788	51.41	-13.88	37.53	43.50	-5.97	QP			
5	189.0743	53.82	-12.66	41.16	43.50	-2.34	QP			
6	324.4560	49.73	-8.56	41.17	46.00	-4.83	QP			

Above 1GHz



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: STAR2015 #1484

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: SPEAKER

Mode: TF PLAYING

Model: TQ-LT1504

Manufacturer: TQL TRADING INC

Polarization: Horizontal

Power Source: AC 120V/60Hz


Date: 2016/07/09

Time: 18:44:36

Engineer Signature:

Distance: 3m

Note: Report NO.:ATE20161336



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	4215.792	43.00	-1.63	41.37	74.00	-32.63	peak			
2	4215.792	35.44	-1.63	33.81	54.00	-20.19	AVG			

Job No.: STAR2015 #1485

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: SPEAKER

Mode: TF PLAYING

Model: TQ-LT1504

Manufacturer: TQL TRADING INC

Polarization: Vertical

Power Source: AC 120V/60Hz


Date: 2016/07/09

Time: 18:47:51

Engineer Signature:

Distance: 3m

Note: Report NO.:ATE20161336



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	4121.864	42.58	-1.50	41.08	74.00	-32.92	peak			
2	4121.864	34.61	-1.50	33.11	54.00	-20.89	AVG			

Test mode 2

Below 1GHz



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber


Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: STAR2015 #1481
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: SPEAKER
Mode: SD PLAYING
Model: TQ-LT1504
Manufacturer: TQL TRADING INC

Polarization: Horizontal
Power Source: AC 120V/60Hz
Date: 2016/07/09
Time: 18:30:39
Engineer Signature:
Distance: 3m

Note: Report NO.:ATE20161336




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	32.4059	45.10	-9.65	35.45	40.00	-4.55	QP			
2	81.2117	52.45	-16.25	36.20	40.00	-3.80	QP			
3	87.7248	50.66	-15.22	35.44	40.00	-4.56	QP			
4	188.4125	52.95	-12.66	40.29	43.50	-3.21	QP			
5	222.1698	47.60	-11.58	36.02	46.00	-9.98	QP			
6	355.4273	48.53	-7.70	40.83	46.00	-5.17	QP			

Job No.: STAR2015 #1480
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: SPEAKER
Mode: SD PLAYING
Model: TQ-LT1504
Manufacturer: TQL TRADING INC

Polarization: Vertical
Power Source: AC 120V/60Hz
Date: 2016/07/09
Time: 18:26:44
Engineer Signature:
Distance: 3m

Note: Report NO.:ATE20161336



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	32.8637	46.84	-9.79	37.05	40.00	-2.95	QP			
2	80.0806	52.40	-16.49	35.91	40.00	-4.09	QP			
3	162.0414	50.14	-14.52	35.62	43.50	-7.88	QP			
4	188.4124	53.03	-12.66	40.37	43.50	-3.13	QP			
5	324.4560	49.11	-8.56	40.55	46.00	-5.45	QP			
6	372.0045	48.88	-7.48	41.40	46.00	-4.60	QP			

Above 1GHz



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber


Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: STAR2015 #1487
Standard: FCC PK
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: SPEAKER
Mode: SD PLAYING
Model: TQ-LT1504
Manufacturer: TQL TRADING INC

Polarization: Horizontal
Power Source: AC 120V/60Hz
Date: 2016/07/09
Time: 18:56:02
Engineer Signature:
Distance: 3m

Note: Report NO.:ATE20161336




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	4141.813	43.29	-1.51	41.78	74.00	-32.22	peak			
2	4141.813	35.55	-1.51	34.04	54.00	-19.96	AVG			

Job No.: STAR2015 #1486
Standard: FCC PK
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: SPEAKER
Mode: SD PLAYING
Model: TQ-LT1504
Manufacturer: TQL TRADING INC

Polarization: Vertical
Power Source: AC 120V/60Hz
Date: 2016/07/09
Time: 18:51:36
Engineer Signature:
Distance: 3m

Note: Report NO.:ATE20161336



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	4718.534	42.71	-0.77	41.94	74.00	-32.06	peak			
2	4718.534	34.75	-0.77	33.98	54.00	-20.02	AVG			