



# EMF ASSESSMENT REPORT

## No. AR19-0046101-01

performed in accordance with

FCC Rules: Code of Federal Regulations (CFR) no. 47  
Part 15 Subpart C § 1.1307(b)(1)

INDUSTRY CANADA

Spectrum Management and Telecommunications Radio Standards Specification  
RSS-102:2015  
Radio Frequency (RF) Exposure Compliance of Radiocommunication Apparatus  
(All Frequency Bands)

<b>PRODUCT</b>	Augmented reality safety glasses and control unit
<b>MODEL(s) TESTED</b>	VISIONAR and VISIONAR – CONTROL UNIT
<b>TRADE MARK(s)</b>	UNIVET
<b>APPLICANT</b>	UNIVET S.r.l. ~ Via G. Prati, 87 ~ I-25086 Rezzato (BS)

Assessed by	Robertino Torri <i>[Laboratory technician]</i>
Approved by	Giovanni Di Turi <i>[Laboratory Manager]</i>

### Revision Sheet

Release No.	Date of Issue	Revision Description
Rev. 0	2020-06-10	First edition Digital signed - AR19-0046101-01_TR_SAR exclusion FCC_UNIVET - Glasses + Control unit

The results of tests and checks reported in this Test Report refer exclusively to the samples tested and described in the Report itself.

This Report shall not be reproduced partially without the written approval of IMQ S.p.A..

The authenticity of this Test Report and its contents can be verified by contacting IMQ S.p.A., responsible for this Test Report.

## 1. GENERAL DATA

<b>SAMPLE</b>				
Samples received on	/	<b>(Item(s) sampled and sent by applicant)</b>		
IMQ reference samples	<b>BEM</b>	/		
Samples tested No.	/			
Object under analysis recognition	<b>Not carried out</b>	Except where stated, characteristics of products were taken from client description and were not verified by the laboratory		
<b>TEST LOCATION</b>				
Testing dates	/			
Testing laboratory.	IMQ S.p.A. - Via Quintiliano, 43 – I-20138 Milano			
Testing site	Viale Lombardia, 20 – I-20021 Bollate (MI)			
<b>ENVIRONMENTAL CONDITIONING</b>				
Parameter	<b>Measured</b>			
Ambient Temperature	/			
Relative Humidity	/			
Atmospheric Pressure	/			
The laboratory is monitored by a continuous environmental conditions measurements system. Temperature, humidity and pressure data are recorded on a weekly basis and stored in local archive.				
<b>REMARKS</b>				
<p>Throughout this report a point is used as the decimal separator.</p> <p>The ability or reliability of this product to perform its intended function in a particular application has not been investigated. IMQ declines any responsibility derived from missing or wrong information provided aside by the applicant.</p>				

## 2. REFERENCE DOCUMENT

DOCUMENT	DATE	TITLE
<input checked="" type="checkbox"/> 47 CFR Part 15	2015	Radio Frequency Device
<input checked="" type="checkbox"/> 447498 D01 v06	2015	RF exposure procedures and equipment authorization policies for mobile and portable devices
<input checked="" type="checkbox"/> RSS-102	2015	Radio Frequency (RF) Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands)

### 3. UNIT UNDER TEST (EUT) DETAILS

#### GENERAL DATA

MODEL (basic)	Description
VISIONAR and VISIONAR – CONTROL UNIT	Augmented reality safety glasses and control unit
VARIANTS (derived)	Description
/	/

**The VISIONAR – CONTROL UNIT contains the radio modules:**

Module	FCC ID:	IC code
GSM and GPS	N7NHL8548	2417C-HL8548
Wi-Fi, BT and BLE	Z64-WL18SBMOD	451I-WL18SBMOD

MANUFACTURER	UNIVET S.r.l. ~ Via G. Prati, 87 ~ I-25086 Rezzato (BS)	
ASSEMBLY PLANT(s)		

#### EUT IDENTIFICATION

EUT type	Glasses and control unit		
EUT use	<input type="checkbox"/> Fixed	<input type="checkbox"/> Mobile	<input checked="" type="checkbox"/> Portable
EUT single or system	<input checked="" type="checkbox"/> Single	<input type="checkbox"/> System	

Antenna Type			
Antenna	Model	2450AT45A100E by JOHANSON (for 2.4 GHz module)	
	Type:	<input checked="" type="checkbox"/> Integral	<input type="checkbox"/> Dedicated
	Gain	1.5 dBi typ.	
Antenna	Model	SRFC025-100 by ANTENOVA (for GSM module)	
	Type:	<input type="checkbox"/> Integral	<input checked="" type="checkbox"/> Dedicated
	Gain	-3.31 dBi (@ 824-960 MHz)	

## 4. SUMMARY OF EMF ASSESSMENT RESULTS

### POSSIBLE TEST CASE VERDICTS:

Test object meets the requirement	PASS
Test object does not meet the requirement	FAIL
Evaluation of test result submit to customer	C.E.

CFR47 Part 15	TITLE	RESULT
1.1307(b)(1)	RF humane exposure	PASS

REF. OF RSS 102	TITLE	RESULT
RSS 102 - § 2.5.1	RF humane exposure	PASS

## 5. RESULTS OF RF EXPOSURE EVALUATION

### 5.1 FCC

TEST REQUIREMENT				
Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines § 1.1307(b)(1).				
EUT classification (fixed, mobile or portable devices)	Portable according to § 2.1093(b) of this Chapter			
LIMITS	According to § 2.1093 of this Chapter, by means of the following guidelines: OET Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies (447498 D01 General RF Exposure Guidance v06)			
Limit for maximum permissible Exposure (MPE)				
Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm <sup>2</sup> )	Average Time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3÷3.0	614	1.63	(100)*	6
3.0÷30	1842/f	4.89/f	(900/f <sup>2</sup> )*	6
30÷300	61.4	0.163	1.0	6
300÷1500	--	--	f/300	6
1500÷100,000	--	--	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3÷3.0	614	1.63	(100)*	30
3.0÷30	824/f	2.19/f	(180/f <sup>2</sup> )*	30
30÷300	27.5	0.073	0.2	30
300÷1500	--	--	f/1500	30
1500÷100,000	--	--	1.0	30

F = Frequency in MHz

\*Plane-wave equivalent power density

The distance from the device's transmitting antenna where the exposure level reaches the maximum permitted limit is calculated using the general equation:

$$S = P * G / 4\pi R^2$$

Where:

S = Power Density (mW/cm<sup>2</sup>)

P = Conducted power (mW)

G = Linear power gain relative to isotropic radiator (numeric gain)

R = Distance (cm)

**RF Exposure evaluation**
**Low threshold limit**

Exposure category	Radio module	Frequency range fMHz	Limit	Limit value (mW/cm <sup>2</sup> )
General population	GSM	850	$f_{\text{MHz}}/1500$	0.5667
	Wi-Fi	2462	/	1.0

**SINGLE TRASMITTER**
**MEASUREMENTS RESULTS**

Radio module	Max output power (dBm)	Antenna gain (dBi)	Max. power (dBm)	Max. Power (W)	Power density @ 20 cm (mW/cm <sup>2</sup> )	Limits (mW/cm <sup>2</sup> )
GSM	33 (*)	-3.31	29.69	0.931	0.185	0.5667
Wi-Fi	20 (*)	0	20	0.100	0.020	1.0

**SIMULTANEOUS TRANSMITTER**

Radio module	Max. power (dBm)	Max. Power (W)	Power density @ 20 cm (mW/cm <sup>2</sup> )	Limits (mW/cm <sup>2</sup> )	S / Limit
GSM	29.69	0.931	0.185	0.5667	0.327
Wi-Fi	20	0.100	0.020	1.0	0.020
<b>Simultaneous transmission (<math>\Sigma</math> S / Limit)</b>					<b>0.347</b>
<b>Limit</b>					<b>1</b>

(\*) Max power permitted for radio module type.

For all transmitter assumed duty cycle 100%.

## 5.2 IC

### TEST REQUIREMENT

**Table 4: RF Field Strength Limits for Devices Used by the General Public (Uncontrolled Environment)**

Frequency Range (MHz)	Electric Field (V/m rms)	Magnetic Field (A/m rms)	Power Density (W/m <sup>2</sup> )	Reference Period (minutes)
0.003-10 <sup>[2]</sup>	83	90	-	Instantaneous*
0.1-10	-	0.73/ $f$	-	6**
1.1-10	$87/f^{0.5}$	-	-	6**
10-20	27.46	0.0728	2	6
20-48	$58.07/f^{0.25}$	$0.1540/f^{0.25}$	$8.944/f^{0.5}$	6
48-300	22.06	0.05852	1.291	6
300-6000	$3.142f^{0.3417}$	$0.008335f^{0.3417}$	$0.02619f^{0.6834}$	6
6000-15000	61.4	0.163	10	6
15000-150000	61.4	0.163	10	$616000/f^{1.2}$
150000-300000	$0.158f^{0.5}$	$4.21 \times 10^{-4}f^{0.5}$	$6.67 \times 10^{-5}f$	$616000/f^{1.2}$

Note:  $f$  is frequency in MHz.

\*Based on nerve stimulation (NS).

\*\* Based on specific absorption rate (SAR).

### RF Exposure evaluation

#### Low threshold limit

Exposure category	Radio module	Frequency range fMHz	Limit	Limit value (W/m <sup>2</sup> )
General population	GSM	850	$0.02619f_{MHz}^{0.6834}$	2.63
	Wi-Fi	2462	$0.02619f_{MHz}^{0.6834}$	5.44

**SINGLE TRASMITTER**
**MEASUREMENTS RESULTS**

Radio module	Max output power (dBm)	Antenna gain (dBi)	Max. power (dBm)	Max. Power (W)	Power density @ 20 cm (W/m <sup>2</sup> )	Limits (W/m <sup>2</sup> )
GSM	33 <sup>(*)</sup>	-3.31	29.69	0.931	1.85	2.63
Wi-Fi	20 <sup>(*)</sup>	0	20	0.100	0.20	5.44

**SIMULTANEOUS TRANSMITTER**

Radio module	Max. power (dBm)	Max. Power (W)	Power density @ 20 cm (W/m <sup>2</sup> )	Limits (W/m <sup>2</sup> )	S / Limit
GSM	29.69	0.931	1.85	2.63	0.704
Wi-Fi	20	0.100	0.20	5.44	0.037
<b>Simultaneous transmission (<math>\Sigma</math> S / Limit)</b>					<b>0.741</b>
<b>Limit</b>					<b>1</b>

<sup>(\*)</sup> Max power permitted for radio module type.

For all transmitter assumed duty cycle 100%.

## 8. PHOTOGRAPHIC DOCUMENTATION

### EUT IDENTIFICATION



**END OF ASSESSMENT REPORT**