

# RF TEST REPORT



Report No.: Q181101S007-FCC-R4

Supersede Report No.: N/A

Applicant	Cedar Kingdom Corporation Limited	
Product Name	Tablet	
Model No.	VT701	
Serial No.	N/A	
Test Standard	FCC Part 15.247, ANSI C63.10: 2013	
Test Date	November 05 to December 05, 2018	
Issue Date	December 06, 2018	
Test Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail	
Equipment complied with the specification		<input checked="" type="checkbox"/>
Equipment did not comply with the specification		<input type="checkbox"/>
Aaron Liang Test Engineer	David Huang Checked By	
This test report may be reproduced in full only Test result presented in this test report is applicable to the tested sample only		

Issued by:

SIEMIC (SHENZHEN-CHINA) LABORATORIES

Zone A, Floor 1, Building 2 Wan Ye Long Technology Park

South Side of Zhoushi Road, Bao'an District, Shenzhen, Guangdong China 518108

Phone: +86 0755 2601 4629801 Email: [China@siemic.com.cn](mailto:China@siemic.com.cn)

## Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

### Accreditations for Conformity Assessment

Country/Region	Scope
USA	EMC, RF/Wireless, SAR, Telecom
Canada	EMC, RF/Wireless, SAR, Telecom
Taiwan	EMC, RF, Telecom, SAR, Safety
Hong Kong	RF/Wireless, SAR, Telecom
Australia	EMC, RF, Telecom, SAR, Safety
Korea	EMI, EMS, RF, SAR, Telecom, Safety
Japan	EMI, RF/Wireless, SAR, Telecom
Singapore	EMC, RF, SAR, Telecom
Europe	EMC, RF, SAR, Telecom, Safety

Test Report No.	Q181101S007-FCC-R4
Page	3 of 38

---

This page has been left blank intentionally.

## CONTENTS

1. REPORT REVISION HISTORY.....	5
2. CUSTOMER INFORMATION .....	5
3. TEST SITE INFORMATION.....	6
4. EQUIPMENT UNDER TEST (EUT) INFORMATION .....	7
5. TEST SUMMARY .....	9
6. MEASUREMENTS, EXAMINATION AND DERIVED RESULTS .....	10
6.1 ANTENNA REQUIREMENT.....	10
6.2 DTS (6 DB) CHANNEL BANDWIDTH .....	11
6.3 MAXIMUM OUTPUT POWER .....	13
6.4 POWER SPECTRAL DENSITY .....	15
6.5 BAND-EDGE & UNWANTED EMISSIONS INTO RESTRICTED FREQUENCY BANDS .....	17
6.6 AC POWER LINE CONDUCTED EMISSIONS.....	20
6.7 RADIATED EMISSIONS & RESTRICTED BAND .....	26
ANNEX A. TEST INSTRUMENT.....	33
ANNEX B. TEST SETUP AND SUPPORTING EQUIPMENT.....	34
ANNEX C. USER MANUAL / BLOCK DIAGRAM / SCHEMATICS / PARTLIST/ DECLARATION OF SIMILARITY.....	38

## 1. Report Revision History

Report No.	Report Version	Description	Issue Date
Q181101S007-FCC-R4	NONE	Original	December 06, 2018

## 2. Customer information

Applicant Name	Cedar Kingdom Corporation Limited
Applicant Add	11/F, AXA Centre 151 Gloucester Road, Wanchai, Hong Kong
Manufacturer	Cedar Kingdom Corporation Limited
Manufacturer Add	11/F, AXA Centre 151 Gloucester Road, Wanchai, Hong Kong

### 3. Test site information

Test Lab A:

Lab performing tests	SIEMIC (Shenzhen-China) LABORATORIES
Lab Address	Zone A, Floor 1, Building 2 Wan Ye Long Technology Park South Side of Zhoushi Road, Bao'an District, Shenzhen, Guangdong China 518108
FCC Test Site No.	535293
IC Test Site No.	4842E-1
Test Software	Radiated Emission Program-To Shenzhen v2.0

Test Lab B:

Lab performing tests	Bureau Veritas Shenzhen Co., Ltd. Dongguan Branch Laboratories
Lab Address	No. 34, Chenwulu Section, Guantai Rd., Houjie Town, Dongguan City, Guangdong 523942, China
FCC Test Site No.	749762
IC Test Site No.	5936A-1
Test Software	ADT_Radiated_V7.6.15.9.2

Note: We just perform Radiated Spurious Emission above 18GHz in the test Lab. B.

#### 4. Equipment under Test (EUT) Information

Description of EUT:	Tablet
Main Model:	VT701
Serial Model:	N/A
Date EUT received:	November 05, 2018
Test Date(s):	November 05 to December 05, 2018
Equipment Category :	DTS
Antenna Gain:	GSM850: -0.86dBi PCS1900: 1.42dBi UMTS-FDD Band V: -0.86dBi UMTS-FDD Band II: 1.42dBi WIFI: 1.5dBi Bluetooth/BLE: 1.5dBi GPS: 0.68dBi
Antenna Type:	PIFA antenna  GSM / GPRS: GMSK UMTS-FDD: QPSK 802.11b/g/n: DSSS, OFDM Bluetooth: GFSK, π /4DQPSK, 8DPSK BLE: GFSK GPS:BPSK
RF Operating Frequency (ies):	GSM850 TX: 824.2 ~ 848.8 MHz; RX: 869.2 ~ 893.8 MHz PCS1900 TX: 1850.2 ~ 1909.8 MHz; RX: 1930.2 ~ 1989.8 MHz UMTS-FDD Band V TX: 826.4 ~ 846.6 MHz; RX: 871.4 ~ 891.6 MHz UMTS-FDD Band II TX: 1852.4 ~ 1907.6 MHz; RX: 1932.4 ~ 1987.6 MHz WIFI: 802.11b/g/n(20M): 2412-2462 MHz Bluetooth& BLE: 2402-2480 MHz GPS: 1575.42 MHz

Test Report No.	Q181101S007-FCC-R4
Page	8 of 38

Max. Output Power: -7.041dBm

GSM 850: 124CH

PCS1900: 299CH

UMTS-FDD Band V: 102CH

UMTS-FDD Band II: 277CH

WIFI :802.11b/g/n(20M): 11CH

Bluetooth: 79CH

BLE: 40CH

GPS:1CH

Number of Channels:

Port: Please refer to the user's manual

Trade Name : VIRZO

Adapter :

Model: VT701

Input Power: Input: AC100-240V~50/60Hz,0.5A

Output: DC 5.0V, 2A

Battery :

Spec: 3.7V, 2500mAh/9.25Wh

FCC ID: 2AKQUVZCKVT701

## 5. Test Summary

The product was tested in accordance with the following specifications.

All testing has been performed according to below product classification:

FCC Rules	Description of Test	Result
§15.203	Antenna Requirement	Compliance
§15.247 (a)(2)	DTS (6 dB) CHANNEL BANDWIDTH	Compliance
§15.247(b)(3)	Conducted Maximum Output Power	Compliance
§15.247(e)	Power Spectral Density	Compliance
§15.247(d)	Band-Edge & Unwanted Emissions into Restricted Frequency Bands	Compliance
§15.207 (a),	AC Power Line Conducted Emissions	Compliance
§15.205, §15.209, §15.247(d)	Radiated Emissions & Unwanted Emissions into Restricted Frequency Bands	Compliance

### Measurement Uncertainty

Emissions		
Test Item	Description	Uncertainty
Band-Edge & Unwanted Emissions into Restricted Frequency Bands and Radiated Emissions & Unwanted Emissions into Restricted Frequency Bands	Confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2 (for EUTs < 0.5m X 0.5m X 0.5m)	+5.6dB/-4.5dB
-	-	-

## **6. Measurements, Examination And Derived Results**

### **6.1 Antenna Requirement**

#### **Applicable Standard**

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

#### **Antenna Connector Construction**

The EUT has 2 antennas:

A permanently attached PIFA antenna for Bluetooth/BLE/WIF/GPS, the gain is 1.5dBi for Bluetooth/BLE, the gain is 1.5dBi for WIFI, the gain is 0.68dBi for GPS.


A permanently attached PIFA antenna for GSM/PCS/UMTS, the gain is -0.86dBi for GSM850, 1.42dBi for PCS1900, -0.86dBi for UMTS-FDD Band V, 1.42dBi for UMTS-FDD Band II.

**The antenna meets up with the ANTENNA REQUIREMENT.**

**Result:** Compliance.

## 6.2 DTS (6 dB) Channel Bandwidth

Temperature	24°C
Relative Humidity	54%
Atmospheric Pressure	1020mbar
Test date :	November 29, 2018
Tested By :	Aaron Liang

Spec	Item	Requirement	Applicable
§ 15.247(a)(2)	a)	6dB BW $\geq$ 500kHz;	<input checked="" type="checkbox"/>
RSS Gen(4.6.1)	b)	99% BW: For FCC reference only; required by IC.	<input checked="" type="checkbox"/>
Test Setup			
Test Procedure		<p>558074 D01 DTS MEAS Guidance v03r03, 8.1 DTS bandwidth</p> <p><u>6dB Emission bandwidth measurement procedure</u></p> <ul style="list-style-type: none"> <li>- Set RBW = 100 kHz.</li> <li>- Set the video bandwidth (VBW) <math>\geq</math> 3 RBW.</li> <li>- Detector = Peak.</li> <li>- Trace mode = max hold.</li> <li>- Sweep = auto couple.</li> <li>- Allow the trace to stabilize.</li> </ul> <p>Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.</p>	
Remark			
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail		

Test Data  Yes  N/A


Test Plot  Yes (See below)  N/A

## 6dB Bandwidth measurement result

### Test Data

CH	Frequency (MHz)	6dB Bandwidth (kHz)	99% Occupied Bandwidth (MHz)
Low	2402	659.419	1.0647
Mid	2440	667.650	1.0627
High	2480	664.501	1.0639


### Test Plots



### 6.3 Maximum Output Power

Temperature	24°C
Relative Humidity	54%
Atmospheric Pressure	1020mbar
Test date :	November 29, 2018
Tested By :	Aaron Liang

#### Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(b) (3), RSS210 (A8.4)	a)	FHSS in 2400-2483.5MHz with $\geq$ 75 channels: $\leq$ 1 Watt	<input type="checkbox"/>
	b)	FHSS in 5725-5850MHz: $\leq$ 1 Watt	<input type="checkbox"/>
	c)	For all other FHSS in the 2400-2483.5MHz band: $\leq$ 0.125 Watt.	<input type="checkbox"/>
	d)	FHSS in 902-928MHz with $\geq$ 50 channels: $\leq$ 1 Watt	<input type="checkbox"/>
	e)	FHSS in 902-928MHz with $\geq$ 25 & $<$ 50 channels: $\leq$ 0.25 Watt	<input type="checkbox"/>
	f)	DTS in 902-928MHz, 2400-2483.5MHz: $\leq$ 1 Watt	<input checked="" type="checkbox"/>
Test Setup		 <b>Spectrum Analyzer</b> <b>EUT</b>	
Test Procedure		<p>558074 D01 DTS MEAS Guidance v03r03, 9.1.2 Integrated band power method</p> <p>Maximum output power measurement procedure</p> <ol style="list-style-type: none"> <li>Set the RBW <math>\geq</math> DTS bandwidth.</li> <li>Set VBW <math>\geq</math> <math>3 \times</math> RBW.</li> <li>Set span <math>\geq</math> <math>3 \times</math> RBW</li> <li>Sweep time = auto couple.</li> <li>Detector = peak.</li> <li>Trace mode = max hold.</li> <li>Allow trace to fully stabilize.</li> <li>Use peak marker function to determine the peak amplitude level.</li> </ol>	
Remark			
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail		

Test Data  Yes  N/A


Test Plot  Yes (See below)  N/A

### Output Power measurement result

#### Test Data


Type	CH	Frequency (MHz)	Conducted Power (dBm)	Limit (dBm)	Result
Output power	Low	2402	-8.041	30	Pass
	Mid	2440	-9.472	30	Pass
	High	2480	-9.390	30	Pass

#### Test Plots



## 6.4 Power Spectral Density

Temperature	24°C
Relative Humidity	54%
Atmospheric Pressure	1020mbar
Test date :	November 29, 2018
Tested By :	Aaron Liang

Spec	Item	Requirement	Applicable
§15.247(e)	a)	The power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.	<input checked="" type="checkbox"/>
Test Setup			
Test Procedure		<p>558074 D01 DTS MEAS Guidance v03r03, 10.2 power spectral density method power spectral density measurement procedure</p> <ul style="list-style-type: none"> <li>- a) Set analyzer center frequency to DTS channel center frequency.</li> <li>- b) Set the span to 1.5 times the DTS bandwidth.</li> <li>- c) Set the RBW to: <math>3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}</math>.</li> <li>- d) Set the VBW <math>\geq 3 \times \text{RBW}</math>.</li> <li>- e) Detector = peak.</li> <li>- f) Sweep time = auto couple.</li> <li>- g) Trace mode = max hold.</li> <li>- h) Allow trace to fully stabilize.</li> <li>- i) Use the peak marker function to determine the maximum amplitude level within the RBW.</li> <li>- j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.</li> </ul>	
Remark			
Result		<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail	

**Test Data**  Yes

N/A

**Test Plot**  Yes (See below)

N/A


## Power Spectral Density measurement result

### Test Data

Type	CH	Freq (MHz)	Reading (dBm)	Factor (dB)	Result (dBm)	Limit (dBm)	Result
PSD	Low	2402	-19.63	-5.23	-24.86	8	Pass
	Mid	2440	-16.95	-5.23	-22.18	8	Pass
	High	2480	-14.47	-5.23	-19.70	8	Pass

Note: factor=10log(3/10)=-5.23


### Test Plots



## 6.5 Band-Edge & Unwanted Emissions into Restricted Frequency Bands

Temperature	26 °C
Relative Humidity	59%
Atmospheric Pressure	1015mbar
Test date :	December 03&04, 2018
Tested By :	Aaron Liang

### Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(d)	a)	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.	<input checked="" type="checkbox"/>
Test Setup	 <p>The diagram illustrates the test setup. An 'EUT &amp; Support Units' is positioned on a 'Turn Table' at a height of '0.8/1.5m' above a 'Ground Plane'. A '3m' horizontal distance separates the EUT from an 'Ant. Tower'. The 'Ant. Tower' is mounted on a vertical post and is connected to a 'Test Receiver' which is shown with a waveform display and control buttons.</p>		
Test Procedure	<p>Radiated Method Only</p> <ul style="list-style-type: none"> <li>- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.</li> <li>- 2. Position the EUT without connection to measurement instrument. Put it on the Rotated table and turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.</li> </ul>		


	<ul style="list-style-type: none"> <li>- 3. First, set both RBW and VBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100kHz bandwidth from band edge, check the emission of EUT, if pass then set Spectrum Analyzer as below:           <ul style="list-style-type: none"> <li>a. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasiy Peak detection at frequency below 1GHz.</li> <li>b. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz with Peak detection for Peak measurement at frequency above 1GHz.</li> <li>c. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz with Peak detection for Average Measurement as below at frequency above 1GHz.</li> </ul> </li> <li>- 4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.</li> <li>- 5. Repeat above procedures until all measured frequencies were complete.</li> </ul>
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data     Yes       N/A

Test Plot     Yes (See below)       N/A

## Test Plots

### Band Edge measurement result




Note: Both Horizontal and vertical polarities were investigated.

## 6.6 AC Power Line Conducted Emissions

Temperature	26 °C
Relative Humidity	59%
Atmospheric Pressure	1015mbar
Test date :	December 03, 2018
Tested By :	Aaron Liang

### Requirement(s):


Spec	Item	Requirement	Applicable														
47CFR§15.207, RSS210 (A8.1)	a)	<p>For Low-power radio-frequency devices that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 [mu] H/50 ohms line impedance stabilization network (LISN). The lower limit applies at the boundary between the frequencies ranges.</p> <table border="1"> <thead> <tr> <th rowspan="2">Frequency ranges (MHz)</th> <th colspan="2">Limit (dB<math>\mu</math>V)</th> </tr> <tr> <th>QP</th> <th>Average</th> </tr> </thead> <tbody> <tr> <td>0.15 ~ 0.5</td> <td>66 – 56</td> <td>56 – 46</td> </tr> <tr> <td>0.5 ~ 5</td> <td>56</td> <td>46</td> </tr> <tr> <td>5 ~ 30</td> <td>60</td> <td>50</td> </tr> </tbody> </table>	Frequency ranges (MHz)	Limit (dB $\mu$ V)		QP	Average	0.15 ~ 0.5	66 – 56	56 – 46	0.5 ~ 5	56	46	5 ~ 30	60	50	<input checked="" type="checkbox"/>
Frequency ranges (MHz)	Limit (dB $\mu$ V)																
	QP	Average															
0.15 ~ 0.5	66 – 56	56 – 46															
0.5 ~ 5	56	46															
5 ~ 30	60	50															
Test Setup	 <p><b>Note:</b> 1. Support units were connected to second LISN. 2. Both of LISNs (AMN) are 80cm from EUT and at least 80cm from other units and other metal planes support units.</p>																
Procedure	<ol style="list-style-type: none"> <li>The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m x 1m x 0.8m high, non-metallic table.</li> <li>The power supply for the EUT was fed through a 50W/50mH EUT LISN, connected to filtered mains.</li> <li>The RF OUT of the EUT LISN was connected to the EMI test receiver via a low-loss</li> </ol>																

	<p>coaxial cable.</p> <ol style="list-style-type: none"> <li>4. All other supporting equipment were powered separately from another main supply.</li> <li>5. The EUT was switched on and allowed to warm up to its normal operating condition.</li> <li>6. A scan was made on the NEUTRAL line (for AC mains) or Earth line (for DC power) over the required frequency range using an EMI test receiver.</li> <li>7. High peaks, relative to the limit line, The EMI test receiver was then tuned to the selected frequencies and the necessary measurements made with a receiver bandwidth setting of 10 kHz.</li> <li>8. Step 7 was then repeated for the LIVE line (for AC mains) or DC line (for DC power).</li> </ol>
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data  Yes  N/A

Test Plot  Yes (See below)  N/A

**Test Mode:** Transmitting Mode




### *Test Data*

#### Phase Line Plot at 120Vac, 60Hz

No.	P/L	Frequency (MHz)	Reading (dB $\mu$ V)	Detector	Corrected (dB)	Result (dB $\mu$ V)	Limit (dB $\mu$ V)	Margin (dB)
1	L1	0.1578	35.21	QP	10.03	45.24	65.58	-20.34
2	L1	0.1578	15.51	AVG	10.03	25.54	55.58	-30.04
3	L1	0.4308	44.68	QP	10.03	54.71	57.24	-2.53
4	L1	0.4308	30.21	AVG	10.03	40.24	47.24	-7.00
5	L1	0.7467	32.82	QP	10.03	42.85	56.00	-13.15
6	L1	0.7467	18.58	AVG	10.03	28.61	46.00	-17.39
7	L1	1.1952	30.64	QP	10.03	40.67	56.00	-15.33
8	L1	1.1952	16.39	AVG	10.03	26.42	46.00	-19.58
9	L1	4.9812	27.32	QP	10.08	37.40	56.00	-18.60
10	L1	4.9812	15.16	AVG	10.08	25.24	46.00	-20.76
11	L1	13.1322	34.47	QP	10.20	44.67	60.00	-15.33
12	L1	13.1322	21.98	AVG	10.20	32.18	50.00	-17.82

**Test Mode:** Transmitting Mode




**Test Data**

Phase Neutral Plot at 120Vac, 60Hz

No.	P/L	Frequency (MHz)	Reading (dB $\mu$ V)	Detector	Corrected (dB)	Result (dB $\mu$ V)	Limit (dB $\mu$ V)	Margin (dB)
1	N	0.1500	37.16	QP	10.02	47.18	66.00	-18.82
2	N	0.1500	17.13	AVG	10.02	27.15	56.00	-28.85
3	N	0.4269	40.13	QP	10.02	50.15	57.31	-7.16
4	N	0.4269	26.02	AVG	10.02	36.04	47.31	-11.27
5	N	0.7545	28.35	QP	10.03	38.38	56.00	-17.62
6	N	0.7545	14.53	AVG	10.03	24.56	46.00	-21.44
7	N	5.6364	20.95	QP	10.08	31.03	60.00	-28.97
8	N	5.6364	10.73	AVG	10.08	20.81	50.00	-29.19
9	N	13.3779	29.30	QP	10.18	39.48	60.00	-20.52
10	N	13.3779	17.75	AVG	10.18	27.93	50.00	-22.07
11	N	16.1079	28.38	QP	10.21	38.59	60.00	-21.41
12	N	16.1079	18.86	AVG	10.21	29.07	50.00	-20.93

**Test Mode:** Transmitting Mode




**Test Data**

**Phase Line Plot at 240Vac, 60Hz**

No.	P/L	Frequency (MHz)	Reading (dB $\mu$ V)	Detector	Corrected (dB)	Result (dB $\mu$ V)	Limit (dB $\mu$ V)	Margin (dB)
1	L1	0.1500	29.08	QP	10.03	39.11	66.00	-26.89
2	L1	0.1500	-0.62	AVG	10.03	9.41	56.00	-46.59
3	L1	0.4581	32.50	QP	10.03	42.53	56.73	-14.20
4	L1	0.4581	18.67	AVG	10.03	28.70	46.73	-18.03
5	L1	0.8442	28.66	QP	10.03	38.69	56.00	-17.31
6	L1	0.8442	11.20	AVG	10.03	21.23	46.00	-24.77
7	L1	2.1507	28.09	QP	10.04	38.13	56.00	-17.87
8	L1	2.1507	11.44	AVG	10.04	21.48	46.00	-24.52
9	L1	4.4703	27.27	QP	10.07	37.34	56.00	-18.66
10	L1	4.4703	10.46	AVG	10.07	20.53	46.00	-25.47
11	L1	12.7890	36.72	QP	10.19	46.91	60.00	-13.09
12	L1	12.7890	17.12	AVG	10.19	27.31	50.00	-22.69

**Test Mode:** Transmitting Mode



### Test Data

Phase Neutral Plot at 240Vac, 60Hz



No.	P/L	Frequency (MHz)	Reading (dB $\mu$ V)	Detector	Corrected (dB)	Result (dB $\mu$ V)	Limit (dB $\mu$ V)	Margin (dB)
1	N	0.2670	32.93	QP	10.02	42.95	61.21	-18.26
2	N	0.2670	20.15	AVG	10.02	30.17	51.21	-21.04
3	N	0.4620	40.43	QP	10.02	50.45	56.66	-6.21
4	N	0.4620	27.55	AVG	10.02	37.57	46.66	-9.09
5	N	0.8052	32.27	QP	10.03	42.30	56.00	-13.70
6	N	0.8052	19.32	AVG	10.03	29.35	46.00	-16.65
7	N	2.8254	27.66	QP	10.05	37.71	56.00	-18.29
8	N	2.8254	17.73	AVG	10.05	27.78	46.00	-18.22
9	N	5.2425	28.30	QP	10.07	38.37	60.00	-21.63
10	N	5.2425	18.31	AVG	10.07	28.38	50.00	-21.62
11	N	13.0308	37.14	QP	10.18	47.32	60.00	-12.68
12	N	13.0308	24.94	AVG	10.18	35.12	50.00	-14.88

## 6.7 Radiated Emissions & Restricted Band

Temperature	26 °C
Relative Humidity	59%
Atmospheric Pressure	1015mbar
Test date :	December 03, 2018
Tested By :	Aaron Liang

### Requirement(s):

Spec	Item	Requirement	Applicable																
47CFR§15. 247(d), RSS210	a)	<p>Except higher limit as specified elsewhere in other section, the emissions from the low-power radio-frequency devices shall not exceed the field strength levels specified in the following table and the level of any unwanted emissions shall not exceed the level of the fundamental emission. The tighter limit applies at the band edges</p> <table border="1"> <thead> <tr> <th>Frequency range (MHz)</th> <th>Field Strength (μV/m)</th> </tr> </thead> <tbody> <tr> <td>0.009~0.490</td> <td>2400/F(KHz)</td> </tr> <tr> <td>0.490~1.705</td> <td>24000/F(KHz)</td> </tr> <tr> <td>1.705~30.0</td> <td>30</td> </tr> <tr> <td>30 – 88</td> <td>100</td> </tr> <tr> <td>88 – 216</td> <td>150</td> </tr> <tr> <td>216~960</td> <td>200</td> </tr> <tr> <td>Above 960</td> <td>500</td> </tr> </tbody> </table>	Frequency range (MHz)	Field Strength (μV/m)	0.009~0.490	2400/F(KHz)	0.490~1.705	24000/F(KHz)	1.705~30.0	30	30 – 88	100	88 – 216	150	216~960	200	Above 960	500	<input checked="" type="checkbox"/>
Frequency range (MHz)	Field Strength (μV/m)																		
0.009~0.490	2400/F(KHz)																		
0.490~1.705	24000/F(KHz)																		
1.705~30.0	30																		
30 – 88	100																		
88 – 216	150																		
216~960	200																		
Above 960	500																		
(A8.5)	b)	<p>For non-restricted band, In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB or 30dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, determined by the measurement method on output power to be used. Attenuation below the general limits specified in § 15.209(a) is not required</p> <p><input checked="" type="checkbox"/> 20 dB down <input type="checkbox"/> 30 dB down</p>	<input checked="" type="checkbox"/>																
	c)	or restricted band, emission must also comply with the radiated emission limits specified in 15.209	<input checked="" type="checkbox"/>																

Test Setup	 <p>The diagram shows the test setup. An EUT (Equipment Under Test) is placed on a turntable, which is positioned on a ground plane. A loop antenna is positioned 3 meters away from the EUT. An RF test receiver is connected to the loop antenna. The EUT is mounted on a support unit, and its height is indicated as 0.8m. The turntable is also labeled with 0.8/1.5m.</p>  <p>The diagram shows a more detailed view of the antenna setup. The EUT and support units are on a turntable, which is on a ground plane. An antenna tower is positioned 3 meters away from the EUT. The antenna height is adjustable, ranging from 1m to 4m. A test receiver is connected to the antenna tower.</p>
Procedure	<ol style="list-style-type: none"> <li>1. The EUT was switched on and allowed to warm up to its normal operating condition.</li> <li>2. The test was carried out at the selected frequency points obtained from the EUT characterization. Maximization of the emissions, was carried out by rotating the EUT, changing the antenna polarization, and adjusting the antenna height in the following manner:             <ol style="list-style-type: none"> <li>a. Vertical or horizontal polarization (whichever gave the higher emission level over a full rotation of the EUT) was chosen.</li> <li>b. The EUT was then rotated to the direction that gave the maximum emission.</li> <li>c. Finally, the antenna height was adjusted to the height that gave the maximum emission.</li> </ol> </li> <li>3. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasiy Peak detection at frequency below 1GHz.</li> <li>4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz with Peak detection for Peak measurement at frequency above 1GHz.</li> </ol>

	<p>The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz with Peak detection for Average Measurement as below at frequency above 1GHz.</p> <p>5. Steps 2 and 3 were repeated for the next frequency point, until all selected frequency points were measured.</p>
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail
Test Data	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> N/A
Test Plot	<input checked="" type="checkbox"/> Yes (See below) <input type="checkbox"/> N/A

## Test Result:

Test Mode:	Transmitting Mode
------------	-------------------

Frequency range: 9KHz - 30MHz

Freq. (MHz)	Detection value	Factor	Reading	Result	Limit@3m	Margin
		(dB/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dB)
--	--	--	--	--	--	>20
--	--	--	--	--	--	>20

Note:


The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log (\text{specific distance}/\text{test distance})$ (dB);

Limit line = specific limits(dBuv) + distance extrapolation factor.

**Test Mode:** Transmitting Mode

**30MHz -1GHz**




**Test Data**

**Vertical Polarity Plot @3m**

No.	P/L	Frequency	Reading	Ant_F	PA_G	Cab_L	Result	Limit	Margin	Height	Degr ee
		(MHz)	(dBuV/m)	(dB/m)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	( )
1	H	599.3213	33.50	19.09	21.58	2.49	33.50	46.00	-12.50	100	74
2	H	502.9395	30.47	17.74	21.80	2.42	28.83	46.00	-17.17	100	115
3	H	359.1860	28.75	14.84	22.12	2.03	23.50	46.00	-22.50	100	216
4	H	300.3673	30.51	13.61	22.29	1.79	23.62	46.00	-22.38	100	187
5	H	120.2766	26.20	13.88	22.36	1.16	18.88	43.50	-24.62	100	66
6	H	72.3376	33.28	7.75	22.39	0.97	19.61	40.00	-20.39	100	188

### 30MHz -1GHz



### Test Data

Horizontal Polarity Plot @3m

N o.	P/ L	Frequency (MHz)	Reading (dBuV/m)	Ant_F (dB/m)	PA_G (dB)	Cab_L (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degr ee
1	V	599.3213	31.53	19.09	21.58	2.49	31.53	46.00	-14.47	100	71
2	V	364.2595	27.20	14.95	22.11	2.03	22.07	46.00	-23.93	100	206
3	V	159.7844	34.10	12.60	22.27	1.39	25.82	43.50	-17.68	100	18
4	V	71.5806	44.15	7.77	22.39	0.97	30.50	40.00	-9.50	200	258
5	V	54.4516	46.99	7.91	22.39	0.78	33.29	40.00	-6.71	100	188
6	V	37.5479	35.44	15.69	22.27	0.78	29.64	40.00	-10.36	100	321

### Above 1GHz

Test Mode:	Transmitting Mode
------------	-------------------

#### Low Channel (2402 MHz)

Frequency (MHz)	S.A. Reading (dB $\mu$ V)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord. Amp. (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
4804	44.6	AV	V	33.39	7.22	48.46	36.75	54	-17.25
4804	45.1	AV	H	33.39	7.22	48.46	37.25	54	-16.75
4804	66.76	PK	V	33.39	7.22	48.46	58.91	74	-15.09
4804	66.83	PK	H	33.39	7.22	48.46	58.98	74	-15.02
8958	37.74	AV	V	37.18	9.34	48.59	35.67	54	-18.33
8958	35.31	AV	H	37.18	9.34	48.59	33.24	54	-20.76
8958	49.84	PK	V	37.18	9.34	48.59	47.77	74	-26.23
8958	51.85	PK	H	37.18	9.34	48.59	49.78	74	-24.22

#### Middle Channel (2440 MHz)

Frequency (MHz)	S.A. Reading (dB $\mu$ V)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord. Amp. (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
4880	49.9	AV	V	33.62	7.53	48.36	42.69	54	-11.31
4880	43.34	AV	H	33.62	7.53	48.36	36.13	54	-17.87
4880	65.43	PK	V	33.62	7.53	48.36	58.22	74	-15.78
4880	67.78	PK	H	33.62	7.53	48.36	60.57	74	-13.43
12970	31.56	AV	V	39.52	13.08	46.6	37.56	54	-16.44
12970	35.92	AV	H	39.52	13.08	46.6	41.92	54	-12.08
12970	48.63	PK	V	39.52	13.08	46.6	54.63	74	-19.37
12970	57.09	PK	H	39.52	13.08	46.6	63.09	74	-10.91

**High Channel (2480 MHz)**

Frequency (MHz)	S.A. Reading (dB $\mu$ V)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord. Amp. (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
4960	49.8	AV	V	33.89	7.86	48.31	43.24	54	-10.76
4960	45.67	AV	H	33.89	7.86	48.31	39.11	54	-14.89
4960	67.59	PK	V	33.89	7.86	48.31	61.03	74	-12.97
4960	68.46	PK	H	33.89	7.86	48.31	61.9	74	-12.1
17803	14.25	AV	V	42.75	19.94	43.87	33.07	54	-20.93
17803	15.25	AV	H	42.75	19.94	43.87	34.07	54	-19.93
17803	38.16	PK	V	42.75	19.94	43.87	56.98	74	-17.02
17803	40.96	PK	H	42.75	19.94	43.87	59.78	74	-14.22

**Note:**

- 1, The testing has been conformed to  $10*2480\text{MHz}=24,800\text{MHz}$
- 2, All other emissions more than 30 dB below the limit
- 3, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case.
- 4, The radiated spurious test above 18GHz is subcontracted to Bureau Veritas Shenzhen Co., Ltd. Dongguan Branch Laboratories and found 30dB below the limit at least.


## Annex A. TEST INSTRUMENT

Instrument	Model	Serial #	Cal Date	Cal Due
<b>AC Line Conducted Emissions</b>				
EMI test receiver	ESCS30	8471241027	01/05/2018	01/04/2019
Artificial Mains Network	8127	8127713	01/05/2018	01/04/2019
ISN	ISN T800	34373	01/05/2018	01/04/2019
<b>Radiated Emissions</b>				
EMI test receiver	ESL6	1300.5001K06-100262-eQ	01/05/2018	01/04/2019
Active Antenna	AL-130	121031	02/08/2018	02/07/2019
3m Semi-anechoic Chamber	9m*6m*6m	N/A	10/18/2018	10/17/2019
Signal Amplifier	8447E	443008	01/25/2018	01/24/2019
MXA signal analyzer	N9020A	MY49100060	01/05/2018	01/04/2019
Horn Antenna	HAH-118	71259	01/26/2018	01/25/2019
Horn Antenna	HAH-118	71283	02/02/2018	02/01/2019
AMPLIFIER	EM01G26G	60613	01/25/2018	01/24/2019
AMPLIFIER	Emc012645	980077	01/05/2018	01/04/2019
Bilog Antenna (30MHz~6GHz)	JB6	A110712	02/08/2018	02/07/2019
<b>RF Conducted</b>				
DC Power Supply	E3640A	MY40004013	01/05/2018	01/04/2019
MXA Signal Analyzer	N9020A	MY49100060	01/05/2018	01/04/2019
MXG Vector Signal Generator	N5182A	MY50140530	01/05/2018	01/04/2019
Series Signal Generator	E4421B	US40051152	05/12/2018	05/11/2019
RF control unit	JS0806-0806-2	188060112	04/25/2018	04/24/2019
Wireless Connectivity Tester	CMW270	1201.0002K75-101601-PE	04/25/2018	04/24/2019
Weinschel	1580-1	TL177	01/05/2018	01/04/2019
Universal Radio Communica	CMU200	121393	02/11/2018	02/10/2019


## Annex B. TEST SETUP AND SUPPORTING EQUIPMENT

### Annex B.i. TEST SET UP BLOCK


Block Configuration Diagram for AC Line Conducted Emissions



Block Configuration Diagram for Radiated Emissions ( Below 1GHz ) .



Block Configuration Diagram for Radiated Emissions ( Above 1GHz ) .



## Annex C. ii. SUPPORTING EQUIPMENT DESCRIPTION

The following is a description of supporting equipment and details of cables used with the EUT.

### Supporting Equipment:

Manufacturer	Equipment Description	Model	Serial No
Cedar Kingdom Corporation Limited	Adapter	V-501C	N/A
Cedar Kingdom Corporation Limited	Earphone	V-501C	N/A

### Supporting Cable:

Cable type	Shield Type	Ferrite Core	Length	Serial No
USB Cable	Un-shielding	No	0.8m	N/A

## Annex C. User Manual / Block Diagram / Schematics / Partlist/ DECLARATION OF SIMILARITY

Please see the attachment