

TEST REPORT

FCC ID: 2AKSAMOBULAA-R

Product: Mobile phone

Model No.: S1701

Additional Model No.: Please refer to page 5

Trade Mark: MOBULAA

Report No.: TCT191127E914

Issued Date: Dec. 09, 2019

Issued for:

Shenzhen YLWD Technology Co., Ltd

RM1002.A.Haisong BLD.RD, Tairan.FuTian District, Shenzhen, China

Issued By:

Shenzhen Tongce Testing Lab.

**1B/F., Building 1, Yibaolai Industrial Park, Qiaotou, Fuyong, Baoan District,
Shenzhen, Guangdong, China**

TEL: +86-755-27673339

FAX: +86-755-27673332

This test report was based on TCT190708E005; Change product model No., trade mark and photos.

Note: This report shall not be reproduced except in full, without the written approval of Shenzhen Tongce Testing Lab.

This document may be altered or revised by Shenzhen Tongce Testing Lab. personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample.

TABLE OF CONTENTS

| | |
|--|----------|
| 1. Test Certification | 3 |
| 2. Test Result Summary | 4 |
| 3. EUT Description..... | 5 |
| 4. General Information..... | 7 |
| 4.1. Test environment and mode..... | 7 |
| 4.2. Description of Support Units..... | 7 |
| 5. Facilities and Accreditations | 8 |
| 5.1. Facilities | 8 |
| 5.2. Location | 8 |
| 5.3. Measurement Uncertainty..... | 8 |
| 6. Test Results and Measurement Data | 9 |
| 6.1. Antenna requirement | 9 |
| 6.2. Conducted Emission..... | 10 |
| 6.3. Conducted Output Power | 14 |
| 6.4. 20dB Occupy Bandwidth | 19 |
| 6.5. Carrier Frequencies Separation | 24 |
| 6.6. Hopping Channel Number | 29 |
| 6.7. Dwell Time | 32 |
| 6.8. Pseudorandom Frequency Hopping Sequence | 37 |
| 6.9. Conducted Band Edge Measurement | 38 |
| 6.10. Conducted Spurious Emission Measurement..... | 42 |
| 6.11. Radiated Spurious Emission Measurement | 46 |

Appendix A: Photographs of Test Setup**Appendix B: Photographs of EUT**

1. Test Certification

| | |
|------------------------------|---|
| Product: | Mobile phone |
| Model No.: | S1701 |
| Additional Model No.: | Please refer to page 5 |
| Trade Mark: | MOBULAA |
| Applicant: | Shenzhen YLWD Technology Co., Ltd |
| Address: | RM1002.A.Haisong BLD.RD, Tairan.FuTian District, Shenzhen, China |
| Manufacturer: | Shenzhen YLWD Technology Co., Ltd |
| Address: | RM1002.A.Haisong BLD.RD, Tairan.FuTian District, Shenzhen, China |
| Date of Test: | Jul. 09, 2019 - Aug. 23, 2019 |
| Applicable Standards: | FCC CFR Title 47 Part 15 Subpart C Section 15.247 FCC KDB 558074 D01 15.247 Meas Guidance v05r02 ANSI C63.10:2013 |

The above equipment has been tested by Shenzhen Tongce Testing Lab. and found compliance with the requirements set forth in the technical standards mentioned above. The results of testing in this report apply only to the product/system, which was tested. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Tested By:

Kevin Huang

Date:

Aug. 23, 2019

Reviewed By:

Beryl Zhao

Date:

Dec. 09, 2019

Approved By:

Tomsin

Date:

Dec. 09, 2019

2. Test Result Summary

| Requirement | CFR 47 Section | Result |
|----------------------------------|---------------------|--------|
| Antenna Requirement | §15.203/§15.247 (c) | PASS |
| AC Power Line Conducted Emission | §15.207 | PASS |
| Conducted Peak Output Power | §15.247 (b)(1) | PASS |
| 20dB Occupied Bandwidth | §15.247 (a)(1) | PASS |
| Carrier Frequencies Separation | §15.247 (a)(1) | PASS |
| Hopping Channel Number | §15.247 (a)(1) | PASS |
| Dwell Time | §15.247 (a)(1) | PASS |
| Radiated Emission | §15.205/§15.209 | PASS |
| Band Edge | §15.247(d) | PASS |

Note:

1. PASS: *Test item meets the requirement.*
2. Fail: *Test item does not meet the requirement.*
3. N/A: *Test case does not apply to the test object.*
4. *The test result judgment is decided by the limit of test standard.*

3. EUT Description

| | |
|-------------------------------|---|
| Product: | Mobile phone |
| Model No.: | S1701 |
| Additional Model No.: | S1702, S1703, S1704, S1705, S1706, S1707, S1708, S1709, S1710, S2401, S2402, S2403, S2404, S2405, S2406, S2407, S2408, S2409, S2410, N1701, N1702, N1703, N1704, N1705, N1706, N1707, N1708, N1709, N1710, N2401, N2402, N2403, N2404, N2405, N2406, N2407, N2408, N2409, N2410, Q1701, Q1702, Q1703, Q1704, Q1705, Q1706, Q1707, Q1708, Q1709, Q1710, Q2401, Q2402, Q2403, Q2404, Q2405, Q2406, Q2407, Q2408, Q2409, Q2410, P1701, P1702, P1703, P1704, P1705, P1706, P1707, P1708, P1709, P1710, P2401, P2402, P2403, P2404, P2405, P2406, P2407, P2408, P2409, P2410, R1701, R1702, R1703R1704, R1705, R1706, R1707, R1708, R1709, R1710, R2401, R2402, R2403, R2404, R2405, R2406, R2407, R2408, R2409, R2410, M1701, M1702, M1703, M1704, M1705, M1706, M1707, M1708, M1709, M1710, M2401, M2402, M2403, M2404, M2405, M2406, M2407, M2408, M2409, M2410 |
| Trade Mark: | MOBULAA |
| Bluetooth Version: | V2.1+EDR |
| Operation Frequency: | 2402MHz~2480MHz |
| Transfer Rate: | 1/2/3 Mbits/s |
| Number of Channel: | 79 |
| Modulation Type: | GFSK, π/4-DQPSK, 8DPSK |
| Modulation Technology: | FHSS |
| Antenna Type: | Internal Antenna |
| Antenna Gain: | 1.5dBi |
| Power Supply: | Rechargeable Li-ion Battery DC 3.7V |
| AC adapter: | Adapter Information: MODEL: M1702 INPUT: AC 100-240V, 50/60Hz 0.2A max OUTPUT: DC 5.0V, 350mA |
| Remark: | All models above are identical in interior structure, electrical circuits and components, and just model names are different for the marketing requirement. |

Operation Frequency each of channel for GFSK, $\pi/4$ -DQPSK, 8DPSK

| Channel | Frequency | Channel | Frequency | Channel | Frequency | Channel | Frequency |
|---------|-----------|---------|-----------|---------|-----------|---------|-----------|
| 0 | 2402MHz | 20 | 2422MHz | 40 | 2442MHz | 60 | 2462MHz |
| 1 | 2403MHz | 21 | 2423MHz | 41 | 2443MHz | 61 | 2463MHz |
| ... | ... | ... | ... | ... | ... | ... | ... |
| 10 | 2412MHz | 30 | 2432MHz | 50 | 2452MHz | 70 | 2472MHz |
| 11 | 2413MHz | 31 | 2433MHz | 51 | 2453MHz | 71 | 2473MHz |
| ... | ... | ... | ... | ... | ... | ... | ... |
| 18 | 2420MHz | 38 | 2440MHz | 58 | 2460MHz | 78 | 2480MHz |
| 19 | 2421MHz | 39 | 2441MHz | 59 | 2461MHz | | - |

Remark: Channel 0, 39 & 78 have been tested for GFSK, $\pi/4$ -DQPSK, 8DPSK modulation mode.

4. General Information

4.1. Test environment and mode

| Operating Environment: | | |
|---|--|-------------------|
| Condition | Conducted Emission | Radiated Emission |
| Temperature: | 25.0 °C | 25.0 °C |
| Humidity: | 55 % RH | 55 % RH |
| Atmospheric Pressure: | 1010 mbar | 1010 mbar |
| Test Mode: | | |
| Engineering mode: | Keep the EUT in continuous transmitting by select channel and modulations with Fully-charged battery | |
| <p>The sample was placed 0.8m & 1.5m for the measurement below & above 1GHz above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case(Z axis) are shown in Test Results of the following pages.</p> | | |

4.2. Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

| Equipment | Model No. | Serial No. | FCC ID | Trade Name |
|-----------|-----------|------------|--------|------------|
| / | / | / | / | / |

Note:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.
3. For conducted measurements (Output Power, 20dB Occupied Bandwidth, Carrier Frequencies Separation, Hopping Channel Number, Dwell Time, Spurious Emissions), the antenna of EUT is connected to the test equipment via temporary antenna connector, the antenna connector is soldered on the antenna port of EUT, and the temporary antenna connector is listed in the Test Instruments.

5. Facilities and Accreditations

5.1. Facilities

The test facility is recognized, certified, or accredited by the following organizations:

- FCC - Registration No.: 645098

Shenzhen Tongce Testing Lab

The 3m Semi-anechoic chamber has been registered and fully described in a report with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.

- IC - Registration No.: 10668A-1

The 3m Semi-anechoic chamber of Shenzhen TCT Testing Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing

5.2. Location

Shenzhen Tongce Testing Lab

Address: 1B/F., Building 1, Yibaolai Industrial Park, Qiaotou, Fuyong, Baoan District, Shenzhen, Guangdong, China

Tel: 86-755-27673339


5.3. Measurement Uncertainty

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

| No. | Item | MU |
|-----|-------------------------------|-------------------------|
| 1 | Conducted Emission | $\pm 2.56\text{dB}$ |
| 2 | RF power, conducted | $\pm 0.12\text{dB}$ |
| 3 | Spurious emissions, conducted | $\pm 0.11\text{dB}$ |
| 4 | All emissions, radiated(<1G) | $\pm 3.92\text{dB}$ |
| 5 | All emissions, radiated(>1G) | $\pm 4.28\text{dB}$ |
| 6 | Temperature | $\pm 0.1^\circ\text{C}$ |
| 7 | Humidity | $\pm 1.0\%$ |

6. Test Results and Measurement Data

6.1. Antenna requirement

| Standard requirement: | FCC Part15 C Section 15.203 /247(c) |
|--|--|
| 15.203 requirement: | An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. |
| 15.247(c) (1)(i) requirement: | (i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi. |
| E.U.T Antenna: | The Bluetooth antenna is internal antenna which permanently attached, and the best case gain of the antenna is 1.5dBi. |
|  | |

6.2. Conducted Emission

6.2.1. Test Specification

| Test Requirement: | FCC Part15 C Section 15.207 | | | | | | | | | | | | | | |
|--------------------------|--|--------------------------|--------------|--|------------|---------|----------|-----------|-----------|-------|----|----|------|----|----|
| Test Method: | ANSI C63.10:2013 | | | | | | | | | | | | | | |
| Frequency Range: | 150 kHz to 30 MHz | | | | | | | | | | | | | | |
| Receiver setup: | RBW=9 kHz, VBW=30 kHz, Sweep time=auto | | | | | | | | | | | | | | |
| Limits: | <table border="1"> <thead> <tr> <th rowspan="2">Frequency range (MHz)</th> <th colspan="2">Limit (dBuV)</th> </tr> <tr> <th>Quasi-peak</th> <th>Average</th> </tr> </thead> <tbody> <tr> <td>0.15-0.5</td> <td>66 to 56*</td> <td>56 to 46*</td> </tr> <tr> <td>0.5-5</td> <td>56</td> <td>46</td> </tr> <tr> <td>5-30</td> <td>60</td> <td>50</td> </tr> </tbody> </table> | Frequency range (MHz) | Limit (dBuV) | | Quasi-peak | Average | 0.15-0.5 | 66 to 56* | 56 to 46* | 0.5-5 | 56 | 46 | 5-30 | 60 | 50 |
| Frequency range (MHz) | Limit (dBuV) | | | | | | | | | | | | | | |
| | Quasi-peak | Average | | | | | | | | | | | | | |
| 0.15-0.5 | 66 to 56* | 56 to 46* | | | | | | | | | | | | | |
| 0.5-5 | 56 | 46 | | | | | | | | | | | | | |
| 5-30 | 60 | 50 | | | | | | | | | | | | | |
| Test Setup: | <p>Reference Plane</p> <p>Remark: E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m</p> | | | | | | | | | | | | | | |
| Test Mode: | Charging + transmitting | | | | | | | | | | | | | | |
| Test Procedure: | <ol style="list-style-type: none"> 1. The E.U.T is connected to an adapter through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment. 2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs). 3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10:2013 on conducted measurement. | | | | | | | | | | | | | | |
| Test Result: | PASS | | | | | | | | | | | | | | |

6.2.2. Test Instruments


| Conducted Emission Shielding Room Test Site (843) | | | | |
|---|------------------------|-----------|---------------|-----------------|
| Equipment | Manufacturer | Model | Serial Number | Calibration Due |
| Test Receiver | R&S | ESPI | 101402 | Jul. 29, 2020 |
| LISN | Schwarzbeck | NSLK 8126 | 8126453 | Sep. 11, 2020 |
| Coax cable (9KHz-30MHz) | TCT | CE-05 | N/A | Sep. 08, 2020 |
| EMI Test Software | Shurples Technology | EZ-EMC | N/A | N/A |

Note: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).

6.2.3. Test data

Please refer to following diagram for individual

Conducted Emission on Line Terminal of the power line (150 kHz to 30MHz)



| Site: FCC Part 15C Conduction(QP) | | | | Phase: L1 | Temperature: 25 | | | | |
|-----------------------------------|-----|-----------|--------------------|-------------------|------------------|----------|---------|---------------------|----------------|
| No. | Mk. | Freq. MHz | Reading Level dBμV | Correct Factor dB | Measurement dBμV | Limit dB | Over dB | Power: AC 120V/60Hz | Humidity: 55 % |
| 1 | * | 0.1500 | 43.83 | 10.12 | 53.95 | 66.00 | -12.05 | QP | |
| 2 | | 0.1500 | 26.89 | 10.12 | 37.01 | 56.00 | -18.99 | AVG | |
| 3 | | 0.1723 | 23.07 | 10.12 | 33.19 | 54.85 | -21.66 | AVG | |
| 4 | | 0.1725 | 42.50 | 10.12 | 52.62 | 64.84 | -12.22 | QP | |
| 5 | | 0.4828 | 34.03 | 10.13 | 44.16 | 56.29 | -12.13 | QP | |
| 6 | | 0.5010 | 21.64 | 10.13 | 31.77 | 46.00 | -14.23 | AVG | |
| 7 | | 0.9284 | 17.48 | 10.12 | 27.60 | 46.00 | -18.40 | AVG | |
| 8 | | 0.9600 | 33.61 | 10.12 | 43.73 | 56.00 | -12.27 | QP | |
| 9 | | 2.0129 | 15.76 | 10.12 | 25.88 | 46.00 | -20.12 | AVG | |
| 10 | | 2.0130 | 26.28 | 10.12 | 36.40 | 56.00 | -19.60 | QP | |
| 11 | | 3.5250 | 28.34 | 10.13 | 38.47 | 56.00 | -17.53 | QP | |
| 12 | | 4.0289 | 12.19 | 10.13 | 22.32 | 46.00 | -23.68 | AVG | |

Note:

Freq. = Emission frequency in MHz

Reading level (dB μ V) = Receiver reading

Corr. Factor (dB) = LISN factor + Cable loss

Measurement (dB μ V) = Reading level (dB μ V) + Corr. Factor (dB)

Limit (dB μ V) = Limit stated in standard

Margin (dB) = Measurement (dB μ V) - Limits (dB μ V)


Q.P. = Quasi-Peak

AVG = average

Any value more than 10dB below limit have not been specifically reported.

* is meaning the worst frequency has been tested in the frequency range 150 kHz to 30MHz

Conducted Emission on Neutral Terminal of the power line (150 kHz to 30MHz)



| Site | | | | Phase: | N | | Temperature: | 25 |
|------------------------------------|-----|---------|---------------|----------------|--------------|-------|--------------|---------|
| Limit: FCC Part 15C Conduction(QP) | | | | Power: | AC 120V/60Hz | | Humidity: | 55 % |
| No. | Mk. | Freq. | Reading Level | Correct Factor | Measurement | Limit | Over | |
| | | MHz | dBuV | dB | dBuV | dB | Detector | Comment |
| 1 | | 0.3750 | 24.29 | 10.13 | 34.42 | 58.39 | -23.97 | QP |
| 2 | | 0.3975 | 10.60 | 10.13 | 20.73 | 47.91 | -27.18 | AVG |
| 3 | | 0.4874 | 10.93 | 10.13 | 21.06 | 46.21 | -25.15 | AVG |
| 4 * | | 0.4965 | 26.23 | 10.13 | 36.36 | 56.06 | -19.70 | QP |
| 5 | | 0.8565 | 21.10 | 10.12 | 31.22 | 56.00 | -24.78 | QP |
| 6 | | 0.8608 | 5.95 | 10.12 | 16.07 | 46.00 | -29.93 | AVG |
| 7 | | 0.9688 | 7.03 | 10.12 | 17.15 | 46.00 | -28.85 | AVG |
| 8 | | 0.9825 | 21.76 | 10.12 | 31.88 | 56.00 | -24.12 | QP |
| 9 | | 2.1389 | 3.65 | 10.12 | 13.77 | 46.00 | -32.23 | AVG |
| 10 | | 2.1929 | 16.85 | 10.12 | 26.97 | 56.00 | -29.03 | QP |
| 11 | | 15.8010 | 14.63 | 10.18 | 24.81 | 60.00 | -35.19 | QP |
| 12 | | 15.9809 | 1.23 | 10.18 | 11.41 | 50.00 | -38.59 | AVG |

Note1:

Freq. = Emission frequency in MHz

Reading level (dB μ V) = Receiver reading

Corr. Factor (dB) = LISN factor + Cable loss

Measurement (dB μ V) = Reading level (dB μ V) + Corr. Factor (dB)

Limit (dB μ V) = Limit stated in standard

Margin (dB) = Measurement (dB μ V) – Limits (dB μ V)

Q.P. =Quasi-Peak

AVG =average

Any value more than 10dB below limit have not been specifically reported.


* is meaning the worst frequency has been tested in the frequency range 150 kHz to 30MHz.

Note2:

Measurements were conducted in all three channels (high, middle, low) and three modulation (GFSK, Pi/4DQPSK, 8DPSK), and the worst case Mode (Highest channel and 8DPSK) was submitted only.

6.3. Conducted Output Power

6.3.1. Test Specification

| | |
|--------------------------|---|
| Test Requirement: | FCC Part15 C Section 15.247 (b)(1) |
| Test Method: | KDB 558074 D01 v05r02 |
| Limit: | Section 15.247 (b) The maximum peak conducted output power of the intentional radiator shall not exceed the following: (1) For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band 0.125 watts. |
| Test Setup: |  <p style="text-align: center;">Spectrum Analyzer EUT</p> |
| Test Mode: | Transmitting mode with modulation |
| Test Procedure: | <p>Use the following spectrum analyzer settings: Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel RBW > the 20 dB bandwidth of the emission being measured $VBW \geq RBW$ Sweep = auto Detector function = peak Trace = max hold Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission.</p> |
| Test Result: | PASS |

6.3.2. Test Instruments

| Equipment | Manufacturer | Model | Serial Number | Calibration Due |
|-------------------------|--------------|--------|---------------|-----------------|
| Spectrum Analyzer | Agilent | N9020A | MY49100619 | Sep. 11, 2020 |
| RF Cable (9KHz-26.5GHz) | TCT | RE-06 | N/A | Sep. 11, 2020 |
| Antenna Connector | TCT | RFC-01 | N/A | Sep. 11, 2020 |

Note: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).

6.3.3. Test Data

| GFSK mode | | | |
|--------------|-------------------------|-------------|--------|
| Test channel | Peak Output Power (dBm) | Limit (dBm) | Result |
| Lowest | -2.08 | 30.00 | PASS |
| Middle | -1.10 | 30.00 | PASS |
| Highest | -1.08 | 30.00 | PASS |

| Pi/4DQPSK mode | | | |
|----------------|-------------------------|-------------|--------|
| Test channel | Peak Output Power (dBm) | Limit (dBm) | Result |
| Lowest | -2.10 | 21.00 | PASS |
| Middle | -1.22 | 21.00 | PASS |
| Highest | -1.07 | 21.00 | PASS |


| 8DPSK mode | | | |
|--------------|-------------------------|-------------|--------|
| Test channel | Peak Output Power (dBm) | Limit (dBm) | Result |
| Lowest | -2.14 | 21.00 | PASS |
| Middle | -1.19 | 21.00 | PASS |
| Highest | -1.07 | 21.00 | PASS |

Test plots as follows:


Lowest channel




Middle channel




Highest channel



Lowest channel




Middle channel




Highest channel



Lowest channel



Middle channel




Highest channel



6.4. 20dB Occupy Bandwidth

6.4.1. Test Specification

| | |
|--------------------------|---|
| Test Requirement: | FCC Part15 C Section 15.247 (a)(1) |
| Test Method: | KDB 558074 D01 v05r02 |
| Limit: | N/A |
| Test Setup: |  <p style="text-align: center;">Spectrum Analyzer EUT</p> |
| Test Mode: | Transmitting mode with modulation |
| Test Procedure: | <ol style="list-style-type: none"> 1. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement. 2. Set to the maximum power setting and enable the EUT transmit continuously. 3. Use the following spectrum analyzer settings for 20dB Bandwidth measurement. Span = approximately 2 to 5 times the 20 dB bandwidth, centered on a hopping channel; $1\% \leq RBW \leq 5\%$ of the 20 dB bandwidth; $VBW \geq 3RBW$; Sweep = auto; Detector function = peak; Trace = max hold. 4. Measure and record the results in the test report. |
| Test Result: | PASS |

6.4.2. Test Instruments

| Equipment | Manufacturer | Model | Serial Number | Calibration Due |
|-------------------------|--------------|--------|---------------|-----------------|
| Spectrum Analyzer | Agilent | N9020A | MY49100619 | Sep. 11, 2020 |
| RF Cable (9KHz-26.5GHz) | TCT | RE-06 | N/A | Sep. 11, 2020 |
| Antenna Connector | TCT | RFC-01 | N/A | Sep. 11, 2020 |

Note: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).

6.4.3. Test data

| Test channel | 20dB Occupy Bandwidth (kHz) | | | |
|--------------|-----------------------------|----------------|-------|------------|
| | GFSK | $\pi/4$ -DQPSK | 8DPSK | Conclusion |
| Lowest | 889.3 | 1187 | 1215 | PASS |
| Middle | 912.8 | 1221 | 1190 | PASS |
| Highest | 885.4 | 1179 | 1211 | PASS |

Test plots as follows:

Lowest channel




Middle channel



Highest channel



Lowest channel



Middle channel



Highest channel



Lowest channel



Middle channel



Highest channel



6.5. Carrier Frequencies Separation

6.5.1. Test Specification

6.5.2. Test Instruments

| Equipment | Manufacturer | Model | Serial Number | Calibration Due |
|----------------------------|--------------|--------|---------------|-----------------|
| Spectrum Analyzer | Agilent | N9020A | MY49100619 | Sep. 11, 2020 |
| RF Cable (9KHz-26.5GHz) | TCT | RE-06 | N/A | Sep. 11, 2020 |
| Antenna Connector | TCT | RFC-01 | N/A | Sep. 11, 2020 |

Note: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).

6.5.3. Test data

| GFSK mode | | | |
|--------------|--------------------------------------|-------------|--------|
| Test channel | Carrier Frequencies Separation (kHz) | Limit (kHz) | Result |
| Lowest | 1000 | 912.8 | PASS |
| Middle | 1000 | 912.8 | PASS |
| Highest | 1000 | 912.8 | PASS |

| Pi/4 DQPSK mode | | | |
|-----------------|--------------------------------------|-------------|--------|
| Test channel | Carrier Frequencies Separation (kHz) | Limit (kHz) | Result |
| Lowest | 1000 | 814.0 | PASS |
| Middle | 1000 | 814.0 | PASS |
| Highest | 1000 | 814.0 | PASS |

| 8DPSK mode | | | |
|--------------|--------------------------------------|-------------|--------|
| Test channel | Carrier Frequencies Separation (kHz) | Limit (kHz) | Result |
| Lowest | 1000 | 810.0 | PASS |
| Middle | 1000 | 810.0 | PASS |
| Highest | 1000 | 810.0 | PASS |

Note: According to section 6.4


| Mode | 20dB bandwidth (kHz) (worse case) | Limit (kHz) (Carrier Frequencies Separation) |
|----------------|--------------------------------------|---|
| GFSK | 912.8 | 912.8 |
| $\pi/4$ -DQPSK | 1221 | 814.0 |
| 8DPSK | 1215 | 810.0 |

Test plots as follows:


Lowest channel



Middle channel



Highest channel




Pi/4DQPSK Modulation

Lowest channel




Middle channel



Highest channel



Lowest channel



Middle channel



Highest channel



6.6. Hopping Channel Number

6.6.1. Test Specification


6.6.2. Test Instruments

| Equipment | Manufacturer | Model | Serial Number | Calibration Due |
|----------------------------|--------------|--------|---------------|-----------------|
| Spectrum Analyzer | Agilent | N9020A | MY49100619 | Sep. 11, 2020 |
| RF Cable (9KHz-26.5GHz) | TCT | RE-06 | N/A | Sep. 11, 2020 |
| Antenna Connector | TCT | RFC-01 | N/A | Sep. 11, 2020 |


Note: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).

6.6.3. Test data


| Mode | Hopping channel numbers | Limit | Result |
|------------------------|-------------------------|-------|--------|
| GFSK, Pi/4DQPSK, 8DPSK | 79 | 15 | PASS |

Test plots as follows:


GFSK



Pi/4DQPSK



8DPSK



6.7. Dwell Time

6.7.1. Test Specification

6.7.2. Test Instruments

| Equipment | Manufacturer | Model | Serial Number | Calibration Due |
|----------------------------|--------------|--------|---------------|-----------------|
| Spectrum Analyzer | Agilent | N9020A | MY49100619 | Sep. 11, 2020 |
| RF Cable (9KHz-26.5GHz) | TCT | RE-06 | N/A | Sep. 11, 2020 |
| Antenna Connector | TCT | RFC-01 | N/A | Sep. 11, 2020 |

Note: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).

6.7.3. Test Data

| Mode | Packet | Hops Over Occupancy Time (hops) | Package Transfer Time (ms) | Dwell time (second) | Limit (second) | Result |
|------------|--------|---------------------------------|----------------------------|---------------------|----------------|--------|
| GFSK | DH1 | 320 | 0.398 | 0.127 | 0.4 | PASS |
| GFSK | DH3 | 160 | 1.659 | 0.265 | 0.4 | PASS |
| GFSK | DH5 | 106.67 | 2.936 | 0.313 | 0.4 | PASS |
| Pi/4 DQPSK | 2-DH1 | 320 | 0.396 | 0.127 | 0.4 | PASS |
| Pi/4 DQPSK | 2-DH3 | 160 | 1.665 | 0.266 | 0.4 | PASS |
| Pi/4 DQPSK | 2-DH5 | 106.67 | 2.916 | 0.311 | 0.4 | PASS |
| 8DPSK | 3-DH1 | 320 | 0.402 | 0.129 | 0.4 | PASS |
| 8DPSK | 3-DH3 | 160 | 1.674 | 0.268 | 0.4 | PASS |
| 8DPSK | 3-DH5 | 106.67 | 2.952 | 0.315 | 0.4 | PASS |

Note: 1. In normal mode, hopping rate is 1600 hops/s in 79 hopping channels.

For DH1, With channel hopping rate $(1600 / 2 / 79)$ in Occupancy Time Limit (0.4×79) (s), Hops Over Occupancy Time comes to $(1600 / 2 / 79) \times (0.4 \times 79) = 320$ hops

For DH3, With channel hopping rate $(1600 / 4 / 79)$ in Occupancy Time Limit (0.4×79) (s), Hops Over Occupancy Time comes to $(1600 / 4 / 79) \times (0.4 \times 79) = 160$ hops

For DH5, With channel hopping rate $(1600 / 6 / 79)$ in Occupancy Time Limit (0.4×79) (s), Hops Over Occupancy Time comes to $(1600 / 6 / 79) \times (0.4 \times 79) = 106.67$ hops


2. Dwell Time(s) = Hops Over Occupancy Time (hops) x Package Transfer Time

Test plots as follows:


GFSK
DH1



DH3




DH5




Pi/4DQPSK


2-DH1



2-DH3




2-DH5




8DPSK


3-DH1



3-DH3



3-DH5



6.8. Pseudorandom Frequency Hopping Sequence

| Test Requirement: | FCC Part15 C Section 15.247 (a)(1) requirement: |
|-------------------|---|
|-------------------|---|


Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

Alternatively. Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a Pseudorandom ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

EUT Pseudorandom Frequency Hopping Sequence


The pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first one of 9 consecutive ones; i.e. the shift register is initialized with nine ones.

- Number of shift register stages: 9
- Length of pseudo-random sequence: $2^9 - 1 = 511$ bits
- Longest sequence of zeros: 8 (non-inverted signal)



Linear Feedback Shift Register for Generation of the PRBS sequence

An example of Pseudorandom Frequency Hopping Sequence as follow:



Each frequency used equally on the average by each transmitter.

The system receivers have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shift frequencies in synchronization with the transmitted signals.