

FCC ID : 2AKSNS

According to KDB 447498 D01 General RF Exposure Guidance

At 100 MHz to 6 GHz and for test separation distances \leq 50 mm, the SAR test exclusion threshold is determined according to the following

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \times [\sqrt{f_{(\text{GHz})}}] \leq 3.0$$

1. SAR test exclusion threshold

Frequency : 2 480 MHz (min. separation distances = 0 mm)

SAR test exclusion thresholds(5 mm) = $3 \times 5 / (\sqrt{2.480}) = 9.525 \text{ mW}$

| Max. tune-up tolerance(mW) | SAR Test Exclusion Thresholds(5 mm) (mW) |
|----------------------------|--|
| 1 | 9.525 |

Calculation value : $1 \text{ (mW)} / 5 \text{ (mm)} \times \sqrt{2.480} = 0.31$

So, Calculation value \leq 3.0

Remark:

-Max. conducted power (mW) : maximum tolerance power of EUT (-4 dBm)

-Max. conducted power 0.40 (mW) is closest 1 (mW), so 1 (mW) was calculated.

-When the minimum test separation distance is $< 5 \text{ mm}$, a distance of 5 mm is applied to determine SAR test exclusion.

2. Conclusion : No SAR is required.