




11AX40SISO-Ant1-5230-PASS



11AX40SISO-Ant1-5755-PASS



11AX40SISO-Ant1-5795-PASS

8.4 UNDESIRABLE RADIATED SPURIOUS EMISSION

8.4.1 Applicable Standard

According to FCC Part 15.407 (b)
According to 789033 D02 Section II(G)

8.4.2 Conformance Limit

For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

For transmitters operating in the 5.725-5.85 GHz band: All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

The emission measurements shall be performed using a minimum resolution bandwidth of 1 MHz. A lower resolution bandwidth may be employed near the band edge, when necessary, provided the measured energy is integrated to show the total power over 1 MHz.

Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in §15.209. The emissions from an intentional radiator shall not exceed the field strength levels specified in the following table 15.209(a):

Restricted Frequency(MHz)	Field Strength (μV/m)	Field Strength (dBμV/m)	Measurement Distance
0.009-0.490	2400/F(KHz)	20 log (uV/m)	300
0.490-1.705	24000/F(KHz)	20 log (uV/m)	30
1.705-30	30	29.5	30
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

The provisions of §15.205 apply to intentional radiators operating under this section, 15.205 Restricted bands of operation

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(2)
13.36-13.41			

Remark: 1. Emission level in dBuV/m=20 log (uV/m)
2. Measurement was performed at an antenna to the closed point of EUT distance of meters.

3. Only spurious frequency is permitted to locate within the Restricted Bands specified in provision of 15.205, and the emissions located in restricted bands also comply with 15.209 limit.

8.4.3 Test Configuration

Test according to clause 6.2 radio frequency test setup

8.4.4 Test Procedure

■ Unwanted Emissions Measurements below 1000 MHz

Compliance shall be demonstrated using CISPR quasi-peak detection; however, peak detection is permitted as an alternative to quasi-peak detection.

The EUT was placed on a turn table which is 0.8m above ground plane.

And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.

Repeat above procedures until all frequency measured was complete.

We use software control the EUT, Let EUT hopping on and transmit with highest power, All the modes have been tested and the worst result was reported.

Use the following spectrum analyzer settings:

Set RBW=120kHz for $f < 1$ GHz(30MHz to 1GHz), 200Hz for $f < 150$ KHz(9KHz to 150KHz), 9KHz for < 30 MHz

(150KHz to 30KHz).

Set the VBW > RBW.

Detector = Peak.

Trace mode = max hold.

Follow the guidelines in ANSI C63.10-2013 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization, etc. A pre-amp and a high pass filter are required for this test, in order to provide the measuring system with sufficient sensitivity. Allow the trace to stabilize. The peak reading of the emission, after being corrected by the antenna factor, cable loss, pre-amp gain, etc., is the peak field strength, which must comply with the limit specified in Section 15.35(b). Submit this data.

Repeat above procedures until all frequency measured was complete.

■ Unwanted Maximum peak Emissions Measurements above 1000 MHz

Maximum emission levels are measured by setting the analyzer as follows:

RBW = 1 MHz.

VBW $\geq$ 3 MHz.

Detector = Peak.

Sweep time = auto.

Trace mode = max hold.

Allow sweeps to continue until the trace stabilizes. Note that if the transmission is not continuous, the time required for the trace to stabilize will increase by a factor of approximately $1/x$, where x is the duty cycle. For example, at 50 percent duty cycle, the measurement time will increase by a factor of two relative to measurement time for continuous transmission.

■ Unwanted Average Emissions Measurements above 1000 MHz

Method VB (Averaging using reduced video bandwidth): Alternative method.

RBW = 1 MHz.

Video bandwidth. • If the EUT is configured to transmit with duty cycle $\geq$ 98 percent, set $VBW \leq RBW/100$ (i.e., 10 kHz) but not less than 10 Hz.

• If the EUT duty cycle is < 98 percent, set $VBW \geq 1/T$, where T is defined in section II.B.1.a).

Video bandwidth mode or display mode • The instrument shall be set to ensure that video filtering is applied in the power domain. Typically, this requires setting the detector mode to RMS and setting the Average-VBW Type to Power (RMS).

• As an alternative, the analyzer may be set to linear detector mode. Ensure that video filtering is applied in linear voltage domain (rather than in a log or dB domain). Some analyzers require linear display mode in order to accomplish this. Others have a setting for Average-VBW Type, which can be set to "Voltage" regardless of the display mode.

Detector = Peak.

Sweep time = auto.

Trace mode = max hold.

Allow max hold to run for at least 50 traces if the transmitted signal is continuous or has at least 98 percent duty cycle. For lower duty cycles, increase the minimum number of traces by a factor of $1/x$, where x is the duty cycle. For example, use at least 200 traces if the duty cycle is 25 percent. (If a specific emission is demonstrated to be continuous—i.e., 100 percent duty cycle—rather than turning on and off with the transmit cycle, at least 50 traces shall be averaged.)

■ Band edge measurements.

Unwanted band-edge emissions may be measured using either of the special band-edge measurement techniques (the marker-delta or integration methods) described below. Note that the marker-delta method is primarily a radiated measurement technique that requires the 99% occupied bandwidth edge to be within 2 MHz of the authorized band edge, whereas the integration method can be used in either a radiated or conducted measurement without any special requirement with regards to the displacement of the unwanted emission(s) relative to the authorized bandwidth.

Marker-Delta Method.

The marker-delta method, as described in ANSI C63.10, can be used to perform measurements of the radiated unwanted emissions level of emissions provided that the 99% occupied bandwidth of the fundamental is within 2 MHz of the authorized band-edge.

8.4.5 Test Results

The voltage AC120V and the modes 802.11a/n/ac/ax has been tested and the worst result recorded as below

- ☒ For Undesirable radiated Spurious Emission in U-NII – 1
All the modes 802.11a/n/ac/ax has been tested and the worst result 802.11a recorded as below:
: ☒ Undesirable radiated Spurious Emission Above 1GHz (1GHz to 40GHz)

Test mode:		802.11a		Frequency(MHz):		5180	
Freq. (MHz)	Ant.Pol. H/V	Field Strength (dBuV/m)	E.I.R.P (dBm)	Limit (dBm)	Margin(d B)		
8083.416	V	54.25	-40.98	-27	13.98		
11501.61	V	59.35	-35.88	-27	8.88		
17602.97	V	64.68	-30.55	-27	3.55		
7304.370	H	53.63	-41.60	-27	14.60		
10041.53	H	59.57	-35.66	-27	8.66		
17985.99	H	67.14	-28.09	-27	1.09		

Test mode:		802.11a		Frequency(MHz):		5200	
Freq. (MHz)	Ant.Pol. H/V	Field Strength (dBuV/m)	E.I.R.P (dBm)	Limit (dBm)	Margin(d B)		
8101.417	V	55.17	-40.06	-27	13.06		
10743.57	V	58.87	-36.36	-27	9.36		
17988.99	V	67.05	-28.18	-27	1.18		
8256.426	H	54.86	-40.37	-27	13.37		
11340.60	H	59.85	-35.38	-27	8.38		
17998.99	H	66.88	-28.35	-27	1.35		

Test mode:		802.11a		Frequency(MHz):		5240	
Freq. (MHz)	Ant.Pol. H/V	Field Strength (dBuV/m)	E.I.R.P (dBm)	Limit (dBm)	Margin(d B)		
8254.426	V	55.34	-39.89	-27	12.89		
10718.57	V	60.03	-35.20	-27	8.20		
17991.99	V	67.68	-27.55	-27	0.55		
8202.423	H	55.18	-40.05	-27	13.05		
11569.62	H	59.63	-35.60	-27	8.60		
17990.99	H	67.24	-27.99	-27	0.99		

Note: (1) All Readings are Peak Value (VBW=3MHz) and AV Value (VBW=10Hz).
(2) Emission Level= Reading Level+Probe Factor +Cable Loss.
(3) EIRP[dBm] = E[dBμV/m] + 20 log(d[meters]) - 104.77
d is the measurement distance in 3 meters

Frequency: 5180

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Margin (dB)	
		PK	AV	PK	AV	PK	AV
8083.4167	V	54.25	39.35	74	54	19.75	14.65
11501.6177	V	59.35	43.65	74	54	14.65	10.35
17602.9766	V	64.68	45.26	74	54	9.32	8.74
7304.3708	H	53.63	39.75	74	54	20.37	14.25
10041.5319	H	59.57	41.76	74	54	14.43	12.24
17985.9992	H	67.14	46.38	74	54	6.86	7.62

Frequency: 5200

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Margin (dB)	
		PK	AV	PK	AV	PK	AV
8101.4177	V	55.17	39.98	74	54	18.83	14.02
10743.5732	V	58.87	43.40	74	54	15.13	10.60
17988.9994	V	67.05	46.74	74	54	6.95	7.26
8256.4268	H	54.86	39.68	74	54	19.14	14.32
11340.6083	H	59.85	41.75	74	54	14.15	12.25
17998.9999	H	66.88	47.02	74	54	7.12	6.98

Frequency: 5240

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Margin (dB)	
		PK	AV	PK	AV	PK	AV
8254.4267	V	55.34	39.50	74	54	18.66	14.50
10718.5717	V	60.03	43.73	74	54	13.97	10.27
17991.9995	V	67.68	46.66	74	54	6.32	7.34
8202.4237	H	55.18	39.18	74	54	18.82	14.82
11569.6217	H	59.63	42.56	74	54	14.37	11.44
17990.9995	H	67.24	46.79	74	54	6.76	7.21

Note: (1) All Readings are Peak Value (VBW=3MHz) and AV Value (VBW=10Hz).
(2) Emission Level= Reading Level+Correct Factor +Cable Loss.
(3) Correct Factor= Ant_F + Cab_L - Preamp
(4) The reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

● ☒ Undesirable radiated Undesirable radiated Spurious Emission in Band Edge

Test mode: 802.11ax Frequency(MHz): 5180

Freq. (MHz)	Ant.Pol. H/V	Field Strength (RBW=100KHz) (dBuV/m)	E.I.R.P (dBm)	Limit (dBm)	Verdict
5115.22	V	54.27	-40.96	-27	Pass
5146.66	H	54.09	-41.14	-27	Pass

Test mode: 802.11ax Frequency(MHz): 5240

Freq. (MHz)	Ant.Pol. H/V	Field Strength (RBW=100KHz) (dBuV/m)	E.I.R.P (dBm)	Limit (dBm)	Verdict
5352.04	V	54.16	-41.07	-27	Pass
5353.25	H	54.59	-40.64	-27	Pass

Note: (1) All Readings are Peak Value (VBW=3MHz) and AV Value (VBW=10Hz).
 (2) Emission Level= Reading Level+Correct Factor +Cable Loss.
 (3) Correct Factor= Ant_F + Cab_L - Preamp
 (4) EIRP[dBm] = E[dBuV/m] + 20 log(d[meters]) - 104.77
 d is the measurement distance in 3 meters

Test mode: 802.11ax Frequency(MHz): 5180

Frequency (MHz)	Polarity	PK(dBuV/m) (VBW=3MHz)	Limit 3m (dBuV/m)	AV(dBuV/m) (VBW=10Hz)	Limit 3m (dBuV/m)
5115.22	V	54.27	74.00	46.75	54.00
5146.66	H	54.09	74.00	47.17	54.00

Test mode: 802.11ax Frequency(MHz): 5240

Frequency (MHz)	Polarity	PK(dBuV/m) (VBW=3MHz)	Limit 3m (dBuV/m)	AV(dBuV/m) (VBW=10Hz)	Limit 3m (dBuV/m)
5352.04	V	54.16	74.00	47.30	54.00
5353.25	H	54.59	74.00	47.88	54.00


Note: (1) All Readings are Peak Value (VBW=3MHz) and AV Value (VBW=10Hz).
 (2) Emission Level= Reading Level+Correct Factor +Cable Loss.
 (3) Correct Factor= Ant_F + Cab_L - Preamp
 (4) Data of measurement within this frequency range shown " -- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

U-NII - 1

Test Model Undesirable radiated Spurious Emission in Restricted Band (5100-5150MHz)

☒ 802.11ax ☐ 802.11n(HT20) ☐ 802.11n(HT40)

☒ 5180 ☐ 5200 ☐ 5240 Ant.Pol H




U-NII - 1


Test Model Undesirable radiated Spurious Emission in Restricted Band (5100-5150MHz)

☒ 802.11ax ☐ 802.11n(HT20) ☐ 802.11n(HT40)


☒ 5180 ☐ 5200 ☐ 5240 Ant.Pol V



U-NII - 1				
Test Model	Undesirable radiated Spurious Emission in Restricted Band (5350-5400MHz)			
	☒ 802.11ax	☐ 802.11n(HT20)	☐ 802.11n(HT40)	
	☐ 5180	☐ 5200	☒ 5240	Ant.Pol H



U-NII - 1				
Test Model	Undesirable radiated Spurious Emission in Restricted Band (5350-5400MHz)			
	☒ 802.11ax	☐ 802.11n(HT20)	☐ 802.11n(HT40)	
	☐ 5180	☐ 5200	☒ 5240	Ant.Pol V



■ For Undesirable radiated Spurious Emission in U-NII -3

☑ Undesirable radiated Spurious Emission Above 1GHz (1GHz to 40GHz)

All the modes 802.11a/n/ac/ax has been tested and the worst result 802.11a recorded as below:

Test mode: 802.11a Frequency(MHz): 5745

Freq. (MHz)	Ant.Pol. H/V	Field Strength (dBuV/m)	E.I.R.P (dBm)	Limit (dBm)	Over(dB)
7858.4034	V	54.21	-41.02	-27	14.02
10904.5826	V	59.21	-36.02	-27	9.02
17988.9994	V	66.70	-28.53	-27	1.53
9669.51	H	57.40	-37.83	-27	10.83
13084.7109	H	61.46	-33.77	-27	6.77
17978.9988	H	67.06	-28.17	-27	1.17

Test mode: 802.11a Frequency(MHz): 5785

Freq. (MHz)	Ant.Pol. H/V	Field Strength (dBuV/m)	E.I.R.P (dBm)	Limit (dBm)	Over(dB)
8915.4656	V	55.30	-39.93	-27	12.93
12793.6937	V	62.06	-33.17	-27	6.17
17993.9996	V	66.68	-28.55	-27	1.55
7843.4026	H	54.14	-41.09	-27	14.09
12015.648	H	59.35	-35.88	-27	8.88
17998.9999	H	66.21	-29.02	-27	2.02

Test mode: 802.11a Frequency(MHz): 5825

Freq. (MHz)	Ant.Pol. H/V	Field Strength (dBuV/m)	E.I.R.P (dBm)	Limit (dBm)	Over(dB)
7307.371	V	53.33	-41.9	-27	14.90
10724.572	V	59.19	-36.04	-27	9.04
17987.9993	V	66.80	-28.43	-27	1.43
8220.4247	H	56.18	-39.05	-27	12.05
11563.6214	H	59.34	-35.89	-27	8.89
17994.9997	H	67.23	-28.00	-27	1.00

Note: (1) All Readings are Peak Value (VBW=3MHz) and AV Value (VBW=10Hz).

(2) Emission Level= Reading Level+Probe Factor +Cable Loss.

(3) EIRP[dBm] = E[dBuV/m] + 20 log(d[meters]) - 104.77

d is the measurement distance in 3 meters

Test mode: 802.11a		Frequency(MHz): 5745			
Freq. (MHz)	Ant.Pol.	Emission Level(dBuV/m)	Limit 3m(dBuV/m)	Over(dB)	Detector
7858.4034	V	54.21	74.00	19.79	Peak
10904.5826	V	59.21	74.00	14.79	Peak
17988.9994	V	66.70	74.00	7.30	Peak
7858.4034	V	38.90	54.00	15.10	Avg
10904.5826	V	41.78	54.00	12.22	Avg
17988.9994	V	46.75	54.00	7.25	Avg
9669.51	H	57.40	74.00	16.60	Peak
13084.7109	H	61.46	74.00	12.54	Peak
17978.9988	H	67.06	74.00	6.94	Peak
9669.51	H	42.49	54.00	11.51	Avg
13084.7109	H	46.19	54.00	7.81	Avg
17978.9988	H	46.20	54.00	7.80	Avg

Test mode: 802.11a		Frequency(MHz): 5785			
Freq. (MHz)	Ant.Pol.	Emission Level(dBuV/m)	Limit 3m(dBuV/m)	Over(dB)	Detector
8915.4656	V	55.30	74.00	18.70	Peak
12793.6937	V	62.06	74.00	11.94	Peak
17993.9996	V	66.68	74.00	7.32	Peak
8915.4656	V	42.25	54.00	11.75	Avg
12793.6937	V	46.85	54.00	7.15	Avg
17993.9996	V	46.78	54.00	7.22	Avg
7843.4026	H	54.14	74.00	19.86	Peak
12015.648	H	59.35	74.00	14.65	Peak
17998.9999	H	66.21	74.00	7.79	Peak
7843.4026	H	38.76	54.00	15.24	Avg
12015.648	H	42.97	54.00	11.03	Avg
17998.9999	H	47.02	54.00	6.98	Avg

Test mode: 802.11a		Frequency(MHz): 5825			
Freq. (MHz)	Ant.Pol.	Emission Level(dBuV/m)	Limit 3m(dBuV/m)	Over(dB)	Detector
7307.371	V	53.33	74.00	20.67	Peak
10724.572	V	59.19	74.00	14.81	Peak
17987.9993	V	66.80	74.00	7.20	Peak
7307.371	V	38.95	54.00	15.05	Avg
10724.572	V	44.00	54.00	10.00	Avg
17987.9993	V	47.26	54.00	6.74	Avg
8220.4247	H	56.18	74.00	17.82	Peak
11563.6214	H	59.34	74.00	14.66	Peak
17994.9997	H	67.23	74.00	6.77	Peak
8220.4247	H	38.81	54.00	15.19	Avg
11563.6214	H	42.62	54.00	11.38	Avg
17994.9997	H	46.89	54.00	7.11	Avg

- Note:**
- (1) All Readings are Peak Value (VBW=3MHz) and Peak Value (VBW=10Hz).
 - (2) Emission Level= Reading Level+Correct Factor +Cable Loss.
 - (3) Correct Factor= Ant_F + Cab_L - Preamp
 - (4) The reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.


● ☒ Undesirable radiated Spurious Emission in band edge

Test mode:		802.11ax(20)		Frequency:		5745	
Freq. (MHz)	Ant.Pol. H/V	Field Strength (RBW=100KHz) (dBuV/m)		E.I.R.P (dBm)		Limit (dBm)	Verdict
5722.87	V	73.20		-22.03		-27	PASS
5721.74	H	72.85		-22.38		-27	PASS


Test mode:		802.11ax(20)		Frequency:		5825	
Freq. (MHz)	Ant.Pol. H/V	Field Strength (RBW=100KHz) (dBuV/m)		E.I.R.P (dBm)		Limit (dBm)	Verdict
5850.68	V	71.20		-24.03		-27	PASS
5850.50	H	68.71		-26.52		-27	PASS

Note: (1) All Readings are Peak Value (VBW=3MHz) and Peak Value (VBW=10Hz).
 (2) Emission Level= Reading Level+Correct Factor +Cable Loss.
 (3) Correct Factor= Ant_F + Cab_L - Preamp
 (4) EIRP[dBm] = E[dBuV/m] + 20 log(d[meters]) - 104.77
 d is the measurement distance in 3 meters


Test Model U-NII -3
Undesirable radiated ☒ 802.11ax Undesirable radiated ☒ 5745 Spurious Emission in Band Edge ☐ 802.11n(HT20) ☐ 802.11n(HT40)
Ant.Pol V




Test Model U-NII -3
Undesirable radiated ☒ 802.11ax Undesirable radiated ☒ 5745 Spurious Emission in Band Edge ☐ 802.11n(HT20) ☐ 802.11n(HT40)
Ant.Pol H



Test Model U-NII -3
Undesirable radiated Undesirable radiated Spurious Emission in Band Edge
☒ 802.11ax ☐ 802.11n(HT20) ☐ 802.11n(HT40)
☒ 5825 Ant.Pol V




Test Model U-NII -3
Undesirable radiated Undesirable radiated Spurious Emission in Band Edge
☒ 802.11ax ☐ 802.11n(HT20) ☐ 802.11n(HT40)
☒ 5825 Ant.Pol H



- Undesirable radiated Spurious Emission below 1GHz (30MHz to 1GHz)
All the modes 802.11a/n has been tested and the worst result 802.11a recorded as below:

5180




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Detector	Limit [dBμV/m]	Margin [dB]	Polarity
1	30.971	36.17	-18.67	17.50	PK	40.00	22.50	Vertical
2	67.8679	35.72	-18.48	17.24	PK	40.00	22.76	Vertical
3	473.7337	33.24	-10.03	23.21	PK	46.00	22.79	Vertical
4	599.96	35.23	-6.10	29.13	PK	46.00	16.87	Vertical
5	708.7087	31.20	-5.80	25.40	PK	46.00	20.60	Vertical
6	840.7608	30.68	-4.33	26.35	PK	46.00	19.65	Vertical

Final Data List

NO.	Freq. [MHz]	Factor [dB/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]
1	30.971	-18.67	16.70	40.00	23.30
2	67.8679	-18.48	16.80	40.00	23.20
3	473.7337	-10.03	23.13	46.00	22.87
4	599.96	-6.10	29.05	46.00	16.95
5	708.7087	-5.80	25.15	46.00	20.85
6	840.7608	-4.33	25.46	46.00	20.54




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Detector	Limit [dBμV/m]	Margin [dB]	Polarity
1	30.971	36.35	-18.67	17.68	PK	40.00	22.32	Horizontal
2	55.2452	33.13	-16.74	16.39	PK	40.00	23.61	Horizontal
3	406.7367	35.91	-11.45	24.46	PK	46.00	21.54	Horizontal
4	599.96	30.91	-6.10	24.81	PK	46.00	21.19	Horizontal
5	712.5926	32.74	-5.77	26.97	PK	46.00	19.03	Horizontal
6	799.98	35.72	-5.11	30.61	PK	46.00	15.39	Horizontal

Final Data List

NO.	Freq. [MHz]	Factor [dB/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]
1	30.971	-18.67	17.55	40.00	22.45
2	55.2452	-16.74	15.62	40.00	24.38
3	406.7367	-11.45	23.52	46.00	22.48
4	599.96	-6.10	23.87	46.00	22.13
5	712.5926	-5.77	26.39	46.00	19.61
6	799.98	-5.11	30.03	46.00	15.97

5200




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Detector	Limit [dBμV/m]	Margin [dB]	Polarity
1	30.971	35.69	-18.67	17.02	PK	40.00	22.98	Vertical
2	47.4775	33.04	-16.39	16.65	PK	40.00	23.35	Vertical
3	51.3614	33.30	-16.21	17.09	PK	40.00	22.91	Vertical
4	599.96	36.04	-6.10	29.94	PK	46.00	16.06	Vertical
5	620.3504	32.32	-7.28	25.04	PK	46.00	20.96	Vertical
6	813.5736	31.56	-4.81	26.75	PK	46.00	19.25	Vertical

Final Data List

NO.	Freq. [MHz]	Factor [dB/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]
1	30.971	-18.67	16.06	40.00	23.94
2	47.4775	-16.39	15.69	40.00	24.31
3	51.3614	-16.21	16.97	40.00	23.03
4	599.96	-6.10	29.18	46.00	16.82
5	620.3504	-7.28	24.28	46.00	21.72
6	813.5736	-4.81	25.99	46.00	20.01




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Detector	Limit [dBμV/m]	Margin [dB]	Polarity
1	30.971	35.17	-18.67	16.50	PK	40.00	23.50	Horizontal
2	54.2743	33.11	-16.60	16.51	PK	40.00	23.49	Horizontal
3	406.7367	35.89	-11.45	24.44	PK	46.00	21.56	Horizontal
4	599.96	30.99	-6.10	24.89	PK	46.00	21.11	Horizontal
5	712.5926	33.59	-5.77	27.82	PK	46.00	18.18	Horizontal
6	799.98	34.46	-5.11	29.35	PK	46.00	16.65	Horizontal

Final Data List

NO.	Freq. [MHz]	Factor [dB/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]
1	30.971	-18.67	16.16	40.00	23.84
2	54.2743	-16.60	15.53	40.00	24.47
3	406.7367	-11.45	24.29	46.00	21.71
4	599.96	-6.10	24.74	46.00	21.26
5	712.5926	-5.77	27.03	46.00	18.97
6	799.98	-5.11	28.92	46.00	17.08

5240




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Detector	Limit [dBμV/m]	Margin [dB]	Polarity
1	30.971	34.77	-18.67	16.10	PK	40.00	23.90	Vertical
2	45.5355	32.89	-16.66	16.23	PK	40.00	23.77	Vertical
3	57.1872	33.77	-17.00	16.77	PK	40.00	23.23	Vertical
4	599.96	35.53	-6.10	29.43	PK	46.00	16.57	Vertical
5	609.6697	32.08	-6.65	25.43	PK	46.00	20.57	Vertical
6	808.7187	31.47	-4.90	26.57	PK	46.00	19.43	Vertical

Final Data List

NO.	Freq. [MHz]	Factor [dB/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]
1	30.971	-18.67	16.09	40.00	23.91
2	45.5355	-16.66	16.22	40.00	23.78
3	57.1872	-17.00	16.60	40.00	23.40
4	599.96	-6.10	28.62	46.00	17.38
5	609.6697	-6.65	24.62	46.00	21.38
6	808.7187	-4.90	25.59	46.00	20.41



Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Detector	Limit [dBμV/m]	Margin [dB]	Polarity
1	30.971	34.82	-18.67	16.15	PK	40.00	23.85	Horizontal
2	54.2743	33.55	-16.60	16.95	PK	40.00	23.05	Horizontal
3	406.7367	35.30	-11.45	23.85	PK	46.00	22.15	Horizontal
4	599.96	31.30	-6.10	25.20	PK	46.00	20.80	Horizontal
5	712.5926	34.09	-5.77	28.32	PK	46.00	17.68	Horizontal
6	799.98	33.00	-5.11	27.89	PK	46.00	18.11	Horizontal

Final Data List

NO.	Freq. [MHz]	Factor [dB/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]
1	30.971	-18.67	15.28	40.00	24.72
2	54.2743	-16.60	16.08	40.00	23.92
3	406.7367	-11.45	23.34	46.00	22.66
4	599.96	-6.10	24.69	46.00	21.31
5	712.5926	-5.77	27.64	46.00	18.36
6	799.98	-5.11	27.21	46.00	18.79

8.5 POWER LINE CONDUCTED EMISSIONS

8.5.1 Applicable Standard

According to FCC Part 15.207(a)

8.5.2 Conformance Limit

Frequency(MHz)	Conducted Emission Limit	
	Quasi-peak	Average
0.15-0.5	66-56	56-46
0.5-5.0	56	46
5.0-30.0	60	50

Note: 1. The lower limit shall apply at the transition frequencies

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

8.5.3 Test Configuration

Test according to clause 6.3 conducted emission test setup

8.5.4 Test Procedure


The EUT was placed on a table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Repeat above procedures until all frequency measured were complete.

8.5.5 Test Results

PASS



Site Conduction 2#

Phase: **L1**

Temperature: 25.3

Limit: (CE)FCC PART 15 class B_QP


Power: AC 120V/60Hz

Humidity: 50 %

Mode: Wifi 5G

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1	*	0.1550	39.37	10.69	50.06	65.73	-15.67	QP	
2		0.1550	22.39	10.69	33.08	55.73	-22.65	AVG	
3		0.1750	38.02	10.68	48.70	64.72	-16.02	QP	
4		0.1750	20.94	10.68	31.62	54.72	-23.10	AVG	
5		0.3350	26.71	10.70	37.41	59.33	-21.92	QP	
6		0.3350	11.62	10.70	22.32	49.33	-27.01	AVG	
7		0.5450	23.21	10.74	33.95	56.00	-22.05	QP	
8		0.5450	16.11	10.74	26.85	46.00	-19.15	AVG	
9		11.8550	20.03	10.67	30.70	60.00	-29.30	QP	
10		11.8550	8.18	10.67	18.85	50.00	-31.15	AVG	
11		20.6050	20.34	11.11	31.45	60.00	-28.55	QP	
12		20.6050	5.33	11.11	16.44	50.00	-33.56	AVG	



Site Conduction 2#

Phase: **N**

Temperature: 25.3

Limit: (CE)FCC PART 15 class B_QP

Power: AC 120V/60Hz

Humidity: 50 %

Mode: Wifi 5G

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1	*	0.1500	41.46	10.69	52.15	66.00	-13.85	QP	
2		0.1500	22.58	10.69	33.27	56.00	-22.73	AVG	
3		0.2000	36.01	10.66	46.67	63.61	-16.94	QP	
4		0.2000	19.70	10.66	30.36	53.61	-23.25	AVG	
5		0.2850	32.10	10.69	42.79	60.67	-17.88	QP	
6		0.2850	18.12	10.69	28.81	50.67	-21.86	AVG	
7		0.5450	28.88	10.74	39.62	56.00	-16.38	QP	
8		0.5450	15.73	10.74	26.47	46.00	-19.53	AVG	
9		2.6250	16.08	10.68	26.76	56.00	-29.24	QP	
10		2.6250	1.05	10.68	11.73	46.00	-34.27	AVG	
11		15.3550	21.04	10.77	31.81	60.00	-28.19	QP	
12		15.3550	5.90	10.77	16.67	50.00	-33.33	AVG	

8.6 ANTENNA APPLICATION

8.6.1 Antenna Requirement

Standard	Requirement
FCC CRF Part 15.203	An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, §15.213, §15.217, §15.219, or §15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.407 (a), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

8.6.2 Result

PASS.

The EUT has antennas: an Internal Antenna for WIFI 5G, the antenna gain is 4.90 dBi

Note: ☒ Antennas use a permanently attached antenna which is not replaceable.
☐ Not using a standard antenna jack or electrical connector for antenna replacement
☐ The antenna has to be professionally installed (please provide method of installation)

Which in accordance to section 15.203, please refer to the internal photos.

Detail of factor for radiated emission

Frequency(MHz)	Ant_F(dB)	Cab_L(dB)	Preamp(dB)	Correct Factor(dB)
0.009	20.6	0.03	\	20.63
0.15	20.7	0.1	\	20.8
1	20.9	0.15	\	21.05
10	20.1	0.28	\	20.38
30	18.8	0.45	\	19.25
30	11.7	0.62	27.9	-15.58
100	12.5	1.02	27.8	-14.28
300	12.9	1.91	27.5	-12.69
600	19.2	2.92	27	-4.88
800	21.1	3.54	26.6	-1.96
1000	22.3	4.17	26.2	0.27
1000	25.6	1.76	41.4	-14.04
3000	28.9	3.27	43.2	-11.03
5000	31.1	4.2	44.6	-9.3
8000	36.2	5.95	44.7	-2.55
10000	38.4	6.3	43.9	0.8
12000	38.5	7.14	42.3	3.34
15000	40.2	8.15	41.4	6.95
18000	45.4	9.02	41.3	13.12
18000	37.9	1.81	47.9	-8.19
21000	37.9	1.95	48.7	-8.85
25000	39.3	2.01	42.8	-1.49
28000	39.6	2.16	46.0	-4.24
31000	41.2	2.24	44.5	-1.06
34000	41.5	2.29	46.6	-2.81
37000	43.8	2.30	46.4	-0.3
40000	43.2	2.50	42.2	3.5

----- END OF REPORT -----