

Choose certainty.
Add value.

Report On

RF Exposure Assessment of the EDTracker Ltd EDTPWL001 EDTracker Pro Wireless

FCC ID: 2AKV8-000001

Document 75938172 Report 07 Issue 1

April 2017



Product Service

TÜV SÜD Product Service, Octagon House, Concorde Way, Segensworth North, Fareham, Hampshire, United Kingdom, PO15 5RL Tel: +44 (0) 1489 558100. Website: www.tuv-sud.co.uk

REPORT ON	RF Exposure Assessment of the

EDTracker Ltd

EDTPWL001 EDTracker Pro Wireless

Document 75938172 Report 07 Issue 1

April 2017

PREPARED FOR EDTracker Ltd

16 Woodhurst Lane

Wokingham Berkshire RG41 1JQ

UK

PREPARED BY

David Guyett-Smith

Chief Engineer - Technical Solutions

APPROVED BY

Matthew Russell

Authorised Signatory

DATED 11 April 2017



CONTENTS

Section	1	Page No
1	REPORT SUMMARY	3
1.1	Introduction	4
1.2	Regional Requirements	5
1.3	Regional Requirements Product Information	5
1.3.1	Technical Description	5
1.3.2	Supported Features	5
1.3.3	Antennas	5
1.4	Brief Summary of Results	5
2	TEST DETAILS	7
2.1	Rationale for Assessment of the RF Exposure	8
2.2	Test Result Details	
3	DISCLAIMERS AND COPYRIGHT	10
3.1	Disclaimers and Copyright	11



SECTION 1

REPORT SUMMARY

RF Exposure Assessment of the EDTracker Ltd EDTPWL001 EDTracker Pro Wireless



1.1 INTRODUCTION

The information contained in this report is intended to show verification of the RF Exposure Assessment of the EDTracker Ltd EDTPWL001 EDTracker Pro Wireless to the requirements of the applied test specifications.

Objective To perform RF Exposure Assessment to determine the

Equipment Under Test's (EUT's) compliance of the applied

rules.

Applicant EDTracker Ltd

Manufacturer EDTracker Ltd

Manufacturing Description EDTracker Pro Wireless

Model Number(s) EDTPWL001

Test Specification/Issue/Date EN 62311:2008

CFR 47 Pt1.1310



1.2 REGIONAL REQUIREMENTS

The table below shows the regional requirements that are referenced in this test report. A full list of the requirements is shown in Annex A.

Report Reference	Regional Requirement
EU	EN 62311:2008
FCC	CFR 47 Pt1.1310

1.3 PRODUCT INFORMATION

1.3.1 Technical Description

The Equipment under test was an EDTracker Ltd EDTPWL001 EDTracker Pro Wireless. A full technical description can be found in the manufacturer's documentation.

All reported calculations were carried out on the relevant information supplied for the EDTPWL001 EDTracker Pro Wireless to demonstrate compliance with the applied test specification(s). The sample assessed was found to comply with the requirements of the applied rules.

1.3.2 Supported Features

The following radio access technologies and frequency bands are supported by the equipment under test.

Radio Access Technology	2.4 GHz SRD
Frequency Band	2403-2481

1.3.3 Antennas

The following antennas are supported by the equipment under test.

No.	Model	Gain (dBi)
1	2.4 GHz	-0.5

1.4 BRIEF SUMMARY OF RESULTS

The wireless device described within this report has been shown to be capable of compliance with the basic restrictions related to human exposure to electromagnetic fields for both General Public and Occupational. The calculations shown in this report were made in accordance with the procedures specified in the applied test specification(s).

Required Compliance Boundary (m)	
Occupational	General Population
0.2	0.2

Table 1 - Compliance Boundary Results



Product Service

Regional	Calculated I	Calculated RF exposure level at compliance boundary of 0.2 m								
Requirement	S Field (W/r	S Field (W/m²)		E Field (V/m)		H Field (A/m)				
	Result	Limit	Result	Limit	Result	Limit				
EU	0.0887	50.0000	5.7816	137.0000	0.0153	0.3600				
FCC*	0.0089	5.0000	N/A	N/A	N/A	N/A				

^{*} Requirement and Result in mW/cm²

Table 2 – Occupational Results

The calculations show that the EUT complies with the occupational exposure levels described in the EN 62311:2008 and CFR 47 Pt1.1310 at the point of investigation, 0.2 m.

Regional	Calculated RF e	Calculated RF exposure level at compliance boundary of 0.2 m							
Requirement	S Field (W/m²)		E Field (V/m)		H Field (A/m)				
	Result	Limit	Result	Limit	Result	Limit			
EU	0.0887	10.0000	5.7816	61.0000	0.0153	0.1600			
FCC*	0.0089	1.0000	N/A	N/A	N/A	N/A			

^{*} Requirement and Result in mW/cm²

Table 3 – General Population Results

The calculations show that the EUT complies with the occupational exposure levels described in the EN 62311:2008 and CFR 47 Pt1.1310 at the point of investigation, 0.2 m.



SECTION 2

TEST DETAILS



2.1 RATIONALE FOR ASSESSMENT OF THE RF EXPOSURE

The aim of the assessment report is to evaluate the compliance boundary for a set of given input power(s) according to the basic restrictions (directly or indirectly via compliance with reference levels) related to human exposure to radio frequency electromagnetic fields. The chosen assessment method to establish the compliance boundary in the far-field region is the reference method as defined in the relevant specifications.

The RF exposure assessment is based upon the following criteria:

The EDTPWL001 EDTracker Pro Wireless operates with the following transmitters active on the antenna ports shown in Section 1.3.3. For each transmitter, the Radio Access Technology (RAT), EIRP inclusive of antenna gain and duty cycle, gain of the antenna and lowest frequency of operation are shown as they contribute to the calculation of S Field, E field and H field values according to the following formulas.

The power flux (S Field):

$$S = \frac{PG_{(\theta,\phi)}}{4\pi r^2}$$

The electric field strength (E Field):

$$E = \frac{\sqrt{30PG}(\theta,\phi)}{r}$$

The magnetic field strength (H Field):

$$H=\frac{E}{\eta_{o}}$$

Where:

P = Average Power (W)

G = Antenna Gain (dBi)

r = Distance (cm) or (m)

 $\eta_{o} = 377$



2.2 TEST RESULT DETAILS

The frequencies shown in the tables below have been chosen based on the lowest possible frequency that the EUT can transmit.

Antenna Port	Tx No.	Ant No.	RAT	EIRP (W)	Duty Cycle (%)	Gain (dBi)	Frequency (MHz)	RF Exposure Level at compliance boundary of 0.2 m		pliance
								S Field (W/m²)	E Field (V/m)	H Field (A/m)
1	1	1	2.4 GHz SRD	0.045	20	-0.5	2403.2	0.0887	5.7816	0.0153

Table 4 – Occupational Transmitter Summary

Antenna	Tx	Ant	RAT	EIRP	Duty Cycle	Gain	Frequency	RF Exposure	e Level at com	pliance
Port	No.	No.		(W)	(%)	(dBi)	(MHz)	boundary of	0.2 m	
								S Field	E Field	H Field
								(W/m ²)	(V/m)	(A/m)
1	1	1	2.4 GHz SRD	0.045	20	-0.5	2403.2	0.0887	5.7816	0.0153

Table 5 – General Population Transmitter Summary



SECTION 3

DISCLAIMERS AND COPYRIGHT



3.1 DISCLAIMERS AND COPYRIGHT

This report relates only to the actual item/items tested.

This report must not be reproduced, except in its entirety, without the written permission of TÜV SÜD Product Service

© 2017 TÜV SÜD Product Service



ANNEX A

REGIONAL REQUIREMENTS



Frequency Range (MHz)	Power Density (W/m²)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)
0.065 - 1	-	610	1.6/f
1 - 10	-	610/f	1.6/f
10 - 400	10	61	0.162
400 - 2000	f/40	3*f^0.5	0.008*f^0.5
2000 - 300000	50	137	0.36

Table A.1 – EN 62311:2008 Occupational Limits

Frequency Range (MHz)	Power Density (W/m²)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)
0.003 - 0.15	-	87	5
0.15 - 1	-	87	0.73/f
1 - 10	-	87/f^0.5	0.73/f
10 - 400	2	28	0.073
400 - 2000	f/200	1.375*f^0.5	0.0037*f^0.5
2000 - 300000	10	61	0.16

Table A.2 – EN 62311:2008 General Population Limits

Frequency Range (MHz)	S Field (mW/cm²)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)
0 - 0.3	-	-	-
0.3 - 3	100	614	1.63
3 - 30	900/f^2	1842/f	4.89/f
30 - 300	1	61.4	0.163
300 - 1500	f/300	-	-
1500 - 100000	5	-	-

Table A.3 – CFR 47 Pt1.1310 Occupational Limits

Frequency Range (MHz)	S Field (mW/cm²)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)
0 - 0.3	-	-	-
0.3 - 3	100	614	1.63
3 - 30	180/f^2	824/f	2.19/f
30 - 300	0.2	27.5	0.073
300 - 1500	f/1500	-	-
1500 - 100000	1	-	-

Table A.4 – CFR 47 Pt1.1310 General Population Limits